



## INDEX

---

### Numerics

802.1AE Tagging [7-2](#)

---

### A

abbreviating commands [2-3](#)

AC (command switch) [8-9](#)

access-class command [33-17](#)

access control entries

See ACEs

access control entry (ACE) [38-3](#)

access-denied response, VMPS [14-24](#)

accessing

clusters, switch [8-12](#)

command switches [8-10](#)

member switches [8-12](#)

switch clusters [8-12](#)

accessing stack members [9-21](#)

access lists

See ACLs

access ports

in switch clusters [8-8](#)

accounting

with 802.1x [12-52](#)

with IEEE 802.1x [12-16](#)

with RADIUS [11-35](#)

with TACACS+ [11-12, 11-17](#)

ACEs

and QoS [34-7](#)

defined [33-1](#)

Ethernet [33-2](#)

IP [33-2](#)

ACLs

ACEs [33-1](#)

any keyword [33-9](#)

applying

time ranges to [33-14](#)

to an interface [33-17, 38-7](#)

to IPv6 interfaces [38-7](#)

to QoS [34-7](#)

classifying traffic for QoS [34-43](#)

comments in [33-16](#)

compiling [33-20](#)

defined [33-1, 33-5](#)

examples of [33-20, 34-43](#)

extended IP, configuring for QoS classification [34-45](#)

extended IPv4

creating [33-8](#)

matching criteria [33-6](#)

hardware and software handling [33-18](#)

host keyword [33-10](#)

IP

creating [33-5](#)

fragments and QoS guidelines [34-34](#)

implicit deny [33-7, 33-12, 33-13](#)

implicit masks [33-7](#)

matching criteria [33-6](#)

undefined [33-18](#)

IPv4

applying to interfaces [33-17](#)

creating [33-5](#)

matching criteria [33-6](#)

named [33-12](#)

numbers [33-6](#)

terminal lines, setting on [33-17](#)

- unsupported features [33-5](#)
- IPv6
  - applying to interfaces [38-7](#)
  - configuring [38-3, 38-4](#)
  - displaying [38-8](#)
  - interactions with other features [38-4](#)
  - limitations [38-2, 38-3](#)
  - matching criteria [38-3](#)
  - named [38-2](#)
  - precedence of [38-2](#)
  - supported [38-2](#)
  - unsupported features [38-3](#)
- MAC extended [33-21, 34-46](#)
- matching [33-5, 33-18, 38-3](#)
- monitoring [33-24, 38-8](#)
- named, IPv4 [33-12](#)
- named, IPv6 [38-2](#)
- names [38-4](#)
- number per QoS class map [34-35](#)
- port [33-2, 38-1](#)
- QoS [34-7, 34-43](#)
- resequencing entries [33-12](#)
- router [33-2, 38-1](#)
- standard IP, configuring for QoS classification [34-44](#)
- standard IPv4
  - creating [33-7](#)
  - matching criteria [33-6](#)
- support in hardware [33-18](#)
- time ranges [33-14](#)
- types supported [33-2](#)
- unsupported features, IPv4 [33-5](#)
- unsupported features, IPv6 [38-3](#)
- active link [20-4, 20-5](#)
- active links [20-1](#)
- active traffic monitoring, IP SLAs [32-1](#)
- address aliasing [23-2](#)
- addresses
  - displaying the MAC address table [5-23](#)
  - dynamic
    - accelerated aging [17-8](#)
    - changing the aging time [5-15](#)
    - default aging [17-8](#)
    - defined [5-13](#)
    - learning [5-14](#)
    - removing [5-16](#)
  - IPv6 [36-2](#)
  - MAC, discovering [5-24](#)
  - static
    - adding and removing [5-20](#)
    - defined [5-13](#)
- address resolution [5-24](#)
- Address Resolution Protocol
  - See ARP
- advertisements
  - CDP [26-1](#)
  - LLDP [27-1, 27-2](#)
  - VTP [14-15, 15-3](#)
- aggregatable global unicast addresses [36-3](#)
- aggregated ports
  - See EtherChannel
- aggregate policers [34-54](#)
- aggregate policing [1-10](#)
- aging, accelerating [17-8](#)
- aging time
  - accelerated
    - for MSTP [18-23](#)
    - for STP [17-8, 17-21](#)
  - MAC address table [5-15](#)
  - maximum
    - for MSTP [18-24](#)
    - for STP [17-21, 17-22](#)
- alarms, RMON [29-4](#)
- allowed-VLAN list [14-17](#)
- ARP
  - defined [1-5, 5-24](#)
  - table
    - address resolution [5-24](#)
    - managing [5-24](#)

- attributes, RADIUS
    - vendor-proprietary [11-38](#)
    - vendor-specific [11-36](#)
  - attribute-value pairs [12-13, 12-16, 12-21, 12-22](#)
  - authentication
    - local mode with AAA [11-40](#)
    - open1x [12-30](#)
    - RADIUS
      - key [11-28](#)
      - login [11-30](#)
    - TACACS+
      - defined [11-11](#)
      - key [11-13](#)
      - login [11-14](#)
    - See also port-based authentication
  - authentication compatibility with Catalyst 6000 switches [12-8](#)
  - authentication failed VLAN
    - See restricted VLAN
  - authentication manager
    - CLI commands [12-9](#)
    - compatibility with older 802.1x CLI commands [12-9 to ??](#)
    - overview [12-7](#)
  - authoritative time source, described [5-2](#)
  - authorization
    - with RADIUS [11-34](#)
    - with TACACS+ [11-12, 11-16](#)
  - authorized ports with IEEE 802.1x [12-10](#)
  - autoconfiguration [3-3](#)
  - auto enablement [12-32](#)
  - automatic advise (auto-advise) in switch stacks [9-10](#)
  - automatic copy (auto-copy) in switch stacks [9-10](#)
  - automatic discovery
    - considerations
      - beyond a noncandidate device [8-7](#)
      - brand new switches [8-8](#)
      - connectivity [8-4](#)
      - different VLANs [8-6](#)
      - management VLANs [8-7](#)
      - non-CDP-capable devices [8-5](#)
      - noncluster-capable devices [8-5](#)
      - in switch clusters [8-4](#)
      - See also CDP
    - automatic extraction (auto-extract) in switch stacks [9-10](#)
    - automatic QoS
      - See QoS
    - automatic recovery, clusters [8-9](#)
      - See also HSRP
    - automatic upgrades (auto-upgrade) in switch stacks [9-10](#)
    - auto-MDIX
      - configuring [13-15](#)
      - described [13-15](#)
    - autonegotiation
      - duplex mode [1-3](#)
      - interface configuration guidelines [13-12](#)
      - mismatches [40-11](#)
    - Auto-QoS video devices [1-11](#)
    - autosensing, port speed [1-3](#)
    - auxiliary VLAN
      - See voice VLAN
    - availability, features [1-6](#)
- 
- ## B
- BackboneFast
    - described [19-5](#)
    - disabling [19-14](#)
    - enabling [19-13](#)
  - backup interfaces
    - See Flex Links
  - backup links [20-1](#)
  - banners
    - configuring
      - login [5-13](#)
      - message-of-the-day login [5-11](#)
    - default configuration [5-11](#)
    - when displayed [5-11](#)

- Berkeley r-tools replacement [11-52](#)
- binding database
  - DHCP snooping
    - See DHCP snooping binding database
- bindings
  - DHCP snooping database [21-6](#)
  - IP source guard [21-12](#)
- binding table, DHCP snooping
  - See DHCP snooping binding database
- blocking packets [24-7](#)
- booting
  - boot loader, function of [3-1](#)
  - boot process [3-1](#)
  - manually [3-19](#)
  - specific image [3-20](#)
- boot loader
  - accessing [3-21](#)
  - described [3-1](#)
  - environment variables [3-21](#)
  - prompt [3-21](#)
  - trap-door mechanism [3-2](#)
- Boot Loader Upgrade and Image Verification for the FIPS Mode of Operation [3-24](#)
- BPDUs
  - error-disabled state [19-2](#)
  - filtering [19-3](#)
  - RSTP format [18-12](#)
- BPDUs filtering
  - described [19-3](#)
  - disabling [19-12](#)
  - enabling [19-12](#)
  - support for [1-7](#)
- BPDUs guard
  - described [19-2](#)
  - disabling [19-12](#)
  - enabling [19-11](#)
  - support for [1-7](#)
- bridge protocol data unit
  - See BPDUs

- broadcast storm-control command [24-4](#)
- broadcast storms [24-1](#)

## C

- cables, monitoring for unidirectional links [25-1](#)
- candidate switch
  - automatic discovery [8-4](#)
  - defined [8-3](#)
  - requirements [8-3](#)
  - See also command switch, cluster standby group, and member switch
- Catalyst 6000 switches
  - authentication compatibility [12-8](#)
- CA trustpoint
  - configuring [11-49](#)
  - defined [11-47](#)
- CDP
  - and trusted boundary [34-39](#)
  - automatic discovery in switch clusters [8-4](#)
  - configuring [26-2](#)
  - default configuration [26-2](#)
  - defined with LLDP [27-1](#)
  - described [26-1](#)
  - disabling for routing device [26-4](#)
  - enabling and disabling
    - on an interface [26-4](#)
    - on a switch [26-4](#)
  - monitoring [26-5](#)
  - overview [26-1](#)
  - power negotiation extensions [13-4](#)
  - support for [1-5](#)
  - transmission timer and holdtime, setting [26-3](#)
  - updates [26-3](#)
- CGMP
  - as IGMP snooping learning method [23-8](#)
  - joining multicast group [23-3](#)
- CipherSuites [11-48](#)
- Cisco 7960 IP Phone [16-1](#)

Cisco Discovery Protocol

See CDP

Cisco intelligent power management [13-4](#)

Cisco IOS File System

See IFS

Cisco IOS IP SLAs [32-1](#)

Cisco Secure ACS

attribute-value pairs for downloadable ACLs [12-22](#)

attribute-value pairs for redirect URL [12-21](#)

Cisco Secure ACS configuration guide [12-63](#)

CiscoWorks 2000 [1-4, 31-4](#)

CISP [12-32](#)

CIST regional root

See MSTP

CIST root

See MSTP

civic location [27-3](#)

class maps for QoS

configuring [34-47](#)

described [34-7](#)

displaying [34-74](#)

class of service

See CoS

clearing interfaces [13-21](#)

CLI

abbreviating commands [2-3](#)

command modes [2-1](#)

configuration logging [2-5](#)

described [1-4](#)

editing features

enabling and disabling [2-6](#)

keystroke editing [2-7](#)

wrapped lines [2-8](#)

error messages [2-4](#)

filtering command output [2-9](#)

getting help [2-3](#)

history

changing the buffer size [2-5](#)

described [2-5](#)

disabling [2-6](#)

recalling commands [2-6](#)

managing clusters [8-13](#)

no and default forms of commands [2-4](#)

Client Information Signalling Protocol

See CISP

client mode, VTP [15-3](#)

clock

See system clock

clusters, switch

accessing [8-12](#)

automatic discovery [8-4](#)

automatic recovery [8-9](#)

benefits [1-1](#)

compatibility [8-4](#)

described [8-1](#)

LRE profile considerations [8-13](#)

managing

through CLI [8-13](#)

through SNMP [8-14](#)

planning [8-4](#)

planning considerations

automatic discovery [8-4](#)

automatic recovery [8-9](#)

CLI [8-13](#)

host names [8-12](#)

IP addresses [8-12](#)

LRE profiles [8-13](#)

passwords [8-12](#)

RADIUS [8-13](#)

SNMP [8-13, 8-14](#)

TACACS+ [8-13](#)

See also candidate switch, command switch, cluster standby group, member switch, and standby command switch

cluster standby group

automatic recovery [8-11](#)

considerations [8-10](#)

defined [8-2](#)

- requirements [8-3](#)
- virtual IP address [8-10](#)
- See also HSRP
- CNS [1-5](#)
  - Configuration Engine
    - configID, deviceID, hostname [4-3](#)
    - configuration service [4-2](#)
    - described [4-1](#)
    - event service [4-3](#)
  - embedded agents
    - described [4-5](#)
    - enabling automated configuration [4-6](#)
    - enabling configuration agent [4-9](#)
    - enabling event agent [4-8](#)
  - management functions [1-4](#)
- CoA Request Commands [11-23](#)
- Coarse Wave Division Multiplexer
  - See CWDM SFPs
- command-line interface
  - See CLI
- command modes [2-1](#)
- commands
  - abbreviating [2-3](#)
  - no and default [2-4](#)
- commands, setting privilege levels [11-8](#)
- command switch
  - accessing [8-10](#)
  - active (AC) [8-9](#)
  - configuration conflicts [40-11](#)
  - defined [8-2](#)
  - passive (PC) [8-9](#)
  - password privilege levels [8-14](#)
  - priority [8-9](#)
  - recovery
    - from command-switch failure [8-9, 40-8](#)
    - from lost member connectivity [40-11](#)
  - redundant [8-9](#)
  - replacing
    - with another switch [40-10](#)
  - with cluster member [40-8](#)
  - requirements [8-3](#)
  - standby (SC) [8-9](#)
  - See also candidate switch, cluster standby group, member switch, and standby command switch
- community strings
  - configuring [8-13, 31-9](#)
  - for cluster switches [31-4](#)
  - in clusters [8-13](#)
  - overview [31-4](#)
  - SNMP [8-13](#)
- compatibility, feature [24-12](#)
- compatibility, software
  - See stacks, switch
- config.text [3-18](#)
- configurable leave timer, IGMP [23-5](#)
- configuration, initial
  - defaults [1-12](#)
  - Express Setup [1-1](#)
- configuration changes, logging [30-10](#)
- configuration conflicts, recovering from lost member connectivity [40-11](#)
- configuration examples, network [1-14](#)
- configuration files
  - archiving [42-20](#)
  - clearing the startup configuration [42-19](#)
  - creating using a text editor [42-9](#)
  - default name [3-18](#)
  - deleting a stored configuration [42-19](#)
  - described [42-8](#)
  - downloading
    - automatically [3-18](#)
    - preparing [42-10, 42-13, 42-16](#)
    - reasons for [42-8](#)
    - using FTP [42-13](#)
    - using RCP [42-17](#)
    - using TFTP [42-11](#)
  - guidelines for creating and using [42-8](#)
  - guidelines for replacing and rolling back [42-21](#)

- invalid combinations when copying [42-5](#)
- limiting TFTP server access [31-18](#)
- obtaining with DHCP [3-8](#)
- password recovery disable considerations [11-5](#)
- replacing a running configuration [42-19, 42-20](#)
- rolling back a running configuration [42-19, 42-21](#)
- specifying the filename [3-18](#)
- system contact and location information [31-18](#)
- types and location [42-9](#)
- uploading
  - preparing [42-10, 42-13, 42-16](#)
  - reasons for [42-8](#)
  - using FTP [42-15](#)
  - using RCP [42-18](#)
  - using TFTP [42-12](#)
- configuration logger [30-10](#)
- configuration logging [2-5](#)
- configuration replacement [42-19](#)
- configuration rollback [42-19, 42-20](#)
- configuration settings, saving [3-15](#)
- configure terminal command [13-7](#)
- configuring 802.1x user distribution [12-58](#)
- configuring port-based authentication violation modes [12-41](#)
- configuring small-frame arrival rate [24-5](#)
- conflicts, configuration [40-11](#)
- connections, secure remote [11-42](#)
- connectivity problems [40-13, 40-14, 40-16](#)
- consistency checks in VTP Version 2 [15-4](#)
- console port, connecting to [2-9](#)
- control protocol, IP SLAs [32-3](#)
- corrupted software, recovery steps with Xmodem [40-2](#)
- CoS
  - in Layer 2 frames [34-2](#)
  - override priority [16-6](#)
  - trust priority [16-6](#)
- CoS input queue threshold map for QoS [34-13](#)
- CoS output queue threshold map for QoS [34-15](#)
- CoS-to-DSCP map for QoS [34-56](#)

- counters, clearing interface [13-21](#)
- CPU utilization, troubleshooting [40-24](#)
- crashinfo file [40-22](#)
- critical authentication, IEEE 802.1x [12-55](#)
- critical VLAN [12-24](#)
- critical voice VLAN
  - configuring [12-55](#)
- cryptographic software image
  - SSH [11-41](#)
  - SSL [11-46](#)
  - switch stack considerations [9-14](#)
- customjzeable web pages, web-based authentication [6-6](#)
- CWDM SFPs [1-16](#)

---

## D

- DACL
  - See downloadable ACL
- daylight saving time [5-7](#)
- debugging
  - enabling all system diagnostics [40-20](#)
  - enabling for a specific feature [40-19](#)
  - redirecting error message output [40-20](#)
  - using commands [40-18](#)
- default commands [2-4](#)
- default configuration
  - 802.1x [12-35](#)
  - auto-QoS [34-17](#)
  - banners [5-11](#)
  - CDP [26-2](#)
  - DHCP [21-7](#)
  - DHCP option 82 [21-8](#)
  - DHCP snooping [21-8](#)
  - DHCP snooping binding database [21-8](#)
  - DNS [5-10](#)
  - dynamic ARP inspection [22-5](#)
  - EtherChannel [39-9](#)
  - Ethernet interfaces [13-11](#)
  - Flex Links [20-8](#)

- IGMP filtering [23-24](#)
- IGMP snooping [23-6, 37-6](#)
- IGMP throttling [23-24](#)
- initial switch information [3-3](#)
- IP SLAs [32-5](#)
- IP source guard [21-14](#)
- IPv6 [36-7](#)
- Layer 2 interfaces [13-11](#)
- LLDP [27-4](#)
- MAC address table [5-15](#)
- MAC address-table move update [20-8](#)
- MSTP [18-14](#)
- MVR [23-19](#)
- optional spanning-tree configuration [19-9](#)
- password and privilege level [11-2](#)
- RADIUS [11-27](#)
- RMON [29-3](#)
- RSPAN [28-9](#)
- SNMP [31-8](#)
- SPAN [28-9](#)
- SSL [11-48](#)
- standard QoS [34-32](#)
- STP [17-11](#)
- switch stacks [9-16](#)
- system message logging [30-3](#)
- system name and prompt [5-9](#)
- TACACS+ [11-13](#)
- UDLD [25-4](#)
- VLAN, Layer 2 Ethernet interfaces [14-15](#)
- VLANs [14-8](#)
- VMPS [14-25](#)
- voice VLAN [16-3](#)
- VTP [15-7](#)
- default gateway [3-14](#)
- default web-based authentication configuration
  - 802.1X [6-9](#)
- deleting VLANs [14-9](#)
- denial-of-service attack [24-1](#)
- description command [13-18](#)
- designing your network, examples [1-14](#)
- destination addresses
  - in IPv4 ACLs [33-9](#)
  - in IPv6 ACLs [38-5](#)
- destination-IP address-based forwarding, EtherChannel [39-7](#)
- destination-MAC address forwarding, EtherChannel [39-7](#)
- detecting indirect link failures, STP [19-5](#)
- device [42-24](#)
- device discovery protocol [26-1, 27-1](#)
- device manager
  - benefits [1-1](#)
  - described [1-2, 1-4](#)
  - in-band management [1-5](#)
  - upgrading a switch [42-24](#)
- DHCP
  - enabling
    - relay agent [21-9](#)
  - DHCP-based autoconfiguration
    - client request message exchange [3-4](#)
    - configuring
      - client side [3-3](#)
      - DNS [3-7](#)
      - relay device [3-7](#)
      - server side [3-6](#)
      - TFTP server [3-7](#)
    - example [3-9](#)
    - lease options
      - for IP address information [3-6](#)
      - for receiving the configuration file [3-6](#)
    - overview [3-3](#)
    - relationship to BOOTP [3-3](#)
    - relay support [1-5](#)
    - support for [1-5](#)
  - DHCP-based autoconfiguration and image update
    - configuring [3-11 to 3-14](#)
    - understanding [3-5](#)
  - DHCP binding database
    - See DHCP snooping binding database



## DHCP binding table

See DHCP snooping binding database

## DHCP option 82

circuit ID suboption [21-5](#)

configuration guidelines [21-8](#)

default configuration [21-7](#)

displaying [21-12](#)

overview [21-3](#)

packet format, suboption

circuit ID [21-5](#)

remote ID [21-5](#)

remote ID suboption [21-5](#)

## DHCP server port-based address allocation

configuration guidelines [21-21](#)

default configuration [21-21](#)

described [21-21](#)

displaying [21-24](#)

enabling [21-21](#)

reserved addresses [21-22](#)

## DHCP server port-based address assignment

support for [1-5](#)

## DHCP snooping

accepting untrusted packets form edge switch [21-3](#), [21-10](#)

binding database

See DHCP snooping binding database

configuration guidelines [21-8](#)

default configuration [21-7](#)

displaying binding tables [21-12](#)

message exchange process [21-4](#)

option 82 data insertion [21-3](#)

trusted interface [21-2](#)

untrusted interface [21-2](#)

untrusted messages [21-2](#)

## DHCP snooping binding database

adding bindings [21-11](#)

binding file

format [21-6](#)

location [21-6](#)

bindings [21-6](#)

clearing agent statistics [21-12](#)

configuration guidelines [21-8](#)

configuring [21-11](#)

default configuration [21-7](#), [21-8](#)

deleting

binding file [21-12](#)

bindings [21-12](#)

database agent [21-12](#)

described [21-6](#)

displaying [21-12](#)

enabling [21-11](#)

entry [21-6](#)

renewing database [21-12](#)

resetting

delay value [21-12](#)

timeout value [21-12](#)

## DHCP snooping binding table

See DHCP snooping binding database

Differentiated Services architecture, QoS [34-1](#)Differentiated Services Code Point [34-2](#)directed unicast requests [1-5](#)

## directories

changing [42-3](#)

creating and removing [42-4](#)

displaying the working [42-3](#)

## discovery, clusters

See automatic discovery

## DNS

and DHCP-based autoconfiguration [3-7](#)

default configuration [5-10](#)

displaying the configuration [5-11](#)

in IPv6 [36-3](#)

overview [5-9](#)

setting up [5-10](#)

support for [1-5](#)

## domain names

DNS [5-9](#)

VTP [15-8](#)

## Domain Name System

See DNS

downloadable ACL [12-20, 12-22, 12-63](#)

### downloading

#### configuration files

preparing [42-10, 42-13, 42-16](#)

reasons for [42-8](#)

using FTP [42-13](#)

using RCP [42-17](#)

using TFTP [42-11](#)

#### image files

deleting old image [42-28](#)

preparing [42-26, 42-29, 42-33](#)

reasons for [42-24](#)

using CMS [1-2](#)

using FTP [42-30](#)

using HTTP [1-2, 42-24](#)

using RCP [42-34](#)

using TFTP [42-26](#)

using the device manager or Network Assistant [42-24](#)

DSCP [1-10, 34-2](#)

DSCP input queue threshold map for QoS [34-13](#)

DSCP output queue threshold map for QoS [34-15](#)

DSCP-to-CoS map for QoS [34-59](#)

DSCP-to-DSCP-mutation map for QoS [34-60](#)

DSCP transparency [34-40](#)

DTP [1-7, 14-14](#)

dual-action detection [39-4](#)

dual IPv4 and IPv6 templates [36-6](#)

### dual protocol stacks

IPv4 and IPv6 [36-6](#)

SDM templates supporting [36-6](#)

### dynamic access ports

characteristics [14-4](#)

configuring [14-26](#)

defined [13-2](#)

### dynamic addresses

See addresses

## dynamic ARP inspection

ARP cache poisoning [22-1](#)

ARP requests, described [22-1](#)

ARP spoofing attack [22-1](#)

### clearing

log buffer [22-16](#)

statistics [22-16](#)

configuration guidelines [22-5](#)

### configuring

ACLs for non-DHCP environments [22-9](#)

in DHCP environments [22-6](#)

log buffer [22-13](#)

rate limit for incoming ARP packets [22-4, 22-11](#)

default configuration [22-5](#)

denial-of-service attacks, preventing [22-11](#)

described [22-1](#)

DHCP snooping binding database [22-2](#)

### displaying

ARP ACLs [22-16](#)

configuration and operating state [22-16](#)

log buffer [22-16](#)

statistics [22-16](#)

trust state and rate limit [22-16](#)

error-disabled state for exceeding rate limit [22-4](#)

function of [22-2](#)

interface trust states [22-3](#)

### log buffer

clearing [22-16](#)

configuring [22-13](#)

displaying [22-16](#)

logging of dropped packets, described [22-4](#)

man-in-the middle attack, described [22-2](#)

network security issues and interface trust states [22-3](#)

priority of ARP ACLs and DHCP snooping entries [22-4](#)

### rate limiting of ARP packets

configuring [22-11](#)

described [22-4](#)

error-disabled state [22-4](#)

- statistics
  - clearing [22-16](#)
  - displaying [22-16](#)
  - validation checks, performing [22-13](#)
- dynamic auto trunking mode [14-14](#)
- dynamic desirable trunking mode [14-14](#)
- Dynamic Host Configuration Protocol
  - See DHCP-based autoconfiguration
- dynamic port VLAN membership
  - described [14-24](#)
  - reconfirming [14-27](#)
  - troubleshooting [14-29](#)
  - types of connections [14-26](#)
- Dynamic Trunking Protocol
  - See DTP

## E

- EAC [7-2](#)
- editing features
  - enabling and disabling [2-6](#)
  - keystrokes used [2-7](#)
  - wrapped lines [2-8](#)
- elections
  - See stack master
- ELIN location [27-3](#)
- enable password [11-3](#)
- enable secret password [11-3](#)
- encryption, CipherSuite [11-48](#)
- encryption for passwords [11-3](#)
- Endpoint Admission Control (EAC) [7-2](#)
- environment variables, function of [3-22](#)
- error-disabled state, BPDU [19-2](#)
- error messages during command entry [2-4](#)
- EtherChannel
  - automatic creation of [39-3, 39-5](#)
  - channel groups
    - numbering of [39-3](#)
  - configuration guidelines [39-9](#)

- default configuration [39-9](#)
- described [39-2](#)
- displaying status [39-17](#)
- forwarding methods [39-6, 39-12](#)
- IEEE 802.3ad, described [39-5](#)
- interaction
  - with STP [39-9](#)
  - with VLANs [39-10](#)
- LACP
  - described [39-5](#)
  - displaying status [39-17](#)
  - hot-standby ports [39-14](#)
  - interaction with other features [39-6](#)
  - modes [39-5](#)
  - port priority [39-15](#)
  - system priority [39-15](#)
- load balancing [39-6, 39-12](#)
- PAgP
  - aggregate-port learners [39-13](#)
  - compatibility with Catalyst 1900 [39-13](#)
  - described [39-3](#)
  - displaying status [39-17](#)
  - interaction with other features [39-5](#)
  - interaction with virtual switches [39-4](#)
  - learn method and priority configuration [39-13](#)
  - modes [39-4](#)
  - support for [1-3](#)
  - with dual-action detection [39-4](#)
- port-channel interfaces
  - described [39-3](#)
  - numbering of [39-3](#)
- port groups [13-3](#)
- support for [1-3](#)
- EtherChannel guard
  - described [19-7](#)
  - disabling [19-14](#)
  - enabling [19-14](#)
- Ethernet VLANs
  - adding [14-8](#)

- defaults and ranges [14-8](#)
- modifying [14-8](#)
- EUI [36-3](#)
- events, RMON [29-4](#)
- examples
  - network configuration [1-14](#)
- expedite queue for QoS [34-73](#)
- Express Setup [1-1](#)
  - See also getting started guide
- extended crashinfo file [40-22](#)
- extended-range VLANs
  - configuration guidelines [14-11](#)
  - configuring [14-11](#)
  - creating [14-12](#)
  - defined [14-1](#)
- extended system ID
  - MSTP [18-17](#)
  - STP [17-4, 17-14](#)
- extended universal identifier
  - See EUI
- Extensible Authentication Protocol over LAN [12-1](#)

## F

- fa0 interface [1-5](#)
- Fast Convergence [20-3](#)
- features, incompatible [24-12](#)
- fiber-optic, detecting unidirectional links [25-1](#)
- files
  - basic crashinfo
    - description [40-22](#)
    - location [40-22](#)
  - copying [42-4](#)
  - crashinfo, description [40-22](#)
  - deleting [42-5](#)
  - displaying the contents of [42-7](#)
  - extended crashinfo
    - description [40-23](#)
    - location [40-23](#)

- tar
  - creating [42-6](#)
  - displaying the contents of [42-6](#)
  - extracting [42-7](#)
  - image file format [42-25](#)
- file system
  - displaying available file systems [42-2](#)
  - displaying file information [42-3](#)
  - local file system names [42-1](#)
  - network file system names [42-4](#)
  - setting the default [42-3](#)
- filtering
  - IPv6 traffic [38-3, 38-7](#)
  - non-IP traffic [33-21](#)
  - show and more command output [2-9](#)
- filtering show and more command output [2-9](#)
- filters, IP
  - See ACLs, IP
- flash device, number of [42-1](#)
- flexible authentication ordering
  - configuring [12-65](#)
  - overview [12-30](#)
- Flex Link Multicast Fast Convergence [20-3](#)
- Flex Links
  - configuration guidelines [20-8](#)
  - configuring [20-9](#)
  - configuring preferred VLAN [20-11](#)
  - configuring VLAN load balancing [20-10](#)
  - default configuration [20-8](#)
  - description [20-1](#)
  - link load balancing [20-2](#)
  - monitoring [20-14](#)
  - VLANs [20-2](#)
- flooded traffic, blocking [24-8](#)
- flow-based packet classification [1-10](#)
- flowcharts
  - QoS classification [34-6](#)
  - QoS egress queueing and scheduling [34-14](#)
  - QoS ingress queueing and scheduling [34-12](#)

QoS policing and marking [34-10](#)

## flowcontrol

configuring [13-14](#)

described [13-14](#)

## forward-delay time

MSTP [18-23](#)

STP [17-21](#)

## FTP

### configuration files

downloading [42-13](#)

overview [42-12](#)

preparing the server [42-13](#)

uploading [42-15](#)

### image files

deleting old image [42-32](#)

downloading [42-30](#)

preparing the server [42-29](#)

uploading [42-32](#)

## G

general query [20-5](#)

Generating IGMP Reports [20-3](#)

get-bulk-request operation [31-3](#)

get-next-request operation [31-3, 31-4](#)

get-request operation [31-3, 31-4](#)

get-response operation [31-3](#)

global configuration mode [2-2](#)

global leave, IGMP [23-12](#)

guest VLAN and 802.1x [12-22](#)

guide mode [1-2](#)

## GUIs

See device manager and Network Assistant

## H

### hello time

MSTP [18-23](#)

STP [17-20](#)

help, for the command line [2-3](#)

HFTM space [40-23](#)

## history

changing the buffer size [2-5](#)

described [2-5](#)

disabling [2-6](#)

recalling commands [2-6](#)

history table, level and number of syslog messages [30-9](#)

host names, in clusters [8-12](#)

hosts, limit on dynamic ports [14-29](#)

HP OpenView [1-4](#)

HQATM space [40-23](#)

## HSRP

automatic cluster recovery [8-11](#)

cluster standby group considerations [8-10](#)

See also clusters, cluster standby group, and standby command switch

## HTTP over SSL

see HTTPS

## HTTPS [11-46](#)

configuring [11-50](#)

self-signed certificate [11-47](#)

HTTP secure server [11-46](#)

## Hulc Forwarding TCAM Manager

See HFTM space

## Hulc QoS/ACL TCAM Manager

See HQATM space

## ICMP

IPv6 [36-3](#)

time-exceeded messages [40-16](#)

traceroute and [40-16](#)

unreachable messages and IPv6 [38-4](#)

## ICMP ping

executing [40-13](#)

overview [40-13](#)

- ICMPv6 [36-3](#)
- IDS appliances
  - and ingress RSPAN [28-19](#)
  - and ingress SPAN [28-12](#)
- IEEE 802.1D
  - See STP
- IEEE 802.1p [16-1](#)
- IEEE 802.1Q
  - configuration limitations [14-15](#)
  - native VLAN for untagged traffic [14-19](#)
- IEEE 802.1s
  - See MSTP
- IEEE 802.1w
  - See RSTP
- IEEE 802.1x
  - See port-based authentication
- IEEE 802.3ad
  - See EtherChannel
- IEEE 802.3af
  - See PoE
- IEEE 802.3x flow control [13-14](#)
- ifIndex values, SNMP [31-5](#)
- IFS [1-5](#)
- IGMP
  - configurable leave timer
    - described [23-5](#)
    - enabling [23-10](#)
  - flooded multicast traffic
    - controlling the length of time [23-11](#)
    - disabling on an interface [23-12](#)
    - global leave [23-12](#)
    - query solicitation [23-12](#)
    - recovering from flood mode [23-12](#)
  - joining multicast group [23-3](#)
  - join messages [23-3](#)
  - leave processing, enabling [23-10, 37-9](#)
  - leaving multicast group [23-5](#)
  - queries [23-4](#)
  - report suppression
    - described [23-6](#)
    - disabling [23-15, 37-11](#)
    - supported versions [23-2](#)
- IGMP filtering
  - configuring [23-24](#)
  - default configuration [23-24](#)
  - described [23-23](#)
  - monitoring [23-28](#)
  - support for [1-4](#)
- IGMP groups
  - configuring filtering [23-27](#)
  - setting the maximum number [23-26](#)
- IGMP Immediate Leave
  - configuration guidelines [23-10](#)
  - described [23-5](#)
  - enabling [23-10](#)
- IGMP profile
  - applying [23-25](#)
  - configuration mode [23-24](#)
  - configuring [23-25](#)
- IGMP snooping
  - and address aliasing [23-2](#)
  - configuring [23-6](#)
  - default configuration [23-6, 37-6](#)
  - definition [23-1](#)
  - enabling and disabling [23-7, 37-7](#)
  - global configuration [23-7](#)
  - Immediate Leave [23-5](#)
  - method [23-8](#)
  - monitoring [23-16, 37-12](#)
  - querier
    - configuration guidelines [23-13](#)
    - configuring [23-13](#)
    - supported versions [23-2](#)
    - VLAN configuration [23-7](#)
- IGMP throttling
  - configuring [23-27](#)
  - default configuration [23-24](#)
  - described [23-24](#)

- displaying action [23-28](#)
- Immediate Leave, IGMP [23-5](#)
  - enabling [37-9](#)
- inaccessible authentication bypass [12-24](#)
  - support for multiauth ports [12-25](#)
- initial configuration
  - defaults [1-12](#)
  - Express Setup [1-1](#)
- interface
  - range macros [13-9](#)
- interface command [?? to 13-7](#)
- interface configuration mode [2-2](#)
- interfaces
  - auto-MDIX, configuring [13-15](#)
  - configuration guidelines
    - duplex and speed [13-12](#)
  - configuring
    - procedure [13-7](#)
  - counters, clearing [13-21](#)
  - default configuration [13-11](#)
  - described [13-18](#)
  - descriptive name, adding [13-18](#)
  - displaying information about [13-21](#)
  - flow control [13-14](#)
  - management [1-4](#)
  - monitoring [13-20](#)
  - naming [13-18](#)
  - physical, identifying [13-7](#)
  - range of [13-8](#)
  - restarting [13-22](#)
  - shutting down [13-22](#)
  - speed and duplex, configuring [13-13](#)
  - status [13-20](#)
  - supported [13-7](#)
  - types of [13-1](#)
- interfaces range macro command [13-9](#)
- interface types [13-7](#)
- Internet Protocol version 6
  - See IPv6
- inter-VLAN routing [35-1](#)
- Intrusion Detection System
  - See IDS appliances
- inventory management TLV [27-3, 27-7](#)
- IP ACLs
  - for QoS classification [34-7](#)
  - implicit deny [33-7, 33-12](#)
  - implicit masks [33-7](#)
  - named [33-12](#)
  - undefined [33-18](#)
- IP addresses
  - 128-bit [36-2](#)
  - candidate or member [8-3, 8-12](#)
  - classes of [35-4](#)
  - cluster access [8-2](#)
  - command switch [8-3, 8-10, 8-12](#)
  - discovering [5-24](#)
  - for IP routing [35-4](#)
  - IPv6 [36-2](#)
  - redundant clusters [8-10](#)
  - standby command switch [8-10, 8-12](#)
  - See also IP information
- ip igmp profile command [23-24](#)
- IP information
  - assigned
    - manually [3-14](#)
    - through DHCP-based autoconfiguration [3-3](#)
  - default configuration [3-3](#)
- IP phones
  - and QoS [16-1](#)
  - automatic classification and queueing [34-17](#)
  - configuring [16-4](#)
  - ensuring port security with QoS [34-39](#)
  - trusted boundary for QoS [34-39](#)
- IP Port Security for Static Hosts
  - on a Layer 2 access port [21-16](#)
- IP precedence [34-2](#)
- IP-precedence-to-DSCP map for QoS [34-57](#)
- IP routing

- disabling [35-4](#)
  - enabling [35-4](#)
- IP Service Level Agreements
  - See IP SLAs
- IP service levels, analyzing [32-1](#)
- IP SLAs
  - benefits [32-2](#)
  - configuration guidelines [32-5](#)
  - Control Protocol [32-3](#)
  - default configuration [32-5](#)
  - definition [32-1](#)
  - measuring network performance [32-2](#)
  - monitoring [32-6](#)
  - operation [32-2](#)
  - responder
    - described [32-3](#)
    - enabling [32-5](#)
  - response time [32-4](#)
  - SNMP support [32-2](#)
  - supported metrics [32-1](#)
- IP source guard
  - and 802.1x [21-15](#)
  - and DHCP snooping [21-12](#)
  - and port security [21-15](#)
  - and private VLANs [21-15](#)
  - and routed ports [21-15](#)
  - and TCAM entries [21-15](#)
  - and trunk interfaces [21-15](#)
  - and VRF [21-15](#)
  - binding configuration
    - automatic [21-12](#)
    - manual [21-12](#)
  - binding table [21-12](#)
  - configuration guidelines [21-15](#)
  - default configuration [21-14](#)
  - described [21-12](#)
  - disabling [21-16](#)
  - displaying
    - active IP or MAC bindings [21-20](#)
    - bindings [21-20](#)
    - configuration [21-20](#)
    - enabling [21-15, 21-16](#)
    - filtering
      - source IP address [21-13](#)
      - source IP and MAC address [21-13](#)
    - source IP address filtering [21-13](#)
    - source IP and MAC address filtering [21-13](#)
    - static bindings
      - adding [21-15, 21-16](#)
      - deleting [21-16](#)
    - static hosts [21-16](#)
- IP traceroute
  - executing [40-17](#)
  - overview [40-16](#)
- IP unicast routing
  - assigning IP addresses to Layer 3 interfaces [35-4](#)
  - configuring static routes [35-5](#)
  - disabling [35-4](#)
  - enabling [35-4](#)
  - inter-VLAN [35-1](#)
  - IP addressing
    - classes [35-4](#)
    - configuring [35-4](#)
  - steps to configure [35-3](#)
  - subnet mask [35-4](#)
  - with SVIs [35-3](#)
- IPv4 ACLs
  - applying to interfaces [33-17](#)
  - extended, creating [33-8](#)
  - named [33-12](#)
  - standard, creating [33-7](#)
- IPv4 and IPv6
  - dual protocol stacks [36-5](#)
- IPv6
  - ACLs
    - displaying [38-8](#)
    - limitations [38-2](#)
    - matching criteria [38-3](#)



- port [38-1](#)
- precedence [38-2](#)
- router [38-1](#)
- supported [38-2](#)
- addresses [36-2](#)
- address formats [36-2](#)
- applications [36-5](#)
- assigning address [36-8](#)
- autoconfiguration [36-5](#)
- configuring static routes [36-11](#)
- default configuration [36-7](#)
- defined [36-1](#)
- forwarding [36-8](#)
- ICMP [36-3](#)
- monitoring [36-12](#)
- neighbor discovery [36-3](#)
- SDM templates [37-1, 38-1](#)
- Stateless Autoconfiguration [36-5](#)
- supported features [36-2](#)
- IPv6 traffic, filtering [38-3](#)

---

## J

- join messages, IGMP [23-3](#)

---

## L

### LACP

- See EtherChannel

- Layer 2 frames, classification with CoS [34-2](#)

- Layer 2 interfaces, default configuration [13-11](#)

### Layer 2 traceroute

- and ARP [40-15](#)
- and CDP [40-15](#)
- broadcast traffic [40-14](#)
- described [40-14](#)
- IP addresses and subnets [40-15](#)
- MAC addresses and VLANs [40-15](#)

- multicast traffic [40-15](#)
- multiple devices on a port [40-15](#)
- unicast traffic [40-14](#)
- usage guidelines [40-15](#)

- Layer 3 features [1-11](#)

### Layer 3 interfaces

- assigning IP addresses to [35-4](#)
- assigning IPv6 addresses to [36-8](#)
- changing from Layer 2 mode [35-4](#)

- Layer 3 packets, classification methods [34-2](#)

- LDAP [4-2](#)

- Leaking IGMP Reports [20-4](#)

### LEDs, switch

- See hardware installation guide

### lightweight directory access protocol

- See LDAP

- line configuration mode [2-2](#)

### Link Aggregation Control Protocol

- See EtherChannel

- link failure, detecting unidirectional [18-7](#)

### Link Layer Discovery Protocol

- See CDP

- link local unicast addresses [36-3](#)

### link redundancy

- See Flex Links

- links, unidirectional [25-1](#)

### link-state tracking

- configuring [39-19](#)
- described [39-17](#)

### LLDP

- configuring [27-4](#)
  - characteristics [27-6](#)
  - default configuration [27-4](#)
- enabling [27-5](#)
- monitoring and maintaining [27-11](#)
- overview [27-1](#)
- supported TLVs [27-1](#)
- switch stack considerations [27-2](#)
- transmission timer and holdtime, setting [27-6](#)

## LLDP-MED

### configuring

procedures [27-4](#)

TLVs [27-7](#)

monitoring and maintaining [27-11](#)

overview [27-1](#), [27-2](#)

supported TLVs [27-2](#)

## LLDP Media Endpoint Discovery

See LLDP-MED

local SPAN [28-2](#)

location TLV [27-3](#), [27-7](#)

## login authentication

with RADIUS [11-30](#)

with TACACS+ [11-14](#)

login banners [5-11](#)

## log messages

See system message logging

Long-Reach Ethernet (LRE) technology [1-15](#)

## loop guard

described [19-9](#)

enabling [19-15](#)

support for [1-7](#)

LRE profiles, considerations in switch clusters [8-13](#)

# M

## MAB

See MAC authentication bypass

## MAB inactivity timer

default setting [12-36](#)

range [12-38](#)

MAC/PHY configuration status TLV [27-2](#)

## MAC addresses

aging time [5-15](#)

and VLAN association [5-14](#)

building the address table [5-14](#)

default configuration [5-15](#)

disabling learning on a VLAN [5-23](#)

discovering [5-24](#)

displaying [5-23](#)

displaying in the IP source binding table [21-20](#)

## dynamic

learning [5-14](#)

removing [5-16](#)

in ACLs [33-21](#)

## static

adding [5-20](#)

allowing [5-22](#), [5-23](#)

characteristics of [5-20](#)

dropping [5-22](#)

removing [5-21](#)

MAC address learning [1-5](#)

MAC address learning, disabling on a VLAN [5-23](#)

MAC address notification, support for [1-11](#)

## MAC address-table move update

configuration guidelines [20-8](#)

configuring [20-12](#)

default configuration [20-8](#)

description [20-6](#)

monitoring [20-14](#)

MAC address-to-VLAN mapping [14-24](#)

## MAC authentication bypass

configuring [12-58](#)

overview [12-17](#)

## MAC extended access lists

applying to Layer 2 interfaces [33-22](#)

configuring for QoS [34-46](#)

creating [33-21](#)

defined [33-21](#)

for QoS classification [34-5](#)

## MACSec

magic packet [12-27](#)

manageability features [1-5](#)

## management access

### in-band

browser session [1-5](#)

CLI session [1-5](#)

device manager [1-5](#)

- SNMP [1-5](#)
  - out-of-band console port connection [1-5](#)
- management address TLV [27-2](#)
- management options
  - CLI [2-1](#)
  - clustering [1-2](#)
  - CNS [4-1](#)
  - Network Assistant [1-2](#)
  - overview [1-4](#)
- management VLAN
  - considerations in switch clusters [8-7](#)
  - discovery through different management VLANs [8-7](#)
- mapping tables for QoS
  - configuring
    - CoS-to-DSCP [34-56](#)
    - DSCP [34-56](#)
    - DSCP-to-CoS [34-59](#)
    - DSCP-to-DSCP-mutation [34-60](#)
    - IP-precedence-to-DSCP [34-57](#)
    - policed-DSCP [34-58](#)
  - described [34-10](#)
- marking
  - action with aggregate policers [34-54](#)
  - described [34-3, 34-8](#)
- matching
  - IPv6 ACLs [38-3](#)
- matching, IPv4 ACLs [33-5](#)
- maximum aging time
  - MSTP [18-24](#)
  - STP [17-21](#)
- maximum hop count, MSTP [18-24](#)
- maximum number of allowed devices, port-based authentication [12-38](#)
- MDA
  - configuration guidelines [12-13 to 12-14](#)
  - described [1-8, 12-13](#)
  - exceptions with authentication process [12-5](#)
- membership mode, VLAN port [14-3](#)
- member switch
  - automatic discovery [8-4](#)
  - defined [8-2](#)
  - managing [8-13](#)
  - passwords [8-12](#)
  - recovering from lost connectivity [40-11](#)
  - requirements [8-3](#)
  - See also candidate switch, cluster standby group, and standby command switch
- memory consistency check errors
  - example [40-23](#)
- memory consistency check routines [1-4, 40-23](#)
- memory consistency integrity [1-4, 40-23](#)
- messages, to users through banners [5-11](#)
- MIBs
  - overview [31-1](#)
  - SNMP interaction with [31-4](#)
- mirroring traffic for analysis [28-1](#)
- mismatches, autonegotiation [40-11](#)
- module number [13-7](#)
- monitoring
  - access groups [33-24](#)
  - cables for unidirectional links [25-1](#)
  - CDP [26-5](#)
  - features [1-11](#)
  - Flex Links [20-14](#)
  - IGMP
    - filters [23-28](#)
    - snooping [23-16, 37-12](#)
  - interfaces [13-20](#)
  - IP SLAs operations [32-6](#)
  - IPv4 ACL configuration [33-24](#)
  - IPv6 [36-12](#)
  - IPv6 ACL configuration [38-8](#)
  - MAC address-table move update [20-14](#)
  - multicast router interfaces [23-16, 37-12](#)
  - MVR [23-22](#)
  - network traffic for analysis with probe [28-2](#)
  - port
    - blocking [24-20](#)

- protection [24-20](#)
  - SFP status [13-21, 40-13](#)
  - speed and duplex mode [13-13](#)
  - traffic flowing among switches [29-1](#)
  - traffic suppression [24-20](#)
  - VLANs [14-13](#)
  - VMPS [14-28](#)
  - VTP [15-16](#)
- mrouter Port [20-3](#)
- mrouter port [20-5](#)
- MSTP
  - boundary ports
    - configuration guidelines [18-15](#)
    - described [18-6](#)
  - BPDU filtering
    - described [19-3](#)
    - enabling [19-12](#)
  - BPDU guard
    - described [19-2](#)
    - enabling [19-11](#)
  - CIST, described [18-3](#)
  - CIST regional root [18-3](#)
  - CIST root [18-5](#)
  - configuration guidelines [18-14, 19-10](#)
  - configuring
    - forward-delay time [18-23](#)
    - hello time [18-23](#)
    - link type for rapid convergence [18-25](#)
    - maximum aging time [18-24](#)
    - maximum hop count [18-24](#)
    - MST region [18-15](#)
    - neighbor type [18-25](#)
    - path cost [18-20](#)
    - port priority [18-19](#)
    - root switch [18-17](#)
    - secondary root switch [18-18](#)
    - switch priority [18-22](#)
- CST
  - defined [18-3](#)
- operations between regions [18-4](#)
  - default configuration [18-14](#)
  - default optional feature configuration [19-9](#)
  - displaying status [18-26](#)
  - enabling the mode [18-15](#)
  - EtherChannel guard
    - described [19-7](#)
    - enabling [19-14](#)
  - extended system ID
    - effects on root switch [18-17](#)
    - effects on secondary root switch [18-18](#)
    - unexpected behavior [18-17](#)
  - IEEE 802.1s
    - implementation [18-6](#)
    - port role naming change [18-6](#)
    - terminology [18-5](#)
  - instances supported [17-9](#)
  - interface state, blocking to forwarding [19-2](#)
  - interoperability and compatibility among modes [17-10](#)
  - interoperability with IEEE 802.1D
    - described [18-8](#)
    - restarting migration process [18-26](#)
- IST
  - defined [18-2](#)
  - master [18-3](#)
  - operations within a region [18-3](#)
- loop guard
  - described [19-9](#)
  - enabling [19-15](#)
- mapping VLANs to MST instance [18-16](#)
- MST region
  - CIST [18-3](#)
  - configuring [18-15](#)
  - described [18-2](#)
  - hop-count mechanism [18-5](#)
  - IST [18-2](#)
  - supported spanning-tree instances [18-2](#)
- optional features supported [1-6](#)

- overview [18-2](#)
- Port Fast
  - described [19-2](#)
  - enabling [19-10](#)
- preventing root switch selection [19-8](#)
- root guard
  - described [19-8](#)
  - enabling [19-15](#)
- root switch
  - configuring [18-17](#)
  - effects of extended system ID [18-17](#)
  - unexpected behavior [18-17](#)
- shutdown Port Fast-enabled port [19-2](#)
- status, displaying [18-26](#)
- multiauth
  - support for inaccessible authentication bypass [12-25](#)
- multiauth mode
  - See multiple-authentication mode
- multicast groups
  - Immediate Leave [23-5](#)
  - joining [23-3](#)
  - leaving [23-5](#)
  - static joins [23-9, 37-8](#)
- multicast router interfaces, monitoring [23-16, 37-12](#)
- multicast router ports, adding [23-9, 37-8](#)
- multicast storm [24-1](#)
- multicast storm-control command [24-4](#)
- multicast television application [23-17](#)
- multicast VLAN [23-17](#)
- Multicast VLAN Registration
  - See MVR
- multidomain authentication
  - See MDA
- multiple authentication [12-14](#)
- multiple authentication mode
  - configuring [12-45](#)
- MVR
  - and address aliasing [23-20](#)
  - and IGMPv3 [23-20](#)

- configuration guidelines [23-20](#)
- configuring interfaces [23-21](#)
- default configuration [23-19](#)
- described [23-17](#)
- example application [23-17](#)
- modes [23-21](#)
- monitoring [23-22](#)
- multicast television application [23-17](#)
- setting global parameters [23-20](#)
- support for [1-4](#)

---

## N

### NAC

- critical authentication [12-24, 12-55](#)
- IEEE 802.1x authentication using a RADIUS server [12-60](#)
- IEEE 802.1x validation using RADIUS server [12-60](#)
- inaccessible authentication bypass [12-55](#)
- Layer 2 IEEE 802.1x validation [12-30, 12-60](#)

named IPv4 ACLs [33-12](#)

### NameSpace Mapper

See NSM

### native VLAN

- configuring [14-19](#)
- default [14-19](#)

### NDAC [7-2](#)

### NEAT

- configuring [12-61](#)
- overview [12-31](#)

neighbor discovery, IPv6 [36-3](#)

### Network Assistant

- benefits [1-1](#)
- described [1-4](#)
- downloading image files [1-2](#)
- guide mode [1-2](#)
- management options [1-2](#)
- managing switch stacks [9-2, 9-13](#)
- upgrading a switch [42-24](#)

- wizards [1-2](#)
- network configuration examples
  - increasing network performance [1-14](#)
  - long-distance, high-bandwidth transport [1-16](#)
  - providing network services [1-15](#)
  - server aggregation and Linux server cluster [1-15](#)
  - small to medium-sized network [1-16](#)
- network design
  - performance [1-14](#)
  - services [1-15](#)
- Network Device Admission Control (NDAC) [7-2](#)
- Network Edge Access Topology
  - See NEAT
- network management
  - CDP [26-1](#)
  - RMON [29-1](#)
  - SNMP [31-1](#)
- network performance, measuring with IP SLAs [32-2](#)
- network policy TLV [27-2, 27-7](#)
- Network Time Protocol
  - See NTP
- no commands [2-4](#)
- nonhierarchical policy maps
  - described [34-9](#)
- non-IP traffic filtering [33-21](#)
- nontrunking mode [14-14](#)
- normal-range VLANs [14-4](#)
  - configuration guidelines [14-6](#)
  - configuring [14-4](#)
  - defined [14-1](#)
- NSM [4-3](#)
- NTP
  - associations
    - defined [5-2](#)
  - overview [5-2](#)
  - stratum [5-2](#)
  - support for [1-5](#)
  - time
    - services [5-2](#)

- synchronizing [5-2](#)

---

## O

- offline configuration for switch stacks [9-6](#)
- off mode, VTP [15-3](#)
- online diagnostics
  - overview [41-1](#)
  - running tests [41-3](#)
  - understanding [41-1](#)
- open1x
  - configuring [12-66](#)
- open1x authentication
  - overview [12-30](#)
- optimizing system resources [10-1](#)
- options, management [1-4](#)
- out-of-profile markdown [1-10](#)

---

## P

- packet modification, with QoS [34-16](#)
- PAgP
  - See EtherChannel
- passwords
  - default configuration [11-2](#)
  - disabling recovery of [11-5](#)
  - encrypting [11-3](#)
  - for security [1-8](#)
  - in clusters [8-12](#)
  - overview [11-1](#)
  - recovery of [40-3](#)
  - setting
    - enable [11-3](#)
    - enable secret [11-3](#)
    - Telnet [11-6](#)
    - with usernames [11-7](#)
  - VTP domain [15-8](#)
- path cost

- MSTP [18-20](#)
- STP [17-18](#)
- PC (passive command switch) [8-9](#)
- performance, network design [1-14](#)
- performance features [1-3](#)
- persistent self-signed certificate [11-47](#)
- per-user ACLs and Filter-Ids [12-8](#)
- per-VLAN spanning-tree plus
  - See PVST+
- physical ports [13-2](#)
- PIM-DVMRP, as snooping method [23-8](#)
- ping
  - character output description [40-14](#)
  - executing [40-13](#)
  - overview [40-13](#)
- PoE
  - auto mode [13-5](#)
  - CDP with power consumption, described [13-4](#)
  - CDP with power negotiation, described [13-4](#)
  - Cisco intelligent power management [13-4](#)
  - configuring [13-16](#)
  - devices supported [13-4](#)
  - high-power devices operating in low-power mode [13-4](#)
  - IEEE power classification levels [13-5](#)
  - power budgeting [13-17](#)
  - power consumption [13-17](#)
  - powered-device detection and initial power allocation [13-4](#)
  - power management modes [13-5](#)
  - power negotiation extensions to CDP [13-4](#)
  - standards supported [13-4](#)
  - static mode [13-6](#)
  - troubleshooting [40-12](#)
- policed-DSCP map for QoS [34-58](#)
- policers
  - configuring
    - for each matched traffic class [34-49](#)
    - for more than one traffic class [34-54](#)
  - described [34-3](#)
  - displaying [34-74](#)
  - number of [34-35](#)
  - types of [34-9](#)
- policing
  - described [34-3](#)
  - token-bucket algorithm [34-9](#)
- policy maps for QoS
  - characteristics of [34-49](#)
  - described [34-7](#)
  - displaying [34-75](#)
  - nonhierarchical on physical ports
    - described [34-9](#)
- port ACLs
  - defined [33-2](#)
  - types of [33-2](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - accounting [12-16](#)
  - authentication server
    - defined [6-2, 12-3](#)
    - RADIUS server [12-3](#)
  - client, defined [6-2, 12-3](#)
  - configuration guidelines [6-9, 12-36](#)
  - configuring
    - 802.1x authentication [12-42](#)
    - guest VLAN [12-53](#)
    - host mode [12-45](#)
    - inaccessible authentication bypass [12-55](#)
    - manual re-authentication of a client [12-48](#)
    - periodic re-authentication [12-47](#)
    - quiet period [12-48](#)
    - RADIUS server [6-13, 12-45](#)
    - RADIUS server parameters on the switch [6-11, 12-43](#)
    - restricted VLAN [12-53](#)
    - switch-to-client frame-retransmission number [12-49, 12-50](#)

- switch-to-client retransmission time [12-48](#)
- violation modes [12-41](#)
- default configuration [6-9, 12-35](#)
- described [12-1](#)
- device roles [6-2, 12-2](#)
- displaying statistics [6-17, 12-68](#)
- downloadable ACLs and redirect URLs
  - configuring [12-63 to 12-65, ?? to 12-65](#)
  - overview [12-20 to 12-22](#)
- EAPOL-start frame [12-5](#)
- EAP-request/identity frame [12-5](#)
- EAP-response/identity frame [12-5](#)
- enabling
  - 802.1X authentication [6-11](#)
- encapsulation [12-3](#)
- flexible authentication ordering
  - configuring [12-65](#)
  - overview [12-30](#)
- guest VLAN
  - configuration guidelines [12-23, 12-24](#)
  - described [12-22](#)
- host mode [12-11](#)
- inaccessible authentication bypass
  - configuring [12-55](#)
  - described [12-24](#)
  - guidelines [12-37](#)
- initiation and message exchange [12-5](#)
- magic packet [12-27](#)
- maximum number of allowed devices per port [12-38](#)
- method lists [12-42](#)
- multiple authentication [12-14](#)
- per-user ACLs
  - configuration tasks [12-20](#)
  - described [12-19](#)
  - RADIUS server attributes [12-19](#)
- ports
  - authorization state and dot1x port-control command [12-10](#)
  - authorized and unauthorized [12-10](#)
  - voice VLAN [12-26](#)
- port security
  - described [12-27](#)
- readiness check
  - configuring [12-38](#)
  - described [12-17, 12-38](#)
- resetting to default values [12-67](#)
- statistics, displaying [12-68](#)
- switch
  - as proxy [6-2, 12-3](#)
  - RADIUS client [12-3](#)
- switch supplicant
  - configuring [12-61](#)
  - overview [12-31](#)
- user distribution
  - guidelines [12-29](#)
  - overview [12-29](#)
- VLAN assignment
  - AAA authorization [12-42](#)
  - characteristics [12-18](#)
  - configuration tasks [12-18](#)
  - described [12-17](#)
- voice aware 802.1x security
  - configuring [12-39](#)
  - described [12-31, 12-39](#)
- voice VLAN
  - described [12-26](#)
  - PVID [12-26](#)
  - VVID [12-26](#)
- wake-on-LAN, described [12-27](#)
- with ACLs and RADIUS Filter-Id attribute [12-33](#)
- port-based authentication methods, supported [12-7](#)
- port blocking [1-3, 24-7](#)
- port-channel
  - See EtherChannel
- port description TLV [27-1](#)
- Port Fast
  - described [19-2](#)
  - enabling [19-10](#)



- mode, spanning tree [14-25](#)
  - support for [1-6](#)
  - port membership modes, VLAN [14-3](#)
  - port priority
    - MSTP [18-19](#)
    - STP [17-16](#)
  - ports
    - access [13-2](#)
    - blocking [24-7](#)
    - dynamic access [14-4](#)
    - protected [24-6](#)
    - static-access [14-3, 14-10](#)
    - switch [13-2](#)
    - trunks [14-3, 14-14](#)
    - VLAN assignments [14-10](#)
  - port security
    - aging [24-17](#)
    - and QoS trusted boundary [34-39](#)
    - configuring [24-12](#)
    - default configuration [24-11](#)
    - described [24-8](#)
    - displaying [24-20](#)
    - on trunk ports [24-14](#)
    - sticky learning [24-9](#)
    - violations [24-10](#)
    - with other features [24-11](#)
  - port-shutdown response, VMPS [14-24](#)
  - port VLAN ID TLV [27-2](#)
  - power management TLV [27-2, 27-7](#)
  - Power over Ethernet
    - See PoE
  - preemption, default configuration [20-8](#)
  - preemption delay, default configuration [20-8](#)
  - preferential treatment of traffic
    - See QoS
  - preventing unauthorized access [11-1](#)
  - primary links [20-2](#)
  - priority
    - overriding CoS [16-6](#)
    - trusting CoS [16-6](#)
  - private VLAN edge ports
    - See protected ports
  - privileged EXEC mode [2-2](#)
  - privilege levels
    - changing the default for lines [11-9](#)
    - command switch [8-14](#)
    - exiting [11-10](#)
    - logging into [11-10](#)
    - mapping on member switches [8-14](#)
    - overview [11-2, 11-8](#)
    - setting a command with [11-8](#)
  - protected ports [1-8, 24-6](#)
  - protocol storm protection [24-18](#)
  - provisioning new members for a switch stack [9-6](#)
  - proxy reports [20-3](#)
  - pruning, VTP
    - disabling
      - in VTP domain [15-14](#)
      - on a port [14-19](#)
    - enabling
      - in VTP domain [15-14](#)
      - on a port [14-19](#)
    - examples [15-6](#)
    - overview [15-5](#)
  - pruning-eligible list
    - changing [14-19](#)
    - for VTP pruning [15-5](#)
    - VLANs [15-14](#)
  - PVST+
    - described [17-9](#)
    - IEEE 802.1Q trunking interoperability [17-10](#)
    - instances supported [17-9](#)
- 
- ## Q
- QoS
    - and MQC commands [34-1](#)
    - auto-QoS

- categorizing traffic [34-17](#)
- configuration and defaults display [34-31](#)
- configuration guidelines [34-29](#)
- described [34-16](#)
- disabling [34-31](#)
- displaying generated commands [34-31](#)
- displaying the initial configuration [34-31](#)
- effects on running configuration [34-29](#)
- list of generated commands [34-20, 34-24](#)
- basic model [34-3](#)
- classification
  - class maps, described [34-7](#)
  - defined [34-3](#)
  - DSCP transparency, described [34-40](#)
  - flowchart [34-6](#)
  - forwarding treatment [34-2](#)
  - in frames and packets [34-2](#)
  - IP ACLs, described [34-7](#)
  - MAC ACLs, described [34-5, 34-7](#)
  - options for IP traffic [34-5](#)
  - options for non-IP traffic [34-4](#)
  - policy maps, described [34-7](#)
  - trust DSCP, described [34-4](#)
  - trusted CoS, described [34-4](#)
  - trust IP precedence, described [34-4](#)
- class maps
  - configuring [34-47](#)
  - displaying [34-74](#)
- configuration guidelines
  - auto-QoS [34-29](#)
  - standard QoS [34-34](#)
- configuring
  - aggregate policers [34-54](#)
  - auto-QoS [34-16](#)
  - default port CoS value [34-38](#)
  - DSCP maps [34-56](#)
  - DSCP transparency [34-40](#)
  - DSCP trust states bordering another domain [34-41](#)
  - egress queue characteristics [34-66](#)
  - ingress queue characteristics [34-62](#)
  - IP extended ACLs [34-45](#)
  - IP standard ACLs [34-43](#)
  - MAC ACLs [34-46](#)
  - port trust states within the domain [34-36](#)
  - trusted boundary [34-39](#)
- default auto configuration [34-17](#)
- default standard configuration [34-32](#)
- displaying statistics [34-74](#)
- DSCP transparency [34-40](#)
- egress queues
  - allocating buffer space [34-67](#)
  - buffer allocation scheme, described [34-14](#)
  - configuring shaped weights for SRR [34-71](#)
  - configuring shared weights for SRR [34-72](#)
  - described [34-3](#)
  - displaying the threshold map [34-70](#)
  - flowchart [34-14](#)
  - mapping DSCP or CoS values [34-69](#)
  - scheduling, described [34-4](#)
  - setting WTD thresholds [34-67](#)
  - WTD, described [34-15](#)
- enabling globally [34-36](#)
- flowcharts
  - classification [34-6](#)
  - egress queueing and scheduling [34-14](#)
  - ingress queueing and scheduling [34-12](#)
  - policing and marking [34-10](#)
- implicit deny [34-7](#)
- ingress queues
  - allocating bandwidth [34-64](#)
  - allocating buffer space [34-64](#)
  - buffer and bandwidth allocation, described [34-13](#)
  - configuring shared weights for SRR [34-64](#)
  - configuring the priority queue [34-65](#)
  - described [34-3](#)
  - displaying the threshold map [34-63](#)
  - flowchart [34-12](#)

- mapping DSCP or CoS values [34-62](#)
- priority queue, described [34-13](#)
- scheduling, described [34-3](#)
- setting WTD thresholds [34-62](#)
- WTD, described [34-13](#)
- IP phones
  - automatic classification and queueing [34-17](#)
  - detection and trusted settings [34-17, 34-39](#)
- limiting bandwidth on egress interface [34-73](#)
- mapping tables
  - CoS-to-DSCP [34-56](#)
  - displaying [34-74](#)
  - DSCP-to-CoS [34-59](#)
  - DSCP-to-DSCP-mutation [34-60](#)
  - IP-precedence-to-DSCP [34-57](#)
  - policed-DSCP [34-58](#)
  - types of [34-10](#)
- marked-down actions [34-51](#)
- marking, described [34-3, 34-8](#)
- overview [34-1](#)
- packet modification [34-16](#)
- policers
  - configuring [34-51, 34-54](#)
  - described [34-8](#)
  - displaying [34-74](#)
  - number of [34-35](#)
  - types of [34-9](#)
- policies, attaching to an interface [34-8](#)
- policing
  - described [34-3, 34-8](#)
  - token bucket algorithm [34-9](#)
- policy maps
  - characteristics of [34-49](#)
  - displaying [34-75](#)
  - nonhierarchical on physical ports [34-49](#)
- QoS label, defined [34-3](#)
- queues
  - configuring egress characteristics [34-66](#)
  - configuring ingress characteristics [34-62](#)
  - high priority (expedite) [34-15, 34-73](#)
  - location of [34-11](#)
  - SRR, described [34-12](#)
  - WTD, described [34-11](#)
- rewrites [34-16](#)
- support for [1-10](#)
- trust states
  - bordering another domain [34-41](#)
  - described [34-4](#)
  - trusted device [34-39](#)
  - within the domain [34-36](#)
- quality of service
  - See QoS
- queries, IGMP [23-4](#)
- query solicitation, IGMP [23-12](#)

---

## R

### RADIUS

- attributes
  - vendor-proprietary [11-38](#)
  - vendor-specific [11-36](#)
- configuring
  - accounting [11-35](#)
  - authentication [11-30](#)
  - authorization [11-34](#)
  - communication, global [11-28, 11-36](#)
  - communication, per-server [11-28](#)
  - multiple UDP ports [11-28](#)
- default configuration [11-27](#)
- defining AAA server groups [11-32](#)
- displaying the configuration [11-40](#)
- identifying the server [11-28](#)
- in clusters [8-13](#)
- limiting the services to the user [11-34](#)
- method list, defined [11-26](#)
- operation of [11-19](#)
- overview [11-18](#)
- server load balancing [11-40](#)

- suggested network environments [11-18](#)
- tracking services accessed by user [11-35](#)
- RADIUS Change of Authorization [11-20](#)
- range
  - macro [13-9](#)
  - of interfaces [13-8](#)
- rapid convergence [18-9](#)
- rapid per-VLAN spanning-tree plus
  - See rapid PVST+
- rapid PVST+
  - described [17-9](#)
  - IEEE 802.1Q trunking interoperability [17-10](#)
  - instances supported [17-9](#)
- Rapid Spanning Tree Protocol
  - See RSTP
- rcommand command [8-13](#)
- RCP
  - configuration files
    - downloading [42-17](#)
    - overview [42-16](#)
    - preparing the server [42-16](#)
    - uploading [42-18](#)
  - image files
    - deleting old image [42-36](#)
    - downloading [42-34](#)
    - preparing the server [42-33](#)
    - uploading [42-36](#)
- readiness check
  - port-based authentication
    - configuring [12-38](#)
    - described [12-17, 12-38](#)
- reconfirmation interval, VMPS, changing [14-27](#)
- reconfirming dynamic VLAN membership [14-27](#)
- recovery procedures [40-1](#)
- redirect URL [12-20, 12-21, 12-63](#)
- redundancy
  - EtherChannel [39-3](#)
  - STP
    - backbone [17-8](#)
    - path cost [14-22](#)
    - port priority [14-20](#)
- redundant links and UplinkFast [19-13](#)
- reloading software [3-23](#)
- Remote Authentication Dial-In User Service
  - See RADIUS
- Remote Copy Protocol
  - See RCP
- Remote Network Monitoring
  - See RMON
- Remote SPAN
  - See RSPAN
- remote SPAN [28-2](#)
- report suppression, IGMP
  - described [23-6](#)
  - disabling [23-15, 37-11](#)
- resequencing ACL entries [33-12](#)
- reserved addresses in DHCP pools [21-22](#)
- resetting a UDLD-shutdown interface [25-6](#)
- responder, IP SLAs
  - described [32-3](#)
  - enabling [32-5](#)
- response time, measuring with IP SLAs [32-4](#)
- restricted VLAN
  - configuring [12-53](#)
  - described [12-23](#)
  - using with IEEE 802.1x [12-23](#)
- restricting access
  - overview [11-1](#)
  - passwords and privilege levels [11-2](#)
  - RADIUS [11-18](#)
  - TACACS+ [11-10](#)
- retry count, VMPS, changing [14-28](#)
- RFC
  - 1112, IP multicast and IGMP [23-2](#)
  - 1157, SNMPv1 [31-2](#)
  - 1166, IP addresses [35-4](#)
  - 1305, NTP [5-2](#)
  - 1757, RMON [29-2](#)

- 1901, SNMPv2C [31-2](#)
  - 1902 to 1907, SNMPv2 [31-2](#)
  - 2236, IP multicast and IGMP [23-2](#)
  - 2273-2275, SNMPv3 [31-2](#)
  - RFC 5176 Compliance [11-21](#)
  - RMON
    - default configuration [29-3](#)
    - displaying status [29-6](#)
    - enabling alarms and events [29-3](#)
    - groups supported [29-2](#)
    - overview [29-1](#)
    - statistics
      - collecting group Ethernet [29-6](#)
      - collecting group history [29-5](#)
    - support for [1-11](#)
  - root guard
    - described [19-8](#)
    - enabling [19-15](#)
    - support for [1-7](#)
  - root switch
    - MSTP [18-17](#)
    - STP [17-14](#)
  - router ACLs
    - defined [33-2](#)
    - types of [33-3](#)
  - RSPAN
    - characteristics [28-7](#)
    - configuration guidelines [28-15](#)
    - default configuration [28-9](#)
    - defined [28-2](#)
    - destination ports [28-6](#)
    - displaying status [28-21](#)
    - interaction with other features [28-8](#)
    - monitored ports [28-5](#)
    - monitoring ports [28-6](#)
    - overview [1-11, 28-1](#)
    - received traffic [28-4](#)
    - sessions
      - creating [28-15](#)
      - defined [28-3](#)
      - limiting source traffic to specific VLANs [28-20](#)
      - specifying monitored ports [28-15](#)
      - with ingress traffic enabled [28-19](#)
    - source ports [28-5](#)
    - transmitted traffic [28-5](#)
    - VLAN-based [28-6](#)
  - RSTP
    - active topology [18-9](#)
    - BPDU
      - format [18-12](#)
      - processing [18-12](#)
    - designated port, defined [18-9](#)
    - designated switch, defined [18-9](#)
    - interoperability with IEEE 802.1D
      - described [18-8](#)
      - restarting migration process [18-26](#)
      - topology changes [18-13](#)
    - overview [18-8](#)
    - port roles
      - described [18-9](#)
      - synchronized [18-11](#)
    - proposal-agreement handshake process [18-10](#)
    - rapid convergence
      - described [18-9](#)
      - edge ports and Port Fast [18-9](#)
      - point-to-point links [18-10, 18-25](#)
      - root ports [18-10](#)
    - root port, defined [18-9](#)
    - See also MSTP
  - running configuration
    - replacing [42-19, 42-20](#)
    - rolling back [42-19, 42-21](#)
  - running configuration, saving [3-15](#)
- 
- ## S
- SC (standby command switch) [8-9](#)
  - scheduled reloads [3-23](#)

- SCP
  - and SSH [11-52](#)
  - configuring [11-53](#)
- SDM
  - templates
    - configuring [10-2](#)
    - number of [10-1](#)
- SDM template [38-3](#)
  - configuration guidelines [10-1](#)
  - configuring [10-1](#)
  - types of [10-1](#)
- Secure Copy Protocol
- secure HTTP client
  - configuring [11-51](#)
  - displaying [11-52](#)
- secure HTTP server
  - configuring [11-50](#)
  - displaying [11-52](#)
- secure MAC addresses
  - deleting [24-16](#)
  - maximum number of [24-9](#)
  - types of [24-9](#)
- secure remote connections [11-42](#)
- Secure Shell
  - See SSH
- Secure Socket Layer
  - See SSL
- security, port [24-8](#)
- Security Exchange Protocol (SXP) [7-2](#)
- security features [1-7](#)
- Security Group Access Control List (SGACL) [7-2](#)
- Security Group Tag (SGT) [7-2](#)
- See SCP
- sequence numbers in log messages [30-7](#)
- server mode, VTP [15-3](#)
- service-provider network, MSTP and RSTP [18-1](#)
- set-request operation [31-4](#)
- setup program
  - failed command switch replacement [40-10](#)
  - replacing failed command switch [40-8](#)
- severity levels, defining in system messages [30-8](#)
- SFPs
  - monitoring status of [13-21, 40-13](#)
  - security and identification [40-12](#)
  - status, displaying [40-13](#)
- SGACL [7-2](#)
- SGT [7-2](#)
- shaped round robin
  - See SRR
- show access-lists hw-summary command [33-18](#)
- show and more command output, filtering [2-9](#)
- show cdp traffic command [26-5](#)
- show cluster members command [8-13](#)
- show configuration command [13-18](#)
- show forward command [40-21](#)
- show interfaces command [13-13, 13-18](#)
- show interfaces switchport [20-4](#)
- show lldp traffic command [27-11](#)
- show platform forward command [40-21](#)
- show platform team command [40-23](#)
- show running-config command
  - displaying ACLs [33-17, 33-18](#)
  - interface description in [13-22](#)
- shutdown command on interfaces [13-22](#)
- Simple Network Management Protocol
  - See SNMP
- small-frame arrival rate, configuring [24-5](#)
- SNAP [26-1](#)
- SNMP
  - accessing MIB variables with [31-4](#)
  - agent
    - described [31-4](#)
    - disabling [31-9](#)
  - and IP SLAs [32-2](#)
  - authentication level [31-12](#)
  - community strings
    - configuring [31-9](#)
    - for cluster switches [31-4](#)

- overview [31-4](#)
  - configuration examples [31-19](#)
  - default configuration [31-8](#)
  - engine ID [31-8](#)
  - groups [31-8, 31-11](#)
  - host [31-8](#)
  - ifIndex values [31-5](#)
  - in-band management [1-5](#)
  - in clusters [8-13](#)
  - informs
    - and trap keyword [31-14](#)
    - described [31-5](#)
    - differences from traps [31-5](#)
    - disabling [31-17](#)
    - enabling [31-17](#)
  - limiting access by TFTP servers [31-18](#)
  - limiting system log messages to NMS [30-9](#)
  - manager functions [1-4, 31-3](#)
  - managing clusters with [8-14](#)
  - notifications [31-5](#)
  - overview [31-1, 31-4](#)
  - security levels [31-3](#)
  - setting CPU threshold notification [31-17](#)
  - status, displaying [31-20](#)
  - system contact and location [31-18](#)
  - trap manager, configuring [31-15](#)
  - traps
    - described [31-3, 31-5](#)
    - differences from informs [31-5](#)
    - disabling [31-17](#)
    - enabling [31-14](#)
    - enabling MAC address notification [5-16, 5-18, 5-19](#)
    - overview [31-1, 31-4](#)
    - types of [31-14](#)
  - users [31-8, 31-11](#)
  - versions supported [31-2](#)
- SNMP and Syslog Over IPv6 [36-6](#)
- SNMPv1 [31-2](#)
- SNMPv2C [31-2](#)
- SNMPv3 [31-2](#)
- snooping, IGMP [23-1](#)
- software compatibility
- See stacks, switch
- software images
- location in flash [42-24](#)
  - recovery procedures [40-2](#)
  - scheduling reloads [3-23](#)
  - tar file format, described [42-25](#)
  - See also downloading and uploading
- source addresses
- in IPv4 ACLs [33-9](#)
  - in IPv6 ACLs [38-5](#)
- source-and-destination-IP address based forwarding, EtherChannel [39-7](#)
- source-and-destination MAC address forwarding, EtherChannel [39-7](#)
- source-IP address based forwarding, EtherChannel [39-7](#)
- source-MAC address forwarding, EtherChannel [39-6](#)
- SPAN
- configuration guidelines [28-10](#)
  - default configuration [28-9](#)
  - destination ports [28-6](#)
  - displaying status [28-21](#)
  - interaction with other features [28-8](#)
  - monitored ports [28-5](#)
  - monitoring ports [28-6](#)
  - overview [1-11, 28-1](#)
  - ports, restrictions [24-12](#)
  - received traffic [28-4](#)
  - sessions
    - configuring ingress forwarding [28-13, 28-20](#)
    - creating [28-10](#)
    - defined [28-3](#)
    - limiting source traffic to specific VLANs [28-14](#)
    - removing destination (monitoring) ports [28-12](#)
    - specifying monitored ports [28-10](#)
    - with ingress traffic enabled [28-12](#)

- source ports [28-5](#)
  - transmitted traffic [28-5](#)
  - VLAN-based [28-6](#)
- spanning tree and native VLANs [14-15](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [28-4](#)
- SRR
  - configuring
    - shaped weights on egress queues [34-71](#)
    - shared weights on egress queues [34-72](#)
    - shared weights on ingress queues [34-64](#)
  - described [34-12](#)
  - shaped mode [34-12](#)
  - shared mode [34-12](#)
  - support for [1-10, 1-11](#)
- SSH
  - configuring [11-43](#)
  - cryptographic software image [11-41](#)
  - described [1-5, 11-42](#)
  - encryption methods [11-42](#)
  - switch stack considerations [9-14](#)
  - user authentication methods, supported [11-42](#)
- SSL
  - configuration guidelines [11-49](#)
  - configuring a secure HTTP client [11-51](#)
  - configuring a secure HTTP server [11-50](#)
  - cryptographic software image [11-46](#)
  - described [11-46](#)
  - monitoring [11-52](#)
- stack, switch
  - MAC address of [9-5, 9-16](#)
- stack changes, effects on
  - IP routing [35-3](#)
- stack master
  - bridge ID (MAC address) [9-5](#)
  - defined [9-1](#)
  - election [9-4](#)
  - See also stacks, switch
- stack member
  - accessing CLI of specific member [9-21](#)
  - configuring
    - member number [9-19](#)
    - priority value [9-20](#)
  - defined [9-1](#)
  - displaying information of [9-22](#)
  - number [9-5](#)
  - priority value [9-6](#)
  - provisioning a new member [9-20](#)
  - replacing [9-13](#)
  - See also stacks, switch
- stack protocol version [9-9](#)
- stacks, switch
  - accessing CLI of specific member [9-21](#)
  - assigning information
    - member number [9-19](#)
    - priority value [9-20](#)
    - provisioning a new member [9-20](#)
  - auto-advise [9-10](#)
  - auto-copy [9-10](#)
  - auto-extract [9-10](#)
  - auto-upgrade [9-10](#)
  - bridge ID [9-5](#)
  - compatibility, software [9-8](#)
  - configuration file [9-13](#)
  - configuration scenarios [9-14](#)
  - default configuration [9-16](#)
  - description of [9-1](#)
  - displaying information of [9-22](#)
  - enabling persistent MAC address timer [9-16](#)
  - incompatible software and image upgrades [9-12](#)
  - management connectivity [9-13](#)
  - managing [9-1](#)
  - membership [9-2](#)
  - merged [9-3](#)
  - MSTP instances supported [17-9](#)
  - offline configuration
    - described [9-6](#)



- effects of adding a provisioned switch [9-7](#)
  - effects of removing a provisioned switch [9-8](#)
  - effects of replacing a provisioned switch [9-8](#)
  - provisioned configuration, defined [9-6](#)
  - provisioned switch, defined [9-6](#)
  - provisioning a new member [9-20](#)
- partitioned [9-3](#)
- provisioned switch
  - adding [9-7](#)
  - removing [9-8](#)
  - replacing [9-8](#)
- replacing a failed member [9-13](#)
- software compatibility [9-8](#)
- software image version [9-8](#)
- stack protocol version [9-9](#)
- system-wide configuration considerations [9-13](#)
- version-mismatch (VM) mode
  - automatic upgrades with auto-upgrade [9-10](#)
  - examples [9-11](#)
  - manual upgrades with auto-advise [9-10](#)
  - upgrades with auto-extract [9-10](#)
- version-mismatch mode
  - described [9-9](#)
- See also stack master and stack member
- standby command switch
  - configuring
  - considerations [8-10](#)
  - defined [8-2](#)
  - priority [8-9](#)
  - requirements [8-3](#)
  - virtual IP address [8-10](#)
- See also cluster standby group and HSRP
- standby group, cluster
  - See cluster standby group and HSRP
- standby links [20-2](#)
- startup configuration
  - booting
    - manually [3-19](#)
    - specific image [3-20](#)
  - clearing [42-19](#)
  - configuration file
    - automatically downloading [3-18](#)
    - specifying the filename [3-18](#)
  - static access ports
    - assigning to VLAN [14-10](#)
    - defined [13-2, 14-3](#)
  - static addresses
    - See addresses
  - static MAC addressing [1-8](#)
  - static routes
    - configuring [35-5](#)
    - configuring for IPv6 [36-11](#)
  - static VLAN membership [14-2](#)
  - statistics
    - 802.1X [6-17](#)
    - 802.1x [12-68](#)
    - CDP [26-5](#)
    - interface [13-21](#)
    - LLDP [27-11](#)
    - LLDP-MED [27-11](#)
    - NMSP [27-11](#)
    - QoS ingress and egress [34-74](#)
    - RMON group Ethernet [29-6](#)
    - RMON group history [29-5](#)
    - SNMP input and output [31-20](#)
    - VTP [15-16](#)
- sticky learning [24-9](#)
- storm control
  - configuring [24-3](#)
  - described [24-1](#)
  - disabling [24-5](#)
  - displaying [24-20](#)
  - support for [1-3](#)
  - thresholds [24-1](#)
- STP
  - accelerating root port selection [19-4](#)
  - BackboneFast
    - described [19-5](#)

- disabling [19-14](#)
  - enabling [19-13](#)
- BPDU filtering
  - described [19-3](#)
  - disabling [19-12](#)
  - enabling [19-12](#)
- BPDU guard
  - described [19-2](#)
  - disabling [19-12](#)
  - enabling [19-11](#)
- BPDU message exchange [17-3](#)
- configuration guidelines [17-12, 19-10](#)
- configuring
  - forward-delay time [17-21](#)
  - hello time [17-20](#)
  - maximum aging time [17-21](#)
  - path cost [17-18](#)
  - port priority [17-16](#)
  - root switch [17-14](#)
  - secondary root switch [17-16](#)
  - spanning-tree mode [17-13](#)
  - switch priority [17-19](#)
  - transmit hold-count [17-22](#)
- counters, clearing [17-22](#)
- default configuration [17-11](#)
- default optional feature configuration [19-9](#)
- designated port, defined [17-3](#)
- designated switch, defined [17-3](#)
- detecting indirect link failures [19-5](#)
- disabling [17-14](#)
- displaying status [17-22](#)
- EtherChannel guard
  - described [19-7](#)
  - disabling [19-14](#)
  - enabling [19-14](#)
- extended system ID
  - effects on root switch [17-14](#)
  - effects on the secondary root switch [17-16](#)
  - overview [17-4](#)
  - unexpected behavior [17-14](#)
- features supported [1-6](#)
- IEEE 802.1D and bridge ID [17-4](#)
- IEEE 802.1D and multicast addresses [17-8](#)
- IEEE 802.1t and VLAN identifier [17-4](#)
- inferior BPDU [17-3](#)
- instances supported [17-9](#)
- interface state, blocking to forwarding [19-2](#)
- interface states
  - blocking [17-5](#)
  - disabled [17-7](#)
  - forwarding [17-5, 17-6](#)
  - learning [17-6](#)
  - listening [17-6](#)
  - overview [17-4](#)
- interoperability and compatibility among modes [17-10](#)
- limitations with IEEE 802.1Q trunks [17-10](#)
- load sharing
  - overview [14-20](#)
  - using path costs [14-22](#)
  - using port priorities [14-20](#)
- loop guard
  - described [19-9](#)
  - enabling [19-15](#)
- modes supported [17-9](#)
- multicast addresses, effect of [17-8](#)
- optional features supported [1-6](#)
- overview [17-2](#)
- path costs [14-22](#)
- Port Fast
  - described [19-2](#)
  - enabling [19-10](#)
- port priorities [14-21](#)
- preventing root switch selection [19-8](#)
- protocols supported [17-9](#)
- redundant connectivity [17-8](#)
- root guard
  - described [19-8](#)

- enabling [19-15](#)
- root port, defined [17-3](#)
- root switch
  - configuring [17-14](#)
  - effects of extended system ID [17-4, 17-14](#)
  - election [17-3](#)
  - unexpected behavior [17-14](#)
- shutdown Port Fast-enabled port [19-2](#)
- status, displaying [17-22](#)
- superior BPDU [17-3](#)
- timers, described [17-20](#)
- UplinkFast
  - described [19-4](#)
  - enabling [19-13](#)
- stratum, NTP [5-2](#)
- subnet mask [35-4](#)
- success response, VMPS [14-24](#)
- summer time [5-7](#)
- SunNet Manager [1-4](#)
- supported port-based authentication methods [12-7](#)
- SVIs
  - and IP unicast routing [35-3](#)
  - and router ACLs [33-3](#)
  - connecting VLANs [13-6](#)
  - defined [13-3](#)
- switch [36-2](#)
- switch clustering technology [8-1](#)
  - See also clusters, switch
- switch console port [1-5](#)
- Switch Database Management
  - See SDM
- Switched Port Analyzer
  - See SPAN
- switched ports [13-2](#)
- switchport backup interface [20-4, 20-5](#)
- switchport block multicast command [24-8](#)
- switchport block unicast command [24-8](#)
- switchport protected command [24-7](#)
- switch priority
  - MSTP [18-22](#)
  - STP [17-19](#)
- switch software features [1-1](#)
- switch virtual interface
  - See SVI
- SXP [7-2](#)
- syslog
  - See system message logging
- system capabilities TLV [27-2](#)
- system clock
  - configuring
    - daylight saving time [5-7](#)
    - manually [5-5](#)
    - summer time [5-7](#)
    - time zones [5-6](#)
  - displaying the time and date [5-5](#)
  - overview [5-1](#)
  - See also NTP
- system description TLV [27-2](#)
- system message logging
  - default configuration [30-3](#)
  - defining error message severity levels [30-8](#)
  - disabling [30-3](#)
  - displaying the configuration [30-13](#)
  - enabling [30-4](#)
  - facility keywords, described [30-13](#)
  - level keywords, described [30-9](#)
  - limiting messages [30-9](#)
  - message format [30-2](#)
  - overview [30-1](#)
  - sequence numbers, enabling and disabling [30-7](#)
  - setting the display destination device [30-4](#)
  - synchronizing log messages [30-5](#)
  - syslog facility [1-11](#)
  - time stamps, enabling and disabling [30-7](#)
  - UNIX syslog servers
    - configuring the daemon [30-12](#)
    - configuring the logging facility [30-12](#)
    - facilities supported [30-13](#)

## system name

default configuration [5-9](#)default setting [5-9](#)manual configuration [5-9](#)

See also DNS

system name TLV [27-2](#)system prompt, default setting [5-8, 5-9](#)system resources, optimizing [10-1](#)**T**

## TACACS+

accounting, defined [11-12](#)authentication, defined [11-11](#)authorization, defined [11-11](#)

## configuring

accounting [11-17](#)authentication key [11-13](#)authorization [11-16](#)login authentication [11-14](#)default configuration [11-13](#)displaying the configuration [11-18](#)identifying the server [11-13](#)in clusters [8-13](#)limiting the services to the user [11-16](#)operation of [11-12](#)overview [11-10](#)support for [1-9](#)tracking services accessed by user [11-17](#)

## tar files

creating [42-6](#)displaying the contents of [42-6](#)extracting [42-7](#)image file format [42-25](#)

## TCAM

memory consistency check errors

example [40-23](#)memory consistency check routines [1-4, 40-23](#)memory consistency integrity [1-4, 40-23](#)

## space

HFTM [40-23](#)HQATM [40-23](#)unassigned [40-23](#)TDR [1-11](#)

## Telnet

accessing management interfaces [2-9](#)number of connections [1-5](#)setting a password [11-6](#)temporary self-signed certificate [11-47](#)

## Terminal Access Controller Access Control System Plus

See TACACS+

terminal lines, setting a password [11-6](#)

ternary content addressable memory

See TCAM

## TFTP

configuration files

downloading [42-11](#)preparing the server [42-10](#)uploading [42-12](#)configuration files in base directory [3-7](#)configuring for autoconfiguration [3-7](#)

image files

deleting [42-28](#)downloading [42-26](#)preparing the server [42-26](#)uploading [42-28](#)limiting access by servers [31-18](#)TFTP server [1-5](#)threshold, traffic level [24-2](#)

## time

See NTP and system clock

## Time Domain Reflector

See TDR

time-range command [33-14](#)time ranges in ACLs [33-14](#)time stamps in log messages [30-7](#)time zones [5-6](#)

## TLVs

- defined 27-1
- LLDP 27-1
- LLDP-MED 27-2
- Token Ring VLANs
  - support for 14-5
  - VTP support 15-4
- ToS 1-10
- traceroute, Layer 2
  - and ARP 40-15
  - and CDP 40-15
  - broadcast traffic 40-14
  - described 40-14
  - IP addresses and subnets 40-15
  - MAC addresses and VLANs 40-15
  - multicast traffic 40-15
  - multiple devices on a port 40-15
  - unicast traffic 40-14
  - usage guidelines 40-15
- traceroute command 40-17
  - See also IP traceroute
- traffic
  - blocking flooded 24-8
  - fragmented 33-4
  - fragmented IPv6 38-2
  - unfragmented 33-4
- traffic policing 1-10
- traffic suppression 24-1
- transmit hold-count
  - see STP
- transparent mode, VTP 15-3
- trap-door mechanism 3-2
- traps
  - configuring MAC address notification 5-16, 5-18, 5-19
  - configuring managers 31-14
  - defined 31-3
  - enabling 5-16, 5-18, 5-19, 31-14
  - notification types 31-14
  - overview 31-1, 31-4
- troubleshooting
  - connectivity problems 40-13, 40-14, 40-16
  - CPU utilization 40-24
  - detecting unidirectional links 25-1
  - displaying crash information 40-22
  - setting packet forwarding 40-21
  - SFP security and identification 40-12
  - show forward command 40-21
  - with CiscoWorks 31-4
  - with debug commands 40-18
  - with ping 40-13
  - with system message logging 30-1
  - with traceroute 40-16
- trunk failover
  - See link-state tracking
- trunking encapsulation 1-7
- trunk ports
  - configuring 14-16
  - defined 13-3, 14-3
- trunks
  - allowed-VLAN list 14-17
  - load sharing
    - setting STP path costs 14-22
    - using STP port priorities 14-20, 14-21
  - native VLAN for untagged traffic 14-19
  - parallel 14-22
  - pruning-eligible list 14-19
  - to non-DTP device 14-14
- trusted boundary for QoS 34-39
- trusted port states
  - between QoS domains 34-41
  - classification options 34-4
  - ensuring port security for IP phones 34-39
  - support for 1-10
  - within a QoS domain 34-36
- trustpoints, CA 11-46
- twisted-pair Ethernet, detecting unidirectional links 25-1
- type of service
  - See ToS

## U

### UDLD

- configuration guidelines [25-4](#)
- default configuration [25-4](#)
- disabling
  - globally [25-5](#)
  - on fiber-optic interfaces [25-5](#)
  - per interface [25-5](#)
- echoing detection mechanism [25-2](#)
- enabling
  - globally [25-4](#)
  - per interface [25-5](#)
- link-detection mechanism [25-1](#)
- neighbor database [25-2](#)
- overview [25-1](#)
- resetting an interface [25-6](#)
- status, displaying [25-6](#)
- support for [1-6](#)

unauthorized ports with IEEE 802.1x [12-10](#)

- unicast MAC address filtering [1-5](#)
  - and adding static addresses [5-21](#)
  - and broadcast MAC addresses [5-21](#)
  - and CPU packets [5-21](#)
  - and multicast addresses [5-21](#)
  - and router MAC addresses [5-21](#)
  - configuration guidelines [5-21](#)
  - described [5-21](#)

unicast storm [24-1](#)

unicast storm control command [24-4](#)

unicast traffic, blocking [24-8](#)

UniDirectional Link Detection protocol

See UDLD

UNIX syslog servers

- daemon configuration [30-12](#)
- facilities supported [30-13](#)
- message logging configuration [30-12](#)

unrecognized Type-Length-Value (TLV) support [15-4](#)

upgrading software images

See downloading

UplinkFast

- described [19-4](#)
- disabling [19-13](#)
- enabling [19-13](#)

uploading

- configuration files
  - preparing [42-10, 42-13, 42-16](#)
  - reasons for [42-8](#)
  - using FTP [42-15](#)
  - using RCP [42-18](#)
  - using TFTP [42-12](#)

image files

- preparing [42-26, 42-29, 42-33](#)
- reasons for [42-24](#)
- using FTP [42-32](#)
- using RCP [42-36](#)
- using TFTP [42-28](#)

user EXEC mode [2-2](#)

username-based authentication [11-7](#)

## V

version-dependent transparent mode [15-4](#)

version-mismatch (VM) mode

- automatic upgrades with auto-upgrade [9-10](#)
- manual upgrades with auto-advise [9-10](#)
- upgrades with auto-extract [9-10](#)

version-mismatch mode

- described [9-9](#)

virtual IP address

- cluster standby group [8-10](#)
- command switch [8-10](#)

virtual switches and PAgP [39-4](#)

vlan.dat file [14-4](#)

VLAN 1, disabling on a trunk port [14-17](#)

VLAN 1 minimization [14-17](#)

vlan-assignment response, VMPS [14-24](#)

VLAN configuration

- at bootup [14-7](#)
  - saving [14-7](#)
- VLAN configuration mode [2-2](#)
- VLAN database
  - and startup configuration file [14-7](#)
  - and VTP [15-1](#)
  - VLAN configuration saved in [14-6](#)
  - VLANs saved in [14-4](#)
- VLAN filtering and SPAN [28-6](#)
- vlan global configuration command [14-6](#)
- VLAN ID, discovering [5-24](#)
- VLAN load balancing on flex links [20-2](#)
  - configuration guidelines [20-8](#)
- VLAN management domain [15-2](#)
- VLAN Management Policy Server
  - See VMPS
- VLAN membership
  - confirming [14-27](#)
  - modes [14-3](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [14-8](#)
  - adding to VLAN database [14-8](#)
  - aging dynamic addresses [17-9](#)
  - allowed on trunk [14-17](#)
  - and spanning-tree instances [14-3, 14-6, 14-12](#)
  - configuration guidelines, extended-range VLANs [14-11](#)
  - configuration guidelines, normal-range VLANs [14-6](#)
  - configuring [14-1](#)
  - configuring IDs 1006 to 4094 [14-11](#)
  - connecting through SVIs [13-6](#)
  - creating [14-9](#)
  - default configuration [14-8](#)
  - deleting [14-9](#)
  - described [13-1, 14-1](#)
  - displaying [14-13](#)
  - extended-range [14-1, 14-11](#)
  - features [1-7](#)
  - illustrated [14-2](#)
  - limiting source traffic with RSPAN [28-20](#)
  - limiting source traffic with SPAN [28-14](#)
  - modifying [14-8](#)
  - multicast [23-17](#)
  - native, configuring [14-19](#)
  - normal-range [14-1, 14-4](#)
  - parameters [14-5](#)
  - port membership modes [14-3](#)
  - static-access ports [14-10](#)
  - STP and IEEE 802.1Q trunks [17-10](#)
  - supported [14-3](#)
  - Token Ring [14-5](#)
  - traffic between [14-2](#)
  - VTP modes [15-3](#)
- VLAN Trunking Protocol
  - See VTP
- VLAN trunks [14-14](#)
- VMPS
  - administering [14-28](#)
  - configuration example [14-29](#)
  - configuration guidelines [14-25](#)
  - default configuration [14-25](#)
  - description [14-23](#)
  - dynamic port membership
    - described [14-24](#)
    - reconfirming [14-27](#)
    - troubleshooting [14-29](#)
  - entering server address [14-26](#)
  - mapping MAC addresses to VLANs [14-24](#)
  - monitoring [14-28](#)
  - reconfirmation interval, changing [14-27](#)
  - reconfirming membership [14-27](#)
  - retry count, changing [14-28](#)
- voice aware 802.1x security
  - port-based authentication
    - configuring [12-39](#)
    - described [12-31, 12-39](#)

- voice-over-IP [16-1](#)
  - voice VLAN
    - Cisco 7960 phone, port connections [16-1](#)
    - configuration guidelines [16-3](#)
    - configuring IP phones for data traffic
      - override CoS of incoming frame [16-6](#)
      - trust CoS priority of incoming frame [16-6](#)
    - configuring ports for voice traffic in
      - 802.1p priority tagged frames [16-5](#)
      - 802.1Q frames [16-4](#)
    - connecting to an IP phone [16-4](#)
    - default configuration [16-3](#)
    - described [16-1](#)
    - displaying [16-6](#)
    - IP phone data traffic, described [16-2](#)
    - IP phone voice traffic, described [16-2](#)
  - VQP [1-7, 14-23](#)
  - VTP
    - adding a client to a domain [15-15](#)
    - advertisements [14-15, 15-3](#)
    - and extended-range VLANs [14-3, 15-1](#)
    - and normal-range VLANs [14-3, 15-1](#)
    - client mode, configuring [15-11](#)
    - configuration
      - guidelines [15-8](#)
      - requirements [15-10](#)
      - saving [15-8](#)
    - configuration requirements [15-10](#)
    - configuration revision number
      - guideline [15-15](#)
      - resetting [15-16](#)
    - consistency checks [15-4](#)
    - default configuration [15-7](#)
    - described [15-1](#)
    - domain names [15-8](#)
    - domains [15-2](#)
    - modes
      - client [15-3](#)
      - off [15-3](#)
      - server [15-3](#)
      - transitions [15-3](#)
      - transparent [15-3](#)
    - monitoring [15-16](#)
    - passwords [15-8](#)
    - pruning
      - disabling [15-14](#)
      - enabling [15-14](#)
      - examples [15-6](#)
      - overview [15-5](#)
      - support for [1-7](#)
    - pruning-eligible list, changing [14-19](#)
    - server mode, configuring [15-10, 15-13](#)
    - statistics [15-16](#)
    - support for [1-7](#)
    - Token Ring support [15-4](#)
    - transparent mode, configuring [15-10](#)
    - using [15-1](#)
    - Version
      - enabling [15-13](#)
    - version, guidelines [15-9](#)
    - Version 1 [15-4](#)
    - Version 2
      - configuration guidelines [15-9](#)
      - overview [15-4](#)
    - Version 3
      - overview [15-4](#)
- 
- ## W
- web authentication [12-17](#)
    - configuring [6-16 to ??](#)
    - described [1-7](#)
  - web-based authentication
    - customizeable web pages [6-6](#)
    - description [6-1](#)
  - web-based authentication, interactions with other features [6-7](#)
  - weighted tail drop



See WTD

wired location service

- configuring [27-9](#)

- displaying [27-11](#)

- location TLV [27-3](#)

- understanding [27-3](#)

wizards [1-2](#)

WTD

- described [34-11](#)

- setting thresholds

  - egress queue-sets [34-67](#)

  - ingress queues [34-62](#)

- support for [1-10, 1-11](#)

---

## **X**

Xmodem protocol [40-2](#)