

Configuring Internal Power Supplies

- Information About Internal Power Supplies, page 1
- How to Configure Internal Power Supplies, page 1
- Monitoring Internal Power Supplies, page 2
- Configuration Examples for Internal Power Supplies, page 2
- Additional References, page 3
- Feature History and Information for Internal Power Supplies, page 4

Information About Internal Power Supplies

See the switch installation guide for information about the power supplies.

How to Configure Internal Power Supplies

Configuring Internal Power Supply

You can use the **power supply** EXEC command to configure and manage the internal power supply on the switch. The switch does not support the **no power supply** EXEC command.

Follow these steps beginning in user EXEC mode:

Procedure

	Command or Action	Purpose	
Step 1	<pre>power supply switch_number slot{A B} { off on }</pre>	Sets the specified power supply to off or on by using one of these keywords:	
	Example: Switch# power supply 1 slot A on	 A —Selects the power supply in slot A. B —Selects power supply in slot B. 	

	Command or Action	Purpose	
		Note Power supply slot B is the closest to the outer edge of the switch.	
		• off —Set the power supply off.	
		• on —Set the power supply on.	
		By default, the switch power supply is on .	
Step 2	show environment power	Verifies your settings.	
	Example:		
	Switch# show environment power		

Monitoring Internal Power Supplies

Table 1: Show Commands for Power Supplies

Command	Purpose
show environment power [all switch switch_number]	(Optional) Displays the status of the internal power supplies for each switch in the stack or for the specified switch. The range is 1 to 9, depending on the switch member numbers in the stack. The switch keywords are available only on stacking-capable switches.

Configuration Examples for Internal Power Supplies

This example shows how to set the power supply in slot A to off:

```
Switch# power supply 1 slot A off
Disabling Power supply A may result in a power loss to PoE devices and/or switches ...
Continue? (yes/[no]): yes
Switch#
Jun 10 04:52:54.389: %PLATFORM_ENV-6-FRU_PS_OIR: FRU Power Supply 1 powered off
Jun 10 04:52:56.717: %PLATFORM_ENV-1-FAN_NOT_PRESENT: Fan is not present
Switch#
```

This example shows how to set the power supply in slot A to on:

```
Switch# power supply 1 slot A on Jun 10 04:54:39.600: %PLATFORM_ENV-6-FRU_PS_OIR: FRU Power Supply 1 powered on
```

This example shows the output of the **show env power** command:

Table 2: show env power Status Descriptions

Field	Description
ОК	The power supply is present and power is good.
Not Present	No power supply is installed.
No Input Power	The power supply is present but there is no input power.
Disabled	The power supply and input power are present, but power supply is switched off by CLI.
Not Responding	The power supply is not recognizable or is faulty.
Failure-Fan	The power supply fan is faulty.

Additional References

Error Message Decoder

Description	Link
To help you research and resolve system error messages in this release, use the Error Message Decoder tool.	https://www.cisco.com/cgi-bin/Support/Errordecoder/index.cgi

MIBs

MIB	MIBs Link
All supported MIBs for this release.	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

Technical Assistance

Description	Link
The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.	http://www.cisco.com/support
To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.	
Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.	

Feature History and Information for Internal Power Supplies

Release	Modification
Cisco IOS 15.0(2)EX1	This feature was introduced.