



---

## A

aaa accounting dot1x command [2-1](#)  
aaa authentication dot1x command [2-3](#)  
aaa authorization network command [2-5](#)  
AAA methods [2-3](#)  
abort command [2-723](#)  
access control entries  
    See ACEs  
access control lists  
    See ACLs  
access groups  
    IP [2-141](#)  
    MAC, displaying [2-498](#)  
access list, IPv6 [2-205](#)  
access map configuration mode [2-260](#)  
access mode [2-667](#)  
access ports [2-667](#)  
ACEs [2-83](#), [2-330](#)  
ACLs  
    deny [2-81](#)  
    displaying [2-379](#)  
    for non-IP protocols [2-240](#)  
    IP [2-141](#)  
    matching [2-260](#)  
    on Layer 2 interfaces [2-141](#)  
    permit [2-328](#)  
action command [2-6](#)  
address aliasing [2-310](#)  
aggregate-port learner [2-316](#)  
allowed VLANs [2-686](#)  
apply command [2-723](#)  
archive download-sw command [2-8](#)

archive tar command [2-11](#)  
archive upload-sw command [2-14](#)  
arp access-list command [2-16](#)  
audience [xix](#)  
authentication failed VLAN  
    See dot1x auth-fail vlan  
auth-fail max-attempts  
    See dot1x auth-fail max-attempts  
auth-fail vlan  
    See dot1x auth-fail vlan  
authorization state of controlled port [2-115](#)  
autonegotiation of duplex mode [2-124](#)  
auto qos voip command [2-18](#)

---

## B

BackboneFast, for STP [2-601](#)  
backup interfaces  
    configuring [2-662](#)  
    displaying [2-441](#)  
boot (boot loader) command [A-2](#)  
boot auto-download-sw command [2-23](#)  
boot boothlpr command [2-24](#)  
boot config-file command [2-25](#)  
boot enable-break command [2-26](#)  
boot helper command [2-27](#)  
boot helper-config file command [2-28](#)  
booting  
    Cisco IOS image [2-31](#)  
    displaying environment variables [2-388](#)  
    interrupting [2-23](#), [2-26](#)  
    manually [2-29](#)

boot loader

- accessing [A-1](#)
- booting
  - Cisco IOS image [A-2](#)
  - helper image [2-27](#)
- directories
  - creating [A-15](#)
  - displaying a list of [A-7](#)
  - removing [A-19](#)
- displaying
  - available commands [A-12](#)
  - memory heap utilization [A-14](#)
  - version [A-26](#)
- environment variables
  - described [A-20](#)
  - displaying settings [A-20](#)
  - location of [A-21](#)
  - setting [A-20](#)
  - unsetting [A-24](#)
- files
  - copying [A-5](#)
  - deleting [A-6](#)
  - displaying a list of [A-7](#)
  - displaying the contents of [A-4, A-16, A-23](#)
  - renaming [A-17](#)
- file system
  - formatting [A-10](#)
  - initializing flash [A-9](#)
  - running a consistency check [A-11](#)
- loading helper images [A-13](#)
- prompt [A-1](#)
- resetting the system [A-18](#)

boot manual command [2-29](#)

boot private-config-file command [2-30](#)

boot system command [2-31](#)

BPDU filtering, for spanning tree [2-602, 2-636](#)

BPDU guard, for spanning tree [2-604, 2-636](#)

broadcast storm control [2-655](#)

---

## C

candidate switches

- See clusters

cat (boot loader) command [A-4](#)

caution, description [xx](#)

CDP, enabling protocol tunneling for [2-223](#)

channel-group command [2-32](#)

channel-protocol command [2-35](#)

Cisco Network Assistant

- See Network Assistant [xx](#)

Cisco SoftPhone

- auto-QoS configuration [2-18](#)
- trusting packets sent from [2-302](#)

class command [2-36](#)

class-map command [2-38](#)

class maps

- creating [2-38](#)
- defining the match criteria [2-262](#)
- displaying [2-392](#)

class of service

- See CoS

clear dot1x command [2-40](#)

clear eap sessions command [2-41](#)

clear ip arp inspection log command [2-42](#)

clear ip arp inspection statistics command [2-43](#)

clear ipc command [2-45](#)

clear ip dhcp snooping database command [2-44](#)

clear l2protocol-tunnel counters command [2-46](#)

clear lacp command [2-47](#)

clear mac address-table command [2-48, 2-50](#)

clear pagp command [2-51](#)

clear port-security command [2-52](#)

clear spanning-tree counters command [2-54](#)

clear spanning-tree detected-protocols command [2-55](#)

clear vmps statistics command [2-56](#)

clear vtp counters command [2-57](#)

cluster commander-address command [2-58](#)

cluster discovery hop-count command [2-60](#)

- cluster enable command [2-61](#)
- cluster holdtime command [2-63](#)
- cluster member command [2-64](#)
- cluster outside-interface command [2-66](#)
- cluster requirements [xx](#)
- cluster run command [2-67](#)
- clusters
  - adding candidates [2-64](#)
  - binding to HSRP group [2-68](#)
  - building manually [2-64](#)
  - communicating with
    - devices outside the cluster [2-66](#)
    - members by using Telnet [2-357](#)
  - debug messages, display [B-5](#)
  - displaying
    - candidate switches [2-395](#)
    - debug messages [B-5](#)
    - member switches [2-397](#)
    - status [2-393](#)
  - hop-count limit for extended discovery [2-60](#)
  - HSRP standby groups [2-68](#)
  - redundancy [2-68](#)
  - SNMP trap [2-591](#)
- cluster standby-group command [2-68](#)
- cluster timer command [2-70](#)
- command modes defined [1-1](#)
- commands changed in Cisco IOS Release 12.2(20)SE [1-5](#)
- command switch
  - See clusters
- configuration, initial
  - See getting started guide and hardware installation guide
- configuration files
  - password recovery disable considerations [A-1](#)
  - specifying the name [2-25, 2-30](#)
- configuring multiple interfaces [2-137](#)

- config-vlan mode
  - commands [2-709](#)
  - description [1-4](#)
  - entering [2-708](#)
  - summary [1-2](#)
- conventions
  - command [xx](#)
  - for examples [xx](#)
  - publication [xx](#)
  - text [xx](#)
- copy (boot loader) command [A-5](#)
- CoS
  - assigning default value to incoming packets [2-272](#)
  - assigning to Layer 2 protocol packets [2-226](#)
  - overriding the incoming value [2-272](#)
- CoS-to-DSCP map [2-276](#)
- CPU ASIC statistics, displaying [2-399](#)
- crashinfo files [2-130](#)

---

## D

- debug auto qos command [B-2](#)
- debug backup command [B-4](#)
- debug cluster command [B-5](#)
- debug dot1x command [B-7](#)
- debug dtp command [B-8](#)
- debug eap command [B-9](#)
- debug etherchannel command [B-10](#)
- debug ilpower command [B-11](#)
- debug interface command [B-14](#)
- debug ip dhcp snooping command [B-12](#)
- debug ip igmp filter command [B-15](#)
- debug ip igmp max-groups command [B-16](#)
- debug ip igmp snooping command [B-17](#)
- debug ip verify source packet command [B-13](#)
- debug lacp command [B-18](#)
- debug mac-notification command [B-19](#)
- debug matm command [B-20](#)
- debug matm move update command [B-21](#)

- debug monitor command [B-22](#)
- debug mvrdbg command [B-23](#)
- debug nvram command [B-24](#)
- debug pagp command [B-25](#)
- debug platform acl command [B-26](#)
- debug platform backup interface command [B-27](#)
- debug platform configuration command [B-35](#)
- debug platform cpu-queues command [B-28](#)
- debug platform device-manager command [B-30](#)
- debug platform dot1x command [B-31](#)
- debug platform etherchannel command [B-32](#)
- debug platform fallback-bridging command [B-33](#)
- debug platform forw-tcam command [B-34](#)
- debug platform ip arp inspection command [B-37](#)
- debug platform ip dhcp command [B-38](#)
- debug platform ip igmp snooping command [B-39](#)
- debug platform ip multicast command [B-41](#)
- debug platform ip unicast command [B-43](#)
- debug platform led command [B-45](#)
- debug platform matm command [B-46](#)
- debug platform messaging application command [B-47](#)
- debug platform phy command [B-48](#)
- debug platform pm command [B-50](#)
- debug platform port-asic command [B-52](#)
- debug platform port-security command [B-53](#)
- debug platform qos-acl-tcam command [B-54](#)
- debug platform remote-commands command [B-55](#)
- debug platform resource-manager command [B-56](#)
- debug platform snmp command [B-57](#)
- debug platform span command [B-58](#)
- debug platform supervisor-asic command [B-59](#)
- debug platform sw-bridge command [B-60](#)
- debug platform tcam command [B-61](#)
- debug platform udd command [B-64](#)
- debug platform vlan command [B-65](#)
- debug pm command [B-66](#)
- debug port-security command [B-68](#)
- debug qos-manager command [B-69](#)
- debug spanning-tree backbonefast command [B-72](#)
- debug spanning-tree bpdu command [B-73](#)
- debug spanning-tree bpdu-opt command [B-74](#)
- debug spanning-tree command [B-70](#)
- debug spanning-tree mstp command [B-75](#)
- debug spanning-tree switch command [B-77](#)
- debug spanning-tree uplinkfast command [B-79](#)
- debug sw-vlan command [B-80](#)
- debug sw-vlan ifs command [B-82](#)
- debug sw-vlan notification command [B-83](#)
- debug sw-vlan vtp command [B-85](#)
- debug udd command [B-87](#)
- debug vqpc command [B-89](#)
- define interface-range command [2-71](#)
- delete (boot loader) command [A-6](#)
- delete command [2-73](#)
- deny (ARP access-list configuration) command [2-74](#)
- deny (IPv6) command [2-76](#)
- deny command [2-81](#)
- detect mechanism, causes [2-125](#)
- device manager requirements [xx](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-169](#)
  - enabling
    - on a VLAN [2-176](#)
    - option 82 [2-167, 2-169](#)
    - trust on an interface [2-174](#)
  - error recovery timer [2-127](#)
  - rate limiting [2-173](#)
- DHCP snooping binding database
  - binding file, configuring [2-165](#)
  - bindings
    - adding [2-163](#)
    - deleting [2-163](#)
    - displaying [2-457](#)
  - clearing database agent statistics [2-44](#)
  - database agent, configuring [2-165](#)

**DHCP snooping (continued)**

- displaying
  - binding entries 2-457
  - database agent status 2-459
  - renewing 2-361
- dir (boot loader) command A-7
- directories, deleting 2-73
- documentation, related xx
- document conventions xx
- domain name, VTP 2-733, 2-737
- dot1x auth-fail max-attempts 2-91
- dot1x auth-fail vlan 2-93
- dot1x command 2-89
- dot1x control-direction command 2-95
- dot1x critical global configuration command 2-97
- dot1x critical interface configuration command 2-99
- dot1x default command 2-101
- dot1x fallback command 2-102
- dot1x guest-vlan command 2-103
- dot1x host-mode command 2-106
- dot1x initialize command 2-108
- dot1x mac-auth-bypass command 2-109
- dot1x max-reauth-req command 2-111
- dot1x max-req command 2-112
- dot1x multiple-hosts command 2-113
- dot1x pae command 2-114
- dot1x port-control command 2-115
- dot1x re-authenticate command 2-117
- dot1x re-authentication command 2-118
- dot1x reauthentication command 2-119
- dot1x timeout command 2-120
- dropping packets, with ACL matches 2-6
- drop threshold, Layer 2 protocol tunneling 2-223
- DSCP-to-CoS map 2-276
- DSCP-to-DSCP-mutation map 2-276
- DTP 2-668
- DTP flap
  - error detection for 2-125
  - error recovery timer 2-127
- DTP negotiation 2-672
- dual IPv4 and IPv6 templates 2-322
- dual-purpose uplink ports
  - selecting the type 2-266
- duplex command 2-123
- dynamic-access ports
  - configuring 2-660
  - restrictions 2-661
- dynamic ARP inspection
  - ARP ACLs
    - apply to a VLAN 2-149
    - define 2-16
    - deny packets 2-74
    - display 2-383
    - permit packets 2-320
  - clear
    - log buffer 2-42
    - statistics 2-43
  - display
    - ARP ACLs 2-383
    - configuration and operating state 2-453
    - log buffer 2-453
    - statistics 2-453
    - trust state and rate limit 2-453
  - enable per VLAN 2-159
  - error detection for 2-125
  - error recovery timer 2-127
  - log buffer
    - clear 2-42
    - configure 2-153
    - display 2-453
  - rate-limit incoming ARP packets 2-151
  - statistics
    - clear 2-43
    - display 2-453
  - trusted interface state 2-155
  - type of packet logged 2-160
  - validation checks 2-157
- dynamic auto VLAN membership mode 2-667

dynamic desirable VLAN membership mode [2-667](#)

Dynamic Host Configuration Protocol (DHCP)

See DHCP snooping

Dynamic Trunking Protocol

See DTP

---

## E

EAP-request/identity frame

maximum number to send [2-112](#)

response time before retransmitting [2-120](#)

encapsulation methods [2-686](#)

environment variables, displaying [2-388](#)

errdisable detect cause command [2-125](#)

errdisable recovery command [2-127](#)

error conditions, displaying [2-432](#)

error disable detection [2-125](#)

error-disabled interfaces, displaying [2-441](#)

EtherChannel

assigning Ethernet interface to channel group [2-32](#)

creating port-channel logical interface [2-135](#)

debug EtherChannel/PAgP, display [B-10](#)

debug platform-specific events, display [B-32](#)

displaying [2-436](#)

enabling Layer 2 protocol tunneling for

LACP [2-224](#)

PAgP [2-224](#)

UDLD [2-224](#)

interface information, displaying [2-441](#)

LACP

clearing channel-group information [2-47](#)

debug messages, display [B-18](#)

displaying [2-492](#)

modes [2-32](#)

port priority for hot-standby ports [2-227](#)

restricting a protocol [2-35](#)

system priority [2-229](#)

**LACP (continued)**

load-distribution methods [2-338](#)

PAgP

aggregate-port learner [2-316](#)

clearing channel-group information [2-51](#)

debug messages, display [B-25](#)

displaying [2-541](#)

error detection for [2-125](#)

error recovery timer [2-127](#)

learn method [2-316](#)

modes [2-32](#)

physical-port learner [2-316](#)

priority of interface for transmitted traffic [2-318](#)

Ethernet controller, internal register display [2-401](#)

Ethernet statistics, collecting [2-363](#)

examples, conventions for [xx](#)

exception crashinfo command [2-130](#)

exit command [2-723](#)

extended discovery of candidate switches [2-60](#)

extended-range VLANs

and allowed VLAN list [2-686](#)

and pruning-eligible list [2-686](#)

configuring [2-708](#)

extended system ID for STP [2-610](#)

---

## F

fallback profile command [2-131](#)

fan information, displaying [2-428](#)

file name, VTP [2-733](#)

files, deleting [2-73](#)

flash\_init (boot loader) command [A-9](#)

Flex Links

configuring [2-662](#)

displaying [2-441](#)

flowcontrol command [2-133](#)

format (boot loader) command [A-10](#)

forwarding packets, with ACL matches [2-6](#)

forwarding results, display [C-6](#)

frame forwarding information, displaying [C-6](#)  
 front-end controller  
   counter and status information [C-8](#)  
 fsck (boot loader) command [A-11](#)

---

## G

global configuration mode [1-2, 1-3](#)

---

## H

hardware ACL statistics [2-379](#)  
 help (boot loader) command [A-12](#)  
 hierarchical policy maps [2-336](#)  
 hop-count limit for clusters [2-60](#)  
 host connection, port configuration [2-666](#)  
 host ports, private VLANs [2-670](#)  
 Hot Standby Router Protocol  
   See HSRP  
 HSRP  
   binding HSRP group to cluster [2-68](#)  
   standby group [2-68](#)

---

## I

IEEE 802.1Q trunk ports and native VLANs [2-725](#)  
 IEEE 802.1Q tunnel ports  
   configuring [2-667](#)  
   displaying [2-417](#)  
   limitations [2-668](#)  
 IEEE 802.1x  
   and switchport modes [2-668](#)  
   violation error recovery [2-127](#)  
   See also port-based authentication  
 IEEE 802.1X Port Based Authentication  
   enabling guest VLAN supplicant [2-92, 2-102, 2-131](#)

IGMP filters  
   applying [2-179](#)  
   debug messages, display [B-15](#)  
 IGMP groups, setting maximum [2-180](#)  
 IGMP maximum groups, debugging [B-16](#)  
 IGMP profiles  
   creating [2-182](#)  
   displaying [2-461](#)  
 IGMP snooping  
   adding ports as a static member of a group [2-198](#)  
   displaying [2-462, 2-467, 2-469](#)  
   enabling [2-184](#)  
   enabling the configurable-leave timer [2-186](#)  
   enabling the Immediate-Leave feature [2-195](#)  
   flooding query count [2-192](#)  
   interface topology change notification behavior [2-194](#)  
   multicast table [1-5, 2-465](#)  
   querier [2-188](#)  
   query solicitation [2-192](#)  
   report suppression [2-190](#)  
   switch topology change notification behavior [2-192](#)  
 images  
   See software images  
 Immediate-Leave feature, MVR [2-312](#)  
 Immediate-Leave processing  
   IPv6 [2-219](#)  
 immediate-leave processing [2-195](#)  
 initial configuration  
   See getting started guide and hardware installation guide  
 interface configuration mode [1-2, 1-4](#)  
 interface port-channel command [2-135](#)  
 interface range command [2-137](#)  
 interface-range macros [2-71](#)

## interfaces

- assigning Ethernet interface to channel group [2-32](#)
- configuring [2-123](#)
- configuring multiple [2-137](#)
- creating port-channel logical [2-135](#)
- debug messages, display [B-14](#)
- disabling [2-589](#)
- displaying the MAC address table [2-509](#)
- restarting [2-589](#)

interface speed, configuring [2-646](#)

interface vlan command [2-139](#)

internal registers, displaying [2-401, 2-410](#)

## Internet Group Management Protocol

See IGMP

## invalid GBIC

- error detection for [2-125](#)
- error recovery timer [2-127](#)

ip access-group command [2-141](#)

ip address command [2-144](#)

IP addresses, setting [2-144](#)

IP address matching [2-260](#)

ip admission command [2-146](#)

ip admission name proxy http command [2-147](#)

ip arp inspection filter vlan command [2-149](#)

ip arp inspection limit command [2-151](#)

ip arp inspection log-buffer command [2-153](#)

ip arp inspection trust command [2-155](#)

ip arp inspection validate command [2-157](#)

ip arp inspection vlan command [2-159](#)

ip arp inspection vlan logging command [2-160](#)

## IP DHCP snooping

See DHCP snooping

ip dhcp snooping binding command [2-163](#)

ip dhcp snooping command [2-162](#)

ip dhcp snooping database command [2-165](#)

ip dhcp snooping information option allow-untrusted command [2-169](#)

ip dhcp snooping information option command [2-167](#)

ip dhcp snooping information option format remote-id command [2-171](#)

ip dhcp snooping limit rate command [2-173](#)

ip dhcp snooping trust command [2-174](#)

ip dhcp snooping verify command [2-175](#)

ip dhcp snooping vlan command [2-176](#)

ip dhcp snooping vlan information option format-type circuit-id string command [2-177](#)

ip igmp filter command [2-179](#)

ip igmp max-groups command [2-180](#)

ip igmp profile command [2-182](#)

ip igmp snooping command [2-184](#)

ip igmp snooping last-member-query-interval command [2-186](#)

ip igmp snooping querier command [2-188](#)

ip igmp snooping report-suppression command [2-190](#)

ip igmp snooping tcn command [2-192](#)

ip igmp snooping tcn flood command [2-194](#)

ip igmp snooping vlan immediate-leave command [2-195](#)

ip igmp snooping vlan mrouter command [2-196](#)

ip igmp snooping vlan static command [2-198](#)

IP multicast addresses [2-309](#)

## IP phones

auto-QoS configuration [2-18](#)

trusting packets sent from [2-302](#)

IP-precedence-to-DSCP map [2-276](#)

ip source binding command [2-200](#)

## IP source guard

disabling [2-204](#)

displaying

binding entries [2-471](#)

configuration [2-473](#)

dynamic binding entries only [2-457](#)

enabling [2-204](#)

static IP source bindings [2-200](#)

ip ssh command [2-202](#)

## IPv6 access list

deny conditions [2-76](#)

ipv6 access-list command [2-205](#)

ipv6 mld snooping command [2-208](#)



ipv6 mld snooping last-listener-query count  
     command [2-210](#)  
 ipv6 mld snooping last-listener-query-interval  
     command [2-212](#)  
 ipv6 mld snooping listener-message-suppression  
     command [2-214](#)  
 ipv6 mld snooping robustness-variable command [2-215](#)  
 ipv6 mld snooping tcn command [2-217](#)  
 ipv6 mld snooping vlan command [2-219](#)  
 IPv6 SDM template [2-364](#)  
 ipv6 traffic-filter command [2-221](#)  
 ip verify source command [2-204](#)

---

## J

jumbo frames  
     See MTU

---

## L

l2protocol-tunnel command [2-223](#)  
 l2protocol-tunnel cos command [2-226](#)  
 LACP  
     See EtherChannel  
 lacp port-priority command [2-227](#)  
 lacp system-priority command [2-229](#)  
 Layer 2 mode, enabling [2-658](#)  
 Layer 2 protocol ports, displaying [2-489](#)  
 Layer 2 protocol-tunnel  
     error detection for [2-125](#)  
     error recovery timer [2-127](#)  
 Layer 2 protocol tunnel counters [2-46](#)  
 Layer 2 protocol tunneling error recovery [2-224](#)  
 Layer 2 traceroute  
     IP addresses [2-699](#)  
     MAC addresses [2-696](#)  
 Layer 3 mode, enabling [2-658](#)  
 line configuration mode [1-2, 1-5](#)

Link Aggregation Control Protocol  
     See EtherChannel  
 link flap  
     error detection for [2-125](#)  
     error recovery timer [2-127](#)  
 link state group command [2-231](#)  
 link state track command [2-233](#)  
 load\_helper (boot loader) command [A-13](#)  
 load-distribution methods for EtherChannel [2-338](#)  
 logging event command [2-234](#)  
 logging event power-inline-status command [2-235](#)  
 logging file command [2-236](#)  
 logical interface [2-135](#)  
 loopback error  
     detection for [2-125](#)  
     recovery timer [2-127](#)  
 loop guard, for spanning tree [2-611, 2-615](#)

---

## M

mac access-group command [2-238](#)  
 MAC access-groups, displaying [2-498](#)  
 MAC access list configuration mode [2-240](#)  
 mac access-list extended command [2-240](#)  
 MAC access lists [2-81](#)  
 MAC addresses  
     displaying  
         aging time [2-504](#)  
         all [2-502](#)  
         dynamic [2-507](#)  
         MAC address-table move updates [2-511](#)  
         notification settings [2-513](#)  
         number of addresses in a VLAN [2-505](#)  
         per interface [2-509](#)  
         per VLAN [2-517](#)  
         static [2-515](#)  
         static and dynamic entries [2-500](#)

**MAC addresses (continued)**

- dynamic
    - aging time [2-242](#)
    - deleting [2-48](#)
    - displaying [2-507](#)
  - enabling MAC address notification [2-245](#)
  - enabling MAC address-table move update [2-243](#)
  - matching [2-260](#)
  - static
    - adding and removing [2-247](#)
    - displaying [2-515](#)
    - dropping on an interface [2-248](#)
  - tables [2-502](#)
- MAC address notification, debugging [B-19](#)
- mac address-table aging-time [2-238, 2-260](#)
- mac address-table aging-time command [2-242](#)
- mac address-table move update command [2-243](#)
- mac address-table notification command [2-245](#)
- mac address-table static command [2-247](#)
- mac address-table static drop command [2-248](#)
- macro apply command [2-250](#)
- macro description command [2-253](#)
- macro global command [2-254](#)
- macro global description command [2-257](#)
- macro name command [2-258](#)
- macros
  - adding a description [2-253](#)
  - adding a global description [2-257](#)
  - applying [2-254](#)
  - creating [2-258](#)
  - displaying [2-543](#)
  - interface range [2-71, 2-137](#)
  - specifying parameter values [2-254](#)
  - tracing [2-254](#)
- manual
  - audience [xix](#)
  - purpose of [xix](#)

- maps
  - QoS
    - defining [2-276](#)
    - displaying [2-527](#)
  - VLAN
    - creating [2-720](#)
    - defining [2-260](#)
    - displaying [2-579](#)
- match (access-map configuration) command [2-260](#)
- match (class-map configuration) command [2-262](#)
- maximum transmission unit
  - See MTU
- mdix auto command [2-264](#)
- MDL snooping
  - displaying [2-483](#)
- media-type command [2-266](#)
- member switches
  - See clusters
- memory (boot loader) command [A-14](#)
- mkdir (boot loader) command [A-15](#)
- MLD snooping
  - configuring [2-214, 2-215](#)
  - configuring queries [2-210, 2-212](#)
  - configuring topology change notification [2-217](#)
  - displaying [2-481, 2-485, 2-487](#)
  - enabling [2-208](#)
- MLD snooping on a VLAN
  - enabling [2-219](#)
- mls qos aggregate-policer command [2-270](#)
- mls qos command [2-268](#)
- mls qos cos command [2-272](#)
- mls qos dscp-mutation command [2-274](#)
- mls qos map command [2-276](#)
- mls qos queue-set output buffers command [2-280](#)
- mls qos queue-set output threshold command [2-282](#)
- mls qos rewrite ip dscp command [2-284](#)
- mls qos srr-queue input bandwidth command [2-286](#)
- mls qos srr-queue input buffers command [2-288](#)
- mls qos-srr-queue input cos-map command [2-290](#)

- mls qos srr-queue input dscp-map command 2-292
- mls qos srr-queue input priority-queue command 2-294
- mls qos srr-queue input threshold command 2-296
- mls qos-srr-queue output cos-map command 2-298
- mls qos srr-queue output dscp-map command 2-300
- mls qos trust command 2-302
- mls qos vlan-based command 2-304
- mode, MVR 2-309
- Mode button, and password recovery 2-367
- modes, commands 1-1
- monitor session command 2-305
- more (boot loader) command A-16

## MSTP

- displaying 2-558, 2-559, 2-560, 2-561
- interoperability 2-55
- link type 2-613

### MST region

- aborting changes 2-619
- applying changes 2-619
- configuration name 2-619
- configuration revision number 2-619
- current or pending display 2-619
- displaying 2-558, 2-559, 2-560, 2-561
- MST configuration mode 2-619
- VLANs-to-instance mapping 2-619

- path cost 2-621

- protocol mode 2-617

- restart protocol migration process 2-55

### root port

- loop guard 2-611
- preventing from becoming designated 2-611
- restricting which can be root 2-611
- root guard 2-611

## MSTP (continued)

### root switch

- affects of extended system ID 2-610
- hello-time 2-624, 2-632
- interval between BPDU messages 2-625
- interval between hello BPDU messages 2-624, 2-632
- max-age 2-625
- maximum hop count before discarding BPDU 2-626
- port priority for selection of 2-628
- primary or secondary 2-632
- switch priority 2-631

### state changes

- blocking to forwarding state 2-638
- enabling BPDU filtering 2-602, 2-636
- enabling BPDU guard 2-604, 2-636
- enabling Port Fast 2-636, 2-638
- forward-delay time 2-623
- length of listening and learning states 2-623
- rapid transition to forwarding 2-613
- shutting down Port Fast-enabled ports 2-636
- state information display 2-557

## MTU

- configuring size 2-693
- displaying global setting 2-568

## Multicast Listener Discovery

- See MLD

- multicast group address, MVR 2-312

- multicast groups, MVR 2-310

## Multicast Listener Discovery

- See MLD

- multicast router learning method 2-196

## multicast router ports

- IPv6 2-219

- multicast router ports, configuring 2-196

- multicast storm control 2-655

- multicast VLAN, MVR 2-309

## multicast VLAN registration

- See MVR

## Multiple Spanning Tree Protocol

See MSTP

## MVR

- and address aliasing [2-310](#)
- configuring [2-309](#)
- configuring interfaces [2-312, 2-315](#)
- debug messages, display [B-23](#)
- displaying [2-535](#)
- displaying interface information [2-537](#)
- members, displaying [2-539](#)
- mvr (global configuration) command [2-309](#)
- mvr (interface configuration) command [2-312, 2-315](#)
- mvr vlan group command [2-313](#)

## N

- native VLANs [2-686](#)
- native VLAN tagging [2-725](#)
- Network Assistant requirements [xx](#)
- nonegotiate
  - DTP messaging [2-672](#)
- nonegotiate, speed [2-646](#)
- non-IP protocols
  - denying [2-81](#)
  - forwarding [2-328](#)
- non-IP traffic access lists [2-240](#)
- non-IP traffic forwarding
  - denying [2-81](#)
  - permitting [2-328](#)
- normal-range VLANs [2-708, 2-714](#)
- note, description [xx](#)
- no vlan command [2-708, 2-718](#)

## O

## online diagnostics

- displaying
  - configured boot-up coverage level [2-414](#)
  - current scheduled tasks [2-414](#)
  - event logs [2-414](#)
  - supported test suites [2-414](#)
  - test ID [2-414](#)
  - test results [2-414](#)
  - test statistics [2-414](#)
- enabling
  - scheduling [2-86](#)
- global configuration mode
  - clearing test-based testing schedule [2-86](#)
  - setting test-based testing [2-86](#)
  - setting up test-based testing [2-86](#)
- removing
  - scheduling [2-86](#)
- scheduled switchover
  - disabling [2-86](#)
  - enabling [2-86](#)
- setting
  - test interval [2-86](#)

## P

## PAgP

See EtherChannel

- pagp learn-method command [2-316](#)
- pagp port-priority command [2-318](#)
- password, VTP [2-733, 2-737](#)
- password-recovery mechanism, enabling and disabling [2-367](#)
- permit (ARP access-list configuration) command [2-320](#)
- permit (IPv6) command [2-322](#)
- permit (MAC access-list configuration) command [2-328](#)
- per-VLAN spanning-tree plus
  - See STP

- physical-port learner [2-316](#)
- PID, displaying [2-452](#)
- PIM-DVMRP, as multicast router learning method [2-196](#)
- PoE
  - configuring the power budget [2-343](#)
  - configuring the power management mode [2-340](#)
  - displaying controller register values [2-408](#)
  - displaying power management information [2-551](#)
  - logging of status [2-235](#)
- police aggregate command [2-333](#)
- police command [2-331](#)
- policed-DSCP map [2-276](#)
- policy-map command [2-335](#)
- policy maps
  - applying to an interface [2-369, 2-374](#)
  - creating [2-335](#)
  - displaying [2-546](#)
  - hierarchical [2-336](#)
  - policers
    - displaying [2-520](#)
    - for a single class [2-331](#)
    - for multiple classes [2-270, 2-333](#)
    - policed-DSCP map [2-276](#)
  - traffic classification
    - defining the class [2-36](#)
    - defining trust states [2-701](#)
    - setting DSCP or IP precedence values [2-372](#)
- Port Aggregation Protocol
  - See EtherChannel
- port-based authentication
  - AAA method list [2-3](#)
  - debug messages, display [B-7](#)
  - enabling IEEE 802.1x
    - globally [2-89](#)
    - per interface [2-115](#)
  - guest VLAN [2-103](#)
  - host modes [2-106](#)
  - IEEE 802.1x AAA accounting methods [2-1](#)
  - initialize an interface [2-108](#)
  - port-based authentication (continued)**
    - MAC authentication bypass [2-109](#)
    - manual control of authorization state [2-115](#)
    - PAE as authenticator [2-114](#)
    - periodic re-authentication
      - enabling [2-119](#)
      - time between attempts [2-120](#)
    - quiet period between failed authentication exchanges [2-120](#)
    - re-authenticating IEEE 802.1x-enabled ports [2-117](#)
    - resetting configurable IEEE 802.1x parameters [2-101](#)
    - switch-to-authentication server retransmission time [2-120](#)
    - switch-to-client frame-retransmission number [2-111 to 2-112](#)
    - switch-to-client retransmission time [2-120](#)
  - port-channel load-balance command [2-338](#)
  - Port Fast, for spanning tree [2-638](#)
  - port ranges, defining [2-71](#)
  - ports, debugging [B-66](#)
  - ports, protected [2-685](#)
  - port security
    - aging [2-679](#)
    - debug messages, display [B-68](#)
    - enabling [2-674](#)
    - violation error recovery [2-127](#)
  - port trust states for QoS [2-302](#)
  - port types, MVR [2-312](#)
  - power information, displaying [2-428](#)
  - power inline command [2-340](#)
  - power inline consumption command [2-343](#)
  - Power over Ethernet
    - See PoE
  - priority-queue command [2-345](#)
  - private-vlan command [2-347](#)
  - private-vlan mapping command [2-350](#)

## private VLANs

- association [2-683](#)
- configuring [2-347](#)
- configuring ports [2-670](#)
- displaying [2-574](#)
- host ports [2-670](#)
- mapping
  - configuring [2-683](#)
  - displaying [2-441](#)
- promiscuous ports [2-670](#)

privileged EXEC mode [1-2, 1-3](#)product identification information, displaying [2-452](#)promiscuous ports, private VLANs [2-670](#)protected ports, displaying [2-447](#)

## pruning

VLANs [2-686](#)

## VTP

- displaying interface information [2-441](#)
- enabling [2-733, 2-737](#)

pruning-eligible VLAN list [2-688](#)

## PVST+

See STP

---

**Q**

## QoS

## auto-QoS

- configuring [2-18](#)
- debug messages, display [1-5, B-2](#)
- displaying [2-384](#)

## class maps

- creating [2-38](#)
- defining the match criteria [2-262](#)
- displaying [2-392](#)

defining the CoS value for an incoming packet [2-272](#)displaying configuration information [2-384, 2-519](#)DSCP transparency [2-284](#)**QoS (continued)**

## DSCP trusted ports

- applying DSCP-to-DSCP-mutation map to [2-274](#)
- defining DSCP-to-DSCP-mutation map [2-276](#)

## egress queues

- allocating buffers [2-280](#)
- defining the CoS output queue threshold map [2-298](#)
- defining the DSCP output queue threshold map [2-300](#)
- displaying buffer allocations [2-523](#)
- displaying CoS output queue threshold map [2-527](#)
- displaying DSCP output queue threshold map [2-527](#)
- displaying queueing strategy [2-523](#)
- displaying queue-set settings [2-530](#)
- enabling bandwidth shaping and scheduling [2-650](#)
- enabling bandwidth sharing and scheduling [2-652](#)
- limiting the maximum output on a port [2-648](#)
- mapping a port to a queue-set [2-352](#)
- mapping CoS values to a queue and threshold [2-298](#)
- mapping DSCP values to a queue and threshold [2-300](#)
- setting maximum and reserved memory allocations [2-282](#)
- setting WTD thresholds [2-282](#)

enabling [2-268](#)

## ingress queues

- allocating buffers [2-288](#)
- assigning SRR scheduling weights [2-286](#)
- defining the CoS input queue threshold map [2-290](#)
- defining the DSCP input queue threshold map [2-292](#)
- displaying buffer allocations [2-523](#)
- displaying CoS input queue threshold map [2-527](#)
- displaying DSCP input queue threshold map [2-527](#)
- displaying queueing strategy [2-523](#)
- displaying settings for [2-521](#)
- enabling the priority queue [2-294](#)
- mapping CoS values to a queue and threshold [2-290](#)
- mapping DSCP values to a queue and threshold [2-292](#)
- setting WTD thresholds [2-296](#)

**QoS (continued)**

- maps
  - defining [2-276, 2-290, 2-292, 2-298, 2-300](#)
  - displaying [2-527](#)
- policy maps
  - applying an aggregate policer [2-333](#)
  - applying to an interface [2-369, 2-374](#)
  - creating [2-335](#)
  - defining policers [2-270, 2-331](#)
  - displaying policers [2-520](#)
  - displaying policy maps [2-546](#)
  - hierarchical [2-336](#)
  - policed-DSCP map [2-276](#)
  - setting DSCP or IP precedence values [2-372](#)
  - traffic classifications [2-36](#)
  - trust states [2-701](#)
- port trust states [2-302](#)
- queues, enabling the expedite [2-345](#)
- statistics
  - in-profile and out-of-profile packets [2-523](#)
  - packets enqueued or dropped [2-523](#)
  - sent and received CoS values [2-523](#)
  - sent and received DSCP values [2-523](#)
- trusted boundary for IP phones [2-302](#)
- VLAN-based [2-304](#)
- quality of service
  - See QoS
- querytime, MVR [2-309](#)
- queue-set command [2-352](#)

---

**R**

- radius-server dead-criteria command [2-353](#)
- radius-server host command [2-355](#)
- rapid per-VLAN spanning-tree plus
  - See STP
- rapid PVST+
  - See STP
- rcommand command [2-357](#)

- re-authenticating IEEE 802.1x-enabled ports [2-117](#)
- re-authentication
  - periodic [2-119](#)
  - time between attempts [2-120](#)
- receiver ports, MVR [2-312](#)
- receiving flow-control packets [2-133](#)
- recovery mechanism
  - causes [2-127](#)
  - display [2-390, 2-430, 2-434](#)
  - timer interval [2-128](#)
- redundancy for cluster switches [2-68](#)
- remote-span command [2-359](#)
- Remote Switched Port Analyzer
  - See RSPAN
- rename (boot loader) command [A-17](#)
- renew ip dhcp snooping database command [2-361](#)
- requirements
  - cluster **xx**
  - device manager **xx**
  - Network Assistant **xx**
- reset (boot loader) command [A-18](#)
- reset command [2-723](#)
- resource templates, displaying [2-553](#)
- restricted VLAN
  - See dot1x auth-fail vlan
- rmdir (boot loader) command [A-19](#)
- rmon collection stats command [2-363](#)
- root guard, for spanning tree [2-611](#)
- routed ports
  - IP addresses on [2-145](#)
  - number supported [2-145](#)
- RSPAN
  - configuring [2-305](#)
  - displaying [2-533](#)
  - filter RSPAN traffic [2-305](#)
  - remote-span command [2-359](#)

**RSPAN (continued)**

## sessions

- add interfaces to [2-305](#)
- displaying [2-533](#)
- start new [2-305](#)

**S**

## scheduled switchover

- disabling [2-86](#)
- enabling [2-86](#)

sdm prefer command [2-364](#)

## SDM templates

- allowed resources [2-365](#)
- displaying [2-553](#)
- dual IPv4 and IPv6 [2-364](#)

secure ports, limitations [2-676](#)sending flow-control packets [2-133](#)service password-recovery command [2-367](#)service-policy command [2-369](#)set (boot loader) command [A-20](#)set command [2-372](#)setup command [2-374](#)setup express command [2-377](#)show access-lists command [2-379](#)show archive status command [2-382](#)show arp access-list command [2-383](#)show auto qos command [2-384](#)show boot command [2-388](#)show cable-diagnostics tdr command [2-390](#)show changes command [2-723](#)show class-map command [2-392](#)show cluster candidates command [2-395](#)show cluster command [2-393](#)show cluster members command [2-397](#)show controllers cpu-interface command [2-399](#)show controllers ethernet-controller command [2-401](#)show controllers power inline command [2-408](#)show controllers team command [2-410](#)show controller utilization command [2-412](#)show current command [2-723](#)show dot1q-tunnel command [2-417](#)show dot1x command [2-418](#)show dtp [2-423](#)show eap command [2-425](#)show env command [2-428](#)show errdisable detect command [2-430](#)show errdisable flap-values command [2-432](#)show errdisable recovery command [2-434](#)show etherchannel command [2-436](#)show flowcontrol command [2-439](#)show interfaces command [2-441](#)show interfaces counters command [2-450](#)show inventory command [2-452](#)show ip arp inspection command [2-453](#)show ipc command [2-475](#)show ip dhcp snooping binding command [2-457](#)show ip dhcp snooping command [2-456](#)show ip dhcp snooping database command [2-459](#)show ip igmp profile command [2-461](#)show ip igmp snooping address command [2-483](#)show ip igmp snooping command [2-462, 2-481](#)show ip igmp snooping groups command [2-465](#)show ip igmp snooping mrouter command [2-467, 2-485](#)show ip igmp snooping querier command [2-469, 2-487](#)show ip source binding command [2-471](#)show ipv6 access-list command [2-479](#)show ip verify source command [2-473](#)show l2protocol-tunnel command [2-489](#)show lacp command [2-492](#)show link state group command [2-496](#)show mac access-group command [2-498](#)show mac address-table address command [2-502](#)show mac address-table aging time command [2-504](#)show mac address-table command [2-500](#)show mac address-table count command [2-505](#)show mac address-table dynamic command [2-507](#)show mac address-table interface command [2-509](#)



- show mac address-table move update command [2-511](#)
- show mac address-table notification command [2-50,2-513, B-21](#)
- show mac address-table static command [2-515](#)
- show mac address-table vlan command [2-517](#)
- show mls qos aggregate-policer command [2-520](#)
- show mls qos command [2-519](#)
- show mls qos input-queue command [2-521](#)
- show mls qos interface command [2-523](#)
- show mls qos maps command [2-527](#)
- show mls qos queue-set command [2-530](#)
- show mls qos vlan command [2-532](#)
- show monitor command [2-533](#)
- show mvr command [2-535](#)
- show mvr interface command [2-537](#)
- show mvr members command [2-539](#)
- show pagp command [2-541](#)
- show parser macro command [2-543](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform etherchannel command [C-5](#)
- show platform forward command [C-6](#)
- show platform frontend-controller command [C-8](#)
- show platform igmp snooping command [C-9](#)
- show platform ip multicast command [C-11](#)
- show platform ip unicast command [C-12](#)
- show platform ipv6 unicast command [C-16](#)
- show platform layer4op command [C-18](#)
- show platform mac-address-table command [C-19](#)
- show platform messaging command [C-20](#)
- show platform monitor command [C-21](#)
- show platform mvr table command [C-22](#)
- show platform pm command [C-23](#)
- show platform port-asic command [C-24](#)
- show platform port-security command [C-28](#)
- show platform qos command [C-29](#)
- show platform resource-manager command [C-30](#)
- show platform snmp counters command [C-32](#)
- show platform spanning-tree command [C-33](#)
- show platform stp-instance command [C-34](#)
- show platform tcam command [C-35](#)
- show platform vlan command [C-38](#)
- show policy-map command [2-546](#)
- show port security command [2-548](#)
- show power inline command [2-551](#)
- show proposed command [2-723](#)
- show sdm prefer command [2-553](#)
- show setup express command [2-556](#)
- show spanning-tree command [2-557](#)
- show storm-control command [2-566](#)
- show system mtu command [2-568](#)
- show trust command [2-701](#)
- show udd command [2-569](#)
- show version command [2-572](#)
- show vlan access-map command [2-579](#)
- show vlan command [2-574](#)
- show vlan command, fields [2-576](#)
- show vlan filter command [2-580](#)
- show vmps command [2-581](#)
- show vtp command [2-584](#)
- shutdown command [2-589](#)
- shutdown threshold, Layer 2 protocol tunneling [2-223](#)
- shutdown vlan command [2-590](#)
- Smartports macros
  - See macros
- SNMP host, specifying [2-595](#)
- SNMP informs, enabling the sending of [2-591](#)
- snmp-server enable traps command [2-591](#)
- snmp-server host command [2-595](#)
- snmp trap mac-notification command [2-599](#)
- SNMP traps
  - enabling MAC address notification trap [2-599](#)
  - enabling the MAC address notification feature [2-245](#)
  - enabling the sending of [2-591](#)
- SoftPhone
  - See Cisco SoftPhone

- software images
  - deleting [2-73](#)
  - downloading [2-8](#)
  - upgrading [2-8](#)
  - uploading [2-14](#)
- software version, displaying [2-572](#)
- source ports, MVR [2-312](#)
- SPAN
  - configuring [2-305](#)
  - debug messages, display [B-22](#)
  - displaying [2-533](#)
  - filter SPAN traffic [2-305](#)
  - sessions
    - add interfaces to [2-305](#)
    - displaying [2-533](#)
    - start new [2-305](#)
- spanning [2-640](#)
- spanning-tree backbonefast command [2-601](#)
- spanning-tree bpdudfilter command [2-602](#)
- spanning-tree bpduguard command [2-604](#)
- spanning-tree cost command [2-606](#)
- spanning-tree etherchannel command [2-608](#)
- spanning-tree extend system-id command [2-610](#)
- spanning-tree guard command [2-611](#)
- spanning-tree link-type command [2-613](#)
- spanning-tree loopguard default command [2-615](#)
- spanning-tree mode command [2-617](#)
- spanning-tree mst configuration command [2-619](#)
- spanning-tree mst cost command [2-621](#)
- spanning-tree mst forward-time command [2-623](#)
- spanning-tree mst hello-time command [2-624](#)
- spanning-tree mst max-age command [2-625](#)
- spanning-tree mst max-hops command [2-626](#)
- spanning-tree mst port-priority command [2-628](#)
- spanning-tree mst pre-standard command [2-630](#)
- spanning-tree mst priority command [2-631](#)
- spanning-tree mst root command [2-632](#)
- spanning-tree portfast (global configuration)
  - command [2-636](#)
- spanning-tree portfast (interface configuration)
  - command [2-638](#)
- spanning-tree port-priority command [2-634](#)
- Spanning Tree Protocol
  - See STP
- spanning-tree transmit hold-count command [2-640](#)
- spanning-tree uplinkfast command [2-641](#)
- spanning-tree vlan command [2-643](#)
- speed command [2-646](#)
- srr-queue bandwidth limit command [2-648](#)
- srr-queue bandwidth shape command [2-650](#)
- srr-queue bandwidth share command [2-652](#)
- SSH, configuring version [2-202](#)
- static-access ports, configuring [2-660](#)
- statistics, Ethernet group [2-363](#)
- sticky learning, enabling [2-674](#)
- storm-control command [2-655](#)
- STP
  - BackboneFast [2-601](#)
  - counters, clearing [2-54](#)
  - debug messages, display
    - BackboneFast events [B-72](#)
    - MSTP [B-75](#)
    - optimized BPDUs handling [B-74](#)
    - spanning-tree activity [B-70](#)
    - switch shim [B-77](#)
    - transmitted and received BPDUs [B-73](#)
    - UplinkFast [B-79](#)
  - detection of indirect link failures [2-601](#)
  - enabling protocol tunneling for [2-223](#)
  - EtherChannel misconfiguration [2-608](#)
  - extended system ID [2-610](#)
  - path cost [2-606](#)
  - protocol modes [2-617](#)

**STP (continued)**

- root port
  - accelerating choice of new [2-641](#)
  - loop guard [2-611](#)
  - preventing from becoming designated [2-611](#)
  - restricting which can be root [2-611](#)
  - root guard [2-611](#)
  - UplinkFast [2-641](#)
- root switch
  - affects of extended system ID [2-610, 2-644](#)
  - hello-time [2-643](#)
  - interval between BPDU messages [2-643](#)
  - interval between hello BPDU messages [2-643](#)
  - max-age [2-643](#)
  - port priority for selection of [2-634](#)
  - primary or secondary [2-643](#)
  - switch priority [2-643](#)
- state changes
  - blocking to forwarding state [2-638](#)
  - enabling BPDU filtering [2-602, 2-636](#)
  - enabling BPDU guard [2-604, 2-636](#)
  - enabling Port Fast [2-636, 2-638](#)
  - enabling timer to recover from error state [2-127](#)
  - forward-delay time [2-643](#)
  - length of listening and learning states [2-643](#)
  - shutting down Port Fast-enabled ports [2-636](#)
- state information display [2-557](#)
- VLAN options [2-631, 2-643](#)
- SVIs, creating [2-139](#)
- Switched Port Analyzer
  - See SPAN
- switching characteristics
  - modifying [2-658](#)
  - returning to interfaces [2-658](#)
- switchport access command [2-660](#)
- switchport backup interface command [2-662](#)
- switchport block command [2-665](#)
- switchport command [2-658](#)
- switchport host command [2-666](#)

- switchport mode command [2-667](#)
- switchport mode private-vlan command [2-670](#)
- switchport nonegotiate command [2-672](#)
- switchport port-security aging command [2-679](#)
- switchport port-security command [2-674](#)
- switchport priority extend command [2-681](#)
- switchport private-vlan command [2-683](#)
- switchport protected command [2-685](#)
- switchports, displaying [2-441](#)
- switchport trunk command [2-686](#)
- switchport voice vlan command [2-689](#)
- system env temperature threshold yellow command [2-691](#)
- system message logging [2-235](#)
- system message logging, save message to flash [2-236](#)
- system mtu command [2-693](#)
- system resource templates [2-364](#)

---

**T**

- tar files, creating, listing, and extracting [2-11](#)
- TDR, running [2-695](#)
- Telnet, using to communicate to cluster switches [2-357](#)
- temperature information, displaying [2-428](#)
- templates, system resources [2-364](#)
- test cable-diagnostics tdr command [2-695](#)
- traceroute mac command [2-696](#)
- traceroute mac ip command [2-699](#)
- trunking, VLAN mode [2-667](#)
- trunk mode [2-667](#)
- trunk ports [2-667](#)
- trunks, to non-DTP device [2-668](#)
- trusted boundary for QoS [2-302](#)
- trusted port states for QoS [2-302](#)
- tunnel ports, Layer 2 protocol, displaying [2-489](#)
- type (boot loader) command [A-23](#)

## U

## UDLD

- aggressive mode [2-703, 2-705](#)
- debug messages, display [B-87](#)
- enable globally [2-703](#)
- enable per interface [2-705](#)
- error recovery timer [2-127](#)
- message timer [2-703](#)
- normal mode [2-703, 2-705](#)
- reset a shutdown interface [2-707](#)
- status [2-569](#)
- udld command [2-703](#)
- udld port command [2-705](#)
- udld reset command [2-707](#)
- unicast storm control [2-655](#)
- UniDirectional Link Detection
  - See UDLD
- unknown multicast traffic, preventing [2-665](#)
- unknown unicast traffic, preventing [2-665](#)
- unset (boot loader) command [A-24](#)
- upgrading
  - software images [2-8](#)
  - monitoring status of [2-382](#)
- upgrading information
  - See release notes
- UplinkFast, for STP [2-641](#)
- user EXEC mode [1-2, 1-3](#)

## V

- version (boot loader) command [A-26](#)
- VLAN
  - enabling guest VLAN supplicant [2-92, 2-102, 2-131](#)
  - vlan (global configuration) command [2-708](#)
  - vlan (VLAN configuration) command [2-714](#)
  - vlan access-map command [2-720](#)
  - VLAN access map configuration mode [2-720](#)
  - VLAN access maps
    - actions [2-6](#)
    - displaying [2-579](#)
  - VLAN-based QoS [2-304](#)
  - VLAN configuration
    - rules [2-711, 2-716](#)
    - saving [2-708, 2-718](#)
  - VLAN configuration mode
    - commands
      - VLAN [2-714](#)
      - VTP [2-737](#)
    - description [1-5](#)
    - entering [2-722](#)
    - summary [1-2](#)
  - vlan database command [2-722](#)
  - vlan dot1q tag native command [2-725](#)
  - vlan filter command [2-726](#)
  - VLAN filters, displaying [2-580](#)
  - VLAN ID range [2-708, 2-714](#)
  - VLAN maps
    - applying [2-726](#)
    - creating [2-720](#)
    - defining [2-260](#)
    - displaying [2-579](#)
  - VLAN Query Protocol
    - See VQP
  - VLANs
    - adding [2-708](#)
    - configuring [2-708, 2-714](#)
    - debug messages, display
      - ISL [B-83](#)
      - VLAN IOS file system error tests [B-82](#)
      - VLAN manager activity [B-80](#)
      - VTP [B-85](#)
    - displaying configurations [2-574](#)
    - extended-range [2-708](#)
    - MAC addresses
      - displaying [2-517](#)
      - number of [2-505](#)
    - media types [2-711, 2-716](#)

**VLANs (continued)**

normal-range [2-708, 2-714](#)

private [2-670](#)

  configuring [2-347](#)

  displaying [2-574](#)

  See also private VLANs

restarting [2-590](#)

saving the configuration [2-708](#)

shutting down [2-590](#)

SNMP traps for VTP [2-593, 2-596](#)

suspending [2-590](#)

variables [2-714](#)

**VLAN Trunking Protocol**

  See VTP

**VMPS**

  configuring servers [2-731](#)

  displaying [2-581](#)

  error recovery timer [2-128](#)

  reconfirming dynamic VLAN assignments [2-728](#)

vmpls reconfirm (global configuration) command [2-729](#)

vmpls reconfirm (privileged EXEC) command [2-728](#)

vmpls retry command [2-730](#)

vmpls server command [2-731](#)

**voice VLAN**

  configuring [2-689](#)

  setting port priority [2-681](#)

**VQP**

  and dynamic-access ports [2-661](#)

  clearing client statistics [2-56](#)

  displaying information [2-581](#)

  per-server retry count [2-730](#)

  reconfirmation interval [2-729](#)

  reconfirming dynamic VLAN assignments [2-728](#)

**VTP**

  changing characteristics [2-733](#)

  clearing pruning counters [2-57](#)

  configuring

    domain name [2-733, 2-737](#)

    file name [2-733](#)

    mode [2-733, 2-737](#)

    password [2-733, 2-737](#)

  counters display fields [2-585](#)

  displaying information [2-584](#)

  enabling

    pruning [2-733, 2-737](#)

    tunneling for [2-223](#)

    Version 2 [2-733, 2-737](#)

  mode [2-733, 2-737](#)

  pruning [2-733, 2-737](#)

  saving the configuration [2-708, 2-718](#)

  statistics [2-584](#)

  status [2-584](#)

  status display fields [2-586](#)

vtp (global configuration) command [2-733](#)

vtp (VLAN configuration) command [2-737](#)

