



INDEX

A

aaa accounting dot1x command [2-1](#)
aaa authentication dot1x command [2-3](#)
aaa authorization network command [2-5](#)
AAA methods [2-3](#)
abort command [2-746](#)
access control entries
 See ACEs
access control lists
 See ACLs
access groups
 IP [2-148](#)
 MAC, displaying [2-520](#)
access list, IPv6 [2-213](#)
access map configuration mode [2-271](#)
access mode [2-689](#)
access ports [2-689](#)
ACEs [2-85](#), [2-340](#)
ACLs
 deny [2-83](#)
 displaying [2-389](#)
 for non-IP protocols [2-251](#)
 IP [2-148](#)
 matching [2-271](#)
 on Layer 2 interfaces [2-148](#)
 permit [2-338](#)
action command [2-6](#)
address aliasing [2-321](#)
aggregate-port learner [2-326](#)
allowed VLANs [2-708](#)
apply command [2-746](#)
archive download-sw command [2-8](#)

archive tar command [2-11](#)
archive upload-sw command [2-14](#)
arp access-list command [2-16](#)
audience [xix](#)
authentication failed VLAN
 See dot1x auth-fail vlan
auth-fail max-attempts
 See dot1x auth-fail max-attempts
auth-fail vlan
 See dot1x auth-fail vlan
authorization state of controlled port [2-117](#)
autonegotiation of duplex mode [2-128](#)
auto qos voip command [2-18](#)

B

BackboneFast, for STP [2-623](#)
backup interfaces
 configuring [2-683](#)
 displaying [2-453](#)
boot (boot loader) command [A-2](#)
boot auto-download-sw command [2-22](#)
boot boothlpr command [2-24](#)
boot config-file command [2-25](#)
boot enable-break command [2-26](#)
boot helper command [2-27](#)
boot helper-config file command [2-28](#)
booting
 Cisco IOS image [2-31](#)
 displaying environment variables [2-398](#)
 interrupting [2-22](#), [2-26](#)
 manually [2-29](#)

boot loader

- accessing [A-1](#)

- booting

- Cisco IOS image [A-2](#)

- helper image [2-27](#)

- directories

- creating [A-14](#)

- displaying a list of [A-7](#)

- removing [A-18](#)

- displaying

- available commands [A-12](#)

- memory heap utilization [A-13](#)

- version [A-25](#)

- environment variables

- described [A-19](#)

- displaying settings [A-19](#)

- location of [A-20](#)

- setting [A-19](#)

- unsetting [A-23](#)

- files

- copying [A-5](#)

- deleting [A-6](#)

- displaying a list of [A-7](#)

- displaying the contents of [A-4, A-15, A-22](#)

- renaming [A-16](#)

- file system

- formatting [A-10](#)

- initializing flash [A-9](#)

- running a consistency check [A-11](#)

- prompt [A-1](#)

- resetting the system [A-17](#)

- boot manual command [2-29](#)

- boot private-config-file command [2-30](#)

- boot system command [2-31](#)

- BPDU filtering, for spanning tree [2-624, 2-658](#)

- BPDU guard, for spanning tree [2-626, 2-658](#)

- broadcast storm control [2-676](#)

C

- candidate switches

- See clusters

- cat (boot loader) command [A-4](#)

- caution, description **xx**

- CDP, enabling protocol tunneling for [2-231](#)

- channel-group command [2-32](#)

- channel-protocol command [2-35](#)

- Cisco Network Assistant

- See Network Assistant **xx**

- Cisco SoftPhone

- auto-QoS configuration [2-18](#)

- trusting packets sent from [2-313](#)

- class command [2-37](#)

- class-map command [2-39](#)

- class maps

- creating [2-39](#)

- defining the match criteria [2-273](#)

- displaying [2-403](#)

- class of service

- See CoS

- clear dot1x command [2-41](#)

- clear eap sessions command [2-42](#)

- clear errdisable interface [2-43](#)

- clear ip arp inspection log command [2-44](#)

- clear ip arp inspection statistics command [2-45](#)

- clear ipc command [2-48](#)

- clear ip dhcp snooping database command [2-46](#)

- clear l2protocol-tunnel counters command [2-49](#)

- clear lacp command [2-50](#)

- clear mac address-table command [2-51, 2-53](#)

- clear pagp command [2-54](#)

- clear port-security command [2-55](#)

- clear spanning-tree counters command [2-57](#)

- clear spanning-tree detected-protocols command [2-58](#)

- clear vmps statistics command [2-59](#)

- clear vtp counters command [2-60](#)
 - cluster commander-address command [2-61](#)
 - cluster discovery hop-count command [2-63](#)
 - cluster enable command [2-64](#)
 - cluster holdtime command [2-65](#)
 - cluster member command [2-66](#)
 - cluster outside-interface command [2-68](#)
 - cluster requirements [xxi](#)
 - cluster run command [2-69](#)
 - clusters
 - adding candidates [2-66](#)
 - binding to HSRP group [2-70](#)
 - building manually [2-66](#)
 - communicating with
 - devices outside the cluster [2-68](#)
 - members by using Telnet [2-367](#)
 - debug messages, display [B-5](#)
 - displaying
 - candidate switches [2-406](#)
 - debug messages [B-5](#)
 - member switches [2-408](#)
 - status [2-404](#)
 - hop-count limit for extended discovery [2-63](#)
 - HSRP standby groups [2-70](#)
 - redundancy [2-70](#)
 - SNMP trap [2-613](#)
 - cluster standby-group command [2-70](#)
 - cluster timer command [2-72](#)
 - command modes defined [1-1](#)
 - commands changed in Cisco IOS Release 12.2(20)SE [1-6](#)
 - command switch
 - See clusters
 - configuration, initial
 - See getting started guide and hardware installation guide
 - configuration files
 - password recovery disable considerations [A-1](#)
 - specifying the name [2-25, 2-30](#)
 - configuring multiple interfaces [2-144](#)
 - config-vlan mode
 - commands [2-732](#)
 - description [1-4](#)
 - entering [2-731](#)
 - summary [1-2](#)
 - conventions
 - command [xx](#)
 - for examples [xx](#)
 - publication [xx](#)
 - text [xx](#)
 - copy (boot loader) command [A-5](#)
 - CoS
 - assigning default value to incoming packets [2-283](#)
 - assigning to Layer 2 protocol packets [2-234](#)
 - overriding the incoming value [2-283](#)
 - CoS-to-DSCP map [2-287](#)
 - CPU ASIC statistics, displaying [2-410](#)
 - crashinfo files [2-137](#)
-
- ## D
- debug auto qos command [B-2](#)
 - debug backup command [B-4](#)
 - debug cluster command [B-5](#)
 - debug dot1x command [B-7](#)
 - debug dtp command [B-8](#)
 - debug eap command [B-9](#)
 - debug etherchannel command [B-10](#)
 - debug ilpower command [B-11](#)
 - debug interface command [B-12](#)
 - debug ip dhcp snooping command [B-13](#)
 - debug ip igmp filter command [B-15](#)
 - debug ip igmp max-groups command [B-16](#)
 - debug ip igmp snooping command [B-17](#)
 - debug ip verify source packet command [B-14](#)
 - debug lacp command [B-18](#)
 - debug mac-notification command [B-19](#)
 - debug matm command [B-20](#)
 - debug matm move update command [B-21](#)

- debug monitor command [B-22](#)
- debug mvrdbg command [B-23](#)
- debug nvram command [B-24](#)
- debug pagp command [B-25](#)
- debug platform acl command [B-26](#)
- debug platform backup interface command [B-27](#)
- debug platform configuration command [B-35](#)
- debug platform cpu-queues command [B-28](#)
- debug platform device-manager command [B-30](#)
- debug platform dot1x command [B-31](#)
- debug platform etherchannel command [B-32](#)
- debug platform fallback-bridging command [B-33](#)
- debug platform forw-tcam command [B-34](#)
- debug platform ip arp inspection command [B-36](#)
- debug platform ip dhcp command [B-37](#)
- debug platform ip igmp snooping command [B-38](#)
- debug platform ip multicast command [B-40](#)
- debug platform ip unicast command [B-42](#)
- debug platform ip wccp command [B-44](#)
- debug platform led command [B-45](#)
- debug platform matm command [B-46](#)
- debug platform messaging application command [B-47](#)
- debug platform phy command [B-48](#)
- debug platform pm command [B-50](#)
- debug platform port-asic command [B-52](#)
- debug platform port-security command [B-53](#)
- debug platform qos-acl-tcam command [B-54](#)
- debug platform remote-commands command [B-55](#)
- debug platform resource-manager command [B-56](#)
- debug platform snmp command [B-57](#)
- debug platform span command [B-58](#)
- debug platform supervisor-asic command [B-59](#)
- debug platform sw-bridge command [B-60](#)
- debug platform tcam command [B-61](#)
- debug platform uddl command [B-63](#)
- debug platform vlan command [B-64](#)
- debug pm command [B-65](#)
- debug port-security command [B-67](#)
- debug qos-manager command [B-68](#)
- debug spanning-tree backbonefast command [B-71](#)
- debug spanning-tree bpdu command [B-72](#)
- debug spanning-tree bpdu-opt command [B-73](#)
- debug spanning-tree command [B-69](#)
- debug spanning-tree mstp command [B-74](#)
- debug spanning-tree switch command [B-76](#)
- debug spanning-tree uplinkfast command [B-78](#)
- debug sw-vlan command [B-79](#)
- debug sw-vlan ifs command [B-81](#)
- debug sw-vlan notification command [B-82](#)
- debug sw-vlan vtp command [B-83](#)
- debug uddl command [B-85](#)
- debug vqpc command [B-87](#)
- define interface-range command [2-73](#)
- delete (boot loader) command [A-6](#)
- delete command [2-75](#)
- deny (ARP access-list configuration) command [2-76](#)
- deny (IPv6) command [2-78](#)
- deny command [2-83](#)
- detect mechanism, causes [2-129](#)
- device manager requirements [xx](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [2-176](#)
 - enabling
 - on a VLAN [2-182](#)
 - option 82 [2-174, 2-176](#)
 - trust on an interface [2-180](#)
 - error recovery timer [2-134](#)
 - rate limiting [2-179](#)
- DHCP snooping binding database
 - binding file, configuring [2-172](#)
 - bindings
 - adding [2-170](#)
 - deleting [2-170](#)
 - displaying [2-472](#)

DHCP snooping binding database (continued)

- clearing database agent statistics [2-46](#)
- database agent, configuring [2-172](#)
- displaying
 - binding entries [2-472](#)
 - database agent status [2-474, 2-476](#)
- renewing [2-371](#)
- dir (boot loader) command [A-7](#)
- directories, deleting [2-75](#)
- documentation, related [xx](#)
- document conventions [xx](#)
- domain name, VTP [2-756, 2-760](#)
- dot1x auth-fail max-attempts [2-93](#)
- dot1x auth-fail vlan [2-95](#)
- dot1x command [2-91](#)
- dot1x control-direction command [2-97](#)
- dot1x critical global configuration command [2-99](#)
- dot1x critical interface configuration command [2-101](#)
- dot1x default command [2-103](#)
- dot1x fallback command [2-104](#)
- dot1x guest-vlan command [2-105](#)
- dot1x host-mode command [2-108](#)
- dot1x initialize command [2-110](#)
- dot1x mac-auth-bypass command [2-111](#)
- dot1x max-reauth-req command [2-113](#)
- dot1x max-req command [2-114](#)
- dot1x multiple-hosts command [2-115](#)
- dot1x pae command [2-116](#)
- dot1x port-control command [2-117](#)
- dot1x re-authenticate command [2-119](#)
- dot1x re-authentication command [2-120](#)
- dot1x reauthentication command [2-121](#)
- dot1x test eapol-capable command [2-122](#)
- dot1x test timeout command [2-123](#)
- dot1x timeout command [2-124](#)
- dropping packets, with ACL matches [2-6](#)
- drop threshold, Layer 2 protocol tunneling [2-231](#)
- DSCP-to-CoS map [2-287](#)
- DSCP-to-DSCP-mutation map [2-287](#)

- DTP [2-690](#)
- DTP flap
 - error detection for [2-129](#)
 - error recovery timer [2-134](#)
- DTP negotiation [2-694](#)
- dual-purpose uplink ports
 - selecting the type [2-277](#)
- duplex command [2-127](#)
- dynamic-access ports
 - configuring [2-681](#)
 - restrictions [2-682](#)
- dynamic ARP inspection
 - ARP ACLs
 - apply to a VLAN [2-156](#)
 - define [2-16](#)
 - deny packets [2-76](#)
 - display [2-393](#)
 - permit packets [2-330](#)
 - clear
 - log buffer [2-44](#)
 - statistics [2-45](#)
 - display
 - ARP ACLs [2-393](#)
 - configuration and operating state [2-467](#)
 - log buffer [2-467](#)
 - statistics [2-467](#)
 - trust state and rate limit [2-467](#)
 - enable per VLAN [2-166](#)
 - error detection for [2-129](#)
 - error recovery timer [2-134](#)
 - log buffer
 - clear [2-44](#)
 - configure [2-160](#)
 - display [2-467](#)
 - rate-limit incoming ARP packets [2-158](#)
 - statistics
 - clear [2-45](#)
 - display [2-467](#)
 - trusted interface state [2-162](#)

dynamic ARP inspection (continued)

type of packet logged [2-167](#)

validation checks [2-164](#)

dynamic auto VLAN membership mode [2-689](#)

dynamic desirable VLAN membership mode [2-689](#)

Dynamic Host Configuration Protocol (DHCP)

See DHCP snooping

Dynamic Trunking Protocol

See DTP

E

EAP-request/identity frame

maximum number to send [2-114](#)

response time before retransmitting [2-124](#)

encapsulation methods [2-708](#)

environment variables, displaying [2-398](#)

errdisable detect cause command [2-129](#)

errdisable detect cause small-frame comand [2-131](#)

errdisable recovery cause small-frame [2-133](#)

errdisable recovery command [2-134](#)

error conditions, displaying [2-442](#)

error disable detection [2-129](#)

error-disabled interfaces, displaying [2-453](#)

EtherChannel

assigning Ethernet interface to channel group [2-32](#)

creating port-channel logical interface [2-142](#)

debug EtherChannel/PAGP, display [B-10](#)

debug platform-specific events, display [B-32](#)

displaying [2-446](#)

enabling Layer 2 protocol tunneling for

LACP [2-232](#)

PAGP [2-232](#)

UDLD [2-232](#)

interface information, displaying [2-453](#)

EtherChannel (continued)

LACP

clearing channel-group information [2-50](#)

debug messages, display [B-18](#)

displaying [2-512](#)

modes [2-32](#)

port priority for hot-standby ports [2-235](#)

restricting a protocol [2-35](#)

system priority [2-237](#)

load-distribution methods [2-348](#)

PAGP

aggregate-port learner [2-326](#)

clearing channel-group information [2-54](#)

debug messages, display [B-25](#)

displaying [2-564](#)

error detection for [2-129](#)

error recovery timer [2-134](#)

learn method [2-326](#)

modes [2-32](#)

physical-port learner [2-326](#)

priority of interface for transmitted traffic [2-328](#)

Ethernet controller, internal register display [2-412](#)

Ethernet statistics, collecting [2-373](#)

examples, conventions for [xx](#)

exception crashinfo command [2-137](#)

exit command [2-746](#)

extended discovery of candidate switches [2-63](#)

extended-range VLANs

and allowed VLAN list [2-708](#)

and pruning-eligible list [2-708](#)

configuring [2-731](#)

extended system ID for STP [2-632](#)

F

- fallback profile command [2-138](#)
- fallback profiles, displaying [2-449](#)
- fan information, displaying [2-438](#)
- file name, VTP [2-756](#)
- files, deleting [2-75](#)
- flash_init (boot loader) command [A-9](#)
- Flex Links
 - configuring [2-683](#)
 - configuring preferred VLAN [2-685](#)
 - displaying [2-453](#)
- flowcontrol command [2-140](#)
- format (boot loader) command [A-10](#)
- forwarding packets, with ACL matches [2-6](#)
- forwarding results, display [C-6](#)
- frame forwarding information, displaying [C-6](#)
- front-end controller, counter and status information [C-8](#)
- fsck (boot loader) command [A-11](#)

G

- global configuration mode [1-2, 1-3](#)

H

- hardware ACL statistics [2-389](#)
- help (boot loader) command [A-12](#)
- hierarchical policy maps [2-346](#)
- hop-count limit for clusters [2-63](#)
- host connection, port configuration [2-688](#)
- host ports, private VLANs [2-692](#)
- Hot Standby Router Protocol
 - See HSRP
- HSRP
 - binding HSRP group to cluster [2-70](#)
 - standby group [2-70](#)

I

- IEEE 802.1Q trunk ports and native VLANs [2-748](#)
- IEEE 802.1Q tunnel ports
 - configuring [2-689](#)
 - displaying [2-427](#)
 - limitations [2-690](#)
- IEEE 802.1x
 - and switchport modes [2-690](#)
 - violation error recovery [2-134](#)
 - See also port-based authentication
- IEEE 802.1X Port Based Authentication
 - enabling guest VLAN supplicant [2-94, 2-104, 2-139](#)
- IGMP filters
 - applying [2-185](#)
 - debug messages, display [B-15](#)
- IGMP groups, setting maximum [2-187](#)
- IGMP maximum groups, debugging [B-16](#)
- IGMP profiles
 - creating [2-189](#)
 - displaying [2-479](#)
- IGMP snooping
 - adding ports as a static member of a group [2-206](#)
 - displaying [2-480, 2-485, 2-487](#)
 - enabling [2-191](#)
 - enabling the configurable-leave timer [2-193](#)
 - enabling the Immediate-Leave feature [2-202](#)
 - flooding query count [2-199](#)
 - interface topology change notification behavior [2-201](#)
 - multicast table [1-6, 2-483](#)
 - querier [2-195](#)
 - query solicitation [2-199](#)
 - report suppression [2-197](#)
 - switch topology change notification behavior [2-199](#)
- images
 - See software images
- Immediate-Leave feature, MVR [2-323](#)
- immediate-leave processing [2-202](#)
- Immediate-Leave processing, IPv6 [2-227](#)

- initial configuration
 - See getting started guide and hardware installation guide
- interface configuration mode [1-2, 1-4](#)
- interface port-channel command [2-142](#)
- interface range command [2-144](#)
- interface-range macros [2-73](#)
- interfaces
 - assigning Ethernet interface to channel group [2-32](#)
 - configuring [2-127](#)
 - configuring multiple [2-144](#)
 - creating port-channel logical [2-142](#)
 - debug messages, display [B-12](#)
 - disabling [2-609](#)
 - displaying the MAC address table [2-532](#)
 - restarting [2-609](#)
- interface speed, configuring [2-668](#)
- interface vlan command [2-146](#)
- internal registers, displaying [2-412, 2-421](#)
- Internet Group Management Protocol
 - See IGMP
- invalid GBIC
 - error detection for [2-129](#)
 - error recovery timer [2-134](#)
- ip access-group command [2-148](#)
- ip address command [2-151](#)
- IP addresses, setting [2-151](#)
- IP address matching [2-271](#)
- ip admission command [2-153](#)
- ip admission name proxy http command [2-154](#)
- ip arp inspection filter vlan command [2-156](#)
- ip arp inspection limit command [2-158](#)
- ip arp inspection log-buffer command [2-160](#)
- ip arp inspection trust command [2-162](#)
- ip arp inspection validate command [2-164](#)
- ip arp inspection vlan command [2-166](#)
- ip arp inspection vlan logging command [2-167](#)
- IP DHCP snooping
 - See DHCP snooping
- ip dhcp snooping binding command [2-170](#)
- ip dhcp snooping command [2-169](#)
- ip dhcp snooping database command [2-172](#)
- ip dhcp snooping information option allow-untrusted command [2-176](#)
- ip dhcp snooping information option command [2-174](#)
- ip dhcp snooping information option format remote-id command [2-178](#)
- ip dhcp snooping limit rate command [2-179](#)
- ip dhcp snooping trust command [2-180](#)
- ip dhcp snooping verify command [2-181](#)
- ip dhcp snooping vlan command [2-182](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [2-183](#)
- ip igmp filter command [2-185](#)
- ip igmp max-groups command [2-187](#)
- ip igmp profile command [2-189](#)
- ip igmp snooping command [2-191](#)
- ip igmp snooping last-member-query-interval command [2-193](#)
- ip igmp snooping querier command [2-195](#)
- ip igmp snooping report-suppression command [2-197](#)
- ip igmp snooping tcn command [2-199](#)
- ip igmp snooping tcn flood command [2-201](#)
- ip igmp snooping vlan immediate-leave command [2-202](#)
- ip igmp snooping vlan mrouter command [2-204](#)
- ip igmp snooping vlan static command [2-206](#)
- IP multicast addresses [2-320](#)
- IP phones
 - auto-QoS configuration [2-18](#)
 - trusting packets sent from [2-313](#)
- IP-precedence-to-DSCP map [2-287](#)
- ip source binding command [2-208](#)

- IP source guard
 - disabling [2-212](#)
 - displaying
 - binding entries [2-489](#)
 - configuration [2-491](#)
 - dynamic binding entries only [2-472](#)
 - enabling [2-212](#)
 - static IP source bindings [2-208](#)
 - ip ssh command [2-210](#)
 - IPv6 access list, deny conditions [2-78](#)
 - ipv6 access-list command [2-213](#)
 - ipv6 mld snooping command [2-216](#)
 - ipv6 mld snooping last-listener-query count command [2-218](#)
 - ipv6 mld snooping last-listener-query-interval command [2-220](#)
 - ipv6 mld snooping listener-message-suppression command [2-222](#)
 - ipv6 mld snooping robustness-variable command [2-223](#)
 - ipv6 mld snooping tcn command [2-225](#)
 - ipv6 mld snooping vlan command [2-227](#)
 - IPv6 SDM template [2-374](#)
 - ipv6 traffic-filter command [2-229](#)
 - ip verify source command [2-212](#)
-
- J**
- jumbo frames
 - See MTU
-
- L**
- l2protocol-tunnel command [2-231](#)
 - l2protocol-tunnel cos command [2-234](#)
 - LACP
 - See EtherChannel
 - lacp port-priority command [2-235](#)
 - lacp system-priority command [2-237](#)
 - Layer 2 mode, enabling [2-679](#)
 - Layer 2 protocol ports, displaying [2-509](#)
 - Layer 2 protocol-tunnel
 - error detection for [2-129](#)
 - error recovery timer [2-134](#)
 - Layer 2 protocol tunnel counters [2-49](#)
 - Layer 2 protocol tunneling error recovery [2-232](#)
 - Layer 2 traceroute
 - IP addresses [2-722](#)
 - MAC addresses [2-719](#)
 - Layer 3 mode, enabling [2-679](#)
 - line configuration mode [1-2, 1-5](#)
 - Link Aggregation Control Protocol
 - See EtherChannel
 - link flap
 - error detection for [2-129](#)
 - error recovery timer [2-134](#)
 - link state group command [2-242](#)
 - link state track command [2-244](#)
 - load-distribution methods for EtherChannel [2-348](#)
 - location (global configuration) command [2-238](#)
 - location (interface configuration) command [2-240](#)
 - logging event command [2-245](#)
 - logging event power-inline-status command [2-246](#)
 - logging file command [2-247](#)
 - logical interface [2-142](#)
 - loopback error
 - detection for [2-129](#)
 - recovery timer [2-134](#)
 - loop guard, for spanning tree [2-633, 2-637](#)
-
- M**
- mac access-group command [2-249](#)
 - MAC access-groups, displaying [2-520](#)
 - MAC access list configuration mode [2-251](#)
 - mac access-list extended command [2-251](#)

- MAC access lists [2-83](#)
- MAC addresses
 - displaying
 - aging time [2-526](#)
 - all [2-524](#)
 - dynamic [2-530](#)
 - MAC address-table move updates [2-534](#)
 - notification settings [2-536](#)
 - number of addresses in a VLAN [2-528](#)
 - per interface [2-532](#)
 - per VLAN [2-540](#)
 - static [2-538](#)
 - static and dynamic entries [2-522](#)
 - dynamic
 - aging time [2-253](#)
 - deleting [2-51](#)
 - displaying [2-530](#)
 - enabling MAC address notification [2-256](#)
 - enabling MAC address-table move update [2-254](#)
 - matching [2-271](#)
 - static
 - adding and removing [2-258](#)
 - displaying [2-538](#)
 - dropping on an interface [2-259](#)
 - tables [2-524](#)
- MAC address notification, debugging [B-19](#)
- mac address-table aging-time [2-249, 2-271](#)
- mac address-table aging-time command [2-253](#)
- mac address-table move update command [2-254](#)
- mac address-table notification command [2-256](#)
- mac address-table static command [2-258](#)
- mac address-table static drop command [2-259](#)
- macro apply command [2-261](#)
- macro description command [2-264](#)
- macro global command [2-265](#)
- macro global description command [2-268](#)
- macro name command [2-269](#)
- macros
 - adding a description [2-264](#)
 - adding a global description [2-268](#)
 - applying [2-265](#)
 - creating [2-269](#)
 - displaying [2-566](#)
 - interface range [2-73, 2-144](#)
 - specifying parameter values [2-265](#)
 - tracing [2-265](#)
- manual
 - audience [xix](#)
 - purpose of [xix](#)
- maps
 - QoS
 - defining [2-287](#)
 - displaying [2-550](#)
 - VLAN
 - creating [2-743](#)
 - defining [2-271](#)
 - displaying [2-599](#)
- match (access-map configuration) command [2-271](#)
- match (class-map configuration) command [2-273](#)
- maximum transmission unit
 - See MTU
- mdix auto command [2-275](#)
- media-type command [2-277](#)
- member switches
 - See clusters
- memory (boot loader) command [A-13](#)
- mkdir (boot loader) command [A-14](#)
- MLD snooping
 - configuring [2-222, 2-223](#)
 - configuring queries [2-218, 2-220](#)
 - configuring topology change notification [2-225](#)
 - displaying [2-499, 2-501, 2-503, 2-505](#)
 - enabling [2-216](#)
- MLD snooping on a VLAN, enabling [2-227](#)

- mls qos aggregate-policer command [2-281](#)
- mls qos command [2-279](#)
- mls qos cos command [2-283](#)
- mls qos dscp-mutation command [2-285](#)
- mls qos map command [2-287](#)
- mls qos queue-set output buffers command [2-291](#)
- mls qos queue-set output threshold command [2-293](#)
- mls qos rewrite ip dscp command [2-295](#)
- mls qos srr-queue input bandwidth command [2-297](#)
- mls qos srr-queue input buffers command [2-299](#)
- mls qos-srr-queue input cos-map command [2-301](#)
- mls qos srr-queue input dscp-map command [2-303](#)
- mls qos srr-queue input priority-queue command [2-305](#)
- mls qos srr-queue input threshold command [2-307](#)
- mls qos-srr-queue output cos-map command [2-309](#)
- mls qos srr-queue output dscp-map command [2-311](#)
- mls qos trust command [2-313](#)
- mls qos vlan-based command [2-315](#)
- mode, MVR [2-320](#)
- Mode button, and password recovery [2-377](#)
- modes, commands [1-1](#)
- monitor session command [2-316](#)
- more (boot loader) command [A-15](#)
- MSTP
 - displaying [2-581](#)
 - interoperability [2-58](#)
 - link type [2-635](#)
 - MST region
 - aborting changes [2-641](#)
 - applying changes [2-641](#)
 - configuration name [2-641](#)
 - configuration revision number [2-641](#)
 - current or pending display [2-641](#)
 - displaying [2-581](#)
 - MST configuration mode [2-641](#)
 - VLANs-to-instance mapping [2-641](#)
 - path cost [2-643](#)
 - protocol mode [2-639](#)
 - restart protocol migration process [2-58](#)

MSTP (continued)

- root port
 - loop guard [2-633](#)
 - preventing from becoming designated [2-633](#)
 - restricting which can be root [2-633](#)
 - root guard [2-633](#)
- root switch
 - affects of extended system ID [2-632](#)
 - hello-time [2-646, 2-654](#)
 - interval between BPDU messages [2-647](#)
 - interval between hello BPDU messages [2-646, 2-654](#)
 - max-age [2-647](#)
 - maximum hop count before discarding BPDU [2-648](#)
 - port priority for selection of [2-650](#)
 - primary or secondary [2-654](#)
 - switch priority [2-653](#)
- state changes
 - blocking to forwarding state [2-660](#)
 - enabling BPDU filtering [2-624, 2-658](#)
 - enabling BPDU guard [2-626, 2-658](#)
 - enabling Port Fast [2-658, 2-660](#)
 - forward-delay time [2-645](#)
 - length of listening and learning states [2-645](#)
 - rapid transition to forwarding [2-635](#)
 - shutting down Port Fast-enabled ports [2-658](#)
- state information display [2-580](#)
- MTU
 - configuring size [2-716](#)
 - displaying global setting [2-588](#)
- Multicast Listener Discovery
 - See MLD
- multicast group address, MVR [2-323](#)
- multicast groups, MVR [2-321](#)
- Multicast Listener Discovery
 - See MLD
- multicast router learning method [2-204](#)
- multicast router ports, configuring [2-204](#)

multicast router ports, IPv6 [2-227](#)
 multicast storm control [2-676](#)
 multicast VLAN, MVR [2-320](#)
 multicast VLAN registration
 See MVR
 Multiple Spanning Tree Protocol
 See MSTP
 MVR
 and address aliasing [2-321](#)
 configuring [2-320](#)
 configuring interfaces [2-323](#)
 debug messages, display [B-23](#)
 displaying [2-558](#)
 displaying interface information [2-560](#)
 members, displaying [2-562](#)
 mvr (global configuration) command [2-320](#)
 mvr (interface configuration) command [2-323](#)
 mvr vlan group command [2-324](#)

N

native VLANs [2-708](#)
 native VLAN tagging [2-748](#)
 Network Admission Control Software Configuration Guide [2-153, 2-155](#)
 Network Assistant requirements [xx](#)
 nonegotiate, speed [2-668](#)
 nonegotiating DTP messaging [2-694](#)
 non-IP protocols
 denying [2-83](#)
 forwarding [2-338](#)
 non-IP traffic access lists [2-251](#)
 non-IP traffic forwarding
 denying [2-83](#)
 permitting [2-338](#)
 normal-range VLANs [2-731, 2-737](#)
 note, description [xx](#)
 no vlan command [2-731, 2-741](#)

O

online diagnostics
 displaying
 configured boot-up coverage level [2-425](#)
 current scheduled tasks [2-425](#)
 event logs [2-425](#)
 supported test suites [2-425](#)
 test ID [2-425](#)
 test results [2-425](#)
 test statistics [2-425](#)
 global configuration mode
 clearing health monitoring diagnostic test schedule [2-44](#)
 clearing test-based testing schedule [2-88](#)
 setting health monitoring diagnostic testing [2-44](#)
 setting test-based testing [2-88](#)
 setting up health monitoring diagnostic test schedule [2-44](#)
 setting up test-based testing [2-88](#)
 health monitoring diagnostic tests, configuring [2-86](#)
 scheduled switchover
 disabling [2-88](#)
 enabling [2-88](#)
 scheduling
 enabling [2-88](#)
 removing [2-88](#)
 test interval, setting [2-88](#)

P

PAGP
 See EtherChannel
 pagp learn-method command [2-326](#)
 pagp port-priority command [2-328](#)
 password, VTP [2-756, 2-760](#)
 password-recovery mechanism, enabling and disabling [2-377](#)
 permit (ARP access-list configuration) command [2-330](#)
 permit (IPv6) command [2-332](#)

- permit (MAC access-list configuration) command [2-338](#)
- per-VLAN spanning-tree plus
 - See STP
- physical-port learner [2-326](#)
- PID, displaying [2-466](#)
- PIM-DVMRP, as multicast router learning method [2-204](#)
- PoE
 - configuring the power budget [2-353](#)
 - configuring the power management mode [2-350](#)
 - displaying controller register values [2-419](#)
 - displaying power management information [2-574](#)
 - logging of status [2-246](#)
- police aggregate command [2-343](#)
- police command [2-341](#)
- policed-DSCP map [2-287](#)
- policy-map command [2-345](#)
- policy maps
 - applying to an interface [2-379, 2-384](#)
 - creating [2-345](#)
 - displaying [2-569](#)
 - hierarchical [2-346](#)
 - policers
 - displaying [2-543](#)
 - for a single class [2-341](#)
 - for multiple classes [2-281, 2-343](#)
 - policed-DSCP map [2-287](#)
 - traffic classification
 - defining the class [2-37](#)
 - defining trust states [2-724](#)
 - setting DSCP or IP precedence values [2-382](#)
- Port Aggregation Protocol
 - See EtherChannel
- port-based authentication
 - AAA method list [2-3](#)
 - debug messages, display [B-7](#)
 - enabling IEEE 802.1x
 - globally [2-91](#)
 - per interface [2-117](#)
 - guest VLAN [2-105](#)
 - port-based authentication (continued)**
 - host modes [2-108](#)
 - IEEE 802.1x AAA accounting methods [2-1](#)
 - initialize an interface [2-110, 2-123](#)
 - MAC authentication bypass [2-111](#)
 - manual control of authorization state [2-117](#)
 - PAE as authenticator [2-116](#)
 - periodic re-authentication
 - enabling [2-121](#)
 - time between attempts [2-124](#)
 - quiet period between failed authentication exchanges [2-124](#)
 - re-authenticating IEEE 802.1x-enabled ports [2-119](#)
 - resetting configurable IEEE 802.1x parameters [2-103](#)
 - switch-to-authentication server retransmission time [2-124](#)
 - switch-to-client frame-retransmission number [2-113 to 2-114](#)
 - switch-to-client retransmission time [2-124](#)
 - test for IEEE 802.1x readiness [2-122](#)
- port-channel load-balance command [2-348](#)
- Port Fast, for spanning tree [2-660](#)
- port ranges, defining [2-73](#)
- ports, debugging [B-65](#)
- ports, protected [2-707](#)
- port security
 - aging [2-701](#)
 - debug messages, display [B-67](#)
 - enabling [2-696](#)
 - violation error recovery [2-134](#)
- port trust states for QoS [2-313](#)
- port types, MVR [2-323](#)
- power information, displaying [2-438](#)
- power inline command [2-350](#)
- power inline consumption command [2-353](#)
- Power over Ethernet
 - See PoE
- priority-queue command [2-355](#)
- private-vlan command [2-357](#)
- private-vlan mapping command [2-360](#)

private VLANs

- association [2-705](#)
- configuring [2-357](#)
- configuring ports [2-692](#)
- displaying [2-594](#)
- host ports [2-692](#)
- mapping
 - configuring [2-705](#)
 - displaying [2-453](#)
- promiscuous ports [2-692](#)

privileged EXEC mode [1-2, 1-3](#)product identification information, displaying [2-466](#)promiscuous ports, private VLANs [2-692](#)protected ports, displaying [2-458](#)

pruning

VLANs [2-708](#)

VTP

- displaying interface information [2-453](#)
- enabling [2-756, 2-760](#)

pruning-eligible VLAN list [2-710](#)

PVST+

See STP

Q

QoS

auto-QoS

- configuring [2-18](#)
- debug messages, display [1-6, B-2](#)
- displaying [2-394](#)

class maps

- creating [2-39](#)
- defining the match criteria [2-273](#)
- displaying [2-403](#)

defining the CoS value for an incoming packet [2-283](#)displaying configuration information [2-394, 2-542](#)DSCP transparency [2-295](#)**QoS (continued)**

DSCP trusted ports

- applying DSCP-to-DSCP-mutation map to [2-285](#)
- defining DSCP-to-DSCP-mutation map [2-287](#)

egress queues

- allocating buffers [2-291](#)
- defining the CoS output queue threshold map [2-309](#)
- defining the DSCP output queue threshold map [2-311](#)

displaying buffer allocations [2-546](#)displaying CoS output queue threshold map [2-550](#)displaying DSCP output queue threshold map [2-550](#)displaying queueing strategy [2-546](#)displaying queue-set settings [2-553](#)enabling bandwidth shaping and scheduling [2-672](#)enabling bandwidth sharing and scheduling [2-674](#)limiting the maximum output on a port [2-670](#)mapping a port to a queue-set [2-362](#)mapping CoS values to a queue and threshold [2-309](#)mapping DSCP values to a queue and threshold [2-311](#)setting maximum and reserved memory allocations [2-293](#)setting WTD thresholds [2-293](#)enabling [2-279](#)

ingress queues

allocating buffers [2-299](#)assigning SRR scheduling weights [2-297](#)defining the CoS input queue threshold map [2-301](#)defining the DSCP input queue threshold map [2-303](#)displaying buffer allocations [2-546](#)displaying CoS input queue threshold map [2-550](#)

QoS (continued)

- ingress queues (continued)
 - displaying DSCP input queue threshold map [2-550](#)
 - displaying queuing strategy [2-546](#)
 - displaying settings for [2-544](#)
 - enabling the priority queue [2-305](#)
 - mapping CoS values to a queue and threshold [2-301](#)
 - mapping DSCP values to a queue and threshold [2-303](#)
 - setting WTD thresholds [2-307](#)
- maps
 - defining [2-287, 2-301, 2-303, 2-309, 2-311](#)
 - displaying [2-550](#)
- policy maps
 - applying an aggregate policer [2-343](#)
 - applying to an interface [2-379, 2-384](#)
 - creating [2-345](#)
 - defining policers [2-281, 2-341](#)
 - displaying policers [2-543](#)
 - displaying policy maps [2-569](#)
 - hierarchical [2-346](#)
 - policed-DSCP map [2-287](#)
 - setting DSCP or IP precedence values [2-382](#)
 - traffic classifications [2-37](#)
 - trust states [2-724](#)
- port trust states [2-313](#)
- queues, enabling the expedite [2-355](#)
- statistics
 - in-profile and out-of-profile packets [2-546](#)
 - packets enqueued or dropped [2-546](#)
 - sent and received CoS values [2-546](#)
 - sent and received DSCP values [2-546](#)
- trusted boundary for IP phones [2-313](#)
- VLAN-based [2-315](#)
- quality of service
 - See QoS

- querytime, MVR [2-320](#)
- queue-set command [2-362](#)

R

- radius-server dead-criteria command [2-363](#)
- radius-server host command [2-365](#)
- rapid per-VLAN spanning-tree plus
 - See STP
- rapid PVST+
 - See STP
- rcommand command [2-367](#)
- re-authenticating IEEE 802.1x-enabled ports [2-119](#)
- re-authentication
 - periodic [2-121](#)
 - time between attempts [2-124](#)
- receiver ports, MVR [2-323](#)
- receiving flow-control packets [2-140](#)
- recovery mechanism
 - causes [2-134](#)
 - display [2-43, 2-400, 2-440, 2-444](#)
 - timer interval [2-135](#)
- redundancy for cluster switches [2-70](#)
- remote-span command [2-369](#)
- Remote Switched Port Analyzer
 - See RSPAN
- rename (boot loader) command [A-16](#)
- renew ip dhcp snooping database command [2-371](#)
- requirements
 - cluster [xxi](#)
 - device manager [xx](#)
 - Network Assistant [xx](#)
- reset (boot loader) command [A-17](#)
- reset command [2-746](#)
- resource templates, displaying [2-576](#)
- restricted VLAN
 - See dot1x auth-fail vlan

rmdir (boot loader) command [A-18](#)
 rmon collection stats command [2-373](#)
 root guard, for spanning tree [2-633](#)
 routed ports

- IP addresses on [2-152](#)
- number supported [2-152](#)

 RSPAN

- configuring [2-316](#)
- displaying [2-556](#)
- filter RSPAN traffic [2-316](#)
- remote-span command [2-369](#)
- sessions
 - displaying [2-556](#)

S

scheduled switchover

- disabling [2-88](#)
- enabling [2-88](#)

 sdm prefer command [2-374](#)
 SDM templates

- allowed resources [2-375](#)
- displaying [2-576](#)
- dual IPv4 and IPv6 [2-374](#)

 secure ports, limitations [2-698](#)
 sending flow-control packets [2-140](#)
 service password-recovery command [2-377](#)
 service-policy command [2-379](#)
 set (boot loader) command [A-19](#)
 set command [2-382](#)
 setup command [2-384](#)
 setup express command [2-387](#)
 show access-lists command [2-389](#)
 show archive status command [2-392](#)
 show arp access-list command [2-393](#)
 show auto qos command [2-394](#)
 show boot command [2-398](#)
 show cable-diagnostics tdr command [2-400](#)
 show changes command [2-746](#)
 show class-map command [2-403](#)
 show cluster candidates command [2-406](#)
 show cluster command [2-404](#)
 show cluster members command [2-408](#)
 show controllers cpu-interface command [2-410](#)
 show controllers ethernet-controller command [2-412](#)
 show controllers power inline command [2-419](#)
 show controllers team command [2-421](#)
 show controller utilization command [2-423](#)
 show current command [2-746](#)
 show dot1q-tunnel command [2-427](#)
 show dot1x command [2-428](#)
 show dtp [2-433](#)
 show eap command [2-435](#)
 show env command [2-438](#)
 show errdisable detect command [2-440](#)
 show errdisable flap-values command [2-442](#)
 show errdisable recovery command [2-444](#)
 show etherchannel command [2-446](#)
 show fallback profile command [2-449](#)
 show flowcontrol command [2-451](#)
 show interfaces command [2-453](#)
 show interfaces counters command [2-464](#)
 show inventory command [2-466](#)
 show ip arp inspection command [2-467](#)
 show ipc command [2-493](#)
 show ip dhcp snooping binding command [2-472](#)
 show ip dhcp snooping command [2-471](#)
 show ip dhcp snooping database command [2-474, 2-476](#)
 show ip igmp profile command [2-479](#)
 show ip igmp snooping address command [2-501](#)
 show ip igmp snooping command [2-480, 2-499](#)
 show ip igmp snooping groups command [2-483](#)
 show ip igmp snooping mrouter command [2-485, 2-503](#)
 show ip igmp snooping querier command [2-487, 2-505](#)
 show ip source binding command [2-489](#)
 show ipv6 access-list command [2-497](#)
 show ipv6 route updated [2-507](#)
 show ip verify source command [2-491](#)

- show l2protocol-tunnel command [2-509](#)
- show lacp command [2-512](#)
- show link state group command [2-518](#)
- show mac access-group command [2-520](#)
- show mac address-table address command [2-524](#)
- show mac address-table aging time command [2-526](#)
- show mac address-table command [2-522](#)
- show mac address-table count command [2-528](#)
- show mac address-table dynamic command [2-530](#)
- show mac address-table interface command [2-532](#)
- show mac address-table move update command [2-534](#)
- show mac address-table notification command [2-53, 2-536, B-21](#)
- show mac address-table static command [2-538](#)
- show mac address-table vlan command [2-540](#)
- show mls qos aggregate-policer command [2-543](#)
- show mls qos command [2-542](#)
- show mls qos input-queue command [2-544](#)
- show mls qos interface command [2-546](#)
- show mls qos maps command [2-550](#)
- show mls qos queue-set command [2-553](#)
- show mls qos vlan command [2-555](#)
- show monitor command [2-556](#)
- show mvr command [2-558](#)
- show mvr interface command [2-560](#)
- show mvr members command [2-562](#)
- show pagp command [2-564](#)
- show parser macro command [2-566](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform configuration command [C-4](#)
- show platform etherchannel command [C-5](#)
- show platform forward command [C-6](#)
- show platform frontend-controller command [C-8](#)
- show platform igmp snooping command [C-9](#)
- show platform ip multicast command [C-11](#)
- show platform ip unicast command [C-12](#)
- show platform ipv6 unicast command [C-17](#)
- show platform ip wccp command [C-16](#)
- show platform layer4op command [C-19](#)
- show platform mac-address-table command [C-20](#)
- show platform messaging command [C-21](#)
- show platform monitor command [C-22](#)
- show platform mvr table command [C-23](#)
- show platform pm command [C-24](#)
- show platform port-asic command [C-25](#)
- show platform port-security command [C-29](#)
- show platform qos command [C-30](#)
- show platform resource-manager command [C-31](#)
- show platform snmp counters command [C-33](#)
- show platform spanning-tree command [C-34](#)
- show platform stp-instance command [C-35](#)
- show platform team command [C-36](#)
- show platform vlan command [C-39](#)
- show policy-map command [2-569](#)
- show port security command [2-571](#)
- show power inline command [2-574](#)
- show proposed command [2-746](#)
- show sdm prefer command [2-576](#)
- show setup express command [2-579](#)
- show spanning-tree command [2-580](#)
- show storm-control command [2-586](#)
- show system mtu command [2-588](#)
- show trust command [2-724](#)
- show udd command [2-589](#)
- show version command [2-592](#)
- show vlan access-map command [2-599](#)
- show vlan command [2-594](#)
- show vlan command, fields [2-596](#)
- show vlan filter command [2-600](#)
- show vmps command [2-601](#)
- show vtp command [2-604](#)
- shutdown command [2-609](#)
- shutdown threshold, Layer 2 protocol tunneling [2-231](#)
- shutdown vlan command [2-610](#)
- small violation-rate command [2-611](#)
- Smartports macros
 - See macros

- SNMP host, specifying [2-617](#)
- SNMP informs, enabling the sending of [2-613](#)
- snmp-server enable traps command [2-613](#)
- snmp-server host command [2-617](#)
- snmp trap mac-notification command [2-621](#)
- SNMP traps
 - enabling MAC address notification trap [2-621](#)
 - enabling the MAC address notification feature [2-256](#)
 - enabling the sending of [2-613](#)
- SoftPhone
 - See Cisco SoftPhone
- software images
 - deleting [2-75](#)
 - downloading [2-8](#)
 - upgrading [2-8](#)
 - uploading [2-14](#)
- software version, displaying [2-592](#)
- source ports, MVR [2-323](#)
- SPAN
 - configuring [2-316](#)
 - debug messages, display [B-22](#)
 - displaying [2-556](#)
 - filter SPAN traffic [2-316](#)
 - sessions
 - add interfaces to [2-316](#)
 - displaying [2-556](#)
 - start new [2-316](#)
- spanning-tree backbonefast command [2-623](#)
- spanning-tree bpduguard command [2-624](#)
- spanning-tree bpduguard command [2-626](#)
- spanning-tree cost command [2-628](#)
- spanning-tree etherchannel command [2-630](#)
- spanning-tree extend system-id command [2-632](#)
- spanning-tree guard command [2-633](#)
- spanning-tree link-type command [2-635](#)
- spanning-tree loopguard default command [2-637](#)
- spanning-tree mode command [2-639](#)
- spanning-tree mst configuration command [2-641](#)
- spanning-tree mst cost command [2-643](#)
- spanning-tree mst forward-time command [2-645](#)
- spanning-tree mst hello-time command [2-646](#)
- spanning-tree mst max-age command [2-647](#)
- spanning-tree mst max-hops command [2-648](#)
- spanning-tree mst port-priority command [2-650](#)
- spanning-tree mst pre-standard command [2-652](#)
- spanning-tree mst priority command [2-653](#)
- spanning-tree mst root command [2-654](#)
- spanning-tree portfast (global configuration) command [2-658](#)
- spanning-tree portfast (interface configuration) command [2-660](#)
- spanning-tree port-priority command [2-656](#)
- Spanning Tree Protocol
 - See STP
- spanning-tree transmit hold-count command [2-662](#)
- spanning-tree uplinkfast command [2-663](#)
- spanning-tree vlan command [2-665](#)
- speed command [2-668](#)
- srr-queue bandwidth limit command [2-670](#)
- srr-queue bandwidth share command [2-674](#)
- SSH, configuring version [2-210](#)
- static-access ports, configuring [2-681](#)
- statistics, Ethernet group [2-373](#)
- sticky learning, enabling [2-696](#)
- storm-control command [2-676](#)
- STP
 - BackboneFast [2-623](#)
 - counters, clearing [2-57](#)
 - debug messages, display
 - BackboneFast events [B-71](#)
 - MSTP [B-74](#)
 - optimized BPDUs handling [B-73](#)
 - spanning-tree activity [B-69](#)
 - switch shim [B-76](#)
 - transmitted and received BPDUs [B-72](#)
 - UplinkFast [B-78](#)
 - detection of indirect link failures [2-623](#)
 - enabling protocol tunneling for [2-231](#)

STP (continued)

- EtherChannel misconfiguration [2-630](#)
- extended system ID [2-632](#)
- path cost [2-628](#)
- protocol modes [2-639](#)
- root port
 - accelerating choice of new [2-663](#)
 - loop guard [2-633](#)
 - preventing from becoming designated [2-633](#)
 - restricting which can be root [2-633](#)
 - root guard [2-633](#)
 - UplinkFast [2-663](#)
- root switch
 - affects of extended system ID [2-632, 2-666](#)
 - hello-time [2-665](#)
 - interval between BPDU messages [2-665](#)
 - interval between hello BPDU messages [2-665](#)
 - max-age [2-665](#)
 - port priority for selection of [2-656](#)
 - primary or secondary [2-665](#)
 - switch priority [2-665](#)
- state changes
 - blocking to forwarding state [2-660](#)
 - enabling BPDU filtering [2-624, 2-658](#)
 - enabling BPDU guard [2-626, 2-658](#)
 - enabling Port Fast [2-658, 2-660](#)
 - enabling timer to recover from error state [2-134](#)
 - forward-delay time [2-665](#)
 - length of listening and learning states [2-665](#)
 - shutting down Port Fast-enabled ports [2-658](#)
- state information display [2-580](#)
- VLAN options [2-653, 2-665](#)

SVIs, creating [2-146](#)

Switched Port Analyzer

- See SPAN

switching characteristics

- modifying [2-679](#)
- returning to interfaces [2-679](#)

switchport access command [2-681](#)

- switchport backup interface command [2-683](#)
- switchport block command [2-687](#)
- switchport command [2-679](#)
- switchport host command [2-688](#)
- switchport mode command [2-689](#)
- switchport mode private-vlan command [2-692](#)
- switchport nonegotiate command [2-694](#)
- switchport port-security aging command [2-701](#)
- switchport port-security command [2-696](#)
- switchport priority extend command [2-703](#)
- switchport private-vlan command [2-705](#)
- switchport protected command [2-707](#)
- switchports, displaying [2-453](#)
- switchport trunk command [2-708](#)
- switchport voice vlan command [2-711, 2-712](#)
- system env temperature threshold yellow command [2-714](#)
- system message logging [2-246](#)
- system message logging, save message to flash [2-247](#)
- system mtu command [2-716](#)
- system resource templates [2-374](#)

T

- tar files, creating, listing, and extracting [2-11](#)
- TDR, running [2-718](#)
- Telnet, using to communicate to cluster switches [2-367](#)
- temperature information, displaying [2-438](#)
- templates, system resources [2-374](#)
- test cable-diagnostics tdr command [2-718](#)
- traceroute mac command [2-719](#)
- traceroute mac ip command [2-722](#)
- trunking, VLAN mode [2-689](#)
- trunk mode [2-689](#)
- trunk ports [2-689](#)
- trunks, to non-DTP device [2-690](#)
- trusted boundary for QoS [2-313](#)
- trusted port states for QoS [2-313](#)
- tunnel ports, Layer 2 protocol, displaying [2-509](#)
- type (boot loader) command [A-22](#)

U

UDLD

- aggressive mode [2-726, 2-728](#)
- debug messages, display [B-85](#)
- enable globally [2-726](#)
- enable per interface [2-728](#)
- error recovery timer [2-134](#)
- message timer [2-726](#)
- normal mode [2-726, 2-728](#)
- reset a shutdown interface [2-730](#)
- status [2-589](#)

udld command [2-726](#)

udld port command [2-728](#)

udld reset command [2-730](#)

unicast storm control [2-676](#)

UniDirectional Link Detection

See UDLD

unknown multicast traffic, preventing [2-687](#)

unknown unicast traffic, preventing [2-687](#)

unset (boot loader) command [A-23](#)

upgrading

software images

downloading [2-8](#)

monitoring status of [2-392](#)

upgrading information

See release notes

UplinkFast, for STP [2-663](#)

user EXEC mode [1-2, 1-3](#)

V

version (boot loader) command [A-25](#)

vlan (global configuration) command [2-731](#)

vlan (VLAN configuration) command [2-737](#)

vlan access-map command [2-743](#)

VLAN access map configuration mode [2-743](#)

VLAN access maps

actions [2-6](#)

displaying [2-599](#)

VLAN-based QoS [2-315](#)

VLAN configuration

rules [2-734, 2-739](#)

saving [2-731, 2-741](#)

VLAN configuration mode

commands

VLAN [2-737](#)

VTP [2-760](#)

description [1-5](#)

entering [2-745](#)

summary [1-2](#)

vlan database command [2-745](#)

vlan dot1q tag native command [2-748](#)

vlan filter command [2-749](#)

VLAN filters, displaying [2-600](#)

VLAN ID range [2-731, 2-737](#)

VLAN maps

applying [2-749](#)

creating [2-743](#)

defining [2-271](#)

displaying [2-599](#)

VLAN Query Protocol

See VQP

VLANs

adding [2-731](#)

configuring [2-731, 2-737](#)

debug messages, display

ISL [B-82](#)

VLAN IOS file system error tests [B-81](#)

VLAN manager activity [B-79](#)

VTP [B-83](#)

displaying configurations [2-594](#)

enabling guest VLAN supplicant [2-94, 2-104, 2-139](#)

extended-range [2-731](#)

VLANs (continued)

- MAC addresses
 - displaying [2-540](#)
 - number of [2-528](#)
- media types [2-734, 2-739](#)
- normal-range [2-731, 2-737](#)
- private [2-692](#)
 - configuring [2-357](#)
 - displaying [2-594](#)
 - See also private VLANs
- restarting [2-610](#)
- saving the configuration [2-731](#)
- shutting down [2-610](#)
- SNMP traps for VTP [2-615, 2-618](#)
- suspending [2-610](#)
- variables [2-737](#)

VLAN Trunking Protocol

See VTP

VMPS

- configuring servers [2-754](#)
- displaying [2-601](#)
- error recovery timer [2-135](#)
- reconfirming dynamic VLAN assignments [2-751](#)
- vmmps reconfirm (global configuration) command [2-752](#)
- vmmps reconfirm (privileged EXEC) command [2-751](#)
- vmmps retry command [2-753](#)
- vmmps server command [2-754](#)

voice VLAN

- configuring [2-711, 2-712](#)
- setting port priority [2-703](#)

VQP

- and dynamic-access ports [2-682](#)
- clearing client statistics [2-59](#)
- displaying information [2-601](#)
- per-server retry count [2-753](#)
- reconfirmation interval [2-752](#)
- reconfirming dynamic VLAN assignments [2-751](#)

VTP

- changing characteristics [2-756](#)
- clearing pruning counters [2-60](#)
- configuring
 - domain name [2-756, 2-760](#)
 - file name [2-756](#)
 - mode [2-756, 2-760](#)
 - password [2-756, 2-760](#)
- counters display fields [2-605](#)
- displaying information [2-604](#)
- enabling
 - pruning [2-756, 2-760](#)
 - tunneling for [2-231](#)
 - Version 2 [2-756, 2-760](#)
- mode [2-756, 2-760](#)
- pruning [2-756, 2-760](#)
- saving the configuration [2-731, 2-741](#)
- statistics [2-604](#)
- status [2-604](#)
- status display fields [2-607](#)
- vtp (global configuration) command [2-756](#)
- vtp (VLAN configuration) command [2-760](#)

