



## INDEX

### A

- aaa accounting dot1x command [1](#)
- aaa authentication dot1x command [3](#)
- aaa authorization network command [5, 18, 23, 25, 27, 29, 126, 486, 5, 36](#)
- AAA methods [3](#)
- abort command [856](#)
- access control entries
  - See ACEs
- access control lists
  - See ACLs
- access groups
  - IP [189](#)
  - MAC, displaying [612](#)
- access list, IPv6 [259](#)
- access map configuration mode [337](#)
- access mode [797](#)
- access ports [797](#)
- ACEs [111, 413](#)
- ACLs
  - deny [109](#)
  - displaying [468](#)
  - for non-IP protocols [308](#)
  - IP [189](#)
  - matching [337](#)
  - on Layer 2 interfaces [189](#)
  - permit [411](#)
- action command [6](#)
- address aliasing [386](#)
- aggregate-port learner [399](#)
- allowed VLANs [817](#)
- apply command [856](#)
- archive download-sw command [8](#)
- archive tar command [11](#)
- archive upload-sw command [14](#)
- arp access-list command [16](#)
- authentication control-direction command [18](#)
- authentication event command [20](#)
- authentication failed VLAN
  - See dot1x auth-fail vlan
- authentication fallback command [23](#)
- authentication host-mode command [25](#)
- authentication open command [27](#)
- authentication order command [29](#)
- authentication periodic command [31](#)
- authentication port-control command [33](#)
- authentication priority command [35](#)
- authentication timer command [37](#)
- authentication violation command [39](#)
- auth-fail max-attempts
  - See dot1x auth-fail max-attempts
- auth-fail vlan
  - See dot1x auth-fail vlan
- auth open command [27](#)
- auth order command [29](#)
- authorization state of controlled port [145](#)
- auth timer command [37](#)
- autonegotiation of duplex mode [158](#)
- auto qos voip command [41](#)

**B**

- BackboneFast, for STP [728](#)
- backup interfaces
  - configuring [791](#)
  - displaying [541](#)
- boot (boot loader) command [2](#)
- boot auto-download-sw command [45](#)
- boot config-file command [47](#)
- boot enable-break command [48](#)
- boot helper command [49](#)
- boot helper-config file command [50](#)
- booting
  - Cisco IOS image [53](#)
  - displaying environment variables [481](#)
  - interrupting [45, 48](#)
  - manually [51](#)
- boot loader
  - accessing [1](#)
  - booting
    - Cisco IOS image [2](#)
    - helper image [49](#)
  - directories
    - creating [14](#)
    - displaying a list of [7](#)
    - removing [18](#)
  - displaying
    - available commands [12](#)
    - memory heap utilization [13](#)
    - version [25](#)
  - environment variables
    - described [19](#)
    - displaying settings [19](#)
    - location of [20](#)
    - setting [19](#)
    - unsetting [23](#)
- boot loader (continued)
  - files
    - copying [5](#)
    - deleting [6](#)
    - displaying a list of [7](#)
    - displaying the contents of [4, 15, 22](#)
    - renaming [16](#)
  - file system
    - formatting [10](#)
    - initializing flash [9](#)
    - running a consistency check [11](#)
  - prompt [1](#)
  - resetting the system [17](#)
- boot manual command [51](#)
- boot private-config-file command [52](#)
- boot system command [53](#)
- BPDU filtering, for spanning tree [729, 764](#)
- BPDU guard, for spanning tree [731, 764](#)
- broadcast storm control [782](#)

**C**

- candidate switches
  - See clusters
- cat (boot loader) command [4](#)
- CDP, enabling protocol tunneling for [287](#)
- channel-group command [54](#)
- channel-protocol command [57](#)
- Cisco SoftPhone
  - auto-QoS configuration [41](#)
  - trusting packets sent from [378](#)
- CISP
  - See Client Information Signalling Protocol
- cisp
  - debug platform cisp command [36](#)
- cisp enable command [58](#)
- class command [59](#)
- class-map command [61](#)

- class maps
  - creating [61](#)
  - defining the match criteria [339](#)
  - displaying [487](#)
- class of service
  - See CoS
- clear dot1x command [63](#)
- clear eap sessions command [64](#)
- clear energywise neighbors command [65](#)
- clear errdisable interface [66](#)
- clear ip arp inspection log command [67](#)
- clear ip arp inspection statistics command [68](#)
- clear ipc command [71](#)
- clear ip dhcp snooping database command [69](#)
- clear ipv6 dhcp conflict command [72](#)
- clear l2protocol-tunnel counters command [73](#)
- clear lacp command [74](#)
- clear mac address-table command [75, 76](#)
- clear nmsp statistics command [77](#)
- clear pagp command [78](#)
- clear port-security command [79](#)
- clear spanning-tree counters command [81](#)
- clear spanning-tree detected-protocols command [82](#)
- clear vmmps statistics command [83](#)
- clear vtp counters command [84](#)
- Client Information Signalling Protocol [58, 126, 486, 5, 36](#)
- cluster commander-address command [85](#)
- cluster discovery hop-count command [87](#)
- cluster enable command [88](#)
- cluster holdtime command [89](#)
- cluster member command [90](#)
- cluster outside-interface command [92](#)
- cluster run command [93](#)
- clusters
  - adding candidates [90](#)
  - binding to HSRP group [94](#)
  - building manually [90](#)
- clusters (continued)
  - communicating with
    - devices outside the cluster [92](#)
    - members by using Telnet [440](#)
  - debug messages, display [6](#)
  - displaying
    - candidate switches [490](#)
    - debug messages [6](#)
    - member switches [492](#)
    - status [488](#)
  - hop-count limit for extended discovery [87](#)
  - HSRP standby groups [94](#)
  - redundancy [94](#)
  - SNMP trap [717](#)
- cluster standby-group command [94](#)
- cluster timer command [96](#)
- command modes defined [1](#)
- command switch
  - See clusters
- configuration files
  - password recovery disable considerations [1](#)
  - specifying the name [47, 52](#)
- configuring multiple interfaces [185](#)
- config-vlan mode
  - commands [842](#)
  - description [4](#)
  - entering [841](#)
  - summary [2](#)
- copy (boot loader) command [5](#)
- CoS
  - assigning default value to incoming packets [348](#)
  - assigning to Layer 2 protocol packets [290](#)
  - overriding the incoming value [348](#)
- CoS-to-DSCP map [352](#)
- CPU ASIC statistics, displaying [494](#)
- crashinfo files [178](#)

**D**

- debug auto qos command 2
- debug backup command 4
- debug cisp command 5
- debug cluster command 6
- debug dot1x command 8
- debug dtp command 10
- debug eap command 11
- debug etherchannel command 12
- debug ilpower command 14
- debug interface command 15
- debug ip dhcp snooping command 17
- debug ip igmp filter command 19
- debug ip igmp max-groups command 20
- debug ip igmp snooping command 21
- debug ip verify source packet command 18
- debug lacp command 22
- debug lldp packets command 23
- debug mac-notification command 24
- debug matm command 25
- debug matm move update command 26
- debug monitor command 27
- debug mvrdbg command 29
- debug nmsp command 31
- debug nvram command 32
- debug pagp command 33
- debug platform acl command 34
- debug platform backup interface command 35
- debug platform cisp command 36
- debug platform configuration command 44
- debug platform cpu-queues command 37
- debug platform device-manager command 39
- debug platform dot1x command 40
- debug platform etherchannel command 41
- debug platform fallback-bridging command 42
- debug platform forw-tcam command 43
- debug platform ip arp inspection command 46
- debug platform ip dhcp command 47
- debug platform ip igmp snooping command 48
- debug platform ip multicast command 50
- debug platform ip source-guard command 52
- debug platform ip unicast command 53
- debug platform ip wccp command 55
- debug platform led command 56
- debug platform matm command 57
- debug platform messaging application command 59
- debug platform phy command 60
- debug platform pm command 62
- debug platform port-asic command 64
- debug platform port-security command 65
- debug platform qos-acl-tcam command 66
- debug platform remote-commands command 67
- debug platform resource-manager command 68
- debug platform snmp command 69
- debug platform span command 70
- debug platform supervisor-asic command 71
- debug platform sw-bridge command 72
- debug platform tcam command 73
- debug platform udd command 75
- debug platform vlan command 76
- debug pm command 77
- debug port-security command 79
- debug qos-manager command 80
- debug spanning-tree backbonefast command 83
- debug spanning-tree bpdu command 84
- debug spanning-tree bpdu-opt command 85
- debug spanning-tree command 81
- debug spanning-tree mstp command 86
- debug spanning-tree switch command 88
- debug spanning-tree uplinkfast command 90
- debug sw-vlan command 91
- debug sw-vlan ifs command 93
- debug sw-vlan notification command 95
- debug sw-vlan vtp command 97
- debug udd command 99
- debug vqpc command 101
- define interface-range command 98

- delete (boot loader) command [6](#)
- delete command [100](#)
- deny (ARP access-list configuration) command [102](#)
- deny (IPv6) command [104](#)
- deny command [109](#)
- detect mechanism, causes [169](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [217](#)
  - enabling
    - on a VLAN [224](#)
    - option 82 [215, 217](#)
    - trust on an interface [222](#)
  - error recovery timer [175](#)
  - rate limiting [221](#)
- DHCP snooping binding database
  - binding file, configuring [213](#)
  - bindings
    - adding [211](#)
    - deleting [211](#)
    - displaying [561](#)
  - clearing database agent statistics [69](#)
  - database agent, configuring [213](#)
  - displaying
    - binding entries [561](#)
    - database agent status [564, 566](#)
  - renewing [444](#)
- dir (boot loader) command [7](#)
- directories, deleting [100](#)
- domain name, VTP [867, 871](#)
- dot1x auth-fail max-attempts [120](#)
- dot1x auth-fail vlan [122](#)
- dot1x command [118](#)
- dot1x control-direction command [124](#)
- dot1x credentials (global configuration) command [126](#)
- dot1x critical global configuration command [127](#)
- dot1x critical interface configuration command [129](#)
- dot1x default command [131](#)
- dot1x fallback command [132](#)
- dot1x guest-vlan command [133](#)
- dot1x host-mode command [136](#)
- dot1x initialize command [138](#)
- dot1x mac-auth-bypass command [139](#)
- dot1x max-reauth-req command [141](#)
- dot1x max-req command [142](#)
- dot1x multiple-hosts command [143](#)
- dot1x pae command [144](#)
- dot1x port-control command [145](#)
- dot1x re-authenticate command [147](#)
- dot1x re-authentication command [148](#)
- dot1x reauthentication command [149](#)
- dot1x test eapol-capable command [150](#)
- dot1x test timeout command [151](#)
- dot1x timeout command [152](#)
- dot1x violation-mode command [155](#)
- dropping packets, with ACL matches [6](#)
- drop threshold, Layer 2 protocol tunneling [287](#)
- DSCP-to-CoS map [352](#)
- DSCP-to-DSCP-mutation map [352](#)
- DTP [798](#)
- DTP flap
  - error detection for [169](#)
  - error recovery timer [175](#)
- DTP negotiation [802](#)
- dual-purpose uplink ports
  - selecting the type [342](#)
- duplex command [157](#)
- dynamic-access ports
  - configuring [787](#)
  - restrictions [788](#)
- dynamic ARP inspection
  - ARP ACLs
    - apply to a VLAN [197](#)
    - define [16](#)
    - deny packets [102](#)
    - display [472](#)
    - permit packets [403](#)

## dynamic ARP inspection (continued)

## clear

log buffer [67](#)statistics [68](#)

## display

ARP ACLs [472](#)configuration and operating state [556](#)log buffer [556](#)statistics [556](#)trust state and rate limit [556](#)enable per VLAN [207](#)error detection for [169](#)error recovery timer [175](#)

## log buffer

clear [67](#)configure [201](#)display [556](#)rate-limit incoming ARP packets [199](#)

## statistics

clear [68](#)display [556](#)trusted interface state [203](#)type of packet logged [208](#)validation checks [205](#)dynamic auto VLAN membership mode [797](#)dynamic desirable VLAN membership mode [797](#)

## Dynamic Host Configuration Protocol (DHCP)

See DHCP snooping

## Dynamic Trunking Protocol

See DTP

energywise query command [165](#)environment variables, displaying [481](#)errdisable detect cause command [169](#)errdisable detect cause small-frame command [172](#)errdisable recovery cause small-frame [174](#)errdisable recovery command [175](#)error conditions, displaying [530](#)error disable detection [169](#)error-disabled interfaces, displaying [541](#)

## EtherChannel

assigning Ethernet interface to channel group [54](#)creating port-channel logical interface [183](#)debug EtherChannel/PAGP, display [12](#)debug platform-specific events, display [41](#)displaying [534](#)

enabling Layer 2 protocol tunneling for

LACP [288](#)PAgP [288](#)UDLD [288](#)interface information, displaying [541](#)

## LACP

clearing channel-group information [74](#)debug messages, display [22](#)displaying [603](#)modes [54](#)port priority for hot-standby ports [291](#)restricting a protocol [57](#)system priority [293](#)load-distribution methods [421](#)**E**

## EAP-request/identity frame

maximum number to send [142](#)response time before retransmitting [152](#)encapsulation methods [817](#)energywise (global configuration) command [159, 161](#)energywise domain command [163](#)

## EtherChannel (continued)

## PAgP

- aggregate-port learner [399](#)
- clearing channel-group information [78](#)
- debug messages, display [33](#)
- displaying [663](#)
- error detection for [169](#)
- error recovery timer [175](#)
- learn method [399](#)
- modes [54](#)
- physical-port learner [399](#)
- priority of interface for transmitted traffic [401](#)

Ethernet controller, internal register display [496](#)

Ethernet statistics, collecting [449](#)

exception crashinfo command [178](#)

exit command [856](#)

extended discovery of candidate switches [87](#)

## extended-range VLANs

- and allowed VLAN list [817](#)
- and pruning-eligible list [817](#)
- configuring [841](#)

extended system ID for STP [737](#)

---

**F**

fallback profile command [179](#)

fallback profiles, displaying [537](#)

fan information, displaying [526](#)

file name, VTP [867](#)

files, deleting [100](#)

flash\_init (boot loader) command [9](#)

flexible authentication ordering [29](#)

## Flex Links

- configuring [791](#)
- configuring preferred VLAN [793](#)
- displaying [541](#)

flowcontrol command [181](#)

format (boot loader) command [10](#)

forwarding packets, with ACL matches [6](#)

forwarding results, display [6](#)

frame forwarding information, displaying [6](#)

front-end controller, counter and status information [8](#)

fsck (boot loader) command [11](#)

---

**G**

global configuration mode [2, 3](#)

---

**H**

hardware ACL statistics [468](#)

help (boot loader) command [12](#)

hierarchical policy maps [419](#)

hop-count limit for clusters [87](#)

host connection, port configuration [796](#)

host ports, private VLANs [800](#)

## Hot Standby Router Protocol

See HSRP

## HSRP

binding HSRP group to cluster [94](#)

standby group [94](#)

---

**I**

IEEE 802.1Q trunk ports and native VLANs [858](#)

## IEEE 802.1Q tunnel ports

configuring [797](#)

displaying [511](#)

limitations [798](#)

## IEEE 802.1x

and switchport modes [798](#)

violation error recovery [175](#)

See also port-based authentication

## IEEE 802.1X Port Based Authentication

enabling guest VLAN supplicant [121, 132, 180](#)

- IGMP filters
  - applying [227](#)
  - debug messages, display [19](#)
- IGMP groups, setting maximum [229](#)
- IGMP maximum groups, debugging [20](#)
- IGMP profiles
  - creating [231](#)
  - displaying [569](#)
- IGMP snooping
  - adding ports as a static member of a group [248](#)
  - displaying [570, 575, 577](#)
  - enabling [233](#)
  - enabling the configurable-leave timer [235](#)
  - enabling the Immediate-Leave feature [244](#)
  - flooding query count [241](#)
  - interface topology change notification behavior [243](#)
  - multicast table [573](#)
  - querier [237](#)
  - query solicitation [241](#)
  - report suppression [239](#)
  - switch topology change notification behavior [241](#)
- images
  - See software images
- Immediate-Leave feature, MVR [388](#)
- immediate-leave processing [244](#)
- Immediate-Leave processing, IPv6 [283](#)
- interface configuration mode [2, 4](#)
- interface port-channel command [183](#)
- interface range command [185](#)
- interface-range macros [98](#)
- interfaces
  - assigning Ethernet interface to channel group [54](#)
  - configuring [157](#)
  - configuring multiple [185](#)
  - creating port-channel logical [183](#)
  - debug messages, display [15](#)
  - disabling [713](#)
  - displaying the MAC address table [624](#)
  - restarting [713](#)
- interface speed, configuring [774](#)
- interface vlan command [187](#)
- internal registers, displaying [496, 505](#)
- Internet Group Management Protocol
  - See IGMP
- invalid GBIC
  - error detection for [169](#)
  - error recovery timer [175](#)
- ip access-group command [189](#)
- ip address command [192](#)
- IP addresses, setting [192](#)
- IP address matching [337](#)
- ip admission command [194](#)
- ip admission name proxy http command [195](#)
- ip arp inspection filter vlan command [197](#)
- ip arp inspection limit command [199](#)
- ip arp inspection log-buffer command [201](#)
- ip arp inspection trust command [203](#)
- ip arp inspection validate command [205](#)
- ip arp inspection vlan command [207](#)
- ip arp inspection vlan logging command [208](#)
- IP DHCP snooping
  - See DHCP snooping
- ip dhcp snooping binding command [211](#)
- ip dhcp snooping command [210](#)
- ip dhcp snooping database command [213](#)
- ip dhcp snooping information option allow-untrusted command [217](#)
- ip dhcp snooping information option command [215](#)
- ip dhcp snooping information option format remote-id command [219](#)
- ip dhcp snooping limit rate command [221](#)
- ip dhcp snooping trust command [222](#)
- ip dhcp snooping verify command [223](#)
- ip dhcp snooping vlan command [224](#)
- ip dhcp snooping vlan information option format-type circuit-id string command [225](#)
- ip igmp filter command [227](#)
- ip igmp max-groups command [229, 254, 256](#)
- ip igmp profile command [231](#)



ip igmp snooping command [233](#)  
 ip igmp snooping last-member-query-interval command [235](#)  
 ip igmp snooping querier command [237](#)  
 ip igmp snooping report-suppression command [239](#)  
 ip igmp snooping tcen command [241](#)  
 ip igmp snooping tcen flood command [243](#)  
 ip igmp snooping vlan immediate-leave command [244](#)  
 ip igmp snooping vlan mrouter command [246](#)  
 ip igmp snooping vlan static command [248](#)  
 IP multicast addresses [385](#)  
 IP phones  
     auto-QoS configuration [41](#)  
     trusting packets sent from [378](#)  
 IP-precedence-to-DSCP map [352](#)  
 ip source binding command [250](#)  
 IP source guard  
     disabling [258](#)  
     displaying  
         binding entries [579](#)  
         configuration [581](#)  
         dynamic binding entries only [561](#)  
     enabling [258](#)  
     static IP source bindings [250](#)  
 ip ssh command [252](#)  
 IPv6 access list, deny conditions [104](#)  
 ipv6 access-list command [259](#)  
 ipv6 address dhcp command [262](#)  
 ipv6 dhcp client request vendor command [263](#)  
 ipv6 dhcp ping packets command [264](#)  
 ipv6 dhcp pool command [266](#)  
 ipv6 dhcp server command [269](#)  
 ipv6 mld snooping command [271](#)  
 ipv6 mld snooping last-listener-query count command [273](#)  
 ipv6 mld snooping last-listener-query-interval command [275](#)  
 ipv6 mld snooping listener-message-suppression command [277](#)  
 ipv6 mld snooping robustness-variable command [279](#)

ipv6 mld snooping tcen command [281](#)  
 ipv6 mld snooping vlan command [283](#)  
 IPv6 SDM template [450](#)  
 ipv6 traffic-filter command [285](#)  
 ip verify source command [258](#)

---

## J

jumbo frames  
     See MTU

---

## L

l2protocol-tunnel command [287](#)  
 l2protocol-tunnel cos command [290](#)  
 LACP  
     See EtherChannel  
 lacp port-priority command [291](#)  
 lacp system-priority command [293](#)  
 Layer 2 mode, enabling [785](#)  
 Layer 2 protocol ports, displaying [600](#)  
 Layer 2 protocol-tunnel  
     error detection for [169](#)  
     error recovery timer [175](#)  
 Layer 2 protocol tunnel counters [73](#)  
 Layer 2 protocol tunneling error recovery [288](#)  
 Layer 2 traceroute  
     IP addresses [832](#)  
     MAC addresses [829](#)  
 Layer 3 mode, enabling [785](#)  
 line configuration mode [2, 5](#)  
 Link Aggregation Control Protocol  
     See EtherChannel  
 link flap  
     error detection for [169](#)  
     error recovery timer [175](#)  
 link state group command [299](#)  
 link state track command [301](#)

load-distribution methods for EtherChannel [421](#)  
 location (global configuration) command [295](#)  
 location (interface configuration) command [297](#)  
 logging event command [302](#)  
 logging event power-inline-status command [303](#)  
 logging file command [304](#)  
 logical interface [183](#)  
 loopback error  
   detection for [169](#)  
   recovery timer [175](#)  
 loop guard, for spanning tree [739, 743](#)

## M

mac access-group command [306](#)  
 MAC access-groups, displaying [612](#)  
 MAC access list configuration mode [308](#)  
 mac access-list extended command [308](#)  
 MAC access lists [109](#)  
 MAC addresses  
   disabling MAC address learning per VLAN [311](#)  
   displaying  
     aging time [618](#)  
     all [616](#)  
     dynamic [622](#)  
     MAC address-table move updates [627](#)  
     notification settings [626, 629](#)  
     number of addresses in a VLAN [620](#)  
     per interface [624](#)  
     per VLAN [633](#)  
     static [631](#)  
     static and dynamic entries [614](#)  
   dynamic  
     aging time [310](#)  
     deleting [75](#)  
     displaying [622](#)  
   enabling MAC address notification [315](#)  
   enabling MAC address-table move update [313](#)  
   matching [337](#)  
 MAC addresses (continued)  
   static  
     adding and removing [317](#)  
     displaying [631](#)  
     dropping on an interface [318](#)  
   tables [616](#)  
 MAC address notification, debugging [24](#)  
 mac address-table aging-time [306, 337](#)  
 mac address-table aging-time command [310](#)  
 mac address-table learning command [311](#)  
 mac address-table move update command [313](#)  
 mac address-table notification command [315](#)  
 mac address-table static command [317](#)  
 mac address-table static drop command [318](#)  
 macro apply command [320](#)  
 macro auto execute command [323](#)  
 macro auto global processing command [328](#)  
 macro description command [330](#)  
 macro global command [331](#)  
 macro global description command [334](#)  
 macro name command [335](#)  
 macros  
   adding a description [330](#)  
   adding a global description [334](#)  
   applying [331](#)  
   creating [335](#)  
   displaying [665](#)  
   interface range [98, 185](#)  
   specifying parameter values [331](#)  
   tracing [331](#)  
 maps  
   QoS  
     defining [352](#)  
     displaying [643](#)  
   VLAN  
     creating [853](#)  
     defining [337](#)  
     displaying [702](#)  
 match (access-map configuration) command [337](#)

- match (class-map configuration) command [339](#)
- maximum transmission unit
  - See MTU
- mdix auto command [341](#)
- media-type command [342](#)
- member switches
  - See clusters
- memory (boot loader) command [13](#)
- mkdir (boot loader) command [14](#)
- MLD snooping
  - configuring [277, 279](#)
  - configuring queries [273, 275](#)
  - configuring topology change notification [281](#)
  - displaying [590, 592, 594, 596](#)
  - enabling [271](#)
- MLD snooping on a VLAN, enabling [283](#)
- mls qos aggregate-policer command [346](#)
- mls qos command [344](#)
- mls qos cos command [348](#)
- mls qos dscp-mutation command [350](#)
- mls qos map command [352](#)
- mls qos queue-set output buffers command [356](#)
- mls qos queue-set output threshold command [358](#)
- mls qos rewrite ip dscp command [360](#)
- mls qos srr-queue input bandwidth command [362](#)
- mls qos srr-queue input buffers command [364](#)
- mls qos-srr-queue input cos-map command [366](#)
- mls qos srr-queue input dscp-map command [368](#)
- mls qos srr-queue input priority-queue command [370](#)
- mls qos srr-queue input threshold command [372](#)
- mls qos-srr-queue output cos-map command [374](#)
- mls qos srr-queue output dscp-map command [376](#)
- mls qos trust command [378](#)
- mls qos vlan-based command [380](#)
- mode, MVR [385](#)
- Mode button, and password recovery [454](#)
- modes, commands [1](#)
- monitor session command [381](#)
- more (boot loader) command [15](#)
- MSTP
  - displaying [683](#)
  - interoperability [82](#)
  - link type [741](#)
  - MST region
    - aborting changes [747](#)
    - applying changes [747](#)
    - configuration name [747](#)
    - configuration revision number [747](#)
    - current or pending display [747](#)
    - displaying [683](#)
    - MST configuration mode [747](#)
    - VLANs-to-instance mapping [747](#)
  - path cost [749](#)
  - protocol mode [745](#)
  - restart protocol migration process [82](#)
  - root port
    - loop guard [739](#)
    - preventing from becoming designated [739](#)
    - restricting which can be root [739](#)
    - root guard [739](#)
  - root switch
    - affects of extended system ID [737](#)
    - hello-time [752, 760](#)
    - interval between BPDU messages [753](#)
    - interval between hello BPDU messages [752, 760](#)
    - max-age [753](#)
    - maximum hop count before discarding BPDU [754](#)
    - port priority for selection of [756](#)
    - primary or secondary [760](#)
    - switch priority [759](#)
  - state changes
    - blocking to forwarding state [766](#)
    - enabling BPDU filtering [729, 764](#)
    - enabling BPDU guard [731, 764](#)
    - enabling Port Fast [764, 766](#)
    - forward-delay time [751](#)
    - length of listening and learning states [751](#)

## MSTP (continued)

- rapid transition to forwarding [741](#)

- shutting down Port Fast-enabled ports [764](#)

- state information display [682](#)

## MTU

- configuring size [826](#)

- displaying global setting [691](#)

- multicast group address, MVR [388](#)

- multicast groups, MVR [386](#)

## Multicast Listener Discovery

- See MLD

- multicast router learning method [246](#)

- multicast router ports, configuring [246](#)

- multicast router ports, IPv6 [283](#)

- multicast storm control [782](#)

- multicast VLAN, MVR [385](#)

- multicast VLAN registration

- See MVR

## Multiple Spanning Tree Protocol

- See MSTP

## MVR

- and address aliasing [386](#)

- configuring [385](#)

- configuring interfaces [388](#)

- debug messages, display [29](#)

- displaying [652](#)

- displaying interface information [654](#)

- members, displaying [656](#)

- mvr (global configuration) command [385](#)

- mvr (interface configuration) command [388](#)

- mvr vlan group command [389](#)

**N**

- native VLANs [817](#)

- native VLAN tagging [858](#)

- Network Admission Control Software Configuration Guide [194, 196](#)

- network-policy (global configuration) command [392](#)

- network-policy command [391](#)

- network-policy profile (network-policy configuration) command [394](#)

- nmosp attachment suppress command [398](#)

- nmosp command [396](#)

- nonegotiate, speed [774](#)

- nonegotiating DTP messaging [802](#)

- non-IP protocols

- denying [109](#)

- forwarding [411](#)

- non-IP traffic access lists [308](#)

- non-IP traffic forwarding

- denying [109](#)

- permitting [411](#)

- normal-range VLANs [841, 847](#)

- no vlan command [841, 851](#)

**O**

- online diagnostics

- displaying

- configured boot-up coverage level [509](#)

- current scheduled tasks [509](#)

- event logs [509](#)

- supported test suites [509](#)

- test ID [509](#)

- test results [509](#)

- test statistics [509](#)

- global configuration mode

- clearing health monitoring diagnostic test schedule [67](#)

- clearing test-based testing schedule [115](#)

- setting health monitoring diagnostic testing [67](#)

- setting test-based testing [115](#)

- setting up health monitoring diagnostic test schedule [67](#)

- setting up test-based testing [115](#)

- health monitoring diagnostic tests, configuring [112](#)

## online diagnostics (continued)

- scheduled switchover

- disabling [115](#)

- enabling [115](#)

- scheduling

- enabling [115](#)

- removing [115](#)

- test interval, setting [115](#)

**P**

## PAGP

- See EtherChannel

pagp learn-method command [399](#)

pagp port-priority command [401](#)

password, VTP [867, 871](#)

password-recovery mechanism, enabling and disabling [454](#)

permit (ARP access-list configuration) command [403](#)

permit (IPv6) command [405](#)

permit (MAC access-list configuration) command [411](#)

per-VLAN spanning-tree plus

- See STP

physical-port learner [399](#)

PID, displaying [555](#)

PIM-DVMRP, as multicast router learning method [246](#)

## PoE

- configuring the power budget [426](#)

- configuring the power management mode [423](#)

- displaying controller register values [503](#)

- displaying power management information [673](#)

- logging of status [303](#)

police aggregate command [416](#)

police command [414](#)

policed-DSCP map [352](#)

policy-map command [418](#)

## policy maps

- applying to an interface [456, 461](#)

- creating [418](#)

- displaying [668](#)

- hierarchical [419](#)

- policers

- displaying [636](#)

- for a single class [414](#)

- for multiple classes [346, 416](#)

- policed-DSCP map [352](#)

- traffic classification

- defining the class [59](#)

- defining trust states [834](#)

- setting DSCP or IP precedence values [459](#)

## Port Aggregation Protocol

- See EtherChannel

## port-based authentication

- AAA method list [3](#)

- configuring violation modes [155](#)

- debug messages, display [8](#)

- enabling IEEE 802.1x

- globally [118](#)

- per interface [145](#)

- guest VLAN [133](#)

- host modes [136](#)

- IEEE 802.1x AAA accounting methods [1](#)

- initialize an interface [138, 151](#)

- MAC authentication bypass [139](#)

- manual control of authorization state [145](#)

- PAE as authenticator [144](#)

- periodic re-authentication

- enabling [149](#)

- time between attempts [152](#)

- quiet period between failed authentication exchanges [152](#)

- re-authenticating IEEE 802.1x-enabled ports [147](#)

- resetting configurable IEEE 802.1x parameters [131](#)

- switch-to-authentication server retransmission time [152](#)

port-based authentication (continued)

- switch-to-client frame-retransmission number [141 to 142](#)
- switch-to-client retransmission time [152](#)
- test for IEEE 802.1x readiness [150](#)

port-channel load-balance command [421](#)

Port Fast, for spanning tree [766](#)

port ranges, defining [98](#)

ports, debugging [77](#)

ports, protected [815](#)

port security

- aging [809](#)
- debug messages, display [79](#)
- enabling [804](#)
- violation error recovery [175](#)

port trust states for QoS [378](#)

port types, MVR [388](#)

power information, displaying [526](#)

power inline command [423](#)

power inline consumption command [426](#)

Power over Ethernet

- See PoE

priority-queue command [428](#)

private-vlan command [430](#)

private-vlan mapping command [433](#)

private VLANs

- association [813](#)
- configuring [430](#)
- configuring ports [800](#)
- displaying [697](#)
- host ports [800](#)
- mapping
  - configuring [813](#)
  - displaying [541](#)
- promiscuous ports [800](#)

privileged EXEC mode [2, 3](#)

product identification information, displaying [555](#)

promiscuous ports, private VLANs [800](#)

protected ports, displaying [546](#)

pruning

- VLANs [817](#)
- VTP
  - displaying interface information [541](#)
  - enabling [867, 871](#)

pruning-eligible VLAN list [819](#)

PVST+

- See STP

---

## Q

QoS

auto-QoS

- configuring [41](#)
- debug messages, display [2](#)
- displaying [477](#)

class maps

- creating [61](#)
- defining the match criteria [339](#)
- displaying [487](#)

defining the CoS value for an incoming packet [348](#)

displaying configuration information [477, 635](#)

DSCP transparency [360](#)

DSCP trusted ports

- applying DSCP-to-DSCP-mutation map to [350](#)
- defining DSCP-to-DSCP-mutation map [352](#)

egress queues

- allocating buffers [356](#)
- defining the CoS output queue threshold map [374](#)
- defining the DSCP output queue threshold map [376](#)
- displaying buffer allocations [639](#)
- displaying CoS output queue threshold map [643](#)
- displaying DSCP output queue threshold map [643](#)
- displaying queueing strategy [639](#)
- displaying queue-set settings [646](#)
- enabling bandwidth shaping and scheduling [778](#)

## QoS (continued)

- enabling bandwidth sharing and scheduling [780](#)
- limiting the maximum output on a port [776](#)
- mapping a port to a queue-set [435](#)
- mapping CoS values to a queue and threshold [374](#)
- mapping DSCP values to a queue and threshold [376](#)
- setting maximum and reserved memory allocations [358](#)
- setting WTD thresholds [358](#)
- enabling [344](#)
- ingress queues
  - allocating buffers [364](#)
  - assigning SRR scheduling weights [362](#)
  - defining the CoS input queue threshold map [366](#)
  - defining the DSCP input queue threshold map [368](#)
  - displaying buffer allocations [639](#)
  - displaying CoS input queue threshold map [643](#)
  - displaying DSCP input queue threshold map [643](#)
  - displaying queueing strategy [639](#)
  - displaying settings for [637](#)
  - enabling the priority queue [370](#)
  - mapping CoS values to a queue and threshold [366](#)
  - mapping DSCP values to a queue and threshold [368](#)
  - setting WTD thresholds [372](#)
- maps
  - defining [352, 366, 368, 374, 376](#)
  - displaying [643](#)
- policy maps
  - applying an aggregate policer [416](#)
  - applying to an interface [456, 461](#)
  - creating [418](#)
  - defining policers [346, 414](#)
  - displaying policers [636](#)
  - displaying policy maps [668](#)
  - hierarchical [419](#)

## QoS (continued)

- policed-DSCP map [352](#)
- setting DSCP or IP precedence values [459](#)
- traffic classifications [59](#)
- trust states [834](#)
- port trust states [378](#)
- queues, enabling the expedite [428](#)
- statistics
  - in-profile and out-of-profile packets [639](#)
  - packets enqueued or dropped [639](#)
  - sent and received CoS values [639](#)
  - sent and received DSCP values [639](#)
- trusted boundary for IP phones [378](#)
- VLAN-based [380](#)
- quality of service
  - See QoS
- querytime, MVR [385](#)
- queue-set command [435](#)

---

**R**

- radius-server dead-criteria command [436](#)
- radius-server host command [438](#)
- rapid per-VLAN spanning-tree plus
  - See STP
- rapid PVST+
  - See STP
- rcommand command [440](#)
- re-authenticating IEEE 802.1x-enabled ports [147](#)
- re-authentication
  - periodic [149](#)
  - time between attempts [152](#)
- receiver ports, MVR [388](#)
- receiving flow-control packets [181](#)
- recovery mechanism
  - causes [175](#)
  - display [66, 483, 528, 532](#)
  - timer interval [176](#)
- redundancy for cluster switches [94](#)

- remote-span command [442](#)
  - Remote Switched Port Analyzer
    - See RSPAN
  - rename (boot loader) command [16](#)
  - renew ip dhcp snooping database command [444](#)
  - reset (boot loader) command [17](#)
  - reset command [856](#)
  - resource templates, displaying [675](#)
  - restricted VLAN
    - See dot1x auth-fail vlan
  - rmdir (boot loader) command [18](#)
  - rmon collection stats command [449](#)
  - root guard, for spanning tree [739](#)
  - routed ports
    - IP addresses on [193](#)
    - number supported [193](#)
  - RSPAN
    - configuring [381](#)
    - displaying [649](#)
    - filter RSPAN traffic [381](#)
    - remote-span command [442](#)
    - sessions
      - displaying [649](#)
- 
- S**
- scheduled switchover
    - disabling [115](#)
    - enabling [115](#)
  - sdm prefer command [450](#)
  - SDM templates
    - allowed resources [451](#)
    - displaying [675](#)
    - dual IPv4 and IPv6 [450](#)
  - secure ports, limitations [806](#)
  - sending flow-control packets [181](#)
  - service password-recovery command [454](#)
  - service-policy command [456](#)
  - set (boot loader) command [19](#)
  - set command [459](#)
  - setup command [461](#)
  - setup express command [464](#)
  - shell trigger command [466](#)
  - show access-lists command [468](#)
  - show archive status command [471](#)
  - show arp access-list command [472](#)
  - show authentication command [473](#)
  - show auto qos command [477](#)
  - show boot command [481](#)
  - show cable-diagnostics tdr command [483](#)
  - show changes command [856](#)
  - show cisp command [486](#)
  - show class-map command [487](#)
  - show cluster candidates command [490](#)
  - show cluster command [488](#)
  - show cluster members command [492](#)
  - show controllers cpu-interface command [494](#)
  - show controllers ethernet-controller command [496](#)
  - show controllers power inline command [503](#)
  - show controllers team command [505](#)
  - show controller utilization command [507](#)
  - show current command [856](#)
  - show dot1q-tunnel command [511](#)
  - show dot1x command [512](#)
  - show dtp [517](#)
  - show eap command [519](#)
  - show energywise command [522](#)
  - show env command [526](#)
  - show errdisable detect command [528](#)
  - show errdisable flap-values command [530](#)
  - show errdisable recovery command [532](#)
  - show etherchannel command [534](#)
  - show fallback profile command [537](#)
  - show flowcontrol command [539](#)
  - show interfaces command [541](#)
  - show interfaces counters command [552](#)
  - show inventory command [555](#)
  - show ip arp inspection command [556](#)



- show ipc command [583](#)
- show ip dhcp snooping binding command [561](#)
- show ip dhcp snooping command [560](#)
- show ip dhcp snooping database command [564, 566](#)
- show ip igmp profile command [569](#)
- show ip igmp snooping address command [592](#)
- show ip igmp snooping command [570, 590](#)
- show ip igmp snooping groups command [573](#)
- show ip igmp snooping mrouter command [575, 594](#)
- show ip igmp snooping querier command [577, 596](#)
- show ip source binding command [579](#)
- show ipv6 access-list command [587](#)
- show ipv6 dhcp conflict command [589](#)
- show ipv6 route updated [598](#)
- show ip verify source command [581](#)
- show l2protocol-tunnel command [600](#)
- show lacp command [603](#)
- show link state group command [610](#)
- show location [607](#)
- show mac access-group command [612](#)
- show mac address-table address command [616](#)
- show mac address-table aging time command [618](#)
- show mac address-table command [614](#)
- show mac address-table count command [620](#)
- show mac address-table dynamic command [622](#)
- show mac address-table interface command [624](#)
- show mac address-table learning command [626](#)
- show mac address-table move update command [627](#)
- show mac address-table notification command [76, 629, 26](#)
- show mac address-table static command [631](#)
- show mac address-table vlan command [633](#)
- show mls qos aggregate-policer command [636](#)
- show mls qos command [635](#)
- show mls qos input-queue command [637](#)
- show mls qos interface command [639](#)
- show mls qos maps command [643](#)
- show mls qos queue-set command [646](#)
- show mls qos vlan command [648](#)
- show monitor command [649](#)
- show mvr command [652](#)
- show mvr interface command [654](#)
- show mvr members command [656](#)
- show network-policy profile command [658](#)
- show nmsp command [660](#)
- show pagp command [663](#)
- show parser macro command [665](#)
- show platform acl command [2](#)
- show platform backup interface command [3](#)
- show platform configuration command [4](#)
- show platform etherchannel command [5](#)
- show platform forward command [6](#)
- show platform frontend-controller command [8](#)
- show platform igmp snooping command [9](#)
- show platform ip multicast command [11](#)
- show platform ip unicast command [12](#)
- show platform ipv6 unicast command [17](#)
- show platform ip wccp command [16](#)
- show platform layer4op command [19](#)
- show platform mac-address-table command [20](#)
- show platform messaging command [21](#)
- show platform monitor command [22](#)
- show platform mvr table command [23](#)
- show platform pm command [24](#)
- show platform port-asic command [25](#)
- show platform port-security command [30](#)
- show platform qos command [31](#)
- show platform resource-manager command [32](#)
- show platform snmp counters command [34](#)
- show platform spanning-tree command [35](#)
- show platform stack manager command [37](#)
- show platform stp-instance command [36](#)
- show platform team command [38](#)
- show platform vlan command [41](#)
- show policy-map command [668](#)
- show port security command [670](#)
- show power inline command [673](#)
- show proposed command [856](#)
- show sdm prefer command [675](#)

- show setup express command [678](#)
- show shell command [679](#)
- show spanning-tree command [682](#)
- show storm-control command [688](#)
- show system mtu command [691](#)
- show trust command [834](#)
- show udd command [692](#)
- show version command [695](#)
- show vlan access-map command [702](#)
- show vlan command [697](#)
- show vlan command, fields [699](#)
- show vlan filter command [704](#)
- show vmps command [705](#)
- show vtp command [708](#)
- shutdown command [713](#)
- shutdown threshold, Layer 2 protocol tunneling [287](#)
- shutdown vlan command [714](#)
- small violation-rate command [715](#)
- Smartports macros
  - See macros
- SNMP host, specifying [721](#)
- SNMP informs, enabling the sending of [717](#)
- snmp-server enable traps command [717](#)
- snmp-server host command [721](#)
- snmp trap mac-notification command [726](#)
- SNMP traps
  - enabling MAC address notification trap [726](#)
  - enabling the MAC address notification feature [315](#)
  - enabling the sending of [717](#)
- SoftPhone
  - See Cisco SoftPhone
- software images
  - deleting [100](#)
  - downloading [8](#)
  - upgrading [8](#)
  - uploading [14](#)
- software version, displaying [695](#)
- source ports, MVR [388](#)
- SPAN
  - configuring [381](#)
  - debug messages, display [27](#)
  - displaying [649](#)
  - filter SPAN traffic [381](#)
  - sessions
    - add interfaces to [381](#)
    - displaying [649](#)
    - start new [381](#)
  - spanning-tree backbonefast command [728](#)
  - spanning-tree bpdupfilter command [729](#)
  - spanning-tree bpduguard command [731](#)
  - spanning-tree cost command [733](#)
  - spanning-tree etherchannel command [735](#)
  - spanning-tree extend system-id command [737](#)
  - spanning-tree guard command [739](#)
  - spanning-tree link-type command [741](#)
  - spanning-tree loopguard default command [743](#)
  - spanning-tree mode command [745](#)
  - spanning-tree mst configuration command [747](#)
  - spanning-tree mst cost command [749](#)
  - spanning-tree mst forward-time command [751](#)
  - spanning-tree mst hello-time command [752](#)
  - spanning-tree mst max-age command [753](#)
  - spanning-tree mst max-hops command [754](#)
  - spanning-tree mst port-priority command [756](#)
  - spanning-tree mst pre-standard command [758](#)
  - spanning-tree mst priority command [759](#)
  - spanning-tree mst root command [760](#)
  - spanning-tree portfast (global configuration) command [764](#)
  - spanning-tree portfast (interface configuration) command [766](#)
  - spanning-tree port-priority command [762](#)
- Spanning Tree Protocol
  - See STP
  - spanning-tree transmit hold-count command [768](#)
  - spanning-tree uplinkfast command [769](#)
  - spanning-tree vlan command [771](#)

- speed command [774](#)
- srr-queue bandwidth limit command [776](#)
- srr-queue bandwidth share command [780](#)
- SSH, configuring version [252](#)
- static-access ports, configuring [787](#)
- statistics, Ethernet group [449](#)
- sticky learning, enabling [804](#)
- storm-control command [782](#)
- STP
  - BackboneFast [728](#)
  - counters, clearing [81](#)
  - debug messages, display
    - BackboneFast events [83](#)
    - MSTP [86](#)
    - optimized BPDUs handling [85](#)
    - spanning-tree activity [81](#)
    - switch shim [88](#)
    - transmitted and received BPDUs [84](#)
    - UplinkFast [90](#)
  - detection of indirect link failures [728](#)
  - enabling protocol tunneling for [287](#)
  - EtherChannel misconfiguration [735](#)
  - extended system ID [737](#)
  - path cost [733](#)
  - protocol modes [745](#)
  - root port
    - accelerating choice of new [769](#)
    - loop guard [739](#)
    - preventing from becoming designated [739](#)
    - restricting which can be root [739](#)
    - root guard [739](#)
    - UplinkFast [769](#)
  - root switch
    - affects of extended system ID [737, 772](#)
    - hello-time [771](#)
    - interval between BPDU messages [771](#)
    - interval between hello BPDU messages [771](#)
    - max-age [771](#)
    - port priority for selection of [762](#)
- STP (continued)
  - primary or secondary [771](#)
  - switch priority [771](#)
  - state changes
    - blocking to forwarding state [766](#)
    - enabling BPDU filtering [729, 764](#)
    - enabling BPDU guard [731, 764](#)
    - enabling Port Fast [764, 766](#)
    - enabling timer to recover from error state [175](#)
    - forward-delay time [771](#)
    - length of listening and learning states [771](#)
    - shutting down Port Fast-enabled ports [764](#)
  - state information display [682](#)
  - VLAN options [759, 771](#)
- SVIs, creating [187](#)
- SVI status calculation [789](#)
- Switched Port Analyzer
  - See SPAN
- switching characteristics
  - modifying [785](#)
  - returning to interfaces [785](#)
- switchport access command [787](#)
- switchport autostate exclude command [789](#)
- switchport backup interface command [791](#)
- switchport block command [795](#)
- switchport command [785](#)
- switchport host command [796](#)
- switchport mode command [797](#)
- switchport mode private-vlan command [800](#)
- switchport nonegotiate command [802](#)
- switchport port-security aging command [809](#)
- switchport port-security command [804](#)
- switchport priority extend command [811](#)
- switchport private-vlan command [813](#)
- switchport protected command [815](#)
- switchports, displaying [541](#)
- switchport trunk command [817](#)
- switchport voice vlan command [821, 822](#)
- system env temperature threshold yellow command [824](#)

system message logging [303](#)  
 system message logging, save message to flash [304](#)  
 system mtu command [826](#)  
 system resource templates [450](#)

---

## T

tar files, creating, listing, and extracting [11](#)  
 TDR, running [828](#)  
 Telnet, using to communicate to cluster switches [440](#)  
 temperature information, displaying [526](#)  
 templates, system resources [450](#)  
 test cable-diagnostics tdr command [828](#)  
 test relay [829](#)  
 traceroute mac command [829](#)  
 traceroute mac ip command [832](#)  
 trunking, VLAN mode [797](#)  
 trunk mode [797](#)  
 trunk ports [797](#)  
 trunks, to non-DTP device [798](#)  
 trusted boundary for QoS [378](#)  
 trusted port states for QoS [378](#)  
 tunnel ports, Layer 2 protocol, displaying [600](#)  
 type (boot loader) command [22](#)

---

## U

### UDLD

aggressive mode [836, 838](#)  
 debug messages, display [99](#)  
 enable globally [836](#)  
 enable per interface [838](#)  
 error recovery timer [175](#)  
 message timer [836](#)  
 normal mode [836, 838](#)  
 reset a shutdown interface [840](#)  
 status [692](#)

udld command [836](#)

udld port command [838](#)  
 udld reset command [840](#)  
 unicast storm control [782](#)  
 UniDirectional Link Detection

See UDLD

unknown multicast traffic, preventing [795](#)  
 unknown unicast traffic, preventing [795](#)  
 unset (boot loader) command [23](#)  
 upgrading  
   software images  
     downloading [8](#)  
     monitoring status of [471](#)  
 UplinkFast, for STP [769](#)  
 user EXEC mode [2, 3](#)

---

## V

version (boot loader) command [25](#)  
 vlan (global configuration) command [841](#)  
 vlan (VLAN configuration) command [847](#)  
 vlan access-map command [853](#)  
 VLAN access map configuration mode [853](#)  
 VLAN access maps  
   actions [6](#)  
   displaying [702](#)  
 VLAN-based QoS [380](#)  
 VLAN configuration  
   rules [844, 849](#)  
   saving [841, 851](#)  
 VLAN configuration mode  
   commands  
     VLAN [847](#)  
     VTP [871](#)  
   description [5](#)  
   entering [855](#)  
   summary [2](#)  
 vlan database command [855](#)  
 vlan dot1q tag native command [858](#)  
 vlan filter command [860](#)

- VLAN filters, displaying [704](#)
- VLAN ID range [841, 847](#)
- VLAN maps
  - applying [860](#)
  - creating [853](#)
  - defining [337](#)
  - displaying [702](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [841](#)
  - configuring [841, 847](#)
  - debug messages, display
    - ISL [95](#)
    - VLAN IOS file system error tests [93](#)
    - VLAN manager activity [91](#)
    - VTP [97](#)
  - displaying configurations [697](#)
  - enabling guest VLAN supplicant [121, 132, 180](#)
  - extended-range [841](#)
  - MAC addresses
    - displaying [633](#)
    - number of [620](#)
  - media types [844, 849](#)
  - normal-range [841, 847](#)
  - private [800](#)
    - configuring [430](#)
    - displaying [697](#)
    - See also private VLANs
  - restarting [714](#)
  - saving the configuration [841](#)
  - shutting down [714](#)
  - SNMP traps for VTP [719, 723](#)
  - suspending [714](#)
  - variables [847](#)
- VLAN Trunking Protocol
  - See VTP
- VMPS
  - configuring servers [865](#)
  - displaying [705](#)
  - error recovery timer [176](#)
  - reconfirming dynamic VLAN assignments [862](#)
  - vmmps reconfirm (global configuration) command [863](#)
  - vmmps reconfirm (privileged EXEC) command [862](#)
  - vmmps retry command [864](#)
  - vmmps server command [865](#)
  - voice VLAN
    - configuring [821, 822](#)
    - setting port priority [811](#)
- VQP
  - and dynamic-access ports [788](#)
  - clearing client statistics [83](#)
  - displaying information [705](#)
  - per-server retry count [864](#)
  - reconfirmation interval [863](#)
  - reconfirming dynamic VLAN assignments [862](#)
- VTP
  - changing characteristics [867](#)
  - clearing pruning counters [84](#)
  - configuring
    - domain name [867, 871](#)
    - file name [867](#)
    - mode [867, 871](#)
    - password [867, 871](#)
  - counters display fields [709](#)
  - displaying information [708](#)
  - enabling
    - pruning [867, 871](#)
    - tunneling for [287](#)
    - Version 2 [867, 871](#)
  - mode [867, 871](#)
  - pruning [867, 871](#)
  - saving the configuration [841, 851](#)
  - statistics [708](#)
  - status [708](#)
  - status display fields [711](#)

vtp (global configuration) command [867](#)

vtp (VLAN configuration) command [871](#)