



---

## Numerics

### 10-Gigabit Ethernet interfaces

configuration guidelines [11-13](#)

defined [11-4](#)

### 802.1D

See STP

### 802.1Q

and trunk ports [11-3](#)

configuration limitations [13-18](#)

encapsulation [13-16](#)

native VLAN for untagged traffic [13-23](#)

### 802.1s

See MSTP

### 802.1w

See RSTP

### 802.1x

See port-based authentication

### 802.1z flow control [11-16](#)

### 802.3ad

See EtherChannel

### 802.3af

See PoE [1-9](#)

---

## A

abbreviating commands [2-3](#)

ABRs [31-25](#)

AC (command switch) [6-10, 6-20](#)

access-class command [28-20](#)

access control entries

See ACEs

access-denied response, VMPS [13-28](#)

access groups

applying ACLs to interfaces [28-21](#)

IP [28-21](#)

Layer 2 [28-21](#)

Layer 3 [28-21](#)

accessing

clusters, switch [6-13](#)

command switches [6-11](#)

member switches [6-13](#)

stack members [5-15](#)

switch clusters [6-13](#)

access lists

See ACLs

access ports

defined [11-2](#)

in switch clusters [6-9](#)

accounting

with RADIUS [9-28](#)

with TACACS+ [9-11, 9-17](#)

ACEs

and QoS [29-7](#)

defined [28-2](#)

Ethernet [28-2](#)

IP [28-2](#)

ACLs

ACEs [28-2](#)

any keyword [28-13](#)

## ACLs (continued)

## applying

- on bridged packets 28-39
- on multicast packets 28-40
- on routed packets 28-40
- on switched packets 28-38
- time ranges to 28-17
- to an interface 28-20
- to QoS 29-7

## classifying traffic for QoS 29-37

## comments in 28-19

## compiling 28-22

## configuring with VLAN maps 28-37

## defined 28-1, 28-7

## examples of 28-22, 29-37

## extended IP

- configuring for QoS classification 29-38
- creating 28-11
- matching criteria 28-7

## hardware and software handling 28-22

## host keyword 28-13

## IP

- applying to interface 28-20
- applying to interfaces 28-20
- creating 28-7
- fragments and QoS guidelines 29-29
- implicit deny 28-10, 28-14, 28-16
- implicit masks 28-10
- matching criteria 28-7
- named 28-15
- terminal lines, setting on 28-19
- undefined 28-21
- violations, logging 28-16

## limiting actions 28-38

## logging messages 28-10

## log keyword 28-16

## MAC extended 28-27, 29-39

## matching 28-7, 28-21

## monitoring 28-41

## ACLs (continued)

## named 28-15

## number per QoS class map 29-29

## numbers 28-7

## port 28-2

## precedence of 28-2

## QoS 29-7, 29-37

## resequencing entries 28-15

## router 28-2

## standard IP

## configuring for QoS classification 29-37

## creating 28-9

## matching criteria 28-7

## supported features 28-22

## support for 1-6

## time ranges 28-17

## unsupported features 28-6

## using router ACLs with VLAN maps 28-37

## VLAN maps

## configuration guidelines 28-30

## configuring 28-30

## active router 32-1

## address aliasing 20-2

## addresses

## displaying the MAC address table 7-28

## dynamic

- accelerated aging 16-9
- changing the aging time 7-22
- default aging 16-9
- defined 7-20
- learning 7-21
- removing 7-23

## MAC, discovering 7-28

## multicast

- group address range 33-3
- STP address management 16-9

## static

- adding and removing 7-25
- defined 7-20

- address resolution [7-28, 31-9](#)
- Address Resolution Protocol
  - See ARP
- adjacency tables, with CEF [31-61](#)
- administrative distances
  - defined [31-72](#)
  - OSPF [31-31](#)
  - routing protocol defaults [31-63](#)
- advertisements
  - CDP [22-1](#)
  - RIP [31-20](#)
  - VTP [13-19, 14-3](#)
- aggregate addresses, BGP [31-56](#)
- aggregated ports
  - See EtherChannel
- aggregate policers [29-45](#)
- aggregate policing [1-7](#)
- aggregator template [5-7, 8-1](#)
- aging, accelerating [16-9](#)
- aging time
  - accelerated
    - for MSTP [17-21](#)
    - for STP [16-9, 16-23](#)
  - MAC address table [7-22](#)
  - maximum
    - for MSTP [17-22](#)
    - for STP [16-23](#)
- alarms, RMON [25-3](#)
- allowed-VLAN list [13-21](#)
- area border routers
  - See ABRs
- ARP
  - configuring [31-10](#)
  - defined [1-4, 7-28, 31-9](#)
  - encapsulation [31-11](#)
  - static cache configuration [31-10](#)
  - table
    - address resolution [7-28](#)
    - managing [7-28](#)
- ASBRs [31-25](#)
- AS-path filters, BGP [31-50](#)
- attributes, RADIUS
  - vendor-proprietary [9-31](#)
  - vendor-specific [9-29](#)
- audience [xxxiii](#)
- authentication
  - EIGRP [31-38](#)
  - HSRP [32-9](#)
  - local mode with AAA [9-36](#)
  - NTP associations [7-5](#)
  - RADIUS
    - key [9-21](#)
    - login [9-23](#)
  - See also port-based authentication
  - TACACS+
    - defined [9-11](#)
    - key [9-13](#)
    - login [9-14](#)
- authentication keys, and routing protocols [31-73](#)
- authoritative time source, described [7-2](#)
- authorization
  - with RADIUS [9-27](#)
  - with TACACS+ [9-11, 9-16](#)
- authorized ports with 802.1x [10-4](#)
- autoconfiguration [4-3](#)
- automatic discovery
  - adding member switches [6-18](#)
  - considerations
    - beyond a noncandidate device [6-8](#)
    - brand new switches [6-9](#)
    - connectivity [6-5](#)
    - different VLANs [6-7](#)
    - management VLANs [6-7](#)
    - non-CDP-capable devices [6-6](#)
    - noncluster-capable devices [6-6](#)
    - routed ports [6-8](#)

automatic discovery (continued)  
   creating a cluster standby group [6-20](#)  
   in switch clusters [6-5](#)  
   See also CDP

automatic QoS  
   See QoS

automatic recovery, clusters [6-10](#)  
   See also HSRP

autonegotiation  
   duplex mode [1-3](#)  
   interface configuration guidelines [11-14](#)  
   mismatches [36-12](#)

autonomous system boundary routers  
   See ASBRs

autonomous systems, in BGP [31-44](#)

Auto-RP, described [33-5](#)

autosensing, port speed [1-3](#)

auxiliary VLAN  
   See voice VLAN

availability, features [1-5](#)

---

## B

### BackboneFast

described [18-7](#)  
 disabling [18-17](#)  
 enabling [18-16](#)  
 support for [1-5](#)

### banners

configuring  
   login [7-20](#)  
   message-of-the-day login [7-19](#)

default configuration [7-18](#)

when displayed [7-18](#)

### BGP

aggregate addresses [31-56](#)  
 aggregate routes, configuring [31-56](#)  
 CIDR [31-56](#)  
 clear commands [31-59](#)

### BGP (continued)

community filtering [31-52](#)  
 configuring neighbors [31-54](#)  
 default configuration [31-42](#)  
 described [31-41](#)  
 enabling [31-44](#)  
 monitoring [31-59](#)  
 multipath support [31-47](#)  
 neighbors, types of [31-44](#)  
 path selection [31-47](#)  
 peers, configuring [31-54](#)  
 prefix filtering [31-51](#)  
 resetting sessions [31-46](#)  
 route dampening [31-58](#)  
 route maps [31-49](#)  
 route reflectors [31-57](#)  
 routing domain confederation [31-56](#)  
 show commands [31-59](#)  
 supernets [31-56](#)  
 support for [1-8](#)  
 Version 4 [31-41](#)

binding cluster group and HSRP group [32-11](#)

blocking packets [21-6](#)

### booting

boot loader, function of [4-2](#)  
 boot process [4-1](#)  
 manually [4-13](#)  
 specific image [4-13](#)

### boot loader

accessing [4-14](#)  
 described [4-2](#)  
 environment variables [4-14](#)  
 prompt [4-14](#)  
 trap-door mechanism [4-2](#)

bootstrap router (BSR), described [33-5](#)

### Border Gateway Protocol

See BGP

## BPDU

- error-disabled state [18-3](#)
- filtering [18-3](#)
- RSTP format [17-10](#)

## BPDU filtering

- described [18-3](#)
- disabling [18-15](#)
- enabling [18-14](#)
- support for [1-5](#)

## BPDU guard

- described [18-3](#)
- disabling [18-14](#)
- enabling [18-13](#)
- support for [1-5](#)

bridged packets, ACLs on [28-39](#)

## bridge groups

See fallback bridging

## bridge protocol data unit

See BPDU

broadcast flooding [31-17](#)

## broadcast packets

- directed [31-14](#)
- flooded [31-14](#)

broadcast storm [21-2](#)

broadcast storm-control command [21-3](#)

broadcast storms [31-14](#)

---

## C

cables, monitoring for unidirectional links [23-1](#)

## candidate switch

- adding [6-18](#)
- automatic discovery [6-5](#)
- defined [6-4](#)
- HC [6-21](#)
- passwords [6-19](#)
- requirements [6-4](#)

## candidate switch (continued)

- standby group [6-20](#)
- See also command switch, cluster standby group, and member switch

caution, described [xxxiv](#)

CC (command switch) [6-21](#)

## CDP

- and trusted boundary [29-34](#)
- automatic discovery in switch clusters [6-5](#)
- configuring [22-2](#)
- default configuration [22-2](#)
- described [22-1](#)
- disabling for routing device [22-3 to 22-4](#)
- enabling and disabling
  - on an interface [22-4](#)
  - on a switch [22-3](#)
- monitoring [22-5](#)
- overview [22-1](#)
- support for [1-4](#)
- switch stack considerations [22-2](#)
- transmission timer and holdtime, setting [22-2](#)
- updates [22-2](#)

CEF [31-60](#)

## CGMP

- as IGMP snooping learning method [20-8](#)
- clearing cached group entries [33-51](#)
- enabling server support [33-33](#)
- joining multicast group [20-3](#)
- overview [33-7](#)
- server support only [33-7](#)
- switch support of [1-3](#)

CIDR [31-56](#)

Cisco 7960 IP Phone [15-1](#)

## Cisco Discovery Protocol

See CDP

## Cisco Express Forwarding

See CEF

## Cisco Group Management Protocol

See CGMP

- Cisco IOS File System
  - See IFS
- Cisco StackWise technology 1-3
  - See also stacks, switch
- CiscoWorks 2000 1-4, 27-5
- classless interdomain routing
  - See CIDR
- classless routing 31-7
- class maps for QoS
  - configuring 29-40
  - described 29-7
  - displaying 29-65
- class of service
  - See CoS
- clearing interfaces 11-24
- CLI
  - abbreviating commands 2-3
  - command modes 2-1
  - described 1-4
  - editing features
    - enabling and disabling 2-6
    - keystroke editing 2-6
    - wrapped lines 2-8
  - error messages 2-4
  - filtering command output 2-8
  - getting help 2-3
  - history
    - changing the buffer size 2-5
    - described 2-4
    - disabling 2-5
    - recalling commands 2-5
  - managing clusters 6-23
  - no and default forms of commands 2-4
- client mode, VTP 14-3
- clock
  - See system clock
- Cluster Management Suite
  - See CMS
- cluster requirements
  - See release notes
- clusters, switch
  - accessing 6-13
  - adding member switches 6-18
  - automatic discovery 6-5
  - automatic recovery 6-10
  - benefits 1-2
  - command switch configuration 6-17
  - compatibility 6-4
  - creating 6-17
  - creating a cluster standby group 6-20
  - described 6-1
  - LRE profile considerations 6-17
  - managing
    - through CLI 6-23
    - through SNMP 6-24
  - planning 6-4
  - planning considerations
    - automatic discovery 6-5
    - automatic recovery 6-10
    - CLI 6-23
    - host names 6-13
    - IP addresses 6-13
    - LRE profiles 6-17
    - passwords 6-14
    - RADIUS 6-16
    - SNMP 6-14, 6-24
    - switch-specific features 6-17
    - switch stacks 6-14
    - TACACS+ 6-16
  - redundancy 6-20
  - troubleshooting 6-22
  - verifying 6-22
- See also candidate switch, command switch, cluster standby group, member switch, and standby command switch

- cluster standby group
  - and HSRP group [32-11](#)
  - automatic recovery [6-12](#)
  - considerations [6-11](#)
  - creating [6-20](#)
  - defined [6-2](#)
  - requirements [6-3](#)
  - virtual IP address [6-11](#)
  - See also HSRP
- CMS
  - benefits [1-2](#)
  - configuration modes [3-5](#)
  - described [1-2, 1-4](#)
  - Front Panel view, described [3-2](#)
  - operating systems and supported browsers [3-9](#)
  - privilege levels [3-7](#)
  - requirements [3-8 to 3-9](#)
  - Topology view [3-15](#)
  - wizards [3-6](#)
- CMS requirements
  - See switch software configuration guide
- Coarse Wave Division Multiplexer
  - See CWDM
- command-line interface
  - See CLI
- command modes [2-1](#)
- commands
  - abbreviating [2-3](#)
  - no and default [2-4](#)
  - setting privilege levels [9-8](#)
- command switch
  - accessing [6-11](#)
  - active (AC) [6-10, 6-20](#)
  - command switch with HSRP disabled (CC) [6-21](#)
  - configuration conflicts [36-12](#)
  - defined [6-2](#)
  - enabling [6-17](#)
  - command switch (continued)
    - passive (PC) [6-10, 6-21](#)
    - password privilege levels [6-23](#)
    - priority [6-10](#)
    - recovery
      - from command-switch failure [6-10, 36-9](#)
      - from lost member connectivity [36-12](#)
    - redundant [6-10, 6-20](#)
    - replacing
      - with another switch [36-11](#)
      - with cluster member [36-9](#)
    - requirements [6-3](#)
    - standby (SC) [6-10, 6-20](#)
    - See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [31-53](#)
- community strings
  - configuring [6-14, 27-8](#)
  - for cluster switches [27-4](#)
  - in clusters [6-14](#)
  - overview [27-4](#)
  - SNMP [6-14](#)
- compatibility, software
  - See stacks, switch
- config.text [4-12](#)
- configuration, initial
  - defaults [1-9](#)
  - Express Setup [1-2, 1-9, 3-12](#)
  - setup (CLI) program [1-9](#)
  - See also hardware installation guide
- configuration conflicts, recovering from lost member connectivity [36-12](#)
- configuration examples, network [1-12](#)
- configuration files
  - clearing the startup configuration [B-19](#)
  - creating using a text editor [B-10](#)
  - default name [4-12](#)
  - deleting a stored configuration [B-19](#)

- configuration files (continued)
  - described [B-8](#)
  - downloading
    - automatically [4-12](#)
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-13](#)
    - using RCP [B-17](#)
    - using TFTP [B-11](#)
  - guidelines for creating and using [B-9](#)
  - invalid combinations when copying [B-5](#)
  - limiting TFTP server access [27-16](#)
  - obtaining with DHCP [4-7](#)
  - password recovery disable considerations [9-5](#)
  - specifying the filename [4-12](#)
  - system contact and location information [27-15](#)
  - types and location [B-9](#)
  - uploading
    - preparing [B-10, B-13, B-16](#)
    - reasons for [B-8](#)
    - using FTP [B-15](#)
    - using RCP [B-18](#)
    - using TFTP [B-11](#)
- configuration modes, CMS [3-5](#)
- configuration settings, saving [4-10](#)
- configure terminal command [11-8](#)
- config-vlan mode [2-2, 13-7](#)
- conflicts, configuration [36-12](#)
- connections, secure remote [9-38](#)
- connectivity problems [36-13, 36-15, 36-17](#)
- consistency checks in VTP Version 2 [14-4](#)
- console port, connecting to [2-9](#)
- conventions
  - command [xxxiv](#)
  - for examples [xxxiv](#)
  - publication [xxxiv](#)
  - text [xxxiv](#)
- corrupted software, recovery steps with XMODEM [36-2](#)
- CoS
  - in Layer 2 frames [29-2](#)
  - override priority [15-6](#)
  - trust priority [15-6](#)
- CoS input queue threshold map for QoS [29-14](#)
- CoS output queue threshold map for QoS [29-17](#)
- CoS-to-DSCP map for QoS [29-48](#)
- counters, clearing interface [11-24](#)
- crashinfo file [36-24](#)
- cross-stack EtherChannel
  - configuration guidelines [30-12](#)
  - configuring
    - on Layer 2 interfaces [30-12](#)
    - on Layer 3 physical interfaces [30-15](#)
  - described [30-2](#)
  - illustration [30-3](#)
  - support for [1-5](#)
- cross-stack UplinkFast, STP
  - described [18-5](#)
  - disabling [18-16](#)
  - enabling [18-16](#)
  - fast-convergence events [18-7](#)
  - Fast Uplink Transition Protocol [18-6](#)
  - normal-convergence events [18-7](#)
  - support for [1-5](#)
- cryptographic software image
  - Kerberos [9-32](#)
  - SSH [9-37](#)
  - switch stack considerations [5-2, 5-11, 9-38](#)
- CWDM [1-23](#)
- CWDM SFPs [1-23](#)



## D

daylight saving time [7-13](#)

## debugging

enabling all system diagnostics [36-21](#)

enabling for a specific feature [36-21](#)

redirecting error message output [36-22](#)

using commands [36-20](#)

default commands [2-4](#)

## default configuration

802.1x [10-11](#)

auto-QoS [29-18](#)

banners [7-18](#)

BGP [31-42](#)

booting [4-12](#)

CDP [22-2](#)

DHCP [19-5](#)

DNS [7-17](#)

EIGRP [31-35](#)

EtherChannel [30-10](#)

fallback bridging [35-4](#)

HSRP [32-4](#)

IGMP [33-27](#)

IGMP filtering [20-22](#)

IGMP snooping [20-7](#)

IGMP throttling [20-22](#)

initial switch information [4-3](#)

IP addressing, IP routing [31-5](#)

IP multicast routing [33-8](#)

Layer 2 interfaces [11-12](#)

MAC address table [7-22](#)

MSDP [34-4](#)

MSTP [17-13](#)

MVR [20-16](#)

NTP [7-4](#)

optional spanning-tree configuration [18-12](#)

OSPF [31-26](#)

password and privilege level [9-2](#)

RADIUS [9-20](#)

## default configuration (continued)

RIP [31-20](#)

RMON [25-3](#)

RSPAN [24-11](#)

SNMP [27-7](#)

SPAN [24-11](#)

standard QoS [29-27](#)

STP [16-13](#)

switch stacks [5-14](#)

system message logging [26-4](#)

system name and prompt [7-15](#)

TACACS+ [9-13](#)

UDLD [23-4](#)

VLAN, Layer 2 Ethernet interfaces [13-19](#)

VLANs [13-8](#)

VMPS [13-29](#)

voice VLAN [15-3](#)

VTP [14-7](#)

default gateway [4-10, 31-12](#)

default networks [31-63](#)

default routes [31-63](#)

default routing [31-2](#)

deleting VLANs [13-10](#)

description command [11-19](#)

designing your network, examples [1-12](#)

desktop template [5-7, 8-1](#)

destination addresses, in ACLs [28-12](#)

destination-IP address-based forwarding,  
EtherChannel [30-8](#)

destination-MAC address forwarding, EtherChannel [30-8](#)

detecting indirect link failures, STP [18-8](#)

device discovery protocol [22-1](#)

Device Manager [3-15](#)

See also Switch Manager

## DHCP

enabling

relay agent [19-6](#)

server [19-6](#)

- DHCP-based autoconfiguration
  - client request message exchange 4-4
  - configuring
    - client side 4-3
    - DNS 4-6
    - relay device 4-6
    - server side 4-5
    - server-side 19-6
    - TFTP server 4-5
  - example 4-8
  - lease options
    - for IP address information 4-5
    - for receiving the configuration file 4-5
  - overview 4-3
  - relationship to BOOTP 4-4
  - relay support 1-4, 1-9
  - support for 1-4
- DHCP option 82
  - circuit ID suboption 19-3
  - configuration guidelines 19-5
  - default configuration 19-5
  - displaying 19-9
  - forwarding address, specifying 19-7
  - helper address 19-7
  - overview 19-2
  - packet format, suboption
    - circuit ID 19-3
    - remote ID 19-3
  - remote ID suboption 19-3
- DHCP snooping
  - configuration guidelines 19-5
  - default configuration 19-5
  - displaying binding tables 19-9
  - displaying configuration 19-10
  - message exchange process 19-3
  - option 82 data insertion 19-2
  - trusted interface 19-2
  - untrusted interface 19-2
  - untrusted messages 19-2
- Differentiated Services architecture, QoS 29-1
- Differentiated Services Code Point 29-2
- Diffusing Update Algorithm (DUAL) 31-34
- directed unicast requests 1-4
- directories
  - changing B-4
  - creating and removing B-4
  - displaying the working B-4
- discovery, clusters
  - See automatic discovery
- Distance Vector Multicast Routing Protocol
  - See DVMRP
- distance-vector protocols 31-3
- distribute-list command 31-72
- DNS
  - and DHCP-based autoconfiguration 4-6
  - default configuration 7-17
  - displaying the configuration 7-18
  - overview 7-16
  - setting up 7-17
  - support for 1-4
- documentation, related xxxv
- document conventions xxxiv
- domain names
  - DNS 7-16
  - VTP 14-8
- Domain Name System
  - See DNS
- downloading
  - configuration files
    - preparing B-10, B-13, B-16
    - reasons for B-8
    - using FTP B-13
    - using RCP B-17
    - using TFTP B-11

## downloading (continued)

## image files

- deleting old image [B-24](#)
- preparing [B-22, B-25, B-29](#)
- reasons for [B-20](#)
- using FTP [B-26](#)
- using RCP [B-31](#)
- using TFTP [B-23](#)

DSCP [1-7, 29-2](#)DSCP input queue threshold map for QoS [29-14](#)DSCP output queue threshold map for QoS [29-17](#)DSCP-to-CoS map for QoS [29-51](#)DSCP-to-DSCP-mutation map for QoS [29-52](#)DTP [1-6, 13-17](#)DUAL finite state machine, EIGRP [31-34](#)duplex mode, configuring [11-14](#)

## DVMRP

## autosummarization

- configuring a summary address [33-47](#)
- disabling [33-49](#)

connecting PIM domain to DVMRP router [33-39](#)enabling unicast routing [33-43](#)

## interoperability

- with Cisco devices [33-37](#)
- with Cisco IOS software [33-7](#)

mrinfo requests, responding to [33-42](#)

## neighbors

- advertising the default route to [33-41](#)
- discovery with Probe messages [33-37](#)
- displaying information [33-42](#)
- prevent peering with nonpruning [33-45](#)
- rejecting nonpruning [33-43](#)

overview [33-7](#)

## DVMRP (continued)

## routes

- adding a metric offset [33-49](#)
- advertising all [33-49](#)
- advertising the default route to neighbors [33-41](#)
- caching DVMRP routes learned in report messages [33-43](#)
- changing the threshold for syslog messages [33-46](#)
- deleting [33-51](#)
- displaying [33-51](#)
- favoring one over another [33-49](#)
- limiting the number injected into MBONE [33-46](#)
- limiting unicast route advertisements [33-37](#)

routing table [33-7](#)source distribution tree, building [33-7](#)support for [1-9](#)

## tunnels

- configuring [33-39](#)
- displaying neighbor information [33-42](#)

## dynamic access ports

- characteristics [13-4](#)
- configuring [13-30](#)
- defined [11-3](#)

## dynamic addresses

See addresses

dynamic auto trunking mode [13-17](#)dynamic desirable trunking mode [13-18](#)

## Dynamic Host Configuration Protocol

See DHCP-based autoconfiguration

## dynamic port VLAN membership

- described [13-28](#)
- reconfirming [13-31](#)
- troubleshooting [13-33](#)
- types of connections [13-30](#)

dynamic routing [31-3](#)

## Dynamic Trunking Protocol

See DTP

## E

EBGP [31-40](#)

editing features

enabling and disabling [2-6](#)

keystrokes used [2-6](#)

wrapped lines [2-8](#)

EIGRP

and IGRP [31-36](#)

authentication [31-38](#)

components [31-34](#)

configuring [31-36](#)

default configuration [31-35](#)

definition [31-34](#)

interface parameters, configuring [31-37](#)

monitoring [31-39](#)

support for [1-8](#)

elections

See stack master

enable password [9-4](#)

enable secret password [9-4](#)

encryption for passwords [9-4](#)

Enhanced IGRP

See EIGRP

environment variables, function of [4-15](#)

equal-cost routing [1-8, 31-61](#)

error messages during command entry [2-4](#)

EtherChannel

802.3ad, described [30-6](#)

automatic creation of [30-5, 30-6](#)

channel groups

binding physical and logical interfaces [30-4](#)

numbering of [30-4](#)

configuration guidelines [30-11](#)

configuring

Layer 2 interfaces [30-12](#)

Layer 3 physical interfaces [30-15](#)

Layer 3 port-channel logical interfaces [30-14](#)

configuring Layer 2 interfaces [30-12](#)

EtherChannel (continued)

default configuration [30-10](#)

described [30-2](#)

displaying status [30-22](#)

forwarding methods [30-7, 30-17](#)

interaction

with STP [30-11](#)

with VLANs [30-11](#)

LACP

described [30-6](#)

displaying status [30-22](#)

hot-standby ports [30-19](#)

interaction with other features [30-7](#)

modes [30-7](#)

port priority [30-21](#)

system priority [30-20](#)

LACP, support for [1-3](#)

Layer 3 interface [31-4](#)

load balancing [30-7, 30-17](#)

logical interfaces, described [30-4](#)

PAgP

aggregate-port learners [30-18](#)

compatibility with Catalyst 1900 [30-18](#)

described [30-5](#)

displaying status [30-22](#)

interaction with other features [30-6](#)

learn method and priority configuration [30-18](#)

modes [30-5](#)

support for [1-3](#)

port-channel interfaces

described [30-4](#)

numbering of [30-4](#)

port groups [11-5](#)

stack changes, effects of [30-9](#)

support for [1-3](#)

EtherChannel guard

described [18-10](#)

disabling [18-17](#)

enabling [18-17](#)

- Ethernet VLANs
    - adding [13-8](#)
    - defaults and ranges [13-8](#)
    - modifying [13-8](#)
  - events, RMON [25-3](#)
  - examples
    - conventions for [xxxiv](#)
    - network configuration [1-12](#)
  - expedite queue for QoS
    - configuring [29-64](#)
  - expert mode [3-6](#)
  - Express Setup [1-2, 1-9, 3-12](#)
    - See also hardware installation guide
  - extended-range VLANs
    - configuration guidelines [13-13](#)
    - configuring [13-12](#)
    - creating [13-14](#)
    - defined [13-1](#)
  - extended system ID
    - MSTP [17-15](#)
    - STP [16-4, 16-16](#)
  - Extensible Authentication Protocol over LAN [10-1](#)
  - external BGP
    - See EBGp
  - external neighbors, BGP [31-44](#)
- 
- F**
- failover support [1-5](#)
  - fallback bridging
    - and protected ports [35-4](#)
    - bridge groups
      - creating [35-4](#)
      - described [35-2](#)
      - displaying [35-11](#)
      - function of [35-2](#)
      - number supported [35-5](#)
      - removing [35-5](#)
  - fallback bridging (continued)
    - bridge table
      - clearing [35-11](#)
      - displaying [35-11](#)
    - configuration guidelines [35-4](#)
    - connecting interfaces with [11-7](#)
    - default configuration [35-4](#)
    - described [35-1](#)
    - frame forwarding
      - flooding packets [35-2](#)
      - forwarding packets [35-2](#)
    - overview [35-1](#)
    - stack changes, effects of [35-3](#)
    - STP
      - disabling on an interface [35-11](#)
      - forward-delay interval [35-10](#)
      - hello BPDU interval [35-9](#)
      - interface priority [35-7](#)
      - keepalive messages [16-2](#)
      - maximum-idle interval [35-10](#)
      - path cost [35-8](#)
      - VLAN-bridge spanning-tree priority [35-7](#)
      - VLAN-bridge STP [35-2](#)
    - support for [1-8](#)
    - SVIs and routed ports [35-1](#)
    - VLAN-bridge STP [16-12, 35-2](#)
  - Fast Uplink Transition Protocol [18-6](#)
  - FIB [31-60](#)
  - fiber-optic, detecting unidirectional links [23-1](#)
  - files
    - copying [B-5](#)
    - crashinfo
      - description [36-24](#)
      - displaying the contents of [36-25](#)
      - location [36-25](#)
    - deleting [B-5](#)
    - displaying the contents of [B-8](#)

## files (continued)

## tar

- creating [B-6](#)
- displaying the contents of [B-6](#)
- extracting [B-7](#)
- image file format [B-21](#)

## file system

- displaying available file systems [B-2](#)
- displaying file information [B-3](#)
- local file system names [B-1](#)
- network file system names [B-5](#)
- setting the default [B-3](#)

## filtering

- in a VLAN [28-30](#)
- non-IP traffic [28-27](#)
- show and more command output [2-8](#)

filtering show and more command output [2-8](#)

## filters, IP

See ACLs, IP

flash device, number of [B-1](#)flooded traffic, blocking [21-6](#)flow-based packet classification [1-7](#)

## flowcharts

- QoS classification [29-6](#)
- QoS egress queueing and scheduling [29-15](#)
- QoS ingress queueing and scheduling [29-13](#)
- QoS policing and marking [29-9](#)

flow control [1-3, 11-16](#)

## forward-delay time

- MSTP [17-21](#)
- STP [16-23](#)

## Forwarding Information Base

See FIB

forwarding nonroutable protocols [35-1](#)

## FTP

- accessing MIB files [A-3](#)
- configuration files
  - downloading [B-13](#)
  - overview [B-12](#)
  - preparing the server [B-13](#)
  - uploading [B-15](#)
- image files
  - deleting old image [B-28](#)
  - downloading [B-26](#)
  - preparing the server [B-25](#)
  - uploading [B-28](#)

---

**G**

- get-bulk-request operation [27-3](#)
- get-next-request operation [27-3, 27-5](#)
- get-request operation [27-3, 27-5](#)
- get-response operation [27-3](#)
- Gigabit modules
  - See SFPs
- global configuration mode [2-2](#)
- guest VLAN and 802.1x [10-8](#)
- guide
  - audience [xxxiii](#)
  - purpose of [xxxiii](#)
- guide mode [1-2, 3-5](#)

---

**H**

- hardware limitations and Layer 3 interfaces [11-21](#)
- HC (candidate switch) [6-21](#)
- hello time
  - MSTP [17-20](#)
  - STP [16-22](#)
- help, for the command line [2-3](#)

## history

changing the buffer size [2-5](#)

described [2-4](#)

disabling [2-5](#)

recalling commands [2-5](#)

history table, level and number of syslog messages [26-10](#)

## host names

abbreviations appended to [6-20](#)

in clusters [6-13](#)

hosts, limit on dynamic ports [13-33](#)

## Hot Standby Router Protocol

See HSRP

HP OpenView [1-4](#)

## HSRP

authentication string [32-9](#)

automatic cluster recovery [6-12](#)

binding to cluster group [32-11](#)

cluster standby group considerations [6-11](#)

command-switch redundancy [1-1, 1-5](#)

configuring [32-3](#)

default configuration [32-4](#)

definition [32-1](#)

guidelines [32-4](#)

monitoring [32-11](#)

overview [32-1](#)

priority [32-6](#)

routing redundancy [1-8](#)

support for ICMP redirect messages [32-10 to 32-11](#)

switch stack considerations [32-2](#)

timers [32-9](#)

tracking [32-6](#)

See also clusters, cluster standby group, and standby command switch

IBPG [31-40](#)

## ICMP

redirect messages [31-12](#)

support for [1-8](#)

time-exceeded messages [36-17](#)

traceroute and [36-17](#)

unreachable messages [28-20](#)

unreachables and ACLs [28-22](#)

## ICMP ping

executing [36-14](#)

overview [36-14](#)

## ICMP Router Discovery Protocol

See IRDP

## IDS appliances

and ingress RSPAN [24-21](#)

and ingress SPAN [24-15](#)

IEEE 802.1p [15-1](#)

ifIndex values, SNMP [27-6](#)

IFS [1-5](#)

## IGMP

configuring the switch

as a member of a group [33-27](#)

statically connected member [33-32](#)

controlling access to groups [33-28](#)

default configuration [33-27](#)

deleting cache entries [33-51](#)

displaying groups [33-51](#)

fast switching [33-32](#)

host-query interval, modifying [33-30](#)

joining multicast group [20-3](#)

join messages [20-3](#)

## IGMP (continued)

leave processing, enabling 20-12

leaving multicast group 20-5

multicast reachability 33-27

overview 33-2

queries 20-4

report suppression

described 20-6

disabling 20-12

support for 1-3

Version 1

changing to Version 2 33-29

described 33-3

Version 2

changing to Version 1 33-29

described 33-3

maximum query response time value 33-31

pruning groups 33-31

query timeout value 33-31

## IGMP filtering

configuring 20-23

default configuration 20-22

described 20-21

monitoring 20-27

support for 1-4

## IGMP groups

configuring filtering 20-25

setting the maximum number 20-25

## IGMP profile

applying 20-24

configuration mode 20-23

configuring 20-23

## IGMP snooping

and address aliasing 20-2

and stack changes 20-6

configuring 20-7

default configuration 20-7

definition 20-2

enabling and disabling 20-7

## IGMP snooping (continued)

global configuration 20-7

Immediate Leave 20-6

in the switch stack 20-6

method 20-8

monitoring 20-13

support for 1-3

VLAN configuration 20-8

## IGMP throttling

configuring 20-25

default configuration 20-22

described 20-22

displaying action 20-27

## IGP 31-25

## IGRP

split horizon 31-24

support for 1-8

Immediate Leave, IGMP 20-6

immediate leave, IGMP 20-12

## initial configuration

defaults 1-9

Express Setup 1-2, 1-9, 3-12

setup (CLI) program 1-9

See also hardware installation guide

## interface

number 11-7

range macros 11-10

interface command 11-7 to 11-8

interface configuration mode 2-2

## interfaces

configuration guidelines

10-Gigabit Ethernet 11-13

duplex and speed 11-14

configuring

duplex mode 11-14

procedure 11-8

speed 11-14

counters, clearing 11-24

described 11-19



- interfaces (continued)
  - descriptive name, adding [11-19](#)
  - displaying information about [11-23](#)
  - flow control [11-16](#)
  - management [1-4](#)
  - monitoring [11-23](#)
  - naming [11-19](#)
  - physical, identifying [11-7](#)
  - range of [11-9](#)
  - restarting [11-24](#)
  - shutting down [11-24](#)
  - status [11-23](#)
  - supported [11-7](#)
  - types of [11-1](#)
- interfaces range macro command [11-10](#)
- interface types [11-7](#)
- Interior Gateway Protocol
  - See IGP
- Interior Gateway Routing Protocol
  - See IGRP
- internal BGP
  - See IBGP
- internal neighbors, BGP [31-44](#)
- Internet Control Message Protocol
  - See ICMP
- Internet Group Management Protocol
  - See IGMP
- Inter-Switch Link
  - See ISL
- inter-VLAN routing [1-8, 31-2](#)
- Intrusion Detection System
  - See IDS
- inventory, cluster [6-22](#)
- ip access group command [28-21](#)
- IP ACLs
  - applying to an interface [28-20](#)
  - extended, creating [28-11](#)
  - for QoS classification [29-7](#)
  - implicit deny [28-10, 28-14, 28-16](#)
  - implicit masks [28-10](#)
  - logging [28-16](#)
  - named [28-15](#)
  - standard, creating [28-9](#)
  - undefined [28-21](#)
  - virtual terminal lines, setting on [28-19](#)
- IP addresses
  - candidate or member [6-4, 6-13](#)
  - classes of [31-6](#)
  - cluster access [6-2](#)
  - command switch [6-3, 6-11, 6-13](#)
  - default configuration [31-5](#)
  - discovering [7-28](#)
  - for IP routing [31-5](#)
  - MAC address association [31-9](#)
  - monitoring [31-18](#)
  - redundant clusters [6-11](#)
  - standby command switch [6-11, 6-13](#)
  - See also IP information
- IP broadcast address [31-16](#)
- ip cef distributed command [31-61](#)
- IP directed broadcasts [31-14](#)
- ip igmp profile command [20-23](#)
- IP information
  - assigned
    - manually [4-10](#)
    - through DHCP-based autoconfiguration [4-3](#)
  - default configuration [4-3](#)

## IP multicast routing

## addresses

- all-hosts [33-3](#)
- all-multicast-routers [33-3](#)
- host group address range [33-3](#)

administratively-scoped boundaries, described [33-35](#)

and IGMP snooping [20-2](#)

## Auto-RP

- adding to an existing sparse-mode cloud [33-14](#)
- benefits of [33-14](#)
- clearing the cache [33-51](#)
- configuration guidelines [33-10](#)
- filtering incoming RP announcement messages [33-17](#)
- overview [33-5](#)
- preventing candidate RP spoofing [33-17](#)
- preventing join messages to false RPs [33-16](#)
- setting up in a new internetwork [33-14](#)
- using with BSR [33-22](#)

## bootstrap router

- configuration guidelines [33-10](#)
- configuring candidate BSRs [33-20](#)
- configuring candidate RPs [33-21](#)
- defining the IP multicast boundary [33-19](#)
- defining the PIM domain border [33-18](#)
- overview [33-5](#)
- using with Auto-RP [33-22](#)

Cisco implementation [33-2](#)

## configuring

- basic multicast routing [33-10](#)
- IP multicast boundary [33-35](#)

default configuration [33-8](#)

## enabling

- multicast forwarding [33-11](#)
- PIM mode [33-11](#)

## group-to-RP mappings

- Auto-RP [33-5](#)
- BSR [33-5](#)

## IP multicast routing (continued)

## MBONE

- deleting sdr cache entries [33-51](#)
- described [33-34](#)
- displaying sdr cache [33-52](#)
- enabling sdr listener support [33-34](#)
- limiting DVMRP routes advertised [33-46](#)
- limiting sdr cache entry lifetime [33-35](#)
- SAP packets for conference session announcement [33-34](#)
- Session Directory (sdr) tool, described [33-34](#)

## monitoring

- packet rate loss [33-52](#)
- peering devices [33-52](#)
- tracing a path [33-52](#)

multicast forwarding, described [33-6](#)

PIMv1 and PIMv2 interoperability [33-9](#)

protocol interaction [33-2](#)

reverse path check (RPF) [33-6](#)

## routing table

- deleting [33-51](#)
- displaying [33-52](#)

## RP

- assigning manually [33-12](#)
- configuring Auto-RP [33-14](#)
- configuring PIMv2 BSR [33-18](#)
- monitoring mapping information [33-23](#)
- using Auto-RP and BSR [33-22](#)

## stacking

- stack master functions [33-8](#)
- stack member functions [33-8](#)

statistics, displaying system and network [33-51](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

- IP phones
  - and QoS [15-1](#)
  - automatic classification and queuing [29-18](#)
  - configuring [15-4](#)
  - ensuring port security with QoS [29-34](#)
  - trusted boundary for QoS [29-34](#)
- IP precedence [29-2](#)
- IP-precedence-to-DSCP map for QoS [29-49](#)
- IP protocols
  - in ACLs [28-12](#)
  - routing [1-8](#)
- IP routes, monitoring [31-74](#)
- IP routing
  - connecting interfaces with [11-7](#)
  - disabling [31-19](#)
  - enabling [31-19](#)
- IP traceroute
  - executing [36-17](#)
  - overview [36-17](#)
- IP unicast routing
  - address resolution [31-9](#)
  - administrative distances [31-63](#), [31-72](#)
  - ARP [31-9](#)
  - assigning IP addresses to Layer 3 interfaces [31-6](#)
  - authentication keys [31-73](#)
  - broadcast
    - address [31-16](#)
    - flooding [31-17](#)
    - packets [31-14](#)
    - storms [31-14](#)
  - classless routing [31-7](#)
  - configuring static routes [31-62](#)
  - default
    - addressing configuration [31-5](#)
    - gateways [31-12](#)
    - networks [31-63](#)
    - routes [31-63](#)
    - routing [31-2](#)
  - directed broadcasts [31-14](#)
  - disabling [31-19](#)
  - dynamic routing [31-3](#)
  - enabling [31-19](#)
  - EtherChannel Layer 3 interface [31-4](#)
  - IGP [31-25](#)
  - inter-VLAN [31-2](#)
  - IP addressing
    - classes [31-6](#)
    - configuring [31-5](#)
  - IRDP [31-13](#)
  - Layer 3 interfaces [31-4](#)
  - MAC address and IP address [31-9](#)
  - passive interfaces [31-71](#)
  - protocols
    - distance-vector [31-3](#)
    - dynamic [31-3](#)
    - link-state [31-3](#)
  - proxy ARP [31-9](#)
  - redistribution [31-64](#)
  - reverse address resolution [31-9](#)
  - routed ports [31-4](#)
  - static routing [31-2](#)
  - steps to configure [31-5](#)
  - subnet mask [31-6](#)
  - subnet zero [31-7](#)
  - supernet [31-7](#)
  - UDP [31-16](#)
  - with SVIs [31-4](#)
  - See also BGP
  - See also EIGRP
  - See also OSPF
  - See also RIP
- IRDP
  - configuring [31-13](#)
  - definition [31-13](#)
  - support for [1-8](#)
- IP unicast routing (continued)
  - disabling [31-19](#)
  - dynamic routing [31-3](#)
  - enabling [31-19](#)
  - EtherChannel Layer 3 interface [31-4](#)
  - IGP [31-25](#)
  - inter-VLAN [31-2](#)
  - IP addressing
    - classes [31-6](#)
    - configuring [31-5](#)
  - IRDP [31-13](#)
  - Layer 3 interfaces [31-4](#)
  - MAC address and IP address [31-9](#)
  - passive interfaces [31-71](#)
  - protocols
    - distance-vector [31-3](#)
    - dynamic [31-3](#)
    - link-state [31-3](#)
  - proxy ARP [31-9](#)
  - redistribution [31-64](#)
  - reverse address resolution [31-9](#)
  - routed ports [31-4](#)
  - static routing [31-2](#)
  - steps to configure [31-5](#)
  - subnet mask [31-6](#)
  - subnet zero [31-7](#)
  - supernet [31-7](#)
  - UDP [31-16](#)
  - with SVIs [31-4](#)
  - See also BGP
  - See also EIGRP
  - See also OSPF
  - See also RIP

## ISL

- and trunk ports [11-3](#)
- encapsulation [1-6, 13-16](#)

## J

- join messages, IGMP [20-3](#)

## K

## KDC

- described [9-32](#)

See also Kerberos

- keepalive messages [16-2](#)

## Kerberos

authenticating to

- boundary switch [9-35](#)

KDC [9-35](#)

- network services [9-35](#)

configuration examples [9-32](#)

configuring [9-36](#)

credentials [9-32](#)

cryptographic software image [9-32](#)

described [9-32](#)

KDC [9-32](#)

operation [9-34](#)

realm [9-33](#)

server [9-33](#)

support for [1-7](#)

switch as trusted third party [9-32](#)

terms [9-33](#)

TGT [9-34](#)

tickets [9-32](#)

## key distribution center

See KDC

## L

## LACP

See EtherChannel

Layer 2 frames, classification with CoS [29-2](#)

Layer 2 interfaces, default configuration [11-12](#)

## Layer 2 traceroute

and ARP [36-16](#)

and CDP [36-15](#)

broadcast traffic [36-15](#)

described [36-15](#)

IP addresses and subnets [36-16](#)

MAC addresses and VLANs [36-16](#)

multicast traffic [36-16](#)

multiple devices on a port [36-16](#)

unicast traffic [36-15](#)

usage guidelines [36-15](#)

Layer 2 trunks [13-17](#)

Layer 3 features [1-8](#)

## Layer 3 interfaces

assigning IP addresses to [31-6](#)

changing from Layer 2 mode [31-6](#)

types of [31-4](#)

Layer 3 packets, classification methods [29-2](#)

## LEDs, switch

See hardware installation guide

line configuration mode [2-2](#)

## Link Aggregation Control Protocol

See EtherChannel

See LACP

links, unidirectional [23-1](#)

link state advertisements (LSAs) [31-29](#)

link-state protocols [31-3](#)

load balancing [32-6](#)

logging messages, ACL [28-10](#)

- login authentication
    - with RADIUS [9-23](#)
    - with TACACS+ [9-14](#)
  - login banners [7-18](#)
  - log messages
    - See system message logging
  - Long-Reach Ethernet (LRE) technology [1-14, 1-21](#)
  - loop guard
    - described [18-11](#)
    - enabling [18-18](#)
    - support for [1-6](#)
  - LRE profiles, considerations in switch clusters [6-17](#)
- 
- ## M
- MAC addresses
    - aging time [7-22](#)
    - and VLAN association [7-21](#)
    - building the address table [7-21](#)
    - default configuration [7-22](#)
    - discovering [7-28](#)
    - displaying [7-28](#)
    - displaying in DHCP snooping binding table [19-10](#)
    - dynamic
      - learning [7-21](#)
      - removing [7-23](#)
    - in ACLs [28-27](#)
    - IP address association [31-9](#)
    - static
      - adding [7-26](#)
      - allowing [7-27](#)
      - characteristics of [7-25](#)
      - dropping [7-27](#)
      - removing [7-26](#)
  - MAC address notification, support for [1-9](#)
  - MAC address-to-VLAN mapping [13-28](#)
  - MAC extended access lists
    - applying to Layer 2 interfaces [28-29](#)
    - configuring for QoS [29-39](#)
    - creating [28-27](#)
    - defined [28-27](#)
    - for QoS classification [29-5](#)
  - macros
    - See SmartPort macros
  - manageability features [1-4](#)
  - management access
    - in-band
      - browser session [1-5](#)
      - CLI session [1-5](#)
      - CMS [1-5](#)
      - SNMP [1-5](#)
    - out-of-band console port connection [1-5](#)
  - management options
    - CLI [2-1](#)
    - clustering [1-3](#)
    - CMS [1-2](#)
    - overview [1-4](#)
    - switch stacks [1-3](#)
  - management VLAN
    - considerations in switch clusters [6-7](#)
    - discovery through different management VLANs [6-7](#)
  - mapping tables for QoS
    - configuring
      - CoS-to-DSCP [29-48](#)
      - DSCP [29-47](#)
      - DSCP-to-CoS [29-51](#)
      - DSCP-to-DSCP-mutation [29-52](#)
      - IP-precedence-to-DSCP [29-49](#)
      - policed-DSCP [29-50](#)
    - described [29-10](#)
  - marking
    - action in policy map [29-42](#)
    - action with aggregate policers [29-45](#)
    - described [29-3, 29-8](#)

- matching, ACLs [28-7](#)
- maximum aging time
  - MSTP [17-22](#)
  - STP [16-23](#)
- maximum hop count, MSTP [17-22](#)
- maximum-paths command [31-47, 31-62](#)
- membership mode, VLAN port [13-3](#)
- member switch
  - adding [6-18](#)
  - automatic discovery [6-5](#)
  - defined [6-2](#)
  - managing [6-23](#)
  - passwords [6-13](#)
  - recovering from lost connectivity [36-12](#)
  - requirements [6-4](#)
  - See also candidate switch, cluster standby group, and standby command switch
- menu bar variations [3-4](#)
- messages
  - logging ACL violations [28-16](#)
  - to users through banners [7-18](#)
- metrics, in BGP [31-48](#)
- metric translations, between routing protocols [31-67](#)
- MHSRP [32-7](#)
- MIBs
  - accessing files with FTP [A-3](#)
  - location of files [A-3](#)
  - overview [27-1](#)
  - SNMP interaction with [27-5](#)
  - supported [A-1](#)
- mini-point-of-presence
  - See POP
- mirroring traffic for analysis [24-1](#)
- mismatches, autonegotiation [36-12](#)
- module number [11-7](#)
- monitoring
  - access groups [28-41](#)
  - ACL configuration [28-41](#)
  - BGP [31-59](#)
  - cables for unidirectional links [23-1](#)
  - CDP [22-5](#)
  - CEF [31-61](#)
  - EIGRP [31-39](#)
  - fallback bridging [35-11](#)
  - features [1-9](#)
  - HSRP [32-11](#)
  - IGMP
    - filters [20-27](#)
    - snooping [20-13](#)
  - interfaces [11-23](#)
  - IP
    - address tables [31-18](#)
    - multicast routing [33-50](#)
    - routes [31-74](#)
  - MSDP peers [34-19](#)
  - multicast router interfaces [20-13](#)
  - MVR [20-21](#)
  - network traffic for analysis with probe [24-2](#)
  - OSPF [31-33](#)
  - port
    - blocking [21-15](#)
    - protection [21-15](#)
  - RP mapping information [33-23](#)
  - source-active messages [34-19](#)
  - speed and duplex mode [11-15](#)
  - traffic flowing among switches [25-1](#)
  - traffic suppression [21-15](#)
  - VLAN
    - filters [28-42](#)
    - maps [28-42](#)
  - VLANs [13-16](#)
  - VMPS [13-32](#)
  - VTP [14-16](#)

## MSDP (continued)

- benefits of [34-3](#)
- clearing MSDP connections and statistics [34-19](#)
- controlling source information
  - forwarded by switch [34-12](#)
  - originated by switch [34-9](#)
  - received by switch [34-14](#)
- default configuration [34-4](#)
- dense-mode regions
  - sending SA messages to [34-17](#)
  - specifying the originating address [34-18](#)
- filtering
  - incoming SA messages [34-14](#)
  - SA messages to a peer [34-12](#)
  - SA requests from a peer [34-11](#)
- join latency, defined [34-6](#)
- meshed groups
  - configuring [34-16](#)
  - defined [34-16](#)
- originating address, changing [34-18](#)
- overview [34-1](#)
- peer-RPF flooding [34-2](#)
- peers
  - configuring a default [34-4](#)
  - monitoring [34-19](#)
  - peering relationship, overview [34-1](#)
  - requesting source information from [34-8](#)
  - shutting down [34-16](#)
- source-active messages
  - caching [34-6](#)
  - clearing cache entries [34-19](#)
  - defined [34-2](#)
  - filtering from a peer [34-11](#)
  - filtering incoming [34-14](#)
  - filtering to a peer [34-12](#)
  - limiting data with TTL [34-14](#)
  - monitoring [34-19](#)
  - restricting advertised sources [34-9](#)
- support for [1-8](#)

## MSTP

- boundary ports
  - configuration guidelines [17-14](#)
  - described [17-5](#)
- BPDU filtering
  - described [18-3](#)
  - enabling [18-14](#)
- BPDU guard
  - described [18-3](#)
  - enabling [18-13](#)
- CIST, described [17-3](#)
- configuration guidelines [17-13, 18-12](#)
- configuring
  - forward-delay time [17-21](#)
  - hello time [17-20](#)
  - link type for rapid convergence [17-23](#)
  - maximum aging time [17-22](#)
  - maximum hop count [17-22](#)
  - MST region [17-14](#)
  - path cost [17-19](#)
  - port priority [17-18](#)
  - root switch [17-15](#)
  - secondary root switch [17-17](#)
  - switch priority [17-20](#)
- CST
  - defined [17-3](#)
  - operations between regions [17-4](#)
- default configuration [17-13](#)
- default optional feature configuration [18-12](#)
- displaying status [17-24](#)
- enabling the mode [17-14](#)
- EtherChannel guard
  - described [18-10](#)
  - enabling [18-17](#)
- extended system ID
  - effects on root switch [17-15](#)
  - effects on secondary root switch [17-17](#)
  - unexpected behavior [17-16](#)
- instances supported [16-10](#)

## MSTP (continued)

- interface state, blocking to forwarding [18-2](#)
- interoperability and compatibility among modes [16-11](#)
- interoperability with 802.1D
  - described [17-6](#)
  - restarting migration process [17-23](#)

## IST

- defined [17-3](#)
- master [17-3](#)
- operations within a region [17-3](#)

## loop guard

- described [18-11](#)
- enabling [18-18](#)

mapping VLANs to MST instance [17-14](#)

## MST region

- CIST [17-3](#)
- configuring [17-14](#)
- described [17-2](#)
- hop-count mechanism [17-5](#)
- IST [17-3](#)
- supported spanning-tree instances [17-2](#)

optional features supported [1-5](#)overview [17-2](#)

## Port Fast

- described [18-2](#)
- enabling [18-12](#)

preventing root switch selection [18-10](#)

## root guard

- described [18-10](#)
- enabling [18-17](#)

## root switch

- configuring [17-16](#)
- effects of extended system ID [17-15](#)
- unexpected behavior [17-16](#)
- shutdown Port Fast-enabled port [18-3](#)
- stack changes, effects of [17-6](#)
- status, displaying [17-24](#)

## multicast groups

- Immediate Leave [20-6](#)
- joining [20-3](#)
- leaving [20-5](#)
- static joins [20-11](#)

## multicast packets

- ACLs on [28-40](#)
- blocking [21-6](#)

multicast router interfaces, monitoring [20-13](#)multicast router ports, adding [20-10](#)

## Multicast Source Discovery Protocol

See MSDP

multicast storm [21-2](#)multicast storm-control command [21-4](#)

## Multicast VLAN Registration

See MVR

## Multiple HSRP

see MHSRP

## Multiple Spanning Tree Protocol

See MSTP

## MVR

- and address aliasing [20-17](#)
- configuring interfaces [20-19](#)
- default configuration [20-16](#)
- described [20-14](#)
- in the switch stack [20-16](#)
- modes [20-18](#)
- monitoring [20-21](#)
- setting global parameters [20-17](#)
- support for [1-4](#)

---

 N
named IP ACLs [28-15](#)

## native VLAN

- configuring [13-23](#)
- default [13-23](#)



- neighbor discovery/recovery, EIGRP [31-34](#)
- neighbors, BGP [31-54](#)
- network configuration examples
  - cost-effective wiring closet [1-14](#)
  - high-performance wiring closet [1-15](#)
  - increasing network performance [1-12](#)
  - large network [1-18](#)
  - long-distance, high-bandwidth transport [1-23](#)
  - multidwelling network [1-21](#)
  - providing network services [1-13](#)
  - redundant Gigabit backbone [1-15](#)
  - server aggregation and Linux server cluster [1-16](#)
  - small to medium-sized network [1-17](#)
- network design
  - performance [1-13](#)
  - services [1-13](#)
- network management
  - CDP [22-1](#)
  - RMON [25-1](#)
  - SNMP [27-1](#)
- Network Time Protocol
  - See NTP
- no commands [2-4](#)
- non-IP traffic filtering [28-27](#)
- nontrunking mode [13-17](#)
- normal-range VLANs
  - configuration modes [13-6](#)
  - defined [13-1](#)
- no switchport command [11-3](#)
- note, described [xxxiv](#)
- not-so-stubby areas
  - See NSSA
- NSSA, OSPF [31-29](#)

- NTP
  - associations
    - authenticating [7-5](#)
    - defined [7-2](#)
    - enabling broadcast messages [7-7](#)
    - peer [7-6](#)
    - server [7-6](#)
  - default configuration [7-4](#)
  - displaying the configuration [7-11](#)
  - overview [7-2](#)
  - restricting access
    - creating an access group [7-9](#)
    - disabling NTP services per interface [7-10](#)
  - source IP address, configuring [7-10](#)
  - stratum [7-2](#)
  - support for [1-4](#)
  - synchronizing devices [7-6](#)
  - time
    - services [7-2](#)
    - synchronizing [7-2](#)

---

## O

- Open Shortest Path First
  - See OSPF
- optimizing system resources [8-1](#)
- options, management [1-4](#)
- OSPF
  - area parameters, configuring [31-29](#)
  - configuring [31-27](#)
  - default configuration
    - metrics [31-31](#)
    - route [31-31](#)
    - settings [31-26](#)
  - described [31-25](#)

## OSPF (continued)

- interface parameters, configuring [31-28](#)
  - LSA group pacing [31-32](#)
  - monitoring [31-33](#)
  - router IDs [31-32](#)
  - route summarization [31-30](#)
  - support for [1-8](#)
  - virtual links [31-30](#)
- out-of-profile markdown [1-7](#)

## P

- packet modification, with QoS [29-17](#)

## PAgP

See EtherChannel

- parallel paths, in routing tables [31-61](#)

## passive interfaces

- configuring [31-71](#)
- OSPF [31-31](#)

## passwords

- default configuration [9-2](#)
- disabling recovery of [9-5](#)
- encrypting [9-4](#)
- for security [1-6](#)
- in clusters [6-14, 6-19](#)
- overview [9-1](#)
- recovery of [36-4](#)
- setting
  - enable [9-3](#)
  - enable secret [9-4](#)
  - Telnet [9-6](#)
  - with usernames [9-7](#)
- VTP domain [14-8](#)

## path cost

- MSTP [17-19](#)
- STP [16-20](#)

## PBR

- defined [31-68](#)
  - enabling [31-69](#)
  - fast-switched policy-based routing [31-70](#)
  - local policy-based routing [31-70](#)
- PC (passive command switch) [6-10, 6-21](#)
- peers, BGP [31-54](#)
- performance, network design [1-12](#)
- performance features [1-3](#)

## per-VLAN spanning-tree plus

See PVST+

- physical ports [11-2](#)

## PIM

- default configuration [33-8](#)
  - dense mode
    - overview [33-4](#)
    - rendezvous point (RP), described [33-4](#)
    - RPF lookups [33-7](#)
  - displaying neighbors [33-52](#)
  - enabling a mode [33-11](#)
  - overview [33-3](#)
  - router-query message interval, modifying [33-26](#)
  - shared tree and source tree, overview [33-23](#)
  - shortest path tree, delaying the use of [33-25](#)
  - sparse mode
    - join messages and shared tree [33-4](#)
    - overview [33-4](#)
    - prune messages [33-5](#)
    - RPF lookups [33-7](#)
  - support for [1-8](#)
  - versions
    - interoperability [33-9](#)
    - troubleshooting interoperability problems [33-23](#)
    - v2 improvements [33-4](#)
- PIM-DVMRP, as snooping method [20-8](#)

- ping
  - character output description [36-14](#)
  - executing [36-14](#)
  - overview [36-14](#)
- PoE
  - configuring [11-18](#)
  - support for [1-9](#)
  - troubleshooting [36-13](#)
- policed-DSCP map for QoS [29-50](#)
- policers
  - configuring
    - for each matched traffic class [29-42](#)
    - for more than one traffic class [29-45](#)
  - described [29-3](#)
  - displaying [29-65](#)
  - number of [29-29](#)
  - types of [29-8](#)
- policing
  - described [29-3](#)
  - token-bucket algorithm [29-9](#)
- policy-based routing
  - See PBR
- policy maps for QoS
  - characteristics of [29-42](#)
  - configuring [29-42](#)
  - described [29-7](#)
  - displaying [29-66](#)
- POP [1-21](#)
- port ACLs
  - defined [28-2](#)
  - types of [28-3](#)
- Port Aggregation Protocol
  - See EtherChannel
  - See PAgP
- port-based authentication
  - authentication server
    - defined [10-2](#)
    - RADIUS server [10-2](#)
  - client, defined [10-2](#)
  - configuration guidelines [10-12](#)
  - configuring
    - 802.1x authentication [10-13](#)
    - guest VLAN [10-20](#)
    - host mode [10-19](#)
    - manual re-authentication of a client [10-16](#)
    - periodic re-authentication [10-16](#)
    - quiet period [10-16](#)
    - RADIUS server [10-15](#)
    - RADIUS server parameters on the switch [10-14](#)
    - switch-to-client frame-retransmission number [10-18](#)
    - switch-to-client retransmission time [10-17](#)
  - default configuration [10-11](#)
  - described [10-1](#)
  - device roles [10-2](#)
  - displaying statistics [10-21](#)
  - EAPOL-start frame [10-3](#)
  - EAP-request/identity frame [10-3](#)
  - EAP-response/identity frame [10-3](#)
  - encapsulation [10-2](#)
  - guest VLAN
    - configuration guidelines [10-8](#)
    - described [10-8](#)
  - initiation and message exchange [10-3](#)
  - method lists [10-13](#)
  - multiple-hosts mode, described [10-19](#)
  - per-user ACLs
    - AAA authorization [10-13](#)
    - configuration tasks [10-9](#)
    - described [10-8](#)
    - RADIUS server attributes [10-9](#)

- port-based authentication (continued)
- ports
  - authorization state and dot1x port-control command 10-4
  - authorized and unauthorized 10-4
  - voice VLAN 10-6
- port security
  - and voice VLAN 10-6
  - described 10-5
  - interactions 10-6
  - multiple-hosts mode 10-19
- resetting to default values 10-21
- stack changes, effects of 10-9
- statistics, displaying 10-21
- switch
  - as proxy 10-2
  - RADIUS client 10-2
- topologies, supported 10-5
- upgrading from a previous release 10-13
- VLAN assignment
  - AAA authorization 10-13
  - characteristics 10-7
  - configuration tasks 10-8
  - described 10-7
- voice VLAN
  - described 10-6
  - PVID 10-6
  - VVID 10-6
- port blocking 1-3, 21-6
- port-channel
  - See EtherChannel
- Port Fast
  - described 18-2
  - enabling 18-12
  - mode, spanning tree 13-29
  - support for 1-5
- port membership modes, VLAN 13-3
- port priority
  - MSTP 17-18
  - STP 16-18
- ports
  - 10-Gigabit Ethernet module 11-4
  - access 11-2
  - blocking 21-6
  - dynamic access 13-4
  - protected 21-5
  - routed 11-3
  - secure 21-7
  - static-access 13-3, 13-11
  - switch 11-2
  - trunks 13-3, 13-16
  - VLAN assignments 13-11
- port security
  - aging 21-14
  - and QoS trusted boundary 29-34
  - and stacking 21-15
  - configuring 21-11
  - default configuration 21-10
  - described 21-7
  - displaying 21-16
  - on trunk ports 21-12
  - sticky learning 21-8
  - violations 21-9
  - with other features 21-10
- port-shutdown response, VMPS 13-28
- Power over Ethernet
  - See PoE
- preferential treatment of traffic
  - See QoS
- prefix lists, BGP 31-51
- preventing unauthorized access 9-1
- priority
  - HSRP 32-6
  - overriding CoS 15-6
  - trusting CoS 15-6

- private VLAN edge ports
  - See protected ports
- privileged EXEC mode [2-2](#)
- privilege levels
  - changing the default for lines [9-9](#)
  - command switch [6-23](#)
  - exiting [9-10](#)
  - in CMS [3-7](#)
  - logging into [9-10](#)
  - mapping on member switches [6-23](#)
  - overview [9-2, 9-8](#)
  - setting a command with [9-8](#)
- protected ports [1-6, 21-5](#)
- protocol-dependent modules, EIGRP [31-35](#)
- Protocol-Independent Multicast Protocol
  - See PIM
- proxy ARP
  - configuring [31-11](#)
  - definition [31-9](#)
  - with IP routing disabled [31-12](#)
- pruning, VTP
  - disabling
    - in VTP domain [14-14](#)
    - on a port [13-23](#)
  - enabling
    - in VTP domain [14-14](#)
    - on a port [13-22](#)
  - examples [14-5](#)
  - overview [14-4](#)
- pruning-eligible list
  - changing [13-22](#)
  - for VTP pruning [14-5](#)
  - VLANs [14-14](#)
- PVST+
  - 802.1Q trunking interoperability [16-11](#)
  - described [16-10](#)
  - instances supported [16-10](#)

---

## Q

### QoS

- auto-QoS
  - categorizing traffic [29-18](#)
  - configuration and defaults display [29-26](#)
  - configuration guidelines [29-22](#)
  - described [29-18](#)
  - disabling [29-23](#)
  - displaying generated commands [29-23](#)
  - displaying the initial configuration [29-26](#)
  - effects on running configuration [29-22](#)
  - egress queue defaults [29-19](#)
  - enabling for VoIP [29-23](#)
  - example configuration [29-24](#)
  - ingress queue defaults [29-19](#)
  - list of generated commands [29-20](#)
- basic model [29-3](#)
- classification
  - class maps, described [29-7](#)
  - defined [29-3](#)
  - flowchart [29-6](#)
  - forwarding treatment [29-3](#)
  - in frames and packets [29-2](#)
  - IP ACLs, described [29-5, 29-7](#)
  - MAC ACLs, described [29-5, 29-7](#)
  - options for IP traffic [29-5](#)
  - options for non-IP traffic [29-5](#)
  - policy maps, described [29-7](#)
  - trust DSCP, described [29-5](#)
  - trusted CoS, described [29-5](#)
  - trust IP precedence, described [29-5](#)
- class maps
  - configuring [29-40](#)
  - displaying [29-65](#)
- configuration guidelines
  - auto-QoS [29-22](#)
  - standard QoS [29-29](#)

## QoS (continued)

## configuring

- aggregate policers [29-45](#)
- auto-QoS [29-18](#)
- default port CoS value [29-33](#)
- DSCP maps [29-47](#)
- DSCP trust states bordering another domain [29-35](#)
- egress queue characteristics [29-58](#)
- ingress queue characteristics [29-53](#)
- IP extended ACLs [29-38](#)
- IP standard ACLs [29-37](#)
- MAC ACLs [29-39](#)
- policy maps [29-42](#)
- port trust states within the domain [29-31](#)
- trusted boundary [29-34](#)

default auto configuration [29-18](#)default standard configuration [29-27](#)displaying statistics [29-65](#)

## egress queues

- allocating buffer space [29-58](#)
- buffer allocation scheme, described [29-16](#)
- configuring shaped weights for SRR [29-62](#)
- configuring shared weights for SRR [29-63](#)
- described [29-4](#)
- displaying the threshold map [29-61](#)
- flowchart [29-15](#)
- mapping DSCP or CoS values [29-60](#)
- scheduling, described [29-4](#)
- setting WTD thresholds [29-58](#)
- WTD, described [29-17](#)

enabling globally [29-30](#)

## flowcharts

- classification [29-6](#)
- egress queueing and scheduling [29-15](#)
- ingress queueing and scheduling [29-13](#)
- policing and marking [29-9](#)

implicit deny [29-7](#)

## QoS (continued)

## ingress queues

- allocating bandwidth [29-56](#)
- allocating buffer space [29-55](#)
- buffer and bandwidth allocation, described [29-14](#)
- configuring shared weights for SRR [29-56](#)
- configuring the priority queue [29-57](#)
- described [29-3](#)
- displaying the threshold map [29-54](#)
- flowchart [29-13](#)
- mapping DSCP or CoS values [29-54](#)
- priority queue, described [29-14](#)
- scheduling, described [29-3](#)
- setting WTD thresholds [29-54](#)
- WTD, described [29-14](#)

## IP phones

- automatic classification and queueing [29-18](#)
- detection and trusted settings [29-18, 29-34](#)
- limiting bandwidth on egress interface [29-64](#)

## mapping tables

- CoS-to-DSCP [29-48](#)
- displaying [29-65](#)
- DSCP-to-CoS [29-51](#)
- DSCP-to-DSCP-mutation [29-52](#)
- IP-precedence-to-DSCP [29-49](#)
- policed-DSCP [29-50](#)
- types of [29-10](#)

marked-down actions [29-44](#)marking, described [29-3, 29-8](#)overview [29-1](#)packet modification [29-17](#)

## policers

- configuring [29-44, 29-46](#)
- described [29-8](#)
- displaying [29-65](#)
- number of [29-29](#)
- types of [29-8](#)

policies, attaching to an interface [29-9](#)

## QoS (continued)

- policing
  - described 29-3, 29-8
  - token bucket algorithm 29-9
- policy maps
  - characteristics of 29-42
  - configuring 29-42
  - displaying 29-66
- QoS label, defined 29-3
- queues
  - configuring egress characteristics 29-58
  - configuring ingress characteristics 29-53
  - high priority (expedite) 29-17, 29-64
  - location of 29-11
  - SRR, described 29-12
  - WTD, described 29-11
- rewrites 29-17
- support for 1-7
- trust states
  - bordering another domain 29-35
  - described 29-5
  - trusted device 29-34
  - within the domain 29-31
- quality of service
  - See QoS
- queries, IGMP 20-4

---

**R**
**RADIUS**

- attributes
  - vendor-proprietary 9-31
  - vendor-specific 9-29

**RADIUS (continued)**

- configuring
  - accounting 9-28
  - authentication 9-23
  - authorization 9-27
  - communication, global 9-21, 9-29
  - communication, per-server 9-21
  - multiple UDP ports 9-21
- default configuration 9-20
- defining AAA server groups 9-25
- displaying the configuration 9-31
- identifying the server 9-21
- in clusters 6-16
- limiting the services to the user 9-27
- method list, defined 9-20
- operation of 9-19
- overview 9-18
- suggested network environments 9-18
- support for 1-7
- tracking services accessed by user 9-28
- range
  - macro 11-10
  - of interfaces 11-9
- rapid convergence 17-8
- rapid per-VLAN spanning-tree plus
  - See rapid PVST+
- rapid PVST+
  - 802.1Q trunking interoperability 16-11
  - described 16-10
  - instances supported 16-10
- Rapid Spanning Tree Protocol
  - See RSTP
- RARP 31-9
- rcommand command 6-23

- RCP
  - configuration files
    - downloading [B-17](#)
    - overview [B-16](#)
    - preparing the server [B-16](#)
    - uploading [B-18](#)
  - image files
    - deleting old image [B-32](#)
    - downloading [B-31](#)
    - preparing the server [B-29](#)
    - uploading [B-33](#)
  - reconfirmation interval, VMPS, changing [13-31](#)
  - recovery procedures [36-1](#)
  - redundancy
    - EtherChannel [30-2](#)
    - HSRP [32-1](#)
    - STP
      - backbone [16-9](#)
      - multidrop backbone [18-5](#)
      - path cost [13-26](#)
      - port priority [13-24](#)
  - redundant clusters
    - See cluster standby group
  - redundant links and UplinkFast [18-15](#)
  - reliable transport protocol, EIGRP [31-34](#)
  - reloading software [4-16](#)
  - Remote Authentication Dial-In User Service
    - See RADIUS
  - Remote Copy Protocol
    - See RCP
  - Remote Network Monitoring
    - See RMON
  - Remote SPAN
    - See RSPAN
  - report suppression, IGMP
    - described [20-6](#)
    - disabling [20-12](#)
  - requirements
    - cluster
      - See release notes
    - CMS
      - See switch software configuration guide
  - resequencing ACL entries [28-15](#)
  - resets, in BGP [31-46](#)
  - resetting a UDLD-shutdown interface [23-6](#)
  - restricting access
    - NTP services [7-8](#)
    - overview [9-1](#)
    - passwords and privilege levels [9-2](#)
    - RADIUS [9-18](#)
    - TACACS+ [9-10](#)
  - retry count, VMPS, changing [13-32](#)
  - reverse address resolution [31-9](#)
  - Reverse Address Resolution Protocol
    - See RARP
  - RFC
    - 1058, RIP [31-20](#)
    - 1112, IP multicast and IGMP [20-2](#)
    - 1157, SNMPv1 [27-2](#)
    - 1163, BGP [31-40](#)
    - 1166, IP addresses [31-6](#)
    - 1253, OSPF [31-25](#)
    - 1267, BGP [31-40](#)
    - 1305, NTP [7-2](#)
    - 1587, NSSAs [31-25](#)
    - 1757, RMON [25-2](#)
    - 1771, BGP [31-40](#)
    - 1901, SNMPv2C [27-2](#)
    - 1902 to 1907, SNMPv2 [27-2](#)
    - 2236, IP multicast and IGMP [20-2](#)
    - 2273-2275, SNMPv3 [27-2](#)



## RIP

- advertisements [31-20](#)
- authentication [31-23](#)
- configuring [31-21](#)
- default configuration [31-20](#)
- described [31-20](#)
- hop counts [31-20](#)
- split horizon [31-23](#)
- summary addresses [31-23](#)
- support for [1-8](#)

## RMON

- default configuration [25-3](#)
- displaying status [25-6](#)
- enabling alarms and events [25-3](#)
- groups supported [25-2](#)
- overview [25-1](#)
- statistics
  - collecting group Ethernet [25-6](#)
  - collecting group history [25-5](#)
- support for [1-9](#)

## root guard

- described [18-10](#)
- enabling [18-17](#)
- support for [1-6](#)

## root switch

- MSTP [17-15](#)
- STP [16-16](#)

route calculation timers, OSPF [31-31](#)route dampening, BGP [31-58](#)routed packets, ACLs on [28-40](#)

## routed ports

- configuring [31-4](#)
- defined [11-3](#)
- in switch clusters [6-8](#)
- IP addresses on [11-20, 31-4](#)

route-map command [31-70](#)

## route maps

- BGP [31-49](#)
- policy-based routing [31-68](#)

## router ACLs

- defined [28-2](#)
- types of [28-4](#)

route reflectors, BGP [31-57](#)router ID, OSPF [31-32](#)route selection, BGP [31-47](#)route summarization, OSPF [31-30](#)

## routing

- default [31-2](#)
- dynamic [31-3](#)
- redistribution of information [31-64](#)
- static [31-2](#)

routing domain confederation, BGP [31-56](#)

## Routing Information Protocol

See RIP

routing protocol administrative distances [31-63](#)

## RSPAN

- and stack changes [24-10](#)
- characteristics [24-9](#)
- configuration guidelines [24-17](#)
- default configuration [24-11](#)
- destination ports [24-8](#)
- displaying status [24-24](#)
- in a switch stack [24-2](#)
- interaction with other features [24-9](#)
- monitored ports [24-6](#)
- monitoring ports [24-8](#)
- overview [1-9, 24-1](#)
- received traffic [24-5](#)
- session limits [24-11](#)
- sessions
  - creating [24-18](#)
  - defined [24-4](#)
  - limiting source traffic to specific VLANs [24-23](#)
  - specifying monitored ports [24-18](#)
  - with ingress traffic enabled [24-21](#)
- source ports [24-6](#)
- transmitted traffic [24-6](#)
- VLAN-based [24-7](#)

## RSTP

- active topology [17-7](#)
- BPDU
  - format [17-10](#)
  - processing [17-11](#)
- designated port, defined [17-7](#)
- designated switch, defined [17-7](#)
- interoperability with 802.1D
  - described [17-6](#)
  - restarting migration process [17-23](#)
  - topology changes [17-11](#)
- overview [17-6](#)
- port roles
  - described [17-7](#)
  - synchronized [17-9](#)
- proposal-agreement handshake process [17-8](#)
- rapid convergence
  - cross-stack rapid convergence [17-8](#)
  - described [17-8](#)
  - edge ports and Port Fast [17-8](#)
  - point-to-point links [17-8](#), [17-23](#)
  - root ports [17-8](#)
- root port, defined [17-7](#)
- See also MSTP
- running configuration, saving [4-10](#)

## S

- SC (standby command switch) [6-10](#), [6-20](#)
- scheduled reloads [4-16](#)
- SDM
  - described [8-1](#)
  - switch stack consideration [5-7](#)
  - templates
    - configuring [8-4](#)
    - number of [8-1](#)
- SDM mismatch mode [5-7](#), [8-2](#)

## SDM template

- aggregator [8-1](#)
- configuring [8-3](#)
- desktop [8-1](#)
- secure MAC addresses
  - and switch stacks [21-15](#)
  - deleting [21-13](#)
  - maximum number of [21-8](#)
  - types of [21-8](#)
- secure ports
  - and switch stacks [21-15](#)
  - configuring [21-7](#)
- secure remote connections [9-38](#)
- Secure Shell
  - See SSH
- security, port [21-7](#)
- security features [1-6](#)
- sequence numbers in log messages [26-8](#)
- server mode, VTP [14-3](#)
- service-provider network, MSTP and RSTP [17-1](#)
- set-request operation [27-5](#)
- setup (CLI) program [1-9](#)
  - See also hardware installation guide
- setup program, failed command switch replacement [36-11](#)
- setup program, replacing failed command switch [36-9](#)
- severity levels, defining in system messages [26-9](#)
- SFPs
  - numbering of [11-8](#)
  - security and identification [36-13](#)
- shaped round robin
  - See SRR
- show access-lists hw-summary command [28-22](#)
- show and more command output, filtering [2-8](#)
- show cdp traffic command [22-5](#)
- show cluster members command [6-23](#)
- show configuration command [11-19](#)
- show forward command [36-22](#)
- show interfaces command [11-15](#), [11-19](#)
- show platform forward command [36-22](#)

- show running-config command
  - displaying ACLs [28-20, 28-21, 28-31, 28-34](#)
  - interface description in [11-19](#)
- shutdown command on interfaces [11-24](#)
- Simple Network Management Protocol
  - See SNMP
- small form-factor pluggable modules
  - See SFPs
- SmartPort macros
  - applying Cisco-default macros [12-5](#)
  - applying parameter values [12-3, 12-5](#)
  - configuration guidelines [12-2](#)
  - creating and applying [12-3](#)
  - default configuration [12-2](#)
  - defined [12-1](#)
  - displaying [12-6](#)
  - tracing [12-2](#)
- SNAP [22-1](#)
- SNMP
  - accessing MIB variables with [27-5](#)
  - agent
    - described [27-4](#)
    - disabling [27-8](#)
  - authentication level [27-11](#)
  - community strings
    - configuring [27-8](#)
    - for cluster switches [27-4](#)
    - overview [27-4](#)
  - configuration examples [27-16](#)
  - default configuration [27-7](#)
  - engine ID [27-7](#)
  - groups [27-7, 27-10](#)
  - host [27-7](#)
  - ifIndex values [27-6](#)
  - in-band management [1-5](#)
  - in clusters [6-14](#)
- SNMP (continued)
  - informs
    - and trap keyword [27-12](#)
    - described [27-5](#)
    - differences from traps [27-5](#)
    - disabling [27-15](#)
    - enabling [27-15](#)
  - limiting access by TFTP servers [27-16](#)
  - limiting system log messages to NMS [26-10](#)
  - manager functions [1-4, 27-3](#)
  - managing clusters with [6-24](#)
  - MIBs
    - location of [A-3](#)
    - supported [A-1](#)
  - notifications [27-5](#)
  - overview [27-1, 27-5](#)
  - security levels [27-3](#)
  - status, displaying [27-17](#)
  - system contact and location [27-15](#)
  - trap manager, configuring [27-14](#)
  - traps
    - described [27-3, 27-5](#)
    - differences from informs [27-5](#)
    - disabling [27-15](#)
    - enabling [27-12](#)
    - enabling MAC address notification [7-23](#)
    - overview [27-1, 27-5](#)
    - types of [27-12](#)
    - users [27-7, 27-10](#)
    - versions supported [27-2](#)
- SNMPv1 [27-2](#)
- SNMPv2C [27-2](#)
- SNMPv3 [27-2](#)
- snooping, IGMP [20-2](#)
- software compatibility
  - See stacks, switch

- software images
  - location in flash [B-20](#)
  - recovery procedures [36-2](#)
  - scheduling reloads [4-16](#)
  - tar file format, described [B-21](#)
  - See also downloading and uploading
- source addresses, in ACLs [28-12](#)
- source-and-destination-IP address based forwarding, EtherChannel [30-8](#)
- source-and-destination MAC address forwarding, EtherChannel [30-8](#)
- source-IP address based forwarding, EtherChannel [30-8](#)
- source-MAC address forwarding, EtherChannel [30-8](#)
- SPAN
  - and stack changes [24-10](#)
  - configuration guidelines [24-11](#)
  - default configuration [24-11](#)
  - destination ports [24-8](#)
  - displaying status [24-24](#)
  - interaction with other features [24-9](#)
  - monitored ports [24-6](#)
  - monitoring ports [24-8](#)
  - overview [1-9, 24-1](#)
  - received traffic [24-5](#)
  - session limits [24-11](#)
  - sessions
    - configuring ingress forwarding [24-16, 24-22](#)
    - creating [24-12](#)
    - defined [24-4](#)
    - limiting source traffic to specific VLANs [24-16](#)
    - removing destination (monitoring) ports [24-14](#)
    - specifying monitored ports [24-12](#)
    - with ingress traffic enabled [24-15](#)
  - source ports [24-6](#)
  - transmitted traffic [24-6](#)
  - VLAN-based [24-7](#)
- spanning tree and native VLANs [13-19](#)
- Spanning Tree Protocol
  - See STP
- SPAN traffic [24-5](#)
- speed, configuring on interfaces [11-14](#)
- split horizon
  - IGRP [31-24](#)
  - RIP [31-23](#)
- SRR
  - configuring
    - shaped weights on egress queues [29-62](#)
    - shared weights on egress queues [29-63](#)
    - shared weights on ingress queues [29-56](#)
  - described [29-12](#)
  - shaped mode [29-12](#)
  - shared mode [29-12](#)
  - support for [1-8](#)
- SSH
  - configuring [9-39](#)
  - cryptographic software image [9-37](#)
  - described [1-5, 9-38](#)
  - encryption methods [9-38](#)
  - switch stack considerations [5-11, 9-38](#)
  - user authentication methods, supported [9-38](#)
- stack changes, effects on
  - 802.1x port-based authentication [10-9](#)
  - ACL configuration [28-6](#)
  - CDP [22-2](#)
  - cross-stack EtherChannel [30-12](#)
  - EtherChannel [30-9](#)
  - fallback bridging [35-3](#)
  - HSRP [32-2](#)
  - IGMP snooping [20-6](#)
  - IP routing [31-3](#)
  - MAC address tables [7-22](#)
  - MSTP [17-6](#)
  - multicast routing [33-8](#)
  - MVR [20-14](#)
  - port security [21-15](#)
  - SDM template selection [8-2](#)
  - SNMP [27-1](#)

- stack changes, effects on (continued)
  - SPAN and RSPAN 24-10
  - STP 16-12
  - switch clusters 6-14
  - system message log 26-2
  - VLANs 13-6
  - VTP 14-6
- stack master
  - bridge ID (MAC address) 5-5
  - defined 5-1
  - election 5-4
  - re-election 5-4
  - See also stacks, switch
- stack member
  - accessing CLI of specific member 5-15
  - configuring
    - member number 5-14
    - priority value 5-15
  - defined 5-1
  - displaying information of 5-15
  - hot-swappable 5-9
  - number 5-5
  - priority value 5-6
  - See also stacks, switch
- stack member number 11-7
- stack protocol version 5-8
- stacks, switch
  - accessing CLI of specific member 5-15
  - assigning information
    - member number 5-14
    - priority value 5-15
  - benefits 1-2
  - bridge ID 5-5
  - CDP considerations 22-2
  - compatibility, software 5-7
  - configuration file 5-9
  - configuration scenarios 5-11
  - default configuration 5-14
  - default settings 5-14
  - stacks, switch (continued)
    - description of 5-1
    - displaying information of 5-15
    - hot-swappable 5-9
    - HSRP considerations 32-2
    - in clusters 6-14
    - MAC address considerations 7-22
    - management connectivity 5-10
    - managing 5-1
    - membership 5-3
    - merged 5-3
    - MSTP instances supported 16-10
    - multicast routing, stack master and member roles 33-8
    - partitioned 5-3, 36-8
    - See also stack master and stack member
    - software compatibility 5-7
    - software image version 5-7
    - stack protocol version 5-8
    - STP
      - bridge ID 16-3
      - instances supported 16-10
      - root port selection 16-3
      - stack root switch election 16-3
    - system messages
      - hostnames in the display 26-1
      - remotely monitoring 26-2
    - system prompt consideration 7-14
    - system-wide configuration considerations 5-10
    - upgrading B-34
  - StackWise technology, Cisco 1-3
  - See also stacks, switch
  - Standby Command Configuration window 6-21
  - standby command switch
    - configuring 6-20
    - considerations 6-11
    - defined 6-2
    - priority 6-10
    - requirements 6-3

- standby command switch (continued)
  - virtual IP address [6-11](#)
  - See also cluster standby group and HSRP
- standby group, cluster
  - See cluster standby group and HSRP
- standby ip command [32-4](#)
- standby router [32-1](#)
- standby timers, HSRP [32-9](#)
- startup configuration
  - booting
    - manually [4-13](#)
    - specific image [4-13](#)
  - clearing [B-19](#)
  - configuration file
    - automatically downloading [4-12](#)
    - specifying the filename [4-12](#)
  - default boot configuration [4-12](#)
- static access ports
  - assigning to VLAN [13-11](#)
  - defined [11-3, 13-3](#)
- static addresses
  - See addresses
- static IP routing [1-8](#)
- static MAC addressing [1-6](#)
- static routes, configuring [31-62](#)
- static routing [31-2](#)
- static VLAN membership [13-2](#)
- statistics
  - 802.1x [10-21](#)
  - CDP [22-5](#)
  - interface [11-23](#)
  - IP multicast routing [33-51](#)
  - OSPF [31-33](#)
  - QoS ingress and egress [29-65](#)
  - RMON group Ethernet [25-6](#)
  - RMON group history [25-5](#)
  - SNMP input and output [27-17](#)
  - VTP [14-16](#)
- sticky learning [21-8](#)
- storm control
  - configuring [21-3](#)
  - described [21-2](#)
  - displaying [21-15](#)
  - support for [1-3](#)
  - thresholds [21-2](#)
- STP
  - 802.1D and bridge ID [16-4](#)
  - 802.1D and multicast addresses [16-9](#)
  - 802.1t and VLAN identifier [16-4](#)
  - accelerating root port selection [18-4](#)
  - BackboneFast
    - described [18-7](#)
    - disabling [18-17](#)
    - enabling [18-16](#)
  - BPDU filtering
    - described [18-3](#)
    - disabling [18-15](#)
    - enabling [18-14](#)
  - BPDU guard
    - described [18-3](#)
    - disabling [18-14](#)
    - enabling [18-13](#)
  - BPDU message exchange [16-3](#)
  - configuration guidelines [16-13, 18-12](#)
  - configuring
    - forward-delay time [16-23](#)
    - hello time [16-22](#)
    - maximum aging time [16-23](#)
    - path cost [16-20](#)
    - port priority [16-18](#)
    - root switch [16-16](#)
    - secondary root switch [16-17](#)
    - spanning-tree mode [16-14](#)
    - switch priority [16-21](#)
  - counters, clearing [16-24](#)
  - cross-stack UplinkFast
    - described [18-5](#)
    - enabling [18-16](#)

- STP (continued)
  - default configuration [16-13](#)
  - default optional feature configuration [18-12](#)
  - designated port, defined [16-4](#)
  - designated switch, defined [16-4](#)
  - detecting indirect link failures [18-8](#)
  - disabling [16-15](#)
  - displaying status [16-24](#)
  - EtherChannel guard
    - described [18-10](#)
    - disabling [18-17](#)
    - enabling [18-17](#)
  - extended system ID
    - effects on root switch [16-16](#)
    - effects on the secondary root switch [16-17](#)
    - overview [16-4](#)
    - unexpected behavior [16-16](#)
  - features supported [1-5](#)
  - inferior BPDU [16-3](#)
  - instances supported [16-10](#)
  - interface state, blocking to forwarding [18-2](#)
  - interface states
    - blocking [16-7](#)
    - disabled [16-8](#)
    - forwarding [16-6, 16-7](#)
    - learning [16-7](#)
    - listening [16-7](#)
    - overview [16-5](#)
  - interoperability and compatibility among modes [16-11](#)
  - keepalive messages [16-2](#)
  - limitations with 802.1Q trunks [16-11](#)
  - load sharing
    - overview [13-24](#)
    - using path costs [13-26](#)
    - using port priorities [13-24](#)
  - loop guard
    - described [18-11](#)
    - enabling [18-18](#)
  - modes supported [16-10](#)
- STP (continued)
  - multicast addresses, effect of [16-9](#)
  - optional features supported [1-5](#)
  - overview [16-2](#)
  - path costs [13-26](#)
  - Port Fast
    - described [18-2](#)
    - enabling [18-12](#)
  - port priorities [13-25](#)
  - preventing root switch selection [18-10](#)
  - protocols supported [16-10](#)
  - redundant connectivity [16-9](#)
  - root guard
    - described [18-10](#)
    - enabling [18-17](#)
  - root port, defined [16-3](#)
  - root port selection on a switch stack [16-3](#)
  - root switch
    - configuring [16-16](#)
    - effects of extended system ID [16-4, 16-16](#)
    - election [16-3](#)
    - unexpected behavior [16-16](#)
  - shutdown Port Fast-enabled port [18-3](#)
  - stack changes, effects of [16-12](#)
  - status, displaying [16-24](#)
  - superior BPDU [16-3](#)
  - timers, described [16-22](#)
  - UplinkFast
    - described [18-4](#)
    - enabling [18-15](#)
  - VLAN-bridge [16-12](#)
  - stratum, NTP [7-2](#)
  - stub areas, OSPF [31-29](#)
  - subnet mask [31-6](#)
  - subnet zero [31-7](#)
  - success response, VMPS [13-28](#)
  - summer time [7-13](#)
  - SunNet Manager [1-4](#)
  - supernet [31-7](#)

- SVIs
    - and IP unicast routing [31-4](#)
    - and router ACLs [28-4](#)
    - connecting VLANs [11-6](#)
    - defined [11-4](#)
    - routing between VLANs [13-2](#)
  - switch clustering technology [6-1](#)
    - See also clusters, switch
  - switch console port [1-5](#)
  - Switch Database Management
    - See SDM
  - switched packets, ACLs on [28-38](#)
  - Switched Port Analyzer
    - See SPAN
  - switched ports [11-2](#)
  - Switch Manager [3-15](#)
    - See also Device Manager
  - switchport block multicast command [21-6](#)
  - switchport block unicast command [21-6](#)
  - switchport command [11-12](#)
  - switchport protected command [21-5](#)
  - switch priority
    - MSTP [17-20](#)
    - STP [16-21](#)
  - switch software features [1-1](#)
  - switch virtual interface
    - See SVI
  - synchronization, BGP [31-44](#)
  - syslog
    - See system message logging
  - system clock
    - configuring
      - daylight saving time [7-13](#)
      - manually [7-11](#)
      - summer time [7-13](#)
      - time zones [7-12](#)
    - displaying the time and date [7-12](#)
    - overview [7-2](#)
    - See also NTP
  - system message logging
    - default configuration [26-4](#)
    - defining error message severity levels [26-9](#)
    - disabling [26-4](#)
    - displaying the configuration [26-13](#)
    - enabling [26-5](#)
    - facility keywords, described [26-13](#)
    - level keywords, described [26-9](#)
    - limiting messages [26-10](#)
    - message format [26-2](#)
    - overview [26-1](#)
    - sequence numbers, enabling and disabling [26-8](#)
    - setting the display destination device [26-5](#)
    - stack changes, effects of [26-2](#)
    - synchronizing log messages [26-6](#)
    - syslog facility [1-9](#)
    - time stamps, enabling and disabling [26-7](#)
    - UNIX syslog servers
      - configuring the daemon [26-11](#)
      - configuring the logging facility [26-12](#)
      - facilities supported [26-13](#)
  - system name
    - default configuration [7-15](#)
    - default setting [7-15](#)
    - manual configuration [7-15](#)
    - See also DNS
  - system prompt
    - default setting [7-14 to 7-15](#)
    - manual configuration [7-16](#)
  - system resources, optimizing [8-1](#)
- 
- T
- TACACS+
    - accounting, defined [9-11](#)
    - authentication, defined [9-11](#)
    - authorization, defined [9-11](#)



- TACACS+ (continued)
  - configuring
    - accounting [9-17](#)
    - authentication key [9-13](#)
    - authorization [9-16](#)
    - login authentication [9-14](#)
  - default configuration [9-13](#)
  - displaying the configuration [9-17](#)
  - identifying the server [9-13](#)
  - in clusters [6-16](#)
  - limiting the services to the user [9-16](#)
  - operation of [9-12](#)
  - overview [9-10](#)
  - support for [1-7](#)
  - tracking services accessed by user [9-17](#)
- tar files
  - creating [B-6](#)
  - displaying the contents of [B-6](#)
  - extracting [B-7](#)
  - image file format [B-21](#)
- TDR [1-9](#)
- Telnet
  - accessing management interfaces [2-9](#)
  - from a browser [2-10](#)
  - number of connections [1-5](#)
  - setting a password [9-6](#)
- templates, SDM [8-1](#)
- Terminal Access Controller Access Control System Plus
  - See TACACS+
- terminal lines, setting a password [9-6](#)
- TFTP
  - configuration files
    - downloading [B-11](#)
    - preparing the server [B-10](#)
    - uploading [B-11](#)
  - configuration files in base directory [4-6](#)
  - configuring for autoconfiguration [4-5](#)
- TFTP (continued)
  - image files
    - deleting [B-24](#)
    - downloading [B-23](#)
    - preparing the server [B-22](#)
    - uploading [B-24](#)
  - limiting access by servers [27-16](#)
- TFTP server [1-4](#)
- threshold, traffic level [21-2](#)
- time
  - See NTP and system clock
- Time Domain Reflector
  - See TDR
- time-range command [28-17](#)
- time ranges in ACLs [28-17](#)
- time stamps in log messages [26-7](#)
- time zones [7-12](#)
- Token Ring VLANs
  - support for [13-5](#)
  - VTP support [14-4](#)
- Topology view, described [3-2, 3-15](#)
- ToS [1-7](#)
- traceroute, Layer 2
  - and ARP [36-16](#)
  - and CDP [36-15](#)
  - broadcast traffic [36-15](#)
  - described [36-15](#)
  - IP addresses and subnets [36-16](#)
  - MAC addresses and VLANs [36-16](#)
  - multicast traffic [36-16](#)
  - multiple devices on a port [36-16](#)
  - unicast traffic [36-15](#)
  - usage guidelines [36-15](#)
- traceroute command [36-17](#)
  - See also IP traceroute
- traffic
  - blocking flooded [21-6](#)
  - fragmented [28-5](#)
  - unfragmented [28-5](#)

- traffic policing 1-7
  - traffic suppression 21-2
  - transparent mode, VTP 14-3, 14-12
  - trap-door mechanism 4-2
  - traps
    - configuring MAC address notification 7-23
    - configuring managers 27-12
    - defined 27-3
    - enabling 7-23, 27-12
    - notification types 27-12
    - overview 27-1, 27-5
  - troubleshooting
    - connectivity problems 36-13, 36-15, 36-17
    - detecting unidirectional links 23-1
    - displaying crash information 36-24
    - PIMv1 and PIMv2 interoperability problems 33-23
    - setting packet forwarding 36-22
    - SFP security and identification 36-13
    - show forward command 36-22
    - with CiscoWorks 27-5
    - with debug commands 36-20
    - with ping 36-14
    - with system message logging 26-1
    - with traceroute 36-17
  - trunking encapsulation 1-6
  - trunk ports
    - configuring 13-20
    - defined 11-3, 13-3
    - encapsulation 13-20, 13-25, 13-26
    - secure MAC addresses on 21-11
  - trunks
    - allowed-VLAN list 13-21
    - configuring 13-20, 13-25, 13-26
    - ISL 13-16
    - load sharing
      - setting STP path costs 13-26
      - using STP port priorities 13-24, 13-25
  - trunks (continued)
    - native VLAN for untagged traffic 13-23
    - parallel 13-26
    - pruning-eligible list 13-22
    - to non-DTP device 13-17
    - understanding 13-17
  - trusted boundary for QoS 29-34
  - trusted port states
    - between QoS domains 29-35
    - classification options 29-5
    - ensuring port security for IP phones 29-34
    - support for 1-7
    - within a QoS domain 29-31
  - twisted-pair Ethernet, detecting unidirectional links 23-1
  - type of service
    - See ToS
- 
- ## U
- UDLD
    - default configuration 23-4
    - disabling
      - fiber-optic interfaces 23-5
      - globally 23-5
      - per interface 23-6
    - echoing detection mechanism 23-3
    - enabling
      - globally 23-5
      - per interface 23-6
    - link-detection mechanism 23-1
    - neighbor database 23-2
    - overview 23-1
    - resetting an interface 23-6
    - status, displaying 23-7
    - support for 1-5
  - UDP, configuring 31-16
  - unauthorized ports with 802.1x 10-4

- unicast MAC address filtering [1-4](#)
    - and adding static addresses [7-27](#)
    - and broadcast MAC addresses [7-26](#)
    - and CPU packets [7-26](#)
    - and multicast addresses [7-26](#)
    - and router MAC addresses [7-26](#)
    - configuration guidelines [7-26](#)
    - described [7-26](#)
  - unicast storm [21-2](#)
  - unicast storm control command [21-4](#)
  - unicast traffic, blocking [21-6](#)
  - UniDirectional Link Detection protocol
    - See UDLD
  - UNIX syslog servers
    - daemon configuration [26-11](#)
    - facilities supported [26-13](#)
    - message logging configuration [26-12](#)
  - unrecognized Type-Length-Value (TLV) support [14-4](#)
  - upgrading information
    - See release notes
  - upgrading software images
    - See downloading
  - UplinkFast
    - described [18-4](#)
    - disabling [18-16](#)
    - enabling [18-15](#)
    - support for [1-5](#)
  - uploading
    - configuration files
      - preparing [B-10, B-13, B-16](#)
      - reasons for [B-8](#)
      - using FTP [B-15](#)
      - using RCP [B-18](#)
      - using TFTP [B-11](#)
    - uploading (continued)
      - image files
        - preparing [B-22, B-25, B-29](#)
        - reasons for [B-20](#)
        - using FTP [B-28](#)
        - using RCP [B-33](#)
        - using TFTP [B-24](#)
    - User Datagram Protocol
      - See UDP
    - user EXEC mode [2-2](#)
    - username-based authentication [9-7](#)
- 
- V
- version-dependent transparent mode [14-4](#)
  - version mismatch (VM) mode [5-8](#)
  - virtual IP address
    - cluster standby group [6-11, 6-21](#)
    - command switch [6-11, 6-21](#)
    - See also IP addresses
  - virtual router [32-1, 32-2](#)
  - vlan.dat file [13-4](#)
  - VLAN 1, disabling on a trunk port [13-21](#)
  - VLAN 1 minimization [13-21](#)
  - VLAN ACLs
    - See VLAN maps
  - vlan-assignment response, VMPS [13-28](#)
  - VLAN configuration
    - at bootup [13-7](#)
    - saving [13-7](#)
  - VLAN configuration mode [2-2, 13-7](#)
  - VLAN database
    - and startup configuration file [13-7](#)
    - and VTP [14-1](#)
    - VLAN configuration saved in [13-7](#)
    - VLANs saved in [13-4](#)
  - vlan database command [13-7](#)

- VLAN filtering and SPAN [24-7](#)
- vlan global configuration command [13-7](#)
- VLAN ID, discovering [7-28](#)
- VLAN management domain [14-2](#)
- VLAN Management Policy Server
  - See VMPS
- VLAN map entries, order of [28-30](#)
- VLAN maps
  - applying [28-34](#)
  - common uses for [28-34](#)
  - configuration example [28-35](#)
  - configuration guidelines [28-30](#)
  - configuring [28-30](#)
  - creating [28-31](#)
  - defined [28-2](#)
  - denying access example [28-36](#)
  - denying and permitting packets [28-32](#)
  - displaying [28-42](#)
  - examples [28-36](#)
  - removing [28-34](#)
  - support for [1-7](#)
  - with router ACLs [28-41](#)
- VLAN membership
  - confirming [13-31](#)
  - modes [13-3](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [13-8](#)
  - adding to VLAN database [13-8](#)
  - aging dynamic addresses [16-10](#)
  - allowed on trunk [13-21](#)
  - and spanning-tree instances [13-3, 13-6, 13-13](#)
  - configuration guidelines, extended-range VLANs [13-13](#)
  - configuration guidelines, normal-range VLANs [13-6](#)
  - configuration options [13-6](#)
  - configuring [13-1](#)
  - configuring IDs 1006 to 4094 [13-13](#)
  - connecting through SVIs [11-6](#)
- VLANs (continued)
  - creating in config-vlan mode [13-9](#)
  - creating in VLAN configuration mode [13-10](#)
  - default configuration [13-8](#)
  - deleting [13-10](#)
  - described [11-2, 13-1](#)
  - displaying [13-16](#)
  - extended-range [13-1, 13-12](#)
  - features [1-6](#)
  - illustrated [13-2](#)
  - internal [13-13](#)
  - in the switch stack [13-6](#)
  - limiting source traffic with RSPAN [24-23](#)
  - limiting source traffic with SPAN [24-16](#)
  - modifying [13-8](#)
  - native, configuring [13-23](#)
  - normal-range [13-1, 13-4](#)
  - number supported [1-6](#)
  - parameters [13-5](#)
  - port membership modes [13-3](#)
  - static-access ports [13-11](#)
  - STP and 802.1Q trunks [16-11](#)
  - supported [13-3](#)
  - Token Ring [13-5](#)
  - traffic between [13-2](#)
  - VLAN-bridge STP [16-12, 35-2](#)
  - VTP modes [14-3](#)
- VLAN Trunking Protocol
  - See VTP
- VLAN trunks [13-16, 13-17](#)
- VMPS
  - administering [13-32](#)
  - configuration example [13-33](#)
  - configuration guidelines [13-29](#)
  - default configuration [13-29](#)
  - description [13-27](#)

## VMPS (continued)

- dynamic port membership
  - described 13-28
  - reconfirming 13-31
  - troubleshooting 13-33
- entering server address 13-30
- mapping MAC addresses to VLANs 13-28
- monitoring 13-32
- reconfirmation interval, changing 13-31
- reconfirming membership 13-31
- retry count, changing 13-32

## voice-over-IP 15-1

## voice VLAN

- Cisco 7960 phone, port connections 15-1
- configuration guidelines 8-4, 15-3
- configuring IP phones for data traffic
  - override CoS of incoming frame 15-6
  - trust CoS priority of incoming frame 15-6
- configuring ports for voice traffic in
  - 802.1p priority tagged frames 15-5
  - 802.1Q frames 15-4
- connecting to an IP phone 15-4
- default configuration 15-3
- described 15-1
- displaying 15-6

## VQP 1-6, 13-27

## VTP

- adding a client to a domain 14-14
- advertisements 13-19, 14-3
- and extended-range VLANs 14-2
- and normal-range VLANs 14-2
- client mode, configuring 14-11
- configuration
  - global configuration mode 14-7
  - guidelines 14-8
  - privileged EXEC mode 14-7
  - requirements 14-9
  - saving 14-7
- VLAN configuration mode 14-8

## VTP (continued)

- configuration mode options 14-7
- configuration requirements 14-9
- configuration revision number
  - guideline 14-14
  - resetting 14-15
- configuring
  - client mode 14-11
  - server mode 14-9
  - transparent mode 14-12
- consistency checks 14-4
- default configuration 14-7
- described 14-1
- disabling 14-12
- domain names 14-8
- domains 14-2
- modes
  - client 14-3, 14-11
  - server 14-3, 14-9
  - transitions 14-3
  - transparent 14-3, 14-12
- monitoring 14-16
- passwords 14-8
- pruning
  - disabling 14-14
  - enabling 14-14
  - examples 14-5
  - overview 14-4
  - support for 1-6
- pruning-eligible list, changing 13-22
- server mode, configuring 14-9
- statistics 14-16
- support for 1-6
- Token Ring support 14-4
- transparent mode, configuring 14-12
- using 14-1
- version, guidelines 14-9
- Version 1 14-4

VTP (continued)

Version 2

- configuration guidelines [14-9](#)
- disabling [14-13](#)
- enabling [14-13](#)
- overview [14-4](#)

---

W

weighted tail drop

See WTD

wizards [1-2, 3-6](#)

WTD

- described [29-11](#)
- setting thresholds
  - egress queue-sets [29-58](#)
  - ingress queues [29-54](#)
- support for [1-8](#)

---

X

XMODEM protocol [36-2](#)