



Numerics

- 10-Gigabit Ethernet interfaces
 - configuration guidelines [11-14](#)
 - defined [11-4](#)
- 802.1D
 - See STP
- 802.1Q
 - and trunk ports [11-3](#)
 - configuration limitations [13-19](#)
 - encapsulation [13-17](#)
 - native VLAN for untagged traffic [13-23](#)
- 802.1s
 - See MSTP
- 802.1w
 - See RSTP
- 802.1x
 - See port-based authentication
- 802.3ad
 - See EtherChannel
- 802.3af
 - See PoE
- 802.3z flow control [11-17](#)

A

- abbreviating commands [2-3](#)
- ABRs [34-25](#)
- AC (command switch) [6-10, 6-20](#)
- access-class command [31-20](#)

- access control entries
 - See ACEs
- access-denied response, VMPS [13-28](#)
- access groups
 - applying ACLs to interfaces [31-21](#)
 - IP [31-21](#)
 - Layer 2 [31-21](#)
 - Layer 3 [31-21](#)
- accessing
 - clusters, switch [6-13](#)
 - command switches [6-11](#)
 - member switches [6-13](#)
 - stack members [5-19](#)
 - switch clusters [6-13](#)
- access lists
 - See ACLs
- access ports
 - defined [11-3](#)
 - in switch clusters [6-9](#)
- accounting
 - with 802.1x [10-5, 10-21](#)
 - with RADIUS [9-28](#)
 - with TACACS+ [9-11, 9-17](#)
- ACEs
 - and QoS [32-7](#)
 - defined [31-2](#)
 - Ethernet [31-2](#)
 - IP [31-2](#)
- ACLs
 - ACEs [31-2](#)
 - any keyword [31-13](#)

ACLs (continued)

applying

- on bridged packets [31-38](#)
- on multicast packets [31-40](#)
- on routed packets [31-39](#)
- on switched packets [31-38](#)
- time ranges to [31-17](#)
- to an interface [31-20](#)
- to QoS [32-7](#)

classifying traffic for QoS [32-38](#)comments in [31-19](#)compiling [31-22](#)configuring with VLAN maps [31-37](#)defined [31-1](#), [31-7](#)examples of [31-22](#), [32-38](#)

extended IP

- configuring for QoS classification [32-40](#)
- creating [31-11](#)
- matching criteria [31-7](#)

hardware and software handling [31-22](#)host keyword [31-13](#)

IP

- applying to an interface [31-20](#)
- applying to interfaces [31-20](#)
- creating [31-7](#)
- fragments and QoS guidelines [32-31](#)
- implicit deny [31-10](#), [31-14](#), [31-16](#)
- implicit masks [31-10](#)
- matching criteria [31-7](#)
- named [31-15](#)
- terminal lines, setting on [31-19](#)
- undefined [31-21](#)
- violations, logging [31-16](#)

limiting actions [31-38](#)logging messages [31-10](#)log keyword [31-16](#)MAC extended [31-27](#), [32-41](#)matching [31-7](#), [31-21](#)monitoring [31-40](#)

ACLs (continued)

named [31-15](#)number per QoS class map [32-31](#)numbers [31-7](#)port [31-2](#)precedence of [31-2](#)QoS [32-7](#), [32-38](#)resequencing entries [31-15](#)router [31-2](#)

standard IP

configuring for QoS classification [32-39](#)creating [31-9](#)matching criteria [31-7](#)supported features [31-22](#)support for [1-7](#)time ranges [31-17](#)unsupported features [31-6](#)using router ACLs with VLAN maps [31-37](#)

VLAN maps

configuration guidelines [31-30](#)configuring [31-30](#)active links [20-1](#)active router [35-1](#)address aliasing [23-2](#)

addresses

displaying the MAC address table [7-28](#)

dynamic

- accelerated aging [17-9](#)
- changing the aging time [7-22](#)
- default aging [17-9](#)
- defined [7-20](#)
- learning [7-21](#)
- removing [7-23](#)

MAC, discovering [7-28](#)

multicast

- group address range [36-3](#)
- STP address management [17-9](#)

- addresses (continued)
 - static
 - adding and removing [7-25](#)
 - defined [7-20](#)
- address resolution [7-28, 34-9](#)
- Address Resolution Protocol
 - See ARP
- adjacency tables, with CEF [34-61](#)
- administrative distances
 - defined [34-72](#)
 - OSPF [34-31](#)
 - routing protocol defaults [34-63](#)
- advertisements
 - CDP [25-1](#)
 - RIP [34-20](#)
 - VTP [13-19, 14-3, 14-4](#)
- aggregate addresses, BGP [34-56](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [32-47](#)
- aggregate policing [1-8](#)
- aggregator template [5-10, 8-1](#)
- aging, accelerating [17-9](#)
- aging time
 - accelerated
 - for MSTP [18-21](#)
 - for STP [17-9, 17-23](#)
- MAC address table [7-22](#)
- maximum
 - for MSTP [18-22](#)
 - for STP [17-23](#)
- alarms, RMON [28-3](#)
- allowed-VLAN list [13-21](#)
- area border routers
 - See ABRs
- ARP
 - configuring [34-10](#)
 - defined [1-4, 7-28, 34-9](#)
 - encapsulation [34-11](#)
 - static cache configuration [34-10](#)
 - table
 - address resolution [7-28](#)
 - managing [7-28](#)
- ASBRs [34-25](#)
- AS-path filters, BGP [34-50](#)
- attributes, RADIUS
 - vendor-proprietary [9-31](#)
 - vendor-specific [9-29](#)
- audience [xxxv](#)
- authentication
 - EIGRP [34-38](#)
 - HSRP [35-9](#)
 - local mode with AAA [9-36](#)
 - NTP associations [7-5](#)
 - RADIUS
 - key [9-21](#)
 - login [9-23](#)
 - See also port-based authentication
 - TACACS+
 - defined [9-11](#)
 - key [9-13](#)
 - login [9-14](#)
- authentication keys, and routing protocols [34-73](#)
- authoritative time source, described [7-2](#)
- authorization
 - with RADIUS [9-27](#)
 - with TACACS+ [9-11, 9-16](#)
- authorized ports with 802.1x [10-4](#)
- autoconfiguration [4-3](#)

- automatic discovery
 - adding member switches [6-18](#)
 - considerations
 - beyond a noncandidate device [6-8](#)
 - brand new switches [6-9](#)
 - connectivity [6-5](#)
 - different VLANs [6-7](#)
 - management VLANs [6-7](#)
 - non-CDP-capable devices [6-6](#)
 - noncluster-capable devices [6-6](#)
 - routed ports [6-8](#)
 - creating a cluster standby group [6-20](#)
 - in switch clusters [6-5](#)
 - See also CDP
 - automatic QoS
 - See QoS
 - automatic recovery, clusters [6-10](#)
 - See also HSRP
 - autonegotiation
 - duplex mode [1-3](#)
 - interface configuration guidelines [11-15](#)
 - mismatches [39-13](#)
 - autonomous system boundary routers
 - See ASBRs
 - autonomous systems, in BGP [34-44](#)
 - Auto-RP, described [36-5](#)
 - autosensing, port speed [1-3](#)
 - auxiliary VLAN
 - See voice VLAN
 - availability, features [1-5](#)
-
- B**
- BackboneFast
 - described [19-7](#)
 - disabling [19-17](#)
 - enabling [19-16](#)
 - support for [1-5](#)
 - backup interfaces
 - See Flex Links
 - backup links [20-1](#)
 - banners
 - configuring
 - login [7-20](#)
 - message-of-the-day login [7-19](#)
 - default configuration [7-18](#)
 - when displayed [7-18](#)
 - BGP
 - aggregate addresses [34-56](#)
 - aggregate routes, configuring [34-56](#)
 - CIDR [34-56](#)
 - clear commands [34-59](#)
 - community filtering [34-52](#)
 - configuring neighbors [34-54](#)
 - default configuration [34-42](#)
 - described [34-41](#)
 - enabling [34-44](#)
 - monitoring [34-59](#)
 - multipath support [34-47](#)
 - neighbors, types of [34-44](#)
 - path selection [34-47](#)
 - peers, configuring [34-54](#)
 - prefix filtering [34-51](#)
 - resetting sessions [34-46](#)
 - route dampening [34-58](#)
 - route maps [34-49](#)
 - route reflectors [34-57](#)
 - routing domain confederation [34-56](#)
 - show commands [34-59](#)
 - supernets [34-56](#)
 - support for [1-8](#)
 - Version 4 [34-41](#)
 - binding cluster group and HSRP group [35-11](#)

binding database

- address, DHCP server
 - See DHCP, Cisco IOS server database
- DHCP snooping
 - See DHCP snooping binding database

bindings

- address, Cisco IOS DHCP server [21-5](#)
- DHCP snooping database [21-5](#)
- IP source guard [21-15](#)

binding table, DHCP snooping

- See DHCP snooping binding database

blocking packets [24-6](#)

booting

- boot loader, function of [4-2](#)
- boot process [4-1](#)
- manually [4-13](#)
- specific image [4-13](#)

boot loader

- accessing [4-14](#)
- described [4-2](#)
- environment variables [4-14](#)
- prompt [4-14](#)
- trap-door mechanism [4-2](#)

bootstrap router (BSR), described [36-5](#)

Border Gateway Protocol

- See BGP

BPDU

- error-disabled state [19-3](#)
- filtering [19-3](#)
- RSTP format [18-10](#)

BPDU filtering

- described [19-3](#)
- disabling [19-15](#)
- enabling [19-14](#)
- support for [1-6](#)

BPDU guard

- described [19-3](#)
- disabling [19-14](#)
- enabling [19-13](#)
- support for [1-6](#)

bridged packets, ACLs on [31-38](#)

bridge groups

- See fallback bridging

bridge protocol data unit

- See BPDU

broadcast flooding [34-17](#)

broadcast packets

- directed [34-14](#)
- flooded [34-14](#)

broadcast storm-control command [24-3](#)

broadcast storms [24-2, 34-14](#)

C

cables, monitoring for unidirectional links [26-1](#)

candidate switch

- adding [6-18](#)
- automatic discovery [6-5](#)
- defined [6-4](#)
- HC [6-21](#)
- passwords [6-19](#)
- requirements [6-4](#)
- standby group [6-20](#)

See also command switch, cluster standby group, and member switch

caution, described [xxxvi](#)

CC (command switch) [6-21](#)

CDP

- and trusted boundary [32-36](#)
- automatic discovery in switch clusters [6-5](#)
- configuring [25-2](#)
- default configuration [25-2](#)

- CDP (continued)
 - described [25-1](#)
 - disabling for routing device [25-3 to 25-4](#)
 - enabling and disabling
 - on an interface [25-4](#)
 - on a switch [25-3](#)
 - monitoring [25-5](#)
 - overview [25-1](#)
 - support for [1-5](#)
 - switch stack considerations [25-2](#)
 - transmission timer and holdtime, setting [25-2](#)
 - updates [25-2](#)
- CEF [34-60](#)
- CGMP
 - as IGMP snooping learning method [23-8](#)
 - clearing cached group entries [36-51](#)
 - enabling server support [36-33](#)
 - joining multicast group [23-3](#)
 - overview [36-7](#)
 - server support only [36-7](#)
 - switch support of [1-4](#)
- CIDR [34-56](#)
- Cisco 7960 IP Phone [16-1](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco StackWise technology [1-3](#)
 - See also stacks, switch
- CiscoWorks 2000 [1-4, 30-5](#)
- classless interdomain routing
 - See CIDR
- classless routing [34-7](#)
- class maps for QoS
 - configuring [32-42](#)
 - described [32-7](#)
 - displaying [32-67](#)
- class of service
 - See CoS
- clearing interfaces [11-25](#)
- CLI
 - abbreviating commands [2-3](#)
 - command modes [2-1](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-6](#)
 - keystroke editing [2-6](#)
 - wrapped lines [2-8](#)
 - error messages [2-4](#)
 - filtering command output [2-8](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-5](#)
 - described [2-4](#)
 - disabling [2-5](#)
 - recalling commands [2-5](#)
 - managing clusters [6-23](#)
 - no and default forms of commands [2-4](#)
- client mode, VTP [14-3](#)
- clock
 - See system clock
- Cluster Management Suite
 - See CMS
- cluster requirements
 - See release notes
- clusters, switch
 - accessing [6-13](#)
 - adding member switches [6-18](#)
 - automatic discovery [6-5](#)
 - automatic recovery [6-10](#)
 - benefits [1-2](#)
 - command switch configuration [6-17](#)

- clusters, switch (continued)
 - compatibility [6-4](#)
 - creating [6-17](#)
 - creating a cluster standby group [6-20](#)
 - described [6-1](#)
 - LRE profile considerations [6-17](#)
 - managing
 - through CLI [6-23](#)
 - through SNMP [6-24](#)
 - planning [6-4](#)
 - planning considerations
 - automatic discovery [6-5](#)
 - automatic recovery [6-10](#)
 - CLI [6-23](#)
 - host names [6-13](#)
 - IP addresses [6-13](#)
 - LRE profiles [6-17](#)
 - passwords [6-14](#)
 - RADIUS [6-16](#)
 - SNMP [6-14, 6-24](#)
 - switch-specific features [6-17](#)
 - switch stacks [6-14](#)
 - TACACS+ [6-16](#)
 - redundancy [6-20](#)
 - troubleshooting [6-22](#)
 - verifying [6-22](#)
 - See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - and HSRP group [35-11](#)
 - automatic recovery [6-12](#)
 - considerations [6-11](#)
 - creating [6-20](#)
 - defined [6-2](#)
 - requirements [6-3](#)
 - virtual IP address [6-11](#)
 - See also HSRP
- CMS
 - benefits [1-2](#)
 - configuration modes [3-5](#)
 - described [1-2, 1-4](#)
 - downloading image files [1-2, 3-16, B-20](#)
 - Front Panel view, described [3-2](#)
 - operating systems and supported browsers [3-9](#)
 - privilege levels [3-7](#)
 - requirements [3-8 to 3-9](#)
 - Topology view [3-15](#)
 - wizards [3-6](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-3](#)
 - no and default [2-4](#)
 - setting privilege levels [9-8](#)
- command switch
 - accessing [6-11](#)
 - active (AC) [6-10, 6-20](#)
 - command switch with HSRP disabled (CC) [6-21](#)
 - configuration conflicts [39-12](#)
 - defined [6-2](#)
 - enabling [6-17](#)
 - passive (PC) [6-10, 6-21](#)
 - password privilege levels [6-23](#)
 - priority [6-10](#)
 - recovery
 - from command-switch failure [6-10, 39-9](#)
 - from lost member connectivity [39-12](#)
 - redundant [6-10, 6-20](#)
 - replacing
 - with another switch [39-11](#)
 - with cluster member [39-9](#)

- command switch (continued)
 - requirements [6-3](#)
 - standby (SC) [6-10, 6-20](#)
 See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [34-53](#)
- community ports [15-2](#)
- community strings
 - configuring [6-14, 30-8](#)
 - for cluster switches [30-4](#)
 - in clusters [6-14](#)
 - overview [30-4](#)
 - SNMP [6-14](#)
- community VLANs [15-2, 15-3](#)
- compatibility, software
 - See stacks, switch
- config.text [4-12](#)
- configuration, initial
 - defaults [1-10](#)
 - Express Setup [1-2, 1-10, 3-12](#)
 - setup (CLI) program [1-10](#)
 See also hardware installation guide
- configuration conflicts, recovering from lost member connectivity [39-12](#)
- configuration examples, network [1-12](#)
- configuration files
 - clearing the startup configuration [B-19](#)
 - creating using a text editor [B-10](#)
 - default name [4-12](#)
 - deleting a stored configuration [B-19](#)
 - described [B-8](#)
 - downloading
 - automatically [4-12](#)
 - preparing [B-10, B-13, B-16](#)
 - reasons for [B-8](#)
 - using FTP [B-13](#)
 - using RCP [B-17](#)
 - using TFTP [B-11](#)
- configuration files (continued)
 - guidelines for creating and using [B-9](#)
 - invalid combinations when copying [B-5](#)
 - limiting TFTP server access [30-16](#)
 - obtaining with DHCP [4-7](#)
 - password recovery disable considerations [9-5](#)
 - specifying the filename [4-12](#)
 - system contact and location information [30-15](#)
 - types and location [B-9](#)
 - uploading
 - preparing [B-10, B-13, B-16](#)
 - reasons for [B-8](#)
 - using FTP [B-15](#)
 - using RCP [B-18](#)
 - using TFTP [B-11](#)
- configuration modes, CMS [3-5](#)
- configuration settings, saving [4-10](#)
- configure terminal command [11-8](#)
- config-vlan mode [2-2, 13-7](#)
- conflicts, configuration [39-12](#)
- connections, secure remote [9-38](#)
- connectivity problems [39-14, 39-16, 39-17](#)
- consistency checks in VTP Version 2 [14-4](#)
- console port, connecting to [2-9](#)
- conventions
 - command [xxxvi](#)
 - for examples [xxxvi](#)
 - publication [xxxvi](#)
 - text [xxxvi](#)
- corrupted software, recovery steps with Xmodem [39-2](#)
- CoS
 - in Layer 2 frames [32-2](#)
 - override priority [16-6](#)
 - trust priority [16-6](#)
- CoS input queue threshold map for QoS [32-14](#)
- CoS output queue threshold map for QoS [32-17](#)
- CoS-to-DSCP map for QoS [32-50](#)

- counters, clearing interface [11-25](#)
 - crashinfo file [39-25](#)
 - cross-stack EtherChannel
 - configuration guidelines [33-12](#)
 - configuring
 - on Layer 2 interfaces [33-12](#)
 - on Layer 3 physical interfaces [33-16](#)
 - described [33-2](#)
 - illustration [33-3](#)
 - support for [1-5](#)
 - cross-stack UplinkFast, STP
 - described [19-5](#)
 - disabling [19-16](#)
 - enabling [19-16](#)
 - fast-convergence events [19-7](#)
 - Fast Uplink Transition Protocol [19-6](#)
 - normal-convergence events [19-7](#)
 - support for [1-5](#)
 - cryptographic software image
 - Kerberos [9-32](#)
 - SSH [9-37](#)
 - switch stack considerations [5-2, 5-14, 9-38](#)
 - CWDM SFPs [1-22](#)
-
- D**
- daylight saving time [7-13](#)
 - debugging
 - enabling all system diagnostics [39-22](#)
 - enabling for a specific feature [39-22](#)
 - redirecting error message output [39-22](#)
 - using commands [39-21](#)
 - default commands [2-4](#)
 - default configuration
 - 802.1x [10-11](#)
 - auto-QoS [32-18](#)
 - banners [7-18](#)
 - default configuration (continued)
 - BGP [34-42](#)
 - booting [4-12](#)
 - CDP [25-2](#)
 - DHCP [21-7](#)
 - DHCP option 82 [21-7](#)
 - DHCP snooping [21-7](#)
 - DHCP snooping binding database [21-7](#)
 - DNS [7-17](#)
 - dynamic ARP inspection [22-5](#)
 - EIGRP [34-35](#)
 - EtherChannel [33-10](#)
 - fallback bridging [38-4](#)
 - Flex Links [20-2](#)
 - HSRP [35-4](#)
 - IGMP [36-27](#)
 - IGMP filtering [23-20](#)
 - IGMP snooping [23-6](#)
 - IGMP throttling [23-20](#)
 - initial switch information [4-3](#)
 - IP addressing, IP routing [34-5](#)
 - IP multicast routing [36-8](#)
 - IP source guard [21-16](#)
 - Layer 2 interfaces [11-12](#)
 - MAC address table [7-22](#)
 - MSDP [37-4](#)
 - MSTP [18-13](#)
 - MVR [23-15](#)
 - NTP [7-4](#)
 - optional spanning-tree configuration [19-12](#)
 - OSPF [34-26](#)
 - password and privilege level [9-2](#)
 - PIM [36-8](#)
 - private VLANs [15-7](#)
 - RADIUS [9-20](#)
 - RIP [34-20](#)
 - RMON [28-3](#)

- default configuration (continued)
 - RSPAN [27-11](#)
 - SNMP [30-7](#)
 - SPAN [27-11](#)
 - standard QoS [32-29](#)
 - STP [17-13](#)
 - switch stacks [5-17](#)
 - system message logging [29-4](#)
 - system name and prompt [7-15](#)
 - TACACS+ [9-13](#)
 - UDLD [26-4](#)
 - VLAN, Layer 2 Ethernet interfaces [13-19](#)
 - VLANs [13-8](#)
 - VMPS [13-29](#)
 - voice VLAN [16-3](#)
 - VTP [14-7](#)
- default gateway [4-10, 34-12](#)
- default networks [34-64](#)
- default routes [34-63](#)
- default routing [34-2](#)
- deleting VLANs [13-11](#)
- description command [11-20](#)
- designing your network, examples [1-12](#)
- desktop template [5-10, 8-1](#)
- destination addresses, in ACLs [31-12](#)
- destination-IP address-based forwarding, EtherChannel [33-8](#)
- destination-MAC address forwarding, EtherChannel [33-8](#)
- detecting indirect link failures, STP [19-8](#)
- device discovery protocol [25-1](#)
- Device Manager [3-9](#)
- DHCP
 - Cisco IOS server database
 - configuring [21-12](#)
 - default configuration [21-7](#)
 - described [21-5](#)
 - enabling
 - relay agent [21-9](#)
 - server [21-8](#)
 - DHCP-based autoconfiguration
 - client request message exchange [4-4](#)
 - configuring
 - client side [4-3](#)
 - DNS [4-6](#)
 - relay device [4-6](#)
 - server side [4-5](#)
 - server-side [21-8](#)
 - TFTP server [4-5](#)
 - example [4-8](#)
 - lease options
 - for IP address information [4-5](#)
 - for receiving the configuration file [4-5](#)
 - overview [4-3](#)
 - relationship to BOOTP [4-4](#)
 - relay support [1-4, 1-9](#)
 - support for [1-4](#)
 - DHCP binding database
 - See DHCP snooping binding database
 - DHCP binding table
 - See DHCP snooping binding database
 - DHCP option 82
 - circuit ID suboption [21-4](#)
 - configuration guidelines [21-8](#)
 - default configuration [21-7](#)
 - displaying [21-14](#)
 - forwarding address, specifying [21-9](#)
 - helper address [21-9](#)
 - overview [21-3](#)
 - packet format, suboption
 - circuit ID [21-4](#)
 - remote ID [21-4](#)
 - remote ID suboption [21-4](#)
 - DHCP snooping
 - and private VLANs [21-12](#)
 - binding database
 - See DHCP snooping binding database
 - configuration guidelines [21-8](#)
 - default configuration [21-7](#)

- DHCP snooping (continued)
 - displaying binding database [21-14](#)
 - displaying configuration [21-14](#)
 - message exchange process [21-4](#)
 - option 82 data insertion [21-3](#)
 - trusted interface [21-2](#)
 - untrusted interface [21-2](#)
 - untrusted messages [21-2](#)
- DHCP snooping binding database
 - adding bindings [21-12](#)
 - binding file
 - format [21-6](#)
 - location [21-5](#)
 - bindings [21-5](#)
 - clearing agent statistics [21-13](#)
 - configuration guidelines [21-8](#)
 - configuring [21-12](#)
 - default configuration [21-7](#)
 - deleting
 - binding file [21-13](#)
 - bindings [21-13](#)
 - database agent [21-13](#)
 - described [21-5](#)
 - displaying
 - binding entries [21-14](#)
 - status and statistics [21-15](#)
 - enabling [21-12](#)
 - entry [21-5](#)
 - renewing database [21-13](#)
 - resetting
 - delay value [21-13](#)
 - timeout value [21-13](#)
 - updating process [21-6](#)
- DHCP snooping binding table
 - See DHCP snooping binding database
- Differentiated Services architecture, QoS [32-2](#)
- Differentiated Services Code Point [32-2](#)
- Diffusing Update Algorithm (DUAL) [34-34](#)
- directed unicast requests [1-4](#)
- directories
 - changing [B-4](#)
 - creating and removing [B-4](#)
 - displaying the working [B-4](#)
- discovery, clusters
 - See automatic discovery
- Distance Vector Multicast Routing Protocol
 - See DVMRP
- distance-vector protocols [34-3](#)
- distribute-list command [34-72](#)
- DNS
 - and DHCP-based autoconfiguration [4-6](#)
 - default configuration [7-17](#)
 - displaying the configuration [7-18](#)
 - overview [7-16](#)
 - setting up [7-17](#)
 - support for [1-4](#)
- documentation, related [xxxvii](#)
- document conventions [xxxvi](#)
- domain names
 - DNS [7-16](#)
 - VTP [14-8](#)
- Domain Name System
 - See DNS
- downloading
 - configuration files
 - preparing [B-10](#), [B-13](#), [B-16](#)
 - reasons for [B-8](#)
 - using FTP [B-13](#)
 - using RCP [B-17](#)
 - using TFTP [B-11](#)

downloading (continued)

image files

- deleting old image [B-24](#)
- preparing [B-22, B-25, B-29](#)
- reasons for [B-20](#)
- using CMS [1-2, 3-16, B-20](#)
- using FTP [B-26](#)
- using HTTP [1-2, 3-16, B-20](#)
- using RCP [B-31](#)
- using TFTP [B-23](#)

DSCP [1-7, 32-2](#)DSCP input queue threshold map for QoS [32-14](#)DSCP output queue threshold map for QoS [32-17](#)DSCP-to-CoS map for QoS [32-52](#)DSCP-to-DSCP-mutation map for QoS [32-53](#)DTP [1-6, 13-17](#)DUAL finite state machine, EIGRP [34-34](#)duplex mode, configuring [11-14](#)

DVMRP

autosummarization

- configuring a summary address [36-47](#)
- disabling [36-49](#)

connecting PIM domain to DVMRP router [36-39](#)enabling unicast routing [36-43](#)

interoperability

- with Cisco devices [36-37](#)
- with Cisco IOS software [36-7](#)

mrinfo requests, responding to [36-42](#)

neighbors

- advertising the default route to [36-41](#)
- discovery with Probe messages [36-37](#)
- displaying information [36-42](#)
- prevent peering with nonpruning [36-45](#)
- rejecting nonpruning [36-43](#)

overview [36-7](#)

DVMRP (continued)

routes

- adding a metric offset [36-49](#)
- advertising all [36-49](#)
- advertising the default route to neighbors [36-41](#)
- caching DVMRP routes learned in report messages [36-43](#)
- changing the threshold for syslog messages [36-46](#)
- deleting [36-51](#)
- displaying [36-51](#)
- favoring one over another [36-49](#)
- limiting the number injected into MBONE [36-46](#)
- limiting unicast route advertisements [36-37](#)

routing table [36-7](#)source distribution tree, building [36-7](#)support for [1-9](#)

tunnels

- configuring [36-39](#)
- displaying neighbor information [36-42](#)

dynamic access ports

- characteristics [13-4](#)
- configuring [13-30](#)
- defined [11-3](#)

dynamic addresses

See addresses

dynamic ARP inspection

- ARP cache poisoning [22-1](#)
- ARP requests, described [22-1](#)
- ARP spoofing attack [22-1](#)

clearing

- log buffer [22-15](#)
- statistics [22-15](#)

configuration guidelines [22-6](#)

configuring

- ACLs for non-DHCP environments [22-8](#)
- in DHCP environments [22-7](#)
- log buffer [22-12](#)
- rate limit for incoming ARP packets [22-4, 22-10](#)

- dynamic ARP inspection (continued)
 - default configuration [22-5](#)
 - denial-of-service attacks, preventing [22-10](#)
 - described [22-1](#)
 - DHCP snooping binding database [22-2](#)
 - displaying
 - ARP ACLs [22-14](#)
 - configuration and operating state [22-14](#)
 - log buffer [22-15](#)
 - statistics [22-15](#)
 - trust state and rate limit [22-14](#)
 - error-disabled state for exceeding rate limit [22-4](#)
 - function of [22-2](#)
 - interface trust states [22-3](#)
 - log buffer
 - clearing [22-15](#)
 - configuring [22-12](#)
 - displaying [22-15](#)
 - logging of dropped packets, described [22-4](#)
 - man-in-the middle attack, described [22-2](#)
 - network security issues and interface trust states [22-3](#)
 - priority of ARP ACLs and DHCP snooping entries [22-4](#)
 - rate limiting of ARP packets
 - configuring [22-10](#)
 - described [22-4](#)
 - error-disabled state [22-4](#)
 - statistics
 - clearing [22-15](#)
 - displaying [22-15](#)
 - validation checks, performing [22-11](#)
- dynamic auto trunking mode [13-18](#)
- dynamic desirable trunking mode [13-18](#)
- Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration

- dynamic port VLAN membership
 - described [13-28](#)
 - reconfirming [13-31](#)
 - troubleshooting [13-33](#)
 - types of connections [13-30](#)
- dynamic routing [34-3](#)
- Dynamic Trunking Protocol
 - See DTP

E

- EBGP [34-40](#)
- editing features
 - enabling and disabling [2-6](#)
 - keystrokes used [2-6](#)
 - wrapped lines [2-8](#)
- EIGRP
 - and IGRP [34-36](#)
 - authentication [34-38](#)
 - components [34-34](#)
 - configuring [34-36](#)
 - default configuration [34-35](#)
 - definition [34-34](#)
 - interface parameters, configuring [34-37](#)
 - monitoring [34-39](#)
 - support for [1-8](#)
- elections
 - See stack master
- enable password [9-4](#)
- enable secret password [9-4](#)
- encryption for passwords [9-4](#)
- Enhanced IGRP
 - See EIGRP
- environment variables, function of [4-15](#)
- equal-cost routing [1-9, 34-62](#)
- error messages during command entry [2-4](#)

EtherChannel

- 802.3ad, described [33-6](#)
- automatic creation of [33-5, 33-6](#)
- channel groups
 - binding physical and logical interfaces [33-4](#)
 - numbering of [33-4](#)
- configuration guidelines [33-11](#)
- configuring
 - Layer 2 interfaces [33-12](#)
 - Layer 3 physical interfaces [33-16](#)
 - Layer 3 port-channel logical interfaces [33-15](#)
- default configuration [33-10](#)
- described [33-2](#)
- displaying status [33-23](#)
- forwarding methods [33-7, 33-18](#)
- interaction
 - with STP [33-11](#)
 - with VLANs [33-12](#)

LACP

- described [33-6](#)
- displaying status [33-23](#)
- hot-standby ports [33-20](#)
- interaction with other features [33-7](#)
- modes [33-7](#)
- port priority [33-22](#)
- system priority [33-21](#)

Layer 3 interface [34-4](#)load balancing [33-7, 33-18](#)logical interfaces, described [33-4](#)

PAGP

- aggregate-port learners [33-19](#)
- compatibility with Catalyst 1900 [33-19](#)
- described [33-5](#)
- displaying status [33-23](#)
- interaction with other features [33-6](#)
- learn method and priority configuration [33-19](#)
- modes [33-5](#)
- support for [1-3](#)

EtherChannel (continued)

- port-channel interfaces
 - described [33-4](#)
 - numbering of [33-4](#)
- port groups [11-5](#)
- stack changes, effects of [33-9](#)
- support for [1-3](#)

EtherChannel guard

- described [19-10](#)
- disabling [19-17](#)
- enabling [19-17](#)

Ethernet VLANs

- adding [13-9](#)
- defaults and ranges [13-8](#)
- modifying [13-9](#)

events, RMON [28-3](#)

examples

- conventions for [xxxvi](#)
- network configuration [1-12](#)

expedite queue for QoS [32-66](#)expert mode [3-6](#)Express Setup [1-2, 1-10, 3-12](#)

See also hardware installation guide

extended-range VLANs

- configuration guidelines [13-13](#)
- configuring [13-12](#)
- creating [13-14](#)
- defined [13-1](#)

extended system ID

- MSTP [18-15](#)
- STP [17-4, 17-16](#)

Extensible Authentication Protocol over LAN [10-1](#)

external BGP

See EBGp

external neighbors, BGP [34-44](#)

F

- failover support [1-5](#)
- fallback bridging
 - and protected ports [38-4](#)
 - bridge groups
 - creating [38-4](#)
 - described [38-2](#)
 - displaying [38-11](#)
 - function of [38-2](#)
 - number supported [38-5](#)
 - removing [38-5](#)
 - bridge table
 - clearing [38-11](#)
 - displaying [38-11](#)
 - configuration guidelines [38-4](#)
 - connecting interfaces with [11-7](#)
 - default configuration [38-4](#)
 - described [38-1](#)
 - frame forwarding
 - flooding packets [38-2](#)
 - forwarding packets [38-2](#)
 - overview [38-1](#)
 - protocol, unsupported [38-4](#)
 - stack changes, effects of [38-3](#)
 - STP
 - disabling on an interface [38-11](#)
 - forward-delay interval [38-10](#)
 - hello BPDU interval [38-9](#)
 - interface priority [38-7](#)
 - keepalive messages [17-2](#)
 - maximum-idle interval [38-10](#)
 - path cost [38-8](#)
 - VLAN-bridge spanning-tree priority [38-7](#)
 - VLAN-bridge STP [38-2](#)
 - support for [1-8](#)
 - SVIs and routed ports [38-1](#)
 - unsupported protocols [38-4](#)
 - VLAN-bridge STP [17-12](#)
- Fast Uplink Transition Protocol [19-6](#)
- FIB [34-60](#)
- fiber-optic, detecting unidirectional links [26-1](#)
- files
 - copying [B-5](#)
 - crashinfo
 - description [39-25](#)
 - displaying the contents of [39-25](#)
 - location [39-25](#)
 - deleting [B-5](#)
 - displaying the contents of [B-8](#)
 - tar
 - creating [B-6](#)
 - displaying the contents of [B-6](#)
 - extracting [B-7](#)
 - image file format [B-21](#)
- file system
 - displaying available file systems [B-2](#)
 - displaying file information [B-3](#)
 - local file system names [B-1](#)
 - network file system names [B-5](#)
 - setting the default [B-3](#)
- filtering
 - in a VLAN [31-30](#)
 - non-IP traffic [31-27](#)
 - show and more command output [2-8](#)
- filtering show and more command output [2-8](#)
- filters, IP
 - See ACLs, IP
- flash device, number of [B-1](#)
- Flex Links
 - configuration guidelines [20-2](#)
 - configuring [20-3](#)
 - default configuration [20-2](#)
 - description [20-1](#)
 - monitoring [20-3](#)
- flooded traffic, blocking [24-6](#)
- flow-based packet classification [1-7](#)

flowcharts

- QoS classification [32-6](#)
- QoS egress queuing and scheduling [32-15](#)
- QoS ingress queuing and scheduling [32-13](#)
- QoS policing and marking [32-9](#)

flow control [1-3, 11-17](#)

forward-delay time

- MSTP [18-21](#)
- STP [17-23](#)

Forwarding Information Base

See FIB

forwarding nonroutable protocols [38-1](#)

FTP

- accessing MIB files [A-3](#)
- configuration files
 - downloading [B-13](#)
 - overview [B-12](#)
 - preparing the server [B-13](#)
 - uploading [B-15](#)
- image files
 - deleting old image [B-28](#)
 - downloading [B-26](#)
 - preparing the server [B-25](#)
 - uploading [B-28](#)

G

- get-bulk-request operation [30-3](#)
- get-next-request operation [30-3, 30-5](#)
- get-request operation [30-3, 30-5](#)
- get-response operation [30-3](#)
- Gigabit modules
 - See SFPs
- global configuration mode [2-2](#)
- guest VLAN and 802.1x [10-8](#)
- guide
 - audience [xxxv](#)
 - purpose of [xxxv](#)
- guide mode [1-2, 3-5](#)

H

- hardware limitations and Layer 3 interfaces [11-21](#)
- HC (candidate switch) [6-21](#)
- hello time
 - MSTP [18-20](#)
 - STP [17-22](#)
- help, for the command line [2-3](#)
- history
 - changing the buffer size [2-5](#)
 - described [2-4](#)
 - disabling [2-5](#)
 - recalling commands [2-5](#)
- history table, level and number of syslog messages [29-10](#)
- host names
 - abbreviations appended to [6-20](#)
 - in clusters [6-13](#)
- host ports
 - configuring [15-11](#)
 - kinds of [15-2](#)
- hosts, limit on dynamic ports [13-33](#)
- Hot Standby Router Protocol
 - See HSRP
- HP OpenView [1-4](#)
- HSRP
 - authentication string [35-9](#)
 - automatic cluster recovery [6-12](#)
 - binding to cluster group [35-11](#)
 - cluster standby group considerations [6-11](#)
 - command-switch redundancy [1-1, 1-5](#)
 - configuring [35-3](#)
 - default configuration [35-4](#)
 - definition [35-1](#)
 - guidelines [35-4](#)
 - monitoring [35-11](#)
 - overview [35-1](#)
 - priority [35-6](#)
 - routing redundancy [1-8](#)
 - support for ICMP redirect messages [35-10 to 35-11](#)

HSRP (continued)

- switch stack considerations [35-2](#)
- timers [35-9](#)
- tracking [35-6](#)
- See also clusters, cluster standby group, and standby command switch

IBPG [34-40](#)

ICMP

- redirect messages [34-12](#)
- support for [1-9](#)
- time-exceeded messages [39-18](#)
- traceroute and [39-18](#)
- unreachable messages [31-20](#)
- unreachables and ACLs [31-22](#)

ICMP ping

- executing [39-15](#)
- overview [39-14](#)

ICMP Router Discovery Protocol

See IRDP

IDS appliances

- and ingress RSPAN [27-21](#)
- and ingress SPAN [27-15](#)

IEEE 802.1p [16-1](#)ifIndex values, SNMP [30-6](#)IFS [1-5](#)

IGMP

- configuring the switch
 - as a member of a group [36-27](#)
 - statically connected member [36-32](#)
- controlling access to groups [36-28](#)
- default configuration [36-27](#)
- deleting cache entries [36-51](#)
- displaying groups [36-51](#)
- fast switching [36-32](#)
- host-query interval, modifying [36-30](#)
- joining multicast group [23-3](#)

IGMP (continued)

- join messages [23-3](#)
- leave processing, enabling [23-11](#)
- leaving multicast group [23-5](#)
- multicast reachability [36-27](#)
- overview [36-2](#)
- queries [23-4](#)
- report suppression
 - described [23-5](#)
 - disabling [23-11](#)
- support for [1-4](#)
- Version 1
 - changing to Version 2 [36-29](#)
 - described [36-3](#)
- Version 2
 - changing to Version 1 [36-29](#)
 - described [36-3](#)
 - maximum query response time value [36-31](#)
 - pruning groups [36-31](#)
 - query timeout value [36-31](#)

IGMP filtering

- configuring [23-21](#)
- default configuration [23-20](#)
- described [23-19](#)
- monitoring [23-25](#)
- support for [1-4](#)

IGMP groups

- configuring filtering [23-23](#)
- setting the maximum number [23-23](#)

IGMP profile

- applying [23-22](#)
- configuration mode [23-21](#)
- configuring [23-21](#)

IGMP snooping

- and address aliasing [23-2](#)
- and stack changes [23-6](#)
- configuring [23-6](#)
- default configuration [23-6](#)
- definition [23-1](#)

IGMP snooping (continued)

- enabling and disabling [23-7](#)
- global configuration [23-7](#)
- Immediate Leave [23-5](#)
- in the switch stack [23-6](#)
- method [23-7](#)
- monitoring [23-12](#)
- support for [1-4](#)
- VLAN configuration [23-7](#)

IGMP throttling

- configuring [23-23](#)
- default configuration [23-20](#)
- described [23-20](#)
- displaying action [23-25](#)

IGP [34-25](#)

IGRP

- split horizon [34-24](#)
- support for [1-8](#)

Immediate Leave, IGMP

- described [23-5](#)
- enabling [23-11](#)

initial configuration

- defaults [1-10](#)
- Express Setup [1-2, 1-10, 3-12](#)
- setup (CLI) program [1-10](#)
- See also hardware installation guide

interface

- number [11-7](#)
- range macros [11-10](#)

interface command [11-7 to 11-8](#)interface configuration mode [2-2](#)

interfaces

- configuration guidelines
 - 10-Gigabit Ethernet [11-14](#)
 - duplex and speed [11-15](#)
- configuring
 - duplex mode [11-14](#)
 - procedure [11-8](#)
 - speed [11-14](#)

interfaces (continued)

- counters, clearing [11-25](#)
- described [11-20](#)
- descriptive name, adding [11-20](#)
- displaying information about [11-24](#)
- flow control [11-17](#)
- management [1-4](#)
- monitoring [11-24](#)
- naming [11-20](#)
- physical, identifying [11-7](#)
- range of [11-9](#)
- restarting [11-25](#)
- shutting down [11-25](#)
- status [11-24](#)
- supported [11-7](#)
- types of [11-1](#)

interfaces range macro command [11-10](#)interface types [11-7](#)

Interior Gateway Protocol

See IGP

Interior Gateway Routing Protocol

See IGRP

internal BGP

See IBGP

internal neighbors, BGP [34-44](#)

Internet Control Message Protocol

See ICMP

Internet Group Management Protocol

See IGMP

Inter-Switch Link

See ISL

inter-VLAN routing [1-8, 34-2](#)

Intrusion Detection System

See IDS appliances

inventory, cluster [6-22](#)ip access group command [31-21](#)

IP ACLs

- applying to an interface [31-20](#)
- extended, creating [31-11](#)
- for QoS classification [32-7](#)
- implicit deny [31-10, 31-14, 31-16](#)
- implicit masks [31-10](#)
- logging [31-16](#)
- named [31-15](#)
- standard, creating [31-9](#)
- undefined [31-21](#)
- virtual terminal lines, setting on [31-19](#)

IP addresses

- candidate or member [6-4, 6-13](#)
- classes of [34-6](#)
- cluster access [6-2](#)
- command switch [6-3, 6-11, 6-13](#)
- default configuration [34-5](#)
- discovering [7-28](#)
- for IP routing [34-5](#)
- MAC address association [34-9](#)
- monitoring [34-18](#)
- redundant clusters [6-11](#)
- standby command switch [6-11, 6-13](#)
- See also IP information

IP broadcast address [34-16](#)

ip cef distributed command [34-61](#)

IP directed broadcasts [34-14](#)

ip igmp profile command [23-21](#)

IP information

- assigned
 - manually [4-10](#)
 - through DHCP-based autoconfiguration [4-3](#)
- default configuration [4-3](#)

IP multicast routing

addresses

- all-hosts [36-3](#)
- all-multicast-routers [36-3](#)
- host group address range [36-3](#)
- administratively-scoped boundaries, described [36-35](#)

IP multicast routing (continued)

and IGMP snooping [23-1](#)

Auto-RP

- adding to an existing sparse-mode cloud [36-14](#)
- benefits of [36-14](#)
- clearing the cache [36-51](#)
- configuration guidelines [36-10](#)
- filtering incoming RP announcement messages [36-17](#)
- overview [36-5](#)
- preventing candidate RP spoofing [36-17](#)
- preventing join messages to false RPs [36-16](#)
- setting up in a new internetwork [36-14](#)
- using with BSR [36-22](#)

bootstrap router

- configuration guidelines [36-10](#)
- configuring candidate BSRs [36-20](#)
- configuring candidate RPs [36-21](#)
- defining the IP multicast boundary [36-19](#)
- defining the PIM domain border [36-18](#)
- overview [36-5](#)
- using with Auto-RP [36-22](#)

Cisco implementation [36-2](#)

configuring

- basic multicast routing [36-10](#)
- IP multicast boundary [36-35](#)

default configuration [36-8](#)

enabling

- multicast forwarding [36-11](#)
- PIM mode [36-11](#)

group-to-RP mappings

- Auto-RP [36-5](#)
- BSR [36-5](#)

MBONE

- deleting sdr cache entries [36-51](#)
- described [36-34](#)
- displaying sdr cache [36-52](#)
- enabling sdr listener support [36-34](#)
- limiting DVMRP routes advertised [36-46](#)
- limiting sdr cache entry lifetime [36-35](#)

IP multicast routing (continued)

- SAP packets for conference session announcement [36-34](#)
- Session Directory (sdr) tool, described [36-34](#)

monitoring

- packet rate loss [36-52](#)
- peering devices [36-52](#)
- tracing a path [36-52](#)

multicast forwarding, described [36-6](#)PIMv1 and PIMv2 interoperability [36-9](#)protocol interaction [36-2](#)reverse path check (RPF) [36-6](#)

routing table

- deleting [36-51](#)
- displaying [36-52](#)

RP

- assigning manually [36-12](#)
- configuring Auto-RP [36-14](#)
- configuring PIMv2 BSR [36-18](#)
- monitoring mapping information [36-23](#)
- using Auto-RP and BSR [36-22](#)

stacking

- stack master functions [36-8](#)
- stack member functions [36-8](#)

statistics, displaying system and network [36-51](#)

See also CGMP

See also DVMRP

See also IGMP

See also PIM

IP phones

- and QoS [16-1](#)
- automatic classification and queueing [32-18](#)
- configuring [16-4](#)
- ensuring port security with QoS [32-35](#)
- trusted boundary for QoS [32-35](#)

IP precedence [32-2](#)IP-precedence-to-DSCP map for QoS [32-50](#)

IP protocols

- in ACLs [31-12](#)
- routing [1-8](#)

IP routes, monitoring [34-74](#)

IP routing

- connecting interfaces with [11-7](#)
- disabling [34-19](#)
- enabling [34-19](#)

IP source guard

- and 802.1x [21-17](#)
- and DHCP snooping [21-15](#)
- and EtherChannels [21-17](#)
- and port security [21-17](#)
- and routed ports [21-17](#)
- and TCAM entries [21-17](#)
- and trunk interfaces [21-17](#)
- and VRF [21-17](#)

binding configuration

- automatic [21-15](#)
- manual [21-15](#)

binding table [21-15](#)configuration guidelines [21-17](#)default configuration [21-16](#)described [21-15](#)disabling [21-18](#)

displaying

- bindings [21-19](#)
- configuration [21-19](#)

enabling [21-17](#)

filtering

- source IP address [21-16](#)
- source IP and MAC address [21-16](#)

source IP address filtering [21-16](#)source IP and MAC address filtering [21-16](#)

static bindings

- adding [21-17](#)
- deleting [21-18](#)

- IP traceroute
 - executing [39-18](#)
 - overview [39-17](#)
 - IP unicast routing
 - address resolution [34-9](#)
 - administrative distances [34-63](#), [34-72](#)
 - ARP [34-9](#)
 - assigning IP addresses to Layer 3 interfaces [34-6](#)
 - authentication keys [34-73](#)
 - broadcast
 - address [34-16](#)
 - flooding [34-17](#)
 - packets [34-14](#)
 - storms [34-14](#)
 - classless routing [34-7](#)
 - configuring static routes [34-62](#)
 - default
 - addressing configuration [34-5](#)
 - gateways [34-12](#)
 - networks [34-64](#)
 - routes [34-63](#)
 - routing [34-2](#)
 - directed broadcasts [34-14](#)
 - disabling [34-19](#)
 - dynamic routing [34-3](#)
 - enabling [34-19](#)
 - EtherChannel Layer 3 interface [34-4](#)
 - IGP [34-25](#)
 - inter-VLAN [34-2](#)
 - IP addressing
 - classes [34-6](#)
 - configuring [34-5](#)
 - IRDP [34-13](#)
 - Layer 3 interfaces [34-4](#)
 - MAC address and IP address [34-9](#)
 - passive interfaces [34-71](#)
 - IP unicast routing (continued)
 - protocols
 - distance-vector [34-3](#)
 - dynamic [34-3](#)
 - link-state [34-3](#)
 - proxy ARP [34-9](#)
 - redistribution [34-64](#)
 - reverse address resolution [34-9](#)
 - routed ports [34-4](#)
 - static routing [34-2](#)
 - steps to configure [34-5](#)
 - subnet mask [34-6](#)
 - subnet zero [34-7](#)
 - supernet [34-7](#)
 - UDP [34-16](#)
 - with SVIs [34-4](#)
 - See also BGP
 - See also EIGRP
 - See also OSPF
 - See also RIP
 - IRDP
 - configuring [34-13](#)
 - definition [34-13](#)
 - support for [1-9](#)
 - ISL
 - and trunk ports [11-3](#)
 - encapsulation [1-6](#), [13-17](#)
 - isolated port [15-2](#)
 - isolated VLANs [15-2](#), [15-3](#)
-
- J**
- join messages, IGMP [23-3](#)

K**KDC**

described [9-32](#)

See also Kerberos

keepalive messages [17-2](#)

Kerberos

authenticating to

boundary switch [9-35](#)

KDC [9-35](#)

network services [9-35](#)

configuration examples [9-32](#)

configuring [9-36](#)

credentials [9-32](#)

cryptographic software image [9-32](#)

described [9-32](#)

KDC [9-32](#)

operation [9-34](#)

realm [9-33](#)

server [9-33](#)

support for [1-7](#)

switch as trusted third party [9-32](#)

terms [9-33](#)

TGT [9-34](#)

tickets [9-32](#)

key distribution center

See KDC

L**LACP**

See EtherChannel

Layer 2 frames, classification with CoS [32-2](#)

Layer 2 interfaces, default configuration [11-12](#)

Layer 2 traceroute

and ARP [39-17](#)

and CDP [39-16](#)

broadcast traffic [39-16](#)

described [39-16](#)

Layer 2 traceroute (continued)

IP addresses and subnets [39-17](#)

MAC addresses and VLANs [39-16](#)

multicast traffic [39-16](#)

multiple devices on a port [39-17](#)

unicast traffic [39-16](#)

usage guidelines [39-16](#)

Layer 2 trunks [13-17](#)

Layer 3 features [1-8](#)

Layer 3 interfaces

assigning IP addresses to [34-6](#)

changing from Layer 2 mode [34-6](#)

types of [34-4](#)

Layer 3 packets, classification methods [32-2](#)

LEDs, switch

See hardware installation guide

line configuration mode [2-2](#)

Link Aggregation Control Protocol

See EtherChannel

link redundancy

See Flex Links

links, unidirectional [26-1](#)

link state advertisements (LSAs) [34-29](#)

link-state protocols [34-3](#)

load balancing [35-6](#)

logging messages, ACL [31-10](#)

login authentication

with RADIUS [9-23](#)

with TACACS+ [9-14](#)

login banners [7-18](#)

log messages

See system message logging

Long-Reach Ethernet (LRE) technology [1-14, 1-21](#)

loop guard

described [19-11](#)

enabling [19-18](#)

support for [1-6](#)

LRE profiles, considerations in switch clusters [6-17](#)

M

MAC addresses

- aging time [7-22](#)
- and VLAN association [7-21](#)
- building the address table [7-21](#)
- default configuration [7-22](#)
- discovering [7-28](#)
- displaying [7-28](#)
- displaying in DHCP snooping binding database [21-14](#)
- displaying in the IP source binding table [21-19](#)
- dynamic
 - learning [7-21](#)
 - removing [7-23](#)
- in ACLs [31-27](#)
- IP address association [34-9](#)
- static
 - adding [7-26](#)
 - allowing [7-27](#)
 - characteristics of [7-25](#)
 - dropping [7-27](#)
 - removing [7-26](#)

MAC address notification, support for [1-9](#)

MAC address-to-VLAN mapping [13-28](#)

MAC extended access lists

- applying to Layer 2 interfaces [31-29](#)
- configuring for QoS [32-41](#)
- creating [31-27](#)
- defined [31-27](#)
- for QoS classification [32-5](#)

macros

See Smartports macros

manageability features [1-4](#)

management access

- in-band
 - browser session [1-5](#)
 - CLI session [1-5](#)
 - CMS [1-5](#)
 - SNMP [1-5](#)
- out-of-band console port connection [1-5](#)

management options

- CLI [2-1](#)
- clustering [1-3](#)
- CMS [1-2](#)
- overview [1-4](#)
- switch stacks [1-3](#)

management VLAN

- considerations in switch clusters [6-7](#)
- discovery through different management VLANs [6-7](#)

mapping tables for QoS

- configuring
 - CoS-to-DSCP [32-50](#)
 - DSCP [32-49](#)
 - DSCP-to-CoS [32-52](#)
 - DSCP-to-DSCP-mutation [32-53](#)
 - IP-precedence-to-DSCP [32-50](#)
 - policed-DSCP [32-51](#)
- described [32-10](#)

marking

- action in policy map [32-44](#)
- action with aggregate policers [32-47](#)
- described [32-3, 32-8](#)

matching, ACLs [31-7](#)

maximum aging time

- MSTP [18-22](#)
- STP [17-23](#)

maximum hop count, MSTP [18-22](#)

- maximum-paths command [34-47, 34-62](#)
- membership mode, VLAN port [13-3](#)
- member switch
 - adding [6-18](#)
 - automatic discovery [6-5](#)
 - defined [6-2](#)
 - managing [6-23](#)
 - passwords [6-13](#)
 - recovering from lost connectivity [39-12](#)
 - requirements [6-4](#)
 - See also candidate switch, cluster standby group, and standby command switch
- menu bar variations [3-4](#)
- messages
 - logging ACL violations [31-16](#)
 - to users through banners [7-18](#)
- metrics, in BGP [34-48](#)
- metric translations, between routing protocols [34-68](#)
- MHSRP [35-7](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [30-1](#)
 - SNMP interaction with [30-5](#)
 - supported [A-1](#)
- mini-point-of-presence
 - See POP
- mirroring traffic for analysis [27-1](#)
- mismatches, autonegotiation [39-13](#)
- module number [11-7](#)
- monitoring
 - access groups [31-40](#)
 - ACL configuration [31-40](#)
 - BGP [34-59](#)
 - cables for unidirectional links [26-1](#)
 - CDP [25-5](#)
 - monitoring (continued)
 - CEF [34-61](#)
 - EIGRP [34-39](#)
 - fallback bridging [38-11](#)
 - features [1-9](#)
 - Flex Links [20-3](#)
 - HSRP [35-11](#)
 - IGMP
 - filters [23-25](#)
 - snooping [23-12](#)
 - interfaces [11-24](#)
 - IP
 - address tables [34-18](#)
 - multicast routing [36-50](#)
 - routes [34-74](#)
 - MSDP peers [37-19](#)
 - multicast router interfaces [23-12](#)
 - MVR [23-19](#)
 - network traffic for analysis with probe [27-2](#)
 - OSPF [34-33](#)
 - port
 - blocking [24-16](#)
 - protection [24-16](#)
 - private VLANs [15-15](#)
 - RP mapping information [36-23](#)
 - SFPs
 - status [11-24, 39-14](#)
 - SFP status [1-9](#)
 - source-active messages [37-19](#)
 - speed and duplex mode [11-16](#)
 - traffic flowing among switches [28-1](#)
 - traffic suppression [24-16](#)
 - VLAN
 - filters [31-41](#)
 - maps [31-41](#)
 - VLANs [13-16](#)
 - VMPS [13-32](#)
 - VTP [14-16](#)

MSDP

- benefits of [37-3](#)
- clearing MSDP connections and statistics [37-19](#)
- controlling source information
 - forwarded by switch [37-12](#)
 - originated by switch [37-9](#)
 - received by switch [37-14](#)
- default configuration [37-4](#)
- dense-mode regions
 - sending SA messages to [37-17](#)
 - specifying the originating address [37-18](#)
- filtering
 - incoming SA messages [37-14](#)
 - SA messages to a peer [37-12](#)
 - SA requests from a peer [37-11](#)
- join latency, defined [37-6](#)
- meshed groups
 - configuring [37-16](#)
 - defined [37-16](#)
- originating address, changing [37-18](#)
- overview [37-1](#)
- peer-RPF flooding [37-2](#)
- peers
 - configuring a default [37-4](#)
 - monitoring [37-19](#)
 - peering relationship, overview [37-1](#)
 - requesting source information from [37-8](#)
 - shutting down [37-16](#)
- source-active messages
 - caching [37-6](#)
 - clearing cache entries [37-19](#)
 - defined [37-2](#)
 - filtering from a peer [37-11](#)
 - filtering incoming [37-14](#)
 - filtering to a peer [37-12](#)
 - limiting data with TTL [37-14](#)
 - monitoring [37-19](#)
 - restricting advertised sources [37-9](#)
- support for [1-9](#)

MSTP

- boundary ports
 - configuration guidelines [18-14](#)
 - described [18-5](#)
- BPDU filtering
 - described [19-3](#)
 - enabling [19-14](#)
- BPDU guard
 - described [19-3](#)
 - enabling [19-13](#)
- CIST, described [18-3](#)
- configuration guidelines [18-13, 19-12](#)
- configuring
 - forward-delay time [18-21](#)
 - hello time [18-20](#)
 - link type for rapid convergence [18-23](#)
 - maximum aging time [18-22](#)
 - maximum hop count [18-22](#)
 - MST region [18-14](#)
 - path cost [18-19](#)
 - port priority [18-18](#)
 - root switch [18-15](#)
 - secondary root switch [18-17](#)
 - switch priority [18-20](#)
- CST
 - defined [18-3](#)
 - operations between regions [18-4](#)
- default configuration [18-13](#)
- default optional feature configuration [19-12](#)
- displaying status [18-24](#)
- enabling the mode [18-14](#)
- EtherChannel guard
 - described [19-10](#)
 - enabling [19-17](#)
- extended system ID
 - effects on root switch [18-15](#)
 - effects on secondary root switch [18-17](#)
 - unexpected behavior [18-16](#)
- instances supported [17-10](#)

MSTP (continued)

- interface state, blocking to forwarding [19-2](#)
- interoperability and compatibility among modes [17-11](#)
- interoperability with 802.1D
 - described [18-6](#)
 - restarting migration process [18-23](#)

IST

- defined [18-3](#)
- master [18-3](#)
- operations within a region [18-3](#)

loop guard

- described [19-11](#)
- enabling [19-18](#)

mapping VLANs to MST instance [18-14](#)

MST region

- CIST [18-3](#)
- configuring [18-14](#)
- described [18-2](#)
- hop-count mechanism [18-5](#)
- IST [18-3](#)
- supported spanning-tree instances [18-2](#)

optional features supported [1-6](#)overview [18-2](#)

Port Fast

- described [19-2](#)
- enabling [19-12](#)

preventing root switch selection [19-10](#)

root guard

- described [19-10](#)
- enabling [19-17](#)

root switch

- configuring [18-16](#)
- effects of extended system ID [18-15](#)
- unexpected behavior [18-16](#)
- shutdown Port Fast-enabled port [19-3](#)
- stack changes, effects of [18-6](#)
- status, displaying [18-24](#)

multicast groups

- Immediate Leave [23-5](#)
- joining [23-3](#)
- leaving [23-5](#)
- static joins [23-10](#)

multicast packets

- ACLs on [31-40](#)
- blocking [24-6](#)

multicast router interfaces, monitoring [23-12](#)multicast router ports, adding [23-9](#)

Multicast Source Discovery Protocol

See MSDP

multicast storm [24-2](#)multicast storm-control command [24-4](#)

Multicast VLAN Registration

See MVR

Multiple HSRP

See MHSRP

Multiple Spanning Tree Protocol

See MSTP

MVR

- and address aliasing [23-16](#)
- configuring interfaces [23-17](#)
- default configuration [23-15](#)
- described [23-13](#)
- in the switch stack [23-15](#)
- modes [23-17](#)
- monitoring [23-19](#)
- setting global parameters [23-16](#)
- support for [1-4](#)

Nnamed IP ACLs [31-15](#)

native VLAN

- configuring [13-23](#)
- default [13-23](#)

neighbor discovery/recovery, EIGRP [34-34](#)neighbors, BGP [34-54](#)

- network configuration examples
 - cost-effective wiring closet [1-14](#)
 - high-performance wiring closet [1-14](#)
 - increasing network performance [1-12](#)
 - large network [1-18](#)
 - long-distance, high-bandwidth transport [1-22](#)
 - multidwelling network [1-21](#)
 - providing network services [1-13](#)
 - redundant Gigabit backbone [1-15](#)
 - server aggregation and Linux server cluster [1-15](#)
 - small to medium-sized network [1-17](#)
 - network design
 - performance [1-13](#)
 - services [1-13](#)
 - network management
 - CDP [25-1](#)
 - RMON [28-1](#)
 - SNMP [30-1](#)
 - Network Time Protocol
 - See NTP
 - no commands [2-4](#)
 - non-IP traffic filtering [31-27](#)
 - nontrunking mode [13-18](#)
 - normal-range VLANs
 - configuration modes [13-7](#)
 - defined [13-1](#)
 - no switchport command [11-4](#)
 - note, described [xxxvi](#)
 - not-so-stubby areas
 - See NSSA
 - NSSA, OSPF [34-29](#)
 - NTP
 - associations
 - authenticating [7-5](#)
 - defined [7-2](#)
 - enabling broadcast messages [7-7](#)
 - peer [7-6](#)
 - server [7-6](#)
 - default configuration [7-4](#)
 - NTP (continued)
 - displaying the configuration [7-11](#)
 - overview [7-2](#)
 - restricting access
 - creating an access group [7-9](#)
 - disabling NTP services per interface [7-10](#)
 - source IP address, configuring [7-10](#)
 - stratum [7-2](#)
 - support for [1-5](#)
 - synchronizing devices [7-6](#)
 - time
 - services [7-2](#)
 - synchronizing [7-2](#)
-
- ## O
- offline configuration for switch stacks [5-7](#)
 - Open Shortest Path First
 - See OSPF
 - optimizing system resources [8-1](#)
 - options, management [1-4](#)
 - OSPF
 - area parameters, configuring [34-29](#)
 - configuring [34-27](#)
 - default configuration
 - metrics [34-31](#)
 - route [34-31](#)
 - settings [34-26](#)
 - described [34-25](#)
 - interface parameters, configuring [34-28](#)
 - LSA group pacing [34-32](#)
 - monitoring [34-33](#)
 - router IDs [34-32](#)
 - route summarization [34-30](#)
 - support for [1-8](#)
 - virtual links [34-30](#)
 - out-of-profile markdown [1-8](#)

P

packet modification, with QoS [32-17](#)

PAGP

See EtherChannel

parallel paths, in routing tables [34-62](#)

passive interfaces

configuring [34-71](#)

OSPF [34-31](#)

passwords

default configuration [9-2](#)

disabling recovery of [9-5](#)

encrypting [9-4](#)

for security [1-6](#)

in clusters [6-14, 6-19](#)

overview [9-1](#)

recovery of [39-4](#)

setting

enable [9-3](#)

enable secret [9-4](#)

Telnet [9-6](#)

with usernames [9-7](#)

VTP domain [14-9](#)

path cost

MSTP [18-19](#)

STP [17-20](#)

PBR

defined [34-68](#)

enabling [34-69](#)

fast-switched policy-based routing [34-70](#)

local policy-based routing [34-70](#)

PC (passive command switch) [6-10, 6-21](#)

peers, BGP [34-54](#)

performance, network design [1-12](#)

performance features [1-3](#)

per-VLAN spanning-tree plus

See PVST+

physical ports [11-2](#)

PIM

default configuration [36-8](#)

dense mode

overview [36-4](#)

rendezvous point (RP), described [36-4](#)

RPF lookups [36-7](#)

displaying neighbors [36-52](#)

enabling a mode [36-11](#)

overview [36-3](#)

router-query message interval, modifying [36-26](#)

shared tree and source tree, overview [36-23](#)

shortest path tree, delaying the use of [36-25](#)

sparse mode

join messages and shared tree [36-4](#)

overview [36-4](#)

prune messages [36-5](#)

RPF lookups [36-7](#)

support for [1-9](#)

versions

interoperability [36-9](#)

troubleshooting interoperability problems [36-23](#)

v2 improvements [36-4](#)

PIM-DVMRP, as snooping method [23-8](#)

ping

character output description [39-15](#)

executing [39-15](#)

overview [39-14](#)

PoE

configuring [11-19](#)

support for [1-9](#)

troubleshooting [39-13](#)

policed-DSCP map for QoS [32-51](#)

policers

configuring

for each matched traffic class [32-44](#)

for more than one traffic class [32-47](#)

described [32-3](#)

displaying [32-67](#)

- policers (continued)
 - number of [32-31](#)
 - types of [32-8](#)
 - policing
 - described [32-3](#)
 - token-bucket algorithm [32-9](#)
 - policy-based routing
 - See PBR
 - policy maps for QoS
 - characteristics of [32-44](#)
 - configuring [32-44](#)
 - described [32-7](#)
 - displaying [32-68](#)
 - POP [1-21](#)
 - port ACLs
 - defined [31-2](#)
 - types of [31-3](#)
 - Port Aggregation Protocol
 - See EtherChannel
 - port-based authentication
 - accounting [10-5](#)
 - authentication server
 - defined [10-2](#)
 - RADIUS server [10-2](#)
 - client, defined [10-2](#)
 - configuration guidelines [10-12](#)
 - configuring
 - 802.1x authentication [10-13](#)
 - guest VLAN [10-20](#)
 - host mode [10-19](#)
 - manual re-authentication of a client [10-16](#)
 - periodic re-authentication [10-16](#)
 - quiet period [10-17](#)
 - RADIUS server [10-16](#)
 - RADIUS server parameters on the switch [10-15](#)
 - switch-to-client frame-retransmission number [10-18](#)
 - switch-to-client retransmission time [10-17](#)
 - default configuration [10-11](#)
 - described [10-1](#)
 - port-based authentication (continued)
 - device roles [10-2](#)
 - displaying statistics [10-22](#)
 - EAPOL-start frame [10-3](#)
 - EAP-request/identity frame [10-3](#)
 - EAP-response/identity frame [10-3](#)
 - encapsulation [10-3](#)
 - guest VLAN
 - configuration guidelines [10-9](#)
 - described [10-8](#)
 - initiation and message exchange [10-3](#)
 - method lists [10-13](#)
 - multiple-hosts mode, described [10-19](#)
 - per-user ACLs
 - AAA authorization [10-13](#)
 - configuration tasks [10-10](#)
 - described [10-9](#)
 - RADIUS server attributes [10-9](#)
 - ports
 - authorization state and dot1x port-control command [10-4](#)
 - authorized and unauthorized [10-4](#)
 - voice VLAN [10-7](#)
 - port security
 - and voice VLAN [10-6](#)
 - described [10-6](#)
 - interactions [10-6](#)
 - multiple-hosts mode [10-19](#)
 - resetting to default values [10-21](#)
 - stack changes, effects of [10-10](#)
 - statistics, displaying [10-22](#)
 - switch
 - as proxy [10-2](#)
 - RADIUS client [10-2](#)
 - topologies, supported [10-5](#)
 - upgrading from a previous release [10-13, 32-24](#)

port-based authentication (continued)

VLAN assignment

AAA authorization [10-13](#)characteristics [10-8](#)configuration tasks [10-8](#)described [10-7](#)

voice VLAN

described [10-7](#)PVID [10-7](#)VVID [10-7](#)port blocking [1-3, 24-6](#)

port-channel

See EtherChannel

Port Fast

described [19-2](#)enabling [19-12](#)mode, spanning tree [13-29](#)support for [1-6](#)port membership modes, VLAN [13-3](#)

port priority

MSTP [18-18](#)STP [17-18](#)

ports

10-Gigabit Ethernet module [11-4](#)access [11-3](#)blocking [24-6](#)dynamic access [13-4](#)protected [24-5](#)routed [11-3](#)secure [24-7](#)static-access [13-3, 13-11](#)switch [11-2](#)trunks [13-3, 13-17](#)VLAN assignments [13-11](#)

port security

aging [24-14](#)and QoS trusted boundary [32-35](#)and stacking [24-15](#)configuring [24-10](#)default configuration [24-9](#)described [24-7](#)displaying [24-16](#)on trunk ports [24-11, 24-12](#)sticky learning [24-8](#)violations [24-8](#)with other features [24-10](#)port-shutdown response, VMPS [13-28](#)

Power over Ethernet

See PoE

preferential treatment of traffic

See QoS

prefix lists, BGP [34-51](#)preventing unauthorized access [9-1](#)primary links [20-1](#)primary VLANs [15-1, 15-3](#)

priority

HSRP [35-6](#)overriding CoS [16-6](#)trusting CoS [16-6](#)

private VLAN edge ports

See protected ports

private VLANs

across multiple switches [15-4](#)and SDM template [15-4](#)and SVIs [15-5](#)and switch stacks [15-5](#)benefits of [15-1](#)community ports [15-2](#)community VLANs [15-2, 15-3](#)

- private VLANs (continued)
 - configuration guidelines [15-7, 15-8](#)
 - configuration tasks [15-6](#)
 - configuring [15-10](#)
 - default configuration [15-7](#)
 - end station access to [15-3](#)
 - IP addressing [15-3](#)
 - isolated port [15-2](#)
 - isolated VLANs [15-2, 15-3](#)
 - mapping [15-14](#)
 - monitoring [15-15](#)
 - ports
 - community [15-2](#)
 - configuration guidelines [15-8](#)
 - configuring host ports [15-11](#)
 - configuring promiscuous ports [15-13](#)
 - described [13-4](#)
 - isolated [15-2](#)
 - promiscuous [15-2](#)
 - primary VLANs [15-1, 15-3](#)
 - promiscuous ports [15-2](#)
 - secondary VLANs [15-2](#)
 - subdomains [15-1](#)
 - traffic in [15-5](#)
 - privileged EXEC mode [2-2](#)
 - privilege levels
 - changing the default for lines [9-9](#)
 - command switch [6-23](#)
 - exiting [9-10](#)
 - in CMS [3-7](#)
 - logging into [9-10](#)
 - mapping on member switches [6-23](#)
 - overview [9-2, 9-8](#)
 - setting a command with [9-8](#)
 - promiscuous ports
 - configuring [15-13](#)
 - defined [15-2](#)
 - protected ports [1-7, 24-5](#)
 - protocol-dependent modules, EIGRP [34-35](#)
 - Protocol-Independent Multicast Protocol
 - See PIM
 - provisioning new members for a switch stack [5-7](#)
 - proxy ARP
 - configuring [34-11](#)
 - definition [34-9](#)
 - with IP routing disabled [34-12](#)
 - pruning, VTP
 - disabling
 - in VTP domain [14-14](#)
 - on a port [13-23](#)
 - enabling
 - in VTP domain [14-14](#)
 - on a port [13-22](#)
 - examples [14-5](#)
 - overview [14-5](#)
 - pruning-eligible list
 - changing [13-22](#)
 - for VTP pruning [14-5](#)
 - VLANs [14-15](#)
 - PVST+
 - 802.1Q trunking interoperability [17-11](#)
 - described [17-10](#)
 - instances supported [17-10](#)
-
- ## Q
- QoS
 - and MQC commands [32-1](#)
 - auto-QoS
 - categorizing traffic [32-18](#)
 - configuration and defaults display [32-28](#)
 - configuration guidelines [32-23](#)
 - described [32-18](#)
 - disabling [32-25](#)
 - displaying generated commands [32-25](#)
 - displaying the initial configuration [32-28](#)
 - effects on running configuration [32-23](#)
 - egress queue defaults [32-19](#)

QoS (continued)

auto-QoS (continued)

enabling for VoIP [32-24](#)example configuration [32-26](#)ingress queue defaults [32-19](#)list of generated commands [32-20](#)basic model [32-3](#)

classification

class maps, described [32-7](#)defined [32-3](#)flowchart [32-6](#)forwarding treatment [32-3](#)in frames and packets [32-2](#)IP ACLs, described [32-5, 32-7](#)MAC ACLs, described [32-5, 32-7](#)options for IP traffic [32-5](#)options for non-IP traffic [32-5](#)policy maps, described [32-7](#)trust DSCP, described [32-5](#)trusted CoS, described [32-5](#)trust IP precedence, described [32-5](#)

class maps

configuring [32-42](#)displaying [32-67](#)

configuration guidelines

auto-QoS [32-23](#)standard QoS [32-31](#)

configuring

aggregate policers [32-47](#)auto-QoS [32-18](#)default port CoS value [32-34](#)DSCP maps [32-49](#)DSCP trust states bordering another domain [32-36](#)egress queue characteristics [32-60](#)ingress queue characteristics [32-55](#)IP extended ACLs [32-40](#)IP standard ACLs [32-38](#)MAC ACLs [32-41](#)policy maps [32-44](#)

QoS (continued)

configuring (continued)

port trust states within the domain [32-32](#)trusted boundary [32-35](#)default auto configuration [32-18](#)default standard configuration [32-29](#)displaying statistics [32-67](#)

egress queues

allocating buffer space [32-60](#)buffer allocation scheme, described [32-16](#)configuring shaped weights for SRR [32-64](#)configuring shared weights for SRR [32-65](#)described [32-4](#)displaying the threshold map [32-63](#)flowchart [32-15](#)mapping DSCP or CoS values [32-62](#)scheduling, described [32-4](#)setting WTD thresholds [32-60](#)WTD, described [32-17](#)enabling globally [32-32](#)

flowcharts

classification [32-6](#)egress queueing and scheduling [32-15](#)ingress queueing and scheduling [32-13](#)policing and marking [32-9](#)implicit deny [32-7](#)

ingress queues

allocating bandwidth [32-58](#)allocating buffer space [32-57](#)buffer and bandwidth allocation, described [32-14](#)configuring shared weights for SRR [32-58](#)configuring the priority queue [32-59](#)described [32-3](#)displaying the threshold map [32-56](#)flowchart [32-13](#)mapping DSCP or CoS values [32-56](#)priority queue, described [32-14](#)scheduling, described [32-3](#)

QoS (continued)

ingress queues (continued)

- setting WTD thresholds [32-56](#)

- WTD, described [32-14](#)

IP phones

- automatic classification and queuing [32-18](#)

- detection and trusted settings [32-18, 32-35](#)

- limiting bandwidth on egress interface [32-66](#)

mapping tables

- CoS-to-DSCP [32-50](#)

- displaying [32-67](#)

- DSCP-to-CoS [32-52](#)

- DSCP-to-DSCP-mutation [32-53](#)

- IP-precedence-to-DSCP [32-50](#)

- policed-DSCP [32-51](#)

- types of [32-10](#)

- marked-down actions [32-46](#)

- marking, described [32-3, 32-8](#)

- overview [32-1](#)

- packet modification [32-17](#)

policers

- configuring [32-46, 32-48](#)

- described [32-8](#)

- displaying [32-67](#)

- number of [32-31](#)

- types of [32-8](#)

- policies, attaching to an interface [32-9](#)

policing

- described [32-3, 32-8](#)

- token bucket algorithm [32-9](#)

policy maps

- characteristics of [32-44](#)

- configuring [32-44](#)

- displaying [32-68](#)

- QoS label, defined [32-3](#)

QoS (continued)

queues

- configuring egress characteristics [32-60](#)

- configuring ingress characteristics [32-55](#)

- high priority (expedite) [32-17, 32-66](#)

- location of [32-11](#)

- SRR, described [32-12](#)

- WTD, described [32-11](#)

- rewrites [32-17](#)

- support for [1-7](#)

trust states

- bordering another domain [32-36](#)

- described [32-5](#)

- trusted device [32-35](#)

- within the domain [32-32](#)

quality of service

- See QoS

- queries, IGMP [23-4](#)

R

RADIUS

attributes

- vendor-proprietary [9-31](#)

- vendor-specific [9-29](#)

configuring

- accounting [9-28](#)

- authentication [9-23](#)

- authorization [9-27](#)

- communication, global [9-21, 9-29](#)

- communication, per-server [9-21](#)

- multiple UDP ports [9-21](#)

- default configuration [9-20](#)

- defining AAA server groups [9-25](#)

- displaying the configuration [9-31](#)

- identifying the server [9-21](#)

- RADIUS (continued)
 - in clusters [6-16](#)
 - limiting the services to the user [9-27](#)
 - method list, defined [9-20](#)
 - operation of [9-19](#)
 - overview [9-18](#)
 - suggested network environments [9-18](#)
 - support for [1-7](#)
 - tracking services accessed by user [9-28](#)
- range
 - macro [11-10](#)
 - of interfaces [11-9](#)
- rapid convergence [18-8](#)
- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - 802.1Q trunking interoperability [17-11](#)
 - described [17-10](#)
 - instances supported [17-10](#)
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP [34-9](#)
- rcommand command [6-23](#)
- RCP
 - configuration files
 - downloading [B-17](#)
 - overview [B-16](#)
 - preparing the server [B-16](#)
 - uploading [B-18](#)
 - image files
 - deleting old image [B-32](#)
 - downloading [B-31](#)
 - preparing the server [B-29](#)
 - uploading [B-33](#)
- reconfirmation interval, VMPS, changing [13-31](#)
- recovery procedures [39-1](#)
- redundancy
 - EtherChannel [33-2](#)
 - HSRP [35-1](#)
 - STP
 - backbone [17-9](#)
 - multidrop backbone [19-5](#)
 - path cost [13-26](#)
 - port priority [13-24](#)
- redundant clusters
 - See cluster standby group
- redundant links and UplinkFast [19-15](#)
- reliable transport protocol, EIGRP [34-34](#)
- reloading software [4-16](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- report suppression, IGMP
 - described [23-5](#)
 - disabling [23-11](#)
- requirements
 - cluster
 - See release notes
- resequencing ACL entries [31-15](#)
- resets, in BGP [34-46](#)
- resetting a UDLD-shutdown interface [26-6](#)
- restricting access
 - NTP services [7-8](#)
 - overview [9-1](#)
 - passwords and privilege levels [9-2](#)
 - RADIUS [9-18](#)
 - TACACS+ [9-10](#)
- retry count, VMPS, changing [13-32](#)

- reverse address resolution [34-9](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [34-20](#)
 - 1112, IP multicast and IGMP [23-2](#)
 - 1157, SNMPv1 [30-2](#)
 - 1163, BGP [34-40](#)
 - 1166, IP addresses [34-6](#)
 - 1253, OSPF [34-25](#)
 - 1267, BGP [34-40](#)
 - 1305, NTP [7-2](#)
 - 1587, NSSAs [34-25](#)
 - 1757, RMON [28-2](#)
 - 1771, BGP [34-40](#)
 - 1901, SNMPv2C [30-2](#)
 - 1902 to 1907, SNMPv2 [30-2](#)
 - 2236, IP multicast and IGMP [23-2](#)
 - 2273-2275, SNMPv3 [30-2](#)
- RIP
 - advertisements [34-20](#)
 - authentication [34-23](#)
 - configuring [34-21](#)
 - default configuration [34-20](#)
 - described [34-20](#)
 - hop counts [34-20](#)
 - split horizon [34-23](#)
 - summary addresses [34-23](#)
 - support for [1-8](#)
- RMON
 - default configuration [28-3](#)
 - displaying status [28-6](#)
 - enabling alarms and events [28-3](#)
 - groups supported [28-2](#)
 - overview [28-1](#)
 - statistics
 - collecting group Ethernet [28-6](#)
 - collecting group history [28-5](#)
 - support for [1-9](#)
- root guard
 - described [19-10](#)
 - enabling [19-17](#)
 - support for [1-6](#)
- root switch
 - MSTP [18-15](#)
 - STP [17-16](#)
- route calculation timers, OSPF [34-31](#)
- route dampening, BGP [34-58](#)
- routed packets, ACLs on [31-39](#)
- routed ports
 - configuring [34-4](#)
 - defined [11-3](#)
 - in switch clusters [6-8](#)
 - IP addresses on [11-21, 34-5](#)
- route-map command [34-70](#)
- route maps
 - BGP [34-49](#)
 - policy-based routing [34-68](#)
- router ACLs
 - defined [31-2](#)
 - types of [31-4](#)
- route reflectors, BGP [34-57](#)
- router ID, OSPF [34-32](#)
- route selection, BGP [34-47](#)
- route summarization, OSPF [34-30](#)
- routing
 - default [34-2](#)
 - dynamic [34-3](#)
 - redistribution of information [34-64](#)
 - static [34-2](#)
- routing domain confederation, BGP [34-56](#)
- Routing Information Protocol
 - See RIP
- routing protocol administrative distances [34-63](#)

RSPAN

- and stack changes [27-10](#)
- characteristics [27-9](#)
- configuration guidelines [27-17](#)
- default configuration [27-11](#)
- destination ports [27-8](#)
- displaying status [27-24](#)
- in a switch stack [27-2](#)
- interaction with other features [27-9](#)
- monitored ports [27-6](#)
- monitoring ports [27-8](#)
- overview [1-9, 27-1](#)
- received traffic [27-5](#)
- session limits [27-11](#)
- sessions
 - creating [27-18](#)
 - defined [27-4](#)
 - limiting source traffic to specific VLANs [27-23](#)
 - specifying monitored ports [27-18](#)
 - with ingress traffic enabled [27-21](#)
- source ports [27-6](#)
- transmitted traffic [27-6](#)
- VLAN-based [27-7](#)

RSTP

- active topology [18-7](#)
- BPDU
 - format [18-10](#)
 - processing [18-11](#)
- designated port, defined [18-7](#)
- designated switch, defined [18-7](#)
- interoperability with 802.1D
 - described [18-6](#)
 - restarting migration process [18-23](#)
 - topology changes [18-11](#)
- overview [18-6](#)
- port roles
 - described [18-7](#)
 - synchronized [18-9](#)
- proposal-agreement handshake process [18-8](#)

RSPAN (continued)

- rapid convergence
 - cross-stack rapid convergence [18-8](#)
 - described [18-8](#)
 - edge ports and Port Fast [18-8](#)
 - point-to-point links [18-8, 18-23](#)
 - root ports [18-8](#)
- root port, defined [18-7](#)
- See also MSTP
- running configuration, saving [4-10](#)

S

- SC (standby command switch) [6-10, 6-20](#)
- scheduled reloads [4-16](#)
- SDM
 - described [8-1](#)
 - switch stack consideration [5-10](#)
 - templates
 - configuring [8-4](#)
 - number of [8-1](#)
- SDM mismatch mode [5-10, 8-2](#)
- SDM template
 - aggregator [8-1](#)
 - configuring [8-3](#)
 - desktop [8-1](#)
 - types of [8-1](#)
- secondary VLANs [15-2](#)
- secure MAC addresses
 - and switch stacks [24-16](#)
 - deleting [24-13](#)
 - maximum number of [24-8](#)
 - types of [24-8](#)
- secure ports
 - and switch stacks [24-15](#)
 - configuring [24-7](#)
- secure remote connections [9-38](#)
- Secure Shell
 - See SSH

- security, port [24-7](#)
- security features [1-6](#)
- sequence numbers in log messages [29-8](#)
- server mode, VTP [14-3](#)
- service-provider network, MSTP and RSTP [18-1](#)
- set-request operation [30-5](#)
- setup (CLI) program [1-10](#)
 - See also hardware installation guide
- setup program
 - failed command switch replacement [39-11](#)
 - replacing failed command switch [39-9](#)
- severity levels, defining in system messages [29-9](#)
- SFPs
 - monitoring status of [1-9, 11-24, 39-14](#)
 - numbering of [11-8](#)
 - security and identification [39-13](#)
 - status
 - displaying [1-9](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [31-22](#)
- show and more command output, filtering [2-8](#)
- show cdp traffic command [25-5](#)
- show cluster members command [6-23](#)
- show configuration command [11-20](#)
- show forward command [39-23](#)
- show interfaces command [11-16, 11-20](#)
- show platform forward command [39-23](#)
- show running-config command
 - displaying ACLs [31-20, 31-21, 31-32, 31-34](#)
 - interface description in [11-20](#)
- shutdown command on interfaces [11-25](#)
- Simple Network Management Protocol
 - See SNMP
- small form-factor pluggable modules
 - See SFPs
- Smartports macros
 - applying Cisco-default macros [12-6](#)
 - applying global parameter values [12-5, 12-6](#)
 - applying macros [12-5](#)
 - applying parameter values [12-5, 12-7](#)
 - configuration guidelines [12-3](#)
 - creating [12-4](#)
 - default configuration [12-2](#)
 - defined [12-1](#)
 - displaying [12-8](#)
 - tracing [12-3](#)
 - website [12-2](#)
- SNAP [25-1](#)
- SNMP
 - accessing MIB variables with [30-5](#)
 - agent
 - described [30-4](#)
 - disabling [30-8](#)
 - authentication level [30-11](#)
 - community strings
 - configuring [30-8](#)
 - for cluster switches [30-4](#)
 - overview [30-4](#)
 - configuration examples [30-16](#)
 - default configuration [30-7](#)
 - engine ID [30-7](#)
 - groups [30-7, 30-10](#)
 - host [30-7](#)
 - ifIndex values [30-6](#)
 - in-band management [1-5](#)
 - in clusters [6-14](#)
 - informs
 - and trap keyword [30-12](#)
 - described [30-5](#)
 - differences from traps [30-5](#)
 - disabling [30-15](#)
 - enabling [30-15](#)

SNMP (continued)

- limiting access by TFTP servers [30-16](#)
 - limiting system log messages to NMS [29-10](#)
 - manager functions [1-4](#), [30-3](#)
 - managing clusters with [6-24](#)
 - MIBs
 - location of [A-3](#)
 - supported [A-1](#)
 - notifications [30-5](#)
 - overview [30-1](#), [30-5](#)
 - security levels [30-3](#)
 - status, displaying [30-17](#)
 - system contact and location [30-15](#)
 - trap manager, configuring [30-14](#)
 - traps
 - described [30-3](#), [30-5](#)
 - differences from informs [30-5](#)
 - disabling [30-15](#)
 - enabling [30-12](#)
 - enabling MAC address notification [7-23](#)
 - overview [30-1](#), [30-5](#)
 - types of [30-12](#)
 - users [30-7](#), [30-10](#)
 - versions supported [30-2](#)
- SNMPv1 [30-2](#)
- SNMPv2C [30-2](#)
- SNMPv3 [30-2](#)
- snooping, IGMP [23-1](#)
- software compatibility
- See stacks, switch
- software images
- location in flash [B-20](#)
 - recovery procedures [39-2](#)
 - scheduling reloads [4-16](#)
 - tar file format, described [B-21](#)
- See also downloading and uploading

- source addresses, in ACLs [31-12](#)
 - source-and-destination-IP address based forwarding, EtherChannel [33-8](#)
 - source-and-destination MAC address forwarding, EtherChannel [33-8](#)
 - source-IP address based forwarding, EtherChannel [33-8](#)
 - source-MAC address forwarding, EtherChannel [33-8](#)
- SPAN
- and stack changes [27-10](#)
 - configuration guidelines [27-11](#)
 - default configuration [27-11](#)
 - destination ports [27-8](#)
 - displaying status [27-24](#)
 - interaction with other features [27-9](#)
 - monitored ports [27-6](#)
 - monitoring ports [27-8](#)
 - overview [1-9](#), [27-1](#)
 - received traffic [27-5](#)
 - session limits [27-11](#)
 - sessions
 - configuring ingress forwarding [27-16](#), [27-22](#)
 - creating [27-12](#)
 - defined [27-4](#)
 - limiting source traffic to specific VLANs [27-16](#)
 - removing destination (monitoring) ports [27-14](#)
 - specifying monitored ports [27-12](#)
 - with ingress traffic enabled [27-15](#)
 - source ports [27-6](#)
 - transmitted traffic [27-6](#)
 - VLAN-based [27-7](#)
- spanning tree and native VLANs [13-19](#)
- Spanning Tree Protocol
- See STP
- SPAN traffic [27-5](#)
- speed, configuring on interfaces [11-14](#)
- split horizon
- IGRP [34-24](#)
 - RIP [34-23](#)

SRR

configuring

shaped weights on egress queues [32-64](#)shared weights on egress queues [32-65](#)shared weights on ingress queues [32-58](#)described [32-12](#)shaped mode [32-12](#)shared mode [32-12](#)support for [1-8](#)

SSH

configuring [9-39](#)cryptographic software image [9-37](#)described [1-5, 9-38](#)encryption methods [9-38](#)switch stack considerations [5-14, 9-38](#)user authentication methods, supported [9-38](#)

stack changes, effects on

802.1x port-based authentication [10-10](#)ACL configuration [31-6](#)CDP [25-2](#)cross-stack EtherChannel [33-12](#)EtherChannel [33-9](#)fallback bridging [38-3](#)HSRP [35-2](#)IGMP snooping [23-6](#)IP routing [34-3](#)MAC address tables [7-22](#)MSTP [18-6](#)multicast routing [36-8](#)MVR [23-13](#)port security [24-15](#)SDM template selection [8-2](#)SNMP [30-1](#)SPAN and RSPAN [27-10](#)STP [17-12](#)switch clusters [6-14](#)system message log [29-2](#)VLANs [13-7](#)VTP [14-6](#)

stack master

bridge ID (MAC address) [5-5](#)defined [5-1](#)election [5-4](#)re-election [5-4](#)

See also stacks, switch

stack member

accessing CLI of specific member [5-19](#)

configuring

member number [5-17](#)priority value [5-18](#)defined [5-1](#)displaying information of [5-20](#)number [5-6](#)priority value [5-7](#)provisioning a new member [5-18](#)replacing [5-13](#)

See also stacks, switch

stack member number [11-7](#)stack protocol version [5-11](#)

stacks, switch

accessing CLI of specific member [5-19](#)

assigning information

member number [5-17](#)priority value [5-18](#)provisioning a new member [5-18](#)benefits [1-2](#)bridge ID [5-5](#)CDP considerations [25-2](#)compatibility, software [5-10](#)configuration file [5-12](#)configuration scenarios [5-15](#)copying an image file from one member to another [B-34](#)default configuration [5-17](#)description of [5-1](#)displaying information of [5-20](#)HSRP considerations [35-2](#)in clusters [6-14](#)incompatible software and image upgrades [5-11, B-34](#)

- stacks, switch (continued)
 - MAC address considerations [7-22](#)
 - management connectivity [5-14](#)
 - managing [5-1](#)
 - membership [5-3](#)
 - merged [5-3](#)
 - MSTP instances supported [17-10](#)
 - multicast routing, stack master and member roles [36-8](#)
 - offline configuration
 - described [5-7](#)
 - effects of adding a provisioned switch [5-8](#)
 - effects of removing a provisioned switch [5-10](#)
 - effects of replacing a provisioned switch [5-10](#)
 - provisioned configuration, defined [5-7](#)
 - provisioned switch, defined [5-7](#)
 - provisioning a new member [5-18](#)
 - partitioned [5-3, 39-8](#)
 - provisioned switch
 - adding [5-8](#)
 - removing [5-10](#)
 - replacing [5-10](#)
 - replacing a failed member [5-13](#)
 - See also stack master and stack member
 - software compatibility [5-10](#)
 - software image version [5-11](#)
 - stack protocol version [5-11](#)
 - STP
 - bridge ID [17-3](#)
 - instances supported [17-10](#)
 - root port selection [17-3](#)
 - stack root switch election [17-3](#)
 - system messages
 - hostnames in the display [29-1](#)
 - remotely monitoring [29-2](#)
 - system prompt consideration [7-14](#)
 - system-wide configuration considerations [5-13](#)
 - upgrading [B-34](#)
- StackWise technology, Cisco [1-3](#)
 - See also stacks, switch
- Standby Command Configuration window [6-21](#)
- standby command switch
 - configuring [6-20](#)
 - considerations [6-11](#)
 - defined [6-2](#)
 - priority [6-10](#)
 - requirements [6-3](#)
 - virtual IP address [6-11](#)
 - See also cluster standby group and HSRP
- standby group, cluster
 - See cluster standby group and HSRP
- standby ip command [35-4](#)
- standby links [20-1](#)
- standby router [35-1](#)
- standby timers, HSRP [35-9](#)
- startup configuration
 - booting
 - manually [4-13](#)
 - specific image [4-13](#)
 - clearing [B-19](#)
 - configuration file
 - automatically downloading [4-12](#)
 - specifying the filename [4-12](#)
 - default boot configuration [4-12](#)
- static access ports
 - assigning to VLAN [13-11](#)
 - defined [11-3, 13-3](#)
- static addresses
 - See addresses
- static IP routing [1-8](#)
- static MAC addressing [1-6](#)
- static routes, configuring [34-62](#)
- static routing [34-2](#)
- static VLAN membership [13-2](#)

statistics

- 802.1x [10-22](#)
- CDP [25-5](#)
- interface [11-24](#)
- IP multicast routing [36-51](#)
- OSPF [34-33](#)
- QoS ingress and egress [32-67](#)
- RMON group Ethernet [28-6](#)
- RMON group history [28-5](#)
- SNMP input and output [30-17](#)
- VTP [14-16](#)

sticky learning [24-8](#)

storm control

- configuring [24-3](#)
- described [24-2](#)
- displaying [24-16](#)
- support for [1-3](#)
- thresholds [24-2](#)

STP

- 802.1D and bridge ID [17-4](#)
- 802.1D and multicast addresses [17-9](#)
- 802.1t and VLAN identifier [17-4](#)
- accelerating root port selection [19-4](#)
- BackboneFast
 - described [19-7](#)
 - disabling [19-17](#)
 - enabling [19-16](#)
- BPDU filtering
 - described [19-3](#)
 - disabling [19-15](#)
 - enabling [19-14](#)
- BPDU guard
 - described [19-3](#)
 - disabling [19-14](#)
 - enabling [19-13](#)
- BPDU message exchange [17-3](#)
- configuration guidelines [17-13, 19-12](#)

STP (continued)

configuring

- forward-delay time [17-23](#)
- hello time [17-22](#)
- maximum aging time [17-23](#)
- path cost [17-20](#)
- port priority [17-18](#)
- root switch [17-16](#)
- secondary root switch [17-17](#)
- spanning-tree mode [17-14](#)
- switch priority [17-21](#)

counters, clearing [17-24](#)

cross-stack UplinkFast

- described [19-5](#)
- enabling [19-16](#)

default configuration [17-13](#)default optional feature configuration [19-12](#)designated port, defined [17-4](#)designated switch, defined [17-4](#)detecting indirect link failures [19-8](#)disabling [17-15](#)displaying status [17-24](#)

EtherChannel guard

- described [19-10](#)
- disabling [19-17](#)
- enabling [19-17](#)

extended system ID

- effects on root switch [17-16](#)
- effects on the secondary root switch [17-17](#)
- overview [17-4](#)
- unexpected behavior [17-16](#)

features supported [1-5](#)inferior BPDU [17-3](#)instances supported [17-10](#)interface state, blocking to forwarding [19-2](#)

STP (continued)

interface states

- blocking [17-7](#)
- disabled [17-8](#)
- forwarding [17-6, 17-7](#)
- learning [17-7](#)
- listening [17-7](#)
- overview [17-5](#)

interoperability and compatibility among modes [17-11](#)keepalive messages [17-2](#)limitations with 802.1Q trunks [17-11](#)

load sharing

- overview [13-24](#)
- using path costs [13-26](#)
- using port priorities [13-24](#)

loop guard

- described [19-11](#)
- enabling [19-18](#)

modes supported [17-10](#)multicast addresses, effect of [17-9](#)optional features supported [1-6](#)overview [17-2](#)path costs [13-26, 13-27](#)

Port Fast

- described [19-2](#)
- enabling [19-12](#)

port priorities [13-25](#)preventing root switch selection [19-10](#)protocols supported [17-10](#)redundant connectivity [17-9](#)

root guard

- described [19-10](#)
- enabling [19-17](#)

root port, defined [17-3](#)root port selection on a switch stack [17-3](#)

STP (continued)

root switch

- configuring [17-16](#)
- effects of extended system ID [17-4, 17-16](#)
- election [17-3](#)
- unexpected behavior [17-16](#)

shutdown Port Fast-enabled port [19-3](#)stack changes, effects of [17-12](#)status, displaying [17-24](#)superior BPDU [17-3](#)timers, described [17-22](#)

UplinkFast

- described [19-4](#)
- enabling [19-15](#)

VLAN-bridge [17-12](#)stratum, NTP [7-2](#)stub areas, OSPF [34-29](#)subdomains, private VLAN [15-1](#)subnet mask [34-6](#)subnet zero [34-7](#)success response, VMPS [13-28](#)summer time [7-13](#)SunNet Manager [1-4](#)supernet [34-7](#)

SVIs

- and IP unicast routing [34-4](#)
- and router ACLs [31-4](#)
- connecting VLANs [11-6](#)
- defined [11-4](#)
- routing between VLANs [13-2](#)

switch clustering technology [6-1](#)

See also clusters, switch

switch console port [1-5](#)

Switch Database Management

See SDM

switched packets, ACLs on [31-38](#)

- Switched Port Analyzer
 - See SPAN
 - switched ports [11-2](#)
 - Switch Manager [3-10](#)
 - switchport block multicast command [24-6](#)
 - switchport block unicast command [24-6](#)
 - switchport command [11-13](#)
 - switchport protected command [24-5](#)
 - switch priority
 - MSTP [18-20](#)
 - STP [17-21](#)
 - switch software features [1-1](#)
 - switch virtual interface
 - See SVI
 - synchronization, BGP [34-44](#)
 - syslog
 - See system message logging
 - system clock
 - configuring
 - daylight saving time [7-13](#)
 - manually [7-11](#)
 - summer time [7-13](#)
 - time zones [7-12](#)
 - displaying the time and date [7-12](#)
 - overview [7-2](#)
 - See also NTP
 - system message logging
 - default configuration [29-4](#)
 - defining error message severity levels [29-9](#)
 - disabling [29-4](#)
 - displaying the configuration [29-13](#)
 - enabling [29-5](#)
 - facility keywords, described [29-13](#)
 - level keywords, described [29-9](#)
 - limiting messages [29-10](#)
 - message format [29-2](#)
 - overview [29-1](#)
 - sequence numbers, enabling and disabling [29-8](#)
 - setting the display destination device [29-5](#)
 - system message logging (continued)
 - stack changes, effects of [29-2](#)
 - synchronizing log messages [29-6](#)
 - syslog facility [1-9](#)
 - time stamps, enabling and disabling [29-7](#)
 - UNIX syslog servers
 - configuring the daemon [29-11](#)
 - configuring the logging facility [29-12](#)
 - facilities supported [29-13](#)
 - system name
 - default configuration [7-15](#)
 - default setting [7-15](#)
 - manual configuration [7-15](#)
 - See also DNS
 - system prompt
 - default setting [7-14 to 7-15](#)
 - manual configuration [7-16](#)
 - system resources, optimizing [8-1](#)
-
- ## T
- TACACS+
 - accounting, defined [9-11](#)
 - authentication, defined [9-11](#)
 - authorization, defined [9-11](#)
 - configuring
 - accounting [9-17](#)
 - authentication key [9-13](#)
 - authorization [9-16](#)
 - login authentication [9-14](#)
 - default configuration [9-13](#)
 - displaying the configuration [9-17](#)
 - identifying the server [9-13](#)
 - in clusters [6-16](#)
 - limiting the services to the user [9-16](#)
 - operation of [9-12](#)
 - overview [9-10](#)
 - support for [1-7](#)
 - tracking services accessed by user [9-17](#)

- tar files
 - creating [B-6](#)
 - displaying the contents of [B-6](#)
 - extracting [B-7](#)
 - image file format [B-21](#)
- TDR [1-9](#)
- Telnet
 - accessing management interfaces [2-9](#)
 - from a browser [2-10](#)
 - number of connections [1-5](#)
 - setting a password [9-6](#)
- templates, SDM [8-1](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password [9-6](#)
- TFTP
 - configuration files
 - downloading [B-11](#)
 - preparing the server [B-10](#)
 - uploading [B-11](#)
 - configuration files in base directory [4-6](#)
 - configuring for autoconfiguration [4-5](#)
 - image files
 - deleting [B-24](#)
 - downloading [B-23](#)
 - preparing the server [B-22](#)
 - uploading [B-24](#)
 - limiting access by servers [30-16](#)
- TFTP server [1-4](#)
- threshold, traffic level [24-2](#)
- time
 - See NTP and system clock
- Time Domain Reflector
 - See TDR
- time-range command [31-17](#)
- time ranges in ACLs [31-17](#)
- time stamps in log messages [29-7](#)
- time zones [7-12](#)
- Token Ring VLANs
 - support for [13-6](#)
 - VTP support [14-4](#)
- Topology view, described [3-2, 3-15](#)
- ToS [1-7](#)
- traceroute, Layer 2
 - and ARP [39-17](#)
 - and CDP [39-16](#)
 - broadcast traffic [39-16](#)
 - described [39-16](#)
 - IP addresses and subnets [39-17](#)
 - MAC addresses and VLANs [39-16](#)
 - multicast traffic [39-16](#)
 - multiple devices on a port [39-17](#)
 - unicast traffic [39-16](#)
 - usage guidelines [39-16](#)
- traceroute command [39-18](#)
 - See also IP traceroute
- traffic
 - blocking flooded [24-6](#)
 - fragmented [31-5](#)
 - unfragmented [31-5](#)
- traffic policing [1-8](#)
- traffic suppression [24-2](#)
- transparent mode, VTP [14-3, 14-12](#)
- trap-door mechanism [4-2](#)
- traps
 - configuring MAC address notification [7-23](#)
 - configuring managers [30-12](#)
 - defined [30-3](#)
 - enabling [7-23, 30-12](#)
 - notification types [30-12](#)
 - overview [30-1, 30-5](#)
- troubleshooting
 - connectivity problems [39-14, 39-16, 39-17](#)
 - detecting unidirectional links [26-1](#)
 - displaying crash information [39-25](#)
 - PIMv1 and PIMv2 interoperability problems [36-23](#)
 - setting packet forwarding [39-23](#)

troubleshooting (continued)

- SFP security and identification [39-13](#)
- show forward command [39-23](#)
- with CiscoWorks [30-5](#)
- with debug commands [39-21](#)
- with ping [39-14](#)
- with system message logging [29-1](#)
- with traceroute [39-17](#)

trunking encapsulation [1-6](#)

trunk ports

- configuring [13-20](#)
- defined [11-3, 13-3](#)
- encapsulation [13-20, 13-25, 13-27](#)
- secure MAC addresses on [24-11, 24-12](#)

trunks

- allowed-VLAN list [13-21](#)
- configuring [13-20, 13-25, 13-27](#)
- ISL [13-17](#)
- load sharing
 - setting STP path costs [13-26](#)
 - using STP port priorities [13-24, 13-25](#)
- native VLAN for untagged traffic [13-23](#)
- parallel [13-26](#)
- pruning-eligible list [13-22](#)
- to non-DTP device [13-17](#)
- understanding [13-17](#)

trusted boundary for QoS [32-35](#)

trusted port states

- between QoS domains [32-36](#)
- classification options [32-5](#)
- ensuring port security for IP phones [32-35](#)
- support for [1-8](#)
- within a QoS domain [32-32](#)

twisted-pair Ethernet, detecting unidirectional links [26-1](#)

type of service

- See ToS

U

UDLD

- default configuration [26-4](#)
- disabling
 - fiber-optic interfaces [26-5](#)
 - globally [26-5](#)
 - per interface [26-6](#)
- echoing detection mechanism [26-3](#)
- enabling
 - globally [26-5](#)
 - per interface [26-6](#)
- link-detection mechanism [26-1](#)
- neighbor database [26-2](#)
- overview [26-1](#)
- resetting an interface [26-6](#)
- status, displaying [26-7](#)
- support for [1-5](#)

UDP, configuring [34-16](#)

unauthorized ports with 802.1x [10-4](#)

unicast MAC address filtering [1-4](#)

- and adding static addresses [7-27](#)
- and broadcast MAC addresses [7-26](#)
- and CPU packets [7-26](#)
- and multicast addresses [7-26](#)
- and router MAC addresses [7-26](#)
- configuration guidelines [7-26](#)
- described [7-26](#)

unicast storm [24-2](#)

unicast storm control command [24-4](#)

unicast traffic, blocking [24-6](#)

UniDirectional Link Detection protocol

- See UDLD

UNIX syslog servers

- daemon configuration [29-11](#)
- facilities supported [29-13](#)
- message logging configuration [29-12](#)

- unrecognized Type-Length-Value (TLV) support [14-4](#)
 - upgrading information
 - See release notes
 - upgrading software images
 - See downloading
 - UplinkFast
 - described [19-4](#)
 - disabling [19-16](#)
 - enabling [19-15](#)
 - support for [1-5](#)
 - uploading
 - configuration files
 - preparing [B-10, B-13, B-16](#)
 - reasons for [B-8](#)
 - using FTP [B-15](#)
 - using RCP [B-18](#)
 - using TFTP [B-11](#)
 - image files
 - preparing [B-22, B-25, B-29](#)
 - reasons for [B-20](#)
 - using FTP [B-28](#)
 - using RCP [B-33](#)
 - using TFTP [B-24](#)
 - User Datagram Protocol
 - See UDP
 - user EXEC mode [2-2](#)
 - username-based authentication [9-7](#)
-
- V**
- version-dependent transparent mode [14-4](#)
 - version mismatch (VM) mode [5-12](#)
 - virtual IP address
 - cluster standby group [6-11, 6-21](#)
 - command switch [6-11, 6-21](#)
 - See also IP addresses
 - virtual router [35-1, 35-2](#)
 - vlan.dat file [13-5](#)
 - VLAN 1, disabling on a trunk port [13-22](#)
 - VLAN 1 minimization [13-21](#)
 - VLAN ACLs
 - See VLAN maps
 - vlan-assignment response, VMPS [13-28](#)
 - VLAN configuration
 - at bootup [13-8](#)
 - saving [13-8](#)
 - VLAN configuration mode [2-2, 13-7](#)
 - VLAN database
 - and startup configuration file [13-8](#)
 - and VTP [14-1](#)
 - VLAN configuration saved in [13-8](#)
 - VLANs saved in [13-5](#)
 - vlan database command [13-7](#)
 - VLAN filtering and SPAN [27-7](#)
 - vlan global configuration command [13-7](#)
 - VLAN ID, discovering [7-28](#)
 - VLAN management domain [14-2](#)
 - VLAN Management Policy Server
 - See VMPS
 - VLAN map entries, order of [31-30](#)
 - VLAN maps
 - applying [31-34](#)
 - common uses for [31-34](#)
 - configuration example [31-35](#)
 - configuration guidelines [31-30](#)
 - configuring [31-30](#)
 - creating [31-31](#)
 - defined [31-2](#)
 - denying access example [31-36](#)
 - denying and permitting packets [31-32](#)
 - displaying [31-41](#)
 - examples [31-36](#)
 - removing [31-34](#)
 - support for [1-7](#)
 - with router ACLs [31-40](#)

- VLAN membership
 - confirming [13-31](#)
 - modes [13-3](#)
- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [13-9](#)
 - adding to VLAN database [13-9](#)
 - aging dynamic addresses [17-10](#)
 - allowed on trunk [13-21](#)
 - and spanning-tree instances [13-3, 13-7, 13-13](#)
 - configuration guidelines, extended-range VLANs [13-13](#)
 - configuration guidelines, normal-range VLANs [13-6](#)
 - configuration options [13-7](#)
 - configuring [13-1](#)
 - configuring IDs 1006 to 4094 [13-13](#)
 - connecting through SVIs [11-6](#)
 - creating in config-vlan mode [13-9](#)
 - creating in VLAN configuration mode [13-10](#)
 - default configuration [13-8](#)
 - deleting [13-11](#)
 - described [11-2, 13-1](#)
 - displaying [13-16](#)
 - extended-range [13-1, 13-12](#)
 - features [1-6](#)
 - illustrated [13-2](#)
 - internal [13-13](#)
 - in the switch stack [13-7](#)
 - limiting source traffic with RSPAN [27-23](#)
 - limiting source traffic with SPAN [27-16](#)
 - modifying [13-9](#)
 - native, configuring [13-23](#)
 - normal-range [13-1, 13-5](#)
 - number supported [1-6](#)
 - parameters [13-5](#)
 - port membership modes [13-3](#)
 - static-access ports [13-11](#)
 - STP and 802.1Q trunks [17-11](#)
 - supported [13-3](#)
- VLANs (continued)
 - Token Ring [13-6](#)
 - traffic between [13-2](#)
 - VLAN-bridge STP [17-12, 38-2](#)
 - VTP modes [14-3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [13-17](#)
- VMPS
 - administering [13-32](#)
 - configuration example [13-33](#)
 - configuration guidelines [13-29](#)
 - default configuration [13-29](#)
 - description [13-27](#)
 - dynamic port membership
 - described [13-28](#)
 - reconfirming [13-31](#)
 - troubleshooting [13-33](#)
 - entering server address [13-30](#)
 - mapping MAC addresses to VLANs [13-28](#)
 - monitoring [13-32](#)
 - reconfirmation interval, changing [13-31](#)
 - reconfirming membership [13-31](#)
 - retry count, changing [13-32](#)
- voice-over-IP [16-1](#)
- voice VLAN
 - Cisco 7960 phone, port connections [16-1](#)
 - configuration guidelines [8-4, 16-3](#)
 - configuring IP phones for data traffic
 - override CoS of incoming frame [16-6](#)
 - trust CoS priority of incoming frame [16-6](#)
 - configuring ports for voice traffic in
 - 802.1p priority tagged frames [16-5](#)
 - 802.1Q frames [16-4](#)
 - connecting to an IP phone [16-4](#)
 - default configuration [16-3](#)
 - described [16-1](#)
 - displaying [16-6](#)
- VQP [1-6, 13-27](#)

VTP

- adding a client to a domain [14-15](#)
- advertisements [13-19](#), [14-3](#), [14-4](#)
- and extended-range VLANs [14-2](#)
- and normal-range VLANs [14-2](#)
- client mode, configuring [14-11](#)
- configuration
 - global configuration mode [14-7](#)
 - guidelines [14-8](#)
 - privileged EXEC mode [14-7](#)
 - requirements [14-9](#)
 - saving [14-8](#)
 - VLAN configuration mode [14-8](#)
- configuration mode options [14-7](#)
- configuration requirements [14-9](#)
- configuration revision number
 - guideline [14-15](#)
 - resetting [14-15](#)
- configuring
 - client mode [14-11](#)
 - server mode [14-10](#)
 - transparent mode [14-12](#)
- consistency checks [14-4](#)
- default configuration [14-7](#)
- described [14-1](#)
- disabling [14-12](#)
- domain names [14-8](#)
- domains [14-2](#)
- modes
 - client [14-3](#), [14-11](#)
 - server [14-3](#), [14-10](#)
 - transitions [14-3](#)
 - transparent [14-3](#), [14-12](#)
- monitoring [14-16](#)
- passwords [14-9](#)

VTP (continued)

- pruning
 - disabling [14-14](#)
 - enabling [14-14](#)
 - examples [14-5](#)
 - overview [14-5](#)
 - support for [1-6](#)
- pruning-eligible list, changing [13-22](#)
- server mode, configuring [14-10](#)
- statistics [14-16](#)
- support for [1-6](#)
- Token Ring support [14-4](#)
- transparent mode, configuring [14-12](#)
- using [14-1](#)
- version, guidelines [14-9](#)
- Version 1 [14-4](#)
- Version 2
 - configuration guidelines [14-9](#)
 - disabling [14-14](#)
 - enabling [14-13](#)
 - overview [14-4](#)

W

- weighted tail drop
 - See WTD
- wizards [1-2](#), [3-6](#)
- WTD
 - described [32-11](#)
 - setting thresholds
 - egress queue-sets [32-60](#)
 - ingress queues [32-56](#)
 - support for [1-8](#)

X

- Xmodem protocol [39-2](#)