



Numerics

- 802.1Q trunk ports and native VLANs [2-626](#)
 - 802.1Q tunnel ports
 - configuring [2-568](#)
 - displaying [2-335](#)
 - limitations [2-569](#)
 - 802.1x
 - and switchport modes [2-569](#)
 - violation error recovery [2-100](#)
- See also port-based authentication

A

- aaa accounting dot1x command [2-1](#)
- aaa authentication dot1x command [2-3](#)
- AAA methods [2-3](#)
- abort command [2-624](#)
- access control entries
 - See ACEs
- access control lists
 - See ACLs
- access groups
 - IP [2-112](#)
 - MAC, displaying [2-399](#)
- access map configuration mode [2-189](#)
- access mode [2-568](#)
- access ports [2-568](#)
- ACEs [2-77, 2-251](#)

ACLs

- deny [2-75](#)
- displaying [2-297](#)
- for non-IP protocols [2-170](#)
- IP [2-112](#)
- matching [2-189](#)
- on Layer 2 interfaces [2-112](#)
- permit [2-249](#)
- action command [2-5](#)
- address aliasing [2-238](#)
- aggregate-port learner [2-243](#)
- allowed VLANs [2-587](#)
- apply command [2-624](#)
- archive copy-sw command [2-7](#)
- archive download-sw command [2-10](#)
- archive tar command [2-14](#)
- archive upload-sw command [2-17](#)
- arp access-list command [2-19](#)
- audience [xvii](#)
- authorization state of controlled port [2-89](#)
- autonegotiation of duplex mode [2-97](#)
- auto qos voip command [2-21](#)

B

- BackboneFast, for STP [2-501](#)
- backup interfaces
 - configuring [2-564](#)
 - displaying [2-357](#)
- boot (boot loader) command [A-2](#)

- boot auto-copy-sw command [2-26](#)
 - boot boothlpr command [2-27](#)
 - boot config-file command [2-28](#)
 - boot enable-break command [2-29](#)
 - boot helper command [2-30](#)
 - boot helper-config file command [2-31](#)
 - booting
 - Cisco IOS image [2-34](#)
 - displaying environment variables [2-307](#)
 - interrupting [2-29](#)
 - manually [2-32](#)
 - boot loader
 - accessing [A-1](#)
 - booting
 - Cisco IOS image [A-2](#)
 - helper image [2-30](#)
 - directories
 - creating [A-16](#)
 - displaying a list of [A-7](#)
 - removing [A-20](#)
 - displaying
 - available commands [A-12](#)
 - memory heap utilization [A-14](#)
 - version [A-27](#)
 - environment variables
 - described [A-21](#)
 - displaying settings [A-21](#)
 - location of [A-22](#)
 - setting [A-21](#)
 - unsetting [A-25](#)
 - files
 - copying [A-5](#)
 - deleting [A-6](#)
 - displaying a list of [A-7](#)
 - displaying the contents of [A-4, A-17, A-24](#)
 - renaming [A-18](#)
 - bootloader (continued)
 - file system
 - formatting [A-10](#)
 - initializing flash [A-9](#)
 - running a consistency check [A-11](#)
 - loading helper images [A-13](#)
 - prompt [A-1](#)
 - resetting the system [A-19](#)
 - boot manual command [2-32](#)
 - boot private-config-file command [2-33](#)
 - boot system command [2-34](#)
 - BPDU filtering, for spanning tree [2-502, 2-535](#)
 - BPDU guard, for spanning tree [2-504, 2-535](#)
 - broadcast storm control [2-552](#)
-
- ## C
- candidate switches
 - See clusters
 - cat (boot loader) command [A-4](#)
 - caution, description [xviii](#)
 - CDP, enabling protocol tunneling for [2-157](#)
 - channel-group command [2-35](#)
 - channel-protocol command [2-39](#)
 - Cisco Network Assistant
 - See Network Assistant [xviii](#)
 - Cisco SoftPhone
 - auto-QoS configuration [2-21](#)
 - trusting packets sent from [2-229](#)
 - class command [2-40](#)
 - class-map command [2-42](#)
 - class maps
 - creating [2-42](#)
 - defining the match criteria [2-191](#)
 - displaying [2-312](#)
 - class of service
 - See CoS

- clear ip arp inspection log command [2-44](#)
 - clear ip arp inspection statistics command [2-45](#)
 - clear ipc command [2-47](#)
 - clear ip dhcp snooping database command [2-46](#)
 - clear l2protocol-tunnel counters command [2-48](#)
 - clear lacp command [2-49](#)
 - clear mac address-table command [2-50](#)
 - clear pagp command [2-52](#)
 - clear spanning-tree counters command [2-53](#)
 - clear spanning-tree detected-protocols command [2-54](#)
 - clear vmps statistics command [2-55](#)
 - clear vtp counters command [2-56](#)
 - cluster commander-address command [2-57](#)
 - cluster discovery hop-count command [2-59](#)
 - cluster enable command [2-60](#)
 - cluster holdtime command [2-62](#)
 - cluster member command [2-63](#)
 - cluster outside-interface command [2-65](#)
 - cluster requirements [xix](#)
 - cluster run command [2-66](#)
 - clusters
 - adding candidates [2-63](#)
 - binding to HSRP group [2-67](#)
 - building manually [2-63](#)
 - communicating with
 - devices outside the cluster [2-65](#)
 - members by using Telnet [2-272](#)
 - debug messages, display [B-4](#)
 - displaying
 - candidate switches [2-315](#)
 - debug messages [B-4](#)
 - member switches [2-317](#)
 - status [2-313](#)
 - hop-count limit for extended discovery [2-59](#)
 - HSRP standby groups [2-67](#)
 - redundancy [2-67](#)
 - SNMP trap [2-491](#)
 - cluster standby-group command [2-67](#)
 - cluster timer command [2-69](#)
 - command modes defined [1-2](#)
 - commands changed in Cisco IOS Release 12.2(18)SE [1-6](#)
 - command switch
 - See clusters
 - configuration, initial
 - See getting started guide and hardware installation guide
 - configuration files
 - password recovery disable considerations [A-1](#)
 - specifying the name [2-28, 2-33](#)
 - configuring multiple interfaces [2-107](#)
 - config-vlan mode
 - commands [2-610](#)
 - description [1-4](#)
 - entering [2-609](#)
 - summary [1-2](#)
 - conventions
 - command [xviii](#)
 - for examples [xviii](#)
 - publication [xviii](#)
 - text [xviii](#)
 - copy (boot loader) command [A-5](#)
 - CoS
 - assigning default value to incoming packets [2-199](#)
 - assigning to Layer 2 protocol packets [2-160](#)
 - overriding the incoming value [2-199](#)
 - CoS-to-DSCP map [2-203](#)
 - CPU ASIC statistics, displaying [2-319](#)
-
- ## D
- debug auto qos command [B-2](#)
 - debug cluster command [B-4](#)
 - debug dot1x command [B-6](#)
 - debug dtp command [B-8](#)
 - debug etherchannel command [B-9](#)
 - debug ilpower command [B-11](#)
 - debug interface command [B-14](#)
 - debug ip dhcp snooping command [B-12](#)
 - debug ip igmp filter command [B-16](#)

- debug ip igmp max-groups command [B-17](#)
- debug ip igmp snooping command [B-18](#)
- debug ip verify source packet command [B-13](#)
- debug lacp command [B-19](#)
- debug mac-notification command [B-20](#)
- debug matm command [B-21](#)
- debug monitor command [B-22](#)
- debug mvrdbg command [B-24](#)
- debug nvram command [B-25](#)
- debug pagp command [B-26](#)
- debug platform acl command [B-27](#)
- debug platform cli-redirect main command [B-28](#)
- debug platform configuration command [B-29](#), [B-37](#)
- debug platform cpu-queues command [B-30](#)
- debug platform device-manager command [B-32](#)
- debug platform dot1x command [B-33](#)
- debug platform etherchannel command [B-34](#)
- debug platform fallback-bridging command [B-35](#)
- debug platform forw-tcam command [B-36](#)
- debug platform ip arp inspection command [B-39](#)
- debug platform ipc command [B-47](#)
- debug platform ip dhcp command [B-40](#)
- debug platform ip igmp snooping command [B-41](#)
- debug platform ip multicast command [B-43](#)
- debug platform ip unicast command [B-45](#)
- debug platform led command [B-48](#)
- debug platform matm command [B-49](#)
- debug platform messaging application command [B-51](#)
- debug platform phy command [B-53](#)
- debug platform pm command [B-55](#)
- debug platform port-asic command [B-57](#)
- debug platform port-security command [B-58](#)
- debug platform qos-acl-tcam command [B-59](#)
- debug platform remote-commands command [B-60](#)
- debug platform resource-manager command [B-61](#)
- debug platform snmp command [B-62](#)
- debug platform span command [B-63](#)
- debug platform stack-manager command [B-64](#)
- debug platform supervisor-asic command [B-65](#)
- debug platform sw-bridge command [B-66](#)
- debug platform tcam command [B-67](#)
- debug platform udd command [B-70](#)
- debug platform vlan command [B-71](#)
- debug pm command [B-72](#)
- debug port-security command [B-74](#)
- debug qos-manager command [B-75](#)
- debug spanning-tree backbonefast command [B-78](#)
- debug spanning-tree bpdu command [B-79](#)
- debug spanning-tree bpdu-opt command [B-80](#)
- debug spanning-tree command [B-76](#)
- debug spanning-tree mstp command [B-81](#)
- debug spanning-tree switch command [B-83](#)
- debug spanning-tree uplinkfast command [B-85](#)
- debug sw-vlan command [B-86](#)
- debug sw-vlan ifs command [B-88](#)
- debug sw-vlan notification command [B-90](#)
- debug sw-vlan vtp command [B-92](#)
- debug udd command [B-94](#)
- debug vqpc command [B-96](#)
- define interface-range command [2-70](#)
- delete (boot loader) command [A-6](#)
- delete command [2-72](#)
- deny (ARP access-list configuration) command [2-73](#)
- deny command [2-75](#)
- detect mechanism, causes [2-98](#)
- device manager requirements [xviii](#)
- DHCP snooping
 - enabling
 - on a VLAN [2-141](#)
 - option 82 [2-136](#)
 - trust on an interface [2-139](#)
 - error recovery timer [2-100](#)
 - rate limiting [2-138](#)

- DHCP snooping binding database
 - binding file, configuring [2-134](#)
 - bindings
 - adding [2-132](#)
 - deleting [2-132](#)
 - clearing database agent statistics [2-46](#)
 - database agent, configuring [2-134](#)
 - displaying
 - binding entries [2-374](#)
 - database agent status [2-376](#)
 - renewing [2-279](#)
- dir (boot loader) command [A-7](#)
- directories, deleting [2-72](#)
- documentation, related [xviii](#)
- document conventions [xviii](#)
- domain name, VTP [2-635, 2-639](#)
- dot1x command [2-78](#)
- dot1x default command [2-80](#)
- dot1x guest-vlan command [2-81](#)
- dot1x host-mode command [2-83](#)
- dot1x initialize command [2-85](#)
- dot1x max-req command [2-86, 2-87](#)
- dot1x multiple-hosts command [2-88](#)
- dot1x port-control command [2-89](#)
- dot1x re-authenticate command [2-91](#)
- dot1x re-authentication command [2-92](#)
- dot1x reauthentication command [2-93](#)
- dot1x timeout command [2-94](#)
- dropping packets, with ACL matches [2-5](#)
- drop threshold, Layer 2 protocol tunneling [2-157](#)
- DSCP-to-CoS map [2-203](#)
- DSCP-to-DSCP-mutation map [2-203](#)
- DTP [2-569](#)
- DTP flap
 - error detection for [2-98](#)
 - error recovery timer [2-100](#)
- DTP negotiation [2-573](#)
- duplex command [2-96](#)
- dynamic-access ports
 - configuring [2-562](#)
 - restrictions [2-563](#)
- dynamic ARP inspection
 - ARP ACLs
 - apply to a VLAN [2-117](#)
 - define [2-19](#)
 - deny packets [2-73](#)
 - display [2-302](#)
 - permit packets [2-247](#)
 - clear
 - log buffer [2-44](#)
 - statistics [2-45](#)
 - display
 - ARP ACLs [2-302](#)
 - configuration and operating state [2-370](#)
 - log buffer [2-370](#)
 - statistics [2-370](#)
 - trust state and rate limit [2-370](#)
 - enable per VLAN [2-127](#)
 - error detection for [2-98](#)
 - error recovery timer [2-100](#)
 - log buffer
 - clear [2-44](#)
 - configure [2-121](#)
 - display [2-370](#)
 - rate-limit incoming ARP packets [2-119](#)
 - statistics
 - clear [2-45](#)
 - display [2-370](#)
 - trusted interface state [2-123](#)
 - type of packet logged [2-129](#)
 - validation checks [2-125](#)
- dynamic auto VLAN membership mode [2-568](#)
- dynamic desirable VLAN membership mode [2-568](#)
- Dynamic Host Configuration Protocol (DHCP)
 - See DHCP snooping
- Dynamic Trunking Protocol
 - See DTP

E

EAP-request/identity frame

- maximum number to send [2-87](#)
- response time before retransmitting [2-94](#)

encapsulation methods [2-587](#)

environment variables, displaying [2-307](#)

errdisable detect cause command [2-98](#)

errdisable recovery command [2-100](#)

error conditions, displaying [2-346](#)

error disable detection [2-98](#)

error-disabled interfaces, displaying [2-357](#)

EtherChannel

- assigning Ethernet interface to channel group [2-35](#)
- creating port-channel logical interface [2-105](#)
- debug EtherChannel/PAgP, display [B-9](#)
- debug platform-specific events, display [B-34](#)
- displaying [2-350](#)
- enabling Layer 2 protocol tunneling for
 - LACP [2-158](#)
 - PAgP [2-158](#)
 - UDLD [2-158](#)
- interface information, displaying [2-357](#)

LACP

- clearing channel-group information [2-49](#)
- debug messages, display [B-19](#)
- displaying [2-395](#)
- modes [2-35](#)
- port priority for hot-standby ports [2-161](#)
- restricting a protocol [2-39](#)
- system priority [2-163](#)

load-distribution methods [2-259](#)

PAgP

- aggregate-port learner [2-243](#)
- clearing channel-group information [2-52](#)
- debug messages, display [B-26](#)
- displaying [2-442](#)
- error detection for [2-98](#)
- error recovery timer [2-100](#)

EtherChannel (continued)

- PAgP (continued)
 - learn method [2-243](#)
 - modes [2-35](#)
 - physical-port learner [2-243](#)
 - priority of interface for transmitted traffic [2-245](#)

Ethernet controller, internal register display [2-321](#)

Ethernet statistics, collecting [2-281](#)

examples, conventions for [xviii](#)

exit command [2-624](#)

extended discovery of candidate switches [2-59](#)

extended-range VLANs

- and allowed VLAN list [2-587](#)
- and pruning-eligible list [2-587](#)
- configuring [2-609](#)

extended system ID for STP [2-510](#)

F

fan information, displaying [2-341](#)

file name, VTP [2-635](#)

files, deleting [2-72](#)

flash_init (boot loader) command [A-9](#)

Flex Links

- configuring [2-564](#)
- displaying [2-357](#)

flowcontrol command [2-103](#)

format (boot loader) command [A-10](#)

forwarding packets, with ACL matches [2-5](#)

forwarding results, display [C-5](#)

frame forwarding information, displaying [C-5](#)

front-end controller

- counter and status information [C-7](#)

fsck (boot loader) command [A-11](#)

G

global configuration mode [1-2, 1-4](#)

H

hardware ACL statistics [2-297](#)
 help (boot loader) command [A-12](#)
 hierarchical policy maps [2-257](#)
 hop-count limit for clusters [2-59](#)
 host connection, port configuration [2-567](#)
 host ports, private VLANs [2-571](#)
 Hot Standby Router Protocol
 See HSRP
 HSRP
 binding HSRP group to cluster [2-67](#)
 standby group [2-67](#)

I

IGMP filters
 applying [2-142](#)
 debug messages, display [B-16](#)
 IGMP groups, setting maximum [2-143](#)
 IGMP maximum groups, debugging [B-17](#)
 IGMP profiles
 creating [2-145](#)
 displaying [2-378](#)
 IGMP snooping
 displaying [2-379, 2-382](#)
 enabling [2-147](#)
 multicast table [1-6, 2-383](#)
 report suppression [2-150](#)
 images
 See software images
 Immediate-Leave feature, MVR [2-240](#)
 Immediate-Leave processing [2-147](#)
 initial configuration
 See getting started guide and hardware installation guide
 interface command [2-110](#)
 interface configuration mode [1-2, 1-4](#)
 interface port-channel command [2-105](#)
 interface range command [2-107](#)
 interface-range macros [2-70](#)
 interfaces
 assigning Ethernet interface to channel group [2-35](#)
 configuring [2-96](#)
 configuring multiple [2-107](#)
 creating port-channel logical [2-105](#)
 debug messages, display [B-14](#)
 disabling [2-489](#)
 displaying the MAC address table [2-411](#)
 restarting [2-489](#)
 interface speed, configuring [2-544](#)
 internal registers, displaying [2-321, 2-331](#)
 Internet Group Management Protocol
 See IGMP
 invalid GBIC
 error detection for [2-98](#)
 error recovery timer [2-100](#)
 ip address command [2-115](#)
 IP addresses, setting [2-115](#)
 IP address matching [2-189](#)
 ip arp inspection filter vlan command [2-117](#)
 ip arp inspection limit command [2-119](#)
 ip arp inspection log-buffer command [2-121](#)
 ip arp inspection trust command [2-123](#)
 ip arp inspection validate command [2-125](#)
 ip arp inspection vlan command [2-127](#)
 ip arp inspection vlan logging command [2-129](#)
 IP DHCP snooping
 See DHCP snooping
 ip dhcp snooping binding command [2-132](#)
 ip dhcp snooping command [2-131](#)
 ip dhcp snooping database command [2-134](#)
 ip dhcp snooping information option command [2-136](#)
 ip dhcp snooping limit rate command [2-138](#)
 ip dhcp snooping trust command [2-139](#)
 ip dhcp snooping verify command [2-140](#)
 ip dhcp snooping vlan command [2-141](#)
 ip igmp filter command [2-142](#)
 ip igmp max-groups command [2-143](#)

ip igmp profile command [2-145](#)
 ip igmp snooping command [2-147](#)
 ip igmp snooping report-suppression command [2-150](#)
 IP multicast addresses [2-237](#)
 IP phones
 auto-QoS configuration [2-21](#)
 trusting packets sent from [2-229](#)
 IP-precedence-to-DSCP map [2-203](#)
 ip source binding command [2-152](#)
 IP source guard
 disabling [2-156](#)
 displaying
 binding entries [2-385](#)
 configuration [2-386](#)
 dynamic binding entries only [2-374](#)
 enabling [2-156](#)
 static IP source bindings [2-152](#)
 ip ssh command [2-154](#)
 ip verify source command [2-156](#)

J

jumbo frames
 See MTU

L

l2protocol-tunnel command [2-157](#)
 l2protocol-tunnel cos command [2-160](#)
 LACP
 See EtherChannel
 lacp port-priority command [2-161](#)
 lacp system-priority command [2-163](#)
 Layer 2 mode, enabling [2-560](#)
 Layer 2 protocol ports, displaying [2-392](#)
 Layer 2 protocol-tunnel
 error detection for [2-98](#)
 error recovery timer [2-100](#)

Layer 2 protocol tunnel counters [2-48](#)
 Layer 2 protocol tunneling error recovery [2-158](#)
 Layer 2 traceroute
 IP addresses [2-600](#)
 MAC addresses [2-597](#)
 Layer 3 mode, enabling [2-560](#)
 line configuration mode [1-3, 1-5](#)
 Link Aggregation Control Protocol
 See EtherChannel
 link flap
 error detection for [2-98](#)
 error recovery timer [2-100](#)
 load_helper (boot loader) command [A-13](#)
 load-distribution methods for EtherChannel [2-259](#)
 logging event power-inline-status command [2-165](#)
 logging file command [2-166](#)
 logical interface [2-105](#)
 loopback error
 detection for [2-98](#)
 recovery timer [2-100](#)
 loop guard, for spanning tree [2-512, 2-516](#)

M

mac access-group command [2-168](#)
 MAC access-groups, displaying [2-399](#)
 MAC access list configuration mode [2-170](#)
 mac access-list extended command [2-170](#)
 MAC access lists [2-75](#)
 MAC addresses
 displaying
 aging time [2-405](#)
 all [2-403](#)
 dynamic [2-409](#)
 notification settings [2-413](#)
 number of addresses in a VLAN [2-407](#)
 per interface [2-411](#)
 per VLAN [2-417](#)

- MAC addresses (continued)
 - displaying (continued)
 - static [2-415](#)
 - static and dynamic entries [2-401](#)
 - dynamic
 - aging time [2-172](#)
 - deleting [2-50](#)
 - displaying [2-409](#)
 - enabling MAC address notification [2-174](#)
 - matching [2-189](#)
 - static
 - adding and removing [2-176](#)
 - displaying [2-415](#)
 - dropping on an interface [2-177](#)
 - tables [2-403](#)
- MAC address notification, debugging [B-20](#)
- mac address-table aging-time [2-168, 2-189](#)
- mac address-table aging-time command [2-172](#)
- mac address-table notification command [2-174](#)
- mac address-table static command [2-176](#)
- mac address-table static drop command [2-177](#)
- macro description command [2-182](#)
- macro global command [2-183](#)
- macro global description command [2-186](#)
- macro name command [2-187](#)
- macros
 - adding a description [2-182](#)
 - adding a global description [2-186](#)
 - applying [2-183](#)
 - creating [2-187](#)
 - displaying [2-444](#)
 - interface range [2-70, 2-107](#)
 - specifying parameter values [2-183](#)
 - tracing [2-183](#)
- manual
 - audience [xvii](#)
 - purpose of [xvii](#)
- maps
 - QoS
 - defining [2-203](#)
 - displaying [2-427](#)
 - VLAN
 - creating [2-621](#)
 - defining [2-189](#)
 - displaying [2-481](#)
- match (access-map configuration) command [2-189](#)
- match (class-map configuration) command [2-191](#)
- maximum transmission unit
 - See MTU
- mdix auto command [2-193](#)
- member switches
 - See clusters
- memory (boot loader) command [A-14](#)
- mkdir (boot loader) command [A-16](#)
- mls qos aggregate-policer command [2-197](#)
- mls qos command [2-195](#)
- mls qos cos command [2-199](#)
- mls qos dscp-mutation command [2-201](#)
- mls qos map command [2-203](#)
- mls qos queue-set output buffers command [2-207](#)
- mls qos queue-set output threshold command [2-209](#)
- mls qos srr-queue input bandwidth command [2-213](#)
- mls qos srr-queue input buffers command [2-215](#)
- mls qos-srr-queue input cos-map command [2-217](#)
- mls qos srr-queue input dscp-map command [2-219](#)
- mls qos srr-queue input priority-queue command [2-221](#)
- mls qos srr-queue input threshold command [2-223](#)
- mls qos-srr-queue output cos-map command [2-225](#)
- mls qos srr-queue output dscp-map command [2-227](#)
- mls qos trust command [2-229](#)
- mls qos vlan-based command [2-231](#)
- mode, MVR [2-237](#)
- Mode button, and password recovery [2-285](#)
- modes, commands [1-2](#)

- monitor session command [2-232](#)
- more (boot loader) command [A-17](#)
- MSTP
 - displaying [2-460](#)
 - interoperability [2-54](#)
 - link type [2-514](#)
- MST region
 - aborting changes [2-520](#)
 - applying changes [2-520](#)
 - configuration name [2-520](#)
 - configuration revision number [2-520](#)
 - current or pending display [2-520](#)
 - displaying [2-460](#)
 - MST configuration mode [2-520](#)
 - VLANs-to-instance mapping [2-520](#)
- path cost [2-522](#)
- protocol mode [2-518](#)
- restart protocol migration process [2-54](#)
- root port
 - loop guard [2-512](#)
 - preventing from becoming designated [2-512](#)
 - restricting which can be root [2-512](#)
 - root guard [2-512](#)
- root switch
 - affects of extended system ID [2-510](#)
 - hello-time [2-525, 2-531](#)
 - interval between BPDU messages [2-526](#)
 - interval between hello BPDU messages [2-525, 2-531](#)
 - max-age [2-526](#)
 - maximum hop count before discarding BPDU [2-527](#)
 - port priority for selection of [2-528](#)
 - primary or secondary [2-531](#)
 - switch priority [2-530](#)
- state changes
 - blocking to forwarding state [2-537](#)
 - enabling BPDU filtering [2-502, 2-535](#)
 - enabling BPDU guard [2-504, 2-535](#)
 - enabling Port Fast [2-535, 2-537](#)
 - forward-delay time [2-524](#)
- MSTP (continued)
 - state changes (continued)
 - length of listening and learning states [2-524](#)
 - rapid transition to forwarding [2-514](#)
 - shutting down Port Fast-enabled ports [2-535](#)
 - state information display [2-459](#)
- MTU
 - configuring size [2-594](#)
 - displaying global setting [2-470](#)
- multicast group address, MVR [2-240](#)
- multicast groups, MVR [2-238](#)
- multicast router learning method [2-147](#)
- multicast router ports, configuring [2-147](#)
- multicast storm control [2-552](#)
- multicast VLAN, MVR [2-237](#)
- multicast VLAN registration
 - See MVR
- multiple hosts on authorized port [2-83](#)
- Multiple Spanning Tree Protocol
 - See MSTP
- MVR
 - and address aliasing [2-238](#)
 - configuring [2-237](#)
 - configuring interfaces [2-240](#)
 - debug messages, display [B-24](#)
 - displaying [2-436](#)
 - displaying interface information [2-438](#)
 - members, displaying [2-440](#)
 - mvr (global configuration) command [2-237](#)
 - mvr (interface configuration) command [2-240](#)
 - mvr vlan group command [2-241](#)

N

- native VLANs [2-587](#)
- native VLAN tagging [2-626](#)
- Network Assistant requirements [xviii](#)

- nonegotiate
 - DTP messaging [2-573](#)
 - speed [2-544](#)
 - non-IP protocols
 - denying [2-75](#)
 - forwarding [2-249](#)
 - non-IP traffic access lists [2-170](#)
 - non-IP traffic forwarding
 - denying [2-75](#)
 - permitting [2-249](#)
 - normal-range VLANs [2-609, 2-615](#)
 - note, description [xviii](#)
 - no vlan command [2-609, 2-619](#)
-
- P**
- PAgP
 - See EtherChannel
 - pagp learn-method command [2-243](#)
 - pagp port-priority command [2-245](#)
 - password, VTP [2-635, 2-639](#)
 - password-recovery mechanism, enabling and disabling [2-285](#)
 - permit (ARP access-list configuration) command [2-247](#)
 - permit command [2-249](#)
 - per-VLAN spanning-tree plus
 - See STP
 - physical-port learner [2-243](#)
 - PIM-DVMRP, as multicast router learning method [2-147](#)
 - PoE
 - configuring the power management mode [2-261](#)
 - displaying controller register values [2-329](#)
 - displaying power management information [2-452](#)
 - logging of status [2-165](#)
 - police aggregate command [2-254](#)
 - police command [2-252](#)
 - policed-DSCP map [2-203](#)
 - policy-map command [2-256](#)
 - policy maps
 - applying to an interface [2-287, 2-292](#)
 - creating [2-256](#)
 - displaying [2-447](#)
 - hierarchical [2-257](#)
 - policers
 - displaying [2-420](#)
 - for a single class [2-252](#)
 - for multiple classes [2-197, 2-254](#)
 - policed-DSCP map [2-203](#)
 - traffic classification
 - defining the class [2-40](#)
 - defining trust states [2-602](#)
 - setting DSCP or IP precedence values [2-290](#)
 - Port Aggregation Protocol
 - See EtherChannel
 - port-based authentication
 - 802.1x AAA accounting methods [2-1](#)
 - AAA method list [2-3](#)
 - debug messages, display [B-6](#)
 - enabling 802.1x
 - globally [2-78](#)
 - per interface [2-89](#)
 - guest VLAN [2-81](#)
 - host modes [2-83](#)
 - initialize an interface [2-85](#)
 - manual control of authorization state [2-89](#)
 - multiple hosts on authorized port [2-83](#)
 - periodic re-authentication
 - enabling [2-93](#)
 - time between attempts [2-94](#)
 - quiet period between failed authentication exchanges [2-94](#)
 - re-authenticating 802.1x-enabled ports [2-91](#)
 - resetting configurable 802.1x parameters [2-80](#)
 - switch-to-authentication server retransmission time [2-94](#)
 - switch-to-client frame-retransmission number [2-86 to 2-87](#)
 - switch-to-client retransmission time [2-94](#)

port-channel load-balance command [2-259](#)

Port Fast, for spanning tree [2-537](#)

port ranges, defining [2-70](#)

ports, debugging [B-72](#)

ports, protected [2-585](#)

port security

- aging [2-579](#)
- debug messages, display [B-74](#)
- enabling [2-575](#)
- violation error recovery [2-100](#)

port trust states for QoS [2-229](#)

port types, MVR [2-240](#)

power information, displaying [2-341](#)

power inline command [2-261](#)

Power over Ethernet

- See PoE

priority-queue command [2-264](#)

priority value, stack member [2-467, 2-555](#)

private-vlan command [2-266](#)

private-vlan mapping command [2-269](#)

private VLANs

- association [2-583](#)
- configuring [2-266](#)
- configuring ports [2-571](#)
- displaying [2-476](#)
- host ports [2-571](#)
- mapping

 - configuring [2-583](#)
 - displaying [2-357](#)

- promiscuous ports [2-571](#)

privileged EXEC mode [1-2, 1-3](#)

promiscuous ports, private VLANs [2-571](#)

protected ports, displaying [2-363](#)

pruning

- VLANs [2-587](#)
- VTP

 - displaying interface information [2-357](#)
 - enabling [2-635, 2-639](#)

pruning-eligible VLAN list [2-589](#)

PVST+

- See STP

Q

QoS

- auto-QoS

 - configuring [2-21](#)
 - debug messages, display [1-6, B-2](#)
 - displaying [2-303](#)

- class maps

 - creating [2-42](#)
 - defining the match criteria [2-191](#)
 - displaying [2-312](#)

- defining the CoS value for an incoming packet [2-199](#)
- displaying configuration information [2-303, 2-419](#)
- DSCP trusted ports

 - applying DSCP-to-DSCP-mutation map to [2-201](#)
 - defining DSCP-to-DSCP-mutation map [2-203](#)

- egress queues

 - allocating buffers [2-207](#)
 - defining the CoS output queue threshold map [2-225](#)
 - defining the DSCP output queue threshold map [2-227](#)
 - displaying buffer allocations [2-423](#)
 - displaying CoS output queue threshold map [2-427](#)
 - displaying DSCP output queue threshold map [2-427](#)
 - displaying queueing strategy [2-423](#)
 - displaying queue-set settings [2-430, 2-432](#)
 - enabling bandwidth shaping and scheduling [2-548](#)
 - enabling bandwidth sharing and scheduling [2-550](#)
 - limiting the maximum output on a port [2-546](#)
 - mapping a port to a queue-set [2-271](#)
 - mapping CoS values to a queue and threshold [2-225](#)
 - mapping DSCP values to a queue and threshold [2-227](#)
 - setting maximum and reserved memory allocations [2-209](#)
 - setting WTD thresholds [2-209](#)

enabling [2-195](#)

QoS (continued)

ingress queues

- allocating buffers [2-215](#)
- assigning SRR scheduling weights [2-213](#)
- defining the CoS input queue threshold map [2-217](#)
- defining the DSCP input queue threshold map [2-219](#)
- displaying buffer allocations [2-423](#)
- displaying CoS input queue threshold map [2-427](#)
- displaying DSCP input queue threshold map [2-427](#)
- displaying queueing strategy [2-423](#)
- displaying settings for [2-421](#)
- enabling the priority queue [2-221](#)
- mapping CoS values to a queue and threshold [2-217](#)
- mapping DSCP values to a queue and threshold [2-219](#)
- setting WTD thresholds [2-223](#)

maps

- defining [2-203](#), [2-217](#), [2-219](#), [2-225](#), [2-227](#)
- displaying [2-427](#)

policy maps

- applying an aggregate policer [2-254](#)
- applying to an interface [2-287](#), [2-292](#)
- creating [2-256](#)
- defining policers [2-197](#), [2-252](#)
- displaying policers [2-420](#)
- displaying policy maps [2-447](#)
- hierarchical [2-257](#)
- policed-DSCP map [2-203](#)
- setting DSCP or IP precedence values [2-290](#)
- traffic classifications [2-40](#)
- trust states [2-602](#)

port trust states [2-229](#)queues, enabling the expedite [2-264](#)

statistics

- in-profile and out-of-profile packets [2-423](#)
- packets enqueued or dropped [2-423](#)
- sent and received CoS values [2-423](#)
- sent and received DSCP values [2-423](#)

trusted boundary for IP phones [2-229](#)VLAN-based [2-231](#)

quality of service

See QoS

querytime, MVR [2-237](#)queue-set command [2-271](#)

R

rapid per-VLAN spanning-tree plus

See STP

rapid PVST+

See STP

rcommand command [2-272](#)re-authenticating 802.1x-enabled ports [2-91](#)

re-authentication

periodic [2-93](#)time between attempts [2-94](#)receiver ports, MVR [2-240](#)receiving flow-control packets [2-103](#)

recovery mechanism

causes [2-100](#)display [2-309](#), [2-344](#), [2-348](#)timer interval [2-101](#)redundancy for cluster switches [2-67](#)reload command [2-274](#)remote command [2-276](#)remote-span command [2-277](#)

Remote Switched Port Analyzer

See RSPAN

rename (boot loader) command [A-18](#)renew ip dhcp snooping database command [2-279](#)

requirements

cluster [xix](#)device manager [xviii](#)Network Assistant [xviii](#)reset (boot loader) command [A-19](#)reset command [2-624](#)resource templates, displaying [2-455](#)rmdir (boot loader) command [A-20](#)rmon collection stats command [2-281](#)

root guard, for spanning tree [2-512](#)

routed ports

IP addresses on [2-116](#)

number supported [2-116](#)

RSPAN

configuring [2-232](#)

displaying [2-433](#)

filter RSPAN traffic [2-232](#)

remote-span command [2-277](#)

sessions

add interfaces to [2-232](#)

displaying [2-433](#)

start new [2-232](#)

S

SDM mismatch mode [2-283, 2-468](#)

sdm prefer command [2-282](#)

secure ports, limitations [2-576](#)

sending flow-control packets [2-103](#)

service password-recovery command [2-285](#)

service-policy command [2-287](#)

session command [2-289](#)

set (boot loader) command [A-21](#)

set command [2-290](#)

setup command [2-292](#)

setup express command [2-295](#)

show access-lists command [2-297](#)

show archive status command [2-300](#)

show arp access-list command [2-302](#)

show auto qos command [2-303](#)

show boot command [2-307](#)

show changes command [2-624](#)

show class-map command [2-312](#)

show cluster candidates command [2-315](#)

show cluster command [2-313](#)

show cluster members command [2-317](#)

show controllers cpu-interface command [2-319](#)

show controllers ethernet-controller command [2-321](#)

show controllers power inline command [2-329](#)

show controllers team command [2-331](#)

show controllers utilization command [2-333](#)

show controller utilization command [2-333](#)

show current command [2-624](#)

show dot1q-tunnel command [2-335](#)

show dot1x command [2-336](#)

show dtp [2-339](#)

show env command [2-341](#)

show errdisable detect command [2-344](#)

show errdisable flap-values command [2-346](#)

show errdisable recovery command [2-348](#)

show etherchannel command [2-350](#)

show flowcontrol command [2-353](#)

show idprom command [2-355](#)

show interfaces command [2-357](#)

show interfaces counters command [2-367](#)

show ip arp inspection command [2-370](#)

show ipc command [2-388](#)

show ip dhcp snooping binding command [2-374](#)

show ip dhcp snooping command [2-373](#)

show ip dhcp snooping database command [2-376](#)

show ip igmp profile command [2-378](#)

show ip igmp snooping command [2-379](#)

show ip igmp snooping groups command [2-383](#)

show ip igmp snooping mrouter command [2-382](#)

show ip source binding command [2-385](#)

show ip verify source command [2-386](#)

show l2protocol-tunnel command [2-392](#)

show lacp command [2-395](#)

show mac access-group command [2-399](#)

show mac address-table address command [2-403](#)

show mac address-table aging time command [2-405](#)

show mac address-table command [2-401](#)

show mac address-table count command [2-407](#)

show mac address-table dynamic command [2-409](#)

show mac address-table interface command [2-411](#)

show mac address-table notification command [2-413](#)

show mac address-table static command [2-415](#)

- show mac address-table vlan command [2-417](#)
- show mls qos aggregate-policer command [2-420](#)
- show mls qos command [2-419](#)
- show mls qos input-queue command [2-421](#)
- show mls qos interface command [2-423](#)
- show mls qos maps command [2-427](#)
- show mls qos queue-set command [2-430](#)
- show mls qos vlan command [2-432](#)
- show monitor command [2-433](#)
- show mvr command [2-436](#)
- show mvr interface command [2-438](#)
- show mvr members command [2-440](#)
- show pagp command [2-442](#)
- show parser macro command [2-444](#)
- show platform acl command [C-2](#)
- show platform configuration command [C-3](#)
- show platform etherchannel command [C-4](#)
- show platform forward command [C-5](#)
- show platform frontend-controller command [C-7](#)
- show platform igmp snooping command [C-8](#)
- show platform ipc trace command [C-13](#)
- show platform ip multicast command [C-10](#)
- show platform ip unicast command [C-11](#)
- show platform layer4op command [C-14](#)
- show platform mac-address-table command [C-15](#)
- show platform messaging command [C-16](#)
- show platform monitor command [C-17](#)
- show platform mvr table command [C-18](#)
- show platform pm command [C-19](#)
- show platform port-asic command [C-20](#)
- show platform port-security command [C-25](#)
- show platform qos command [C-26](#)
- show platform resource-manager command [C-27](#)
- show platform snmp counters command [C-29](#)
- show platform spanning-tree command [C-30](#)
- show platform stack-manager command [C-32](#)
- show platform stp-instance command [C-31](#)
- show platform tb command [C-34](#)
- show platform team command [C-36](#)
- show platform vlan command [C-39](#)
- show policy-map command [2-447](#)
- show port security command [2-449](#)
- show power inline command [2-452](#)
- show proposed command [2-624](#)
- show sdm prefer command [2-455](#)
- show setup express command [2-458](#)
- show spanning-tree command [2-459](#)
- show storm-control command [2-465](#)
- show switch command [2-467](#)
- show system mtu command [2-470](#)
- show trust command [2-602](#)
- show udd command [2-471](#)
- show version command [2-474](#)
- show vlan access-map command [2-481](#)
- show vlan command [2-476](#)
- show vlan command, fields [2-478](#)
- show vlan filter command [2-482](#)
- show vmps command [2-483](#)
- show vtp command [2-485](#)
- shutdown command [2-489](#)
- shutdown threshold, Layer 2 protocol tunneling [2-157](#)
- shutdown vlan command [2-490](#)
- Smartports macros
 - See macros
- SNMP host, specifying [2-495](#)
- SNMP informs, enabling the sending of [2-491](#)
- snmp-server enable traps command [2-491](#)
- snmp-server host command [2-495](#)
- snmp trap mac-notification command [2-499](#)
- SNMP traps
 - enabling MAC address notification trap [2-499](#)
 - enabling the MAC address notification feature [2-174](#)
 - enabling the sending of [2-491](#)
- SoftPhone
 - See Cisco SoftPhone

- software images
 - copying [2-7](#)
 - deleting [2-72](#)
 - downloading [2-10](#)
 - upgrading [2-7, 2-10](#)
 - uploading [2-17](#)
- software version, displaying [2-474](#)
- source ports, MVR [2-240](#)
- SPAN
 - configuring [2-232](#)
 - debug messages, display [B-22](#)
 - displaying [2-433](#)
 - filter SPAN traffic [2-232](#)
 - sessions
 - add interfaces to [2-232](#)
 - displaying [2-433](#)
 - start new [2-232](#)
- spanning-tree backbonefast command [2-501](#)
- spanning-tree bpduguard command [2-502](#)
- spanning-tree bpduguard command [2-504](#)
- spanning-tree cost command [2-506](#)
- spanning-tree etherchannel command [2-508](#)
- spanning-tree extend system-id command [2-510](#)
- spanning-tree guard command [2-512](#)
- spanning-tree link-type command [2-514](#)
- spanning-tree loopguard default command [2-516](#)
- spanning-tree mode command [2-518](#)
- spanning-tree mst configuration command [2-520](#)
- spanning-tree mst cost command [2-522](#)
- spanning-tree mst forward-time command [2-524](#)
- spanning-tree mst hello-time command [2-525](#)
- spanning-tree mst max-age command [2-526](#)
- spanning-tree mst max-hops command [2-527](#)
- spanning-tree mst port-priority command [2-528](#)
- spanning-tree mst priority command [2-530](#)
- spanning-tree mst root command [2-531](#)
- spanning-tree portfast (global configuration)
 - command [2-535](#)
- spanning-tree portfast (interface configuration)
 - command [2-537](#)
- spanning-tree port-priority command [2-533](#)
- Spanning Tree Protocol
 - See STP
- spanning-tree uplinkfast command [2-539](#)
- spanning-tree vlan command [2-541](#)
- speed command [2-544](#)
- srr-queue bandwidth limit command [2-546](#)
- srr-queue bandwidth shape command [2-548](#)
- srr-queue bandwidth share command [2-550](#)
- SSH, configuring version [2-154](#)
- stack member
 - access [2-289](#)
 - number [2-467, 2-558](#)
 - priority value [2-555](#)
 - provisioning [2-556](#)
 - reloading [2-274](#)
- stacks, switch
 - provisioning a new member [2-556](#)
 - reloading [2-274](#)
 - stack member access [2-289](#)
 - stack member number [2-467, 2-558](#)
 - stack member priority value [2-467, 2-555](#)
- static-access ports, configuring [2-562](#)
- statistics, Ethernet group [2-281](#)
- sticky learning, enabling [2-575](#)
- storm-control command [2-552](#)
- STP
 - BackboneFast [2-501](#)
 - counters, clearing [2-53](#)
 - debug messages, display
 - BackboneFast events [B-78](#)
 - MSTP [B-81](#)
 - optimized BPDUs handling [B-80](#)
 - spanning-tree activity [B-76](#)
 - switch shim [B-83](#)
 - transmitted and received BPDUs [B-79](#)
 - UplinkFast [B-85](#)

STP (continued)

- detection of indirect link failures [2-501](#)
- enabling protocol tunneling for [2-157](#)
- EtherChannel misconfiguration [2-508](#)
- extended system ID [2-510](#)
- path cost [2-506](#)
- protocol modes [2-518](#)
- root port
 - accelerating choice of new [2-539](#)
 - loop guard [2-512](#)
 - preventing from becoming designated [2-512](#)
 - restricting which can be root [2-512](#)
 - root guard [2-512](#)
 - UplinkFast [2-539](#)
- root switch
 - affects of extended system ID [2-510, 2-542](#)
 - hello-time [2-541](#)
 - interval between BPDU messages [2-541](#)
 - interval between hello BPDU messages [2-541](#)
 - max-age [2-541](#)
 - port priority for selection of [2-533](#)
 - primary or secondary [2-541](#)
 - switch priority [2-541](#)
- state changes
 - blocking to forwarding state [2-537](#)
 - enabling BPDU filtering [2-502, 2-535](#)
 - enabling BPDU guard [2-504, 2-535](#)
 - enabling Port Fast [2-535, 2-537](#)
 - enabling timer to recover from error state [2-100](#)
 - forward-delay time [2-541](#)
 - length of listening and learning states [2-541](#)
 - shutting down Port Fast-enabled ports [2-535](#)
- state information display [2-459](#)
- VLAN options [2-530, 2-541](#)
- SVIs, creating [2-110](#)
- Switched Port Analyzer
 - See SPAN

- switching characteristics
 - modifying [2-560](#)
 - returning to interfaces [2-560](#)
- switchport access command [2-562](#)
- switchport backup interface command [2-564](#)
- switchport block command [2-566](#)
- switchport command [2-560](#)
- switchport host command [2-567](#)
- switchport mode command [2-568](#)
- switchport mode private-vlan command [2-571](#)
- switchport nonegotiate command [2-573](#)
- switchport port-security aging command [2-579](#)
- switchport port-security command [2-575](#)
- switchport priority extend command [2-581](#)
- switchport private-vlan command [2-583](#)
- switchport protected command [2-585](#)
- switchports, displaying [2-357](#)
- switchport trunk command [2-587](#)
- switchport voice vlan command [2-590](#)
- switch priority command [2-555](#)
- switch provision command [2-556](#)
- switch renumber command [2-558](#)
- system env temperature threshold yellow command [2-592](#)
- system message logging [2-165](#)
- system message logging, save message to flash [2-166](#)
- system mtu command [2-594](#)
- system resource templates [2-282](#)

T

- tar files, creating, listing, and extracting [2-14](#)
- TDR, running [2-596](#)
- Telnet, using to communicate to cluster switches [2-272](#)
- temperature information, displaying [2-341](#)
- templates, system resources [2-282](#)
- test cable-diagnostics tdr command [2-596](#)
- traceroute mac command [2-597](#)

tracert mac ip command [2-600](#)
trunking, VLAN mode [2-568](#)
trunk mode [2-568](#)
trunk ports [2-568](#)
trunks, to non-DTP device [2-569](#)
trusted boundary for QoS [2-229](#)
trusted port states for QoS [2-229](#)
tunnel ports, Layer 2 protocol, displaying [2-392](#)
type (boot loader) command [A-24](#)

U

UDLD

aggressive mode [2-604, 2-606](#)
debug messages, display [B-94](#)
enable globally [2-604](#)
enable per interface [2-606](#)
error recovery timer [2-100](#)
message timer [2-604](#)
normal mode [2-604, 2-606](#)
reset a shutdown interface [2-608](#)
status [2-471](#)
udld command [2-604](#)
udld port command [2-606](#)
udld reset command [2-608](#)
unicast storm control [2-552](#)
UniDirectional Link Detection
 See UDLD
unknown multicast traffic, preventing [2-566](#)
unknown unicast traffic, preventing [2-566](#)
unset (boot loader) command [A-25](#)
upgrading
 software images [2-7, 2-10](#)
 monitoring status of [2-300](#)
upgrading information
 See release notes
UplinkFast, for STP [2-539](#)
user EXEC mode [1-2, 1-3](#)

V

version (boot loader) command [A-27](#)
version mismatch mode [2-468](#)
vlan (global configuration) command [2-609](#)
vlan (VLAN configuration) command [2-615](#)
vlan access-map command [2-621](#)
VLAN access map configuration mode [2-621](#)
VLAN access maps
 actions [2-5](#)
 displaying [2-481](#)
VLAN-based QoS [2-231](#)
VLAN configuration
 rules [2-612, 2-617](#)
 saving [2-609, 2-619](#)
VLAN configuration mode
 commands
 VLAN [2-615](#)
 VTP [2-639](#)
 description [1-5](#)
 entering [2-623](#)
 summary [1-3](#)
vlan database command [2-623](#)
vlan dot1q tag native command [2-626](#)
vlan filter command [2-628](#)
VLAN filters, displaying [2-482](#)
VLAN ID range [2-609, 2-615](#)
VLAN maps
 applying [2-628](#)
 creating [2-621](#)
 defining [2-189](#)
 displaying [2-481](#)
VLAN Query Protocol
 See VQP
VLANs
 adding [2-609](#)
 configuring [2-609, 2-615](#)

VLANs (continued)

- debug messages, display
 - ISL [B-90](#)
 - VLAN IOS file system error tests [B-88](#)
 - VLAN manager activity [B-86](#)
 - VTP [B-92](#)
 - displaying configurations [2-476](#)
 - extended-range [2-609](#)
 - MAC addresses
 - displaying [2-417](#)
 - number of [2-407](#)
 - media types [2-612, 2-617](#)
 - normal-range [2-609, 2-615](#)
 - private [2-571](#)
 - configuring [2-266](#)
 - displaying [2-476](#)
 - See also private VLANs
 - restarting [2-490](#)
 - saving the configuration [2-609](#)
 - shutting down [2-490](#)
 - SNMP traps for VTP [2-493, 2-496](#)
 - suspending [2-490](#)
 - variables [2-615](#)
- VLAN Trunking Protocol
- See VTP
- VM mode [2-468](#)
- VMPS
- configuring servers [2-633](#)
 - displaying [2-483](#)
 - error recovery timer [2-101](#)
 - reconfirming dynamic VLAN assignments [2-630](#)
- vmpls reconfirm (global configuration) command [2-631](#)
- vmpls reconfirm (privileged EXEC) command [2-630](#)
- vmpls retry command [2-632](#)
- vmpls server command [2-633](#)
- voice VLAN
- configuring [2-590](#)
 - setting port priority [2-581](#)

VQP

- and dynamic-access ports [2-563](#)
- clearing client statistics [2-55](#)
- displaying information [2-483](#)
- per-server retry count [2-632](#)
- reconfirmation interval [2-631](#)
- reconfirming dynamic VLAN assignments [2-630](#)

VTP

- changing characteristics [2-635](#)
 - clearing pruning counters [2-56](#)
 - configuring
 - domain name [2-635, 2-639](#)
 - file name [2-635](#)
 - mode [2-635, 2-639](#)
 - password [2-635, 2-639](#)
 - counters display fields [2-486](#)
 - displaying information [2-485](#)
 - enabling
 - pruning [2-635, 2-639](#)
 - tunneling for [2-157](#)
 - Version 2 [2-635, 2-639](#)
 - mode [2-635, 2-639](#)
 - pruning [2-635, 2-639](#)
 - saving the configuration [2-609, 2-619](#)
 - statistics [2-485](#)
 - status [2-485](#)
 - status display fields [2-487](#)
- vtp (global configuration) command [2-635](#)
- vtp (VLAN configuration) command [2-639](#)

X

- XENPAK module serial EEPROM information [2-325, 2-355](#)

