



Configuring Retransmission Interval and Retry Count

- [Finding Feature Information, on page 1](#)
- [Prerequisites for Configuring the Access Point Retransmission Interval and Retry Count, on page 1](#)
- [Information About Retransmission Interval and Retry Count, on page 2](#)
- [How to Configure Access Point Retransmission Interval and Retry Count, on page 2](#)
- [Viewing CAPWAP Maximum Transmission Unit Information \(CLI\), on page 3](#)
- [Configuration Examples for Configuring Access Point Retransmission Interval and Retry Count, on page 4](#)

Finding Feature Information

Your software release may not support all of the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

Prerequisites for Configuring the Access Point Retransmission Interval and Retry Count

- You can configure the retransmission intervals and retry count both at a global and a specific access point level. A global configuration applies these configuration parameters to all the access points. Alternatively, when you configure the retransmission level and retry count at a specific access point level, the values are applied to that particular access point. The access point specific configuration has a higher precedence than the global configuration.

Information About Retransmission Interval and Retry Count

The device and the access points exchange packets using the Control and Provisioning of Wireless Access Points (CAPWAP) reliable transport protocol. For each request, a response is defined. This response is used to acknowledge the receipt of the request message. Response messages are not explicitly acknowledged; therefore, if a response message is not received, the original request message is retransmitted after the retransmit interval. If the request is not acknowledged after a maximum number of retransmissions, the session is closed and the access points reassociate with another device.

How to Configure Access Point Retransmission Interval and Retry Count

Configuring the Access Point Retransmission Interval and Retry Count (CLI)

SUMMARY STEPS

1. `enable`
2. `configure terminal`
3. `ap capwap retransmit interval interval_time`
4. `ap capwap retransmit count count_value`
5. `end`
6. `ap name Cisco_AP capwap retransmit interval interval_time`
7. `ap name Cisco_AP capwap retransmit count count_value`
8. `show ap capwap retransmit`

DETAILED STEPS

	Command or Action	Purpose
Step 1	<code>enable</code> Example: Device# <code>enable</code>	Enters privileged EXEC mode.
Step 2	<code>configure terminal</code> Example: Device# <code>configure terminal</code>	Enters global configuration mode.
Step 3	<code>ap capwap retransmit interval <i>interval_time</i></code> Example: Device(config)# <code>ap capwap retransmit interval 2</code>	Configures the control packet retransmit interval for all access points globally. Note The range for the interval parameter is from 2 to 5.

	Command or Action	Purpose
Step 4	ap capwap retransmit count <i>count_value</i> Example: Device(config)# ap capwap retransmit count 3	Configures the control packet retry count for all access points globally. Note The range for the count is from 3 to 8.
Step 5	end Example: Device(config)# end	Returns to privileged EXEC mode. Alternatively, you can also press Ctrl-Z to exit global configuration mode.
Step 6	ap name <i>Cisco_AP</i> capwap retransmit interval <i>interval_time</i> Example: Device# ap name AP02 capwap retransmit interval 2	Configures the control packet retransmit interval for the individual access point that you specify. Note The range for the interval is from 2 to 5. Note You must be in privileged EXEC mode to use the ap name commands.
Step 7	ap name <i>Cisco_AP</i> capwap retransmit count <i>count_value</i> Example: Device# ap name AP02 capwap retransmit count 3	Configures the control packet retry count for the individual access point that you specify. Note The range for the retry count is from 3 to 8.
Step 8	show ap capwap retransmit Example: Device# show ap capwap retransmit	Displays the CAPWAP retransmit details.

Viewing CAPWAP Maximum Transmission Unit Information (CLI)

SUMMARY STEPS

1. enable
2. show ap name *Cisco_AP* config general

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Device# enable	Enters privileged EXEC mode.

	Command or Action	Purpose
Step 2	show ap name <i>Cisco_AP</i> config general Example: Device# show ap name Maria-1250 config general include MTU	Displays the maximum transmission unit (MTU) for the CAPWAP path on the device. The MTU specifies the maximum size of any packet (in bytes) in a transmission.

Related Topics

[Viewing the CAPWAP Retransmission Details: Example](#), on page 4

[Viewing Maximum Transmission Unit Information: Example](#), on page 4

Configuration Examples for Configuring Access Point Retransmission Interval and Retry Count

Viewing the CAPWAP Retransmission Details: Example

Enter the following command:

```
Device# show ap capwap retransmit
Global control packet retransmit interval : 3
Global control packet retransmit count : 5
```

AP Name	Retransmit Interval	Retransmit Count
-----	-----	-----
3602a	5	3

Viewing Maximum Transmission Unit Information: Example

This example shows how to view the maximum transmission unit (MTU) for the CAPWAP path on the device. The MTU specifies the maximum size of any packet (in bytes) in a transmission:

```
Device# show ap name cisco-ap-name config general | include MTU
CAPWAP Path MTU..... 1500
```