



---

## Symbols

- \$ matches the end of a string [1-7](#)
- () in commands [1-10](#)
- \* matches 0 or more sequences of a pattern [1-7](#)
- + matches 1 or more sequences of a pattern [1-7](#)
- . matches any single character [1-7](#)
- ? command [1-1](#)
- ? matches 0 or 1 occurrence of a pattern [1-7](#)
- ^ matches the beginning of a string [1-7](#)
- \_ matches a comma (,), left brace ({}), left parenthesis [1-7](#)
- “ [1-10](#)

---

## Numerics

- 10-Gigabit Ethernet uplink
  - selecting [2-105](#)
  - showing the mode [2-291](#)
- 802.1Q trunk ports and native VLANs [2-533](#)
- 802.1Q tunnel ports
  - configuring [2-492](#)
- 802.1S Multiple Spanning Tree
  - see MST
- 802.1X Port Based Authentication
  - allowing multiple hosts on a port [2-86](#)
  - debugging 802.1X Port Based Authentication [2-49](#)
  - displaying port based authentication [2-277](#)
  - enabling accounting for authentication sessions [2-3](#)
  - enabling authentication on the system [2-91](#)
  - enabling guest VLAN [2-82](#)
  - enabling manual control of auth state [2-87](#)
  - enabling periodic re-authentication of the client [2-90](#)
  - initializing re-authentication of dot1x ports [2-89](#)

- initializing state machines [2-83](#)
- receive session termination message upon reboot [2-4](#)
- setting maximum number for EAP requests [2-85](#)

---

## A

- abbreviating commands
  - context-sensitive help [1-1](#)
- Access Gateway Module
  - connecting to a module [2-11](#)
  - connecting to a remote module [2-243](#)
  - connecting to a specific remote module [2-249](#)
- access-group
  - displaying mac interface [2-364](#)
  - show mode interface [2-253](#)
- access groups
  - IP [2-5](#)
- access lists
  - clearing an access template [2-26](#)
  - defining ARP [2-10](#)
  - displaying ARP information [2-256](#)
  - See also ACLs, MAC ACLs, and VACLs
- access maps
  - applying with VLAN filter [2-534](#)
- ACLs
  - access-group mode [2-5](#)
  - determining ACL hardware programming [2-6](#)
  - displaying mac access-group interface [2-364](#)
  - using ACL naming conventions for MAC ACLs [2-170](#)
- action clause
  - specifying drop or forward action in a VACL [2-8](#)
- adjacency
  - debugging the adjacency table [2-43](#)

- disabling the debug facility [2-43](#)
- displaying information about the adjacency table [2-254](#)
- displaying IPC table entries [2-43](#)
- aggregate policer
  - displaying information [2-397](#)
- aging time
  - displaying MAC address aging time [2-367](#)
  - MAC address table [2-173](#)
- alarms
  - displaying operational status [2-280](#)
- alternation
  - description [1-9](#)
- anchoring
  - description [1-10](#)
- ARP
  - access list, displaying detailed information [2-256](#)
  - defining access-lists [2-10](#)
- ARP inspection
  - enforce certain types of checking [2-122](#)
- ARP packet
  - deny based on DHCP bindings [2-79](#)
  - permit based on DHCP bindings [2-203](#)
- authentication
  - setting username [2-524](#)
  - using an MD5-type encryption method [2-524](#)
  - verifying MD5 signature [2-525](#)
  - verifying the checksum for Flash memory [2-525](#)
- authorization state
  - enabling manual control [2-87](#)
- authorization state of a controlled port [2-87](#)
- automatic installation
  - displaying status [2-257](#)
- auto-negotiate interface speed
  - example [2-483](#)
- auto-QoS
  - configuring for VoIP [2-12](#)
  - displaying configuration [2-258](#)

---

**B**

- baby giants
  - displaying the system MTU setting [2-423](#)
  - setting the maximum Layer 2 payload size [2-509](#)
- BackboneFast
  - displaying debugging messages [2-68](#)
  - displaying spanning tree status [2-413](#)
  - enabling debugging [2-68](#)
- bindings
  - store for DHCP snooping [2-130](#)
- BOOT environment variable
  - displaying information [2-262](#)
- bootflash
  - displaying information [2-260](#)
- BPDUs
  - debugging spanning tree activities [2-67](#)
- bridge protocol data units
  - See BPDUs
- broadcast suppression level
  - configuring [2-484, 2-486](#)
  - enabling [2-484, 2-486](#)

---

**C**

- Catalyst 4507R [2-213](#)
  - power redundancy mode [2-215](#)
- CDP
  - configuring tunneling encapsulation rate [2-166](#)
  - displaying
    - neighbor information [2-263](#)
  - enabling protocol tunneling for [2-162](#)
  - set drop threshold for [2-164](#)
- CEF
  - displaying next-hop information [2-324](#)
  - displaying VLAN configuration information [2-324](#)
- cisco-desktop
  - macro apply [2-179](#)

- Cisco Express Forwarding
    - See CEF
  - cisco-phone
    - macro apply [2-181](#)
  - cisco-router
    - macro apply [2-183](#)
  - cisco-switch
    - macro apply [2-185](#)
  - clear commands
    - clearing Gigabit Ethernet interfaces [2-24](#)
    - clearing IGMP group cache entries [2-31](#)
    - clearing interface counters [2-21](#)
    - clearing IP access lists [2-26, 2-27](#)
    - clearing IP ARP inspection statistics VLAN [2-28](#)
    - clearing IP DHCP snooping database [2-29](#)
    - clearing IP DHCP snooping database statistics [2-30](#)
    - clearing MFIB counters and routes [2-34](#)
    - clearing MFIB fastdrop entries [2-35](#)
    - clearing PAgP channel information [2-38](#)
    - clearing QoS aggregate counters [2-40](#)
    - clearing VLAN interfaces [2-25](#)
  - CLI string search
    - anchoring [1-10](#)
    - expressions [1-7](#)
    - filtering [1-6](#)
    - multiple-character patterns [1-8](#)
    - multipliers [1-9](#)
    - parentheses for recall [1-10](#)
    - searching outputs [1-6](#)
    - single-character patterns [1-7](#)
    - using [1-6](#)
  - command modes
    - accessing privileged EXEC mode [1-4](#)
    - exiting [1-4](#)
    - understanding user EXEC and configuration modes [1-4](#)
  - condition interface
    - debugging interface-related activities [2-45](#)
  - condition vlan
    - debugging VLAN output [2-48](#)
  - configuration, saving [1-11](#)
  - configuring
    - root as secondary [2-467](#)
  - configuring a SPAN session to monitor
    - limit SPAN source traffic [2-195](#)
  - configuring forward delay [2-463](#)
  - configuring root as primary [2-467](#)
  - CoS
    - assigning to Layer 2 protocol packets [2-163](#)
  - CoS QoS default
    - defining value on an interface [2-228](#)
  - Cost of Service
    - See QoS CoS
  - counters
    - clearing interface counters [2-21](#)
- 
- ## D
- DAI
    - clear statistics [2-28](#)
  - DBL
    - displaying qos dbl [2-398](#)
    - enabling DBL globally on the switch [2-229](#)
  - debug commands
    - debugging backup events [2-44](#)
    - debugging DHCP snooping events [2-54](#)
    - debugging DHCP snooping messages [2-55](#)
    - debugging EtherChannel/PAgP/shim [2-50](#)
    - debugging IPC activity [2-53](#)
    - debugging IP DHCP snooping security messages [2-56](#)
    - debugging NVRAM activities [2-59](#)
    - debugging PAgP activities [2-60](#)
    - debugging port manager activities [2-63](#)
    - debugging software MAC filter updates [2-66](#)
    - debugging spanning tree activities [2-67](#)
    - debugging spanning tree backbonefast [2-68](#)
    - debugging spanning tree UplinkFast [2-71](#)
    - debugging supervisor redundancy [2-65](#)
    - debugging VLAN manager activities [2-72](#)

- displaying monitor activity [2-58](#)
- displaying the adjacency table [2-43](#)
- enabling debug dot1x [2-49](#)
- enabling debugging messages for ISL VLAN IDs [2-74](#)
- enabling debugging messages for VTP [2-75](#)
- enabling debugging of UDLD activity [2-76](#)
- enabling switch shim debugging [2-69](#)
- enabling VLAN manager file system error tests [2-73](#)
- limiting debugging output for VLANs [2-48](#)
- limiting interface debugging output [2-45](#)
- limiting output for debugging standby state changes [2-46](#)
- shortcut to the debug condition interface [2-52](#)
- debugging
  - activity monitoring [2-58](#)
  - DHCP snooping events [2-54](#)
  - DHCP snooping packets [2-55](#)
  - IPC activities [2-53](#)
  - IP DHCP snooping security packets [2-56](#)
  - NVRAM activities [2-59](#)
  - PAgP activities [2-60](#)
  - PAgP shim [2-50](#)
  - PM activities [2-63](#)
  - SMF address insertions and deletions [2-66](#)
  - spanning tree BackboneFast events [2-68](#)
  - spanning tree switch shim [2-69](#)
  - spanning tree UplinkFast events [2-71](#)
  - VLAN manager activities [2-72](#)
  - VLAN manager IOS file system error tests [2-73](#)
  - VTP protocol debug messages [2-75](#)
- debug spanning tree switch [2-69](#)
- debug sw-vlan vtp [2-75](#)
- default CoS value [2-228](#)
- default form of a command, using [1-6](#)
- defining egress DSCP-to-CoS mapping [2-233](#)
- DHCP
  - clearing database statistics [2-30](#)
- DHCP bindings
  - configuring bindings [2-129](#)
- deny ARP packet based on matches [2-79](#)
- permit ARP packet based on matches [2-203](#)
- DHCP snooping
  - clearing database [2-29](#)
  - displaying [2-325](#)
  - displaying binding table [2-326](#)
  - displaying status of DHCP database [2-329](#)
  - displaying status of error detection [2-283](#)
  - enabling DHCP globally [2-128](#)
  - enabling IP source guard [2-160](#)
  - enabling on a VLAN [2-135](#)
  - enabling option 82 [2-132](#)
  - enabling rate limiting on an interface [2-133](#)
  - enabling trust on an interface [2-134](#)
  - establishing binding configuration [2-129](#)
  - renew binding database [2-245](#)
  - store generated bindings [2-130](#)
- diagnostic test
  - displaying attributes [2-267](#)
  - display module-based results [2-269](#)
- displaying error disable recovery [2-284](#)
- displaying inline power status [2-392](#)
- displaying monitoring activity [2-58](#)
- displaying SEEPROM information
  - GBIC [2-292](#)
- displaying SPAN session information [2-422, 2-485](#)
- document conventions [xvi](#)
- document organization [xv](#)
- DOS attack
  - protecting system's resources [2-117](#)
- drop threshold, Layer 2 protocol tunneling [2-164](#)
- DSCP rewrite for IP packets
  - enable [2-236](#)
- dual-capable port
  - selecting a connector [2-192](#)
- duplex mode
  - configuring autonegotiation on an interface [2-94](#)
  - configuring full duplex on an interface [2-94](#)
  - configuring half duplex on an interface [2-94](#)

dynamic ARP inspection  
   preventing [2-117](#)  
 Dynamic Buffer Limiting  
   See DBL  
 Dynamic Host Configuration Protocol  
   See DHCP

---

## E

EAP  
   restarting authentication process [2-85](#)  
 enabling  
   debugging for UDLD [2-76](#)  
   voice VLANs [2-487](#)  
 environmental  
   alarms [2-280](#)  
   displaying information [2-280](#)  
   status [2-280](#)  
   temperature [2-280](#)  
 error disable detection  
   enabling error disable detection [2-96](#)  
 error-disabled state  
   displaying [2-310](#)  
 error disable recovery  
   configuring recovery mechanism variables [2-98](#)  
   displaying recovery timer information [2-284](#)  
   enabling ARP inspection timeout [2-98](#)  
   specifying recovery cause [2-98](#)  
 EtherChannel  
   assigning interfaces to EtherChannel groups [2-16](#)  
   debugging EtherChannel [2-50](#)  
   debugging PAgP shim [2-50](#)  
   debugging spanning tree activities [2-67](#)  
   displaying information for a channel [2-285](#)  
   removing interfaces from EtherChannel groups [2-16](#)  
 EtherChannel guard  
   detecting STP misconfiguration [2-454](#)  
 Explicit Host Tracking  
   clearing the database [2-33](#)

  enabling per-VLAN [2-147](#)  
 expressions  
   matching multiple expression occurrences [1-9](#)  
   multiple-character patterns [1-8](#)  
   multiplying pattern occurrence [1-10](#)  
   single-character patterns [1-7](#)  
 Extensible Authentication Protocol  
   See EAP

---

## F

field replaceable unit (FRU)  
   displaying status information [2-280](#)  
 Flash memory file system  
   displaying file system information [2-260](#)  
   verifying checksum [2-525](#)  
 flow control  
   configuring a gigabit interface for pause frames [2-101](#)  
   displaying per-interface statistics for flow control [2-289](#)

---

## G

GBIC  
   displaying SEEPROM information [2-292](#)  
 Gigabit Ethernet interface  
   clearing the hardware logic [2-24](#)  
 Gigabit Ethernet uplink  
   selecting [2-105](#)  
   showing the mode [2-291](#)  
 global configuration mode  
   using [1-5](#)

---

## H

hardware module  
   resetting a module by toggling the power [2-104](#)  
 hardware uplink  
   selecting the mode [2-105](#)

- showing the mode [2-291](#)
- helper addresses, IP [2-343](#)
- hot standby protocol
  - debugging [2-46](#)
  - disabling debugging [2-46](#)
  - limiting output [2-46](#)

## IDPROMs

- displaying SEEPROM information
  - chassis [2-292](#)
  - clock module [2-292](#)
  - fan trays [2-292](#)
  - module [2-292](#)
  - mux buffer [2-292](#)
  - power supplies [2-292](#)
  - supervisor engine [2-292](#)

## ifIndex persistence

- clearing SNMP ifIndex commands [2-443](#)
- compress SNMP ifIndex table format [2-448](#)
- disabling globally [2-447](#)
- disabling on an interface [2-444](#)
- enabling globally [2-447](#)
- enabling on an interface [2-444](#)

## IGMP

- applying filters for host joining on Layer 2 interfaces [2-137](#)
- clearing IGMP group cache entries [2-31](#)
- configuring frequency for IGMP host-query messages [2-140](#)
- creating an IGMP profile [2-139](#)
- displaying IGMP interface configuration information [2-331](#)
- displaying profiles [2-333](#)
- setting maximum group numbers [2-138](#)

## IGMP profiles

- displaying [2-333](#)

## IGMP snooping

- clearing the EHT database [2-33](#)
- configuring a Layer 2 interface as a group member [2-151](#)
- configuring a Layer 2 interface as a multicast router [2-149](#)
- configuring a static VLAN interface [2-151](#)
- displaying multicast information [2-340](#)
- displaying VLAN information [2-334, 2-338, 2-341](#)
- enabling [2-142](#)
- enabling immediate-leave processing [2-148](#)
- enabling on a VLAN [2-146](#)
- enabling per-VLAN Explicit Host Tracking [2-147](#)

## informs

- enabling [2-445](#)

## inline power

- displaying inline power status [2-392](#)

## inspection log

- clearing log buffer [2-27](#)

## interface

- displaying suppressed multicast bytes [2-304](#)

## interface capabilities

- displaying [2-301](#)

## interface configuration mode

- summary [1-5](#)

## interface link

- display cable disconnect time [2-307](#)

## interfaces

- configuring dot1q tunnel ports [2-492](#)
- creating an interface-range macro [2-78](#)
- debugging output of interface related activities [2-45](#)
- displaying description [2-306](#)
- displaying error-disabled state [2-310](#)
- displaying information when tunneling is enabled [2-358](#)
- displaying status [2-306](#)
- displaying traffic for a specific interface [2-298](#)
- entering interface configuration mode [2-109](#)
- executing a command on multiple ports in a range [2-112](#)
- selecting an interface to configure [2-109](#)

- setting a CoS value for Layer 2 packets [2-163](#)
- setting drop threshold for Layer 2 packets [2-164](#)
- setting the interface type [2-492](#)
- interface speed
  - configuring interface speed [2-481](#)
- interface transceiver
  - displaying diagnostic data [2-313](#)
- internal VLAN allocation
  - configuring [2-535](#)
  - default setting [2-535](#)
  - displaying allocation information [2-434](#)
- Internet Group Management Protocol
  - See IGMP
- IP ARP
  - applying ARP ACL to VLAN [2-115](#)
  - clearing inspection statistics [2-28](#)
  - clearing status of log buffer [2-27](#)
  - controlling packet logging [2-125](#)
  - enabling dynamic inspection [2-124](#)
  - limit rate of incoming requests [2-117](#)
  - set per-port config trust state [2-121](#)
  - showing status of dynamic ARP inspection [2-320](#)
  - showing status of log buffer [2-323](#)
- IPC
  - debugging IPC activities [2-53](#)
- IP DHCP Snooping
  - See DHCP snooping
- IP header validation
  - disabling [2-159](#)
  - enabling [2-159](#)
- IP interfaces
  - displaying usability status [2-342](#)
- IP multicast
  - displaying multicast routing table information [2-348](#)
- IP packets
  - enable DSCP rewrite [2-236](#)
- IP phone and standard desktop
  - enabling Cisco-recommended features [2-181](#)

- IP source binding
  - adding or deleting [2-156](#)
  - displaying bindingstaggering [2-353](#)
- IP source guard
  - debugging messages [2-56](#)
  - displaying configuration and filters [2-354](#)
  - enabling on DHCP snooping [2-160](#)

---

## J

- Jumbo frames
  - enabling jumbo frames [2-199](#)

---

## L

- LACP
  - deselecting channeling protocol [2-18](#)
  - enabling LACP on an interface [2-18](#)
  - setting channeling protocol [2-18](#)
- Layer 2
  - displaying ACL configuration [2-364](#)
- Layer 2 interface type
  - specifying a nontrunking, nontagged single VLAN interface [2-492](#)
  - specifying a trunking VLAN interface [2-492](#)
- Layer 2 protocol ports
  - displaying [2-358](#)
- Layer 2 protocol tunneling error recovery [2-166](#)
- Layer 2 switching
  - enabling voice VLANs [2-487](#)
  - modifying switching characteristics [2-487](#)
- Layer 2 traceroute
  - IP addresses [2-513](#)
- Layer 3 switching
  - displaying information about an adjacency table [2-254](#)
  - displaying port status [2-311](#)
  - displaying status of native VLAN tagging [2-311](#)
- log buffer
  - show status [2-323](#)

## logging

controlling IP ARP packets [2-125](#)

**M**

## MAC Access Control Lists

See MAC ACLs

## MAC ACLs

defining extended MAC access list [2-170](#)

displaying MAC ACL information [2-431](#)

naming an ACL [2-170](#)

## MAC address filtering

configuring [2-177](#)

disabling [2-177](#)

enabling [2-177](#)

## MAC address table

adding static entries [2-187](#)

clearing dynamic entries [2-37](#)

configuring aging time [2-173](#)

displaying dynamic table entry information [2-369](#)

displaying entry count [2-368](#)

displaying information [2-365](#)

displaying interface-based information [2-371](#)

displaying multicast information [2-373](#)

displaying protocol-based information [2-375](#)

displaying static table entry information [2-377](#)

displaying the MAC address aging time [2-367](#)

displaying VLAN-based information [2-379](#)

learning in the protocol buckets [2-174](#)

removing static entries [2-187](#)

## MAC address tables

adding static entries [2-177](#)

deleting secure or specific addresses [2-39](#)

disabling IGMP snooping on static MAC addresses [2-177](#)

removing static entries [2-177](#)

mac-address-table static [2-177](#)

## MAC address unicast filtering

dropping unicast traffic [2-177](#)

## macro keywords

help strings [2-2](#)

mapping secondary VLANs to MST instance [2-220](#)

mapping VLAN(s) to an MST instance [2-107](#)

## match subcommand

accessing [2-19](#)

## maximum transmission unit (MTU)

displaying the system MTU setting [2-423](#)

setting the maximum Layer 2 payload size [2-509](#)

## MD5

verifying MD5 signature [2-525](#)

## message digest 5

See MD5

## MFIB

clearing ip mfib counters [2-34](#)

clearing ip mfib fastdrop [2-35](#)

displaying all active MFIB routes [2-345](#)

displaying MFIB fastdrop table entries [2-347](#)

enabling IP MFIB fastdrops [2-153](#)

## modes

access-group [2-5](#)

show access-group interface [2-253](#)

switching between PVST+, MST, and Rapid PVST [2-459](#)

See also command modes

module password clearing [2-23](#)

## module reset

resetting a module by toggling the power [2-104](#)

## --More-- prompt

filter [1-6](#)

search [1-7](#)

## MST

designating the primary and secondary root [2-467](#)

displaying MST protocol information [2-418](#)

displaying region configuration information [2-418](#)

displaying spanning tree information [2-418](#)

entering MST configuration submode [2-461](#)

setting configuration revision number [2-247](#)

setting path cost and port priority for instances [2-460](#)



- setting the forward delay timer for all instances [2-463](#)
- setting the hello-time delay timer for all instances [2-464](#)
- setting the max-age timer for all instances [2-465](#)
- setting the MST region name [2-200](#)
- specifying the maximum number of hops [2-466](#)
- switching between PVST+ and Rapid PVST [2-459](#)
- using the MST configuration submode revision command [2-247](#)
- using the submode name command [2-200](#)

MTU

- displaying global MTU settings [2-423](#)

multicast

- enabling storm control [2-486](#)

multicast/unicast packets

- prevent forwarding [2-491](#)

Multicast Forwarding Information Base

- See MFIB

multiple-character patterns [1-8](#)

multiple hosts on authorized port [2-86](#)

Multiple Spanning Tree

- See MST

---

## N

native VLAN

- controlling tagging of traffic [2-505](#)
- displaying ports eligible for native tagging [2-433](#)
- displaying ports eligible for tagging [2-433](#)
- enabling tagging on 802.1Q trunk ports [2-533](#)
- specifying the tagging of traffic [2-506](#)

NetFlow

- enabling NetFlow statistics [2-154](#)
- including infer fields in routing statistics [2-154](#)

next-hop

- displaying CEF VLAN information [2-324](#)

no form of a command, using [1-6](#)

NVRAM

- debugging NVRAM activities [2-59](#)

---

## O

output

- pattern searches [1-7](#)

---

## P

packet forwarding

- prevent unknown packets [2-491](#)

packet memory failure

- direct switch action upon detection [2-81](#)

packet memory test

- bootup, displaying results [2-273](#)
- ongoing, displaying results [2-275](#)

PACL

- access-group mode [2-5](#)

paging prompt

- see --More-- prompt

PAgP

- clearing port channel information [2-38](#)
- debugging PAgP activity [2-60](#)
- deselecting channeling protocol [2-18](#)
- displaying port channel information [2-385](#)
- hot standby mode
  - returning to defaults [2-202](#)
  - selecting ports [2-202](#)
- input interface of incoming packets
  - learning [2-201](#)
  - returning to defaults [2-201](#)
  - setting channeling protocol [2-18](#)

parentheses [1-10](#)

password

- clearing on an intelligent line module [2-23](#)
- establishing enhanced password security [2-524](#)
- setting username [2-524](#)

PBR

- displaying route maps [xvi](#)
- redistributing route maps [xvi](#)

## PM activities

- debugging [2-63](#)
- disabling debugging [2-63](#)

## Policy Based Routing

- See PBR

## port, dual-capable

- selecting the connector [2-192](#)

## Port Aggregation Protocol

- See PAGP

## port-based authentication

- displaying debug messages [2-49](#)
- displaying statistics and status [2-277](#)
- enabling 802.1X [2-87](#)
- manual control of authorization state [2-87](#)
- multiple hosts on authorized port [2-86](#)
- periodic re-authentication
  - enabling [2-90](#)
- re-authenticating 802.1X-enabled ports [2-89](#)
- switch-to-client frame-retransmission number [2-85](#)

## port channel

- accessing [2-111](#)
- creating [2-111](#)
- displaying information [2-385](#)
- load distribution method
  - resetting to defaults [2-207](#)
  - setting [2-207](#)

## port range

- executing [2-112](#)

## port security

- debugging ports security [2-64](#)
- deleting secure or specific addresses [2-39](#)
- displaying settings for an interface or switch [2-390](#)
- enabling [2-494](#)
- filter source IP and MAC addresses [2-160](#)
- setting action upon security violation [2-494](#)
- setting the rate limit for bad packets [2-494](#)
- sticky port [2-494](#)

## Port Trust Device

- displaying [2-399](#)

## power status

- displaying inline power [2-392](#)
- displaying power status [2-392](#)

## power supply

- configuring combined and redundant power on the Catalyst 4507R [2-213](#)
- configuring inline power [2-210](#)
- configuring power consumption [2-212](#)
- configuring power redundancy on the Catalyst 4507R [2-215](#)
- displaying the SEEPROM [2-292](#)
- setting inline power state [2-209](#)

## Private VLAN

- See PVLANS

privileged EXEC mode, summary [1-5](#)

## prompts

- system [1-5](#)

## protocol tunneling

- configuring encapsulation rate [2-166](#)
- disabling [2-162](#)
- displaying port information [2-358](#)
- enabling [2-162](#)
- setting a CoS value for Layer 2 packets [2-163](#)
- setting a drop threshold for Layer 2 packets [2-164](#)

## PVLANS

- configuring isolated, primary, and community PVLANS [2-216](#)
- controlling tagging of native VLAN traffic [2-505](#)
- disabling sticky-ARP [2-157](#)
- displaying map information for VLAN SVIs [2-309](#)
- displaying PVLAN information [2-436](#)
- enabling interface configuration mode [2-492](#)
- enabling sticky-ARP [2-157](#)
- mapping VLANs to the same SVI [2-218](#)
- specifying host ports [2-492](#)
- specifying promiscuous ports [2-492](#)

## PVST+

- switching between PVST and MST [2-459](#)

**Q**

## QoS

- account Layer 2 encapsulation [2-223](#)
  - attaching a policy-map to an interface [2-248](#)
  - automatic configuration [2-12](#)
  - clearing aggregate counters [2-40](#)
  - configuring a QoS policy map [2-205](#)
  - configuring auto [2-12](#)
  - defining a named aggregate policer [2-225](#)
  - defining default CoS value [2-228](#)
  - defining ingress CoS-to-DSCP mapping [2-232](#)
  - displaying aggregate policer information [2-397](#)
  - displaying auto configuration [2-258](#)
  - displaying class maps information [2-266](#)
  - displaying configuration information [2-258](#)
  - displaying configurations of policies [2-388](#)
  - displaying policy map information [2-387](#)
  - displaying QoS information [2-396](#)
  - displaying QoS map information [2-400](#)
  - enabling global configuration mode [2-221](#)
  - enabling per-VLAN QoS for a Layer 2 interface [2-239](#)
  - enabling QoS on an interface [2-222](#)
  - mapping DSCP values to transmit queues [2-233](#)
  - mapping egress DSCP-to-CoS [2-233](#)
  - mapping the DSCP-to-CoS value [2-233](#)
  - setting the mapping of policed DSCP values [2-235](#)
  - setting the trust state [2-237](#)
  - specifying flow-based match criteria [2-189](#)
- QoS CoS
- configuring for tunneled Layer 2 protocol packets [2-163](#)
  - defining default CoS value [2-228](#)
- qos dbl [2-229](#)
- question command [1-1](#)
- queueing information
- displaying [2-399](#)

**R**

## Rapid PVST

- switching between PVST and MST [2-459](#)
- re-authenticating 802.1X-enabled ports [2-89](#)
- re-authentication
- periodic [2-90](#)
- reboots
- restoring bindings across [2-129](#)
- redundancy
- accessing the main CPU [2-240](#)
  - changing from active to standby supervisor engine [2-241](#)
  - displaying information [2-402](#)
  - displaying redundancy facility information [2-402](#)
  - displaying RF client list [2-402](#)
  - displaying RF operational counters [2-402](#)
  - displaying RF states [2-402](#)
  - enabling automatic synchronization [2-15](#)
  - forcing switchover to standby supervisor engine [2-241](#)
  - set the mode [2-193](#)
  - synchronizing the route processor configurations [2-187](#)
- related documentation [xv](#)
- remote SPAN
- See RSPAN
- renew commands
- ip dhcp snooping database [2-245](#)
- resetting PVLAN trunk
- setting switchport to trunk [2-492](#)
- rj45 connector, selecting the connector [2-192](#)
- ROM monitor mode
- summary [1-6](#)
- Route Processor Redundancy
- See redundancy
- RPR
- set the redundancy mode [2-193](#)
- RSPAN
- converting VLAN to RSPAN VLAN [2-244](#)
  - displaying list [2-438](#)

## S

saving configuration changes [1-11](#)

secure ports, limitations [2-495](#)

set the redundancy mode [2-193](#)

sfp connector, selecting the connector [2-192](#)

show commands

filtering parameters [1-7](#)

searching and filtering [1-6](#)

show platform commands [1-11](#)

Simple Network Management Protocol

See SNMP

single-character patterns

special characters [1-7](#)

slaveslot0

displaying information on the standby supervisor [2-409](#)

slot0

displaying information about the system [2-411](#)

SMF

debugging address insertions and deletions [2-66](#)

SNMP

debugging spanning tree activities [2-67](#)

ifIndex persistence

clearing SNMP ifIndex commands [2-443](#)

compress SNMP ifIndex table format [2-448](#)

disabling globally [2-447](#)

disabling on an interface [2-444](#)

enabling globally [2-447](#)

enabling on an interface [2-444](#)

informs

disabling [2-445](#)

enabling [2-445](#)

traps

configuring to send when storm occurs [2-484](#)

disabling [2-445](#)

enabling [2-445](#)

software MAC filter

See SMF

SPAN commands

configuring a SPAN session to monitor [2-195](#)

displaying SPAN session information [2-422, 2-485](#)

SPAN enhancements

displaying status [2-383](#)

Spanning Tree Protocol

See STP

SPAN session

displaying session information [2-383](#)

filter ACLs [2-195](#)

specify encaps type [2-195](#)

turn off host learning based on ingress packets [2-195](#)

special characters

anchoring, table [1-10](#)

SSO [2-193](#)

standard desktop

enabling Cisco-recommended features [2-179](#)

standard desktop and Cisco IP phone

enabling Cisco-recommended features [2-181](#)

sticky-ARP

disabling on PVLANS [2-157](#)

enabling on PVLANS [2-157](#)

sticky port

deleting [2-39](#)

enabling security [2-494](#)

storm control

configuring for action when storm occurs [2-484](#)

disabling suppression mode [2-283](#)

displaying settings [2-421](#)

enabling [2-484](#)

enabling broadcast [2-484, 2-486](#)

enabling multicast [2-484, 2-486](#)

enabling suppression mode [2-283](#)

enabling timer to recover from error disable [2-98](#)

enabling unicast [2-484, 2-486](#)

multicast, enabling [2-486](#)

setting high and low levels [2-484](#)

setting suppression level [2-283](#)

## STP

- configuring link type for a port [2-457](#)
- configuring tunneling encapsulation rate [2-166](#)
- debugging all activities [2-67](#)
- debugging spanning tree activities [2-67](#)
- debugging spanning tree BackboneFast events [2-68](#)
- debugging spanning tree UplinkFast [2-71](#)
- detecting misconfiguration [2-454](#)
- displaying active interfaces only [2-413](#)
- displaying BackboneFast status [2-413](#)
- displaying bridge status and configuration [2-413](#)
- displaying spanning tree debug messages [2-67](#)
- displaying summary of interface information [2-413](#)
- enabling BPDU filtering by default on all PortFast ports [2-472](#)
- enabling BPDU filtering on an interface [2-450](#)
- enabling BPDU guard by default on all PortFast ports [2-474](#)
- enabling BPDU guard on an interface [2-452](#)
- enabling extended system ID [2-455](#)
- enabling loop guard as a default on all ports [2-458](#)
- enabling PortFast by default on all access ports [2-475](#)
- enabling PortFast mode [2-470](#)
- enabling protocol tunneling for [2-162](#)
- enabling root guard [2-456](#)
- enabling spanning tree BackboneFast [2-449](#)
- enabling spanning tree on a per VLAN basis [2-479](#)
- enabling spanning tree UplinkFast [2-477](#)
- setting an interface priority [2-476](#)
- setting drop threshold for [2-164](#)
- setting pathcost [2-453](#)
- setting the default pathcost calculation method [2-469](#)
- subinterface configuration mode, summary [1-6](#)
- SVI
  - creating a Layer 3 interface on a VLAN [2-114](#)
- switchport [2-506](#)
- switchport interfaces
  - displaying status of Layer 3 port [2-311](#)
  - displaying status of native VLAN tagging [2-311](#)

## switch shim

- debugging [2-69](#)
- disabling debugging [2-69](#)
- switch to router connection
  - enabling Cisco-recommended features [2-183](#)
- switch to switch connection
  - enabling Cisco-recommended features [2-185](#)
- switch virtual interface
  - See SVI
- sw-vlan [2-72](#)
- system prompts [1-5](#)

---

**T**

- Tab key
  - command completion [1-1](#)
- tables
  - characters with special meaning [1-7](#)
  - mac access-list extended subcommands [2-170](#)
  - match syntax description [2-20](#)
  - multipliers [1-9](#)
  - relationship between duplex and speed commands [2-482](#)
  - show cdp neighbors detail field descriptions [2-265](#)
  - show cdp neighbors field descriptions [2-264](#)
  - show ip interface field descriptions [2-343](#)
  - show vlan command output fields [2-437](#)
  - show vtp command output fields [2-441](#)
  - special characters [1-9](#)
  - special characters used for anchoring [1-10](#)
  - speed command options [2-189, 2-482](#)
  - valid interface types [2-109](#)
- TAC
  - displaying information useful to TAC [2-424](#)
- TCAM
  - debugging spanning tree activities [2-67](#)
- temperature readings
  - displaying information [2-280](#)
- timer information [2-284](#)

traffic shaping  
     enable on an interface [2-250](#)

traps, enabling [2-445](#)

trunk encapsulation  
     setting format [2-506](#)

trunk interfaces  
     displaying trunk interfaces information [2-318](#)

trust state  
     setting [2-121](#)

tunnel ports  
     displaying information about Layer 2 protocol [2-358](#)

TX queues  
     allocating bandwidth [2-516](#)  
     returning to default values [2-516](#)  
     setting priority to high [2-516](#)  
     specifying burst size [2-516](#)  
     specifying traffic rate [2-516](#)

## U

UDLD  
     displaying administrative and operational status [2-426](#)  
     enabling by default on all fiber interfaces [2-518](#)  
     enabling on an individual interface [2-520](#)  
     preventing a fiber interface from being enabled [2-520](#)  
     resetting all shutdown ports [2-522](#)  
     setting the message timer [2-518](#)

Unidirectional Link Detection  
     See UDLD

unknown multicast traffic, preventing [2-491](#)

unknown unicast traffic, preventing [2-491](#)

user EXEC mode, summary [1-5](#)

username  
     setting password and privilege level [2-524](#)

## V

VACLs  
     access-group mode [2-5](#)  
     applying VLAN access maps [2-534](#)  
     displaying VLAN access map information [2-431](#)  
     specifying an action in a VLAN access map [2-8](#)  
     specifying the match clause for a VLAN access-map sequence [2-188](#)  
     using a VLAN filter [2-534](#)

VLAN  
     applying an ARP ACL [2-115](#)  
     configuring [2-527](#)  
     converting to RSPAN VLAN [2-244](#)  
     displaying CEF information [2-324](#)  
     displaying CEF next-hop information [2-324](#)  
     displaying information on switch interfaces [2-334, 2-338](#)  
     displaying information on VLAN switch interfaces [2-341](#)  
     displaying information sorted by group IP address [2-334, 2-338](#)  
     displaying IP address and version information [2-334, 2-338](#)  
     displaying Layer 2 VLAN information [2-428](#)  
     displaying statistical information [2-381](#)  
     displaying VLAN information [2-430](#)  
     enabling dynamic ARP inspection [2-124](#)  
     enabling Explicit Host Tracking [2-147](#)  
     enabling guest per-port [2-82](#)  
     entering VLAN configuration mode [2-531](#)  
     native frames  
         enabling tagging on all 802.1Q trunk ports [2-533](#)  
     pruning the list for VTP [2-506](#)  
     setting the list of allowed [2-506](#)

VLAN Access Control Lists  
     See VACLs

VLAN access map  
     See VACLs

VLAN database  
     resetting [2-246](#)

- VLAN debugging
  - limiting output [2-48](#)
- VLAN manager
  - debugging [2-72](#)
  - disabling debugging [2-72](#)
  - IOS file system error tests
    - debugging [2-73](#)
    - disabling debugging [2-73](#)
- VLAN Query Protocol
  - See VQP
- VLAN query protocol (VQPC)
  - debugging [2-77](#)
- VLANs
  - clearing
    - counters [2-41](#)
  - clearing hardware logic [2-25](#)
  - configuring
    - internal allocation scheme [2-535](#)
  - displaying
    - internal VLAN allocation information [2-434](#)
    - RSPAN VLANs [2-438](#)
  - entering VLAN configuration mode [2-531](#)
- VMPS
  - configuring servers [2-539](#)
  - reconfirming dynamic VLAN assignments [2-537](#)
- voice VLANs
  - enabling [2-487](#)
- VoIP
  - configuring auto-QoS [2-12](#)
- VQP
  - per-server retry count [2-538](#)
  - reconfirming dynamic VLAN assignments [2-537](#)
- VTP
  - configuring the administrative domain name [2-543](#)
  - configuring the device in VTP client mode [2-542](#)
  - configuring the device in VTP server mode [2-546](#)
  - configuring the device in VTP transparent mode [2-547](#)
  - configuring tunnel encapsulation rate [2-166](#)
  - creating a VTP domain password [2-544](#)
  - displaying domain information [2-440](#)
  - displaying statistics information [2-440](#)
  - enabling protocol tunneling for [2-162](#)
  - enabling pruning in the VLAN database [2-545](#)
  - enabling VTP version 2 mode [2-548](#)
  - modifying the VTP configuration storage file name [2-541](#)
  - set drop threshold for [2-164](#)
- VTP protocol code
  - activating debug messages [2-75](#)
  - deactivating debug messages [2-75](#)

