



Whats New in Cisco IOS XE Dublin 17.10.x

- [Hardware Features in Cisco IOS XE Dublin 17.10.1, on page 1](#)
- [Software Features in Cisco IOS XE Dublin 17.10.1, on page 1](#)
- [Hardware and Software Behavior Changes in Cisco IOS XE Dublin 17.10.1, on page 2](#)

Hardware Features in Cisco IOS XE Dublin 17.10.1

There are no new hardware features in this release.

Software Features in Cisco IOS XE Dublin 17.10.1

Feature Name	Description
Custom EAPoL	Allows customization of the default EAPoL EtherType to configure MACsec with EtherType as 876F.
DHCP Gleaning	Introduces support for a read-only DHCP snooping functionality that allows components to register and glean only DHCP version 4 packets.
Enhanced Password Security Through Updated Combination Rule	The character-repetition and restrict-consecutive-letters keywords were introduced for the aaa common-criteria policy command.
MACsec Fallback Key Support with High Availability	Introduces support for the MACsec Fallback Key feature with High Availability. The MACsec Fallback Key feature establishes an MKA session with the pre-shared fallback key whenever the PSK fails to establish a session because of key mismatch.

Feature Name	Description
Programmability <ul style="list-style-type: none"> • Upgrade YANG Models to YANG 1.1 • YANG Data Models 	The following programmability features are introduced in this release: <ul style="list-style-type: none"> • Upgrade YANG Models to YANG 1.1: Cisco-defined YANG models are in YANG Version 1.1 in Cisco IOS XE Dublin 17.10.1 and later releases. • YANG Data Models: For the list of Cisco IOS XE YANG models available with this release, navigate to: https://github.com/YangModels/yang/tree/master/vendor/cisco/xe/17101.
RADIUS Automated Testing Probe-on	The command automate-tester probe-on was introduced. It starts a dead timer and packets are sent to the external RADIUS server after the timer expires.
Reflexive Access Lists (IPv4)	Reflexive access lists allow IP packets to be filtered based on upper-layer session information.
Secure Data Wipe	Introduces support for performing factory reset by using the keyword all secure in the factory-reset command. This option performs data sanitisation and securely resets the device.
SHA256 based Password-masking support	You can use the masked-secret keyword on the enable algorithm type command and username command. The keyword masks the secret input and converts to the selected encryption.
Standalone Mode on Layer 3 EtherChannels	Introduces support for configuring standalone mode/independent mode on Layer 3 EtherChannels.

New on the WebUI

There are no new WebUI features in this release.

Hardware and Software Behavior Changes in Cisco IOS XE Dublin 17.10.1

Behavior Change	Description
debug platform command	The debug platform software fed switch active inject packet-capture start command was modified. full-packet keyword was added. It allows you to capture 1500 bytes of packet. The default packet capture was only for 128 bytes of the packet prior to Cisco IOS XE Dublin 17.10.1.