

# Configuring OSPFv3 Fast Convergence - LSA and SPF Throttling

OSPFv3 Fast Convergence: LSA and SPF Throttling, on page 1

# OSPFv3 Fast Convergence: LSA and SPF Throttling

The Open Shortest Path First version 3 (OSPFv3) link-state advertisement (LSAs) and shortest-path first (SPF) throttling feature provides a dynamic mechanism to slow down link-state advertisement updates in OSPFv3 during times of network instability. It also allows faster OSPFv3 convergence by providing LSA rate limiting in milliseconds.

## Information About OSPFv3 Fast Convergence: LSA and SPF Throttling

## **Fast Convergence: LSA and SPF Throttling**

The OSPFv3 LSA and SPF throttling feature provides a dynamic mechanism to slow down link-state advertisement updates in OSPFv3 during times of network instability. It also allows faster OSPFv3 convergence by providing LSA rate limiting in milliseconds.

OSPFv3 can use static timers for rate-limiting SPF calculation and LSA generation. Although these timers are configurable, the values used are specified in seconds, which poses a limitation on OSPFv3 convergence. LSA and SPF throttling achieves subsecond convergence by providing a more sophisticated SPF and LSA rate-limiting mechanism that is able to react quickly to changes and also provide stability and protection during prolonged periods of instability.

## How to Configure OSPFv3 Fast Convergence: LSA and SPF Throttling

### **Tuning LSA and SPF Timers for OSPFv3 Fast Convergence**

To tune LSA and SPF timers for OSPFv3 fast convergence, perform this procedure:

#### **SUMMARY STEPS**

- 1. enable
- 2. configure terminal

- **3.** router ospfv3 [process-id]
- 4. timers lsa arrival milliseconds
- **5.** timers pacing flood milliseconds
- 6. timers pacing lsa-group seconds
- 7. timers pacing retransmission milliseconds

#### **DETAILED STEPS**

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.
	Example:	Enter your password if prompted.
	Device> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 3	router ospfv3 [process-id]	Enables OSPFv3 router configuration mode for the IPv4 or IPv6 address family.
	Example:	
	Device(config) # router ospfv3 1	
Step 4	timers lsa arrival milliseconds	Sets the minimum interval at which the software accepts the same LSA from OSPFv3 neighbors.
	Example:	
	Device(config-rtr)# timers lsa arrival 300	
Step 5	timers pacing flood milliseconds	Configures LSA flood packet pacing.
	Example:	
	Device(config-rtr)# timers pacing flood 30	
Step 6	timers pacing lsa-group seconds	Changes the interval at which OSPFv3 LSAs are collected
	Example:	into a group and refreshed, checksummed, or aged.
	Device(config-router)# timers pacing lsa-group 300	
Step 7	timers pacing retransmission milliseconds	Configures LSA retransmission packet pacing in IPv4 OSPFv3.
	Example:	
	Device(config-router)# timers pacing retransmission 100	

## **Configuring LSA and SPF Throttling for OSPFv3 Fast Convergence**

To configure LSA and SPF throttling for OSPFv3 fast convergence, perform this procedure:

#### **SUMMARY STEPS**

- 1. enable
- 2. configure terminal

- 3. ipv6 router ospf process-id
- **4. timers throttle spf** *spf-start spf-hold spf-max-wait*
- **5.** timers throttle lsa start-interval hold-interval max-interval
- 6. timers lsa arrival milliseconds
- 7. timers pacing flood milliseconds

#### **DETAILED STEPS**

	Command or Action	Purpose
Step 1	enable	Enables privileged EXEC mode.
	Example:	• Enter your password if prompted.
	Device> enable	
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 3	ipv6 router ospf process-id	Enables OSPFv3 router configuration mode.
	Example:	
	Device(config)# ipv6 router ospf 1	
Step 4	timers throttle spf spf-start spf-hold spf-max-wait	Turns on SPF throttling.
	Example:	
	Device(config-rtr)# timers throttle spf 200 200 200	
Step 5	timers throttle lsa start-interval hold-interval max-interval	Sets rate-limiting values for OSPFv3 LSA generation.
	Example:	
	Device(config-rtr)# timers throttle 1sa 300 300 300	
Step 6	timers lsa arrival milliseconds	Sets the minimum interval at which the software accepts the same LSA from OSPFv3 neighbors.
-	Example:	
	Device(config-rtr)# timers lsa arrival 300	
Step 7	timers pacing flood milliseconds	Configures LSA flood packet pacing.
	Example:	
	Device(config-rtr)# timers pacing flood 30	

# Configuration Examples for OSPFv3 Fast Convergence: LSA and SPF Throttling

## **Example: Configuring LSA and SPF Throttling for OSPFv3 Fast Convergence**

The following example show how to display the configuration values for SPF and LSA throttling timers:

#### Device# show ipv6 ospf

```
Routing Process "ospfv3 1" with ID 10.9.4.1

Event-log enabled, Maximum number of events: 1000, Mode: cyclic It is an autonomous system boundary router Redistributing External Routes from, ospf 2

Initial SPF schedule delay 5000 msecs Minimum hold time between two consecutive SPFs 10000 msecs Maximum wait time between two consecutive SPFs 10000 msecs Minimum LSA interval 5 secs Minimum LSA arrival 1000 msecs
```

## **Additional References**

#### **Related Documents**

Related Topic	Document Title
IPv6 addressing and connectivity	IPv6 Configuration Guide
OSPFv3 Fast Convergence: LSA and SPF Throttling	OSPF Shortest Path First Throttling module

#### Standards and RFCs

Standard/RFC	Title
RFCs for IPv6	IPv6 RFCs

# Feature Information for OSPFv3 Fast Convergence: LSA and SPF Throttling

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Table 1: Feature Information for OSPFv3 Fast Convergence: LSA and SPF Throttling

Releases	Feature Information
Cisco IOS XE Fuji 16.8.1a	The feature was introduced.