

Configuring BGP Large Community

- Restrictions for the BGP Large Community, on page 1
- Information About the BGP Large Community Feature, on page 1
- How to Configure the BGP Large Community, on page 2
- Configuration Example: BGP Large Community, on page 10
- Feature History for BGP Large Community, on page 11

Restrictions for the BGP Large Community

When large communities are specified in commands, they are specified as three non-negative decimal integers separated by colons. For example as 1:2:3. Each integer is stored in 32 bits. The possible range for each integer is four octet decimal which can be from 0 to 4294967295.

Information About the BGP Large Community Feature

The BGP large communities attribute provides the capability for tagging routes and modifying BGP routing policy on routers. BGP large communities can be appended or removed selectively on the large community attribute as the route travels from router to router. The BGP large communities are similar attributes to BGP communities, but with a twelve octet size. However, there are no well-known large communities as in communities. The BGP large communities are also split logically into a 4 octet Global Administrator field and a 8 octet Local Administrator field. A 4 octet Autonomous System can fit into the Global Administrator field.

For more information on BGP large community, see the rfc8092 document.

Large Community Lists

A BGP large community list is used to create groups of large communities which can be used in a match clause of a route map. You can use the large communities to control the routing policy. Routing policy allows you to filter the routes you receive or advertise, or modify the attributes of the routes you receive or advertise. You can also use a large community list to set or delete the large communities selectively.

- Standard large community lists are used to specify large communities.
- Expanded large community lists are used to specify large communities using a regular expression.

A large community list can be either named or numbered and standard or expanded. All the rules of numbered large community lists apply to named large community lists, except that there is no limit on the number of named community lists that can be configured.



A maximum of 100 numbered standard large community lists and 100 numbered expanded large community lists can be configured. A named large community list does not have this limitation.

BGP Large Community Attribute

In an BGP large community, the community value is encoded as a 12 octet number. The following image displays the syntax of the large community attribute.

0 1 2 789012345678 0 12345 9 0 3 4 - 5 - 8 - 6 -1 2 - 6 -+-+-+ Global Administrator Local Data Part Local Data Part -2 Global Administrator: A four-octet namespace identifier. Local Data Part 1: A four-octet operator-defined value. Local Data Part 2: A four-octet operator-defined value

How to Configure the BGP Large Community

The following sections provide configuration information about BGP large community.

Enabling BGP Large Community

To enable the large-communities, perform the following steps.

SUMMARY STEPS

- 1. configure terminal
- 2. router bgp autonomous-system-number

- **3.** neighbor *IP address* remote-as *autonomous-system-number*
- 4. address-family { ipv4 | ipv6 | l2vpn | nsap {unicast |multicast }}
- 5. neighbor *IP address* activate
- 6. neighbor *IP address* send-community {both | extended | standard}
- 7. exit
- 8. end

DETAILED STEPS

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 2	router bgp autonomous-system-number	Enables BGP and assigns the AS number to the local BGP
	Example:	speaker. The AS number can be a 16-bit integer or a 32-b integer in the form of a higher 16-bit decimal number and
	Device(config)# router bgp 64496	a lower 16-bit decimal number.
Step 3	neighbor IP address remote-as	Enters global address family configuration mode. This
	autonomous-system-number	command triggers an automatic notification and session reset for all BGP neighbors.
	Example:	reset for all DOT heighbors.
	Device(config-router)# neighbor 209.165.201.1 remote-as 100	
Step 4	address-family { ipv4 ipv6 l2vpn nsap { unicast	Enters global address family configuration mode. This
	multicast } }	command triggers an automatic notification and session reset for all BGP neighbors.
	Example:	Note It also supports other available address
	Device(config-router-neighbor)# address-family ipv4	
	multicast	
Step 5	neighbor IP address activate	Enters global address family configuration mode and
	Example:	activates the BGP neighbor.
	Device(config-router)# neighbor 209.165.201.1	
	activate	
Step 6	neighbor <i>IP address</i> send-community {both extended	Configures the router to send the large-community attribute
	standard}	to the neighbor 209.165.201.1.
	Example:	• Both—Sends both the extended large community and standard large community attributes to the neighbor.
	Device(config-router-neighbor-af)# neighbor	
	209.105.201.1 send-community standard	to the neighbor.
		standard large community attributes to the • Extended—Sends the extended community

	Command or Action	Purpose
		• Standard—Sends large community and also (regular) community attribute to the neighbor.
	Exits address-family mode and router configuration mode	
	Example:	and enters global configuration mode.
	Device(config-router)# exit Device(config-router)# exit	
Step 8	end	Exits configuration mode and enters privileged EXEC mode.
	Example:	
	Device(config)# end	

Configuring Route-map with Large Community Lists and Matching a Large Community

To match a BGP large community, perform the following steps.

SUMMARY STEPS

- 1. configure terminal
- 2. route-map map-tag [permit | deny] [sequence number]
- **3.** match large-community {name | numbered }
- 4. exit
- **5.** route-map map-tag [permit | deny] [sequence number]
- 6. match large-community {name | numbered } exact match
- 7. end

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 2	<pre>route-map map-tag [permit deny][sequence number]</pre>	1 0
Example:	Example:	conditions for routes from one routing protocol into another.
	Device(config)# route-map test permit 10	
Step 3	match large-community {name numbered }	Matches a large-community lists. Defines the rules for an
	Example:	entry in the large-community lists and ensures that all the

	Command or Action	Purpose
	Device(config-route-map)# match large-community 1	large communities matches the large communities in the routes.
Step 4	<pre>exit Example: Device(config-router)# exit</pre>	Exits router configuration mode and enters global configuration mode.
Step 5	<pre>route-map map-tag [permit deny][sequence number] Example: Device(config)# route-map test permit 10</pre>	Enters the route-map configuration mode and defines the conditions for routes from one routing protocol into another.
Step 6	<pre>match large-community {name numbered } exact match Example: Device(config-route-map)# match large-community 1 exact-match</pre>	Matches a large-community lists. Defines the rules for an entry in the large-community lists and ensures that all the large communities matches the large communities in the routes. The key word exact-match indicates that an exact match is required to match a BGP large community.
Step 7	<pre>end Example: Device(config-route-map)# end</pre>	Exits route map configuration mode and enters privileged EXEC mode.

Defining BGP Large Community List

To define the BGP large community list, perform the following steps. BGP large community supports named and numbered community lists.

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- **3.** ip large-community-list {standard-list-number | standard standard-list-name } {deny | permit} community-number large-community
- **4.** ip large-community-list {*expanded-list number* | **expanded** *expanded-list-name*} {**deny** | **permit**} *regexp*
- 5. exit
- 6. end

	Command or Action	Purpose
Step 1	enable	Enables higher privilege levels, such as privileged EXEC
	Example:	mode.

	Command or Action	Purpose
	Device> enable	• Enter your password if prompted.
Step 2	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 3	ip large-community-list { <i>standard-list-number</i> standard <i>standard-list-name</i> } { deny permit } <i>community-number large-community</i>	Defining the large community based on the standard list number. If you attempt to configure more than 6 communities, the trailing communities that exceed the limi are not processed or saved to the running configuration file
	Example:	
	Numbered Large-community List	
	ip large-community-list 1 permit 1:2:3 5:6:7 ip large-community-list 1 permit 4123456789:4123456780:4123456788	
	Named Large-community List	
	ip large-community-list standard LG_ST permit 1:2:3	
	5:6:7 ip large-community-list standard LG_ST permit 4123456789:4123456780:4123456788	
Step 4	ip large-community-list {expanded-list number expanded expanded-list-name} {deny permit} regexp	Defines the large communities based on regular expression and matches according to Cisco's regular expression
	Example:	implementation.
	Numbered Extended Large-community List	
	<pre>ip large-community-list 100 permit ^5:.*:7\$ ip large-community-list 100 permit ^5:.*:8\$</pre>	
	Named Extended Large-community List	
	ip large-community-list expanded LG_EX permit	
	<pre>^5:.*:7\$ ip large-community-list expanded LG_EX permit ^5:.*:8\$</pre>	
Step 5	exit	Exits router configuration mode and enters global configuration mode.
	Example:	
	Device(config-router)# exit	
Step 6	end	Exits route map configuration mode and enters privileged
	Example:	EXEC mode.
	Device(config) # end	

Configuring the Route-map to Set BGP Large Communities

To set the large-communities, perform the following steps.

SUMMARY STEPS

- 1. configure terminal
- **2.** route-map map-tag [permit | deny] [sequence number]
- **3.** set large-community {none | {xx:yy:zz }}
- 4. exit
- **5.** route-map map-tag [permit | deny] [sequence number]
- 6. set large-community {none | { $xx:yy:zz | additive }$ }
- 7. end

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 2	route-map map-tag [permit deny] [sequence number] Example:	Enters the route-map configuration mode and specifies a set of large communities to a route.
	Device(config)# route-map foo permit 10	
Step 3	set large-community {none {xx:yy:zz }} Example:	A route-map set statement is used to set large communities in a route. It can specify a set of large communities to a route.
	Device(config-route-map)# set large-community 1:2:3 5:6:7	3
Step 4	exit Example:	Exits router configuration mode and enters global configuration mode.
	Device(config-router)# exit	
Step 5	route-map map-tag [permit deny] [sequence number] Example:	Enters the route-map configuration mode and specifies a set of large communities to a route.
	Device(config)# route-map foo permit 10	
Step 6	set large-community {none {xx:yy:zz additive }} Example:	A route-map set statement is used to set large communit in a route. It can specify a set of large communities to a route. Also, the keyword additive adds the large communities without removing the existing large
	Device(config-route-map)# set large-community 1:2:3 5:6:7 additive	communities.

	Command or Action	Purpose
Step 7	end	Exits route map configuration mode and enters privileged
	Example:	EXEC mode.
	Device(config-route-map)# end	

Deleting Large Communities

To delete BGP large communities, perform the following steps.

SUMMARY STEPS

- 1. configure terminal
- **2.** route-map map-tag [permit | deny] [sequence number]
- **3.** set large-comm-list community-list-name delete
- 4. exit
- 5. end

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 2	<pre>route-map map-tag [permit deny] [sequence number]</pre>	Enters the route-map configuration mode and defines the
	Example:	conditions for redistributing routes from one routing protocol into another.
	Device(config)# route-map test permit 10	
Step 3	set large-comm-list community-list-name delete	Deletes the large-communities based on
	Example:	large-community-list matches.
	Device(config-route-map)# set large-comm-list 1	
	<pre>delete Device(config-route-map)#</pre>	
Step 4	exit	Exits router configuration mode and enters global
	Example:	configuration mode.
	Device(config-router)# exit	
Step 5	end	Exits route map configuration mode and enters privileged
	Example:	EXEC mode.
	Device(config-route-map)# end	

Verifying the Configuration of the BGP Large Community

1.1.1.2

To verify the BGP large community, use the following command. This example shows a list of routes that contain all of the large communities given in the command. The listed routes may contain additional large communities.

Device# show bgp large-community 1:2:3 5:6:7 BGP table version is 17, local router ID is 1.1.1.3 Status codes: s suppressed, d damped, h history, * valid, > best, i - internal, r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter, x best-external, a additional-path, c RIB-compressed, Origin codes: i - IGP, e - EGP, ? - incomplete RPKI validation codes: V valid, I invalid, N Not found Next Hop Network Metric LocPrf Weight Path 0 100 0 ? 1.1.1.2

This example displays the listed routes that contain only the given large communities when you add the keyword exact-match in configuration.

0

100

0 ?

```
Device#show bgp large-community 1:2:3 5:6:7 exact-match
BGP table version is 17, local router ID is 1.1.1.3
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
             r RIB-failure, S Stale, m multipath, b backup-path, f RT-Filter,
             x best-external, a additional-path, c RIB-compressed,
Origin codes: i - IGP, e - EGP, ? - incomplete
RPKI validation codes: V valid, I invalid, N Not found
                                         Metric LocPrf Weight Path
     Network
                     Next Hop
 *>i 5.5.5.5/32
                     1.1.1.2
                                              0
                                                 100
                                                          0 2
```

In these examples, the routes 5.5.5.5/32 and 5.5.5/32 contain both the large communities 1:2:3 and 5:6:7. The route 5.5.5.6/32 contains some additional large communities.

This example displays a large-community list.

```
Device#show ip largecommunity-list 20
Large Community standard list 20
    permit 1:1:2
Device#show bgp large-community-list 20
Large Community standard list 20
    permit 1:1:2
```

Troubleshooting Large Communities

To debug the large communities, use **debug ip bgp update** command.

Device#debug ip bgp update

```
*Mar 10 23:25:01.194: BGP(0): 192.0.0.1 rcvd UPDATE w/ attr: nexthop 192.0.0.1, origin ?,
metric 0, merged path 1, AS PATH , community 0:44 1:1 2:3, large-community 3:1:244 3:1:245
*Mar 10 23:25:01.194: BGP(0): 192.0.0.1 rcvd 5.5.5.1/32
*Mar 10 23:25:01.194: BGP(0): Revise route installing 1 of 1 routes for 5.5.5.1/32 ->
192.0.0.1(global) to main IP table
```

Memory Display

The show ip bgp summary command displays large-community memory information.

Device #show ip bgp summary BGP router identifier 1.1.1.1, local AS number 1 BGP table version is 3, main routing table version 3 2 network entries using 496 bytes of memory 2 path entries using 272 bytes of memory 1/1 BGP path/bestpath attribute entries using 288 bytes of memory 1 BGP community entries using 40 bytes of memory 2 BGP large-community entries using 96 bytes of memory 0 BGP route-map cache entries using 0 bytes of memory O BGP filter-list cache entries using O bytes of memory BGP using 1096 total bytes of memory BGP activity 3/1 prefixes, 3/1 paths, scan interval 60 secs 2 networks peaked at 13:04:52 Mar 11 2020 EST (00:07:25.579 ago) Neighbor V AS MsgRcvd MsgSent TblVer InQ OutQ Up/Down State/PfxRcd 192.0.0.2 2 1245 1245 3 0 0 18:47:56 4

Configuration Example: BGP Large Community

The following example shows how to configure route-maps using large-communities.

A route-map set statement is used to set the large communities in a route. It can specify a set of large communities to a route.

The additive keyword adds the large communities without removing the existing large communities (for standard large community-lists only).

Setting Large Communities

This example shows how to set large communities.

route-map foo permit 10 set large-community 1:2:3 5:6:7 route-map foo2 permit 10 set large-community 1:2:3 5:6:7 additive

Matching Large Communities

This example shows how to match large communities.

```
route-map foo permit 10
match large-community 1
route-map foo2 permit 10
```

match large-community 1 exact-match

Deleting Large Communities

This example shows how to delete a large community.

route-map foo set large-comm-list 1 delete

Numbered Standard Large Community List

This example shows how to configure a numbered large community list.

```
ip large-community-list 1 permit 1:2:3 5:6:7
ip large-community-list 1 permit 4123456789:4123456780:4123456788
```

Named Standard Large Community List

This example shows how to configure a named standard large community list.

L

ip large-community-list standard LG_ST permit 1:2:3 5:6:7
ip large-community-list standard LG_ST permit 4123456789:4123456780:4123456788

Numbered Expanded Large Community List

This example shows how to configure a numbered expanded large community list.

ip large-community-list 100 permit ^5:.*:7\$
ip large-community-list 100 permit ^5:.*:8\$

Named Expanded Large Community List

This example shows how to configure a named expanded large community list.

```
ip large-community-list expanded LG_EX permit ^5:.*:7$
ip large-community-list expanded LG_EX permit ^5:.*:8$
```

Feature History for BGP Large Community

This table provides release and related information for the features explained in this module.

These features are available on all the releases subsequent to the one they were introduced in, unless noted otherwise.

Release	Feature	Feature Information
Cisco IOS XE Bengaluru 17.4.1	BGP Large Community	The BGP large communities attribute provides the capability for tagging routes and modifying BGP routing policy on routers. They are similar attributes to BGP communities, but with a twelve octet size.
Cisco IOS XE Cupertino 17.7.1	BGP Large Community	Support for this feature was introduced only on the Cisco Catalyst 9600 Series Supervisor 2 Module (C9600X-SUP-2).

Use the Cisco Feature Navigator to find information about platform and software image support. To access Cisco Feature Navigator, go to https://cfnng.cisco.com/.