



INDEX

A

AAA down policy, NAC Layer 2 IP validation [1-10](#)

abbreviating commands [2-4](#)

ABRs [41-24](#)

AC (command switch) [6-10](#)

access-class command [38-19](#)

access control entries

See ACEs

access control entry (ACE) [44-3](#)

access-denied response, VMPS [16-25](#)

access groups

applying IPv4 ACLs to interfaces [38-20](#)

Layer 2 [38-20](#)

Layer 3 [38-20](#)

accessing

clusters, switch [6-13](#)

command switches [6-11](#)

member switches [6-13](#)

switch clusters [6-13](#)

access lists

See ACLs

access ports

and Layer 2 protocol tunneling [20-10](#)

defined [14-3](#)

in switch clusters [6-9](#)

accounting

with 802.1x [12-48](#)

with IEEE 802.1x [12-14](#)

with RADIUS [11-35](#)

with TACACS+ [11-11, 11-17](#)

ACEs

and QoS [39-7](#)

defined [38-2](#)

Ethernet [38-2](#)

IP [38-2](#)

ACLs

ACEs [38-2](#)

any keyword [38-12](#)

applying

on bridged packets [38-38](#)

on multicast packets [38-40](#)

on routed packets [38-39](#)

on switched packets [38-38](#)

time ranges to [38-16](#)

to an interface [38-19, 44-7](#)

to IPv6 interfaces [44-7](#)

to QoS [39-7](#)

classifying traffic for QoS [39-43](#)

comments in [38-18](#)

compiling [38-22](#)

defined [38-1, 38-7](#)

examples of [38-22, 39-43](#)

extended IP, configuring for QoS classification [39-44](#)

extended IPv4

creating [38-10](#)

matching criteria [38-7](#)

hardware and software handling [38-21](#)

host keyword [38-12](#)

IP

creating [38-7](#)

fragments and QoS guidelines [39-33](#)

implicit deny [38-9, 38-14, 38-15](#)

implicit masks [38-9](#)

matching criteria [38-7](#)

undefined [38-21](#)

IPv4

- applying to interfaces [38-19](#)
- creating [38-7](#)
- matching criteria [38-7](#)
- named [38-14](#)
- numbers [38-8](#)
- terminal lines, setting on [38-19](#)
- unsupported features [38-7](#)

IPv6

- applying to interfaces [44-7](#)
- configuring [44-3, 44-4](#)
- displaying [44-8](#)
- interactions with other features [44-4](#)
- limitations [44-2, 44-3](#)
- matching criteria [44-3](#)
- named [44-2](#)
- precedence of [44-2](#)
- supported [44-2](#)
- unsupported features [44-3](#)

Layer 4 information in [38-37](#)

logging messages [38-8](#)

MAC extended [38-27, 39-45](#)

matching [38-7, 38-20, 44-3](#)

monitoring [38-41, 44-8](#)

named, IPv4 [38-14](#)

named, IPv6 [44-2](#)

names [44-4](#)

number per QoS class map [39-33](#)

port [38-2, 44-1](#)

precedence of [38-2](#)

QoS [39-7, 39-43](#)

resequencing entries [38-14](#)

router [38-2, 44-1](#)

router ACLs and VLAN map configuration guidelines [38-37](#)

standard IP, configuring for QoS classification [39-43](#)

standard IPv4

- creating [38-9](#)

- matching criteria [38-7](#)

- support for [1-8](#)

- support in hardware [38-21](#)

- time ranges [38-16](#)

- types supported [38-2](#)

- unsupported features, IPv4 [38-7](#)

- unsupported features, IPv6 [44-3](#)

- using router ACLs with VLAN maps [38-36](#)

VLAN maps

- configuration guidelines [38-30](#)

- configuring [38-29](#)

active link [25-4, 25-5, 25-6](#)

active links [25-2](#)

active router [45-1](#)

active traffic monitoring, IP SLAs [46-1](#)

address aliasing [28-2](#)

addresses

- displaying the MAC address table [7-23](#)

dynamic

- accelerated aging [21-8](#)

- changing the aging time [7-14](#)

- default aging [21-8](#)

- defined [7-12](#)

- learning [7-13](#)

- removing [7-15](#)

IPv6 [42-2](#)

MAC, discovering [7-23](#)

multicast

- group address range [49-3](#)

- STP address management [21-8](#)

static

- adding and removing [7-19](#)

- defined [7-12](#)

address resolution [7-23, 41-8](#)

Address Resolution Protocol

- See ARP

adjacency tables, with CEF [41-87](#)

administrative distances

- defined [41-99](#)

- OSPF [41-30](#)

- routing protocol defaults [41-89](#)
- administrative VLAN
 - REP, configuring [24-8](#)
- administrative VLAN, REP [24-8](#)
- advertisements
 - CDP [32-1](#)
 - LLDP [31-1, 31-2](#)
 - RIP [41-18](#)
 - VTP [16-16, 17-3](#)
- age timer, REP [24-8](#)
- aggregatable global unicast addresses [42-3](#)
- aggregate addresses, BGP [41-57](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [39-58](#)
- aggregate policing [1-11](#)
- aging, accelerating [21-8](#)
- aging time
 - accelerated
 - for MSTP [22-23](#)
 - for STP [21-8, 21-21](#)
 - MAC address table [7-14](#)
 - maximum
 - for MSTP [22-23, 22-24](#)
 - for STP [21-21, 21-22](#)
- alarm profiles
 - configuring [3-12](#)
 - creating or modifying [3-11](#)
- alarms
 - displaying [3-13](#)
 - power supply [3-2](#)
 - temperature [3-2](#)
- alarms, RMON [34-3](#)
- allowed-VLAN list [16-18](#)
- application engines, redirecting traffic to [48-1](#)
- area border routers
 - See ABRs
- area routing
 - IS-IS [41-62](#)
 - ISO IGRP [41-62](#)
- ARP
 - configuring [41-9](#)
 - defined [1-5, 7-23, 41-8](#)
 - encapsulation [41-9](#)
 - static cache configuration [41-9](#)
 - table
 - address resolution [7-23](#)
 - managing [7-23](#)
- ASBRs [41-24](#)
- AS-path filters, BGP [41-52](#)
- associating the temperature alarms to a relay [3-9](#)
- asymmetrical links, and IEEE 802.1Q tunneling [20-4](#)
- attaching an alarm profile to a port [3-12](#)
- attributes, RADIUS
 - vendor-proprietary [11-38](#)
 - vendor-specific [11-36](#)
- attribute-value pairs [12-12, 12-15, 12-20](#)
- authentication
 - EIGRP [41-38](#)
 - HSRP [45-10](#)
 - local mode with AAA [11-44](#)
 - open1x [12-29](#)
 - RADIUS
 - key [11-28](#)
 - login [11-30](#)
 - TACACS+
 - defined [11-11](#)
 - key [11-13](#)
 - login [11-14](#)
 - See also port-based authentication
- authentication compatibility with Catalyst 6000 switches [12-8](#)
- authentication failed VLAN
 - See restricted VLAN
- authentication keys, and routing protocols [41-99](#)
- authentication manager
 - CLI commands [12-9](#)

- compatibility with older 802.1x CLI commands [12-9 to ??](#)
- overview [12-7](#)
- authoritative time source, described [7-2](#)
- authorization
 - with RADIUS [11-34](#)
 - with TACACS+ [11-11, 11-16](#)
- authorized ports with IEEE 802.1x [12-10](#)
- autoconfiguration [4-3](#)
- auto enablement [12-30](#)
- automatic discovery
 - considerations
 - beyond a noncandidate device [6-7](#)
 - brand new switches [6-9](#)
 - connectivity [6-4](#)
 - different VLANs [6-6](#)
 - management VLANs [6-7](#)
 - non-CDP-capable devices [6-6](#)
 - noncluster-capable devices [6-6](#)
 - routed ports [6-8](#)
 - in switch clusters [6-4](#)
 - See also CDP
- automatic QoS
 - See QoS
- automatic recovery, clusters [6-10](#)
 - See also HSRP
- auto-MDIX
 - configuring [14-19](#)
 - described [14-19](#)
- autonegotiation
 - duplex mode [1-2](#)
 - interface configuration guidelines [14-16](#)
 - mismatches [36-8](#)
- autonomous system boundary routers
 - See ASBRs
- autonomous systems, in BGP [41-45](#)
- Auto-RP, described [49-6](#)
- autosensing, port speed [1-2](#)
- Auto Smartports macros

- displaying [15-5](#)
- autostate exclude [14-5](#)
- auxiliary VLAN
 - See voice VLAN
- availability, features [1-6](#)

B

- BackboneFast
 - described [23-5](#)
 - disabling [23-14](#)
 - enabling [23-13](#)
- backup interfaces
 - See Flex Links
- backup links [25-2](#)
- backup static routing, configuring [47-11](#)
- banners
 - configuring
 - login [7-12](#)
 - message-of-the-day login [7-11](#)
 - default configuration [7-10](#)
 - when displayed [7-10](#)
- Berkeley r-tools replacement [11-56](#)
- BGP
 - aggregate addresses [41-57](#)
 - aggregate routes, configuring [41-57](#)
 - CIDR [41-57](#)
 - clear commands [41-61](#)
 - community filtering [41-54](#)
 - configuring neighbors [41-55](#)
 - default configuration [41-43](#)
 - described [41-42](#)
 - enabling [41-45](#)
 - monitoring [41-61](#)
 - multipath support [41-49](#)
 - neighbors, types of [41-45](#)
 - path selection [41-49](#)
 - peers, configuring [41-55](#)
 - prefix filtering [41-53](#)

- resetting sessions [41-48](#)
- route dampening [41-60](#)
- route maps [41-51](#)
- route reflectors [41-59](#)
- routing domain confederation [41-58](#)
- routing session with multi-VRF CE [41-81](#)
- show commands [41-61](#)
- supernets [41-57](#)
- support for [1-12](#)
- Version 4 [41-42](#)
- binding cluster group and HSRP group [45-12](#)
- binding database
 - address, DHCP server
 - See DHCP, Cisco IOS server database
 - DHCP snooping
 - See DHCP snooping binding database
- bindings
 - address, Cisco IOS DHCP server [26-7](#)
 - DHCP snooping database [26-7](#)
 - IP source guard [26-16](#)
- binding table, DHCP snooping
 - See DHCP snooping binding database
- blocking packets [29-7](#)
- Boolean expressions in tracked lists [47-4](#)
- booting
 - boot loader, function of [4-2](#)
 - boot process [4-2](#)
 - manually [4-18](#)
 - specific image [4-19](#)
- boot loader
 - accessing [4-19](#)
 - described [4-2](#)
 - environment variables [4-19](#)
 - prompt [4-19](#)
 - trap-door mechanism [4-2](#)
- bootstrap router (BSR), described [49-7](#)
- Border Gateway Protocol
 - See BGP
- BPDU

- error-disabled state [23-2](#)
- filtering [23-3](#)
- RSTP format [22-12](#)
- BPDU filtering
 - described [23-3](#)
 - disabling [23-12](#)
 - enabling [23-12](#)
 - support for [1-7](#)
- BPDU guard
 - described [23-2](#)
 - disabling [23-12](#)
 - enabling [23-11](#)
 - support for [1-7](#)
- bridged packets, ACLs on [38-38](#)
- bridge groups
 - See fallback bridging
- bridge protocol data unit
 - See BPDU
- broadcast flooding [41-16](#)
- broadcast packets
 - directed [41-13](#)
 - flooded [41-13](#)
- broadcast storm-control command [29-4](#)
- broadcast storms [29-1, 41-13](#)

C

- cables, monitoring for unidirectional links [33-1](#)
- candidate switch
 - automatic discovery [6-4](#)
 - defined [6-3](#)
 - requirements [6-3](#)
 - See also command switch, cluster standby group, and member switch
- Catalyst 6000 switches
 - authentication compatibility [12-8](#)
- CA trustpoint
 - configuring [11-53](#)
 - defined [11-50](#)

- CDP
 - and trusted boundary [39-39](#)
 - automatic discovery in switch clusters [6-4](#)
 - configuring [32-2](#)
 - default configuration [32-2](#)
 - defined with LLDP [31-1](#)
 - described [32-1](#)
 - disabling for routing device [32-4](#)
 - enabling and disabling
 - on an interface [32-4](#)
 - on a switch [32-4](#)
 - Layer 2 protocol tunneling [20-7](#)
 - monitoring [32-5](#)
 - overview [32-1](#)
 - support for [1-5](#)
 - transmission timer and holdtime, setting [32-3](#)
 - updates [32-3](#)
- CEF
 - defined [41-86](#)
 - enabling [41-87](#)
 - IPv6 [42-18](#)
- CGMP
 - as IGMP snooping learning method [28-8](#)
 - clearing cached group entries [49-60](#)
 - enabling server support [49-43](#)
 - joining multicast group [28-3](#)
 - overview [49-9](#)
 - server support only [49-9](#)
 - switch support of [1-3](#)
- CIDR [41-57](#)
- CipherSuites [11-52](#)
- Cisco 7960 IP Phone [18-1](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS DHCP server
 - See DHCP, Cisco IOS DHCP server
- Cisco IOS File System
 - See IFS
- Cisco IOS IP SLAs [46-1](#)
- Cisco Secure ACS
 - attribute-value pairs for downloadable ACLs [12-20](#)
 - attribute-value pairs for redirect URL [12-20](#)
- Cisco Secure ACS configuration guide [12-59](#)
- CiscoWorks 2000 [1-4, 36-4](#)
- CISP [12-30](#)
- CIST regional root
 - See MSTP
- CIST root
 - See MSTP
- civic location [31-2](#)
- classless interdomain routing
 - See CIDR
- classless routing [41-6](#)
- class maps for QoS
 - configuring [39-46](#)
 - described [39-7](#)
 - displaying [39-78](#)
- class of service
 - See CoS
- clearing interfaces [14-25](#)
- CLI
 - abbreviating commands [2-4](#)
 - command modes [2-1](#)
 - configuration logging [2-5](#)
 - described [1-4](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystroke editing [2-8](#)
 - wrapped lines [2-9](#)
 - error messages [2-5](#)
 - filtering command output [2-10](#)
 - getting help [2-3](#)
 - history
 - changing the buffer size [2-6](#)

- described [2-6](#)
- disabling [2-7](#)
- recalling commands [2-6](#)
- managing clusters [6-14](#)
- no and default forms of commands [2-4](#)
- Client Information Signalling Protocol
 - See CISP
- client mode, VTP [17-3](#)
- client processes, tracking [47-1](#)
- CLNS
 - See ISO CLNS
- clock
 - See system clock
- clusters, switch
 - accessing [6-13](#)
 - automatic discovery [6-4](#)
 - automatic recovery [6-10](#)
 - benefits [1-2](#)
 - compatibility [6-4](#)
 - described [6-1](#)
 - LRE profile considerations [6-14](#)
 - managing
 - through CLI [6-14](#)
 - through SNMP [6-15](#)
 - planning [6-4](#)
 - planning considerations
 - automatic discovery [6-4](#)
 - automatic recovery [6-10](#)
 - CLI [6-14](#)
 - host names [6-13](#)
 - IP addresses [6-13](#)
 - LRE profiles [6-14](#)
 - passwords [6-13](#)
 - RADIUS [6-14](#)
 - SNMP [6-14, 6-15](#)
 - TACACS+ [6-14](#)
 - See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - and HSRP group [45-12](#)
 - automatic recovery [6-12](#)
 - considerations [6-11](#)
 - defined [6-2](#)
 - requirements [6-3](#)
 - virtual IP address [6-11](#)
 - See also HSRP
- CNS [1-4](#)
 - Configuration Engine
 - configID, deviceID, hostname [5-3](#)
 - configuration service [5-2](#)
 - described [5-1](#)
 - event service [5-3](#)
 - embedded agents
 - described [5-5](#)
 - enabling automated configuration [5-6](#)
 - enabling configuration agent [5-9](#)
 - enabling event agent [5-7](#)
 - management functions [1-4](#)
- CoA Request Commands [11-24](#)
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-4](#)
 - no and default [2-4](#)
- commands, setting privilege levels [11-8](#)
- command switch
 - accessing [6-11](#)
 - active (AC) [6-10](#)
 - configuration conflicts [36-7](#)
 - defined [6-1](#)
 - passive (PC) [6-10](#)
 - password privilege levels [6-15](#)
 - priority [6-10](#)
 - recovery
 - from command-switch failure [6-10, 36-4](#)
 - from lost member connectivity [36-7](#)

- redundant [6-10](#)
- replacing
 - with another switch [36-6](#)
 - with cluster member [36-4](#)
- requirements [6-3](#)
- standby (SC) [6-10](#)
- See also candidate switch, cluster standby group, member switch, and standby command switch
- community list, BGP [41-54](#)
- community ports [19-2](#)
- community strings
 - configuring [6-14, 36-8](#)
 - for cluster switches [36-4](#)
 - in clusters [6-14](#)
 - overview [36-4](#)
 - SNMP [6-14](#)
- community VLANs [19-2, 19-3](#)
- compatibility, feature [29-12](#)
- config.text [4-17](#)
- configurable leave timer, IGMP [28-6](#)
- configuration, initial
 - defaults [1-14](#)
 - Express Setup [1-2](#)
- configuration changes, logging [35-10](#)
- configuration conflicts, recovering from lost member connectivity [36-7](#)
- configuration examples, network [1-17](#)
- configuration files
 - archiving [A-18](#)
 - clearing the startup configuration [A-18](#)
 - creating using a text editor [A-9](#)
 - default name [4-17](#)
 - deleting a stored configuration [A-18](#)
 - described [A-8](#)
 - downloading
 - automatically [4-17](#)
 - preparing [A-10, A-12, A-15](#)
 - reasons for [A-8](#)
 - using FTP [A-13](#)
 - using RCP [A-16](#)
 - using TFTP [A-10](#)
 - guidelines for creating and using [A-8](#)
 - guidelines for replacing and rolling back [A-19](#)
 - invalid combinations when copying [A-5](#)
 - limiting TFTP server access [36-16](#)
 - obtaining with DHCP [4-9](#)
 - password recovery disable considerations [11-5](#)
 - replacing a running configuration [A-18, A-19](#)
 - rolling back a running configuration [A-18, A-19](#)
 - specifying the filename [4-17](#)
 - system contact and location information [36-16](#)
 - types and location [A-9](#)
 - uploading
 - preparing [A-10, A-12, A-15](#)
 - reasons for [A-8](#)
 - using FTP [A-14](#)
 - using RCP [A-17](#)
 - using TFTP [A-11](#)
- configuration guidelines
 - REP [24-7](#)
- configuration guidelines, multi-VRF CE [41-74](#)
- configuration logger [35-10](#)
- configuration logging [2-5](#)
- configuration replacement [A-18](#)
- configuration rollback [A-18](#)
- configuration settings, saving [4-15](#)
- configure terminal command [14-9](#)
- configuring 802.1x user distribution [12-55](#)
- configuring port-based authentication violation modes [12-38 to 12-39](#)
- configuring small-frame arrival rate [29-5](#)
- config-vlan mode [2-2](#)
- conflicts, configuration [36-7](#)
- connections, secure remote [11-46](#)
- connectivity problems [36-9, 36-11, 36-12](#)
- consistency checks in VTP Version 2 [17-4](#)
- console port, connecting to [2-10](#)
- content-routing technology

- See WCCP
- control protocol, IP SLAs [46-4](#)
- convergence
 - REP [24-4](#)
- corrupted software, recovery steps with Xmodem [36-2](#)
- CoS
 - override priority [18-6](#)
 - trust priority [18-6](#)
- CoS input queue threshold map for QoS [39-16](#)
- CoS output queue threshold map for QoS [39-18](#)
- CoS-to-DSCP map for QoS [39-61](#)
- counters, clearing interface [14-25](#)
- CPU utilization, troubleshooting [36-20](#)
- crashinfo file [36-19](#)
- critical authentication, IEEE 802.1x [12-51](#)
- critical VLAN [12-23](#)
- cryptographic software image
 - Kerberos [11-40](#)
 - SSH [11-45](#)
 - SSL [11-50](#)
- customer edge devices [41-72](#)
- customizable web pages, web-based authentication [13-6](#)

D

- DACL
 - See downloadable ACL
- daylight saving time [7-6](#)
- debugging
 - enabling all system diagnostics [36-16](#)
 - enabling for a specific feature [36-16](#)
 - redirecting error message output [36-16](#)
 - using commands [36-15](#)
- default commands [2-4](#)
- default configuration
 - 802.1x [12-33](#)
 - auto-QoS [39-20](#)
 - banners [7-10](#)
 - BGP [41-43](#)
 - booting [4-17](#)
 - CDP [32-2](#)
 - DHCP [26-9](#)
 - DHCP option 82 [26-9](#)
 - DHCP snooping [26-9](#)
 - DHCP snooping binding database [26-9](#)
 - DNS [7-9](#)
 - dynamic ARP inspection [27-5](#)
 - EIGRP [41-34](#)
 - EtherChannel [40-10](#)
 - Ethernet interfaces [14-13](#)
 - fallback bridging [51-3](#)
 - Flex Links [25-7, 25-8](#)
 - HSRP [45-5](#)
 - IEEE 802.1Q tunneling [20-4](#)
 - IGMP [49-38](#)
 - IGMP filtering [28-24](#)
 - IGMP snooping [28-7, 43-5, 43-6](#)
 - IGMP throttling [28-24](#)
 - initial switch information [4-3](#)
 - IP addressing, IP routing [41-4](#)
 - IP multicast routing [49-10](#)
 - IP SLAs [46-6](#)
 - IP source guard [26-18](#)
 - IPv6 [42-10](#)
 - IS-IS [41-63](#)
 - Layer 2 interfaces [14-13](#)
 - Layer 2 protocol tunneling [20-11](#)
 - LLDP [31-4](#)
 - MAC address table [7-14](#)
 - MAC address-table move update [25-8](#)
 - MSDP [50-4](#)
 - MSTP [22-14](#)
 - multi-VRF CE [41-74](#)
 - MVR [28-19](#)
 - optional spanning-tree configuration [23-9](#)
 - OSPF [41-25](#)
 - password and privilege level [11-3](#)
 - PIM [49-10](#)

- private VLANs [19-6](#)
- PROFINET [9-4](#)
- PTP [8-2](#)
- RADIUS [11-27](#)
- REP [24-7](#)
- RIP [41-19](#)
- RMON [34-3](#)
- RSPAN [30-9](#)
- SDM template [10-3](#)
- SNMP [36-6](#)
- SPAN [30-9](#)
- SSL [11-52](#)
- standard QoS [39-30](#)
- STP [21-11](#)
- system message logging [35-3](#)
- system name and prompt [7-8](#)
- TACACS+ [11-13](#)
- UDLD [33-4](#)
- VLAN, Layer 2 Ethernet interfaces [16-16](#)
- VLANs [16-7](#)
- VMPS [16-26](#)
- voice VLAN [18-3](#)
- VTP [17-7](#)
- WCCP [48-5](#)
- default gateway [4-15, 41-11](#)
- default networks [41-89](#)
- default router preference
 - See [DRP](#)
- default routes [41-89](#)
- default routing [41-2](#)
- default web-based authentication configuration
 - 802.1X [13-9](#)
- deleting VLANs [16-9](#)
- denial-of-service attack [29-1](#)
- description command [14-20](#)
- designing your network, examples [1-17](#)
- destination addresses
 - in IPv4 ACLs [38-11](#)
 - in IPv6 ACLs [44-5](#)
- destination-IP address-based forwarding, EtherChannel [40-8](#)
- destination-MAC address forwarding, EtherChannel [40-8](#)
- detecting indirect link failures, STP [23-5](#)
- device [A-22](#)
- device discovery protocol [31-1, 32-1](#)
- device manager
 - benefits [1-2](#)
 - described [1-2, 1-4](#)
 - in-band management [1-5](#)
 - upgrading a switch [A-22](#)
- DHCP
 - Cisco IOS server database
 - configuring [26-14](#)
 - default configuration [26-9](#)
 - described [26-7](#)
 - DHCP for IPv6
 - See [DHCPv6](#)
 - enabling
 - relay agent [26-11](#)
- DHCP-based autoconfiguration
 - client request message exchange [4-4](#)
 - configuring
 - client side [4-4](#)
 - DNS [4-8](#)
 - relay device [4-8](#)
 - server side [4-6](#)
 - TFTP server [4-7](#)
 - example [4-9](#)
 - lease options
 - for IP address information [4-6](#)
 - for receiving the configuration file [4-7](#)
 - overview [4-3](#)
 - relationship to BOOTP [4-4](#)
 - relay support [1-4, 1-13](#)
 - support for [1-4](#)
- DHCP-based autoconfiguration and image update
 - configuring [4-11 to 4-14](#)
 - understanding [4-5 to 4-6](#)

DHCP binding database

See DHCP snooping binding database

DHCP binding table

See DHCP snooping binding database

DHCP object tracking, configuring primary interface 47-10

DHCP option 82

- circuit ID suboption 26-5
- configuration guidelines 26-9
- default configuration 26-9
- displaying 26-16
- forwarding address, specifying 26-11
- helper address 26-11
- overview 26-4
- packet format, suboption
 - circuit ID 26-5
 - remote ID 26-5
- remote ID suboption 26-5

DHCP server port-based address allocation

- configuration guidelines 26-27
- default configuration 26-27
- described 26-26
- displaying 26-29
- enabling 26-27
- reserved addresses 26-27

DHCP server port-based address assignment

- support for 1-5

DHCP snooping

- accepting untrusted packets form edge switch 26-3, 26-13
- and private VLANs 26-14
- binding database
 - See DHCP snooping binding database
- configuration guidelines 26-9
- default configuration 26-9
- displaying binding tables 26-16
- message exchange process 26-4
- option 82 data insertion 26-4
- trusted interface 26-2

untrusted interface 26-2

untrusted messages 26-2

DHCP snooping binding database

- adding bindings 26-15
- binding file
 - format 26-8
 - location 26-7
- bindings 26-7
- clearing agent statistics 26-15
- configuration guidelines 26-10
- configuring 26-15
- default configuration 26-9
- deleting
 - binding file 26-15
 - bindings 26-15
 - database agent 26-15
- described 26-7
- displaying 26-16
 - binding entries 26-16
 - status and statistics 26-16
- enabling 26-15
- entry 26-7
- renewing database 26-15
- resetting
 - delay value 26-15
 - timeout value 26-15

DHCP snooping binding table

See DHCP snooping binding database

DHCPv6

- configuration guidelines 42-15
- default configuration 42-15
- described 42-6
- enabling client function 42-17
- enabling DHCPv6 server function 42-15
- support for 1-13

Differentiated Services architecture, QoS 39-2

Differentiated Services Code Point 39-2

Diffusing Update Algorithm (DUAL) 41-33

directed unicast requests 1-5

directories

- changing [A-4](#)
- creating and removing [A-4](#)
- displaying the working [A-4](#)

discovery, clusters

- See automatic discovery

displaying switch alarms [3-13](#)

Distance Vector Multicast Routing Protocol

- See DVMRP

distance-vector protocols [41-3](#)distribute-list command [41-98](#)

DNS

- and DHCP-based autoconfiguration [4-8](#)
- default configuration [7-9](#)
- displaying the configuration [7-10](#)
- in IPv6 [42-3](#)
- overview [7-8](#)
- setting up [7-9](#)
- support for [1-4](#)

DNS-based SSM mapping [49-18, 49-19](#)

domain names

- DNS [7-8](#)
- VTP [17-8](#)

Domain Name System

- See DNS

domains, ISO IGRP routing [41-62](#)dot1q-tunnel switchport mode [16-15](#)

double-tagged packets

- IEEE 802.1Q tunneling [20-2](#)
- Layer 2 protocol tunneling [20-10](#)

downloadable ACL [12-18, 12-20, 12-59](#)

downloading

- configuration files
 - preparing [A-10, A-12, A-15](#)
 - reasons for [A-8](#)
 - using FTP [A-13](#)
 - using RCP [A-16](#)
 - using TFTP [A-10](#)
- image files

deleting old image [A-25](#)preparing [A-24, A-27, A-31](#)reasons for [A-22](#)using FTP [A-28](#)using HTTP [A-22](#)using RCP [A-32](#)using TFTP [A-24](#)using the device manager or Network Assistant [A-22](#)drop threshold for Layer 2 protocol packets [20-11](#)

DRP

configuring [42-13](#)described [42-4](#)IPv6 [42-4](#)support for [1-13](#)DSCP [1-11, 39-2](#)DSCP input queue threshold map for QoS [39-16](#)DSCP output queue threshold map for QoS [39-18](#)DSCP-to-CoS map for QoS [39-64](#)DSCP-to-DSCP-mutation map for QoS [39-65](#)DSCP transparency [39-40](#)DTP [1-7, 16-15](#)dual-action detection [40-5](#)DUAL finite state machine, EIGRP [41-34](#)dual IPv4 and IPv6 templates [10-2, 42-5](#)

dual protocol stacks

- IPv4 and IPv6 [42-5](#)
- SDM templates supporting [42-6](#)

dual-purpose uplinks

- defined [14-6](#)
- LEDs [14-6](#)
- link selection [14-6, 14-14](#)
- setting the type [14-14](#)

DVMRP

autosummarization

- configuring a summary address [49-57](#)
- disabling [49-59](#)

connecting PIM domain to DVMRP router [49-50](#)enabling unicast routing [49-53](#)

- interoperability
 - with Cisco devices [49-48](#)
 - with Cisco IOS software [49-8](#)
- mrinfo requests, responding to [49-52](#)
- neighbors
 - advertising the default route to [49-51](#)
 - discovery with Probe messages [49-48](#)
 - displaying information [49-52](#)
 - prevent peering with nonpruning [49-55](#)
 - rejecting nonpruning [49-54](#)
- overview [49-8](#)
- routes
 - adding a metric offset [49-59](#)
 - advertising all [49-59](#)
 - advertising the default route to neighbors [49-51](#)
 - caching DVMRP routes learned in report messages [49-53](#)
 - changing the threshold for syslog messages [49-56](#)
 - deleting [49-60](#)
 - displaying [49-61](#)
 - favoring one over another [49-59](#)
 - limiting the number injected into MBONE [49-56](#)
 - limiting unicast route advertisements [49-48](#)
- routing table [49-9](#)
- source distribution tree, building [49-9](#)
- support for [1-13](#)
- tunnels
 - configuring [49-50](#)
 - displaying neighbor information [49-52](#)
- dynamic access ports
 - characteristics [16-3](#)
 - configuring [16-27](#)
 - defined [14-3](#)
- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [27-1](#)
 - ARP requests, described [27-1](#)
 - ARP spoofing attack [27-1](#)
- clearing
 - log buffer [27-15](#)
 - statistics [27-15](#)
- configuration guidelines [27-5](#)
- configuring
 - ACLs for non-DHCP environments [27-8](#)
 - in DHCP environments [27-7](#)
 - log buffer [27-12](#)
 - rate limit for incoming ARP packets [27-4, 27-10](#)
- default configuration [27-5](#)
- denial-of-service attacks, preventing [27-10](#)
- described [27-1](#)
- DHCP snooping binding database [27-2](#)
- displaying
 - ARP ACLs [27-14](#)
 - configuration and operating state [27-14](#)
 - log buffer [27-15](#)
 - statistics [27-15](#)
 - trust state and rate limit [27-14](#)
- error-disabled state for exceeding rate limit [27-4](#)
- function of [27-2](#)
- interface trust states [27-3](#)
- log buffer
 - clearing [27-15](#)
 - configuring [27-12](#)
 - displaying [27-15](#)
- logging of dropped packets, described [27-4](#)
- man-in-the middle attack, described [27-2](#)
- network security issues and interface trust states [27-3](#)
- priority of ARP ACLs and DHCP snooping entries [27-4](#)
- rate limiting of ARP packets
 - configuring [27-10](#)
 - described [27-4](#)
 - error-disabled state [27-4](#)
- statistics
 - clearing [27-15](#)
 - displaying [27-15](#)
- validation checks, performing [27-11](#)

dynamic auto trunking mode [16-15](#)
dynamic desirable trunking mode [16-15](#)
Dynamic Host Configuration Protocol
 See DHCP-based autoconfiguration
dynamic port VLAN membership
 described [16-25](#)
 reconfirming [16-28](#)
 troubleshooting [16-30](#)
 types of connections [16-27](#)
dynamic routing [41-3](#)
 ISO CLNS [41-62](#)
Dynamic Trunking Protocol
 See DTP

E

EBGP [41-41](#)
editing features
 enabling and disabling [2-7](#)
 keystrokes used [2-8](#)
 wrapped lines [2-9](#)
EIGRP
 authentication [41-38](#)
 components [41-34](#)
 configuring [41-36](#)
 default configuration [41-34](#)
 definition [41-33](#)
 interface parameters, configuring [41-37](#)
 monitoring [41-40](#)
 stub routing [41-39](#)
ELIN location [31-2](#)
embedded event manager
 actions [37-4](#)
 configuring [37-1, 37-5](#)
 displaying information [37-6](#)
 environmental variables [37-4](#)
 event detectors [37-2](#)
 policies [37-4](#)
 registering and defining an applet [37-5](#)
 registering and defining a TCL script [37-6](#)
 understanding [37-1](#)
enable password [11-4](#)
enable secret password [11-4](#)
enabling SNMP traps [3-13](#)
encryption, CipherSuite [11-52](#)
encryption for passwords [11-4](#)
Enhanced IGRP
 See EIGRP
enhanced object tracking
 backup static routing [47-11](#)
 commands [47-1](#)
 defined [47-1](#)
 DHCP primary interface [47-10](#)
 HSRP [47-7](#)
 IP routing state [47-2](#)
 IP SLAs [47-9](#)
 line-protocol state [47-2](#)
 network monitoring with IP SLAs [47-11](#)
 routing policy, configuring [47-11](#)
 static route primary interface [47-10](#)
 tracked lists [47-3](#)
enhanced object tracking static routing [47-10](#)
environmental variables, embedded event manager [37-4](#)
environment variables, function of [4-20](#)
equal-cost routing [1-12, 41-88](#)
error-disabled state, BPDU [23-2](#)
error messages during command entry [2-5](#)
EtherChannel
 automatic creation of [40-4, 40-6](#)
 channel groups
 binding physical and logical interfaces [40-3](#)
 numbering of [40-3](#)
 configuration guidelines [40-10](#)
 configuring
 Layer 2 interfaces [40-11](#)
 Layer 3 physical interfaces [40-14](#)
 Layer 3 port-channel logical interfaces [40-13](#)
 default configuration [40-10](#)

- described [40-2](#)
 - displaying status [40-20](#)
 - forwarding methods [40-7](#), [40-16](#)
 - IEEE 802.3ad, described [40-6](#)
 - interaction
 - with STP [40-10](#)
 - with VLANs [40-11](#)
 - LACP
 - described [40-6](#)
 - displaying status [40-20](#)
 - hot-standby ports [40-18](#)
 - interaction with other features [40-7](#)
 - modes [40-6](#)
 - port priority [40-19](#)
 - system priority [40-19](#)
 - Layer 3 interface [41-3](#)
 - load balancing [40-7](#), [40-16](#)
 - logical interfaces, described [40-3](#)
 - PAgP
 - aggregate-port learners [40-16](#)
 - compatibility with Catalyst 1900 [40-17](#)
 - described [40-4](#)
 - displaying status [40-20](#)
 - interaction with other features [40-6](#)
 - interaction with virtual switches [40-5](#)
 - learn method and priority configuration [40-16](#)
 - modes [40-5](#)
 - support for [1-3](#)
 - with dual-action detection [40-5](#)
 - port-channel interfaces
 - described [40-3](#)
 - port groups [14-6](#)
 - support for [1-3](#)
- EtherChannel guard
- described [23-7](#)
 - disabling [23-14](#)
 - enabling [23-14](#)
- Ethernet VLANs
- adding [16-8](#)
 - defaults and ranges [16-7](#)
 - modifying [16-8](#)
- EUI [42-3](#)
- event detectors, embedded event manager [37-2](#)
- events, RMON [34-3](#)
- examples
 - network configuration [1-17](#)
- expedite queue for QoS [39-76](#)
- Express Setup [1-2](#)
- See also getting started guide
- extended crashinfo file [36-19](#)
- extended-range VLANs
 - configuration guidelines [16-11](#)
 - configuring [16-10](#)
 - creating [16-12](#)
 - creating with an internal VLAN ID [16-13](#)
 - defined [16-1](#)
- extended system ID
 - MSTP [22-17](#)
 - STP [21-4](#), [21-14](#)
- extended universal identifier
 - See EUI
- Extensible Authentication Protocol over LAN [12-1](#)
- external BGP
 - See EBGp
- external neighbors, BGP [41-45](#)

F

- fa0 interface [1-5](#)
- fallback bridging
 - and protected ports [51-3](#)
- bridge groups
 - creating [51-3](#)
 - described [51-1](#)
 - displaying [51-10](#)
 - function of [51-2](#)
 - number supported [51-4](#)
 - removing [51-4](#)

- bridge table
 - clearing [51-10](#)
 - displaying [51-10](#)
- configuration guidelines [51-3](#)
- connecting interfaces with [14-7](#)
- default configuration [51-3](#)
- described [51-1](#)
- frame forwarding
 - flooding packets [51-2](#)
 - forwarding packets [51-2](#)
- overview [51-1](#)
- protocol, unsupported [51-3](#)
- STP
 - disabling on an interface [51-9](#)
 - forward-delay interval [51-8](#)
 - hello BPDU interval [51-7](#)
 - interface priority [51-6](#)
 - maximum-idle interval [51-8](#)
 - path cost [51-6](#)
 - VLAN-bridge spanning-tree priority [51-5](#)
 - VLAN-bridge STP [51-2](#)
- support for [1-12](#)
- SVIs and routed ports [51-1](#)
- unsupported protocols [51-3](#)
- VLAN-bridge STP [21-10](#)
- Fast Convergence [25-3](#)
- FCS bit error rate alarm
 - configuring [3-10](#)
 - defined [3-3](#)
- FCS error hysteresis threshold [3-2](#)
- features, incompatible [29-12](#)
- FIB [41-87](#)
- fiber-optic, detecting unidirectional links [33-1](#)
- files
 - basic crashinfo
 - description [36-19](#)
 - location [36-19](#)
 - copying [A-5](#)
 - crashinfo, description [36-19](#)
 - deleting [A-5](#)
 - displaying the contents of [A-8](#)
 - extended crashinfo
 - description [36-20](#)
 - location [36-20](#)
 - tar
 - creating [A-6](#)
 - displaying the contents of [A-6](#)
 - extracting [A-7](#)
 - image file format [A-22](#)
- file system
 - displaying available file systems [A-2](#)
 - displaying file information [A-3](#)
 - local file system names [A-1](#)
 - network file system names [A-5](#)
 - setting the default [A-2](#)
- filtering
 - in a VLAN [38-29](#)
 - IPv6 traffic [44-3, 44-7](#)
 - non-IP traffic [38-27](#)
 - show and more command output [2-10](#)
- filtering show and more command output [2-10](#)
- filters, IP
 - See ACLs, IP
- flash device, number of [A-1](#)
- flexible authentication ordering
 - configuring [12-62](#)
 - overview [12-28](#)
- Flex Link Multicast Fast Convergence [25-3](#)
- Flex Links
 - configuration guidelines [25-8](#)
 - configuring [25-8, 25-9](#)
 - configuring preferred VLAN [25-11](#)
 - configuring VLAN load balancing [25-10](#)
 - default configuration [25-7](#)
 - description [25-1](#)
 - link load balancing [25-2](#)
 - monitoring [25-14](#)
 - VLANs [25-2](#)

flooded traffic, blocking [29-8](#)

flow-based packet classification [1-11](#)

flowcharts

- QoS classification [39-6](#)
- QoS egress queueing and scheduling [39-17](#)
- QoS ingress queueing and scheduling [39-15](#)
- QoS policing and marking [39-10](#)

flowcontrol

- configuring [14-18](#)
- described [14-18](#)

forward-delay time

- MSTP [22-23](#)
- STP [21-21](#)

Forwarding Information Base

- See FIB

forwarding nonroutable protocols [51-1](#)

FTP

- configuration files
 - downloading [A-13](#)
 - overview [A-12](#)
 - preparing the server [A-12](#)
 - uploading [A-14](#)
- image files
 - deleting old image [A-29](#)
 - downloading [A-28](#)
 - preparing the server [A-27](#)
 - uploading [A-29](#)

G

general query [25-5](#)

Generating IGMP Reports [25-3](#)

get-bulk-request operation [36-3](#)

get-next-request operation [36-3, 36-4](#)

get-request operation [36-3, 36-4](#)

get-response operation [36-3](#)

global configuration mode [2-2](#)

global leave, IGMP [28-13](#)

global status monitoring alarms [3-2](#)

guest VLAN and 802.1x [12-21](#)

GUIs

See device manager and Network Assistant

H

hardware limitations and Layer 3 interfaces [14-21](#)

hello time

- MSTP [22-22](#)
- STP [21-20](#)

help, for the command line [2-3](#)

hierarchical policy maps [39-8](#)

- configuration guidelines [39-33](#)
- configuring [39-52](#)
- described [39-11](#)

history

- changing the buffer size [2-6](#)
- described [2-6](#)
- disabling [2-7](#)
- recalling commands [2-6](#)

history table, level and number of syslog messages [35-10](#)

host names, in clusters [6-13](#)

host ports

- configuring [19-11](#)
- kinds of [19-2](#)

hosts, limit on dynamic ports [16-30](#)

Hot Standby Router Protocol

- See HSRP

HP OpenView [1-4](#)

HSRP

- authentication string [45-10](#)
- automatic cluster recovery [6-12](#)
- binding to cluster group [45-12](#)
- cluster standby group considerations [6-11](#)
- command-switch redundancy [1-6](#)
- configuring [45-4](#)
- default configuration [45-5](#)
- definition [45-1](#)
- guidelines [45-6](#)

- monitoring [45-13](#)
- object tracking [47-7](#)
- overview [45-1](#)
- priority [45-8](#)
- routing redundancy [1-12](#)
- support for ICMP redirect messages [45-12](#)
- timers [45-11](#)
- tracking [45-8](#)
- See also clusters, cluster standby group, and standby command switch

HSRP for IPv6

- configuring [42-24](#)
- guidelines [42-23](#)

HTTP over SSL

- see HTTPS

HTTPS [11-50](#)

- configuring [11-54](#)
- self-signed certificate [11-51](#)

HTTP secure server [11-50](#)

IBPG [41-41](#)

ICMP

- IPv6 [42-4](#)
- redirect messages [41-11](#)
- support for [1-12](#)
- time-exceeded messages [36-13](#)
- traceroute and [36-13](#)
- unreachable messages [38-20](#)
- unreachable messages and IPv6 [44-4](#)
- unreachables and ACLs [38-21](#)

ICMP Echo operation

- configuring [46-12](#)
- IP SLAs [46-11](#)

ICMP ping

- executing [36-10](#)
- overview [36-10](#)

ICMP Router Discovery Protocol

- See IRDP

ICMPv6 [42-4](#)

IDS appliances

- and ingress RSPAN [30-19](#)
- and ingress SPAN [30-13](#)

IEEE 802.1D

- See STP

IEEE 802.1p [18-1](#)

IEEE 802.1Q

- and trunk ports [14-3](#)
- configuration limitations [16-16](#)
- encapsulation [16-14](#)
- native VLAN for untagged traffic [16-20](#)
- tunneling
 - compatibility with other features [20-5](#)
 - defaults [20-4](#)
 - described [20-1](#)
- tunnel ports with other features [20-6](#)

IEEE 802.1s

- See MSTP

IEEE 802.1w

- See RSTP

IEEE 802.1x

- See port-based authentication

IEEE 802.3ad

- See EtherChannel

IEEE 802.3x flow control [14-18](#)

ifIndex values, SNMP [36-5](#)

IFS [1-5](#)

IGMP

- configurable leave timer
 - described [28-6](#)
 - enabling [28-11](#)
- configuring the switch
 - as a member of a group [49-38](#)
 - statically connected member [49-42](#)
- controlling access to groups [49-39](#)
- default configuration [49-38](#)
- deleting cache entries [49-61](#)

- displaying groups [49-61](#)
- fast switching [49-42](#)
- flooded multicast traffic
 - controlling the length of time [28-12](#)
 - disabling on an interface [28-13](#)
 - global leave [28-13](#)
 - query solicitation [28-13](#)
 - recovering from flood mode [28-13](#)
- host-query interval, modifying [49-40](#)
- joining multicast group [28-3](#)
- join messages [28-3](#)
- leave processing, enabling [28-10, 43-8](#)
- leaving multicast group [28-5](#)
- multicast reachability [49-38](#)
- overview [49-2](#)
- queries [28-4](#)
- report suppression
 - described [28-6](#)
 - disabling [28-15, 43-10](#)
- supported versions [28-3](#)
- support for [1-3](#)
- Version 1
 - changing to Version 2 [49-40](#)
 - described [49-3](#)
- Version 2
 - changing to Version 1 [49-40](#)
 - described [49-3](#)
 - maximum query response time value [49-42](#)
 - pruning groups [49-42](#)
 - query timeout value [49-41](#)
- IGMP filtering
 - configuring [28-24](#)
 - default configuration [28-24](#)
 - described [28-23](#)
 - monitoring [28-28](#)
 - support for [1-3](#)
- IGMP groups
 - configuring filtering [28-27](#)
 - setting the maximum number [28-26](#)
- IGMP helper [1-3, 49-6](#)
- IGMP Immediate Leave
 - configuration guidelines [28-11](#)
 - described [28-5](#)
 - enabling [28-10](#)
- IGMP profile
 - applying [28-26](#)
 - configuration mode [28-24](#)
 - configuring [28-25](#)
- IGMP snooping
 - and address aliasing [28-2](#)
 - configuring [28-6](#)
 - default configuration [28-7, 43-5, 43-6](#)
 - definition [28-2](#)
 - enabling and disabling [28-7, 43-6](#)
 - global configuration [28-7](#)
 - Immediate Leave [28-5](#)
 - method [28-8](#)
 - monitoring [28-15, 43-11](#)
 - querier
 - configuration guidelines [28-14](#)
 - configuring [28-14](#)
 - supported versions [28-3](#)
 - support for [1-3](#)
 - VLAN configuration [28-8](#)
- IGMP throttling
 - configuring [28-27](#)
 - default configuration [28-24](#)
 - described [28-24](#)
 - displaying action [28-28](#)
- IGP [41-24](#)
- Immediate Leave, IGMP [28-5](#)
 - enabling [43-8](#)
- inaccessible authentication bypass [12-23](#)
 - support for multiauth ports [12-23](#)
- initial configuration
 - defaults [1-14](#)
 - Express Setup [1-2](#)
- interface

- range macros [14-11](#)
- interface command [14-8 to 14-9](#)
- interface configuration
 - REP [24-9](#)
- interface configuration mode [2-3](#)
- interfaces
 - auto-MDIX, configuring [14-19](#)
 - configuration guidelines
 - duplex and speed [14-16](#)
 - configuring
 - procedure [14-9](#)
 - counters, clearing [14-25](#)
 - default configuration [14-13](#)
 - described [14-20](#)
 - descriptive name, adding [14-20](#)
 - displaying information about [14-24](#)
 - flow control [14-18](#)
 - management [1-4](#)
 - monitoring [14-24](#)
 - naming [14-20](#)
 - physical, identifying [14-8](#)
 - range of [14-9](#)
 - restarting [14-26](#)
 - shutting down [14-26](#)
 - speed and duplex, configuring [14-17](#)
 - status [14-24](#)
 - supported [14-7](#)
 - types of [14-1](#)
- interfaces range macro command [14-11](#)
- interface types [14-8](#)
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP [41-45](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- inter-VLAN routing [1-12, 41-2](#)
- Intrusion Detection System
 - See IDS appliances
- inventory management TLV [31-2, 31-6](#)
- IP ACLs
 - for QoS classification [39-7](#)
 - implicit deny [38-9, 38-14](#)
 - implicit masks [38-9](#)
 - named [38-14](#)
 - undefined [38-21](#)
- IP addresses
 - 128-bit [42-2](#)
 - candidate or member [6-3, 6-13](#)
 - classes of [41-5](#)
 - cluster access [6-2](#)
 - command switch [6-3, 6-11, 6-13](#)
 - default configuration [41-4](#)
 - discovering [7-23](#)
 - for IP routing [41-4](#)
 - IPv6 [42-2](#)
 - MAC address association [41-8](#)
 - monitoring [41-17](#)
 - redundant clusters [6-11](#)
 - standby command switch [6-11, 6-13](#)
 - See also IP information
- IP broadcast address [41-15](#)
- ip cef distributed command [41-87](#)
- IP directed broadcasts [41-13](#)
- ip igmp profile command [28-24](#)
- IP information
 - assigned
 - manually [4-14](#)
 - through DHCP-based autoconfiguration [4-3](#)
 - default configuration [4-3](#)
- IP multicast routing
 - addresses
 - all-hosts [49-3](#)

- all-multicast-routers [49-3](#)
- host group address range [49-3](#)
- administratively-scoped boundaries, described [49-45](#)
- and IGMP snooping [28-2](#)
- Auto-RP
 - adding to an existing sparse-mode cloud [49-25](#)
 - benefits of [49-25](#)
 - clearing the cache [49-61](#)
 - configuration guidelines [49-11](#)
 - filtering incoming RP announcement messages [49-28](#)
 - overview [49-6](#)
 - preventing candidate RP spoofing [49-28](#)
 - preventing join messages to false RPs [49-27](#)
 - setting up in a new internetwork [49-25](#)
 - using with BSR [49-33](#)
- bootstrap router
 - configuration guidelines [49-11](#)
 - configuring candidate BSRs [49-31](#)
 - configuring candidate RPs [49-32](#)
 - defining the IP multicast boundary [49-30](#)
 - defining the PIM domain border [49-29](#)
 - overview [49-7](#)
 - using with Auto-RP [49-33](#)
- Cisco implementation [49-1](#)
- configuring
 - basic multicast routing [49-11](#)
 - IP multicast boundary [49-45](#)
- default configuration [49-10](#)
- enabling
 - multicast forwarding [49-12](#)
 - PIM mode [49-12](#)
- group-to-RP mappings
 - Auto-RP [49-6](#)
 - BSR [49-7](#)
- MBONE
 - deleting sdr cache entries [49-61](#)
 - described [49-44](#)
 - displaying sdr cache [49-62](#)
 - enabling sdr listener support [49-45](#)
 - limiting DVMRP routes advertised [49-56](#)
 - limiting sdr cache entry lifetime [49-45](#)
 - SAP packets for conference session announcement [49-44](#)
 - Session Directory (sdr) tool, described [49-44](#)
 - monitoring
 - packet rate loss [49-62](#)
 - peering devices [49-62](#)
 - tracing a path [49-62](#)
 - multicast forwarding, described [49-7](#)
 - PIMv1 and PIMv2 interoperability [49-10](#)
 - protocol interaction [49-2](#)
 - reverse path check (RPF) [49-7](#)
 - routing table
 - deleting [49-61](#)
 - displaying [49-61](#)
 - RP
 - assigning manually [49-23](#)
 - configuring Auto-RP [49-25](#)
 - configuring PIMv2 BSR [49-29](#)
 - monitoring mapping information [49-33](#)
 - using Auto-RP and BSR [49-33](#)
 - statistics, displaying system and network [49-61](#)
 - See also CGMP
 - See also DVMRP
 - See also IGMP
 - See also PIM
- IP phones
 - and QoS [18-1](#)
 - automatic classification and queueing [39-20](#)
 - configuring [18-4](#)
 - ensuring port security with QoS [39-38](#)
 - trusted boundary for QoS [39-38](#)
- IP Port Security for Static Hosts
 - on a Layer 2 access port [26-20](#)
 - on a PVLAN host port [26-23](#)
- IP precedence [39-2](#)
- IP-precedence-to-DSCP map for QoS [39-62](#)

IP protocols

- in ACLs [38-11](#)

- routing [1-12](#)

IP routes, monitoring [41-100](#)

IP routing

- connecting interfaces with [14-7](#)

- disabling [41-18](#)

- enabling [41-18](#)

IP Service Level Agreements

- See IP SLAs

IP service levels, analyzing [46-1](#)

IP SLAs

- benefits [46-2](#)

- configuration guidelines [46-6](#)

- configuring object tracking [47-9](#)

- Control Protocol [46-4](#)

- default configuration [46-6](#)

- definition [46-1](#)

- ICMP echo operation [46-11](#)

- measuring network performance [46-3](#)

- monitoring [46-13](#)

- multioperations scheduling [46-5](#)

- object tracking [47-9](#)

- operation [46-3](#)

- reachability tracking [47-9](#)

- responder

- described [46-4](#)

- enabling [46-8](#)

- response time [46-4](#)

- scheduling [46-5](#)

- SNMP support [46-2](#)

- supported metrics [46-2](#)

- threshold monitoring [46-6](#)

- track object monitoring agent, configuring [47-11](#)

- track state [47-9](#)

- UDP jitter operation [46-9](#)

IP source guard

- and 802.1x [26-19](#)

- and DHCP snooping [26-16](#)

- and EtherChannels [26-19](#)

- and port security [26-19](#)

- and private VLANs [26-19](#)

- and routed ports [26-18](#)

- and TCAM entries [26-19](#)

- and trunk interfaces [26-18](#)

- and VRF [26-19](#)

- binding configuration

- automatic [26-16](#)

- manual [26-16](#)

- binding table [26-16](#)

- configuration guidelines [26-18](#)

- default configuration [26-18](#)

- described [26-16](#)

- disabling [26-20](#)

- displaying

- active IP or MAC bindings [26-26](#)

- bindings [26-26](#)

- configuration [26-26](#)

- enabling [26-19, 26-20](#)

- filtering

- source IP address [26-17](#)

- source IP and MAC address [26-17](#)

- source IP address filtering [26-17](#)

- source IP and MAC address filtering [26-17](#)

- static bindings

- adding [26-19, 26-20](#)

- deleting [26-20](#)

- static hosts [26-20](#)

IP traceroute

- executing [36-13](#)

- overview [36-13](#)

IP unicast routing

- address resolution [41-8](#)

- administrative distances [41-89, 41-99](#)

- ARP [41-8](#)

- assigning IP addresses to Layer 3 interfaces [41-5](#)

- authentication keys [41-99](#)

- broadcast

- address [41-15](#)
- flooding [41-16](#)
- packets [41-13](#)
- storms [41-13](#)
- classless routing [41-6](#)
- configuring static routes [41-88](#)
- default
 - addressing configuration [41-4](#)
 - gateways [41-11](#)
 - networks [41-89](#)
 - routes [41-89](#)
 - routing [41-2](#)
- directed broadcasts [41-13](#)
- disabling [41-18](#)
- dynamic routing [41-3](#)
- enabling [41-18](#)
- EtherChannel Layer 3 interface [41-3](#)
- IGP [41-24](#)
- inter-VLAN [41-2](#)
- IP addressing
 - classes [41-5](#)
 - configuring [41-4](#)
- IRDP [41-11](#)
- Layer 3 interfaces [41-3](#)
- MAC address and IP address [41-8](#)
- passive interfaces [41-97](#)
- protocols
 - distance-vector [41-3](#)
 - dynamic [41-3](#)
 - link-state [41-3](#)
- proxy ARP [41-8](#)
- redistribution [41-90](#)
- reverse address resolution [41-8](#)
- routed ports [41-3](#)
- static routing [41-3](#)
- steps to configure [41-4](#)
- subnet mask [41-5](#)
- subnet zero [41-6](#)
- supernet [41-6](#)

- UDP [41-14](#)
- with SVIs [41-3](#)
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP
- IPv4 ACLs
 - applying to interfaces [38-19](#)
 - extended, creating [38-10](#)
 - named [38-14](#)
 - standard, creating [38-9](#)
- IPv4 and IPv6
 - dual protocol stacks [42-5](#)
- IPv6
 - ACLs
 - displaying [44-8](#)
 - limitations [44-2](#)
 - matching criteria [44-3](#)
 - port [44-1](#)
 - precedence [44-2](#)
 - router [44-1](#)
 - supported [44-2](#)
 - addresses [42-2](#)
 - address formats [42-2](#)
 - applications [42-5](#)
 - assigning address [42-10](#)
 - autoconfiguration [42-4](#)
 - CEFv6 [42-18](#)
 - configuring static routes [42-19](#)
 - default configuration [42-10](#)
 - default router preference (DRP) [42-4](#)
 - defined [42-1](#)
 - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [42-7](#)
 - EIGRP IPv6 Commands [42-7](#)
 - Router ID [42-7](#)
 - feature limitations [42-9](#)
 - features not supported [42-8](#)
 - forwarding [42-10](#)

ICMP [42-4](#)
 monitoring [42-26](#)
 neighbor discovery [42-4](#)
 OSPF [42-7](#)
 path MTU discovery [42-4](#)
 SDM templates [10-2, 43-1, 44-1](#)
 Stateless Autoconfiguration [42-4](#)
 supported features [42-2](#)
 switch limitations [42-9](#)
 understanding static routes [42-6](#)

IPv6 traffic, filtering [44-3](#)

IRDP

configuring [41-12](#)
 definition [41-11](#)
 support for [1-12](#)

IS-IS

addresses [41-62](#)
 area routing [41-62](#)
 default configuration [41-63](#)
 monitoring [41-71](#)
 show commands [41-71](#)
 system routing [41-62](#)

ISO CLNS

clear commands [41-71](#)
 dynamic routing protocols [41-62](#)
 monitoring [41-71](#)
 NETs [41-62](#)
 NSAPs [41-62](#)
 OSI standard [41-62](#)

ISO IGRP

area routing [41-62](#)
 system routing [41-62](#)

isolated port [19-2](#)

isolated VLANs [19-2, 19-3](#)

J

join messages, IGMP [28-3](#)

K

KDC

described [11-41](#)
 See also Kerberos

Kerberos

authenticating to
 boundary switch [11-43](#)
 KDC [11-43](#)
 network services [11-44](#)
 configuration examples [11-40](#)
 configuring [11-44](#)
 credentials [11-41](#)
 cryptographic software image [11-40](#)
 described [11-41](#)
 KDC [11-41](#)
 operation [11-43](#)
 realm [11-42](#)
 server [11-42](#)
 support for [1-10](#)
 switch as trusted third party [11-40](#)
 terms [11-41](#)
 TGT [11-42](#)
 tickets [11-41](#)

key distribution center

See KDC

L

l2protocol-tunnel command [20-12](#)

LACP

Layer 2 protocol tunneling [20-9](#)
 See EtherChannel

Layer 2 frames, classification with CoS [39-2](#)

Layer 2 interfaces, default configuration [14-13](#)

Layer 2 protocol tunneling

configuring [20-10](#)
 configuring for EtherChannels [20-14](#)
 default configuration [20-11](#)

- defined [20-8](#)
- guidelines [20-11](#)
- Layer 2 traceroute
 - and ARP [36-12](#)
 - and CDP [36-11](#)
 - broadcast traffic [36-11](#)
 - described [36-11](#)
 - IP addresses and subnets [36-12](#)
 - MAC addresses and VLANs [36-12](#)
 - multicast traffic [36-12](#)
 - multiple devices on a port [36-12](#)
 - unicast traffic [36-11](#)
 - usage guidelines [36-11](#)
- Layer 3 features [1-12](#)
- Layer 3 interfaces
 - assigning IP addresses to [41-5](#)
 - assigning IPv4 and IPv6 addresses to [42-14](#)
 - assigning IPv6 addresses to [42-11](#)
 - changing from Layer 2 mode [41-5, 41-79](#)
 - types of [41-3](#)
- Layer 3 packets, classification methods [39-2](#)
- LDAP [5-2](#)
- Leaking IGMP Reports [25-4](#)
- LEDs, switch
 - See hardware installation guide
- lightweight directory access protocol
 - See LDAP
- line configuration mode [2-3](#)
- Link Aggregation Control Protocol
 - See EtherChannel
- link failure, detecting unidirectional [22-7](#)
- link fault alarm [3-3](#)
- link integrity, verifying with REP [24-3](#)
- Link Layer Discovery Protocol
 - See CDP
- link local unicast addresses [42-3](#)
- link redundancy
 - See Flex Links
- links, unidirectional [33-1](#)
- link state advertisements (LSAs) [41-29](#)
- link-state protocols [41-3](#)
- link-state tracking
 - configuring [40-23](#)
 - described [40-21](#)
- LLDP
 - configuring [31-4](#)
 - characteristics [31-5](#)
 - default configuration [31-4](#)
 - enabling [31-5](#)
 - monitoring and maintaining [31-10](#)
 - overview [31-1](#)
 - supported TLVs [31-1](#)
 - switch stack considerations [31-2](#)
 - transmission timer and holdtime, setting [31-5](#)
- LLDP-MED
 - configuring
 - procedures [31-4](#)
 - TLVs [31-6](#)
 - monitoring and maintaining [31-10](#)
 - overview [31-1, 31-2](#)
 - supported TLVs [31-2](#)
- LLDP Media Endpoint Discovery
 - See LLDP-MED
- load balancing [45-4](#)
- local SPAN [30-2](#)
- location TLV [31-2, 31-6](#)
- logging messages, ACL [38-8](#)
- login authentication
 - with RADIUS [11-30](#)
 - with TACACS+ [11-14](#)
- login banners [7-10](#)
- log messages
 - See system message logging
- loop guard
 - described [23-9](#)
 - enabling [23-15](#)
 - support for [1-7](#)
- LRE profiles, considerations in switch clusters [6-14](#)

M

MAB

See MAC authentication bypass

MAB aging timer [1-8](#)

MAB inactivity timer

default setting [12-33](#)

range [12-36](#)

MAC/PHY configuration status TLV [31-2](#)

MAC addresses

aging time [7-14](#)

and VLAN association [7-13](#)

building the address table [7-13](#)

default configuration [7-14](#)

disabling learning on a VLAN [7-22](#)

discovering [7-23](#)

displaying [7-23](#)

displaying in the IP source binding table [26-26](#)

dynamic

learning [7-13](#)

removing [7-15](#)

in ACLs [38-27](#)

IP address association [41-8](#)

static

adding [7-20](#)

allowing [7-21, 7-22](#)

characteristics of [7-19](#)

dropping [7-21](#)

removing [7-20](#)

MAC address learning [1-5](#)

MAC address learning, disabling on a VLAN [7-22](#)

MAC address notification, support for [1-13](#)

MAC address-table move update

configuration guidelines [25-8](#)

configuring [25-12](#)

default configuration [25-8](#)

description [25-6](#)

monitoring [25-14](#)

MAC address-to-VLAN mapping [16-24](#)

MAC authentication bypass [12-35](#)

configuring [12-55](#)

overview [12-16](#)

See MAB

MAC extended access lists

applying to Layer 2 interfaces [38-28](#)

configuring for QoS [39-45](#)

creating [38-27](#)

defined [38-27](#)

for QoS classification [39-5](#)

magic packet [12-25](#)

manageability features [1-4](#)

management access

in-band

browser session [1-5](#)

CLI session [1-5](#)

device manager [1-5](#)

SNMP [1-5](#)

out-of-band console port connection [1-5](#)

management address TLV [31-2](#)

management options

CLI [2-1](#)

clustering [1-2](#)

CNS [5-1](#)

overview [1-4](#)

management VLAN

considerations in switch clusters [6-7](#)

discovery through different management VLANs [6-7](#)

manual preemption, REP, configuring [24-13](#)

mapping tables for QoS

configuring

CoS-to-DSCP [39-61](#)

DSCP [39-60](#)

DSCP-to-CoS [39-64](#)

DSCP-to-DSCP-mutation [39-65](#)

IP-precedence-to-DSCP [39-62](#)

policed-DSCP [39-63](#)

described [39-12](#)

marking

- action with aggregate policers [39-58](#)
 - described [39-4, 39-8](#)
- matching
 - IPv6 ACLs [44-3](#)
- matching, IPv4 ACLs [38-7](#)
- maximum aging time
 - MSTP [22-23](#)
 - STP [21-21](#)
- maximum hop count, MSTP [22-24](#)
- maximum number of allowed devices, port-based authentication [12-36](#)
- maximum-paths command [41-49, 41-88](#)
- MDA
 - configuration guidelines [12-12 to 12-13](#)
 - described [1-9, 12-12](#)
 - exceptions with authentication process [12-5](#)
- membership mode, VLAN port [16-3](#)
- member switch
 - automatic discovery [6-4](#)
 - defined [6-1](#)
 - managing [6-14](#)
 - passwords [6-13](#)
 - recovering from lost connectivity [36-7](#)
 - requirements [6-3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [7-10](#)
- metrics, in BGP [41-49](#)
- metric translations, between routing protocols [41-93](#)
- metro tags [20-2](#)
- MHSRP [45-4](#)
- MIBs
 - overview [36-1](#)
 - SNMP interaction with [36-4](#)
- mirroring traffic for analysis [30-1](#)
- mismatches, autonegotiation [36-8](#)
- module number [14-8](#)
- monitoring
 - access groups [38-41](#)
- alarms [3-13](#)
- BGP [41-61](#)
- cables for unidirectional links [33-1](#)
- CDP [32-5](#)
- CEF [41-87](#)
- EIGRP [41-40](#)
- fallback bridging [51-10](#)
- features [1-13](#)
- Flex Links [25-14](#)
- HSRP [45-13](#)
- IEEE 802.1Q tunneling [20-17](#)
- IGMP
 - filters [28-28](#)
 - snooping [28-15, 43-11](#)
- interfaces [14-24](#)
- IP
 - address tables [41-17](#)
 - multicast routing [49-60](#)
 - routes [41-100](#)
- IP SLAs operations [46-13](#)
- IPv4 ACL configuration [38-41](#)
- IPv6 [42-26](#)
- IPv6 ACL configuration [44-8](#)
- IS-IS [41-71](#)
- ISO CLNS [41-71](#)
- Layer 2 protocol tunneling [20-17](#)
- MAC address-table move update [25-14](#)
- MSDP peers [50-18](#)
- multicast router interfaces [28-16, 43-11](#)
- multi-VRF CE [41-86](#)
- MVR [28-23](#)
- network traffic for analysis with probe [30-2](#)
- object tracking [47-12](#)
- OSPF [41-32](#)
- port
 - blocking [29-21](#)
 - protection [29-21](#)
- private VLANs [19-14](#)
- PROFINET [9-5](#)

- PTP [8-4](#)
- REP [24-13](#)
- RP mapping information [49-33](#)
- SFP status [14-25, 36-9](#)
- source-active messages [50-18](#)
- speed and duplex mode [14-17](#)
- SSM mapping [49-21](#)
- traffic flowing among switches [34-1](#)
- traffic suppression [29-20](#)
- tunneling [20-17](#)
- VLAN
 - filters [38-41](#)
 - maps [38-41](#)
- VLANs [16-14](#)
- VMPS [16-29](#)
- VTP [17-16](#)
- mrouter Port [25-3](#)
- mrouter port [25-5](#)
- MSDP
 - benefits of [50-3](#)
 - clearing MSDP connections and statistics [50-18](#)
 - controlling source information
 - forwarded by switch [50-11](#)
 - originated by switch [50-8](#)
 - received by switch [50-13](#)
 - default configuration [50-4](#)
 - dense-mode regions
 - sending SA messages to [50-16](#)
 - specifying the originating address [50-17](#)
 - filtering
 - incoming SA messages [50-14](#)
 - SA messages to a peer [50-12](#)
 - SA requests from a peer [50-10](#)
 - join latency, defined [50-6](#)
 - meshed groups
 - configuring [50-15](#)
 - defined [50-15](#)
 - originating address, changing [50-17](#)
 - overview [50-1](#)
 - peer-RPF flooding [50-2](#)
 - peers
 - configuring a default [50-4](#)
 - monitoring [50-18](#)
 - peering relationship, overview [50-1](#)
 - requesting source information from [50-8](#)
 - shutting down [50-15](#)
 - source-active messages
 - caching [50-6](#)
 - clearing cache entries [50-18](#)
 - defined [50-2](#)
 - filtering from a peer [50-10](#)
 - filtering incoming [50-14](#)
 - filtering to a peer [50-12](#)
 - limiting data with TTL [50-13](#)
 - monitoring [50-18](#)
 - restricting advertised sources [50-9](#)
 - support for [1-13](#)
- MSTP
 - boundary ports
 - configuration guidelines [22-15](#)
 - described [22-6](#)
 - BPDU filtering
 - described [23-3](#)
 - enabling [23-12](#)
 - BPDU guard
 - described [23-2](#)
 - enabling [23-11](#)
 - CIST, described [22-3](#)
 - CIST regional root [22-3](#)
 - CIST root [22-5](#)
 - configuration guidelines [22-14, 23-10](#)
 - configuring
 - forward-delay time [22-23](#)
 - hello time [22-22](#)
 - link type for rapid convergence [22-24](#)
 - maximum aging time [22-23](#)
 - maximum hop count [22-24](#)
 - MST region [22-15](#)

- neighbor type [22-25](#)
- path cost [22-20](#)
- port priority [22-19](#)
- root switch [22-17](#)
- secondary root switch [22-18](#)
- switch priority [22-21](#)
- CST
 - defined [22-3](#)
 - operations between regions [22-3](#)
- default configuration [22-14](#)
- default optional feature configuration [23-9](#)
- displaying status [22-26](#)
- enabling the mode [22-15](#)
- EtherChannel guard
 - described [23-7](#)
 - enabling [23-14](#)
- extended system ID
 - effects on root switch [22-17](#)
 - effects on secondary root switch [22-18](#)
 - unexpected behavior [22-17](#)
- IEEE 802.1s
 - implementation [22-6](#)
 - port role naming change [22-6](#)
 - terminology [22-5](#)
- instances supported [21-9](#)
- interface state, blocking to forwarding [23-2](#)
- interoperability and compatibility among modes [21-10](#)
- interoperability with IEEE 802.1D
 - described [22-8](#)
 - restarting migration process [22-25](#)
- IST
 - defined [22-2](#)
 - master [22-3](#)
 - operations within a region [22-3](#)
- loop guard
 - described [23-9](#)
 - enabling [23-15](#)
- mapping VLANs to MST instance [22-16](#)

- MST region
 - CIST [22-3](#)
 - configuring [22-15](#)
 - described [22-2](#)
 - hop-count mechanism [22-5](#)
 - IST [22-2](#)
 - supported spanning-tree instances [22-2](#)
- optional features supported [1-7](#)
- overview [22-2](#)
- Port Fast
 - described [23-2](#)
 - enabling [23-10](#)
- preventing root switch selection [23-8](#)
- root guard
 - described [23-8](#)
 - enabling [23-15](#)
- root switch
 - configuring [22-17](#)
 - effects of extended system ID [22-17](#)
 - unexpected behavior [22-17](#)
- shutdown Port Fast-enabled port [23-2](#)
- status, displaying [22-26](#)
- multiauth
 - support for inaccessible authentication bypass [12-23](#)
- multiauth mode
 - See multiple-authentication mode
- multicast groups
 - Immediate Leave [28-5](#)
 - joining [28-3](#)
 - leaving [28-5](#)
 - static joins [28-10, 43-7](#)
- multicast packets
 - ACLs on [38-40](#)
 - blocking [29-8](#)
- multicast router interfaces, monitoring [28-16, 43-11](#)
- multicast router ports, adding [28-9, 43-8](#)
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm [29-1](#)

- multicast storm-control command [29-4](#)
- multicast television application [28-17](#)
- multicast VLAN [28-17](#)
- Multicast VLAN Registration
 - See MVR
- multidomain authentication
 - See MDA
- multioperations scheduling, IP SLAs [46-5](#)
- multiple authentication [12-13](#)
- multiple authentication mode
 - configuring [12-42](#)
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE
- multi-VRF CE
 - configuration example [41-82](#)
 - configuration guidelines [41-74](#)
 - configuring [41-74](#)
 - default configuration [41-74](#)
 - defined [41-72](#)
 - displaying [41-86](#)
 - monitoring [41-86](#)
 - network components [41-74](#)
 - packet-forwarding process [41-73](#)
 - support for [1-12](#)
- MVR
 - and address aliasing [28-20](#)
 - and IGMPv3 [28-20](#)
 - configuration guidelines [28-19](#)
 - configuring interfaces [28-21](#)
 - default configuration [28-19](#)
 - described [28-17](#)
 - example application [28-17](#)
 - modes [28-20](#)
 - monitoring [28-23](#)
 - multicast television application [28-17](#)
 - setting global parameters [28-20](#)

- support for [1-3](#)

N

NAC

- AAA down policy [1-10](#)
- critical authentication [12-23, 12-51](#)
- IEEE 802.1x authentication using a RADIUS server [12-56](#)
- IEEE 802.1x validation using RADIUS server [12-56](#)
- inaccessible authentication bypass [1-10, 12-51](#)
- Layer 2 IEEE 802.1x validation [1-10, 12-28, 12-56](#)
- Layer 2 IP validation [1-10](#)

- named IPv4 ACLs [38-14](#)

NameSpace Mapper

- See NSM

native VLAN

- and IEEE 802.1Q tunneling [20-4](#)
- configuring [16-20](#)
- default [16-20](#)

NEAT

- configuring [12-57](#)
- overview [12-29](#)

- neighbor discovery, IPv6 [42-4](#)

- neighbor discovery/recovery, EIGRP [41-34](#)

- neighbor offset numbers, REP [24-4](#)

- neighbors, BGP [41-55](#)

Network Admission Control

- NAC

Network Assistant

- benefits [1-2](#)
- described [1-4](#)
- upgrading a switch [A-22](#)

network configuration examples

- increasing network performance [1-17](#)
- providing network services [1-17](#)

network design

- performance [1-17](#)
- services [1-17](#)

Network Edge Access Topology

See NEAT

network management

CDP [32-1](#)

RMON [34-1](#)

SNMP [36-1](#)

network performance, measuring with IP SLAs [46-3](#)

network policy TLV [31-2, 31-6](#)

Network Time Protocol

See NTP

no commands [2-4](#)

nonhierarchical policy maps

configuration guidelines [39-33](#)

described [39-9](#)

non-IP traffic filtering [38-27](#)

nontrunking mode [16-15](#)

normal-range VLANs [16-4](#)

configuration guidelines [16-6](#)

configuring [16-4](#)

defined [16-1](#)

no switchport command [14-4](#)

not-so-stubby areas

See NSSA

NSAPs, as ISO IGRP addresses [41-62](#)

NSF Awareness

IS-IS [41-64](#)

NSM [5-3](#)

NSSA, OSPF [41-29](#)

NTP

associations

defined [7-2](#)

overview [7-2](#)

stratum [7-2](#)

support for [1-5](#)

time

services [7-2](#)

synchronizing [7-2](#)

O

object tracking

HSRP [47-7](#)

IP SLAs [47-9](#)

IP SLAs, configuring [47-9](#)

monitoring [47-12](#)

off mode, VTP [17-3](#)

openlx

configuring [12-62](#)

openlx authentication

overview [12-29](#)

Open Shortest Path First

See OSPF

optimizing system resources [10-1](#)

options, management [1-4](#)

OSPF

area parameters, configuring [41-28](#)

configuring [41-26](#)

default configuration

metrics [41-30](#)

route [41-30](#)

settings [41-25](#)

described [41-23](#)

for IPv6 [42-7](#)

interface parameters, configuring [41-27](#)

LSA group pacing [41-31](#)

monitoring [41-32](#)

router IDs [41-32](#)

route summarization [41-30](#)

support for [1-12](#)

virtual links [41-30](#)

out-of-profile markdown [1-11](#)

P

packet modification, with QoS [39-19](#)

PAgP

Layer 2 protocol tunneling [20-9](#)

- See EtherChannel
- parallel paths, in routing tables [41-88](#)
- passive interfaces
 - configuring [41-97](#)
 - OSPF [41-30](#)
- passwords
 - default configuration [11-3](#)
 - disabling recovery of [11-5](#)
 - encrypting [11-4](#)
 - for security [1-8](#)
 - in clusters [6-13](#)
 - overview [11-1](#)
 - recovery of [36-3](#)
 - setting
 - enable [11-3](#)
 - enable secret [11-4](#)
 - Telnet [11-6](#)
 - with usernames [11-7](#)
 - VTP domain [17-8](#)
- path cost
 - MSTP [22-20](#)
 - STP [21-18](#)
- path MTU discovery [42-4](#)
- PBR
 - defined [41-94](#)
 - enabling [41-95](#)
 - fast-switched policy-based routing [41-96](#)
 - local policy-based routing [41-97](#)
- PC (passive command switch) [6-10](#)
- peers, BGP [41-55](#)
- percentage thresholds in tracked lists [47-6](#)
- performance, network design [1-17](#)
- performance features [1-2](#)
- persistent self-signed certificate [11-51](#)
- per-user ACLs and Filter-Ids [12-8](#)
- per-VLAN spanning-tree plus
 - See PVST+
- PE to CE routing, configuring [41-81](#)
- physical ports [14-2](#)
- PIM
 - default configuration [49-10](#)
 - dense mode
 - overview [49-4](#)
 - rendezvous point (RP), described [49-5](#)
 - RPF lookups [49-8](#)
 - displaying neighbors [49-61](#)
 - enabling a mode [49-12](#)
 - overview [49-3](#)
 - router-query message interval, modifying [49-36](#)
 - shared tree and source tree, overview [49-34](#)
 - shortest path tree, delaying the use of [49-35](#)
 - sparse mode
 - join messages and shared tree [49-5](#)
 - overview [49-4](#)
 - prune messages [49-5](#)
 - RPF lookups [49-8](#)
 - stub routing
 - configuration guidelines [49-21](#)
 - displaying [49-61](#)
 - enabling [49-22](#)
 - overview [49-5](#)
 - support for [1-13](#)
 - versions
 - interoperability [49-10](#)
 - troubleshooting interoperability problems [49-34](#)
 - v2 improvements [49-4](#)
- PIM-DVMRP, as snooping method [28-8](#)
- ping
 - character output description [36-11](#)
 - executing [36-10](#)
 - overview [36-10](#)
- PoE
 - troubleshooting [36-8](#)
- policed-DSCP map for QoS [39-63](#)
- policers
 - configuring
 - for each matched traffic class [39-48](#)
 - for more than one traffic class [39-58](#)

- described [39-4](#)
- displaying [39-78](#)
- number of [39-34](#)
- types of [39-9](#)
- policing
 - described [39-4](#)
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm [39-9](#)
- policy-based routing
 - See PBR
- policy maps for QoS
 - characteristics of [39-48](#)
 - described [39-7](#)
 - displaying [39-78](#)
 - hierarchical [39-8](#)
 - hierarchical on SVIs
 - configuration guidelines [39-33](#)
 - configuring [39-52](#)
 - described [39-11](#)
 - nonhierarchical on physical ports
 - configuration guidelines [39-33](#)
 - described [39-9](#)
- port ACLs
 - defined [38-2](#)
 - types of [38-3](#)
- Port Aggregation Protocol
 - See EtherChannel
- port-based authentication
 - accounting [12-14](#)
 - authentication server
 - defined [12-3](#), [13-2](#)
 - RADIUS server [12-3](#)
 - client, defined [12-3](#), [13-2](#)
 - configuration guidelines [12-34](#), [13-9](#)
 - configuring
 - 802.1x authentication [12-39](#)
 - guest VLAN [12-49](#)
 - host mode [12-42](#)
 - inaccessible authentication bypass [12-51](#)
 - manual re-authentication of a client [12-44](#)
 - periodic re-authentication [12-43](#)
 - quiet period [12-44](#)
 - RADIUS server [12-42](#), [13-13](#)
 - RADIUS server parameters on the switch [12-41](#), [13-11](#)
 - restricted VLAN [12-50](#)
 - switch-to-client frame-retransmission number [12-45](#), [12-46](#)
 - switch-to-client retransmission time [12-45](#)
 - violation modes [12-38 to 12-39](#)
 - default configuration [12-33](#), [13-9](#)
 - described [12-1](#)
 - device roles [12-2](#), [13-2](#)
 - displaying statistics [12-64](#), [13-17](#)
 - downloadable ACLs and redirect URLs
 - configuring [12-59 to 12-61](#), [?? to 12-61](#)
 - overview [12-18 to 12-20](#)
 - EAPOL-start frame [12-5](#)
 - EAP-request/identity frame [12-5](#)
 - EAP-response/identity frame [12-5](#)
 - enabling
 - 802.1X authentication [13-11](#)
 - encapsulation [12-3](#)
 - flexible authentication ordering
 - configuring [12-62](#)
 - overview [12-28](#)
 - guest VLAN
 - configuration guidelines [12-22](#), [12-23](#)
 - described [12-21](#)
 - host mode [12-11](#)
 - inaccessible authentication bypass
 - configuring [12-51](#)
 - described [12-23](#)
 - guidelines [12-35](#)
 - initiation and message exchange [12-5](#)
 - magic packet [12-25](#)
 - maximum number of allowed devices per port [12-36](#)

- method lists [12-39](#)
- multiple authentication [12-13](#)
- per-user ACLs
 - AAA authorization [12-39](#)
 - configuration tasks [12-18](#)
 - described [12-17](#)
 - RADIUS server attributes [12-18](#)
- ports
 - authorization state and dot1x port-control command [12-10](#)
 - authorized and unauthorized [12-10](#)
 - voice VLAN [12-24](#)
- port security
 - described [12-25](#)
- readiness check
 - configuring [12-36](#)
 - described [12-16, 12-36](#)
- resetting to default values [12-64](#)
- statistics, displaying [12-64](#)
- switch
 - as proxy [12-3, 13-2](#)
 - RADIUS client [12-3](#)
- switch supplicant
 - configuring [12-57](#)
 - overview [12-29](#)
- user distribution
 - guidelines [12-27](#)
 - overview [12-27](#)
- VLAN assignment
 - AAA authorization [12-39](#)
 - characteristics [12-16](#)
 - configuration tasks [12-17](#)
 - described [12-16](#)
- voice aware 802.1x security
 - configuring [12-37](#)
 - described [12-29, 12-37](#)
- voice VLAN
 - described [12-24](#)
 - PVID [12-24](#)
 - VVID [12-24](#)
 - wake-on-LAN, described [12-25](#)
 - with ACLs and RADIUS Filter-Id attribute [12-31](#)
- port-based authentication methods, supported [12-7](#)
- port blocking [1-3, 29-7](#)
- port-channel
 - See EtherChannel
- port description TLV [31-1](#)
- Port Fast
 - described [23-2](#)
 - enabling [23-10](#)
 - mode, spanning tree [16-26](#)
 - support for [1-7](#)
- port membership modes, VLAN [16-3](#)
- port not forwarding alarm [3-3](#)
- port not operating alarm [3-3](#)
- port priority
 - MSTP [22-19](#)
 - STP [21-17](#)
- ports
 - access [14-3](#)
 - blocking [29-7](#)
 - dual-purpose uplink [14-6](#)
 - dynamic access [16-3](#)
 - IEEE 802.1Q tunnel [16-4](#)
 - protected [29-6](#)
 - REP [24-6](#)
 - routed [14-4](#)
 - secure [29-8](#)
 - static-access [16-3, 16-9](#)
 - switch [14-2](#)
 - trunks [16-3, 16-14](#)
 - VLAN assignments [16-9](#)
- port security
 - aging [29-17](#)
 - and private VLANs [29-18](#)
 - and QoS trusted boundary [39-38](#)
 - configuring [29-13](#)
 - default configuration [29-11](#)

- described [29-8](#)
- displaying [29-21](#)
- enabling [29-18](#)
- on trunk ports [29-14](#)
- sticky learning [29-9](#)
- violations [29-10](#)
- with other features [29-11](#)
- port-shutdown response, VMPS [16-25](#)
- port status monitoring alarms
 - FCS bit error rate alarm [3-3](#)
 - link fault alarm [3-3](#)
 - port not forwarding alarm [3-3](#)
 - port not operating alarm [3-3](#)
- port VLAN ID TLV [31-2](#)
- power management TLV [31-2, 31-6](#)
- preempt delay time, REP [24-5](#)
- preemption, default configuration [25-7](#)
- preemption delay, default configuration [25-8](#)
- preferential treatment of traffic
 - See QoS
- prefix lists, BGP [41-53](#)
- preventing unauthorized access [11-1](#)
- primary edge port, REP [24-4](#)
- primary interface for object tracking, DHCP, configuring [47-10](#)
- primary interface for static routing, configuring [47-10](#)
- primary links [25-2](#)
- primary VLANs [19-1, 19-3](#)
- priority
 - HSRP [45-8](#)
 - overriding CoS [18-6](#)
 - trusting CoS [18-6](#)
- private VLAN edge ports
 - See protected ports
- private VLANs
 - across multiple switches [19-4](#)
 - and SDM template [19-4](#)
 - and SVIs [19-5](#)
 - benefits of [19-1](#)
 - community ports [19-2](#)
 - community VLANs [19-2, 19-3](#)
 - configuration guidelines [19-6, 19-7, 19-8](#)
 - configuration tasks [19-6](#)
 - configuring [19-9](#)
 - default configuration [19-6](#)
 - end station access to [19-3](#)
 - IP addressing [19-3](#)
 - isolated port [19-2](#)
 - isolated VLANs [19-2, 19-3](#)
 - mapping [19-13](#)
 - monitoring [19-14](#)
 - ports
 - community [19-2](#)
 - configuration guidelines [19-8](#)
 - configuring host ports [19-11](#)
 - configuring promiscuous ports [19-12](#)
 - described [16-4](#)
 - isolated [19-2](#)
 - promiscuous [19-2](#)
 - primary VLANs [19-1, 19-3](#)
 - promiscuous ports [19-2](#)
 - secondary VLANs [19-2](#)
 - subdomains [19-1](#)
 - traffic in [19-5](#)
- privileged EXEC mode [2-2](#)
- privilege levels
 - changing the default for lines [11-9](#)
 - command switch [6-15](#)
 - exiting [11-10](#)
 - logging into [11-10](#)
 - mapping on member switches [6-15](#)
 - overview [11-2, 11-8](#)
 - setting a command with [11-8](#)
- PROFINET [9-1](#)
 - configuring [9-4](#)
 - default configuration [9-4](#)
 - displaying configuration [9-5](#)
- promiscuous ports

- configuring [19-12](#)
- defined [19-2](#)
- protected ports [1-8, 29-6](#)
- protocol-dependent modules, EIGRP [41-34](#)
- Protocol-Independent Multicast Protocol
 - See PIM
- protocol storm protection [29-19](#)
- provider edge devices [41-72](#)
- proxy ARP
 - configuring [41-10](#)
 - definition [41-8](#)
 - with IP routing disabled [41-11](#)
- proxy reports [25-3](#)
- pruning, VTP
 - disabling
 - in VTP domain [17-14](#)
 - on a port [16-20](#)
 - enabling
 - in VTP domain [17-14](#)
 - on a port [16-19](#)
 - examples [17-6](#)
 - overview [17-5](#)
- pruning-eligible list
 - changing [16-19](#)
 - for VTP pruning [17-5](#)
 - VLANs [17-14](#)
- PTP
 - configuring [8-3](#)
 - default configuration [8-2](#)
 - displaying configuration [8-4](#)
- PVST+
 - described [21-9](#)
 - IEEE 802.1Q trunking interoperability [21-10](#)
 - instances supported [21-9](#)

Q

- QoS
 - and MQC commands [39-1](#)

- auto-QoS
 - categorizing traffic [39-20](#)
 - configuration and defaults display [39-29](#)
 - configuration guidelines [39-25](#)
 - described [39-20](#)
 - disabling [39-27](#)
 - displaying generated commands [39-27](#)
 - displaying the initial configuration [39-29](#)
 - effects on running configuration [39-25](#)
 - egress queue defaults [39-21](#)
 - enabling for VoIP [39-26](#)
 - example configuration [39-28](#)
 - ingress queue defaults [39-21](#)
 - list of generated commands [39-22](#)
- basic model [39-4](#)
- classification
 - class maps, described [39-7](#)
 - defined [39-4](#)
 - DSCP transparency, described [39-40](#)
 - flowchart [39-6](#)
 - forwarding treatment [39-3](#)
 - in frames and packets [39-3](#)
 - IP ACLs, described [39-5, 39-7](#)
 - MAC ACLs, described [39-5, 39-7](#)
 - options for IP traffic [39-5](#)
 - options for non-IP traffic [39-5](#)
 - policy maps, described [39-7](#)
 - trust DSCP, described [39-5](#)
 - trusted CoS, described [39-5](#)
 - trust IP precedence, described [39-5](#)
- class maps
 - configuring [39-46](#)
 - displaying [39-78](#)
- configuration guidelines
 - auto-QoS [39-25](#)
 - standard QoS [39-33](#)
- configuring
 - aggregate policers [39-58](#)
 - auto-QoS [39-20](#)

- default port CoS value [39-38](#)
- DSCP maps [39-60](#)
- DSCP transparency [39-40](#)
- DSCP trust states bordering another domain [39-40](#)
- egress queue characteristics [39-70](#)
- ingress queue characteristics [39-66](#)
- IP extended ACLs [39-44](#)
- IP standard ACLs [39-43](#)
- MAC ACLs [39-45](#)
- policy maps, hierarchical [39-52](#)
- port trust states within the domain [39-36](#)
- trusted boundary [39-38](#)
- default auto configuration [39-20](#)
- default standard configuration [39-30](#)
- displaying statistics [39-78](#)
- DSCP transparency [39-40](#)
- egress queues
 - allocating buffer space [39-71](#)
 - buffer allocation scheme, described [39-17](#)
 - configuring shaped weights for SRR [39-74](#)
 - configuring shared weights for SRR [39-75](#)
 - described [39-4](#)
 - displaying the threshold map [39-74](#)
 - flowchart [39-17](#)
 - mapping DSCP or CoS values [39-73](#)
 - scheduling, described [39-4](#)
 - setting WTD thresholds [39-71](#)
 - WTD, described [39-18](#)
- enabling globally [39-35](#)
- flowcharts
 - classification [39-6](#)
 - egress queueing and scheduling [39-17](#)
 - ingress queueing and scheduling [39-15](#)
 - policing and marking [39-10](#)
- implicit deny [39-7](#)
- ingress queues
 - allocating bandwidth [39-68](#)
 - allocating buffer space [39-68](#)
 - buffer and bandwidth allocation, described [39-16](#)
 - configuring shared weights for SRR [39-68](#)
 - configuring the priority queue [39-69](#)
 - described [39-4](#)
 - displaying the threshold map [39-67](#)
 - flowchart [39-15](#)
 - mapping DSCP or CoS values [39-67](#)
 - priority queue, described [39-16](#)
 - scheduling, described [39-4](#)
 - setting WTD thresholds [39-67](#)
 - WTD, described [39-16](#)
- IP phones
 - automatic classification and queueing [39-20](#)
 - detection and trusted settings [39-20, 39-38](#)
- limiting bandwidth on egress interface [39-77](#)
- mapping tables
 - CoS-to-DSCP [39-61](#)
 - displaying [39-78](#)
 - DSCP-to-CoS [39-64](#)
 - DSCP-to-DSCP-mutation [39-65](#)
 - IP-precedence-to-DSCP [39-62](#)
 - policed-DSCP [39-63](#)
 - types of [39-12](#)
- marked-down actions [39-50, 39-55](#)
- marking, described [39-4, 39-8](#)
- overview [39-1](#)
- packet modification [39-19](#)
- policers
 - configuring [39-50, 39-55, 39-59](#)
 - described [39-8](#)
 - displaying [39-78](#)
 - number of [39-34](#)
 - types of [39-9](#)
- policies, attaching to an interface [39-8](#)
- policing
 - described [39-4, 39-8](#)
 - token bucket algorithm [39-9](#)
- policy maps
 - characteristics of [39-48](#)

- displaying [39-78](#)
- hierarchical [39-8](#)
- hierarchical on SVIs [39-52](#)
- nonhierarchical on physical ports [39-48](#)
- QoS label, defined [39-4](#)
- queues
 - configuring egress characteristics [39-70](#)
 - configuring ingress characteristics [39-66](#)
 - high priority (expedite) [39-19, 39-76](#)
 - location of [39-13](#)
 - SRR, described [39-14](#)
 - WTD, described [39-13](#)
- rewrites [39-19](#)
- support for [1-11](#)
- trust states
 - bordering another domain [39-40](#)
 - described [39-5](#)
 - trusted device [39-38](#)
 - within the domain [39-36](#)
- quality of service
 - See QoS
- queries, IGMP [28-4](#)
- query solicitation, IGMP [28-13](#)

R

RADIUS

- attributes
 - vendor-proprietary [11-38](#)
 - vendor-specific [11-36](#)
- configuring
 - accounting [11-35](#)
 - authentication [11-30](#)
 - authorization [11-34](#)
 - communication, global [11-28, 11-36](#)
 - communication, per-server [11-28](#)
 - multiple UDP ports [11-28](#)
- default configuration [11-27](#)
- defining AAA server groups [11-32](#)

- displaying the configuration [11-40](#)
- identifying the server [11-28](#)
- in clusters [6-14](#)
- limiting the services to the user [11-34](#)
- method list, defined [11-27](#)
- operation of [11-20](#)
- overview [11-18](#)
- server load balancing [11-40](#)
- suggested network environments [11-19](#)
- support for [1-10](#)
- tracking services accessed by user [11-35](#)
- RADIUS Change of Authorization [11-20](#)
- range
 - macro [14-11](#)
 - of interfaces [14-10](#)
- rapid convergence [22-9](#)
- rapid per-VLAN spanning-tree plus
 - See rapid PVST+
- rapid PVST+
 - described [21-9](#)
 - IEEE 802.1Q trunking interoperability [21-10](#)
 - instances supported [21-9](#)
- Rapid Spanning Tree Protocol
 - See RSTP
- RARP [41-8](#)
- rcommand command [6-14](#)
- RCP
 - configuration files
 - downloading [A-16](#)
 - overview [A-14](#)
 - preparing the server [A-15](#)
 - uploading [A-17](#)
 - image files
 - deleting old image [A-33](#)
 - downloading [A-32](#)
 - preparing the server [A-31](#)
 - uploading [A-33](#)
- reachability, tracking IP SLAs IP host [47-9](#)
- readiness check

- port-based authentication
 - configuring [12-36](#)
 - described [12-16, 12-36](#)
- reconfirmation interval, VMPS, changing [16-28](#)
- reconfirming dynamic VLAN membership [16-28](#)
- recovery procedures [36-1](#)
- redirect URL [12-18, 12-20, 12-59](#)
- redundancy
 - EtherChannel [40-3](#)
 - HSRP [45-1](#)
 - STP
 - backbone [21-8](#)
 - path cost [16-23](#)
 - port priority [16-21](#)
- redundant links and UplinkFast [23-13](#)
- reliable transport protocol, EIGRP [41-34](#)
- reloading software [4-21](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- Remote Copy Protocol
 - See RCP
- Remote Network Monitoring
 - See RMON
- Remote SPAN
 - See RSPAN
- remote SPAN [30-2](#)
- REP
 - administrative VLAN [24-8](#)
 - administrative VLAN, configuring [24-8](#)
 - age timer [24-8](#)
 - and STP [24-6](#)
 - configuration guidelines [24-7](#)
 - configuring interfaces [24-9](#)
 - convergence [24-4](#)
 - default configuration [24-7](#)
 - manual preemption, configuring [24-13](#)
 - monitoring [24-13](#)
 - neighbor offset numbers [24-4](#)
 - open segment [24-2](#)
 - ports [24-6](#)
 - preempt delay time [24-5](#)
 - primary edge port [24-4](#)
 - ring segment [24-2](#)
 - secondary edge port [24-4](#)
 - segments [24-1](#)
 - characteristics [24-2](#)
 - SNMP traps, configuring [24-13](#)
 - supported interfaces [24-1](#)
 - triggering VLAN load balancing [24-5](#)
 - verifying link integrity [24-3](#)
 - VLAN blocking [24-12](#)
 - VLAN load balancing [24-4](#)
- report suppression, IGMP
 - described [28-6](#)
 - disabling [28-15, 43-10](#)
- resequencing ACL entries [38-14](#)
- reserved addresses in DHCP pools [26-27](#)
- resets, in BGP [41-48](#)
- resetting a UDLD-shutdown interface [33-6](#)
- Resilient Ethernet Protocol
 - See REP
- responder, IP SLAs
 - described [46-4](#)
 - enabling [46-8](#)
- response time, measuring with IP SLAs [46-4](#)
- restricted VLAN
 - configuring [12-50](#)
 - described [12-22](#)
 - using with IEEE 802.1x [12-22](#)
- restricting access
 - overview [11-1](#)
 - passwords and privilege levels [11-2](#)
 - RADIUS [11-18](#)
 - TACACS+ [11-10](#)
- retry count, VMPS, changing [16-29](#)
- reverse address resolution [41-8](#)
- Reverse Address Resolution Protocol
 - See RARP

RFC

- 1058, RIP [41-18](#)
- 1112, IP multicast and IGMP [28-2](#)
- 1157, SNMPv1 [36-2](#)
- 1163, BGP [41-41](#)
- 1166, IP addresses [41-5](#)
- 1253, OSPF [41-24](#)
- 1267, BGP [41-41](#)
- 1305, NTP [7-2](#)
- 1587, NSSAs [41-24](#)
- 1757, RMON [34-2](#)
- 1771, BGP [41-41](#)
- 1901, SNMPv2C [36-2](#)
- 1902 to 1907, SNMPv2 [36-2](#)
- 2236, IP multicast and IGMP [28-2](#)
- 2273-2275, SNMPv3 [36-2](#)

RFC 5176 Compliance [11-21](#)

RIP

- advertisements [41-18](#)
- authentication [41-21](#)
- configuring [41-20](#)
- default configuration [41-19](#)
- described [41-18](#)
- for IPv6 [42-6](#)
- hop counts [41-19](#)
- split horizon [41-22](#)
- summary addresses [41-22](#)
- support for [1-12](#)

RMON

- default configuration [34-3](#)
- displaying status [34-6](#)
- enabling alarms and events [34-3](#)
- groups supported [34-2](#)
- overview [34-1](#)
- statistics
 - collecting group Ethernet [34-5](#)
 - collecting group history [34-5](#)
- support for [1-13](#)

root guard

described [23-8](#)

enabling [23-15](#)

support for [1-7](#)

root switch

MSTP [22-17](#)

STP [21-14](#)

route calculation timers, OSPF [41-30](#)

route dampening, BGP [41-60](#)

routed packets, ACLs on [38-39](#)

routed ports

configuring [41-3](#)

defined [14-4](#)

in switch clusters [6-8](#)

IP addresses on [14-21, 41-4](#)

route-map command [41-96](#)

route maps

BGP [41-51](#)

policy-based routing [41-94](#)

router ACLs

defined [38-2](#)

types of [38-4](#)

route reflectors, BGP [41-59](#)

router ID, OSPF [41-32](#)

route selection, BGP [41-49](#)

route summarization, OSPF [41-30](#)

route targets, VPN [41-74](#)

routing

default [41-2](#)

dynamic [41-3](#)

redistribution of information [41-90](#)

static [41-3](#)

routing domain confederation, BGP [41-58](#)

Routing Information Protocol

See RIP

routing protocol administrative distances [41-89](#)

RSPAN

characteristics [30-8](#)

configuration guidelines [30-15](#)

default configuration [30-9](#)

- defined [30-2](#)
- destination ports [30-7](#)
- displaying status [30-22](#)
- interaction with other features [30-8](#)
- monitored ports [30-5](#)
- monitoring ports [30-7](#)
- overview [1-13, 30-1](#)
- received traffic [30-4](#)
- sessions
 - creating [30-16](#)
 - defined [30-3](#)
 - limiting source traffic to specific VLANs [30-21](#)
 - specifying monitored ports [30-16](#)
 - with ingress traffic enabled [30-19](#)
- source ports [30-5](#)
- transmitted traffic [30-5](#)
- VLAN-based [30-6](#)

RSTP

- active topology [22-9](#)
- BPDUs
 - format [22-12](#)
 - processing [22-12](#)
- designated port, defined [22-9](#)
- designated switch, defined [22-9](#)
- interoperability with IEEE 802.1D
 - described [22-8](#)
 - restarting migration process [22-25](#)
 - topology changes [22-13](#)
- overview [22-8](#)
- port roles
 - described [22-9](#)
 - synchronized [22-11](#)
- proposal-agreement handshake process [22-10](#)
- rapid convergence
 - described [22-9](#)
 - edge ports and Port Fast [22-9](#)
 - point-to-point links [22-10, 22-24](#)
 - root ports [22-10](#)
- root port, defined [22-9](#)

See also MSTP

- running configuration
 - replacing [A-18, A-19](#)
 - rolling back [A-18, A-19](#)
- running configuration, saving [4-15](#)

S

- SC (standby command switch) [6-10](#)
- scheduled reloads [4-21](#)
- scheduling, IP SLAs operations [46-5](#)
- SCP
 - and SSH [11-56](#)
 - configuring [11-57](#)
- SDM
 - templates
 - configuring [10-4](#)
 - number of [10-1](#)
- SDM template [44-3](#)
 - configuration guidelines [10-3](#)
 - configuring [10-3](#)
 - dual IPv4 and IPv6 [10-2](#)
 - types of [10-1](#)
- secondary edge port, REP [24-4](#)
- secondary VLANs [19-2](#)
- Secure Copy Protocol
- secure HTTP client
 - configuring [11-55](#)
 - displaying [11-56](#)
- secure HTTP server
 - configuring [11-54](#)
 - displaying [11-56](#)
- secure MAC addresses
 - deleting [29-16](#)
 - maximum number of [29-10](#)
 - types of [29-9](#)
- secure ports, configuring [29-8](#)
- secure remote connections [11-46](#)
- Secure Shell

- See SSH
- Secure Socket Layer
 - See SSL
- security, port [29-8](#)
- security features [1-8](#)
- See SCP
- sequence numbers in log messages [35-8](#)
- server mode, VTP [17-3](#)
- service-provider network, MSTP and RSTP [22-1](#)
- service-provider networks
 - and customer VLANs [20-2](#)
 - and IEEE 802.1Q tunneling [20-1](#)
 - Layer 2 protocols across [20-8](#)
 - Layer 2 protocol tunneling for EtherChannels [20-9](#)
- set-request operation [36-4](#)
- setting a secondary temperature threshold [3-7, 3-8](#)
- setting power supply alarm options [3-6](#)
- setting the FCS error hysteresis threshold [3-10](#)
- setup program
 - failed command switch replacement [36-6](#)
 - replacing failed command switch [36-4](#)
- severity levels, defining in system messages [35-8](#)
- SFPs
 - monitoring status of [14-25, 36-9](#)
 - security and identification [36-9](#)
 - status, displaying [36-9](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [38-21](#)
- show alarm commands [3-13](#)
- show and more command output, filtering [2-10](#)
- show cdp traffic command [32-6](#)
- show cluster members command [6-14](#)
- show configuration command [14-20](#)
- show forward command [36-17](#)
- show interfaces command [14-17, 14-20](#)
- show interfaces switchport [25-4](#)
- show l2protocol command [20-13, 20-15](#)
- show lldp traffic command [31-10](#)
- show platform forward command [36-17](#)
- show running-config command
 - displaying ACLs [38-19, 38-20, 38-31, 38-34](#)
 - interface description in [14-20](#)
- shutdown command on interfaces [14-26](#)
- shutdown threshold for Layer 2 protocol packets [20-11](#)
- Simple Network Management Protocol
 - See SNMP
- small-frame arrival rate, configuring [29-5](#)
- Smartports macros
 - applying Cisco-default macros [15-3](#)
 - applying global parameter values [15-3](#)
 - configuration guidelines [15-2](#)
 - default configuration [15-1](#)
 - displaying [15-5](#)
 - tracing [15-2](#)
- SNAP [32-1](#)
- SNMP
 - accessing MIB variables with [36-4](#)
 - agent
 - described [36-4](#)
 - disabling [36-7](#)
 - and IP SLAs [46-2](#)
 - authentication level [36-10](#)
 - community strings
 - configuring [36-8](#)
 - for cluster switches [36-4](#)
 - overview [36-4](#)
 - configuration examples [36-17](#)
 - default configuration [36-6](#)
 - engine ID [36-7](#)
 - groups [36-7, 36-9](#)
 - host [36-7](#)
 - ifIndex values [36-5](#)
 - in-band management [1-5](#)
 - in clusters [6-14](#)
 - informs
 - and trap keyword [36-11](#)
 - described [36-5](#)

- differences from traps [36-5](#)
 - disabling [36-15](#)
 - enabling [36-15](#)
 - limiting access by TFTP servers [36-16](#)
 - limiting system log messages to NMS [35-10](#)
 - manager functions [1-4](#), [36-3](#)
 - managing clusters with [6-15](#)
 - notifications [36-5](#)
 - overview [36-1](#), [36-4](#)
 - security levels [36-2](#)
 - setting CPU threshold notification [36-15](#)
 - status, displaying [36-18](#)
 - system contact and location [36-16](#)
 - trap manager, configuring [36-13](#)
 - traps
 - described [36-3](#), [36-5](#)
 - differences from informs [36-5](#)
 - disabling [36-15](#)
 - enabling [36-11](#)
 - enabling MAC address notification [7-15](#), [7-17](#), [7-18](#)
 - overview [36-1](#), [36-4](#)
 - types of [36-12](#)
 - users [36-7](#), [36-9](#)
 - versions supported [36-2](#)
- SNMP and Syslog Over IPv6 [42-8](#)
- SNMP traps
 - REP [24-13](#)
- SNMPv1 [36-2](#)
- SNMPv2C [36-2](#)
- SNMPv3 [36-2](#)
- snooping, IGMP [28-2](#)
- software images
 - location in flash [A-22](#)
 - recovery procedures [36-2](#)
 - scheduling reloads [4-21](#)
 - tar file format, described [A-22](#)
 - See also downloading and uploading
- source addresses
 - in IPv4 ACLs [38-11](#)
 - in IPv6 ACLs [44-5](#)
- source-and-destination-IP address based forwarding, EtherChannel [40-8](#)
- source-and-destination MAC address forwarding, EtherChannel [40-8](#)
- source-IP address based forwarding, EtherChannel [40-8](#)
- source-MAC address forwarding, EtherChannel [40-7](#)
- Source-specific multicast
 - See SSM
- SPAN
 - configuration guidelines [30-10](#)
 - default configuration [30-9](#)
 - destination ports [30-7](#)
 - displaying status [30-22](#)
 - interaction with other features [30-8](#)
 - monitored ports [30-5](#)
 - monitoring ports [30-7](#)
 - overview [1-13](#), [30-1](#)
 - ports, restrictions [29-12](#)
 - received traffic [30-4](#)
 - sessions
 - configuring ingress forwarding [30-14](#), [30-20](#)
 - creating [30-11](#)
 - defined [30-3](#)
 - limiting source traffic to specific VLANs [30-14](#)
 - removing destination (monitoring) ports [30-12](#)
 - specifying monitored ports [30-11](#)
 - with ingress traffic enabled [30-13](#)
 - source ports [30-5](#)
 - transmitted traffic [30-5](#)
 - VLAN-based [30-6](#)
- spanning tree and native VLANs [16-16](#)
- Spanning Tree Protocol
 - See STP
- SPAN traffic [30-4](#)
- split horizon, RIP [41-22](#)
- SRR
 - configuring

- shaped weights on egress queues [39-74](#)
 - shared weights on egress queues [39-75](#)
 - shared weights on ingress queues [39-68](#)
- described [39-14](#)
- shaped mode [39-14](#)
- shared mode [39-14](#)
- support for [1-12](#)
- SSH
 - configuring [11-47](#)
 - cryptographic software image [11-45](#)
 - described [1-5, 11-46](#)
 - encryption methods [11-46](#)
 - user authentication methods, supported [11-46](#)
- SSL
 - configuration guidelines [11-53](#)
 - configuring a secure HTTP client [11-55](#)
 - configuring a secure HTTP server [11-54](#)
 - cryptographic software image [11-50](#)
 - described [11-50](#)
 - monitoring [11-56](#)
- SSM
 - address management restrictions [49-15](#)
 - CGMP limitations [49-15](#)
 - components [49-13](#)
 - configuration guidelines [49-15](#)
 - configuring [49-13, 49-16](#)
 - differs from Internet standard multicast [49-13](#)
 - IGMP snooping [49-15](#)
 - IGMPv3 [49-13](#)
 - IGMPv3 Host Signalling [49-14](#)
 - IP address range [49-14](#)
 - monitoring [49-16](#)
 - operations [49-14](#)
 - PIM [49-13](#)
 - state maintenance limitations [49-15](#)
- SSM mapping [49-16](#)
 - configuration guidelines [49-16](#)
 - configuring [49-16, 49-19](#)
 - DNS-based [49-18, 49-19](#)
 - monitoring [49-21](#)
 - overview [49-17](#)
 - restrictions [49-17](#)
 - static [49-17, 49-19](#)
 - static traffic forwarding [49-20](#)
- standby command switch
 - configuring
 - considerations [6-11](#)
 - defined [6-2](#)
 - priority [6-10](#)
 - requirements [6-3](#)
 - virtual IP address [6-11](#)
 - See also cluster standby group and HSRP
- standby group, cluster
 - See cluster standby group and HSRP
- standby ip command [45-6](#)
- standby links [25-2](#)
- standby router [45-1](#)
- standby timers, HSRP [45-11](#)
- startup configuration
 - booting
 - manually [4-18](#)
 - specific image [4-19](#)
 - clearing [A-18](#)
 - configuration file
 - automatically downloading [4-17](#)
 - specifying the filename [4-17](#)
 - default boot configuration [4-17](#)
- static access ports
 - assigning to VLAN [16-9](#)
 - defined [14-3, 16-3](#)
- static addresses
 - See addresses
- static IP routing [1-12](#)
- static MAC addressing [1-8](#)
- static route primary interface, configuring [47-10](#)
- static routes
 - configuring [41-88](#)
 - configuring for IPv6 [42-19](#)

- understanding [42-6](#)
- static routing [41-3](#)
- static routing support, enhanced object tracking [47-10](#)
- static SSM mapping [49-17](#), [49-19](#)
- static traffic forwarding [49-20](#)
- static VLAN membership [16-2](#)
- statistics
 - 802.1X [13-17](#)
 - 802.1x [12-64](#)
 - CDP [32-5](#)
 - interface [14-25](#)
 - IP multicast routing [49-61](#)
 - LLDP [31-10](#)
 - LLDP-MED [31-10](#)
 - NMSP [31-10](#)
 - OSPF [41-32](#)
 - QoS ingress and egress [39-78](#)
 - RMON group Ethernet [34-5](#)
 - RMON group history [34-5](#)
 - SNMP input and output [36-18](#)
 - VTP [17-16](#)
- sticky learning [29-9](#)
- storm control
 - configuring [29-3](#)
 - described [29-1](#)
 - disabling [29-5](#)
 - displaying [29-21](#)
 - support for [1-3](#)
 - thresholds [29-1](#)
- STP
 - accelerating root port selection [23-4](#)
 - and REP [24-6](#)
 - BackboneFast
 - described [23-5](#)
 - disabling [23-14](#)
 - enabling [23-13](#)
 - BPDUs filtering
 - described [23-3](#)
 - disabling [23-12](#)
 - enabling [23-12](#)
 - BPDUs guard
 - described [23-2](#)
 - disabling [23-12](#)
 - enabling [23-11](#)
 - BPDUs message exchange [21-3](#)
 - configuration guidelines [21-12](#), [23-10](#)
 - configuring
 - forward-delay time [21-21](#)
 - hello time [21-20](#)
 - maximum aging time [21-21](#)
 - path cost [21-18](#)
 - port priority [21-17](#)
 - root switch [21-14](#)
 - secondary root switch [21-16](#)
 - spanning-tree mode [21-13](#)
 - switch priority [21-19](#)
 - transmit hold-count [21-22](#)
 - counters, clearing [21-22](#)
 - default configuration [21-11](#)
 - default optional feature configuration [23-9](#)
 - designated port, defined [21-3](#)
 - designated switch, defined [21-3](#)
 - detecting indirect link failures [23-5](#)
 - disabling [21-14](#)
 - displaying status [21-22](#)
 - EtherChannel guard
 - described [23-7](#)
 - disabling [23-14](#)
 - enabling [23-14](#)
 - extended system ID
 - effects on root switch [21-14](#)
 - effects on the secondary root switch [21-16](#)
 - overview [21-4](#)
 - unexpected behavior [21-15](#)
 - features supported [1-6](#)
 - IEEE 802.1D and bridge ID [21-4](#)
 - IEEE 802.1D and multicast addresses [21-8](#)
 - IEEE 802.1t and VLAN identifier [21-4](#)

- inferior BPDU [21-3](#)
- instances supported [21-9](#)
- interface state, blocking to forwarding [23-2](#)
- interface states
 - blocking [21-5](#)
 - disabled [21-7](#)
 - forwarding [21-5, 21-6](#)
 - learning [21-6](#)
 - listening [21-6](#)
 - overview [21-4](#)
- interoperability and compatibility among modes [21-10](#)
- Layer 2 protocol tunneling [20-7](#)
- limitations with IEEE 802.1Q trunks [21-10](#)
- load sharing
 - overview [16-21](#)
 - using path costs [16-23](#)
 - using port priorities [16-21](#)
- loop guard
 - described [23-9](#)
 - enabling [23-15](#)
- modes supported [21-9](#)
- multicast addresses, effect of [21-8](#)
- optional features supported [1-7](#)
- overview [21-2](#)
- path costs [16-23](#)
- Port Fast
 - described [23-2](#)
 - enabling [23-10](#)
- port priorities [16-22](#)
- preventing root switch selection [23-8](#)
- protocols supported [21-9](#)
- redundant connectivity [21-8](#)
- root guard
 - described [23-8](#)
 - enabling [23-15](#)
- root port, defined [21-3](#)
- root switch
 - configuring [21-15](#)
 - effects of extended system ID [21-4, 21-14](#)
 - election [21-3](#)
 - unexpected behavior [21-15](#)
 - shutdown Port Fast-enabled port [23-2](#)
 - status, displaying [21-22](#)
 - superior BPDU [21-3](#)
 - timers, described [21-20](#)
 - UplinkFast
 - described [23-3](#)
 - enabling [23-13](#)
 - VLAN-bridge [21-10](#)
- stratum, NTP [7-2](#)
- stub areas, OSPF [41-28](#)
- stub routing, EIGRP [41-39](#)
- subdomains, private VLAN [19-1](#)
- subnet mask [41-5](#)
- subnet zero [41-6](#)
- success response, VMPS [16-25](#)
- summer time [7-6](#)
- SunNet Manager [1-4](#)
- supernet [41-6](#)
- supported port-based authentication methods [12-7](#)
- SVI autostate exclude
 - configuring [14-22](#)
 - defined [14-5](#)
- SVI link state [14-5](#)
- SVIs
 - and IP unicast routing [41-3](#)
 - and router ACLs [38-4](#)
 - connecting VLANs [14-7](#)
 - defined [14-4](#)
 - routing between VLANs [16-2](#)
- switch [42-2](#)
- switch clustering technology [6-1](#)
 - See also clusters, switch
- switch console port [1-5](#)
- Switch Database Management
 - See SDM
- switched packets, ACLs on [38-38](#)

Switched Port Analyzer

See SPAN

switched ports [14-2](#)switchport backup interface [25-4, 25-5](#)switchport block multicast command [29-8](#)switchport block unicast command [29-8](#)switchport command [14-13](#)switchport mode dot1q-tunnel command [20-6](#)switchport protected command [29-7](#)

switch priority

MSTP [22-21](#)STP [21-19](#)switch software features [1-1](#)

switch virtual interface

See SVI

synchronization, BGP [41-45](#)

syslog

See system message logging

system capabilities TLV [31-1](#)

system clock

configuring

daylight saving time [7-6](#)manually [7-4](#)summer time [7-6](#)time zones [7-5](#)displaying the time and date [7-5](#)overview [7-1](#)

See also NTP

system description TLV [31-1](#)

system message logging

default configuration [35-3](#)defining error message severity levels [35-8](#)disabling [35-4](#)displaying the configuration [35-13](#)enabling [35-4](#)facility keywords, described [35-13](#)level keywords, described [35-9](#)limiting messages [35-10](#)message format [35-2](#)overview [35-1](#)sequence numbers, enabling and disabling [35-8](#)setting the display destination device [35-5](#)synchronizing log messages [35-6](#)syslog facility [1-13](#)time stamps, enabling and disabling [35-7](#)

UNIX syslog servers

configuring the daemon [35-12](#)configuring the logging facility [35-12](#)facilities supported [35-13](#)

system MTU

and IS-IS LSPs [41-66](#)system MTU and IEEE 802.1Q tunneling [20-5](#)

system name

default configuration [7-8](#)default setting [7-8](#)manual configuration [7-8](#)

See also DNS

system name TLV [31-1](#)system prompt, default setting [7-7, 7-8](#)system resources, optimizing [10-1](#)

system routing

IS-IS [41-62](#)ISO IGRP [41-62](#)

T

TACACS+

accounting, defined [11-11](#)authentication, defined [11-11](#)authorization, defined [11-11](#)

configuring

accounting [11-17](#)authentication key [11-13](#)authorization [11-16](#)login authentication [11-14](#)default configuration [11-13](#)displaying the configuration [11-18](#)identifying the server [11-13](#)

- in clusters [6-14](#)
 - limiting the services to the user [11-16](#)
 - operation of [11-12](#)
 - overview [11-10](#)
 - support for [1-10](#)
 - tracking services accessed by user [11-17](#)
- tagged packets
 - IEEE 802.1Q [20-3](#)
 - Layer 2 protocol [20-7](#)
- tar files
 - creating [A-6](#)
 - displaying the contents of [A-6](#)
 - extracting [A-7](#)
 - image file format [A-22](#)
- TCL script, registering and defining with embedded event manager [37-6](#)
- TDR [1-14](#)
- Telnet
 - accessing management interfaces [2-10](#)
 - number of connections [1-5](#)
 - setting a password [11-6](#)
- temperature alarms, configuring [3-7, 3-8](#)
- temporary self-signed certificate [11-51](#)
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- terminal lines, setting a password [11-6](#)
- TFTP
 - configuration files
 - downloading [A-10](#)
 - preparing the server [A-10](#)
 - uploading [A-11](#)
 - configuration files in base directory [4-7](#)
 - configuring for autoconfiguration [4-7](#)
 - image files
 - deleting [A-25](#)
 - downloading [A-24](#)
 - preparing the server [A-24](#)
 - uploading [A-26](#)
 - limiting access by servers [36-16](#)
 - TFTP server [1-4](#)
 - threshold, traffic level [29-2](#)
 - threshold monitoring, IP SLAs [46-6](#)
 - time
 - See NTP and system clock
 - Time Domain Reflector
 - See TDR
 - time-range command [38-16](#)
 - time ranges in ACLs [38-16](#)
 - time stamps in log messages [35-7](#)
 - time zones [7-5](#)
 - TLVs
 - defined [31-1](#)
 - LLDP [31-1](#)
 - LLDP-MED [31-2](#)
 - Token Ring VLANs
 - support for [16-6](#)
 - VTP support [17-4](#)
 - ToS [1-11](#)
 - traceroute, Layer 2
 - and ARP [36-12](#)
 - and CDP [36-11](#)
 - broadcast traffic [36-11](#)
 - described [36-11](#)
 - IP addresses and subnets [36-12](#)
 - MAC addresses and VLANs [36-12](#)
 - multicast traffic [36-12](#)
 - multiple devices on a port [36-12](#)
 - unicast traffic [36-11](#)
 - usage guidelines [36-11](#)
 - traceroute command [36-13](#)
 - See also IP traceroute
 - tracked lists
 - configuring [47-3](#)
 - types [47-3](#)
 - tracked objects
 - by Boolean expression [47-4](#)
 - by threshold percentage [47-6](#)
 - by threshold weight [47-5](#)

- tracking interface line-protocol state [47-2](#)
- tracking IP routing state [47-2](#)
- tracking objects [47-1](#)
- tracking process [47-1](#)
- track state, tracking IP SLAs [47-9](#)
- traffic
 - blocking flooded [29-8](#)
 - fragmented [38-5](#)
 - fragmented IPv6 [44-2](#)
 - unfragmented [38-5](#)
- traffic policing [1-11](#)
- traffic suppression [29-1](#)
- transmit hold-count
 - see STP
- transparent mode, VTP [17-3](#)
- trap-door mechanism [4-2](#)
- traps
 - configuring MAC address notification [7-15, 7-17, 7-18](#)
 - configuring managers [36-11](#)
 - defined [36-3](#)
 - enabling [7-15, 7-17, 7-18, 36-11](#)
 - notification types [36-12](#)
 - overview [36-1, 36-4](#)
- triggering alarm options
 - configurable relay [3-3](#)
 - methods [3-3](#)
 - SNMP traps [3-4](#)
 - syslog messages [3-4](#)
- troubleshooting
 - connectivity problems [36-9, 36-11, 36-12](#)
 - CPU utilization [36-20](#)
 - detecting unidirectional links [33-1](#)
 - displaying crash information [36-19](#)
 - PIMv1 and PIMv2 interoperability problems [49-34](#)
 - setting packet forwarding [36-17](#)
 - SFP security and identification [36-9](#)
 - show forward command [36-17](#)
 - with CiscoWorks [36-4](#)
 - with debug commands [36-15](#)
 - with ping [36-10](#)
 - with system message logging [35-1](#)
 - with traceroute [36-13](#)
- trunk failover
 - See link-state tracking
- trunking encapsulation [1-7](#)
- trunk ports
 - configuring [16-17](#)
 - defined [14-3, 16-3](#)
- trunks
 - allowed-VLAN list [16-18](#)
 - load sharing
 - setting STP path costs [16-23](#)
 - using STP port priorities [16-21, 16-22](#)
 - native VLAN for untagged traffic [16-20](#)
 - parallel [16-23](#)
 - pruning-eligible list [16-19](#)
 - to non-DTP device [16-15](#)
- trusted boundary for QoS [39-38](#)
- trusted port states
 - between QoS domains [39-40](#)
 - classification options [39-5](#)
 - ensuring port security for IP phones [39-38](#)
 - support for [1-11](#)
 - within a QoS domain [39-36](#)
- trustpoints, CA [11-50](#)
- tunneling
 - defined [20-1](#)
 - IEEE 802.1Q [20-1](#)
 - Layer 2 protocol [20-8](#)
- tunnel ports
 - defined [16-4](#)
 - described [14-3, 20-1](#)
 - IEEE 802.1Q, configuring [20-6](#)
 - incompatibilities with other features [20-5](#)
- twisted-pair Ethernet, detecting unidirectional links [33-1](#)
- type of service
 - See ToS

U

UDLD

- configuration guidelines [33-4](#)
- default configuration [33-4](#)
- disabling
 - globally [33-5](#)
 - on fiber-optic interfaces [33-5](#)
 - per interface [33-5](#)
- echoing detection mechanism [33-2](#)
- enabling
 - globally [33-5](#)
 - per interface [33-5](#)
- Layer 2 protocol tunneling [20-10](#)
- link-detection mechanism [33-1](#)
- neighbor database [33-2](#)
- overview [33-1](#)
- resetting an interface [33-6](#)
- status, displaying [33-6](#)
- support for [1-6](#)

UDP, configuring [41-14](#)

UDP jitter, configuring [46-9](#)

UDP jitter operation, IP SLAs [46-9](#)

unauthorized ports with IEEE 802.1x [12-10](#)

- unicast MAC address filtering [1-5](#)
 - and adding static addresses [7-21](#)
 - and broadcast MAC addresses [7-20](#)
 - and CPU packets [7-20](#)
 - and multicast addresses [7-20](#)
 - and router MAC addresses [7-20](#)
 - configuration guidelines [7-20](#)
 - described [7-20](#)

unicast storm [29-1](#)

unicast storm control command [29-4](#)

unicast traffic, blocking [29-8](#)

UniDirectional Link Detection protocol

See UDLD

UNIX syslog servers

daemon configuration [35-12](#)

facilities supported [35-13](#)

message logging configuration [35-12](#)

unrecognized Type-Length-Value (TLV) support [17-4](#)

upgrading software images

See downloading

UplinkFast

described [23-3](#)

disabling [23-13](#)

enabling [23-13](#)

uploading

configuration files

preparing [A-10, A-12, A-15](#)

reasons for [A-8](#)

using FTP [A-14](#)

using RCP [A-17](#)

using TFTP [A-11](#)

image files

preparing [A-24, A-27, A-31](#)

reasons for [A-22](#)

using FTP [A-29](#)

using RCP [A-33](#)

using TFTP [A-26](#)

User Datagram Protocol

See UDP

user EXEC mode [2-2](#)

username-based authentication [11-7](#)

V

version-dependent transparent mode [17-4](#)

virtual IP address

cluster standby group [6-11](#)

command switch [6-11](#)

Virtual Private Network

See VPN

virtual router [45-1, 45-2](#)

virtual switches and PAgP [40-5](#)

vlan.dat file [16-5](#)

VLAN 1, disabling on a trunk port [16-19](#)

- VLAN 1 minimization [16-18](#)
- VLAN ACLs
 - See VLAN maps
- vlan-assignment response, VMPS [16-25](#)
- VLAN blocking, REP [24-12](#)
- VLAN configuration
 - at bootup [16-7](#)
 - saving [16-7](#)
- VLAN configuration mode [2-2](#)
- VLAN database
 - and startup configuration file [16-7](#)
 - and VTP [17-1](#)
 - VLAN configuration saved in [16-7](#)
 - VLANs saved in [16-4](#)
- vlan dot1q tag native command [20-4](#)
- VLAN filtering and SPAN [30-6](#)
- vlan global configuration command [16-7](#)
- VLAN ID, discovering [7-23](#)
- VLAN link state [14-5](#)
- VLAN load balancing
 - REP [24-4](#)
- VLAN load balancing, triggering [24-5](#)
- VLAN load balancing on flex links [25-2](#)
 - configuration guidelines [25-8](#)
- VLAN management domain [17-2](#)
- VLAN Management Policy Server
 - See VMPS
- VLAN map entries, order of [38-30](#)
- VLAN maps
 - applying [38-34](#)
 - common uses for [38-34](#)
 - configuration guidelines [38-30](#)
 - configuring [38-29](#)
 - creating [38-31](#)
 - defined [38-2](#)
 - denying access to a server example [38-35](#)
 - denying and permitting packets [38-31](#)
 - displaying [38-41](#)
 - examples of ACLs and VLAN maps [38-32](#)
 - removing [38-34](#)
 - support for [1-8](#)
 - wiring closet configuration example [38-35](#)
- VLAN membership
 - confirming [16-28](#)
 - modes [16-3](#)
- VLAN Query Protocol
 - See VQP
- VLANs
 - adding [16-8](#)
 - adding to VLAN database [16-8](#)
 - aging dynamic addresses [21-9](#)
 - allowed on trunk [16-18](#)
 - and spanning-tree instances [16-3, 16-6, 16-11](#)
 - configuration guidelines, extended-range VLANs [16-11](#)
 - configuration guidelines, normal-range VLANs [16-6](#)
 - configuring [16-1](#)
 - configuring IDs 1006 to 4094 [16-11](#)
 - connecting through SVIs [14-7](#)
 - creating [16-8](#)
 - customer numbering in service-provider networks [20-3](#)
 - default configuration [16-7](#)
 - deleting [16-9](#)
 - described [14-2, 16-1](#)
 - displaying [16-14](#)
 - extended-range [16-1, 16-10](#)
 - features [1-7](#)
 - illustrated [16-2](#)
 - internal [16-11](#)
 - limiting source traffic with RSPAN [30-21](#)
 - limiting source traffic with SPAN [30-14](#)
 - modifying [16-8](#)
 - multicast [28-17](#)
 - native, configuring [16-20](#)
 - normal-range [16-1, 16-4](#)
 - number supported [1-7](#)
 - parameters [16-5](#)

- port membership modes [16-3](#)
- static-access ports [16-9](#)
- STP and IEEE 802.1Q trunks [21-10](#)
- supported [16-2](#)
- Token Ring [16-6](#)
- traffic between [16-2](#)
- VLAN-bridge STP [21-10, 51-2](#)
- VTP modes [17-3](#)
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks [16-14](#)
- VMPS
 - administering [16-29](#)
 - configuration example [16-30](#)
 - configuration guidelines [16-26](#)
 - default configuration [16-26](#)
 - description [16-24](#)
 - dynamic port membership
 - described [16-25](#)
 - reconfirming [16-28](#)
 - troubleshooting [16-30](#)
 - entering server address [16-27](#)
 - mapping MAC addresses to VLANs [16-24](#)
 - monitoring [16-29](#)
 - reconfirmation interval, changing [16-28](#)
 - reconfirming membership [16-28](#)
 - retry count, changing [16-29](#)
- voice aware 802.1x security
 - port-based authentication
 - configuring [12-37](#)
 - described [12-29, 12-37](#)
- voice-over-IP [18-1](#)
- voice VLAN
 - Cisco 7960 phone, port connections [18-1](#)
 - configuration guidelines [18-3](#)
 - configuring IP phones for data traffic
 - override CoS of incoming frame [18-6](#)
 - trust CoS priority of incoming frame [18-6](#)
 - configuring ports for voice traffic in
 - 802.1p priority tagged frames [18-5](#)
 - 802.1Q frames [18-4](#)
 - connecting to an IP phone [18-4](#)
 - default configuration [18-3](#)
 - described [18-1](#)
 - displaying [18-6](#)
 - IP phone data traffic, described [18-2](#)
 - IP phone voice traffic, described [18-2](#)
- VPN
 - configuring routing in [41-81](#)
 - forwarding [41-74](#)
 - in service provider networks [41-71](#)
 - routes [41-72](#)
- VPN routing and forwarding table
 - See VRF
- VQP [1-7, 16-24](#)
- VRF
 - defining [41-74](#)
 - tables [41-71](#)
- VRF-aware services
 - ARP [41-78](#)
 - configuring [41-77](#)
 - ftp [41-80](#)
 - HSRP [41-79](#)
 - ping [41-78](#)
 - SNMP [41-78](#)
 - syslog [41-79](#)
 - tftp [41-80](#)
 - traceroute [41-80](#)
- VTP
 - adding a client to a domain [17-15](#)
 - advertisements [16-16, 17-3](#)
 - and extended-range VLANs [16-3, 17-1](#)
 - and normal-range VLANs [16-2, 17-1](#)
 - client mode, configuring [17-11](#)
 - configuration
 - guidelines [17-8](#)
 - requirements [17-10](#)
 - saving [17-8](#)

- configuration requirements [17-10](#)
- configuration revision number
 - guideline [17-15](#)
 - resetting [17-16](#)
- consistency checks [17-4](#)
- default configuration [17-7](#)
- described [17-1](#)
- domain names [17-8](#)
- domains [17-2](#)
- Layer 2 protocol tunneling [20-7](#)
- modes
 - client [17-3](#)
 - off [17-3](#)
 - server [17-3](#)
 - transitions [17-3](#)
 - transparent [17-3](#)
- monitoring [17-16](#)
- passwords [17-8](#)
- pruning
 - disabling [17-14](#)
 - enabling [17-14](#)
 - examples [17-6](#)
 - overview [17-5](#)
 - support for [1-7](#)
- pruning-eligible list, changing [16-19](#)
- server mode, configuring [17-10, 17-13](#)
- statistics [17-16](#)
- support for [1-7](#)
- Token Ring support [17-4](#)
- transparent mode, configuring [17-10](#)
- using [17-1](#)
- Version
 - enabling [17-13](#)
- version, guidelines [17-9](#)
- Version 1 [17-4](#)
- Version 2
 - configuration guidelines [17-9](#)
 - overview [17-4](#)
- Version 3

- overview [17-4](#)

W

WCCP

- authentication [48-3](#)
- configuration guidelines [48-5](#)
- default configuration [48-5](#)
- described [48-1](#)
- displaying [48-9](#)
- dynamic service groups [48-3](#)
- enabling [48-6](#)
- features unsupported [48-4](#)
- forwarding method [48-3](#)
- Layer-2 header rewrite [48-3](#)
- MD5 security [48-3](#)
- message exchange [48-2](#)
- monitoring and maintaining [48-9](#)
- negotiation [48-3](#)
- packet redirection [48-3](#)
- packet-return method [48-3](#)
- redirecting traffic received from a client [48-6](#)
- setting the password [48-6](#)
- unsupported WCCPv2 features [48-4](#)
- web authentication [12-16](#)
 - configuring [13-16 to ??](#)
 - described [1-8](#)
- web-based authentication
 - customizeable web pages [13-6](#)
 - description [13-1](#)
- web-based authentication, interactions with other features [13-7](#)
- Web Cache Communication Protocol
 - See WCCP
- weighted tail drop
 - See WTD
- weight thresholds in tracked lists [47-5](#)
- wired location service
 - configuring [31-8](#)

- displaying [31-10](#)
- location TLV [31-2](#)
- understanding [31-3](#)

WTD

- described [39-13](#)
- setting thresholds
 - egress queue-sets [39-71](#)
 - ingress queues [39-67](#)
- support for [1-12](#)

X

- Xmodem protocol [36-2](#)