



## INDEX

---

### A

aaa accounting dot1x command [2-1](#)  
aaa authentication dot1x command [2-3](#)  
AAA methods [2-3](#)  
access control entries  
    See ACEs  
access control lists  
    See ACLs  
access groups  
    IP [2-150](#)  
    MAC, displaying [2-534](#)  
    matching for QoS classification [2-286](#)  
access list, IPv6 [2-219](#)  
access mode [2-688](#)  
access ports [2-688](#)  
ACEs [2-90, 2-331](#)  
ACLs  
    as match criteria for QoS classes [2-286](#)  
    deny [2-88](#)  
    displaying [2-412](#)  
    for non-IP protocols [2-264](#)  
    IP [2-150](#)  
    on Layer 2 interfaces [2-150](#)  
    permit [2-329](#)  
action command [2-5](#)  
address aliasing [2-309](#)  
aggregate policers  
    applying [2-342](#)  
    creating [2-337](#)  
    displaying [2-566](#)  
    QoS [2-339](#)  
aggregate-port learner [2-318](#)

alarm-contact command [2-7](#)  
alarm-contact status, displaying [2-445](#)  
allowed VLANs [2-704](#)  
archive download-sw command [2-9](#)  
archive tar command [2-12](#)  
archive upload-sw command [2-15](#)  
arp (boot loader) command [A-2](#)  
arp access-list command [2-17](#)  
attaching policy maps to interfaces [2-393](#)  
authorization state of controlled port [2-104](#)  
autonegotiation of duplex mode [2-116](#)

---

### B

backup interfaces  
    configuring [2-681](#)  
    displaying [2-467](#)  
bandwidth, configuring for QoS [2-19](#)  
bandwidth command [2-19](#)  
boot (boot loader) command [A-3](#)  
boot config-file command [2-23](#)  
boot enable-break command [2-24](#)  
boot helper command [2-25](#)  
boot helper-config file command [2-26](#)  
booting  
    Cisco IOS image [2-29](#)  
    displaying environment variables [2-417](#)  
    interrupting [2-24](#)  
    manually [2-27](#)  
boot loader  
    accessing [A-1](#)  
    booting  
        Cisco IOS image [A-3](#)

- helper image [2-25](#)
- directories
  - creating [A-18](#)
  - displaying a list of [A-8](#)
  - removing [A-22](#)
- displaying
  - available commands [A-13](#)
  - memory heap utilization [A-14](#)
  - version [A-29](#)
- environment variables
  - described [A-23](#)
  - displaying settings [A-23](#)
  - location of [A-24](#)
  - setting [A-23](#)
  - unsetting [A-27](#)
- files
  - copying [A-6](#)
  - deleting [A-7](#)
  - displaying a list of [A-8](#)
  - displaying the contents of [A-5, A-19, A-26](#)
  - renaming [A-20](#)
- file system
  - formatting [A-11](#)
  - initializing flash [A-10](#)
  - running a consistency check [A-12](#)
- prompt [A-1](#)
- resetting the system [A-21](#)
- boot manual command [2-27](#)
- boot private-config-file command [2-28](#)
- boot system command [2-29](#)
- BPDU filtering, for spanning tree [2-626, 2-664](#)
- BPDU guard, for spanning tree [2-628, 2-664](#)
- broadcast storm control [2-674](#)
- bundling characteristics, UNI [2-126](#)
- burst bytes, in QoS policers [2-333, 2-338](#)
- CBWFQ, configuring [2-19](#)
- CDP, enabling protocol tunneling for [2-244](#)
- CFM [2-317](#)
- CFM as OAM protocol [2-317](#)
- channel-group command [2-30](#)
- channel-protocol command [2-34](#)
- child policy maps [2-395](#)
- class-based traffic shaping [2-410](#)
- class-based weighted fair queuing
  - See [CBWFQ](#)
- class command [2-36](#)
- class-map command [2-38](#)
- class-map configuration mode [2-38](#)
- class maps
  - creating [2-38](#)
  - defining the match criteria [2-287, 2-289](#)
  - displaying [2-421](#)
  - matching in [2-38](#)
- class of service
  - See [CoS](#)
- clear ip arp inspection log command [2-40](#)
- clear ip arp inspection statistics command [2-41](#)
- clear ipc command [2-44](#)
- clear ipv6 dhcp conflict command [2-45](#)
- clear l2protocol-tunnel counters command [2-46](#)
- clear lacp command [2-47](#)
- clear logging onboard command [2-48](#)
- clear mac address-table command [2-49, 2-50](#)
- clear pagp command [2-51, 2-55](#)
- clear policer cpu uni-eni counters command [2-52](#)
- clear port-security command [2-53](#)
- clear spanning-tree counters command [2-56](#)
- clear spanning-tree detected-protocols command [2-57](#)
- clear vmps statistics command [2-59](#)
- command modes defined [1-1](#)
- committed information rate in QoS policers [2-333, 2-337](#)
- configuration files
  - password recovery disable considerations [A-1](#)
  - specifying the name [2-23, 2-28](#)

---

**C**

cat (boot loader) command [A-5](#)

configuring multiple interfaces [2-146](#)  
 conform-action command [2-60](#)  
 control-plane policer [2-52](#)  
 control-plane policer information, displaying [2-567](#)  
 control-plane security [2-344](#)  
 control plane statistics, clearing [2-52](#)  
 copy (boot loader) command [A-6](#)  
 copy logging onboard module command [2-62](#)  
 CoS
 

- as match criteria for QoS groups [2-287](#)
- for QoS classification [2-397](#)
- setting value in policy maps [2-397](#)

 CoS value, assigning to Layer 2 protocol packets [2-247](#)  
 CPU ASIC statistics, displaying [2-422](#)  
 CPU protection policers, displaying [C-24](#)  
 cpu traffic qos cos command [2-64](#)  
 cpu traffic qos dscp command [2-68](#)  
 cpu traffic qos precedence command [2-73](#)  
 cpu traffic qos qos-group command [2-76](#)

## D

DC power supply [2-353](#)  
 debug backup command [B-2](#)  
 debug dot1x command [B-3](#)  
 debug etherchannel command [B-4](#)  
 debug interface command [B-7](#)  
 debug ip dhcp snooping command [B-8](#)  
 debug ip igmp filter command [B-9](#)  
 debug ip igmp max-groups command [B-10](#)  
 debug ip igmp snooping command [B-11](#)  
 debug ip sla error twamp connection command [B-12](#)  
 debug ip sla error twamp control reflector command [B-14](#)  
 debug ip sla error twamp control server command [B-16](#)  
 debug ip sla error twamp session command [B-18](#)  
 debug ip sla trace twamp connection command [B-20](#)  
 debug ip sla trace twamp control reflector command [B-22](#)  
 debug ip sla trace twamp control server command [B-24](#)  
 debug ip sla trace twamp session command [B-26](#)  
 debug ip verify source packet command [B-28](#)  
 debug lacp command [B-29](#)  
 debug mac-notification command [B-30](#)  
 debug matm command [B-31](#)  
 debug matm move update command [B-32](#)  
 debug monitor command [B-33](#)  
 debug mvrdbg command [B-34](#)  
 debug nvram command [B-35](#)  
 debug pagp command [B-36](#)  
 debug platform acl command [B-37](#)  
 debug platform backup interface command [B-38](#)  
 debug platform cfm command [B-39](#)  
 debug platform cpu-queues command [B-40](#)  
 debug platform dot1ad command [B-42](#)  
 debug platform dot1x command [B-43](#)  
 debug platform etherchannel command [B-44](#)  
 debug platform forw-tcam command [B-45](#)  
 debug platform ip arp inspection command [B-46](#)  
 debug platform ipc command [B-55](#)  
 debug platform ip dhcp command [B-47](#)  
 debug platform ip igmp snooping command [B-48](#)  
 debug platform ip multicast command [B-50](#)  
 debug platform ip source-guard command [B-52](#)  
 debug platform led command [B-56](#)  
 debug platform matm command [B-57](#)  
 debug platform messaging application command [B-58](#)  
 debug platform phy command [B-59](#)  
 debug platform pm command [B-61](#)  
 debug platform policer cpu uni-eni command [B-63](#)  
 debug platform port-asic command [B-64](#)  
 debug platform port-security command [B-65](#)  
 debug platform qos-acl-tcam command [B-66](#)  
 debug platform qos-manager command [B-67](#)  
 debug platform remote-commands command [B-68](#)  
 debug platform rep command [B-69](#)  
 debug platform resource-manager command [B-70](#)  
 debug platform snmp command [B-71](#)  
 debug platform span command [B-72](#)  
 debug platform supervisor-asic command [B-73](#)

- debug platform sw-bridge command [B-74](#)
- debug platform tcam command [B-75](#)
- debug platform uddl command [B-77](#)
- debug platform vlan command [B-78](#)
- debug pm command [B-79](#)
- debug port-security command [B-81](#)
- debug qos-manager command [B-83](#)
- debug rep command [B-82](#)
- debug spanning-tree bpdu command [B-86](#)
- debug spanning-tree bpdu-opt command [B-87](#)
- debug spanning-tree command [B-84](#)
- debug spanning-tree mstp command [B-88](#)
- debug spanning-tree switch command [B-90](#)
- debug sw-vlan command [B-92](#)
- debug sw-vlan ifs command [B-93](#)
- debug sw-vlan notification command [B-94](#)
- debug uddl command [B-96](#)
- debug vqpc command [B-98](#)
- default policer configuration
  - NNIs [C-26](#)
  - UNIs [C-25](#)
- define interface-range command [2-78](#)
- delete (boot loader) command [A-7](#)
- delete command [2-80](#)
- deny (ARP access-list configuration) command [2-81](#)
- deny (IPv6) command [2-83](#)
- deny command [2-88](#)
- detect mechanism, causes [2-117](#)
- DHCP snooping
  - accepting untrusted packets from edge switch [2-175](#)
  - enabling
    - on a VLAN [2-181](#)
    - option 82 [2-173, 2-175](#)
    - trust on an interface [2-179](#)
  - error recovery timer [2-119](#)
  - rate limiting [2-178](#)
- DHCP snooping binding database
  - binding file, configuring [2-171](#)
  - bindings
    - adding [2-169](#)
    - deleting [2-169](#)
    - displaying [2-488](#)
  - clearing database agent statistics [2-42](#)
  - database agent, configuring [2-171](#)
  - displaying
    - binding entries [2-488](#)
    - database agent status [2-490, 2-492](#)
    - renewing [2-369](#)
- diagnostic monitor command [2-91](#)
- diagnostic schedule test command [2-93](#)
- diagnostic start test command [2-95](#)
- differentiated service code point
  - See DSCP
- Digital Optical Monitoring
  - see DoM
- dir (boot loader) command [A-8](#)
- directories, deleting [2-80](#)
- DoM
  - displaying supported transceivers [2-479, 2-616, 2-617](#)
- domains, CFM [2-317](#)
- dot1x default command [2-97](#)
- dot1x host-mode command [2-98](#)
- dot1x initialize command [2-100](#)
- dot1x max-req command [2-101, 2-103](#)
- dot1x port-control command [2-104](#)
- dot1x re-authenticate command [2-106](#)
- dot1x reauthentication command [2-107](#)
- dot1x supplicant force-multicast command [2-108](#)
- dot1x system-auth-control command [2-109](#)
- dot1x test eapol-capable command [2-110](#)
- dot1x test timeout command [2-111](#)
- dot1x timeout command [2-112](#)
- dot1x violation-mode command [2-114](#)
- drop eligibility indicator [2-399](#)
- drop eligibility indicator bit [2-289](#)
- dropping packets, with ACL matches [2-5](#)
- drop threshold, Layer 2 protocol tunneling [2-244](#)
- DSCP

- as match criteria for QoS groups [2-291, 2-297](#)
  - for QoS traffic marking [2-401](#)
  - setting in policy maps [2-401](#)
- dual IPv4 and IPv6 templates [2-324](#)
- dual-purpose uplink ports, selecting the type [2-302](#)
- duplex command [2-115](#)
- dynamic-access ports
  - configuring [2-679](#)
  - restrictions [2-680](#)
- dynamic ARP inspection
  - ARP ACLs
    - apply to a VLAN [2-155](#)
    - define [2-17](#)
    - deny packets [2-81](#)
    - display [2-416](#)
    - permit packets [2-322](#)
  - clear
    - log buffer [2-40](#)
    - statistics [2-41](#)
  - display
    - ARP ACLs [2-416](#)
    - configuration and operating state [2-483](#)
    - log buffer [2-483](#)
    - statistics [2-483](#)
    - trust state and rate limit [2-483](#)
  - enable per VLAN [2-164](#)
  - error detection for [2-117](#)
  - error recovery timer [2-119](#)
  - log buffer
    - clear [2-40](#)
    - configure [2-159](#)
    - display [2-483](#)
  - rate-limit incoming ARP packets [2-157](#)
  - statistics
    - clear [2-41](#)
    - display [2-483](#)
  - trusted interface state [2-161](#)
  - type of packet logged [2-165](#)
  - validation checks [2-162](#)

Dynamic Host Configuration Protocol (DHCP)  
See DHCP snooping

---

## E

- EAP-request/identity frame
  - maximum number to send [2-103](#)
  - response time before retransmitting [2-112](#)
- E-LMI
  - enabling [2-124](#)
  - mapping [2-126](#)
- environment variables, displaying [2-417](#)
- errdisable detect cause command [2-117](#)
- errdisable recovery command [2-119](#)
- error conditions, displaying [2-449](#)
- error disable detection [2-117](#)
- error-disabled interfaces, displaying [2-467](#)
- EtherChannel
  - assigning Ethernet interface to channel group [2-30](#)
  - creating port-channel logical interface [2-144](#)
  - debug EtherChannel/PAGP, display [B-4](#)
  - debug platform-specific events, display [B-44](#)
  - displaying [2-453](#)
  - enabling Layer 2 protocol tunneling for
    - LACP [2-245](#)
    - PAGP [2-245](#)
    - UDLD [2-245](#)
  - interface information, displaying [2-467](#)
  - LACP
    - clearing channel-group information [2-47](#)
    - debug messages, display [B-29](#)
    - displaying [2-521](#)
    - modes [2-30](#)
    - port priority for hot-standby ports [2-248](#)
    - restricting a protocol [2-34](#)
    - system priority [2-250](#)
  - load-distribution methods [2-349](#)
  - PAGP
    - aggregate-port learner [2-318](#)

- clearing channel-group information [2-51](#)
- debug messages, display [B-36](#)
- displaying [2-562](#)
- error detection for [2-117](#)
- error recovery timer [2-119](#)
- learn method [2-318](#)
- modes [2-30](#)
- physical-port learner [2-318](#)
- priority of interface for transmitted traffic [2-320](#)

Ethernet controller, internal register display [2-424](#)

ethernet dot1ad command [2-121](#)

ethernet evc command [2-123](#)

ethernet lmi ce-vlan map command [2-124, 2-126](#)

ethernet lmi command [2-124](#)

ethernet lmi global command [2-124](#)

Ethernet Local Management Interface

- See E-LMI

ethernet loopback interface configuration command [2-128](#)

ethernet loopback privileged EXEC command [2-131](#)

ethernet oam remote-failure command [2-133](#)

Ethernet service

- debugging [B-5](#)
- displaying [2-458](#)

Ethernet service instance [2-389](#)

Ethernet service interfaces [2-461](#)

Ethernet statistics, collecting [2-385](#)

Ethernet UNI configuration [2-135](#)

ethernet uni id command [2-137](#)

Ethernet virtual connections

- See EVCs

EVC configuration mode [2-123](#)

EVCs [2-123](#)

- and VLANs [2-135](#)
- service instances [2-389](#)
- UNI counts [2-727](#)

EVC service

- point-to-multipoint [2-727](#)
- point-to-point [2-727](#)

exceed-action command [2-138](#)

- extended-range VLANs
  - and allowed VLAN list [2-704](#)
  - configuring [2-733](#)
- extended system ID for STP [2-634](#)
- external alarms, configuring [2-7](#)

---

## F

failure logging data

- clearing [2-48](#)
- copying [2-62](#)

fan information, displaying [2-445](#)

files, deleting [2-80](#)

flash\_init (boot loader) command [A-10](#)

Flex Links

- configuring [2-681](#)
- configuring preferred VLAN [2-683](#)
- displaying [2-467](#)

flowcontrol command [2-140](#)

format (boot loader) command [A-11](#)

forwarding packets, with ACL matches [2-5](#)

forwarding results, display [C-8](#)

frame forwarding information, displaying [C-8](#)

front-end controller counter and status information [C-10](#)

fsck (boot loader) command [A-12](#)

---

## G

global configuration mode [1-2, 1-3](#)

---

## H

hardware ACL statistics [2-412](#)

health-monitoring diagnostic testing [2-91](#)

help (boot loader) command [A-13](#)

host connection, port configuration [2-687](#)

host ports, private VLANs [2-691](#)

hw-module module logging onboard command [2-142](#)

- 
- I**
- IEEE 802.1ag Connectivity Fault Management
    - See CFM
  - IEEE 802.1Q trunk ports and native VLANs [2-738](#)
  - IEEE 802.1Q tunnel ports
    - configuring [2-688](#)
    - displaying [2-441](#)
    - limitations [2-689](#)
  - IEEE 802.1x
    - and switchport modes [2-689](#)
    - violation error recovery [2-119](#)
    - See also port-based authentication
  - IGMP filters
    - applying [2-184](#)
    - debug messages, display [B-9](#)
  - IGMP groups, setting maximum [2-186](#)
  - IGMP maximum groups, debugging [B-10](#)
  - IGMP profiles
    - creating [2-188](#)
    - displaying [2-495](#)
  - IGMP snooping
    - adding ports as a static member of a group [2-203](#)
    - displaying [2-496, 2-500, 2-501](#)
    - enabling [2-190](#)
    - enabling the configurable-leave timer [2-192](#)
    - enabling the Immediate-Leave feature [2-200](#)
    - flooding query count [2-198](#)
    - interface topology change notification behavior [2-199](#)
    - multicast table [2-498](#)
    - querier [2-194](#)
    - query solicitation [2-198](#)
    - report suppression [2-196](#)
    - switch topology change notification behavior [2-198](#)
  - images
    - See software images
  - Immediate-Leave feature, MVR [2-311](#)
  - immediate-leave processing [2-200](#)
  - Immediate-Leave processing, IPv6 [2-240](#)
  - input policy maps
    - and ACL classification [2-286](#)
    - and aggregate policers [2-339](#)
    - commands not supported in [2-347](#)
    - configuration guidelines [2-347](#)
  - interface command [2-148](#)
  - interface configuration mode [1-2, 1-4](#)
  - interface port-channel command [2-144](#)
  - interface range command [2-146](#)
  - interface-range macros [2-78](#)
  - interfaces
    - assigning Ethernet interface to channel group [2-30](#)
    - configuring [2-115](#)
    - configuring multiple [2-146](#)
    - creating port-channel logical [2-144](#)
    - debug messages, display [B-7](#)
    - disabling [2-611](#)
    - displaying the MAC address table [2-544](#)
    - restarting [2-611](#)
  - interface speed, configuring [2-672](#)
  - internal registers, displaying [2-424, 2-431](#)
  - Internet Group Management Protocol
    - See IGMP
  - invalid GBIC
    - error detection for [2-117](#)
    - error recovery timer [2-119](#)
  - ip address command [2-153](#)
  - IP addresses, setting [2-153](#)
  - IP address matching [2-284](#)
  - ip arp inspection filter vlan command [2-155](#)
  - ip arp inspection limit command [2-157](#)
  - ip arp inspection log-buffer command [2-159](#)
  - ip arp inspection trust command [2-161](#)
  - ip arp inspection validate command [2-162](#)
  - ip arp inspection vlan command [2-164](#)
  - ip arp inspection vlan logging command [2-165](#)
  - IP DHCP snooping
    - See DHCP snooping
  - ip dhcp snooping binding command [2-169](#)

- ip dhcp snooping command [2-168](#)
  - ip dhcp snooping database command [2-171](#)
  - ip dhcp snooping information option allow-untrusted command [2-175](#)
  - ip dhcp snooping information option command [2-173](#)
  - ip dhcp snooping information option format remote-id command [2-177](#)
  - ip dhcp snooping limit rate command [2-178](#)
  - ip dhcp snooping trust command [2-179](#)
  - ip dhcp snooping verify command [2-180](#)
  - ip dhcp snooping vlan command [2-181](#)
  - ip dhcp snooping vlan information option format-type circuit-id string command [2-182](#)
  - ip igmp filter command [2-184](#)
  - ip igmp max-groups command [2-186](#), [2-213](#), [2-215](#)
  - ip igmp profile command [2-188](#)
  - ip igmp snooping command [2-190](#)
  - ip igmp snooping last-member-query-interval command [2-192](#)
  - ip igmp snooping querier command [2-194](#)
  - ip igmp snooping report-suppression command [2-196](#)
  - ip igmp snooping tcn command [2-198](#)
  - ip igmp snooping tcn flood command [2-199](#)
  - ip igmp snooping vlan immediate-leave command [2-200](#)
  - ip igmp snooping vlan mrouter command [2-201](#)
  - ip igmp snooping vlan static command [2-203](#)
  - IP multicast addresses [2-308](#)
  - IP precedence, as match criteria for QoS groups [2-293](#)
  - ip sla responder twamp command [2-205](#)
  - ip sla server twamp command [2-207](#)
  - ip source binding command [2-209](#)
  - IP source guard
    - disabling [2-217](#)
    - displaying
      - binding entries [2-507](#)
      - configuration [2-508](#)
    - enabling [2-217](#)
    - static IP source bindings [2-209](#)
  - IP source guard, displaying dynamic binding entries [2-488](#)
  - ip ssh command [2-211](#)
  - IPv6 access list, deny conditions [2-83](#)
  - ipv6 access-list command [2-219](#)
  - ipv6 address dhcp command [2-221](#)
  - ipv6 dhcp client request vendor command [2-222](#)
  - ipv6 dhcp ping packets command [2-223](#)
  - ipv6 dhcp pool command [2-224](#)
  - ipv6 dhcp server command [2-227](#)
  - ipv6 mld snooping command [2-229](#)
  - ipv6 mld snooping last-listener-query count command [2-231](#)
  - ipv6 mld snooping last-listener-query-interval command [2-233](#)
  - ipv6 mld snooping listener-message-suppression command [2-235](#)
  - ipv6 mld snooping robustness-variable command [2-236](#)
  - ipv6 mld snooping tcn command [2-238](#)
  - ipv6 mld snooping vlan command [2-240](#)
  - IPv6 SDM template [2-386](#)
  - ipv6 traffic-filter command [2-242](#)
  - ip verify source command [2-217](#)
- 
- ## J
- jumbo frames
    - See MTU
- 
- ## L
- l2protocol-tunnel command [2-244](#)
  - l2protocol-tunnel cos command [2-247](#)
  - LACP
    - See EtherChannel
  - lacp port-priority command [2-248](#)
  - lacp system-priority command [2-250](#)
  - Layer 2 mode, enabling [2-677](#)
  - Layer 2 protocol ports, displaying [2-519](#)
  - Layer 2 protocol-tunnel
    - error detection for [2-117](#)
    - error recovery timer [2-119](#)



- Layer 2 protocol tunnel counters [2-46](#)
  - Layer 2 protocol tunneling error recovery [2-246](#)
  - Layer 2 traceroute
    - IP addresses [2-720](#)
    - MAC addresses [2-717](#)
  - Layer 3 mode, enabling [2-677](#)
  - line configuration mode [1-2, 1-4](#)
  - Link Aggregation Control Protocol
    - See EtherChannel
  - link flap
    - error detection for [2-117](#)
    - error recovery timer [2-119](#)
  - link state group command [2-252](#)
  - link state track command [2-254](#)
  - load-distribution methods for EtherChannel [2-349](#)
  - location (global configuration) command [2-255](#)
  - location (interface configuration) command [2-257](#)
  - logging event command [2-259](#)
  - logging file command [2-260](#)
  - logical interface [2-144](#)
  - loopback error
    - detection for [2-117](#)
    - recovery timer [2-119](#)
  - loop guard, for spanning tree [2-636, 2-640](#)
- 
- M**
- mac access-group command [2-262](#)
  - MAC access-groups, displaying [2-534](#)
  - MAC access list configuration mode [2-264](#)
  - mac access-list extended command [2-264](#)
  - MAC access lists [2-88](#)
  - MAC addresses
    - disabling MAC address learning per VLAN [2-267](#)
    - displaying
      - aging time [2-538](#)
      - all [2-537](#)
      - dynamic [2-542](#)
      - MAC address-table move updates [2-547](#)
      - notification settings [2-546, 2-548](#)
      - number of addresses in a VLAN [2-540](#)
      - per interface [2-544](#)
      - per VLAN [2-552](#)
      - static [2-550](#)
      - static and dynamic entries [2-535](#)
    - dynamic
      - aging time [2-266](#)
      - deleting [2-49](#)
      - displaying [2-542](#)
      - enabling MAC address notification [2-271](#)
      - enabling MAC address-table move update [2-269](#)
      - matching [2-284](#)
      - static
        - adding and removing [2-273](#)
        - displaying [2-550](#)
        - dropping on an interface [2-274](#)
      - tables [2-537](#)
    - MAC address notification, debugging [B-30](#)
    - mac address-table aging-time [2-262, 2-284](#)
    - mac address-table aging-time command [2-266](#)
    - mac address-table learning command [2-267](#)
    - mac address-table move update command [2-269](#)
    - mac address-table notification command [2-271](#)
    - mac address-table static command [2-273](#)
    - mac address-table static drop command [2-274](#)
    - macro description command [2-278](#)
    - macro global command [2-279](#)
    - macro global description command [2-281](#)
    - macro name command [2-282](#)
    - macros
      - adding a description [2-278](#)
      - adding a global description [2-281](#)
      - applying [2-279](#)
      - creating [2-282](#)
      - displaying [2-564](#)
      - interface range [2-78, 2-146](#)
      - specifying parameter values [2-279](#)
      - tracing [2-279](#)

- maintenance end points [2-727](#)
- mapping tables, QoS [2-713](#)
- maps
  - class
    - creating [2-38](#)
  - VLAN
    - creating [2-736](#)
    - defining [2-284](#)
    - displaying [2-605](#)
- match access-group command [2-286](#)
- match cos command [2-287](#)
- match dot1ad dei command [2-289](#)
- match ip dscp command [2-291](#)
- match ip precedence command [2-293](#)
- match qos-group command [2-295](#)
- match vlan command [2-297](#)
- maximum transmission unit
  - See MTU
- mdix auto command [2-300](#)
- ME 3400EG-2CS switch policers [C-24](#)
- ME 3400E-24TS switch policers [C-24](#)
- ME 3400EG-12CS switch policers [C-24](#)
- media-type command [2-302](#)
- memory (boot loader) command [A-14](#)
- mgmt\_clr (boot loader) command [A-15](#)
- mgmt\_init (boot loader) command [A-16, A-17](#)
- mkdir (boot loader) command [A-18](#)
- MLD snooping
  - configuring [2-235, 2-236](#)
  - configuring queries [2-231, 2-233](#)
  - configuring topology change notification [2-238](#)
  - enabling [2-229](#)
- MLD snooping on a VLAN, enabling [2-240](#)
- mode, MVR [2-308](#)
- modes, commands [1-1](#)
- monitor session command [2-304](#)
- more (boot loader) command [A-19](#)
- MSTP
  - displaying [2-586](#)
- interoperability [2-57](#)
- link type [2-638](#)
- MST region
  - aborting changes [2-644](#)
  - applying changes [2-644](#)
  - configuration name [2-644](#)
  - configuration revision number [2-645](#)
  - current or pending display [2-645](#)
  - displaying [2-586](#)
  - MST configuration mode [2-644](#)
  - VLANs-to-instance mapping [2-644](#)
- path cost [2-646](#)
- protocol mode [2-642](#)
- restart protocol migration process [2-57](#)
- root port
  - loop guard [2-636](#)
  - preventing from becoming designated [2-636](#)
  - restricting which can be root [2-636](#)
  - root guard [2-636](#)
- root switch
  - affects of extended system ID [2-634](#)
  - hello-time [2-649, 2-660](#)
  - interval between BDPU messages [2-651](#)
  - interval between hello BPDU messages [2-649, 2-660](#)
  - max-age [2-651](#)
  - maximum hop count before discarding BPDU [2-653](#)
  - port priority for selection of [2-655](#)
  - primary or secondary [2-660](#)
  - switch priority [2-658](#)
- state changes
  - blocking to forwarding state [2-667](#)
  - enabling BPDU filtering [2-626, 2-664](#)
  - enabling BPDU guard [2-628, 2-664](#)
  - enabling Port Fast [2-664, 2-667](#)
  - forward-delay time [2-648](#)
  - length of listening and learning states [2-648](#)
  - rapid transition to forwarding [2-638](#)

- shutting down Port Fast-enabled ports [2-664](#)
- state information display [2-585](#)

## MTU

- configuring size [2-710](#)
- displaying global setting [2-593](#)
- multicast group address, MVR [2-311](#)
- multicast groups, MVR [2-309](#)
- Multicast Listener Discovery
  - See MLD
- multicast router learning method [2-201](#)
- multicast router ports, configuring [2-201](#)
- multicast router ports, IPv6 [2-240](#)
- multicast storm control [2-674](#)
- multicast VLAN, MVR [2-309](#)
- multicast VLAN registration
  - See MVR
- multiple hosts on authorized port [2-98](#)
- Multiple Spanning Tree Protocol
  - See MSTP
- multiplexing, UNI [2-135](#)

## MVR

- and address aliasing [2-309](#)
- configuring [2-308](#)
- configuring interfaces [2-311](#)
- debug messages, display [B-34](#)
- displaying [2-556](#)
- displaying interface information [2-558](#)
- members, displaying [2-560](#)
- mvr (global configuration) command [2-308](#)
- mvr (interface configuration) command [2-311](#)
- mvr vlan group command [2-312](#)

## N

- native VLANs [2-704](#)
- native VLAN tagging [2-738](#)
- network node interface [2-351](#)
- no authentication logging verbose [2-314](#)
- no dot1x logging verbose [2-315](#)

- no mab logging verbose [2-316](#)
- nonegotiate, speed [2-672, 2-673](#)
- non-IP protocols
  - denying [2-88](#)
  - forwarding [2-329](#)
- non-IP traffic access lists [2-264](#)
- non-IP traffic forwarding
  - denying [2-88](#)
  - permitting [2-329](#)
- normal-range VLANs [2-733](#)
- no vlan command [2-733](#)

## O

- OAM PDUs [2-133](#)
- OAM protocol [2-317](#)
- oam protocol cfm svlan command [2-317](#)
- on-board failure logging, displaying [2-530](#)
- on-board failure logging, enabling [2-142](#)
- online diagnostics
  - enabling
    - scheduling [2-93](#)
  - global configuration mode
    - clearing test-based testing schedule [2-93](#)
    - setting test-based testing [2-93](#)
    - setting up test-based testing [2-93](#)
  - removing scheduling [2-93](#)
  - scheduled switchover
    - disabling [2-93](#)
    - enabling [2-93](#)
    - setting test interval [2-93](#)
    - starting testing [2-95](#)
- online diagnostic tests, displaying results [2-437](#)
- online diagnostic tests, starting [2-95](#)
- operation, administration, and maintenance protocol
  - See OAM
- output policy maps
  - and QoS group classification [2-295](#)
  - and traffic shaping [2-410](#)

commands not supported in [2-347](#)  
 configuration guidelines [2-347](#)  
 priority in [2-356](#)  
 queue limit in [2-363](#)

## P

### PAgP

See EtherChannel

pagp learn-method command [2-318](#)  
 pagp port-priority command [2-320](#)  
 parent policy maps [2-395](#)  
 password-recovery mechanism, enabling and disabling [2-391](#)  
 permit (ARP access-list configuration) command [2-322](#)  
 permit (IPv6) command [2-324](#)  
 permit command [2-329](#)  
 per-VLAN spanning-tree plus  
 See STP  
 physical-port learner [2-318](#)  
 PID, displaying [2-482](#)  
 PIM-DVMRP, as multicast router learning method [2-201](#)  
 police  
   multiple conform actions for a class [2-60](#)  
   multiple exceed actions for a class [2-138](#)  
   multiple violate actions for a class [2-731](#)  
   with priority [2-332](#)  
 police aggregate command [2-342](#)  
 police command [2-332](#)  
 policer aggregate command [2-337](#)  
 policer configuration  
   default for NNIs [C-26](#)  
   default for UNIs [C-25](#)  
 policer cpu uni command [2-344](#)  
 policers  
   aggregate [2-337, 2-342](#)  
   for CPU protection [2-344](#)  
   individual [2-332](#)

policy-map class, configuring multiple actions [2-60, 2-138, 2-731](#)  
 policy-map class configuration mode [2-36](#)  
 policy-map class police configuration mode [2-60, 2-335](#)  
 policy-map command [2-346](#)  
 policy-map configuration mode [2-346](#)  
 policy maps  
   and CoS classification [2-287](#)  
   and DSCP classification [2-291](#)  
   and IP precedence classification [2-293](#)  
   and policing [2-335](#)  
   applying [2-393](#)  
   applying to an interface [2-347, 2-393, 2-407](#)  
   child [2-395](#)  
   creating [2-346](#)  
   displaying [2-570](#)  
   hierarchical [2-395](#)  
   parent [2-395](#)  
 policers  
   for a single class [2-332](#)  
   for multiple classes [2-337, 2-342, 2-344, 2-395](#)  
   setting priority [2-355](#)  
   setting QoS group identifier [2-405](#)  
 traffic classification, defining [2-36](#)  
 traffic marking  
   setting CoS values [2-397](#)  
   setting DSCP values [2-399, 2-401](#)  
   setting IP precedence values [2-403](#)

### Port Aggregation Protocol

See EtherChannel

### port-based authentication

AAA method list [2-3](#)  
 configuring violation modes [2-114](#)  
 debug messages, display [B-3](#)  
 enabling 802.1x  
   globally [2-109](#)  
   per interface [2-104](#)  
 host modes [2-98](#)  
 IEEE 802.1x AAA accounting methods [2-1](#)

- initialize an interface [2-100, 2-111](#)
- manual control of authorization state [2-104](#)
- multiple hosts on authorized port [2-98](#)
- periodic re-authentication
  - enabling [2-107](#)
  - time between attempts [2-112](#)
- quiet period between failed authentication exchanges [2-112](#)
- re-authenticating 802.1x-enabled ports [2-106](#)
- resetting configurable 802.1x parameters [2-97](#)
- switch-to-authentication server retransmission time [2-112](#)
- switch-to-client frame-retransmission number [2-101 to 2-103](#)
- switch-to-client retransmission time [2-112](#)
- test for IEEE 802.1x readiness [2-110](#)
- port-channel load-balance command [2-349](#)
- Port Fast, for spanning tree [2-667](#)
- port ranges, defining [2-48, 2-62, 2-78](#)
- ports, debugging [B-79](#)
- ports, protected [2-702](#)
- port security
  - aging [2-698](#)
  - debug messages, display [B-81](#)
  - enabling [2-694](#)
  - violation error recovery [2-119](#)
- port shaping [2-411](#)
- port-type command [2-351](#)
- port types, MVR [2-311](#)
- power information, displaying [2-445](#)
- power-supply alarm indications, configuring [2-353](#)
- power-supply dual command [2-353](#)
- power-supply status, displaying [2-445](#)
- precedence
  - for QoS traffic marking [2-403](#)
  - setting in policy maps [2-403](#)
- priority command [2-355](#)
- priority queuing, QoS [2-355](#)
- priority with police, QoS [2-355](#)
- private-vlan command [2-358](#)

- private-vlan mapping command [2-361](#)
- private VLANs
  - association [2-700](#)
  - configuring [2-358](#)
  - configuring ports [2-691](#)
  - displaying [2-600](#)
  - host ports [2-691](#)
  - mapping
    - configuring [2-700](#)
    - displaying [2-467](#)
  - promiscuous ports [2-691](#)
- privileged EXEC mode [1-2, 1-3](#)
- product identification information, displaying [2-482](#)
- promiscuous ports, private VLANs [2-691](#)
- PVST+
  - See STP

---

## Q

### QoS

- aggregate policers
  - applying [2-342](#)
  - creating [2-337](#)
  - displaying [2-566](#)
- class maps
  - creating [2-38](#)
  - defining the match criteria [2-287, 2-289](#)
  - displaying [2-421](#)
- conform actions, configuring [2-61](#)
- displaying statistics for [2-570, C-33](#)
- exceed actions, configuring [2-139](#)
- policy maps
  - applying an aggregate policer [2-337, 2-342, 2-344, 2-395](#)
  - applying to an interface [2-393, 2-407](#)
  - creating [2-346](#)
  - defining policers [2-332](#)
  - displaying policy maps [2-570](#)
  - setting CoS values [2-397](#)

- setting DSCP values [2-399, 2-401](#)
- setting IP precedence values [2-403](#)
- setting QoS group identifier [2-405](#)
- traffic classifications [2-36](#)

table maps

- configuring [2-713](#)
- displaying [2-594](#)

violate actions, configuring [2-732](#)

QoS groups

- as match criteria [2-295](#)
- for QoS traffic classification [2-405](#)
- setting in policy maps [2-405](#)

QoS match criteria

- ACLs [2-286](#)
- CoS value [2-287](#)
- DSCP value [2-291, 2-297](#)
- precedence value [2-293](#)
- QoS group number [2-295](#)

quality of service

- See QoS

querytime, MVR [2-308](#)

queue-limit command [2-363](#)

---

## R

rapid per-VLAN spanning-tree plus

- See STP

rapid PVST+

- See STP

re-authenticating 802.1x-enabled ports [2-106](#)

re-authentication

- periodic [2-107](#)
- time between attempts [2-112](#)

receiver ports, MVR [2-311](#)

receiving flow-control packets [2-140](#)

recovery mechanism

- causes [2-119](#)
- display [2-419, 2-447, 2-451](#)
- timer interval [2-120](#)

remote-span command [2-367](#)

Remote Switched Port Analyzer

- See RSPAN

rename (boot loader) command [A-20](#)

renew ip dhcp snooping database command [2-369](#)

rep admin vlan command [2-370](#)

rep block port command [2-371](#)

rep lsl-age-timer command [2-375](#)

rep preempt delay command [2-377](#)

rep preempt segment command [2-379](#)

rep segment command [2-380](#)

rep stcn command [2-383](#)

reset (boot loader) command [A-21](#)

resource templates, displaying [2-583](#)

rmdir (boot loader) command [A-22](#)

rmon collection stats command [2-385](#)

root guard, for spanning tree [2-636](#)

routed ports

- IP addresses on [2-154](#)
- number supported [2-154](#)

RSPAN

- configuring [2-304](#)
- displaying [2-554](#)
- filter RSPAN traffic [2-304](#)
- remote-span command [2-367](#)
- sessions
  - add interfaces to [2-304](#)
  - displaying [2-554](#)
  - start new [2-304](#)

---

## S

scheduled switchover

- disabling [2-93](#)
- enabling [2-93](#)

scheduling diagnostic tests [2-93](#)

sdm prefer command [2-386](#)

SDM templates

- allowed resources [2-387](#)

- displaying [2-583](#)
- dual IPv4 and IPv6 [2-386](#)
- secure ports, limitations [2-696](#)
- sending flow-control packets [2-140](#)
- service instance command [2-389](#)
- service instances, displaying [2-459](#)
- service password-recovery command [2-391](#)
- service policy (policy-map class configuration) command [2-395](#)
- service-policy interface configuration command [2-393](#)
- service-policy policy-map class configuration command [2-395](#)
- set (boot loader) command [A-23](#)
- set cos command [2-397](#)
- set dot1ad dei command [2-399](#)
- set dscp command [2-401](#)
- set precedence command [2-403](#)
- set qos-group command [2-405](#)
- setup command [2-407](#)
- SFPs, displaying information about [2-482](#)
- shape average command [2-410](#)
- show access-lists command [2-412](#)
- show aggregate-policer command [2-593](#)
- show archive status command [2-415](#)
- show arp access-list command [2-416](#)
- show boot command [2-417](#)
- show class-map command [2-421](#)
- show controllers cpu-interface command [2-422](#)
- show controllers ethernet-controller command [2-424](#)
- show controllers tcam command [2-431](#)
- show controllers utilization command [2-433](#)
- show controller utilization command [2-433](#)
- show cpu traffic qos command [2-435](#)
- show diagnostic command [2-437](#)
- show dot1q-tunnel command [2-441](#)
- show dot1x command [2-442](#)
- show env command [2-445](#)
- show errdisable detect command [2-447](#)
- show errdisable flap-values command [2-449](#)
- show errdisable recovery command [2-451](#)
- show etherchannel command [2-453](#)
- show ethernet loopback command [2-456](#)
- show ethernet service evc command [2-458](#)
- show ethernet service instance command [2-459](#)
- show ethernet service interface command [2-461](#)
- show flowcontrol command [2-463](#)
- show idprom command [2-465](#)
- show interface rep command [2-477](#)
- show interfaces command [2-467](#)
- show interfaces counters command [2-475](#)
- show interfaces rep command [2-477](#)
- show interface transceivers command [2-479](#)
- show inventory command [2-482](#)
- show ip arp inspection command [2-483](#)
- show ipc command [2-510](#)
- show ip dhcp snooping binding command [2-488](#)
- show ip dhcp snooping command [2-487](#)
- show ip dhcp snooping database command [2-490, 2-492](#)
- show ip igmp profile command [2-495](#)
- show ip igmp snooping command [2-496](#)
- show ip igmp snooping command querier detail [2-501](#)
- show ip igmp snooping groups command [2-498](#)
- show ip igmp snooping mrouter command [2-500](#)
- show ip igmp snooping querier command [2-501](#)
- show ip igmp snooping querier detail command [2-501](#)
- show ip sla standards command [2-503](#)
- show ip sla twamp connection [2-435](#)
- show ip sla twamp connection command [2-504](#)
- show ip sla twamp session command [2-506](#)
- show ip source binding command [2-507](#)
- show ipv6 access-list command [2-514](#)
- show ipv6 dhcp conflict command [2-516](#)
- show ipv6 route updated command [2-517](#)
- show ip verify source command [2-508](#)
- show l2protocol-tunnel command [2-519](#)
- show lacp command [2-521](#)
- show link state group command [2-525](#)
- show location command [2-527](#)

- show logging onboard command [2-530](#)
- show mac access-group command [2-534](#)
- show mac address-table address command [2-537](#)
- show mac address-table aging time command [2-538](#)
- show mac address-table command [2-535](#)
- show mac address-table count command [2-540](#)
- show mac address-table dynamic command [2-542](#)
- show mac address-table interface command [2-544](#)
- show mac address-table learning command [2-546](#)
- show mac address-table move update command [2-547](#)
- show mac address-table notification command [2-50, 2-548, B-32](#)
- show mac address-table static command [2-550](#)
- show mac address-table vlan command [2-552](#)
- show monitor command [2-554](#)
- show mvr command [2-556](#)
- show mvr interface command [2-558](#)
- show mvr members command [2-560](#)
- show pagp command [2-562](#)
- show parser macro command [2-564](#)
- show platform acl command [C-2](#)
- show platform backup interface command [C-3](#)
- show platform cfm command [C-4](#)
- show platform configuration command [C-5](#)
- show platform dl command [C-6](#)
- show platform etherchannel command [C-7](#)
- show platform forward command [C-8](#)
- show platform frontend-controller command [C-10](#)
- show platform igmp snooping command [C-11](#)
- show platform ipc trace command [C-14](#)
- show platform ip multicast command [C-12](#)
- show platform ip unicast command [C-13](#)
- show platform ipv6 unicast command [C-15](#)
- show platform l2pt dm command [C-17](#)
- show platform layer4op command [C-18, C-40](#)
- show platform mac-address-table command [C-19](#)
- show platform messaging command [C-20](#)
- show platform monitor command [C-21](#)
- show platform mvr table command [C-22](#)
- show platform pm command [C-23](#)
- show platform policer cpu command [C-24](#)
- show platform port-asic command [C-28](#)
- show platform port-security command [C-32](#)
- show platform qos command [C-33](#)
- show platform resource-manager command [C-36](#)
- show platform snmp counters command [C-38](#)
- show platform spanning-tree synchronization command [C-39](#)
- show platform stp-instance command [C-41](#)
- show platform team command [C-42](#)
- show platform vlan command [C-44](#)
- show platform vlan mapping command [C-45](#)
- show policer aggregate command [2-566](#)
- show policer cpu uni-eni command [2-567](#)
- show policy-map command [2-570](#)
- show policy-map interface output fields [2-573](#)
- show port security command [2-575](#)
- show port-type command [2-578](#)
- show rep topology command [2-580](#)
- show sdm prefer command [2-583](#)
- show spanning-tree command [2-585](#)
- show storm-control command [2-591](#)
- show system mtu command [2-593](#)
- show uddl command [2-595](#)
- show version command [2-598](#)
- show vlan access-map command [2-605](#)
- show vlan command [2-600](#)
- show vlan command, fields [2-602](#)
- show vlan filter command [2-606](#)
- show vlan mapping command [2-607](#)
- show vmmps command [2-609](#)
- shutdown command [2-611](#)
- shutdown threshold, Layer 2 protocol tunneling [2-244](#)
- shutdown vlan command [2-612](#)
- SNMP host, specifying [2-618](#)
- SNMP informs, enabling the sending of [2-614](#)
- snmp mib rep trap-rate command [2-613](#)
- snmp-server enable traps command [2-614](#)



- snmp-server host command [2-618](#)
- snmp trap mac-notification change command [2-622](#)
- SNMP traps
  - enabling MAC address notification trap [2-622](#)
  - enabling the MAC address notification feature [2-271](#)
  - enabling the sending of [2-614](#)
- software images
  - deleting [2-80](#)
  - downloading [2-9](#)
  - upgrading [2-9](#)
  - uploading [2-15](#)
- software version, displaying [2-598](#)
- source ports, MVR [2-311](#)
- SPAN
  - configuring [2-304](#)
  - debug messages, display [B-33](#)
  - displaying [2-554](#)
  - filter SPAN traffic [2-304](#)
  - sessions
    - add interfaces to [2-304](#)
    - displaying [2-554](#)
    - start new [2-304](#)
- spanning-tree bpdudfilter command [2-624, 2-626](#)
- spanning-tree bpduguard command [2-628](#)
- spanning-tree cost command [2-630](#)
- spanning-tree etherchannel command [2-632](#)
- spanning-tree extend system-id command [2-634](#)
- spanning-tree guard command [2-636](#)
- spanning-tree link-type command [2-638](#)
- spanning-tree loopguard default command [2-640](#)
- spanning-tree mode command [2-642](#)
- spanning-tree mst configuration command [2-644](#)
- spanning-tree mst cost command [2-646](#)
- spanning-tree mst forward-time command [2-648](#)
- spanning-tree mst hello-time command [2-649](#)
- spanning-tree mst max-age command [2-651](#)
- spanning-tree mst max-hops command [2-653](#)
- spanning-tree mst port-priority command [2-655](#)
- spanning-tree mst pre-standard command [2-657](#)
- spanning-tree mst priority command [2-658](#)
- spanning-tree mst root command [2-660](#)
- spanning-tree portfast (global configuration) command [2-664](#)
- spanning-tree portfast (interface configuration) command [2-667](#)
- spanning-tree port-priority command [2-662](#)
- Spanning Tree Protocol
  - See STP
- spanning-tree vlan command [2-669](#)
- speed command [2-672](#)
- SSH, configuring version [2-211](#)
- static-access ports, configuring [2-679](#)
- statistics, Ethernet group [2-385](#)
- sticky learning, enabling [2-694](#)
- storm-control command [2-674](#)
- STP
  - counters, clearing [2-56](#)
  - debug messages, display
    - MSTP [B-88](#)
    - optimized BPDUs handling [B-87](#)
    - spanning-tree activity [B-84](#)
    - switch shim [B-90](#)
    - transmitted and received BPDUs [B-86](#)
  - enabling on ENIs [2-624](#)
  - enabling protocol tunneling for [2-244](#)
  - EtherChannel misconfiguration [2-632](#)
  - extended system ID [2-634](#)
  - path cost [2-630](#)
  - protocol modes [2-642](#)
  - root port
    - loop guard [2-636](#)
    - preventing from becoming designated [2-636](#)
    - restricting which can be root [2-636](#)
    - root guard [2-636](#)
  - root switch
    - affects of extended system ID [2-634, 2-670](#)
    - hello-time [2-669](#)
    - interval between BPDU messages [2-669](#)
    - interval between hello BPDU messages [2-669](#)

- max-age [2-669](#)
- port priority for selection of [2-662](#)
- primary or secondary [2-669](#)
- switch priority [2-669](#)
- state changes
  - blocking to forwarding state [2-667](#)
  - enabling BPDU filtering [2-626, 2-664](#)
  - enabling BPDU guard [2-628, 2-664](#)
  - enabling Port Fast [2-664, 2-667](#)
  - enabling timer to recover from error state [2-119](#)
  - forward-delay time [2-669](#)
  - length of listening and learning states [2-669](#)
  - shutting down Port Fast-enabled ports [2-664](#)
- state information display [2-585](#)
- VLAN options [2-658, 2-669](#)
- SVIs, creating [2-148](#)
- Switched Port Analyzer
  - See SPAN
- switching characteristics
  - modifying [2-677](#)
  - returning to interfaces [2-677](#)
- switchport access command [2-679](#)
- switchport backup interface command [2-681](#)
- switchport block command [2-685](#)
- switchport command [2-677](#)
- switchport host command [2-687](#)
- switchport mode command [2-688](#)
- switchport mode private-vlan command [2-691](#)
- switchport port-security aging command [2-698](#)
- switchport port-security command [2-694](#)
- switchport private-vlan command [2-700](#)
- switchport protected command [2-702](#)
- switchports, displaying [2-467](#)
- switchport trunk command [2-704](#)
- switchport vlan mapping command [2-706](#)
- system env temperature threshold yellow command [2-709](#)
- system message logging, save message to flash [2-260](#)
- system mtu command [2-710](#)
- system resource templates [2-386](#)

---

## T

- table-map command [2-713](#)
- table-map configuration mode [2-713](#)
- table maps
  - configuring [2-713](#)
  - displaying [2-594](#)
  - QoS [2-713](#)
- tar files, creating, listing, and extracting [2-12](#)
- TDR, running [2-715](#)
- temperature information, displaying [2-445](#)
- temperature status, displaying [2-445](#)
- templates, system resources [2-386](#)
- test cable-diagnostics tdr command [2-715](#)
- traceroute mac command [2-717](#)
- traceroute mac ip command [2-720](#)
- traffic shaping, QoS [2-410](#)
- trunking, VLAN mode [2-688](#)
- trunk mode [2-688](#)
- trunk ports [2-688](#)
- tunnel ports, Layer 2 protocol, displaying [2-519](#)
- type (boot loader) command [A-26](#)

---

## U

- UDLD
  - aggressive mode [2-722, 2-724](#)
  - debug messages, display [B-96](#)
  - enable globally [2-722](#)
  - enable per interface [2-724](#)
  - error recovery timer [2-119](#)
  - message timer [2-722](#)
  - normal mode [2-722, 2-724](#)
  - reset a shutdown interface [2-726](#)
  - status [2-595](#)
- udld command [2-722](#)
- udld port command [2-724](#)
- udld reset command [2-726](#)
- UNI

- bundling and multiplexing [2-135](#)
  - Ethernet [2-135](#)
- unicast storm control [2-674](#)
- uni count command [2-727](#)
- UniDirectional Link Detection
  - See UDLD
- UNI ID, Ethernet [2-137](#)
- uni-vlan command [2-729](#)
- unknown multicast traffic, preventing [2-685](#)
- unknown unicast traffic, preventing [2-685](#)
- unset (boot loader) command [A-27](#)
- upgrading
  - software images [2-9](#)
    - monitoring status of [2-415](#)
- user EXEC mode [1-2](#)
- user network interface [2-351](#)

## V

- version (boot loader) command [A-29](#)
- violate-action command [2-731](#)
- vlan access-map command [2-736](#)
- VLAN access map configuration mode [2-736](#)
- VLAN access maps
  - actions [2-5](#)
  - displaying [2-605](#)
- vlan command [2-733](#)
- VLAN configuration mode
  - commands [2-733](#)
  - description [1-4](#)
  - entering [2-733](#)
  - summary [1-2](#)
- vlan dot1q tag native command [2-738](#)
- vlan filter command [2-740](#)
- VLAN filters, displaying [2-606](#)
- VLAN ID range [2-733](#)
- VLAN ID translation
  - See VLAN mapping
- VLAN mapping
  - configuring [2-706](#)
  - described [2-707](#)
  - displaying [2-607](#)
- VLAN maps
  - applying [2-740](#)
  - creating [2-736](#)
  - defining [2-284](#)
  - displaying [2-605](#)
- VLAN Query Protocol
  - See VQP
- VLANs
  - adding [2-733](#)
  - configuring [2-733](#)
  - debug messages, display
    - activation of [B-94](#)
    - VLAN IOS file system error tests [B-93](#)
    - VLAN manager activity [B-92](#)
  - displaying configurations [2-600](#)
  - extended-range [2-733](#)
  - MAC addresses
    - displaying [2-552](#)
    - number of [2-540](#)
  - normal-range [2-733](#)
  - private [2-691](#)
    - configuring [2-358](#)
    - displaying [2-600](#)
    - See also private VLANs
  - restarting [2-612](#)
  - saving the configuration [2-733](#)
  - shutting down [2-612](#)
  - suspending [2-612](#)
- VMPS
  - configuring servers [2-745](#)
  - displaying [2-609](#)
  - error recovery timer [2-120](#)
  - reconfirming dynamic VLAN assignments [2-742](#)
  - vmpls reconfirm (global configuration) command [2-743](#)
  - vmpls reconfirm (privileged EXEC) command [2-742](#)
  - vmpls retry command [2-744](#)

vmps server command [2-745](#)

## VQP

and dynamic-access ports [2-680](#)

clearing client statistics [2-59](#)

displaying information [2-609](#)

per-server retry count [2-744](#)

reconfirmation interval [2-743](#)

reconfirming dynamic VLAN assignments [2-742](#)

## VTP

enabling

tunneling for [2-244](#)

---

## W

Weighted Tail Drop

See WTD

WTD, queue-limit command [2-363](#)