



CHAPTER 4

File Commands

Revised: July 22, 2009, OL-19335-01

This chapter contains the following **file** commands:

- [file list log](#)
- [file list nvboot](#)
- [file tail log](#)
- [file tail nvboot](#)
- [file view log](#)
- [file view nvboot](#)

file list log

file list log *file-spec* [**page** | **detail** | **reverse** | [**date** | **size**]

Syntax Description

<i>file-spec</i>	Required. File to view. You can use * as a wildcard.
page	Optional. Pause output.
detail	Optional. Show detailed listing.
reverse	Optional. Sort in reverse order.
date	Optional. Sort by date.
size	Optional. Sort by size.

Command Default

No default behavior or values.

Command Modes

Admin

Command privilege level: 4

Command History

Release	Modifications
1.5	This command was introduced.

Usage Guidelines

Use this command to list logging files.

Examples

```
admin:file list log sysop detail
```

```
24 Apr,2009 01:26:06          4 sysop.bin
24 Apr,2009 01:23:34          67 sysop00000.log
24 Apr,2009 17:30:49       7,324 sysop00001.log
dir count = 0, file count = 3
```

file list nvboot

`file list nvboot file-spec [page | detail | reverse | date | size]`

Syntax Description	<i>file-spec</i>	Required. File to view. You can use * as a wildcard.
	page	Optional. Pause output.
	detail	Optional. Show detailed listing.
	reverse	Optional. Sort in reverse order.
	date	Optional. Sort by date.
	size	Optional. Sort by size.

Command Default No default behavior or values.

Command Modes Admin
Command privilege level: 4

Command History	Release	Modifications
	1.5	This command was introduced.

Usage Guidelines Use this command to list NV bootlog files.

Examples

```
admin:file list nvboot . detail
09 Nov,2008 03:59:56      46,150  cfsync.log
09 Nov,2008 03:59:57      34,858  cfupgrade.log
09 Nov,2008 04:00:01     132,641  rc.log
09 Nov,2008 03:59:58      23,152  uiNotification.log
28 Oct,2008 17:55:48      34,604  upgPeripheral.log
dir count = 0, file count = 5
```

file tail log

file tail log *{file-spec [hex]}*

Syntax Description

<i>file-spec</i>	Required. File to tail.
<i>hex</i>	Optional. Hexadecimal.

Command Default

No default behavior or values.

Command Modes

Admin
Command privilege level: 4

Command History

Release	Modifications
1.5	This command was introduced.

Usage Guidelines

Use this command to tail the contents of a file in the logging area. Press Control-C to stop the command.

Examples

```
admin:file tail log sysop/sysop00001.log
```

```
Rx Pkts Late                0
Rx Pkts AuthFail           0
Rx Jitter/Call              0
Rx Jitter/Period            0
Control-C pressed
```

file tail nvboot

file tail nvboot *{file-spec [hex]}*

Syntax Description

<i>file-spec</i>	Required. File to tail.
<i>hex</i>	Optional. Hexadecimal.

Command Default

No default behavior or values.

Command Modes

Admin
Command privilege level: 4

Command History

Release	Modifications
1.5	This command was introduced.

Usage Guidelines

Use this command to tail the contents of a file in the NV bootlog area. Press Control-C to stop the command

Examples

```
admin:file tail nvboot rc.log

Starting keyExchange... DONE
Starting cca...
Starting cca... DONE
Starting HDMI Monitor Main Rx...
....
trimming bootlog files
file /nv/bootlog/cfsync.log trimmed to 985 lines
file /nv/bootlog/cfupgrade.log trimmed to 995 lines
file /nv/bootlog/upgPeripheral.log left at 993 lines
file /nv/bootlog/uiNotification.log trimmed to 999 lines
file /nv/bootlog/rc.log trimmed to 3996 lines
Control-C pressed
```

file view log

file view log *{file-spec [hex]}*

Syntax Description	<i>file-spec</i>	Required. Log file to view.
	<i>hex</i>	Optional. Hexadecimal.

Command Default No default behavior or values.

Command Modes Admin
Command privilege level: 4

Command History	Release	Modifications
	1.5	This command was introduced.

Usage Guidelines Use this command to view the contents of a file in the logging area. To view the data, use the following keystroke controls:

- Enter key; Move forward one line
- Space bar: Move forward one page
- b: Move backward one page
- s : Move to the start of the file
- e: Move to the end of the file
- q: Quit the command

Examples

```
admin:file view log sysop/sysop00001.log

2008-10-27 22:19:04,261 - admin CLI login from 191.74.232.125:43776
2008-10-27 22:19:06,651 - admin CLI logout (forced) from 191.74.232.125:43776
2008-10-27 22:19:43,262 - build UI version mismatch. phone:1.0.7, cts:1.0.8
2008-10-27 22:20:08,686 - CTL updated
....
2008-10-27 22:46:07,205 - Local Hold
2008-10-27 22:46:08,412 - Resume Call
More data : enter, space, b, s, e or q
```

file view nvboot

file view nvboot {*file-spec* [*hex*]}

Syntax Description	<i>file-spec</i>	Required. File to view.
	<i>hex</i>	Optional. Hexadecimal.

Command Default No default behavior or values.

Command Modes Admin
Command privilege level: 4

Command History	Release	Modifications
	1.5	This command was introduced.

Usage Guidelines Use this command to view the contents of a file in the NV bootlog area. To view the data, use the following keystroke controls:

- Enter key: Move forward one line
- Space bar: Move forward one page
- b: Move backward one page
- s : Move to the start of the file
- e: Move to the end of the file
- q: Quit the command

Examples

```
admin:file view nvboot rc.log

---NEXT_ENTRY---
*** Processing rcS
Sun Jan  1 00:00:00 GMT 2006
*** Mounting proc
....
Creating CiscoSyslogFifo
Starting /usr/sbin/syslogd
More data : enter, space, b, s, e or q
```

