



USB

- [USB, on page 1](#)

USB

The following table lists the USB BIOS settings that you can configure through a BIOS policy or the default BIOS settings:

Name	Description	Supported Attributes			
		Versions	Platforms	Values	Dependencies
All USB Devices	Whether all physical and virtual USB devices are enabled or disabled	4.2(1)	C240 M6, C220 M6, B200 M6, X210c M6	Enabled , Disabled	
Legacy USB Support	Whether the system supports legacy USB devices.	4.2(1), 5.0(1), 5.0(2)	C240 M6, C220 M6, B200 M6, X210c M6	Auto , Enabled, Disabled	
Make Device Non Bootable	Whether the server can boot from a USB device.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled , Disabled	
xHCI Mode	Whether xHCI mode is enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled , Disabled	
Port 60/64 Emulation	Whether the system supports 60h/64h emulation for complete USB keyboard legacy support.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled, Disabled	You should select Enabled option if you are using a non-USB aware operating system on the server.

Name	Description	Supported Attributes			
		Versions	Platforms	Values	Dependencies
USB Port Front	Whether the front panel USB devices are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5, B200 M6, X210c M6, X210c M7, X410c M7	Enabled, Disabled	
USB Port Internal	Whether the internal USB devices are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled, Disabled	
USB Port KVM	Whether the USB Port KVM devices are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5, B200 M6, X210c M6, X210c M7, X410c M7	Enabled, Disabled	
USB Port Rear	Whether the USB port rear devices are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5, C220 M7, C240 M7	Enabled, Disabled	
USB Port SD Card	Whether the SD card drives are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5, B200 M6, X210c M6, X210c M7, X410c M7	Enabled, Disabled	
USB Port VMedia	Whether the virtual media devices are enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled, Disabled	
XHCI Legacy Support	Whether xHCI mode is enabled or disabled.	4.2(1)	C240 M5, C220 M5, C480 M5	Enabled, Disabled	