



Supported Network Adapter Cards for UCSM Mode

This chapter includes the following sections:

- [Overview, page 1](#)
- [Supported Adapter Cards, page 1](#)
- [Supported Card Combinations, page 2](#)

Overview

The following Network Adapter cards support Cisco UCS Manager integration :

- Cisco Virtual Interface Cards (VICs)
- Converged Network Adapters (CNAs)
- Ethernet adapters

Supported Adapter Cards

The following table shows the officially supported adapter cards for C-Series Rack-Mount Servers integration with Cisco UCS Manager.

Adapter/Server Model	C200 M2	C210 M2	C250 M2
Cisco UCS P81E VIC (N2XX-ACPCI01)	Y	Y	Y
Emulex OCe10102-F CNA (N2XX-AEPCI01)	Y	Y	Y

Adapter/Server Model	C200 M2	C210 M2	C250 M2
QLogic QLE8152 CNA (N2XX-AQPCI01)	Y	Y	Y
Broadcom BCM57711 10Gb (N2XX-ABPCI02)	Y	Y	Y
Intel X520 10Gb (N2XX-AIPCI01)	Y	Y	Y

Supported Card Combinations

The following are the only supported card combinations for the servers to be used in UCSM mode.

- Only Cisco Virtual Interface Cards (VICs) installed in the server. Do not mix with CNAs or Ethernet cards.
- Only one type of CNA (Q or E) installed in the server. Do not mix with VICs or Ethernet adapters.
- Only one type of Ethernet adapter (B or I) installed in the server. Do not mix with VICs or CNAs.