

Managing User Accounts

This chapter includes the following sections:

- Configuring Local Users, page 1
- LDAP Servers (Active Directory), page 3
- Viewing User Sessions, page 10

Configuring Local Users

Before You Begin

You must log in as a user with admin privileges to configure or modify local user accounts.

Procedure

- **Step 1** In the Navigation pane, click the Admin tab.
- Step 2 On the Admin tab, click User Management.
- **Step 3** In the User Management pane, click the Local User tab.

Figure 1: Local Users Tab

ululu and the						CIMC Hostname: ucse_user		
cisco Cisco Integ	ira	ted M	anager	nent Controll	er	Logged in as: admin@10	.21.169.25 Log Out	
Overall Server Status	c	I.t.	• = 1	0 0				
Waiting BIOS POST								
Server Admin	-	Local Users	Active E	Directory Sessions				
User Management	T	o configure	a user, selec	t the user below				
Network Communications Services		isers		1		1		
Certificate Management		10	Enabled	Username	Admin		<u>A</u>	
CIMC Log		2		admin				
Event Management	U.	3					-	
Firmware Management		4						
Utilities	Uľ,	5						
		6						
	LI.	7						
		8						
		9						
		10						
		11						
		12						
		13						
		14						
		15						
	L			1	1			
							rt Values	

Step 4 To configure or modify a local user account, click a row.

Step 5 In the User Details dialog box, update the following properties:

Name	Description
ID column	The unique identifier for the user.
Enabled check box	If checked, the user is enabled on the CIMC.
Username column	The username for the user.

Name	Description
Role column	The role assigned to the user. This can be one of the following:
	• read-only —This user can view information but cannot make changes.
	• user—This user can:
	• View all information
	 Manage the power control options such as power on, power cycle, and power off
	 Launch the KVM console and virtual media
	• Clear all logs
	• admin—This user can perform all actions available through the GUI, CLI, and IPMI.

Step 6 Enter password information.

Step 7 Click Save Changes.

LDAP Servers (Active Directory)

CIMC supports directory services that organize information in a directory, and manage access to this information. CIMC supports Lightweight Directory Access Protocol (LDAP), which stores and maintains directory information in a network. In addition, CIMC supports Microsoft Active Directory (AD). Active Directory is a technology that provides a variety of network services including LDAP-like directory services, Kerberos-based authentication, and DNS-based naming. The CIMC utilizes the Kerberos-based authentication service of LDAP.

When LDAP is enabled in the CIMC, user authentication and role authorization is performed by the LDAP server for user accounts not found in the local user database. The LDAP user authentication format is username@domain.com.

By checking the Enable Encryption check box in the LDAP Settings area, you can require the server to encrypt data sent to the LDAP server.

Configuring the LDAP Server

The CIMC can be configured to use LDAP for user authentication and authorization. To use LDAP, configure users with an attribute that holds the user role and locale information for the CIMC. You can use an existing LDAP attribute that is mapped to the CIMC user roles and locales or you can modify the LDAP schema to add a new custom attribute, such as the CiscoAVPair attribute, which has an attribute ID of 1.3.6.1.4.1.9.287247.1.

r 👉

Important

For more information about altering the schema, see the article at http://technet.microsoft.com/en-us/ library/bb727064.aspx.

Note This example creates a custom attribute named CiscoAVPair, but you can also use an existing LDAP attribute that is mapped to the CIMC user roles and locales.

The following steps must be performed on the LDAP server.

Procedure

- **Step 1** Ensure that the LDAP schema snap-in is installed.
- **Step 2** Using the schema snap-in, add a new attribute with the following properties:

Properties	Value
Common Name	CiscoAVPair
LDAP Display Name	CiscoAVPair
Unique X500 Object ID	1.3.6.1.4.1.9.287247.1
Description	CiscoAVPair
Syntax	Case Sensitive String

Step 3 Add the CiscoAVPair attribute to the user class using the snap-in:

- a) Expand the Classes node in the left pane and type U to select the user class.
- b) Click the Attributes tab and click Add.
- c) Type C to select the CiscoAVPair attribute.
- d) Click OK.
- **Step 4** Add the following user role values to the CiscoAVPair attribute, for the users that you want to have access to CIMC:

Role	CiscoAVPair Attribute Value
admin	shell:roles="admin"
user	shell:roles="user"
read-only	shell:roles="read-only"

Note For more information about adding values to attributes, see the article at http://technet.microsoft.com/ en-us/library/bb727064.aspx.

I

What to Do Next

Use the CIMC to configure the LDAP server.

Configuring LDAP Settings and Group Authorization in CIMC

Before You Begin

You must log in as a user with admin privileges to perform this task.

Procedure

- **Step 1** In the Navigation pane, click the Admin tab.
- Step 2 On the Admin tab, click User Management.
- **Step 3** In the User Management pane, click the Active Directory tab.

Figure 2: Active Directory Tab

isco Cisco Inte	grated Management Contro	ller		CIMC Hostname: Logged in as:	ucse_user admin@10.34.209.64 Log (
overall Server Status	0 0 1 5 5 10 0				
Good	User Management				
Server Admin	Local Users Active Directory Sessions)			
Iser Management	LDAP Settings				
etwork	Enable LDAP:	Binding	Binding Parameters		
ommunications Services	Base DN:		Method: Login Cr	edentials	
ertificate Management	Domain:		Binding DN:		
rent Management	Enable Engranding:				
mware Management	Transt (a teach		Password:		
slities	(0-1000)	Search	arameters		
	Configure LDAP Servers		Filter Attribute:	untName	
	Pre-Configure LDAP Servers				Č I
	LDAP Servers		Group Attribute: member	of	0
	Server	Port	Attribute: CiscoAvF	air	
	1:	389			
	2:	389 Group A	uthorization		-
		Index	Group Name	Group Dor	nain Role
	4:	3268		_	
	5:	3268			
					_
	6:	3268 4	1.		
				1	

Step 4 In the LDAP Settings area, update the following properties:

1

Name	Description
Enable LDAP check box	If checked, user authentication and role authorization is first performed by the LDAP server, and then by the user accounts that are not found in the local user database.
Base DN field	Base Distinguished Name. Specifies the location from where to load the users and groups.
	The Base DN must be in the dc=domain,dc=com format for Active Directory servers.
Domain field	The IPv4 domain name. All users must be in the IPv4 domain.
	This field is required unless you specify at least one Global Catalog server address.
Enable Encryption check box	If checked, the server encrypts all information it sends to the LDAP server.
Timeout (0 - 1800) seconds field	The number of seconds the CIMC waits until the LDAP search operation times out.
	If the search operation times out, CIMC tries to connect to the next server listed on this tab, if one is available.
	Note The value you specify for this field could impact the overall time.

Step 5 In the **Configure LDAP Servers** area, update the following properties:

Name	Description	
Pre-Configure LDAP Servers radio button	If checked, the Active Directory uses the pre-configured LDAP servers.	
LDAP Servers area		
Server column	 The IP address of the six LDAP servers. If you are using Active Directory for LDAP, then servers 1, 2, and 3 are domain controllers, and servers 4, 5, and 6 are Global Catalogs. If you are not using the Active Directory for LDAP, then you can configure a maximum of six LDAP servers. Note You can provide the IP address of the host name as well. 	

GUI Configuration Guide for Cisco UCS E-Series Servers and the Cisco UCS E-Series Network Compute Engine Integrated Management Controller, Release 3.x

I

Name	Description
Port column	The port numbers for the servers. If you are using Active Directory for LDAP, then for servers 1, 2, and 3, which are domain controllers, the default port number is 389. For servers 4, 5, and 6, which are Global Catalogs, the default port number is 3268. LDAPS communication occurs over the TCP 636 port. LDAPS communication to a global catalog server occurs over TCP 3269 port.
Use DNS to Configure LDAP Servers radio button	If checked, you can use DNS to configure access to the LDAP servers.
DNS Parameters area	
Source drop-down list	 Specifies how to obtain the domain name used for DNS SRV request. This can be one of the following: Extracted—Uses the extracted-domain from the login ID. Configured—Uses the configured-search domain. Configured-Extracted—Uses the domain name extracted from the login ID instead of the configured-search domain.
Domain to Search field	A configured domain name that acts as a source for a DNS query. This field is disabled if the source is specified as Extracted .
Forest to Search field	A configured forest name that acts as a source for a DNS query. This field is disabled if the source is specified as Extracted .

Step 6 In the **Binding Parameters** area, update the following properties:

1

Name	Description	
Method drop-down list	This can be one of the following:	
	• Anonymous—Requires NULL username and password. If this option is selected and the LDAP server is configured for anonymous logins, then the user can gain access.	
	• Configured Credentials—Requires a known set of credentials to be specified for the initial bind process. If the initial bind process succeeds, then the distinguished name (DN) of the user name is queried and re-used for the re-binding process. If the re-binding process fails, then the user is denied access.	
	• Login Credentials—Requires the user credentials. If the bind process fails, the user is denied access.	
	Note Login Credentials is the default option.	
Binding DN field	The distinguished name (DN) of the user.	
	This field is editable only if you have selected Configured Credentials option as the binding method.	
Password field	The password of the user.	
	This field is editable only if you have selected Configured Credentials option as the binding method.	

Step 7 In the **Search Parameters** area, update the following fields:

Name	Description	
Filter Attribute field	This field must match the configured attribute in the schema on the LDAP server.	
	By default, this field displays sAMAccountName .	
Group Attribute field	This field must match the configured attribute in the schema on the LDAP server.	
	By default, this field displays memberOf.	

I

Name	Description
Attribute field	An LDAP attribute that contains the role and locale information for the user. This property is always a name-value pair. The system queries the user record for the value that matches this attribute name.
	The LDAP attribute can either use an existing LDAP attribute that is mapped to the CIMC user roles and locales or can modify the schema so that a new LDAP attribute can be created. For example, CiscoAvPair .
	Note If you do not specify this property, the user cannot login. Although the object is located on the LDAP server, it should be an exact match of the attribute that is specified in this field.

Step 8 (Optional) In the Group Authorization area, update the following properties:

Name	Description
LDAP Group Authorization check box	If checked, user authentication is also done on the group level for users that are not found in the local user database or who are not individually authorized to use CIMC in the Active Directory.
Group Name column	The name of the group in the LDAP server database that is authorized to access the server.
Group Domain column	The LDAP server domain the group must reside in.
Role column	 The role assigned to all users in this LDAP server group. This can be one of the following: read-only—This user can view information but cannot make changes. user—This user can: View all information Manage the power control options such as power on, power cycle, and power off
	• Launch the KVM console and virtual media
	° Clear all logs
	• admin—This user can perform all actions available through the GUI, CLI, and IPMI.

Step 9 Click Save Changes.

Viewing User Sessions

Procedure

- **Step 1** In the Navigation pane, click the Admin tab.
- Step 2 On the Admin tab, click User Management.
- **Step 3** In the User Management pane, click the Sessions tab.
- **Step 4** View the following information about current user sessions:
 - Tip Click a column header to sort the table rows, according to the entries in that column.

Name	Description
Session ID column	The unique identifier for the session.
Username column	The username for the user.
IP Address column	The IP address from which the user accessed the server.
Type column	The method by which the user accessed the server. For example, CLI, vKVM, and so on.
Action column	If your user account is assigned the admin user role, this column displays Terminate if you can force the associated user session to end. Otherwise it displays N/A .
	Note You cannot terminate your current session from this tab.