



## Firmware Files for 4.3(3)

- [Firmware Files for 4.3\(3\), on page 1](#)

## Firmware Files for 4.3(3)

This section comprises firmware information for the following release:

- [Firmware Files for Release 4.3.3.240041, on page 1](#)
- [Firmware Files for Release 4.3.3.240002, on page 5](#)

### Firmware Files for Release 4.3.3.240041

The Cisco Host Upgrade Utility contains the following files:

- ucs-s3260-huu-4.3.3.240041.iso

**Table 1: ucs-s3260-huu-4.3.3.240041.iso**

Server	Type	Component	Version
Cisco UCS S3260 M5	CISCO		
		BIOS M5	S3X60M5.4.3.2a.0
		Chassis	4.3(3.240006)
		BMC M5	4.3(3.240041)
		Board Controller	10
		SAS-EXPANDER	B083-B083
		UCSC-C3260-SIOC	4.6(2.230017)
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)

Server	Type	Component	Version
	LSI		
		Cisco RAID controller for UCS C3X60 storage servers	24.21.0-0156
		UCS C3X60 12G Modular SAS Pass Through Controller	13.00.00.12
		Cisco 94008e 12G SAS HBA	20.00.02.01
		UCS S3260 Dual Pass Through Controller based on Broadcom 3316 ROC	13.00.00.12
		Cisco UCS C3000 RAID controller for M4 Server Blade with 4G RAID Cache	29.00.1-0360-31137-033
		UCS S3260 Dual Raid Controller based on Broadcom 3316 ROC	29.00.1-0360-00188-1A6
	QLOGIC		
		Cisco(R) FastLinQ QL45412H 40GbE Adapter	08.04.23.04.03:08.52.18
		QLogic 2672 Dual port 16Gbps Fibre Channel Adapter	8.08.203
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Qlogic 2562 adapter	8.08.01
	NVIDIA		
		NVIDIA T4 PCIe 16GB 70W	90.04.B4.00.04-G183.0200.00.02
	EMULEX		
		Emulex 16002 Dual port 16Gbps Fibre Channel Adapter	12.2.212.14
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11

Server	Type	Component	Version
	MICRON		
		1.9TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		6.4TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	WDC		
		1.9TB 2.5in U.2 WD SN640 NVMe Med. Perf. Value Endurance	R121000A
		3.8TB 2.5in U.2 WD SN640 NVMe Med. Perf. High Endurance	R121000A
		6.4TB 2.5in U.2 WD SN640 NVMe Med. Perf. High Endurance	R121000A
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
	HGST		

Server	Type	Component	Version
		Cisco 800GB 2.5in NVMe based PCIe SSD drive	KMCCP108
		Cisco 1.6TB 2.5in NVMe based PCIe SSD drive	KMCCP108
		Cisco UCS (SN100) 3.8 TB 2.5in SFF NVMe based PCIe SSD	KMCCP108
		800GB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		1.6TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		3.2TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		6.4TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
	INTEL		
		Cisco(R) 500GB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Cisco(R) 1TB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Cisco(R) 2TB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Intel X520 dual port adapter	0x800009FA-1.831.2
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2
		Intel I350 LOM	0x80000F35-1.831.2
		Intel X550T2 Dual Port 10Gb 10GBaseT converged NIC	0x8000179C-1.831.2

Server	Type	Component	Version
		Intel X710DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel XL710QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2
		Cisco(R) Ethernet Converged NIC XXV710DA2	0x8000DEC7-1.831.2
	PERSISTENT-MEMORY		
		Intel Optane DC Persistent Memory, 256GB, 2666MHz	01.02.00.5446
		Intel Optane DC Persistent Memory, 512GB, 2666MHz	01.02.00.5446

#### Firmware Files for Release 4.3.3.240002

The Cisco Host Upgrade Utility contains the following files:

- ucs-c240m7-huu-4.3.3.240002.iso
- ucs-c220m7-huu-4.3.3.240002.iso
- ucs-c220m6-huu-4.3.3.240002.iso
- ucs-c240m6-huu-4.3.3.240002.iso
- ucs-c225m6-huu-4.3.3.240002.iso
- ucs-c245m6-huu-4.3.3.240002.iso
- ucs-s3260-huu-4.3.3.240002.iso

**Table 2: ucs-c240m7-huu-4.3.3.240022.iso**

Server	Type	Description	Version
C240 M7	CISCO		
		Cisco IMC	4.3(3.240022)
		BIOS	C240M7.4.3.3a.0
		Board Controller	36
		SAS-EXPANDER	65.16.09.00
		Retimer Component	1.27.42

Server	Type	Description	Version
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	LSI		
		Cisco TriMode 24G SAS RAID Controller w/4GB Cache	8.6.2.0000-65-00001
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 95008e 12G SAS HBA for external JBOD attach	27.65.08.00
		Cisco 12G SAS RAID Controller with 4GB FBWC (28 Drives)	52.26.0-5016
		Cisco boot optimized M.2 NVMe RAID controller	52.23.0-4857
	QLOGIC		
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Cisco-QLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
		Cisco-QLogic QLE2872, 2x64GFC Gen 7 PCIe HBA	8.04.03
	NVIDIA		

Server	Type	Description	Version
		NVIDIA A100 PCIe FHFL DS 250W 80GB	9200A0000B-1001.0230000B-6079200A00005-1001.0230000B
		Nvidia A30 PCIe FHFL DS 24GB HBM2 165W	920066000B-1001.02050002-6079200660004-1001.02050002
		NVIDIA A40 PCIe FHFL DS 48GB GDDR6 300W	94025C000B-G1330200005-50194025C000F-G1330200005
		Nvidia H100 350W, 80GB, 2slot FHFL PCIe GPU	96.00.74.00.1A-1010.0200.00.02-00.02.0134.0000_n00
		NVIDIA A16 PCIe FHFL DS 250W	<del>907610ADG700004020B40</del> <del>907610ADG700004020B40</del>
		Nvidia L40, 300W, 48GB, 2slot FHFL PCIe GPU	95.02.5D.00.01-G133.0250.00.01
		Nvidia L4, 72W, 24GB, singleslot HHL PCIe GPU	95.04.55.00.01-G193.0200.00.01
		CiscoNVDA MCX631102ASADAT CX6 Lx 2x25GbE SFP28 x8 PCIe NIC	26.38.1900
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
		CiscoEmulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	HERCULES		
		Hercules PCIe Compression and Cryptographic CPU Offload Card	1811-2081
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002

Server	Type	Description	Version
		960GB M.2 Boot NVMe	E2CS003
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		400GB M.2 Boot NVMe	E2CS003
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900



Server	Type	Description	Version
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	INTEL		
		7.6TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5" U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5" U.2 P5620 NVMe High Perf High Endurance	9CV10200
		3.2TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Cisco(R) I710T4LG 4x1 GbE RJ45 PCIe NIC	0x8000E62F-1.831.2
		Intel X710-DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2

Server	Type	Description	Version
		Intel X710-DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E632-1.831.2
		Cisco(R) X710T2LG 2x10 GbE RJ45 OCP 3.0 NIC	0x8000E636-1.831.2
		2.5" U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		2.5" U.2 800GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		Intel Data Center GPU Flex 170, FH-3/4L, 150W PCIe	DG02_1.3260-6.7.0.0
		Intel Data Center GPU Flex 140, HHHL, 75W PCIe	DG02_2.2273-6.7.0.0
	MICROCHIP		

Server	Type	Description	Version
		Cisco Trimode M1 24G RAID Controller W/4GB FBWC (32Drives)	03.01.24.082-p
		Cisco Trimode M1 24G RAID Controller W/4GB FBWC (16 Drives)	03.01.24.082-p
		Cisco Trimode M1 24G HBA Controller (16 Drives)	03.01.24.082-p
		DC packaged in CIMC	1.0.11-3273

Table 3: ucs-c220m7-huu-4.3.3.240022.iso

Server	Type	Description	Version
C220 M7	CISCO		
		Cisco IMC	4.3(3.240022)
		BIOS	C220M7.4.3.3a.0
		Board Controller	34
		Retimer Component	1.27.42
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	LSI		
		Cisco TriMode 24G SAS RAID Controller w/4GB Cache	8.6.2.0-00065-00001

Server	Type	Description	Version
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 95008e 12G SAS HBA for external JBOD attach	27.65.08.00
		Cisco 12G SAS RAID Controller with 4GB FBWC (16 Drives)	52.26.0-5016
		Cisco boot optimized M.2 NVMe RAID controller	52.23.0-4857
	QLOGIC		
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Cisco-QLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
		Cisco-QLogic QLE2872, 2x64GFC Gen 7 PCIe HBA	8.04.03
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
		Cisco-Emulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	NVIDIA		
		Nvidia L4, 72W, 24GB, singleslot HHL PCIe GPU	95.04.55.00.01-G193.0200.00.01
		Cisco-NVDA MCX631102ASADAT CX6 Lx 2x25GbE SFP28 x8 PCIe NIC	26.38.1900
	HERCULES		

Server	Type	Description	Version
		Hercules PCIe Compression and Cryptographic CPU Offload Card	1811-2081
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		960GB M.2 Boot NVMe	E2CS003
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		400GB M.2 Boot NVMe	E2CS003
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900

Server	Type	Description	Version
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	INTEL		
		7.6TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5" U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5" U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5" U.2 P5620 NVMe High Perf High Endurance	9CV10200
		3.2TB 2.5" U.2 P5620 NVMe High Perf High Endurance	9CV10200
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Cisco(R) I710T4LG 4x1 GbE RJ45 PCIe NIC	0x8000E62F-1.831.2
		Intel X710-DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2

Server	Type	Description	Version
		Intel X710-DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E632-1.831.2
		Cisco(R) X710T2LG 2x10 GbE RJ45 OCP 3.0 NIC	0x8000E636-1.831.2
		2.5 U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		2.5 U.2 800GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		Intel Data Center GPU Flex 140, HHHL, 75W PCIe	DG02_2.22736.7.0.0
	MICROCHIP		
		Cisco Trimode M1 24G RAID Controller W/4GB FBWC (32Drives)	03.01.24.082-p
		Cisco Trimode M1 24G RAID Controller W/4GB FBWC (16 Drives)	03.01.24.082-p

Server	Type	Description	Version
		Cisco Trimode M1 24G HBA Controller (16 Drives)	03.01.24.082-p
		DC packaged in CIMC	1.0.11-3273

Table 4: ucs-c220m6-huu-4.3.3.240023.iso

Server	Type	Description	Version
C220 M6	CISCO		
		Cisco IMC	4.3(3.240021)
		BIOS	C220M6.4.3.2e.0
		Board Controller	39
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)
		Cisco UCS VIC 1467 MLOM	5.3(2.46)
		Cisco UCS VIC 1477 MLOM	5.3(2.46)
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	LSI		
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 95008e 12G SAS HBA for external JBOD attach	27.65.08.00



Server	Type	Description	Version
		Cisco 12G SAS RAID Controller with 4GB FBWC (16 Drives)	52.26.0-5016
	QLOGIC		
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		CiscoQLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
	NVIDIA		
		NVIDIA T4 PCIe 16GB 70W	90.04.B4.00.04-G183.0200.00.02
		Cisco-NVDA MCX623436ACCDAB CX6Dx 2x100G QSFP56 x16 OCP NIC	22.38.1900
		Cisco-NVDA MCX631432ACADAB CX6 Lx 2x25G SFP28 x8 OCP NIC	26.38.1900
	BROADCOM		
		Emulex LPe31002 Dual-Port 16G FC HBA	14.2.455.11
		CiscoEmulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	HERCULES		
		Hercules PCIe Compression and Cryptographic CPU Offload Card	1811-2081
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002

Server	Type	Description	Version
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Mellanox ConnectX-5 MCX512A-ACAT dual port 10/25GbE SFP28 NIC	16.35.3006

Server	Type	Description	Version
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	WDC		
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		7.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
		15.3TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
	INTEL		
		1.9TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		3.8TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033

Server	Type	Description	Version
		1.6TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		3.2TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		6.4TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		3.2TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		Cisco 2.5 U.2 1TB Intel P4510 NVMe High Perf. Value Endurance	VDV1CP02
		Cisco 2.5 U.2 4TB Intel P4510 NVMe High Perf. Value Endurance	VDV1CP02

Server	Type	Description	Version
		Cisco 2.5 U.2 8TB Intel P4510 NVMe High Perf. Value Endurance	VDV1CP02
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2
		Intel X550 LOM	0x8000179E-1.831.2
		Intel X710-DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel X710-DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Intel XL710-QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E632-1.831.2
		Cisco 2.5 750GB Intel Optane NVMe Extreme Performance SSD	E201CP07

Server	Type	Description	Version
		Cisco 2.5 375GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		2.5 U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		2.5 U.2 800GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
	PERSSIENTMEMORY		
		Intel Optane PMem 200 series 128GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 256GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 512GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 128GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 128GB	02.02.00.1553
		Intel Optane PMem 200 series 256GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 256GB	02.02.00.1553
		Intel Optane PMem 200 series 256GB	02.02.00.1553
		Intel Optane PMem 200 series 512GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 512GB	02.02.00.1553
		DC packaged in CIMC	1.0.11-3273

Table 5: ucs-c240m6-huu-4.3.3.240023D.iso

Server	Type	Description	Version
C240 M6	CISCO		
		Cisco IMC	4.3(3.240021)
		BIOS	C240M6.4.3.2e.0
		Board Controller	42
		SAS-EXPANDER	65.16.09.00
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)
		Cisco UCS VIC 1467 MLOM	5.3(2.46)
		Cisco UCS VIC 1477 MLOM	5.3(2.46)
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	MICROSEM		
		PCIe-Switch-1	3.70.0.4F
		PCIe-Switch-2	3.70.0.4F
		PCIe-Switch-3	3.70.0.4F
	LSI		
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 12G SAS HBA	27.65.08.00

Server	Type	Description	Version
		Cisco 95008e 12G SAS HBA for external JBOD attach	27.65.08.00
		Cisco 12G SAS RAID Controller with 4GB FBWC (16 Drives)	52.26.05016
		Cisco 12G SAS RAID Controller with 4GB FBWC	52.26.0-5016
		Cisco 12G SAS RAID Controller with 4GB FBWC (28 Drives)	52.26.0-5016
	QLOGIC		
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Cisco-QLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
	NVIDIA		
		NVIDIA A100 PCIe FHFL DS 250W 80GB	9200A000B-1001023000B6079200A0005-1001023000B
		Nvidia A30 PCIe FHFL DS 24GB HBM2 165W	92006600B-10010205002607920066004-10010205002
		NVIDIA A100 PCIe FHFL DS 250W 40GB	92.00.90.00.08-1001.0200.00.04
		NVIDIA A40 PCIe FHFL DS 48GB GDDR6 300W	94025C00B-G13302000550194025C00F-G133020005
		Nvidia A10 PCIe FHFL SS 24GB 150W	94029100B-G1330215006607940291002-G1330215006
		NVIDIA A16 PCIe FHFL DS 250W	940500G-710004023409050ADG71000402340
		Cisco-NVDA MCX623436ACCDAB CX6Dx 2x100G QSFP56 x16 OCP NIC	22.38.1900



Server	Type	Description	Version
		Cisco-NVDA MCX631432ACADAB CX6 Lx 2x25G SFP28 x8 OCP NIC	26.38.1900
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
		Cisco-Emulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	HERCULES		
		Hercules PCIe Compression and Cryptographic CPU Offload Card	1811-2081
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002

Server	Type	Description	Version
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Mellanox ConnectX-5 MCX512A-ACAT dual port 10/25GbE SFP 28 NIC	16.35.3006
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	WDC		
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		7.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
		15.3TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002

Server	Type	Description	Version
	INTEL		
		1.9TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		3.8TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		1.6TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		3.2TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		6.4TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200

Server	Type	Description	Version
		3.2TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		Cisco 2.5 U.2 1TB Intel P4510 NVMe High Perf. Value Endurance	VDV1CP02
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2
		Intel X550 LOM	0x800017A0-1.831.2
		Intel X710-DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel X710-DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Intel XL710-QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E632-1.831.2
		Cisco 2.5 750GB Intel Optane NVMe Extreme Performance SSD	E201CP07

Server	Type	Description	Version
		Cisco 2.5 375GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		2.5 U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		2.5 U.2 800GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
	<del>PERSSIMEMORY</del>		
		Intel Optane PMem 200 series 128GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 256GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 512GB (QS)	02.02.00.1553
		Intel Optane PMem 200 series 128GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 128GB	02.02.00.1553
		Intel Optane PMem 200 series 256GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 256GB	02.02.00.1553
		Intel Optane PMem 200 series 256GB	02.02.00.1553
		Intel Optane PMem 200 series 512GB (ES2)	02.02.00.1553
		Intel Optane PMem 200 series 512GB	02.02.00.1553
		DC packaged in CIMC	1.0.11-3273

Table 6: ucs-c225m6-huu-4.3.3.240023.iso

Server	Type	Description	Version
C225 M6	Cisco		
		Cisco IMC	4.3(3.240021)
		BIOS	C225M6.4.3.2c.0
		Board Controller	27
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)
		Cisco UCS VIC 1467 MLOM	5.3(2.46)
		Cisco UCS VIC 1477 MLOM	5.3(2.46)
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	LSI		
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 12G SAS RAID Controller with 4GB FBWC (16 Drives)	52.26.0-5016
	QLOGIC		

Server	Type	Description	Version
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Cisco-QLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
	NVIDIA		
		NVIDIA T4 PCIe 16GB 70W	90.04.B4.00.04-G183.0200.00.02
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
		Cisco-Emulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002

Server	Type	Description	Version
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Mellanox ConnectX-5 MCX512A-ACAT dual port 10/25GbE SFP28 NIC	16.35.3006
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	WDC		
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002



Server	Type	Description	Version
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		7.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
		15.3TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
	INTEL		
		1.9TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		3.8TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		1.6TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		3.2TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		6.4TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033

Server	Type	Description	Version
		7.6TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		3.2TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2
		Intel X710DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel X710DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Intel XL710QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2

Server	Type	Description	Version
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E632-1.831.2
		Cisco(R) X710T2LG 2x10 GbE RJ45 OCP 3.0 NIC	0x8000E636-1.831.2
		Cisco 2.5 750GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		Cisco 2.5 375GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		2.5 U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		2.5 U.2 800GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		DC packaged in CIMC	1.0.11-3273

Table 7: ucs-c245m6-huu-4.3.3.240023.iso

Server	Type	Description	Version
C245 M6	CISCO		
		Cisco IMC	4.3(3.240021)
		BIOS	C245M6.4.3.2c.0
		Board Controller	29
		SAS-EXPANDER	65.16.09.00
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)
		Cisco UCS VIC 1467 MLOM	5.3(2.46)
		Cisco UCS VIC 1477 MLOM	5.3(2.46)
		Cisco UCS VIC 15428 MLOM	5.3(2.46)
		Cisco UCS VIC 15427 MLOM	5.3(2.46)-48
		Cisco UCS VIC 15235	5.3(2.46)-48
		Cisco UCS VIC 15238 MLOM	5.3(2.46)
		Cisco UCS VIC 15425	5.3(2.46)-48
		Cisco UCS VIC 15237 MLOM	5.3(2.46)-48
	LSI		
		Cisco 12G SAS HBA (16 Drives)	27.65.08.00
		Cisco 12G SAS RAID Controller with 4GB FBWC (28 Drives)	52.26.0-5016
	QLOGIC		

Server	Type	Description	Version
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		CiscoQLogic QLE2772 2x32GFC Gen 6 Enhanced PCIe HBA	8.04.03
	NVIDIA		
		NVIDIA A100 PCIe FHFL DS 250W 80GB	9200A000B-1001023000B6079200A0005-1001023000B
		Nvidia A30 PCIe FHFL DS 24GB HBM2 165W	92006600B-10010205002607920066004-10010205002
		NVIDIA A100 PCIe FHFL DS 250W 40GB	92.00.90.00.08-1001.0200.00.04
		NVIDIA A40 PCIe FHFL DS 48GB GDDR6 300W	94025C00BG1302000550194025C00FG130200005
		Nvidia A10 PCIe FHFL SS 24GB 150W	94029100BG13302150066079402910002G1330215006
		NVIDIA A16 PCIe FHFL DS 250W	906500G170000402014090650ADG17000020140
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
		CiscoEmulex LPe35002M22x32GFC Gen 7 PCIe HBA	14.2.455.11
	MICRON		
		960GB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002

Server	Type	Description	Version
		1.9TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		3.8TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		15.3TB 2.5in U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		1.6TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		3.2TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
		6.4TB 2.5in U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Cisco-MLNX MCX623106AC-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900
		Cisco-MLNX MCX623106AS-CDAT 2x100GbE QSFP56 PCIe NIC	22.38.1900

Server	Type	Description	Version
		Mellanox ConnectX-5 MCX512A-ACAT dual port 10/25GbE SFP28 NIC	16.35.3006
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	MARVELL		
		Cisco Boot optimized M.2 Raid controller	2.3.17.1014
	WDC		
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		7.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
		15.3TB 2.5in U.2 WD SN840 NVMe Extreme Perf. Value Endurance	R2210002
	INTEL		
		1.9TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033

Server	Type	Description	Version
		3.8TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5in U.2 Intel P5500 NVMe High Perf Medium Endurance	2CV1C033
		1.6TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Enduranc	2CV1C033
		3.2TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Enduranc	2CV1C033
		6.4TB 2.5in U.2 Intel P5600 NVMe High Perf Medium Endurance	2CV1C033
		7.6TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		15.3TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		3.8TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.9TB 2.5 U.2 P5520 NVMe High Perf Medium Endurance	9CV10200
		1.6TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		6.4TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200



Server	Type	Description	Version
		3.2TB 2.5 U.2 P5620 NVMe High Perf High Endurance	9CV10200
		15.3TB 2.5in U.2 P5316 NVMe High Perf Low Endurance	ACV10310
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2
		Intel X710DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel X710DA2 Dual Port 10Gb SFP converged NIC	0x8000E631-1.831.2
		Intel XL710QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2
		Cisco Intel E810CQDA2 2x100 GbE QSFP28 PCIe NIC	0x80018F67-1.831.2
		Cisco Intel E810XXVDA4 4x25/10 GbE SFP28 PCIe NIC	0x80018F68-1.831.2
		Cisco Intel E810XXVDA2 2x25/10 GbE SFP PCIe NIC	0x80018F65-1.831.2
		Cisco Intel X710T2LG 2x10 GbE RJ45 PCIe NIC	0x8000E630-1.831.2
		Cisco(R) X710T4LG 4x10 GbE RJ45 PCIe NIC	0x8000E6321.831.2
		Cisco(R) X710T2LG 2x10 GbE RJ45 OCP 3.0 NIC	0x8000E636-1.831.2

Server	Type	Description	Version
		Cisco 2.5 750GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		Cisco 2.5 375GB Intel Optane NVMe Extreme Performance SSD	E201CP07
		2.5 U.2 400GB Intel P5800X Optane NVMe Extreme Performance SSD	L031CP02
		DC packaged in CIMC	1.0.11-3273

Table 8: ucs-s3260-huu-4.3.3.240023.iso

Server	Type	Description	Version
S3260 M5	CISCO		
		BIOS M5	S3X60M5.4.3.2a.0
		Chassis	4.3(3.240001)
		BMC M5	4.3(3.240022)
		Board Controller	10
		SAS-EXPANDER	B083-B083
		UCSC-C3260-SIOC	4.6(2.230017)
		Cisco UCS VIC 1455	5.3(2.46)
		Cisco UCS VIC 1495	5.3(2.46)
	LSI		
		Cisco RAID controller for UCS C3X60 storage servers	24.21.0-0156
		UCS C3X60 12G Modular SAS Pass Through Controller	13.00.00.12
		Cisco 94008e 12G SAS HBA	20.00.02.01

Server	Type	Description	Version
		UCS S3260 Dual Pass Through Controller based on Broadcom 3316 ROC	13.00.00.12
		Cisco UCS C3000 RAID controller for M4 Server Blade with 4G RAID Cache	29.00.1-0360-31137-033
		UCS S3260 Dual Raid Controller based on Broadcom 3316 ROC	29.00.1-0360-00188-1A6
	QLOGIC		
		Cisco(R) FastLinQ QL45412H 40GbE Adapter	08.04.23.04.03:08.52.18
		QLogic 2672 Dual port 16Gbps Fibre Channel Adapter	8.08.203
		Qlogic QLE2692 dualport 16G FC HBA	10.02.08
		Qlogic 2562 adapter	8.08.01
	NVIDIA		
		NVIDIA T4 PCIe 16GB 70W	90.04.B4.00.04-G183.0200.00.02
	EMULEX		
		Emulex 16002 Dual port 16Gbps Fibre Channel Adapter	12.2.212.14
	BROADCOM		
		Emulex LPe31002 DualPort 16G FC HBA	14.2.455.11
	MICRON		
		1.9TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002

Server	Type	Description	Version
		3.8TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		7.6TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf Medium Endurance	E2CS002
		6.4TB 2.5in 7mm U.3 Micron 7450 NVMe High Perf High Endurance	E2CS002
	MELLANOX		
		Mellanox ConnectX-5 MCX516A-CDAT dual port 100GbE QSFP28 NIC	16.35.3006
	WDC		
		1.9TB 2.5in U.2 WD SN640 NVMe Med. Perf. Value Endurance	R121000A
		3.8TB 2.5in U.2 WD SN640 NVMe Med. Perf. High Endurance	R121000A
		6.4TB 2.5in U.2 WD SN640 NVMe Med. Perf. High Endurance	R121000A
		1.6TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		3.2TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
		6.4TB 2.5in U.2 WD SN840 NVMe Extreme Perf. High Endurance	R2210002
	HGST		

Server	Type	Description	Version
		Cisco 800GB 2.5in NVMe based PCIe SSD drive	KMCCP108
		Cisco 1.6TB 2.5in NVMe based PCIe SSD drive	KMCCP108
		Cisco UCS (SN100) 3.8 TB 2.5in SFF NVMe based PCIe SSD	KMCCP108
		800GB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		1.6TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		3.2TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
		6.4TB 2.5in U.2 HGST SN200 NVMe High Perf. High Endurance	KNCCD122
	INTEL		
		Cisco(R) 500GB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Cisco(R) 1TB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Cisco(R) 2TB 2.5in U.2 Intel P4501 NVMe Med. Perf. Value Endurance	QDV1CP08
		Intel X520 dual port adapter	0x800009FA-1.831.2
		Intel i350 Quad Port 1Gb Adapter	0x800011A4-1.831.2

Server	Type	Description	Version
		Intel I350 LOM	0x80000F35-1.831.2
		Intel X550T2 Dual Port 10Gb 10GBaseT converged NIC	0x8000179C-1.831.2
		Intel X710DA4 Quad Port 10Gb SFP converged NIC	0x8000E634-1.831.2
		Intel XL710QDA2 Dual Port 40Gb QSFP converged NIC	0x8000DF30-1.831.2
		Cisco(R) Ethernet Converged NIC XXV710DA2	0x8000DEC7-1.831.2
	PERSISTENTMEMORY		
		Intel Optane DC Persistent Memory, 256GB, 2666MHz	01.02.00.5446
		Intel Optane DC Persistent Memory, 512GB, 2666MHz	01.02.00.5446
		DC packaged in CIMC	1.0.11-3273