



# Configuring Authentication

---

This chapter includes the following sections:

- [Authentication Services, page 1](#)
- [Guidelines and Recommendations for Remote Authentication Providers, page 2](#)
- [User Attributes in Remote Authentication Providers, page 2](#)
- [Two-Factor Authentication, page 4](#)
- [LDAP Group Rule, page 5](#)
- [Nested LDAP Groups, page 5](#)
- [Configuring LDAP Providers, page 5](#)
- [Configuring RADIUS Providers, page 11](#)
- [Configuring TACACS+ Providers, page 13](#)
- [Multiple Authentication Services Configuration, page 14](#)
- [Selecting a Primary Authentication Service, page 20](#)

## Authentication Services

Cisco UCS supports the following two methods to authenticate user logins:

- Local user authentication - uses user accounts that exist locally in the Cisco UCS Manager
- Remote user authentication - uses one of the following protocols:
  - LDAP
  - RADIUS
  - TACACS+

# Guidelines and Recommendations for Remote Authentication Providers

If a system is configured for one of the supported remote authentication services, you must create a provider for that service to ensure that Cisco UCS Manager can communicate with the system. The following guidelines impact user authorization:

## User Accounts in Remote Authentication Services

User accounts can exist locally in Cisco UCS Manager or in the remote authentication server.

You can view the temporary sessions for users who log in through remote authentication services from the Cisco UCS Manager GUI and from the Cisco UCS Manager CLI.

## User Roles in Remote Authentication Services

If you create user accounts in the remote authentication server, you must ensure that the accounts include the roles those users require for working in Cisco UCS Manager and that the names of those roles match the names used in Cisco UCS Manager. Based on the role policy, a user might not be allowed to log in, or is granted only read-only privileges.

# User Attributes in Remote Authentication Providers

For RADIUS and TACACS+ configurations, you must configure a user attribute for Cisco UCS in each remote authentication provider through which users log in to Cisco UCS Manager. This user attribute holds the roles and locales assigned to each user.

**Note**

---

This step is not required for LDAP configurations that use the LDAP Group Mapping to assign roles and locales.

---

When a user logs in, Cisco UCS Manager does the following:

- 1 Queries the remote authentication service.
- 2 Validates the user.
- 3 If the user is validated, checks for the roles and locales assigned to that user.

The following table contains a comparison of the user attribute requirements for the remote authentication providers supported by Cisco UCS.

**Table 1: Comparison of User Attributes by Remote Authentication Provider**

Authentication Provider	Custom Attribute	Schema Extension	Attribute ID Requirements
LDAP	Not required if group mapping is used  Optional if group mapping is not used	Optional. You can choose to do one of the following: <ul style="list-style-type: none"> <li>Do not extend the LDAP schema and configure an existing, unused attribute that meets the requirements.</li> <li>Extend the LDAP schema and create a custom attribute with a unique name, such as CiscoAVPair.</li> </ul>	The Cisco LDAP implementation requires a unicode type attribute.  If you choose to create the CiscoAVPair custom attribute, use the following attribute ID: 1.3.6.1.4.1.9.287247.1  A sample OID is provided in the following section.
RADIUS	Optional	Optional. You can choose to do one of the following: <ul style="list-style-type: none"> <li>Do not extend the RADIUS schema and use an existing unused attribute that meets the requirements.</li> <li>Extend the RADIUS schema and create a custom attribute with a unique name, such as cisco-avpair.</li> </ul>	The vendor ID for the Cisco RADIUS implementation is 009 and the vendor ID for the attribute is 001.  The following syntax example shows how to specify multiples user roles and locales if you choose to create the cisco-avpair attribute: shell:roles="admin,aaa" shell:locales="L1,abc". Use a comma "," as the delimiter to separate multiple values.
TACACS+	Required	Required. You must extend the schema and create a custom attribute with the name cisco-av-pair.	The cisco-av-pair name is the string that provides the attribute ID for the TACACS+ provider.  The following syntax example shows how to specify multiples user roles and locales when you create the cisco-av-pair attribute: cisco-av-pair=shell:roles="admin aaa" shell:locales*"L1 abc". Using an asterisk (*) in the cisco-av-pair attribute syntax flags the locale as optional, preventing authentication failures for other Cisco devices that use the same authorization profile. Use a space as the delimiter to separate multiple values.

### Sample OID for LDAP User Attribute

The following is a sample OID for a custom CiscoAVPair attribute:

```
CN=CiscoAVPair,CN=Schema,
CN=Configuration,CN=X
objectClass: top
objectClass: attributeSchema
cn: CiscoAVPair
distinguishedName: CN=CiscoAVPair,CN=Schema,CN=Configuration,CN=X
instanceType: 0x4
uSNCreated: 26318654
attributeID: 1.3.6.1.4.1.9.287247.1
attributeSyntax: 2.5.5.12
isSingleValued: TRUE
showInAdvancedViewOnly: TRUE
adminDisplayName: CiscoAVPair
adminDescription: UCS User Authorization Field
oMSyntax: 64
LDAPDisplayName: CiscoAVPair
name: CiscoAVPair
objectCategory: CN=Attribute-Schema,CN=Schema,CN=Configuration,CN=X
```

## Two-Factor Authentication

Cisco UCS Manager uses two-factor authentication for remote user logins, which adds a level of security to account logins. Two-factor authentication login requires a username, a token, and a password combination in the password field. You can provide a PIN, a certificate, or a token.

Two-factor authentication uses authentication applications that maintain token servers to generate one-time tokens for users during the login process and store passwords in the AAA server. Requests are sent to the token server to retrieve a vendor-specific attribute. Cisco UCS Manager expects the token server to integrate with the AAA server, therefore it forwards the request to the AAA server. The password and token are validated at the same time by the AAA server. Users must enter the token and password sequence in the same order as it is configured in the AAA server.

Two-factor authentication is supported by associating RADIUS or TACACS+ provider groups with designated authentication domains and enabling two-factor authentication for those domains. Two-factor authentication does not support IPM and is not supported when the authentication realm is set to LDAP, local, or none.

### Web Session Refresh and Web Session Timeout Period

The **Web Session Refresh Period** is the maximum amount of time allowed between refresh requests for a Cisco UCS Manager GUI web session. The **Web Session Timeout** is the maximum amount of time that can elapse after the last refresh request before a Cisco UCS Manager GUI web session becomes inactive.

You can increase the **Web Session Refresh Period** to a value greater than 60 seconds up to 172800 seconds to avoid frequent session timeouts that requires regenerating and re-entering a token and password multiple times. The default value is 7200 seconds when two-factor authentication is enabled, and is 600 seconds when two-factor authentication is not enabled.

You can specify a value between 300 and 172800 for the **Web Session Timeout Period**. The default is 8000 seconds when two-factor authentication is enabled, and 7200 seconds when two-factor authentication is not enabled.

# LDAP Group Rule

The LDAP group rule determines whether Cisco UCS should use LDAP groups when assigning user roles and locales to a remote user.

## Nested LDAP Groups

You can add an LDAP group as a member of another group and nest groups to consolidate member accounts and to reduce the replication of traffic. Cisco UCS Manager release 2.1(2) and higher enables you to search LDAP groups that are nested within another group defined in an LDAP group map.

**Note**

---

Nested LDAP search support is supported only for Microsoft Active Directory servers. The supported versions are Microsoft Windows 2003 SP3, Microsoft Windows 2008 R2, and Microsoft Windows 2012.

---

By default, user rights are inherited when you nest an LDAP group within another group. For example, if you make Group\_1 a member of Group\_2, the users in Group\_1 have the same permissions as the members of Group\_2. You can then search users that are members of Group\_1 by choosing only Group\_2 in the LDAP group map, instead of having to search Group\_1 and Group\_2 separately.

You do not always need to create subgroups in a group map in Cisco UCS Manager.

## Configuring LDAP Providers

### Configuring Properties for LDAP Providers

The properties that you configure in this task are the default settings for all provider connections of this type defined in Cisco UCS Manager. If an individual provider includes a setting for any of these properties, Cisco UCS uses that setting and ignores the default setting.

**Before You Begin**

If you are using Active Directory as your LDAP server, create a user account in the Active Directory server to bind with Cisco UCS. Give this account a non-expiring password.

**Procedure**

- 
- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > LDAP**.
  - Step 3** In the **Properties** area, complete all fields.
    - Note** User login fails if the userDn for an LDAP user exceeds 255 characters.
  - Step 4** Click **Save Changes**.
-

**What to Do Next**

Create an LDAP provider.

**Creating an LDAP Provider**

Cisco UCS Manager supports a maximum of 16 LDAP providers.

**Before You Begin**

If you are using Active Directory as your LDAP server, create a user account in the Active Directory server to bind with Cisco UCS. Give this account a non-expiring password.

- In the LDAP server, perform one of the following configurations:
  - Configure LDAP groups. LDAP groups contain user role and locale information.
  - Configure users with the attribute that holds the user role and locale information for Cisco UCS Manager. You can choose whether to extend the LDAP schema for this attribute. If you do not want to extend the schema, use an existing LDAP attribute to hold the Cisco UCS user roles and locales. If you prefer to extend the schema, create a custom attribute, such as the CiscoAVPair attribute.

The Cisco LDAP implementation requires a unicode type attribute.

If you choose to create the CiscoAVPair custom attribute, use the following attribute ID:  
1.3.6.1.4.1.9.287247.1

- For a cluster configuration, add the management port IPv4 or IPv6 addresses for both fabric interconnects. This configuration ensures that remote users can continue to log in if the first fabric interconnect fails and the system fails over to the second fabric interconnect. All login requests are sourced from these IP addresses, not the virtual IPv4 or IPv6 address used by Cisco UCS Manager.
- If you want to use secure communications, create a trusted point containing the certificate of the root certificate authority (CA) of the LDAP server in Cisco UCS Manager.
- If you need to change the LDAP providers or add or delete them, change the authentication realm for the domain to local, make the changes to the providers, then change the domain authentication realm back to LDAP.
- If you want to use the special characters listed in the following table for defining the attributes of an Active Directory bind distinguished name, you must replace the special character with an escape, by using a backslash (\) followed by the corresponding hexadecimal value of the character.

Special Character	Description	Hexadecimal Value
,	comma	0x2C
+	plus sign	0x2B
"	double quote	0x22
\	backslash	0x5C

Special Character	Description	Hexadecimal Value
<	left angle bracket	0x3C
>	right angle bracket	0x3E
;	semicolon	0x3B
LF	line feed	0x0A
CR	carriage return	0x0D
=	equals sign	0x3D
/	forwards slash	0x2F

<https://msdn.microsoft.com/en-us/library/aa366101> provides more details on replacing special characters with its escape and hexadecimal equivalent.


**Attention**

LDAP remote usernames that include special characters cannot log in to systems that are running versions 2.2(3a) and later. The user cannot log in because of the Nexus OS limitations where special characters, !, %, ^, are not supported in the username.

**Procedure**

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > LDAP**.
- Step 3** In the **Work** pane, click the **General** tab.
- Step 4** In the **Actions** area, click **Create LDAP Provider**.
- Step 5** On the **Create LDAP Provider** page of the wizard, complete all fields with appropriate LDAP service information.
- Step 6** On the **LDAP Group Rule** page of the wizard, complete all fields with appropriate LDAP group rule information.

**What to Do Next**

For implementations involving a single LDAP database, select LDAP as the authentication service.

For implementations involving multiple LDAP databases, configure an LDAP provider group.

## Changing the LDAP Group Rule for an LDAP Provider

### Procedure

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > LDAP**.
- Step 3** Expand **LDAP Providers** and choose the LDAP provider for which you want to change the group rule.
- Step 4** In the **Work** pane, click the **General** tab.
- Step 5** In the **LDAP Group Rules** area, complete the following fields:

Name	Description
<b>Group Authorization</b> field	<p>Whether Cisco UCS also searches LDAP groups when authenticating and assigning user roles and locales to remote users. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Disable</b>—Cisco UCS does not access any LDAP groups.</li> <li>• <b>Enable</b>—Cisco UCS searches all LDAP groups mapped in this Cisco UCS domain. If the remote user is found, Cisco UCS assigns the user roles and locales defined for that LDAP group in the associated LDAP group map.</li> </ul> <p><b>Note</b> Role and locale assignment is cumulative. If a user is included in multiple groups, or has a role or locale specified in the LDAP attribute, Cisco UCS assigns that user all the roles and locales mapped to any of those groups or attributes.</p>
<b>Group Recursion</b> field	<p>Whether Cisco UCS searches both the mapped groups and their parent groups. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Non Recursive</b>—Cisco UCS searches only the groups mapped in this Cisco UCS domain. If none of the groups containing the user explicitly set the user's authorization properties, Cisco UCS uses the default settings.</li> <li>• <b>Recursive</b>—Cisco UCS searches each mapped group and all its parent groups for the user's authorization properties. These properties are cumulative, so for each group Cisco UCS finds with explicit authorization property settings, it applies those settings to the current user. Otherwise it uses the default settings.</li> </ul>
<b>Target Attribute</b> field	<p>The attribute Cisco UCS uses to determine group membership in the LDAP database.</p> <p>The supported string length is 63 characters. The default string is memberOf.</p>

Name	Description
Use Primary Group field	The attribute Cisco UCS uses to determine if the primary group can be configured as an LDAP group map for membership validation. With this option Cisco UCS Manager can download and verify the primary-group membership of the user.

**Step 6** Click **Save Changes**.

## Deleting an LDAP Provider

### Procedure

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > LDAP**.
- Step 3** Expand **LDAP Providers**.
- Step 4** Right-click the LDAP provider that you want to delete and choose **Delete**.
- Step 5** If a confirmation dialog box displays, click **Yes**.

## LDAP Group Mapping

LDAP group mapping eliminates having to define role or locale information in the LDAP user object. UCSM can use group membership information to assign a role or locale to an LDAP user during login for organizations using LDAP groups to restrict access to LDAP databases.

When a user logs in to Cisco UCS Manager, the LDAP group map pulls information about the user's role and locale. If the role and locale criteria match the information in the policy, access is granted. Cisco UCS Manager supports a maximum of 28, 128, or 160 LDAP group maps depending on the release version.



### Note

Cisco UCS Manager Release 3.1(1) supports a maximum of 128 LDAP group maps, and Release 3.1(2) and later releases support a maximum of 160 LDAP group maps.

The role and locale definitions that you configure locally in the Cisco UCS Manager do not update automatically based on changes to an LDAP directory. When deleting or renaming LDAP groups in an LDAP directory, you must also update the Cisco UCS Manager with the change.

You can configure an LDAP group map to include any of the following combinations of roles and locales:

- Roles only
- Locales only

- Both roles and locales

For example, consider an LDAP group representing a group of server administrators at a specific location. The LDAP group map might include user roles such as server profile and server equipment. To restrict access to server administrators at a specific location, you can set the locale to a particular site name.

**Note**

---

Cisco UCS Manager includes out-of-the-box user roles, but does not include any locales. Mapping an LDAP provider group to a locale requires that you create a custom locale.

---

## Creating an LDAP Group Map

### Before You Begin

- Create an LDAP group in the LDAP server.
- Configure the distinguished name for the LDAP group in the LDAP server.
- Create locales in Cisco UCS Manager (optional).
- Create custom roles in Cisco UCS Manager (optional).

### Procedure

---

**Step 1** In the **Navigation** pane, click **Admin**.

**Step 2** Expand **All > User Management > LDAP**.

**Step 3** Right-click **LDAP Group Maps** and choose **Create LDAP Group Map**.

**Step 4** In the **Create LDAP Group Map** dialog box, specify all LDAP group map information, as appropriate.

**Important** The name that you specify in the **LDAP Group DN** field must match the name in the LDAP database.

**Note** If you use a special character in the **LDAP Group DN** field, you must prefix the special character with an escape character \ (single back slash).

---

### What to Do Next

Set the LDAP group rule.

## Deleting an LDAP Group Map

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > LDAP**.
  - Step 3** Expand **LDAP Group Maps**.
  - Step 4** Right-click the LDAP group map that you want to delete and choose **Delete**.
  - Step 5** If a confirmation dialog box displays, click **Yes**.
- 

## Configuring RADIUS Providers

### Configuring Properties for RADIUS Providers

The properties that you configure in this task are the default settings for all provider connections of this type defined in Cisco UCS Manager. If an individual provider includes a setting for any of these properties, Cisco UCS uses that setting and ignores the default setting.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** In the **Admin** tab, expand **User Management > RADIUS**.
  - Step 3** In the **Properties** area, complete all fields.
  - Step 4** Click **Save Changes**.
- 

### What to Do Next

Create a RADIUS provider.

## Creating a RADIUS Provider

Cisco UCS Manager supports a maximum of 16 RADIUS providers.

### Before You Begin

Perform the following configuration in the RADIUS server:

- Configure users with the attribute that holds the user role and locale information for Cisco UCS Manager. You can choose whether to extend the RADIUS schema for this attribute. If you do not want to extend

the schema, use an existing RADIUS attribute to hold the Cisco UCS user roles and locales. If you prefer to extend the schema, create a custom attribute, such as the `cisco-avpair` attribute.

The vendor ID for the Cisco RADIUS implementation is 009 and the vendor ID for the attribute is 001.

The following syntax example shows how to specify multiples user roles and locales if you choose to create the `cisco-avpair` attribute: `shell:roles="admin,aaa" shell:locales="L1,abc"`. Use a comma `,` as the delimiter to separate multiple values.

- For a cluster configuration, add the management port IPv4 or IPv6 addresses for both fabric interconnects. This configuration ensures that remote users can continue to log in if the first fabric interconnect fails and the system fails over to the second fabric interconnect. All login requests are sourced from these IP addresses, not the virtual IP address used by Cisco UCS Manager.

### Procedure

---

**Step 1** In the **Navigation** pane, click **Admin**.

**Step 2** Expand **All > User Management > RADIUS**.

**Step 3** In the **Create RADIUS Provider** dialog box, specify all appropriate RADIUS service information.

**Note** If you use a hostname rather than an IPv4 or IPv6 address, you must ensure a DNS server is configured for the hostname.

**Step 4** Click **Save Changes**.

---

### What to Do Next

For implementations involving a single RADIUS database, select RADIUS as the primary authentication service.

For implementations involving multiple RADIUS databases, configure a RADIUS provider group.

## Deleting a RADIUS Provider

### Procedure

---

**Step 1** In the **Navigation** pane, click **Admin**.

**Step 2** In the **Admin** tab, expand **User Management > RADIUS**.

**Step 3** Right-click the RADIUS provider that you want to delete and choose **Delete**.

**Step 4** If a confirmation dialog box displays, click **Yes**.

---

# Configuring TACACS+ Providers

## Configuring Properties for TACACS+ Providers

The properties that you configure in this task are the default settings for all provider connections of this type defined in Cisco UCS Manager. If an individual provider includes a setting for any of these properties, Cisco UCS uses that setting and ignores the default setting.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** In the **Admin** tab, expand **User Management > TACACS+**.
  - Step 3** In the **Properties** area, complete the **Timeout** field.
  - Step 4** Click **Save Changes**.
- 

### What to Do Next

Create a TACACS+ provider.

## Creating a TACACS+ Provider

Cisco UCS Manager supports a maximum of 16 TACACS+ providers.

### Before You Begin

Perform the following configuration in the TACACS+ server:

- Create the `cisco-av-pair` attribute. You cannot use an existing TACACS+ attribute.  
The `cisco-av-pair` name is the string that provides the attribute ID for the TACACS+ provider.  
The following syntax example shows how to specify multiples user roles and locales when you create the `cisco-av-pair` attribute: `cisco-av-pair=shell:roles="admin aaa" shell:locales*"L1 abc"`.  
Using an asterisk (\*) in the `cisco-av-pair` attribute syntax flags the locale as optional, preventing authentication failures for other Cisco devices that use the same authorization profile. Use a space as the delimiter to separate multiple values.
- For a cluster configuration, add the management port IPv4 or IPv6 addresses for both fabric interconnects. This configuration ensures that remote users can continue to log in if the first fabric interconnect fails and the system fails over to the second fabric interconnect. All login requests are sourced from these IP addresses, not the virtual IP address used by Cisco UCS Manager.

### Procedure

---

**Step 1** In the **Navigation** pane, click **Admin**.

**Step 2** Expand **All > User Management > TACACS+**.

**Step 3** In the **Actions** area of the **General** tab, click **Create TACACS+ Provider**.

**Step 4** In the **Create TACACS+ Provider** dialog box:

a) Complete all fields with TACACS+ service information, as appropriate.

**Note** If you use a hostname rather than an IPv4 or IPv6 address, you must ensure a DNS server is configured for the hostname.

b) Click **OK**.

**Step 5** Click **Save Changes**.

---

### What to Do Next

For implementations involving a single TACACS+ database, select TACACS+ as the primary authentication service.

For implementations involving multiple TACACS+ databases, configure a TACACS+ provider group.

## Deleting a TACACS+ Provider

### Procedure

---

**Step 1** In the **Navigation** pane, click **Admin**.

**Step 2** In the **Admin** tab, expand **User Management > TACACS+**.

**Step 3** Right-click the TACACS+ provider that you want to delete and choose **Delete**.

**Step 4** If a confirmation dialog box displays, click **Yes**.

---

## Multiple Authentication Services Configuration

### Multiple Authentication Services

You can configure Cisco UCS to use multiple authentication services by configuring the following features:

- Provider groups
- Authentication domains

## Provider Groups

A provider group is a set of providers that the Cisco UCS accesses during the authentication process. All of the providers within a provider group are accessed in the order that the Cisco UCS provider uses to authenticate users. If all of the configured servers are unavailable or unreachable, Cisco UCS Manager automatically falls back to the local authentication method using the local username and password.

Cisco UCS Manager allows you to create a maximum of 16 provider groups, with a maximum of eight providers allowed per group.

## Creating an LDAP Provider Group

Creating an LDAP provider group allows you to authenticate using multiple LDAP databases.

### Before You Begin

Create one or more LDAP providers.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > LDAP**.
  - Step 3** Right-click **LDAP Provider Groups** and choose **Create LDAP Provider Group**.
    - Note** If you use a hostname rather than an IPv4 or IPv6 address, you must ensure a DNS server is configured for the hostname.
  - Step 4** In the **Create LDAP Provider Group** dialog box, specify all of the appropriate LDAP provider group information.
- 

### What to Do Next

Configure an authentication domain or select a default authentication service.

## Deleting an LDAP Provider Group

### Before You Begin

Remove the provider group from an authentication configuration.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > LDAP**.
  - Step 3** Expand **LDAP Provider Groups**.
  - Step 4** Right-click the LDAP provider group that you want to delete and choose **Delete**.
  - Step 5** If a confirmation dialog box displays, click **Yes**.
- 

## Creating a RADIUS Provider Group

Creating a RADIUS provider group allows you to authenticate using multiple RADIUS databases.

### Before You Begin

Create one or more RADIUS providers.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > RADIUS**.
  - Step 3** Right-click **RADIUS Provider Groups** and choose **Create RADIUS Provider Group**.
  - Step 4** In the **Create RADIUS Provider Group** dialog box, do the following:
    - a) In the **Name** field, enter a unique name for the group.  
This name can be between 1 and 127 ASCII characters.
    - b) In the **RADIUS Providers** table, choose one or more providers to include in the group.
    - c) Click the >> button to add the providers to the **Included Providers** table.  
You can use the << button to remove providers from the group.
    - d) (Optional) Use the **Move Up** or **Move Down** arrows in the **Included Providers** list to change the order in which the RADIUS providers authenticate providers.
    - e) After you add all of the required providers to the provider group, click **OK**.
- 

### What to Do Next

Configure an authentication domain or select a default authentication service.

## Deleting a RADIUS Provider Group

You cannot delete a provider group if another authentication configuration is using that provider group.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > RADIUS**.
  - Step 3** Expand **RADIUS Provider Groups**.
  - Step 4** Right-click the RADIUS provider group you want to delete and choose **Delete**.
  - Step 5** If a confirmation dialog box displays, click **Yes**.
- 

## Creating a TACACS+ Provider Group

Creating a TACACS+ provider group allows you to authenticate using multiple TACACS+ databases.

### Before You Begin

Create one or more TACACS+ providers.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > TACACS+**.
  - Step 3** Right-click **TACACS+ Provider Groups** and choose **Create TACACS+ Provider Group**.
  - Step 4** In the **Create TACACS+ Provider Group** dialog box, specify all TACACS+ provider group information, as appropriate.
- 

## Deleting a TACACS+ Provider Group

You cannot delete a provider group if another authentication configuration is using that provider group.

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
  - Step 2** Expand **All > User Management > TACACS+**.
  - Step 3** Expand **TACACS+ Provider Groups**.
  - Step 4** Right-click the TACACS+ provider group that you want to delete and choose **Delete**.
  - Step 5** If a confirmation dialog box displays, click **Yes**.
-

## Authentication Domains

The Cisco UCS Manager uses Authentication Domains to leverage multiple authentication systems. You can specify and configure each authentication domain during login; otherwise, Cisco UCS Manager uses the default authentication service configuration.

You can create up to eight authentication domains. Each authentication domain is associated with a provider group and a realm in the Cisco UCS Manager. The Cisco UCS Manager uses all servers within the realm if you do not specify a provider group.

## Creating an Authentication Domain

### Procedure

- 
- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > Authentication**.
- Step 3** Right-click **Authentication Domains** and choose **Create a Domain**.
- Step 4** In the **Create a Domain** dialog box, complete the following fields:

Name	Description
Name	<p>The name of the domain.</p> <p>This name can be between 1 and 16 alphanumeric characters. You cannot use spaces or any special characters other than - (hyphen), _ (underscore), : (colon), and . (period), and you cannot change this name after the object is saved.</p> <p><b>Note</b> For systems using the remote authentication protocol, the authentication domain name is considered part of the username and counts toward the 32-character limit for locally created usernames. Because Cisco UCS inserts 5 characters for formatting, authentication fails if the domain name and username combined characters total exceeds 27.</p>

Name	Description
<b>Web Session Refresh Period (sec)</b>	<p>When a web client connects to Cisco UCS Manager, the client must send refresh requests to Cisco UCS Manager to keep the web session active. This option specifies the maximum amount of time allowed between refresh requests for a user in this domain.</p> <p>If this time limit is exceeded, Cisco UCS Manager considers the web session inactive, but it does not terminate the session.</p> <p>Specify an integer between 60 and 172800. The default is 600 seconds when Two-Factor Authentication is not enabled and 7200 seconds when it is enabled.</p> <p><b>Note</b> The number of seconds set for the <b>Web Session Refresh Period</b> must be less than the number of seconds set for the <b>Web Session Timeout</b>. Do not set the <b>Web Session Refresh Period</b> to the same value as the <b>Web Session Timeout</b>.</p>
<b>Web Session Timeout (sec)</b>	<p>The maximum amount of time that can elapse after the last refresh request before Cisco UCS Manager considers a web session as inactive. If this time limit is exceeded, Cisco UCS Manager automatically terminates the web session.</p> <p>Specify an integer between 300 and 172800. The default is 7200 seconds when Two-Factor Authentication is not enabled and 8000 seconds when it is enabled.</p>
<b>Realm</b>	<p>The authentication protocol to apply to users in this domain. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Local</b>—The user account must be defined locally in this Cisco UCS domain.</li> <li>• <b>Radius</b>—The user must be defined on the RADIUS server specified for this Cisco UCS domain.</li> <li>• <b>Tacacs</b>—The user must be defined on the TACACS+ server specified for this Cisco UCS domain.</li> <li>• <b>Ldap</b>—The user must be defined on the LDAP server specified for this Cisco UCS domain.</li> </ul>
<b>Provider Group</b>	<p>The default provider group to use to authenticate users during remote login.</p> <p><b>Note</b> The <b>Provider Group</b> drop-down list displays when you select Ldap Radius, or Tacacs as the method to authenticate users.</p>

Name	Description
<b>Two Factor Authentication</b>	Two-Factor Authentication is available only when the <b>Realm</b> is set to <b>Radius</b> or <b>Tacacs</b> . When you select this check box, Cisco UCS Manager and the KVM launch manager require users whose accounts are authenticated by Radius or Tacacs servers to enter a token plus a password to log in. When 60 seconds remain for the <b>Web Session Refresh Period</b> to expire, users must generate a new token and enter the token plus their password to continue the session.

**Step 5** Click OK.

---

## Selecting a Primary Authentication Service

### Selecting the Console Authentication Service

#### Before You Begin

If the system uses a remote authentication service, create a provider for that authentication service. If the system uses only local authentication through Cisco UCS, you do not need to create a provider first.

#### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > Authentication**.
- Step 3** Click **Native Authentication**.
- Step 4** In the **Work** pane, click the **General** tab.
- Step 5** In the **Console Authentication** area, complete the following fields:

Name	Description
<b>Realm</b> field	<p>The method by which a user logging into the console is authenticated. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Local</b>—The user account must be defined locally in this Cisco UCS domain.</li> <li>• <b>Radius</b>—The user must be defined on the RADIUS server specified for this Cisco UCS domain.</li> <li>• <b>Tacacs</b>—The user must be defined on the TACACS+ server specified for this Cisco UCS domain.</li> <li>• <b>Ldap</b>—The user must be defined on the LDAP server specified for this Cisco UCS domain.</li> <li>• <b>None</b>—If the user account is local to this Cisco UCS domain, no password is required when the user logs into the console.</li> </ul>
<b>Provider Group</b> drop-down list	<p>The provider group to be used to authenticate a user logging into the console.</p> <p><b>Note</b> The <b>Provider Group</b> drop-down list is displayed when you select Ldap, Radius, or Tacacs as the method by which a user is authenticated.</p>
<b>Two Factor Authentication</b>	<p>Two-factor authentication is available only when the <b>Realm</b> is set to <b>Radius</b> or <b>Tacacs</b>. When this checkbox is selected, the Console requires users whose accounts are authenticated by Radius or Tacacs servers to enter a token plus a password to log in.</p>

**Step 6** Click **Save Changes**.

## Selecting the Default Authentication Service

### Before You Begin

If the system uses a remote authentication service, create a provider for that authentication service. If the system uses only local authentication through Cisco UCS, you do not need to create a provider first.

## Procedure

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > Authentication**.
- Step 3** Click **Native Authentication**.
- Step 4** In the **Work** pane, click the **General** tab.
- Step 5** In the **Default Authentication** area, complete the following fields:

Name	Description
<b>Realm</b> drop-down list	<p>The default method by which a user is authenticated during remote login. This can be one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Local</b>—The user account must be defined locally in this Cisco UCS domain.</li> <li>• <b>Radius</b>—The user account must be defined on the RADIUS server specified for this Cisco UCS domain.</li> <li>• <b>Tacacs</b>—The user account must be defined on the TACACS+ server specified for this Cisco UCS domain.</li> <li>• <b>Ldap</b>—The user account must be defined on the LDAP server specified for this Cisco UCS domain.</li> <li>• <b>None</b>—If the user account is local to this Cisco UCS domain, no password is required when the user logs in remotely.</li> </ul>
<b>Provider Group</b> drop-down list	<p>The default provider group to be used to authenticate the user during remote login.</p> <p><b>Note</b> The <b>Provider Group</b> drop-down is displayed when you select Ldap, Radius, or Tacacs as the method by which a user is authenticated.</p>
<b>Web Session Refresh Period (sec)</b>	<p>When a web client connects to Cisco UCS Manager, the client must send refresh requests to Cisco UCS Manager to keep the web session active. This option specifies the maximum amount of time allowed between refresh requests for a user in this domain.</p> <p>If this time limit is exceeded, Cisco UCS Manager considers the web session inactive, but it does not terminate the session.</p> <p>Specify an integer between 60 and 172800. The default is 600 seconds when Two-Factor Authentication is not enabled and 7200 seconds when it is enabled.</p>

Name	Description
<b>Web Session Timeout (sec)</b>	<p>The maximum amount of time that can elapse after the last refresh request before Cisco UCS Manager considers a web session as inactive. If this time limit is exceeded, Cisco UCS Manager automatically terminates the web session.</p> <p>Specify an integer between 300 and 172800. The default is 7200 seconds when Two-Factor Authentication is not enabled and 8000 seconds when it is enabled.</p>
<b>Two Factor Authentication</b> checkbox	<p>Two-Factor Authentication is available only when the <b>Realm</b> is set to <b>Radius</b> or <b>Tacacs</b>. When you select this check box, Cisco UCS Manager and the KVM launch manager require users whose accounts are authenticated by Radius or Tacacs servers to enter a token plus a password to log in. When 60 seconds remain for the <b>Web Session Refresh Period</b> to expire, users must generate a new token and enter the token plus their password to continue the session.</p> <p><b>Note</b> After you enable two factor authentication and save the configuration, the default <b>Web Session Refresh Period (sec)</b> changes to 7200, and the default <b>Web Session Timeout (sec)</b> changes to 8000.</p>

**Step 6** Click **Save Changes**.

## Role Policy for Remote Users

By default, if user roles are not configured in Cisco UCS Manager read-only access is granted to all users logging in to Cisco UCS Manager from a remote server using the LDAP, RADIUS, or TACACS protocols. For security reasons, it might be desirable to restrict access to those users matching an established user role in Cisco UCS Manager.

You can configure the role policy for remote users in the following ways:

### **assign-default-role**

Does not restrict user access to Cisco UCS Manager based on user roles. Read-only access is granted to all users unless other user roles have been defined in Cisco UCS Manager.

This is the default behavior.

### **no-login**

Restricts user access to Cisco UCS Manager based on user roles. If user roles have not been assigned for the remote authentication system, access is denied.

## Configuring the Role Policy for Remote Users

### Procedure

---

- Step 1** In the **Navigation** pane, click **Admin**.
- Step 2** Expand **All > User Management > Authentication**.
- Step 3** Click **Native Authentication**.
- Step 4** In the **Work** pane, click the **General** tab.
- Step 5** In the **Role Policy for Remote Users** field, click one of the following radio buttons to determine what happens when a user attempts to log in and the remote authentication provider does not supply a user role with the authentication information:
- **No Login**—The user is not allowed to log in to the system, even if the username and password are correct.
  - **Assign Default Role**—The user is allowed to log in with a read-only user role.
- Step 6** Click **Save Changes**.
-