



Managing FC Alias

This chapter contains the following sections:

- [About FC Alias, on page 1](#)
- [Creating a FC Alias , on page 1](#)
- [Updating a FC Alias, on page 2](#)
- [Deleting a FC Alias, on page 2](#)

About FC Alias

FC Alias is the alias for World Wide Port Names (WWPNs) on the fabric for a particular VSAN.

In Cisco UCS Director, you can manage FC Alias on the following Cisco network devices:

- Cisco Nexus 5000, 5500, and 5672 Series switches
- Cisco Nexus 7000 Series switches
- Cisco MDS 9100 Series switches
- Cisco MDS 9500 Series switches
- Cisco MDS 9700 Series switches

Creating a FC Alias

Step 1 Choose **Physical > Network**.

Step 2 On the **Network** page, choose the pod.

Step 3 Select the network device to be configured.

Step 4 Click **View Details**.

Note For creating a FC Alias for Cisco Nexus 7000 Series switches, expand the pod and choose the network device. Click the **VDC** tab, choose the storage type VDC, and click **View Details**.

Step 5 Click the **FCAlias** tab.

Step 6 Click **Add**.

Step 7 In the **Create FCAlias** screen, complete the following fields:

Name	Description
FC Alias Name field	Name of the alias.
VSAN Id field	Click Select . In the Select dialog box, choose the VSAN ID.
Member Type drop-down	Choose one of the following as the type of member: <ul style="list-style-type: none"> • DeviceAlias • pWWN • fWWN
Member field	The value for the member.
Copy Running configuration to Startup configuration check box	Check the check box to copy the running configuration to the startup configuration.

Step 8 Click **Submit**.

Updating a FC Alias

Step 1 In the **FCAlias** tab, select the FC Alias to be updated.

Step 2 Click **Modify**.

Step 3 In the **Update FCAlias** dialog box, complete the following fields:

Name	Description
VDC Name field	Click Select . In the Select dialog box, choose the VDC.
Members List table	The list of members in the Alias.
Copy Running configuration to Startup configuration check box	Check the check box to copy the running configuration to the startup configuration.

Step 4 Click **Submit**.

Deleting a FC Alias

Step 1 In the **FCAlias** tab, select the FC Alias to be deleted.

Step 2 Click **Delete**.

The **Delete FCAlias** dialog box appears to confirm deletion of FC Alias.

- Step 3** Check the **Copy Running configuration to Startup configuration** check box to copy the configuration to the startup configuration.
- Step 4** Click **Submit**.
-

