



CHAPTER 5

Managing the Device Profile

This chapter provides procedures for managing the device profile.

This chapter includes the following sections:

- [Creating a DNS Server Host Name, page 5-1](#)
- [Creating an NTP Server Host Name, page 5-3](#)
- [Deleting a DNS Server Host Name, page 5-4](#)
- [Deleting an NTP Server Host Name, page 5-7](#)
- [Displaying the Device Profile, page 5-10](#)
- [Setting the Core File Policy, page 5-11](#)
- [Setting the Fault Policy, page 5-12](#)
- [Setting the Log Policy, page 5-13](#)
- [Setting the Syslog Policy, page 5-15](#)
- [Setting the Timezone, page 5-16](#)
- [Displaying the DNS Server, page 5-17](#)
- [Displaying the Domain Name, page 5-19](#)
- [Displaying the NTP Server, page 5-20](#)

Creating a DNS Server Host Name

You can create a Domain Name Server (DNS) hostname.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. `connect policy-mgr`

Send document comments to vnmc-docfeedback@cisco.com

2. **scope org**
3. **scope deviceprofile** <profile-name>
4. **create dns** <ip-address>
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|---------------|--|---|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | create dns Example vnmc(policy-mgr) /org/deviceprofile # create dns 209.165.200.225 | Creates a DNS host name. Specify the host name as an IP address in the format a.b.c.d. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to create a DNS host name:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # create dns 209.165.200.225
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #

```

Send document comments to vnmc-docfeedback@cisco.com

Creating an NTP Server Host Name

You can create a network time protocol (NTP) server hostname.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** *<profile-name>*
4. **create ntp-server** *<server-name>*
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | create ntp-server Example vnmc(policy-mgr) /org/deviceprofile # create ntp-server networkTime | Creates a NTP server host name. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to create a NTP server host name:

```
vnmc# connect policy-mgr
```

Send document comments to vnmc-docfeedback@cisco.com

Cisco Virtual Network Management Center
 TAC support: <http://www.cisco.com/tac>
 Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
 The copyrights to certain works contained in this software are owned by other third parties and used and distributed under license. Certain components of this software are licensed under the GNU General Public License (GPL) version 2.0 or the GNU Lesser General Public License (LGPL) Version 2.1. A copy of each such license is available at <http://www.opensource.org/licenses/gpl-2.0.php> and <http://www.opensource.org/licenses/lgpl-2.1.php>

```
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # create ntp-server networkTime
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #
```

Deleting a DNS Server Host Name

You can delete a Domain Name Server (DNS) hostname.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **delete dns <ip-address>**
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |

Send document comments to vnmc-docfeedback@cisco.com

| | Command | Purpose |
|--------|--|------------------------------------|
| Step 3 | scope deviceprofile DP0 Example vnmc(policy-mgr) /org # scope deviceprofile | Places you in device profile mode. |
| Step 4 | delete dns Example vnmc(policy-mgr) /org/deviceprofile # delete dns 209.165.200.225 | Deletes a DNS host name. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to delete a DNS server host name:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr) # scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # delete dns 209.165.200.225
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #

```

Creating the Domain Name

You can create the domain name.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**

Send document comments to vnmc-docfeedback@cisco.com

2. **scope org**
3. **scope deviceprofile** <profile-name>
4. **scope domain-name** <domain-name>
5. **set domain** <domain-name>
6. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | scope domain-name Example vnmc(policy-mgr) /org/deviceprofile # scope domain-name DN0 | Places you in domain mode. |
| Step 5 | set domain Example vnmc(policy-mgr) /org/deviceprofile # set domain EaTest | Creates the domain name. |
| Step 6 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to create the domain name:

```
VNMC-Tech-Docs# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
```

Send document comments to vnmc-docfeedback@cisco.com

```
vnmc(policy-mgr) # scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # scope domain-name DN0
vnmc(policy-mgr) /org/deviceprofile/domain-name # set domain EaTest
vnmc(policy-mgr) /org/deviceprofile/domain-name* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile/domain-name* #
```

Deleting an NTP Server Host Name

You can delete a network time protocol (NTP) server hostname.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** *<profile-name>*
4. **delete ntp-server** *<server-name>*
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |

Send document comments to vnmc-docfeedback@cisco.com

| | Command | Purpose |
|--------|--|------------------------------------|
| Step 4 | delete ntp-server Example vnmc(policy-mgr) /org/deviceprofile # delete ntp-server networkTime | Deletes a NTP server host name. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to delete a NTP server host name:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # delete ntp-server networkTime
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #

```

Setting the Domain Name

You can set the domain name.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** <profile-name>
4. **scope domain-name** <domain-name>
5. **set domain** <domain-name>

Send document comments to vnmc-docfeedback@cisco.com

6. commit-buffer

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | scope domain-name Example vnmc(policy-mgr) /org/deviceprofile # scope domain-name DN0 | Places you in domain name mode. |
| Step 5 | set domain Example vnmc(policy-mgr) /org/deviceprofile/domain-name # set domain testOne | Sets the domain name. |
| Step 6 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the domain name:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # scope domain-name DN0
vnmc(policy-mgr) /org/deviceprofile/domain-name # set domain testOne
vnmc(policy-mgr) /org/deviceprofile/domain-name* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile/domain-name #
```

Send document comments to vnmc-docfeedback@cisco.com

Displaying the Device Profile

You can display the device profile.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **show deviceprofile**

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | show deviceprofile Example vnmc(policy-mgr) /org # show deviceprofile | Displays the device profile. |

EXAMPLES

This example shows how to display the device profile:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # show deviceprofile
```

Send document comments to vnmc-docfeedback@cisco.com

```
Name: default
Core File Policy:
Fault Policy: default
Log File Policy: default
Syslog Policy:
vnmc(policy-mgr) /org #
```

Setting the Core File Policy

You can set the core file policy.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** *<profile-name>*
4. **set corefile** *<policy-name>*
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |

Send document comments to vnmc-docfeedback@cisco.com

| | Command | Purpose |
|--------|---|------------------------------------|
| Step 4 | set corefile Example vnmc(policy-mgr) /org/deviceprofile # set corefile EaCorePA13 | Sets the core file policy. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the core file policy:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile default
vnmc(policy-mgr) /org/deviceprofile # set corefile EaCorePA13
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #

```

Setting the Fault Policy

You can set the fault policy.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** <profile-name>
4. **set faultpolicy** <policy-name>
5. **commit-buffer**

Send document comments to vnmc-docfeedback@cisco.com

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | set faultpolicy Example vnmc(policy-mgr) /org/deviceprofile # set faultpolicy EaFaultPA12 | Sets the fault policy. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the fault policy:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # set faultpolicy EaFaultPA12
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #
```

Setting the Log Policy

You can set the log policy.

Send document comments to vnmc-docfeedback@cisco.com**BEFORE YOU BEGIN**

See [VNMC CLIs Basic Commands](#), page 1-5 for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **set log <policy-name>**
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|---------------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | set log Example vnmc(policy-mgr) /org/deviceprofile # set log EaLogPA12 | Sets the log policy. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the log policy:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
```

Send document comments to vnmc-docfeedback@cisco.com

```

the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # set log EaLogPA12
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #

```

Setting the Syslog Policy

You can set the syslog policy.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **set syslog <policy-name>**
5. **commit-buffer**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |

Send document comments to vnmc-docfeedback@cisco.com

| | Command | Purpose |
|--------|--|------------------------------------|
| Step 4 | set syslog Example vnmc(policy-mgr) /org/deviceprofile # set syslog EaSysPA12 | Sets the syslog policy. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the syslog policy:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # set syslog EaSysPA12
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #
```

Setting the Timezone

You can set the timezone.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **set timezone <zone-name>**
5. **commit-buffer**

Send document comments to vnmc-docfeedback@cisco.com

DETAILED STEPS

| | Command | Purpose |
|--------|---|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | set timezone Example vnmc(policy-mgr) /org/deviceprofile # set timezone pacific | Sets the timezone. |
| Step 5 | commit-buffer Example vnmc(policy-mgr) /org/deviceprofile* # commit-buffer | Commits (saves) the configuration. |

EXAMPLES

This example shows how to set the timezone:

```
vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php
vnmc(policy-mgr)# scope org
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # set timezone pacific
vnmc(policy-mgr) /org/deviceprofile* # commit-buffer
vnmc(policy-mgr) /org/deviceprofile #
```

Displaying the DNS Server

You can display the DNS server.

Send document comments to vnmc-docfeedback@cisco.com

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands](#), page 1-5 for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **show dns**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | show dns Example vnmc(policy-mgr) /org/deviceprofile # show dns | Displays the DNS server. |

EXAMPLES

This example shows how to display the DNS server:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

vnmc(policy-mgr)# scope org

```

Send document comments to vnmc-docfeedback@cisco.com

```
vnmc(policy-mgr) /org # scope deviceprofile DP0
vnmc(policy-mgr) /org/deviceprofile # show dns
```

```
Domain Name Servers:
  IP Address: 209.165.200.226
vnmc(policy-mgr) /org/deviceprofile #
```

Displaying the Domain Name

You can display the domain name.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile** *<profile-name>*
4. **show domain-name**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | show domain-name Example vnmc(policy-mgr) /org/deviceprofile # show domain-name | Displays the domain name. |

EXAMPLES

This example shows how to display the domain name:

Send document comments to vnmc-docfeedback@cisco.com

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

VNMC-Tech-Docs(policy-mgr)# scope org
VNMC-Tech-Docs(policy-mgr) /org # scope deviceprofile DP0
VNMC-Tech-Docs(policy-mgr) /org/deviceprofile # show domain-name

Domain Name:
  Domain
  -----
  Cisco.com
vnmc(policy-mgr) /org/deviceprofile #

```

Displaying the NTP Server

You can display the NTP server.

BEFORE YOU BEGIN

See [VNMC CLIs Basic Commands, page 1-5](#) for basic information about the VNMC CLI.

CLI

Policy manager

SUMMARY STEPS

1. **connect policy-mgr**
2. **scope org**
3. **scope deviceprofile <profile-name>**
4. **show ntp**

DETAILED STEPS

| | Command | Purpose |
|--------|--|---------------------------------------|
| Step 1 | connect policy-mgr Example: vnmc# connect policy-mgr | Places you in the policy manager CLI. |
| Step 2 | scope org Example: vnmc(policy-mgr)# scope org | Places you in organization mode. |

Send document comments to vnmc-docfeedback@cisco.com

| | Command | Purpose |
|--------|--|------------------------------------|
| Step 3 | scope deviceprofile Example vnmc(policy-mgr) /org # scope deviceprofile DP0 | Places you in device profile mode. |
| Step 4 | show ntp Example vnmc(policy-mgr) /org/deviceprofile # show ntp | Displays the NTP server. |

EXAMPLES

This example shows how to display the NTP server:

```

vnmc# connect policy-mgr
Cisco Virtual Network Management Center
TAC support: http://www.cisco.com/tac
Copyright (c) 2002-2010, Cisco Systems, Inc. All rights reserved.
The copyrights to certain works contained in this software are
owned by other third parties and used and distributed under
license. Certain components of this software are licensed under
the GNU General Public License (GPL) version 2.0 or the GNU
Lesser General Public License (LGPL) Version 2.1. A copy of each
such license is available at
http://www.opensource.org/licenses/gpl-2.0.php and
http://www.opensource.org/licenses/lgpl-2.1.php

VNMC-Tech-Docs(policy-mgr)# scope org
VNMC-Tech-Docs(policy-mgr) /org # scope deviceprofile DP0
VNMC-Tech-Docs(policy-mgr) /org/deviceprofile # show ntp

NTP Servers:
  Name: EaTest
VNMC-Tech-Docs(policy-mgr) /org/deviceprofile #

```

Send document comments to vnmc-docfeedback@cisco.com