



CHAPTER 4

Cable Connections and Pin-outs

This section describes the following topics:

- [Unit RS-232 9-Pin Serial Port, page 4-1](#)
- [RJ-45 8-Pin IP Network Port, page 4-2](#)

Unit RS-232 9-Pin Serial Port

[Table 4-1](#) describes the Cisco Unified Videoconferencing 3515 MCU unit RS-232 9-pin D-type serial port pin-out configuration.

Table 4-1 *RS-232 9-pin D-Type Serial Port Pin-out*

| Pin | Function | I/O |
|-----|----------|--------|
| 1 | NC | |
| 2 | RXD | Input |
| 3 | TXD | Output |
| 4 | NC | |
| 5 | GND | |
| 6 | NC | |
| 7 | NC | |
| 8 | NC | |
| 9 | NC | |

RJ-45 8-Pin IP Network Port

Table 4-2 describes the pin-out configuration of the RJ-45 IP network port.

Table 4-2 Pin-out Configuration of the RJ-45 IP Network Port

| Pin | Function | I/O |
|-----|----------|--------|
| 1 | TXD+ | Output |
| 2 | TXD+ | Output |
| 3 | RXD+ | Input |
| 4 | NC | |
| 5 | NC | |
| 6 | RXD- | Input |
| 7 | NC | |
| 8 | NC | |