



## GLOSSARY

Revised: May 14, 2012, OL-25016-02

### A

<b>AAA</b>	authentication, authorization, and accounting
<b>ACAR</b>	automatic callback and automatic rollback
<b>ACF</b>	admission confirmation
<b>ACG</b>	automatic call gapping
<b>ACK</b>	acknowledge
<b>ACL</b>	access control list, automatic congestion level
<b>ACTV</b>	active
<b>ADDR</b>	address
<b>ADM</b>	administrative
<b>AGGR</b>	aggregation
<b>AIN</b>	Advanced Intelligent Network
<b>ALT</b>	alternate
<b>ANC</b>	announcements module
<b>ANI</b>	automatic number identification
<b>ANSI</b>	American National Standards Institute
<b>AOR</b>	address of record
<b>API</b>	application programming interface
<b>ARQ</b>	admission request
<b>AS</b>	application server
<b>ASC</b>	associate
<b>ASP</b>	application service provider
<b>ATIS</b>	Alliance for Telecommunications Industry Solutions

**AUCX** audit connection

**AUEP** audit endpoint

## B

**B8ZS** binary 8-zero substitution

**BCM** Basic Call module

**BDMS** Bulk Data Management System

**BHCA** Busy Hour Call Attempts

**BLG** billing

**BLO** blocking

**BTS** Broadband Telephony Softswitch

**BW** bandwidth

## C

**CA** Call Agent

**CA** California

**CALLP** call processing

**CAROT** Centralized Automatic Reporting on Trunks

**CAS** channel-associated signaling

**CCB** call control block

**CCR** continuity check request

**CCU** Call Control unit

**CD** compact disk

**CDB** call data block

**CD-ROM** compact disk–read only memory

**CDT** Central Daylight Time

**CFG** configuration

**CFN** confusion

<b>CGB</b>	circuit group blocking
<b>CGU</b>	circuit group unblocking
<b>CIC</b>	circuit identification code, carrier identification code
<b>CLI</b>	command line interface
<b>CLLI</b>	common language location identifier
<b>CMJ</b>	circuit reservation rejected
<b>CMTS</b>	cable modem termination system
<b>CNAM</b>	calling name delivery
<b>CODEC</b>	coder/decoder, compression/decompression
<b>COPS</b>	Common Open Policy Service Protocol
<b>CORBA</b>	Common Object Request Broker Architecture
<b>COT</b>	customer-originated trace, continuity testing, central office termination
<b>CPE</b>	customer premises equipment
<b>CPU</b>	central processing unit
<b>CQM</b>	circuit query message
<b>CQR</b>	circuit query response
<b>CRC</b>	cyclic redundancy check
<b>CRCX</b>	create connection
<b>CS</b>	capability set (for example, CS-2)
<b>CST</b>	Central Standard Time
<b>CTRL</b>	control
<b>CTX</b>	Centrex
<b>CVM</b>	circuit verification message
<b>CVR</b>	circuit verification response
<b>CVT</b>	circuit validation test

## D

<b>DB</b>	database
<b>DBA</b>	database administrator
<b>DBM</b>	database management
<b>DF</b>	delivery function
<b>DHCP</b>	Dynamic Host Configuration Protocol
<b>DLCX</b>	delete connection
<b>DLY</b>	delay
<b>DN</b>	directory number
<b>DNIS</b>	dialed number identification service
<b>DNS</b>	domain name system
<b>DPC</b>	destination point code
<b>DSCP</b>	differentiated service code point
<b>DUPU</b>	destination user part unavailable

## E

<b>EA</b>	equal access
<b>EGA</b>	event generator
<b>EM</b>	Element Manager
<b>EM</b>	event message
<b>EMEA</b>	Europe, Middle East, and Asia
<b>EMS</b>	Element Management System
<b>EP</b>	endpoint
<b>EPCF</b>	endpoint connection
<b>ER</b>	easily recognizable
<b>ESA</b>	enhanced subscriber authentication
<b>ESF</b>	extended super frame

**F**

<b>FAS</b>	facility associated signaling
<b>FCAPS</b>	Fault, Configuration, Accounting, Performance, and Security
<b>FPGA</b>	field programmable gate array
<b>FQDN</b>	fully qualified domain name
<b>FS</b>	Feature Server
<b>FSAIN</b>	Feature Server for AIN services
<b>FSPTC</b>	Feature Server for POTS, Tandem, and Centrex services
<b>FTP</b>	File Transfer Protocol
<b>FXS</b>	Foreign Exchange Station

**G**

<b>GAP</b>	generic address parameter
<b>GB</b>	gigabits
<b>GCF</b>	gatekeeper confirmation
<b>GK</b>	gatekeeper
<b>GMT</b>	Greenwich Mean Time
<b>GRA</b>	group reset acknowledge
<b>GRJ</b>	gatekeeper reject
<b>GRP</b>	group
<b>GRQ</b>	gatekeeper request
<b>GRS</b>	group reset
<b>GTD</b>	generic transport descriptor
<b>GTT</b>	global title translation
<b>GUI</b>	Graphical User Interface
<b>GW</b>	gateway

## H

<b>H323</b>	H.323 Protocol
<b>H323GW</b>	H323 gateway
<b>H3A</b>	H.323 signaling adapter
<b>HB</b>	heartbeat
<b>HSS</b>	Home Subscriber Server

## I

<b>IAD</b>	integrated access device
<b>IAM</b>	initial address message
<b>ICMP</b>	Internet Control Message Protocol
<b>ID</b>	identification
<b>IDX</b>	index
<b>IE</b>	information element
<b>IETF</b>	Internet Engineering Task Force
<b>IN</b>	intelligent network
<b>INF</b>	information
<b>INIT</b>	initialize
<b>INR</b>	information request
<b>INS</b>	in service
<b>IOS</b>	Integrated Operating System
<b>IP</b>	Internet Protocol
<b>IPC</b>	inter-process communication
<b>IPM</b>	Internet Protocol Manager
<b>IPsec</b>	Internet Protocol security
<b>ISDN</b>	Integrated Services Digital Network
<b>ISP</b>	Internet service provider
<b>ISUP</b>	ISDN user part

**ITL** Incoming Test Line (same as TTL)

**ITP** IP transfer point

**IVR** interactive voice response

**IXC** interexchange carrier

## J

**JMS** Java message service

## K

**KAM** keepalive module

**kb** kilobit

**KMS** Kerberized management server

## L

**LAF** log archive facility

**LATA** local access and transport area

**LBLK** locally blocked

**LIDB** line information database

**LNP** local number portability

**LPA** loop prevention acknowledgement

**LRN** local routing number

**LSA** local serving area

## M

**M3UA** MTP3 user adapter

**Mb** megabit

**MDCX** modify connection

**MDL** message definition language

<b>MGA</b>	media gateway adapter
<b>MGCP</b>	Media Gateway Control Protocol
<b>MGW</b>	media gateway
<b>MIB</b>	Management Information Base
<b>MIM</b>	M3UA Interface Module
<b>MRMW</b>	multiple readers and multiple writers
<b>ms</b>	millisecond
<b>MTA</b>	media terminal adapter, Metropolitan Trading Area
<b>MTP</b>	message transfer part
<b>MTP1</b>	message transfer part 1
<b>MTP2</b>	message transfer part 2
<b>MTP3</b>	message transfer part 3
<b>MTU</b>	maximum transmission unit

**N**

<b>NANP</b>	North American Numbering Plan
<b>NAS</b>	network access server
<b>NCS</b>	network-based call signaling
<b>NFAS</b>	not facility associated signaling
<b>NFS</b>	network file server
<b>NGN</b>	Next Generation Networks
<b>NIIF</b>	Network Interconnection Interoperability Forum
<b>NML</b>	Network Management Layer
<b>NMS</b>	network management system
<b>NNN</b>	numeric number nomenclature
<b>NOA</b>	nature of address
<b>NPA</b>	Numbering Plan Area
<b>NPAC</b>	Number Portability Administration Center

<b>NR</b>	nonrecoverable
<b>NTP</b>	Network Time Protocol
<b>NU</b>	network unit
<b>NUM</b>	number
<b>NW</b>	network

**O**

<b>OAMP</b>	operations, administration, maintenance, and provisioning
<b>OLI</b>	originating line information
<b>OMNI</b>	Ulticom SS7 stack
<b>OMS</b>	OptiCall Messaging System
<b>OPC</b>	originating point code
<b>OPT</b>	Open Packet Telephony
<b>ORA</b>	Oracle
<b>OS</b>	operating system
<b>OSS</b>	operations support system
<b>OTL</b>	Originating Test Line

**P**

<b>PBX</b>	private branch exchange
<b>PDM</b>	process debug manager
<b>PDU</b>	protocol decode unit
<b>PIC</b>	presubscribed interexchange carrier, point in call
<b>PID</b>	process ID
<b>PMG</b>	process manager
<b>POP</b>	point of presence
<b>POTS</b>	plain old telephone service

<b>PRI</b>	primary rate interface
<b>PSTN</b>	public switched telephone network

## Q

<b>QAM</b>	queue processing module
<b>QoS</b>	quality of service
<b>QVT</b>	Query Verification Tool

## R

<b>RAM</b>	random access memory
<b>RAS</b>	Registration, Admissions, and Status
<b>RBLK</b>	remote block
<b>REL</b>	release
<b>RFC</b>	request for comment
<b>RGW</b>	residential gateway
<b>RKEY</b>	routing key
<b>RKS</b>	record keeping system
<b>RLC</b>	release complete
<b>RMAN</b>	recovery manager
<b>ROM</b>	read only memory
<b>ROTL</b>	Remote Office Test Line
<b>RPF</b>	registration and profiling tool
<b>RQNT</b>	request for notification
<b>RQNT</b>	notification request
<b>RR</b>	resource record
<b>RRJ</b>	request rejected
<b>RRQ</b>	registration request
<b>RSC</b>	reset circuit

<b>RSIP</b>	restart in progress
<b>RT</b>	retransact
<b>RTM</b>	routing module
<b>RTO</b>	retransmission time out
<b>RTP</b>	Real Time Transport Protocol
<b>RUDP</b>	Reliable User Datagram Protocol
<b>RX</b>	retransmit

**S**

<b>S1</b>	severity 1
<b>S2</b>	severity 2
<b>S3</b>	severity 3
<b>S4</b>	severity 4
<b>S7A</b>	SS7 adapter
<b>S7M</b>	SS7 module
<b>SA</b>	security association
<b>SAI</b>	signaling adapter interface
<b>SAP</b>	service access point
<b>SCA</b>	selective call acceptance, status control adapter
<b>SCC</b>	signaling connection control
<b>SCCP</b>	signaling connection control part
<b>SCCS</b>	Switched Control Center System
<b>SCP</b>	service control point, signal control point
<b>SCTP</b>	Stream Control Transmission Protocol
<b>SDH</b>	Synchronous Digital Hierarchy
<b>SDN</b>	software defined network
<b>SFTP</b>	Secure File Transfer Protocol
<b>SG</b>	signaling gateway

<b>SGP</b>	signaling gateway process
<b>SHR</b>	System Health Report (system-health)
<b>SIA</b>	SIP adapter
<b>SID</b>	system identification number
<b>SIP</b>	Session Initiation Protocol
<b>SLC</b>	signaling link code
<b>SLHR</b>	Service Logic Host Route
<b>SM</b>	system manager
<b>SMG</b>	system manager program
<b>SMS</b>	service management system
<b>SNMP</b>	Simple Network Management Protocol
<b>SONET</b>	Synchronous Optical Network
<b>SP</b>	service provider
<b>SQL</b>	Structured Query Language
<b>SRV</b>	service
<b>SS7</b>	Signaling System 7
<b>SSH</b>	secure shell
<b>SSN</b>	subsystem number
<b>SSP</b>	signal switching point
<b>STP</b>	signal transfer point
<b>SUA</b>	SCCP user adapter
<b>SUB</b>	subscriber

## T

<b>T1</b>	trunk level 1
<b>T3</b>	trunk level 3
<b>T5</b>	timer 5
<b>T13</b>	timer 13

<b>T15</b>	timer 15
<b>T17</b>	timer 17
<b>T19</b>	timer 19
<b>T21</b>	timer 21
<b>T23</b>	timer 23
<b>T28</b>	timer 28
<b>T<sub>CCR</sub></b>	timer continuity check request
<b>TAC</b>	Technical Assistance Center
<b>TCAP</b>	Transaction Capabilities Application Part
<b>TCP</b>	Transmission Control Protocol
<b>TDM</b>	telecommunications data link monitor
<b>TEI</b>	terminal endpoint identifier
<b>TERMID</b>	Termination Identification
<b>TFC</b>	transfer controlled
<b>TG</b>	trunk group, trunking gateway
<b>TGID or TGN-ID</b>	trunk group ID
<b>TIA</b>	Telecommunications Industry Association
<b>TMM</b>	Traffic and Measurements module
<b>TMN</b>	Telecommunications Management Network (ITU-T)
<b>TOS</b>	type of service
<b>TPM</b>	terminating point master
<b>TRNS</b>	transient
<b>TSA</b>	TCAP signaling adapter
<b>TSAP</b>	transport service access point
<b>TT</b>	translation type
<b>TTL</b>	Terminating Test Line
<b>TVT</b>	Translation Verification Tool

## U

<b>UBL</b>	unblocking message
<b>UDP</b>	User Datagram Protocol
<b>UEQP</b>	unequipped
<b>ULP</b>	Upper Layer Protocol
<b>URI</b>	uniform resource identifier
<b>URL</b>	universal resource locator
<b>US</b>	United States
<b>USA</b>	United States of America

## V

<b>VOA</b>	Voice Over ATM
<b>VOIP</b>	voice over IP
<b>VOP</b>	Voice Over Packet
<b>VTOC</b>	volume table of contents

## W

## X

<b>XUA</b>	extended unit association
<b>XUDTS</b>	extended unit data service

## Y

## Z