



INDEX

A

adding

- administrator account for Greetings Administrator [9-5](#)
- administrator accounts, default settings (in Connection Administration) [9-3](#)
- alternate contact numbers [4-56](#)
- alternate extensions [4-75](#)
- alternate names [4-79](#)
- class of service [6-2](#)
- MWIs for other extensions [4-6](#)
- SMTP proxy addresses for contacts [10-5](#)
- SMTP proxy addresses for users [4-84](#)
- user accounts, default (in Connection Administration) [9-2](#)
- user templates [7-2, 8-4](#)

addressing priority lists, enabling [4-48](#)

Administrator account [1-2](#)

administrators

- accounts created by importing from Cisco Unified Communications Manager [12-1, 12-2](#)
- creating [9-1](#)
- creating by importing LDAP data [13-2](#)
- deleting [14-2](#)

after sign-in conversation, changing [4-25](#)

alias, effect of changing [14-1](#)

alternate contact numbers [4-56](#)

alternate extensions

- adding [4-75](#)
- advanced settings [4-78](#)
- changing [4-76](#)
- class of service settings [5-2](#)
- custom settings [4-78](#)

deleting [4-77](#)

overview [4-74](#)

alternate greeting

- notification prompt [4-58](#)
- preventing callers from leaving messages [4-59](#)
- preventing callers from skipping [4-59](#)
- transfer to greeting without ringing phone [4-59](#)

alternate names

- adding [4-79](#)
- overview [4-78](#)

application users

- creating [9-1](#)
- deleting [14-2](#)

B

broadcast messages, enabling users to send [4-42](#)

Bulk Administration Tool, accessing [11-3](#)

Bulk Edit, accessing [11-1](#)

C

caller input overview [4-53](#)

call holding

- class of service settings [5-3](#)
- defined [4-8](#)

call screening

- class of service settings [5-3](#)
- defined [4-8](#)

call transfers

- class of service settings [5-3](#)
- defined [4-8](#)

cascading message notification [4-72](#)

- chaining message notification [4-73](#)
- Cisco PCA, securing and changing password [4-4](#)
- Cisco Unified MeetingPlace [4-81](#)
- Cisco Unified MeetingPlace Express [4-81](#)
- Cisco Unified Personal Communicator, configuring to access voice messages [5-2](#)
- Cisco Unity Connection Messaging Assistant, enabling access to [5-4](#)
- Cisco Unity Connection Messaging Inbox, enabling access to [5-5](#)
- class of service
 - adding [6-2](#)
 - alternate extensions [5-2](#)
 - assigning and reassigning users [6-4](#)
 - assigning or reassigning users [6-4](#)
 - Cisco Unified Personal Communicator [5-2](#)
 - Cisco Unity Connection Messaging Assistant [5-4](#)
 - Cisco Unity Connection Messaging Inbox [5-5](#)
 - defaults [6-2](#)
 - deleted message access [5-7](#)
 - deleting [6-4](#)
 - directory listing [5-8](#)
 - greeting length [5-8](#)
 - IMAP client access [5-9](#)
 - live reply [5-11](#)
 - message length [5-12](#)
 - modifying [6-2](#)
 - overview [2-2](#)
 - personal call transfer rules [5-13](#)
 - private distribution lists [5-15](#)
 - restriction tables [5-19](#)
 - sending messages to system distribution list [5-21](#)
 - transfer, screening, and holding [5-3](#)
 - unified client [5-2](#)
- contacts
 - administrator-defined [1-2](#)
 - configuring SMTP proxy addresses for [10-5](#)
 - creating [10-3](#)
 - deleting [10-4](#)
 - finding [3-2](#)

- modifying [10-3](#)
 - overview [10-1](#)
 - user-defined [1-2](#)
- contact templates [10-2](#)
- conversation
 - changing menu responses [4-19](#)
 - changing menu style [4-17](#)
 - changing speed and volume [4-24](#)
 - changing versions [4-16](#)
 - customizing sign-in [4-25](#)
 - option summary [4-14](#)
- credentials [4-2](#)

D

- deleted messages, accessing [5-7](#)
- deleting
 - alternate extensions [4-77](#)
 - class of service [6-4](#)
 - MWIs [4-7](#)
 - user accounts [14-3](#)
 - user templates [7-5, 8-12, 8-13, 8-16](#)
- directory, enabling users to choose to be listed [5-8](#)
- directory handlers
 - default [4-52](#)
 - System Directory Handler [4-52](#)

E

- email in external message store, user access [4-81, 4-82](#)
- enabling
 - addressing priority lists [4-48](#)
 - IMAP client access to voice messages [5-9](#)
 - message aging policy for users [4-12](#)
 - personal call transfer rules [5-15](#)
 - SpeechView for a class of service [5-23](#)
 - Text to Speech for a user [4-82, 4-83](#)
 - voice recognition for a class of service [5-24](#)

Exchange calendars and contacts, accessing [4-80](#)

F

forwarded (relay) messages [4-49](#)

G

greetings

allowing caller input during greetings [4-53](#)

alternate greeting notification prompt [4-58](#)

enabling [4-59](#)

enabling callers to transfer to an alternate contact number during [4-56](#)

managing calls when the alternate greeting is enabled [4-59](#)

overview [4-52](#)

recording in multiple languages [4-60](#)

specifying maximum length [5-8](#)

summary of types available [4-52](#)

I

IMAP client access to voice messages, enabling [5-9](#)

L

languages

language outside callers hear [4-11, 4-21](#)

phone language that users hear [4-21](#)

recording greetings in multiple languages [4-60](#)

LDAP data

creating administrators by importing [13-2](#)

creating user accounts by importing [13-2](#)

live reply, enabling [5-11](#)

M

mailbox-size quotas, customizing for users or templates [4-12](#)

message actions, configuring [4-49](#)

message aging [4-12](#)

message counts [4-32](#)

Message Locator

enabling [4-13](#)

phone view [4-27](#)

messages

addressing and sending settings [4-42](#)

addressing settings, changing [4-43](#)

confirming deletions of messages [4-41](#)

forwarded (relay) [4-49](#)

language used to prompt callers [4-11](#)

marking secure by unidentified callers [4-11](#)

notifications for phone and pager [4-61](#)

notifications for SMS-compatible devices [4-64](#)

notifications for SMTP-compatible devices [4-66](#)

playback order for Message Locator [4-13](#)

playback order for new, saved, and deleted messages [4-34](#)

playback speed and volume of messages [4-31](#)

recording length for users [5-12](#)

relay [4-49](#)

specifying maximum recording length for outside callers [4-11](#)

specifying the amount of time to skip back or ahead when rewinding or fast-forwarding [4-39](#)

streamlined addressing [4-45](#)

what unidentified callers can do [4-11](#)

message security [5-20](#)

message waiting indicators (MWIs), overview [4-5](#)

Microsoft Exchange calendars and contacts, accessing [4-80](#)

modifying

class of service [6-2](#)

notification devices [4-61](#)

user accounts (in Connection Administration) [10-4, 14-2](#)

user templates [7-4](#), [8-11](#), [8-13](#), [8-15](#)

MWIs

adding [4-6](#)

deleting [4-7](#)

editing [4-6](#)

N

notifications

about notification devices [4-61](#)

cascading [4-72](#)

chaining [4-73](#)

phone and pager [4-61](#)

SMS-compatible devices [4-64](#)

SMTP-compatible devices [4-66](#)

O

Operator account [1-2](#)

Outlook calendars and contacts, accessing [4-80](#)

outside caller options [4-11](#)

P

passwords or PINs

allowing users to sign in without entering a password or PIN [4-15](#)

changing [4-2](#), [4-3](#), [4-5](#)

securing and changing Cisco PCA password [4-4](#)

settings [4-2](#)

personal call transfer rules

enabling by class of service [5-14](#)

enabling or disabling for users [5-15](#)

modifying options for user [4-10](#)

overview [5-13](#)

web tool overview [5-14](#)

phone menu, summary of settings [4-14](#)

Phone View [4-27](#)

PIN, changing [4-2](#)

private distribution lists

maximum number of lists [5-16](#)

maximum number of members [5-17](#)

overview [4-79](#)

proxy address, created when a user alias is changed [14-1](#)

Q

quotas for mailboxes, customizing for users or templates [4-12](#)

R

relay messages [4-49](#)

restriction tables [5-19](#)

roles

default roles [2-4](#)

overview [2-4](#)

RSS Feeds [5-5](#)

S

secure messaging [5-20](#)

sending messages

broadcast messages [4-42](#)

confirming recipients by name [4-45](#)

message security [5-20](#)

specifying whether messages are sent upon hang-up [4-47](#)

system distribution lists [5-21](#)

sign-in

conversation [4-25](#)

playing message counts [4-25](#)

playing recorded name [4-25](#)

SMTP proxy addresses

configuring for contacts [10-5](#)

configuring for users [4-84](#)

created when a user alias is changed [14-1](#)

Speech to Text [4-74](#)

speech to text [5-23](#)
 SpeechView, enabling for a class of service [5-23](#)
 SpeechView, transcription delivery [4-74](#)
 System Directory Handler [4-52](#)
 system distribution list, specifying whether users can send messages to [5-21](#)

T

Text to Speech, enabling for a user [4-82, 4-83](#)
 time format for message time stamps, changing [4-30](#)
 transcriptions [4-74, 5-23](#)

U

Undeliverable Messages Mailbox account [1-2](#)
 unidentified caller options [4-11](#)
 unified client [5-2](#)
 Unity Connection Messaging System account [1-2](#)
 user access to email in an external message store [4-81, 4-82](#)
 user accounts

- administrator roles [2-4](#)
- creating by importing from Cisco Unified Communications Manager [12-1, 12-2](#)
- creating by importing LDAP data [13-2](#)
- default accounts [1-1](#)
- mailbox stores [2-3](#)
- overview [1-1](#)
- partitions [2-2](#)
- search spaces [2-2](#)

 users

- creating [9-1](#)
- deleting [14-2, 14-3](#)
- finding [3-1](#)

 users without voice mailboxes [1-1](#)
 users with voice mailboxes [1-1](#)
 user templates

- adding [7-2, 8-4](#)
- default templates [7-1](#)

deleting [7-5, 8-12, 8-13, 8-16](#)
 modifying [7-4, 8-11, 8-13, 8-15](#)
 overview [2-1](#)

utilities and tools

Bulk Administration Tool [11-3](#)

V

voice mailboxes

- creating end users [9-1](#)
- deleting end users [14-2](#)

 voice recognition, enabling for a class of service [5-24](#)
 voice to text [4-74, 5-23](#)

