



Cisco Unified Application Environment Hardware Compatibility Matrix, Release 8.5

Table 1 describes hardware compatibility requirements for installing Cisco Unified Application Environment.

Find additional information about Cisco MCS at this URL:

http://cisco.com/en/US/products/hw/voiceapp/ps378/products_data_sheets_list.html

Table 1 *Hardware Compatibility Matrix*

Cisco MCS Server Family	Cisco Unified Communications Manager Appliance ¹	CPU	RAM	Cisco Unified Application Environment Version
7845	MCS-7845-H1	2x Intel Xeon Processor (3.4GHz)	4GB DDR2	2.3, 2.4, 2.5, 8.0,8.5
	MCS-7845-I1			2.4, 2.5, 8.0, 8.5
	MCS-7845-H2	2x Intel Xeon 5140 Processor (Dual core 2.33GHz)		
	MCS-7845-I2			
	MCS-7845-I3	Single Intel 5540 Quad-core 2.53-GHz; last level cache: 8 MB	128 GB (64 GB per processor slot)	



Table 1 *Hardware Compatibility Matrix (continued)*

Cisco MCS Server Family	Cisco Unified Communications Manager Appliance¹	CPU	RAM	Cisco Unified Application Environment Version
7835	MCS-7835-H1	Intel Xeon 3.4GHz	2GB DDR2	2.4, 2.5, 8.0, 8.5
	MCS-7835-I1	Intel Xeon (3.4GHz)		
	MCS-7835-H2	2x Intel Xeon 5140 Processor (Dual core 2.33GHz)		
	MCS-7835-I2	Intel Xeon 5140 Processor (Dual core 2.33GHz)	PC2-5300 667-MHz DDR2 synchronous dynamic RAM (SDRAM) Fully Buffered DIMMs	
	MCS-7835-I3	Single Intel 5504 Quad-core 2.00-GHz; last level cache: 8 MB	128 GB (64 GB per processor slot)	
7825	MCS-7825-H2	Intel 950 (3.4 GHz)		
	MCS-7825-I2	Intel P4 Pentium D Processor (3.4 GHz)		
	MCS-7825-H3	Intel Xeon 3050 (dual-core 2.13GHz)		
	MCS-7825-I3			
	MCS-7825-I4			
	MCS-7825-H4			
7816	MCS 7816-I3	Intel Celeron D 352 (3.2GHz)	8 GB DDR2	
	MCS-7816-H3			
	MCS-7816-I4	Single Intel Dual Core Xeon E8400 3.0-GHz 6M L2	2-GB (two 1-GB) PC2-5300 Error Checking and Correction (ECC) double-data-rate 2 (DDR2)	

1. The MCS servers used for the Cisco Unified Application Environment require the Microsoft Windows 2008 Server operating system.

Cisco Unified Application Environment also runs on the following MCS servers, but they have not been tested. Performance of these servers is expected to be slower.

- MCS 7835-H2
- MCS 7845-H2
- MCS 7835-I2
- MCS 7845-I2

**Note**

The minimum hardware requirement that supports:

- JTAPI for monitoring 10,000 devices:
Cisco Unified Communications Manager: Platform Type 7845 H2
Cisco Unified Application Environment : MCS 7825 I5
- Increased media port density:
Cisco Unified Application Environment: MCS-7845-I3

[Table 2](#) lists the MCS servers for VMware ESXi 4.0 in lab/demo environment.

Table 2 *MCS servers for VMware ESXi 4.0 (in Lab/Demo Environment)*

Cisco MCS Server Family	Cisco Unified Communications Manager Appliance	CPU	RAM	Cisco Unified Application Environment Version
7845	MCS-7845-I3	Single Intel 5540 Quad-core 2.53-GHz; last level cache: 8 MB	128 GB (64 GB per processor slot)	8.5
7835	MCS-7835-I3	Single Intel 5504 Quad-core 2.00-GHz; last level cache: 8 MB	128 GB (64 GB per processor slot)	8.5

**Note**

Cisco Unified Application Environment 8.5 supports virtualization in a lab/demo environment only and not in production.

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Any Internet Protocol (IP) addresses used in this document are not intended to be actual addresses. Any examples, command display output, and figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses in illustrative content is unintentional and coincidental.

© 2010 Cisco Systems, Inc. All rights reserved.

