



## **Field Notice: Cisco Unified Communications Manager Release 11.5(x) does not support some deprecated phone models**

[Deprecated Phone Models for 11.5\(1\)](#) 2

[Field Notice: Cisco Unified Communications Manager Release 11.5\(x\) does not support some deprecated phone models](#) 2

Revised: July 6, 2016,

## Deprecated Phone Models for 11.5(1)

### Field Notice: Cisco Unified Communications Manager Release 11.5(x) does not support some deprecated phone models

#### NOTICE

THIS FIELD NOTICE IS PROVIDED ON AN "AS IS" BASIS AND DOES NOT IMPLY ANY KIND OF GUARANTEE OR WARRANTY, INCLUDING THE WARRANTY OF MERCHANTABILITY. YOUR USE OF THE INFORMATION ON THE FIELD NOTICE OR MATERIALS LINKED FROM THE FIELD NOTICE IS AT YOUR OWN RISK. CISCO RESERVES THE RIGHT TO CHANGE OR UPDATE THIS FIELD NOTICE AT ANY TIME.

#### Products Affected

Products Affected	Version
Cisco Unified Communications Manager	11.5(x)
Cisco Business Edition 6000	11.5(x)
Cisco Business Edition 7000	11.5(x)

#### Problem Description

The following phone models are deprecated and are not supported by Cisco Unified Communications Manager Release 11.5(x). If you are using any of these phone models and you upgrade to release 11.5(x), you will be unable to use the phone after the upgrade. After you switch over to the new release, registration on the phone will be blocked.

- Cisco IP Phone 12 S
- Cisco IP Phone 12 SP
- Cisco IP Phone 12 SP+
- Cisco IP Phone 30 SP+
- Cisco IP Phone 30 VIP
- Cisco Unified IP Phone 7902G
- Cisco Unified IP Phone 7905G
- Cisco Unified IP Phone 7910
- Cisco Unified IP Phone 7910G
- Cisco Unified IP Phone 7910+SW
- Cisco Unified IP Phone 7910G+SW

- Cisco Unified IP Phone 7912G
- Cisco Unified Wireless IP Phone 7920
- Cisco Unified IP Conference Station 7935

## Background

The legacy phone models are deprecated for the following reasons:

- Security—since legacy phone models are not updated with critical software fixes, we have limited ability to protect customers when security issues arise.
- New feature implementation—legacy phone usage slows down implementation of newer features.
- Sustaining—no development support or regression testing is currently being done for these older phones.

## Problem / Symptom

If you are running any of these phone models, after you upgrade and switch over to the new release, registration will be blocked on the phone. If the phone remains powered on, the phone will make repeated registration attempts, which will create unnecessary network traffic as well as a load on the Cisco CallManager service.

## Upgrades that Involve Deprecated Phones

To guarantee that you have full support, before you upgrade, do the following:

- 1 Confirm whether the phones in your network will be supported in Release 11.5(1).
- 2 Identify any non-supported phones.
- 3 For any non-supported phones, power down the phone and disconnect the phone from the network.
- 4 Provision a supported phone for the phone user. You can use the Migration FX tool to migrate from older model to newer model phones. For details, go to: [http://refreshcollab.cisco.com/webportal/46/CUCM%20Readiness%20Assessment#endpoint\\_refresh\\_tool](http://refreshcollab.cisco.com/webportal/46/CUCM%20Readiness%20Assessment#endpoint_refresh_tool).
- 5 Once all the phones in your network are supported by Release 11.5(1), upgrade your system.



---

**Note** Deprecated phones can also be removed after the upgrade. When the administrator logs in to Cisco Unified Communications Manager after completing the upgrade, the system displays a warning message notifying the administrator of the deprecated phones.

---

## Licensing

You do not need to purchase a new device license to replace a deprecated phone with a supported phone. The device license becomes available for a new phone when you either remove the deprecated phone from the system, or when you switch to the new Cisco Unified Communications Manager version, and the deprecated phone fails to register.

## For More Information

If you require further assistance, or if you have any further questions regarding this field notice, please contact the Cisco Systems [Technical Assistance Center \(TAC\)](#) by one of the following methods:

- [Open a service request on cisco.com](#)
- [By email](#)
- [By Telephone](#)

### **Receive Email Notification for New Field Notices**

[Cisco Notification Service](#)—Set up a profile to receive email updates about reliability, safety, network security, and end-of-sale issues for the Cisco products you specify.





**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA 95134-1706  
USA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV  
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).