



Sample Configuration Profiles

XML Open Format Sample

```
<?xml version="1.0" encoding="UTF-8"?>
<device xsi:type="axl:XIPPhone" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">

  <flat-profile>

    <!-- System Configuration -->

    <Restricted_Access_Domains ua="na"/>
    <Enable_Web_Server ua="na">Yes</Enable_Web_Server>
    <Web_Server_Port ua="na">80</Web_Server_Port>
    <Enable_Web_Admin_Access ua="na">Yes</Enable_Web_Admin_Access>
    <Admin_Password ua="na"/>
    <User_Password ua="rw"/>
    <Phone-UI-user-mode ua="na">No</Phone-UI-user-mode>

    <!-- Internet Connection Type -->

    <Connection_Type ua="rw">DHCP</Connection_Type>

    <!-- Static IP Settings -->

    <Static_IP ua="rw"/>
    <NetMask ua="rw"/>
    <Gateway ua="rw"/>

    <!-- Optional Network Configuration -->

    <HostName ua="rw"/>
    <Domain ua="rw"/>
    <Primary_DNS ua="rw"/>
    <Secondary_DNS ua="rw"/>
    <Syslog_Server ua="na"/>
    <Debug_Level ua="na"/>0</Debug_Level>
    <Layer_2_Logging ua="na">No</Layer_2_Logging>
    <Primary_NTP_Server ua="na">us.pool.ntp.org</Primary_NTP_Server>
    <Secondary_NTP_Server ua="na"/>
    <SSH_Access ua="na">No</SSH_Access>
    <DNS_Cache_TTL_Ignore ua="na">Yes</DNS_Cache_TTL_Ignore>
    <SSH_User_ID ua="na"/>
```

```

<SSH_Password ua="na"/>

<!-- VLAN Settings -->

<Enable_CDP ua="na">Yes</Enable_CDP>
<Enable_LLDP-MED ua="na">Yes</Enable_LLDP-MED>
<Network_Startup_Delay ua="na">3</Network_Startup_Delay>
<VLAN_ID ua="rw">4095</VLAN_ID>

<!-- Inventory Settings -->

<Asset_ID ua="na"/>

<!-- SIP Parameters -->

<Max_Forward ua="na">70</Max_Forward>
<Max_Redirection ua="na">5</Max_Redirection>
<SIP_User_Agent_Name ua="na">$VERSION</SIP_User_Agent_Name>
<SIP_Server_Name ua="na">$VERSION</SIP_Server_Name>
<SIP_Reg_User_Agent_Name ua="na" />
<SIP_Accept_Language ua="na" />
<RFC_2543_Call_Hold ua="na">No</RFC_2543_Call_Hold>
<SIP_TCP_Port_Min ua="na">5060</SIP_TCP_Port_Min>
<SIP_TCP_Port_Max ua="na">5080</SIP_TCP_Port_Max>
<Caller_ID_Header ua="na">PAID-RPID-FROM</Caller_ID_Header>
<Max_INVITE_Retry_Attempts ua="na">3</Max_INVITE_Retry_Attempts>
<Max_NON-INVITE_Retry_Attempts ua="na">3</Max_NON-INVITE_Retry_Attempts>

<!-- SIP Timer Values -->

<SIP_T1 ua="na">0.5</SIP_T1>
<SIP_T2 ua="na">4</SIP_T2>
<INVITE_Expires ua="na">240</INVITE_Expires>
<ReINVITE_Expires ua="na">30</ReINVITE_Expires>
<Reg_Retry_Intvl ua="na">30</Reg_Retry_Intvl>
<Reg_Retry_Long_Intvl ua="na">1200</Reg_Retry_Long_Intvl>
<Reg_Retry_Random_Delay ua="na">0</Reg_Retry_Random_Delay>
<Reg_Retry_Long_Random_Delay ua="na">0</Reg_Retry_Long_Random_Delay>
<Reg_Retry_Intvl_Cap ua="na">0</Reg_Retry_Intvl_Cap>

<!-- Response Status Code Handling -->

<Try_Backup_RSC ua="na">5??, 6??</Try_Backup_RSC>
<Retry_Reg_RSC ua="na">5??, 6??</Retry_Reg_RSC>

<!-- RTP Parameters -->

<RTP_Port_Min ua="na">16384</RTP_Port_Min>
<RTP_Port_Max ua="na">16538</RTP_Port_Max>
<RTP_Packet_Size ua="na">0.02</RTP_Packet_Size>
<RTCP_Tx_Enable ua="na">No</RTCP_Tx_Enable>

<!-- SDP Payload Types -->

<AVT_Dynamic_Payload ua="na">101</AVT_Dynamic_Payload>

<!-- NAT Support Parameters -->

```

```

<NAT_Keep_Alive_Intvl ua="na">15</NAT_Keep_Alive_Intvl>

<!-- Configuration Profile -->

<Provision_Enable ua="na">Yes</Provision_Enable>
<Resync_On_Reset ua="na">Yes</Resync_On_Reset>
<Resync_Random_Delay ua="na">2</Resync_Random_Delay>
<Resync_At__HHmm_ ua="na">0100</Resync_At__HHmm_>
<Resync_At_Random_Delay ua="na">600</Resync_At_Random_Delay>
<Resync_Periodic ua="na">3600</Resync_Periodic>
<Resync_Error_Retry_Delay ua="na">3600</Resync_Error_Retry_Delay>
<Forced_Resync_Delay ua="na">14400</Forced_Resync_Delay>
<Resync_Fails_On_FNF ua="na">Yes</Resync_Fails_On_FNF>
<Profile_Rule ua="na">http://10.74.10.225/yxue2/ut/8831System_wSBC.xml</Profile_Rule>
<Profile_Rule_B ua="na" />
<Profile_Rule_C ua="na">/ut/Register2.xml</Profile_Rule_C>
<Profile_Rule_D ua="na" />
<Resync_DHCP_Option_To_Use ua="na">160,159,66,150</Resync_DHCP_Option_To_Use>
<Log_Request_Msg ua="na">$PN $MAC -- Requesting %s
$SCHEME://$SERVIP:$PORT$PATH</Log_Request_Msg>
<Log_Success_Msg ua="na">$PN $MAC -- Successful %s $SCHEME://$SERVIP:$PORT$PATH --
$ERR</Log_Success_Msg>
<Log_Failure_Msg ua="na">$PN $MAC -- %s failed: $ERR</Log_Failure_Msg>
<User_Configurable_Resync ua="na">Yes</User_Configurable_Resync>
<!-- Firmware Upgrade -->

<Upgrade_Enable ua="na">Yes</Upgrade_Enable>
<Upgrade_Error_Retry_Delay ua="na">3600</Upgrade_Error_Retry_Delay>
<Upgrade_Rule ua="na" />
<Enable_Enterprise_Image_Upgrade ua="na">No</Enable_Enterprise_Image_Upgrade>

<!-- CA Settings -->

<Custom_CA_Rule ua="na" />

<!-- General Purpose Parameters -->
<GPP_A ua="na" />
<GPP_B ua="na" />
<GPP_C ua="na" />
<GPP_D ua="na" />
<GPP_E ua="na" />
<GPP_F ua="na" />
<GPP_G ua="na" />
<GPP_H ua="na" />
<GPP_I ua="na" />
<GPP_J ua="na" />
<GPP_K ua="na" />
<GPP_L ua="na" />
<GPP_M ua="na" />
<GPP_N ua="na" />
<GPP_O ua="na" />
<GPP_P ua="na" />

<!-- Control Timer Values (sec) -->

<Interdigit_Long_Timer ua="na">10</Interdigit_Long_Timer>
<Interdigit_Short_Timer ua="na">3</Interdigit_Short_Timer>

```

```

<!-- Time -->

<Time_Zone ua="na">GMT-8:00</Time_Zone>
<Time_Offset__HH_mm_ ua="na">00/00</Time_Offset__HH_mm_>
<Ignore_DHCP_Time_Offset ua="na">No</Ignore_DHCP_Time_Offset>
<Daylight_Saving_Time_Rule
ua="na">start=3/-1/7/2;end=10/-1/7/2;save=1</Daylight_Saving_Time_Rule>
<Daylight_Saving_Time_Enable ua="na">Yes</Daylight_Saving_Time_Enable>

<!-- Localization -->

<Dictionary_Server_Script ua="na" />
<Language_Selection ua="na" />
<Locale ua="na">en-US</Locale>

- <!-- QoS Settings -->

<SIP_TOS_Value ua="na">0x60</SIP_TOS_Value>
<RTP_TOS_Value ua="na">0xb8</RTP_TOS_Value>

<!-- General -->

<Station_Display_Name ua="na" />
<Text_Logo ua="na" />
<PNG_Picture_Download_URL ua="na" />
<Select_Logo ua="na">Default</Select_Logo>
<Select_Background_Picture ua="na">None</Select_Background_Picture>
<Screen_Saver_Enable ua="rw">No</Screen_Saver_Enable>
<Screen_Saver_Wait ua="rw">300</Screen_Saver_Wait>
<Screen_Saver_Icon ua="rw">Background Picture</Screen_Saver_Icon>
<Co-branding_Banner_Picture_Download_URL ua="na" />

<!-- Miscellaneous Line Key Settings -->

<Call_Appearances_Per_Line ua="na">2</Call_Appearances_Per_Line>

<!-- Supplementary Services -->

<Conference_Serv ua="na">Yes</Conference_Serv>
<Attn_Transfer_Serv ua="na">Yes</Attn_Transfer_Serv>
<Blind_Transfer_Serv ua="na">Yes</Blind_Transfer_Serv>
<Cfwd_All_Serv ua="na">Yes</Cfwd_All_Serv>
<Cfwd_Busy_Serv ua="na">Yes</Cfwd_Busy_Serv>
<Cfwd_No_Ans_Serv ua="na">Yes</Cfwd_No_Ans_Serv>

<!-- Broadsoft Settings -->

<Directory_Enable ua="na">Yes</Directory_Enable>
<XSI_Host_Server ua="na">xsi.iopl.broadworks.net</XSI_Host_Server>
<Directory_Name ua="na">IOP1</Directory_Name>
<Directory_Type ua="na">Enterprise</Directory_Type>
<Directory_User_ID ua="na">broadsoft_user</Directory_User_ID>
<Directory_Password ua="na" />

<!-- LDAP Corporate Directory Search -->

<LDAP_Dir_Enable ua="na">No</LDAP_Dir_Enable>
<LDAP_Corp_Dir_Name ua="na" />

```

```
<LDAP_Server ua="na" />
<LDAP_Auth_Method ua="na">None</LDAP_Auth_Method>
<LDAP_Client_DN ua="na" />
<LDAP_Username ua="na" />
<LDAP_Password ua="na" />
<LDAP_Search_Base ua="na" />
<LDAP_Last_Name_Filter ua="na" />
<LDAP_First_Name_Filter ua="na" />
<LDAP_Search_Item_3 ua="na" />
<LDAP_Item_3_Filter ua="na" />
<LDAP_Search_Item_4 ua="na" />
<LDAP_Item_4_Filter ua="na" />
<LDAP_Display_Attrs ua="na" />
<LDAP_Number_Mapping ua="na" />

<!-- XML Service -->

<XML_Directory_Service_Name ua="na" />
<XML_Directory_Service_URL ua="na" />
<XML_Application_Service_Name ua="na" />
<XML_Application_Service_URL ua="na" />
<XML_User_Name ua="na" />
<XML_Password ua="na" />

<!-- Call Forward -->

<Cfwd_All_Dest ua="rw" />
<Cfwd_Busy_Dest ua="rw" />
<Cfwd_No_Ans_Dest ua="rw" />
<Cfwd_No_Ans_Delay ua="rw">20</Cfwd_No_Ans_Delay>

<!-- Speed Dial -->

<Speed_Dial_2 ua="na" />
<Speed_Dial_3 ua="na" />
<Speed_Dial_4 ua="na" />
<Speed_Dial_5 ua="na" />
<Speed_Dial_6 ua="na" />
<Speed_Dial_7 ua="na" />
<Speed_Dial_8 ua="na" />
<Speed_Dial_9 ua="na" />

<!-- Supplementary Services -->

<Time_Format ua="rw">12hr</Time_Format>
<Date_Format ua="rw">month/day</Date_Format>

<!-- Audio -->

<Ringer_Volume ua="rw">8</Ringer_Volume>
<Speaker_Volume ua="rw">8</Speaker_Volume>

<!-- LCD -->

<LCD_Contrast ua="rw">16</LCD_Contrast>
<Back_Light_Timer ua="na">10s</Back_Light_Timer>
<!-- General -->
```

```

<Line_Enable_1_ ua="na">Yes</Line_Enable_1_>

<!-- NAT Settings -->

<NAT_Keep_Alive_Enable_1_ ua="na">No</NAT_Keep_Alive_Enable_1_>
<NAT_Keep_Alive_Msg_1_ ua="na">$NOTIFY</NAT_Keep_Alive_Msg_1_>

<!-- SIP Settings -->

<SIP_Transport_1_ ua="na">UDP</SIP_Transport_1_>
<SIP_Port_1_ ua="na">5060</SIP_Port_1_>
<SIP_100REL_Enable_1_ ua="na">Yes</SIP_100REL_Enable_1_>
<Auth_Resync-Reboot_1_ ua="na">Yes</Auth_Resync-Reboot_1_>
<SIP_Remote-Party-ID_1_ ua="na">Yes</SIP_Remote-Party-ID_1_>
<Refer-To_Target_Contact_1_ ua="na">No</Refer-To_Target_Contact_1_>
<SIP_Debug_Option_1_ ua="na">None</SIP_Debug_Option_1_>
<Sticky_183_1_ ua="na">No</Sticky_183_1_>
<Auth_INVITE_1_ ua="na">No</Auth_INVITE_1_>
<User_Equal_Phone_1_ ua="na">No</User_Equal_Phone_1_>

<!-- Call Feature Settings -->

<Default_Ring_1_ ua="rw">1</Default_Ring_1_>
<Conference_Bridge_URL_1_ ua="na" />

<!-- Proxy and Registration -->
<Proxy_1_ ua="na" />
<Outbound_Proxy_1_ ua="na">199.19.193.9</Outbound_Proxy_1_>
<Alternate_Proxy_1_ ua="na" />
<Alternate_Outbound_Proxy_1_ ua="na" />
<Register_1_ ua="na">Yes</Register_1_>
<Make_Call_Without_Reg_1_ ua="na">No</Make_Call_Without_Reg_1_>
<Register_Expires_1_ ua="na">3600</Register_Expires_1_>
<Use_DNS_SRV_1_ ua="na">Yes</Use_DNS_SRV_1_>
<Proxy_Fallback_Intvl_1_ ua="na">3600</Proxy_Fallback_Intvl_1_>
<Dual_Registration_1_ ua="na">No</Dual_Registration_1_>

<!-- Subscriber Information -->

<Display_Name_1_ ua="na" />
<User_ID_1_ ua="na" />
<Password_1_ ua="na" />
<Auth_ID_1_ ua="na" />
<Reversed_Auth_Realm_1_ ua="na" />

<!-- Audio Configuration -->

<Preferred_Codec_1_ ua="na">G722</Preferred_Codec_1_>
<Use_Pref_Codec_Only_1_ ua="na">No</Use_Pref_Codec_Only_1_>
<Second_Preferred_Codec_1_ ua="na">Unspecified</Second_Preferred_Codec_1_>
<Third_Preferred_Codec_1_ ua="na">Unspecified</Third_Preferred_Codec_1_>
<G711u_Enable_1_ ua="na">Yes</G711u_Enable_1_>
<G711a_Enable_1_ ua="na">Yes</G711a_Enable_1_>
<G729a_Enable_1_ ua="na">Yes</G729a_Enable_1_>
<G729ab_Enable_1_ ua="na">Yes</G729ab_Enable_1_>
<G722_Enable_1_ ua="na">Yes</G722_Enable_1_>
<iLBC_Enable_1_ ua="na">Yes</iLBC_Enable_1_>
<Silence_Supp_Enable_1_ ua="na">No</Silence_Supp_Enable_1_>

```

```
<DTMF_Tx_Method_1_ ua="na">Auto</DTMF_Tx_Method_1_>

<!-- Dial Plan -->
<Dial_Plan_1_ ua="na">( <8:>x. | [*#]xx[*x] | [*#]xx. | [2-9]11S0 | 00 | 011x. |
[0-1][2-9]xxxxxxxx | 0 | [2-9]xxxxxxxx | xxxx )</Dial_Plan_1_>

</flat-profile>
</device>
```

