



Cisco IP Phone 7800 Series Multiplatform Phones Release Notes for Firmware Release 11.3(1)SR3

First Published: 2020-08-20

Introduction

Use these release notes with the Cisco IP Phone 7800 Series Multiplatform Phones running SIP Firmware Release 11.3(1)SR3.

Phone	Support Requirements
Cisco IP Phone 7800 Series Multiplatform Phones	BroadSoft BroadWorks 22.0 MetaSphere CFS version 9.5 Asterisk 11.0

New and Changed Features

This release is a maintenance release and doesn't contain any new or enhanced features.

To view the resolved and open caveats for this release, see [View Caveats, on page 3](#).

Cisco IP Phone 7800 Series Documentation

See the publications that are specific to your language, phone model, and multiplatform firmware release. Navigate from the following Uniform Resource Locator (URL):

<https://www.cisco.com/c/en/us/products/collaboration-endpoints/ip-phone-7800-series-multiplatform-firmware/index.html>

Upgrade the Firmware

You can upgrade the phone firmware with TFTP, HTTP, or HTTPS. After the upgrade completes, the phone reboots automatically.

Procedure

Step 1

Click this link:

<https://software.cisco.com/download/home/286311381>

On the **Software Download** web page that is displayed, ensure that **IP Phone 7800 Series with Multiplatform Firmware** is selected in the middle pane.

- Step 2** Select your phone model in the right pane.
- Step 3** On the next page that is displayed, select **Multiplatform Firmware**.
- Step 4** Under **Latest Release**, select **11.3.1 MSR3-3**.
- Step 5** (Optional) Place your mouse pointer on the file name to see the file details and checksum values.
- Step 6** Download the corresponding file.
`cmterm-78xx.11-3-1MSR3-3_REL.zip`
- Step 7** Click **Accept License Agreement**.
- Step 8** Unzip the file and place the files in the appropriate location on your upgrade server.
 The appropriate location is the TFTP, HTTP, or HTTPS download folder, depending on the protocol that you want to use for the upgrade.
- Step 9** Upgrade the phone firmware with one of these methods.
- Upgrade the phone firmware from the phone administration web page:
 - a. On the phone administration web page, go to **Admin Login > Advanced, Voice > Provisioning > Firmware Upgrade**.
 - b. In the **Upgrade Rule** field, enter the load file URL as described below.
 Load file URL format:

```
<upgrade protocol>://<upgrade server ip address>[:<port>]/<path>/<file name>.loads
```

 Examples:

```
http://10.73.10.223/firmware/sip78xx.11-3-1MSR3-3.loads
```

```
https://server.domain.com/firmware/sip78xx.11-3-1MSR3-3.loads
```
 - c. Click **Submit All Changes**.
 - Upgrade the phone firmware directly from your web browser:
 In the address bar of your web browser, enter the phone upgrade URL as described below.
 Phone upgrade URL format:

```
<phone protocol>://<phone ip address>[:port]/admin/upgrade?<load file URL>
```

 Load file URL format:

```
<upgrade protocol>://<upgrade server ip address>[:<port>]/<path>/<file name>.loads
```

 Examples:

```
https://10.74.10.225/admin/upgrade?http://10.73.10.223/firmware/sip78xx.11-3-1MSR3-3.loads
```

```
https://10.74.10.225/admin/upgrade?https://server.domain.com/firmware/sip78xx.11-3-1MSR3-3.loads
```

Note Specify the <file name>.loads file in the URL. The <file name>.zip file contains other files.

Limitations and Restrictions

Phone Behavior During Times of Network Congestion

- Administrative tasks, such as an internal port scan or security scan
- Attacks that occur on your network, such as a Denial of Service attack

View Caveats

You can search for caveats (bugs) with the Cisco Bug Search tool.

Known caveats are graded according to severity level, and are either open or resolved.

Before you begin

You have your Cisco.com user ID and password.

Procedure

-
- | | |
|---------------|---|
| Step 1 | <ul style="list-style-type: none"> • To view all caveats that affect this release:
 https://bst.cloudapps.cisco.com/bugsearch/search?kw=*&pf=prdNm&pfVal=286311381&rls=11.3(1)&sb=anfr&bt=custV • To view open caveats that affect this release:
 https://bst.cloudapps.cisco.com/bugsearch/search?kw=*&pf=prdNm&pfVal=286311381&rls=11.3(1)&sb=af&bt=custV • To view resolved caveats that affect this release:
 https://bst.cloudapps.cisco.com/bugsearch/search?kw=*&pf=prdNm&pfVal=286311381&rls=11.3(1)&sb=fr&bt=custV |
| Step 2 | When prompted, log in with your Cisco.com user ID and password. |
| Step 3 | (Optional) For information about a specific caveat, enter the bug ID number (<i>CSCxxxxnnnn</i>) in the Search for field, and press Enter . |
-

Open Caveats

There are no open caveats in this release.

Resolved Caveats

The following list contains the severity 1, 2, and 3 defects that are resolved for the Cisco IP Phone 7800 Series Multiplatform Phones that use Firmware Release 11.3(1)SR3.

For more information about an individual defect, you can access the online history for the defect by accessing the Bug Search tool and entering the Identifier (*CSCxxxxxxx*). You must be a registered `cisco.com` user to access this defect information.

Because the defect status continually changes, the list reflects a snapshot of the defects that were resolved at the time this report was compiled. For an updated view of the resolved defects or to view specific bugs, access the Bug Search Toolkit as described in [View Caveats, on page 3](#).

- CSCvs56201 GDS screen may not come out after factory reset
- CSCvv04154 3PCC-ML: GDS operation failed
- CSCvu68891 Parser error when tag on header in INVITE contains more than 79 characters

Cisco IP Phone Firmware Support Policy

For information on the support policy for phones, see <https://cisco.com/go/phonefirmwaresupport>.

