



Unified Personal Communicator Settings

Use Unified Personal Communicator settings to configure the settings that apply to all Cisco Unified Personal Communicator users.

Configuring Cisco Unified Personal Communicator Settings

Follow this procedure to configure the Unified Personal Communicator settings.

Procedure

- Step 1** Choose **Application > Unified Personal Communicator > Settings**.
The Unified Personal Communicator Settings window displays.
- Step 2** Enter the appropriate configuration settings as described in [Table 23-1](#).
- Step 3** Enter the appropriate LDAP attribute name for your environment that maps to the given Cisco Unified Personal Communicator attribute name. For a list of Cisco Unified Personal Communicator attribute names and the corresponding default LDAP name, see [Table 23-2](#).
- Step 4** To save the data, click the **Save** icon that displays in the tool bar in the upper, left corner of the window (or click the **Save** button that displays at the bottom of the window).

Table 23-1 Cisco Unified Personal Communicator Configuration Settings

Field	Description
Primary TFTP Server	This parameter specifies the primary TFTP server address, either as a fully qualified domain name or as an IP address. Maximum characters: 128
Backup TFTP Server	This parameter specifies the backup TFTP server address, either as a fully qualified domain name or as an IP address. Maximum characters: 128

Table 23-2 LDAP Attribute Mapping

Unified Personal Communicator Attribute Name	Default LDAP Attribute Name
UID	employeenumber
LastName	sn
Nickname	nickname
Photo	jpegPhoto
DisplayName	displayName
NameSuffix	
BusinessEMail	mail
BusinessPhoneNumber	telephoneNumber
BusinessMobilePhone	mobile
BusinessFax	facsimileTelephoneNumber
HomeEMail	
HomeFax	
FirstName	givenName
MiddleName	initials
UserID	uid
Title	title
NamePrefix	
Gender	
IM	uid
BusinessVoiceMail	voicemail
BusinessPager	pager
BusinessOtherPhone	
HomeMobilePhone	
URL	labeledURL