



Cisco VVB Introduction

Cisco Virtualized Voice Browser (VVB) is designed to facilitate concurrent multimedia communication processing.

Cisco VVB has the following features:

- Facilitates self-service options such as access to check account information or user-directed call routing by processing user commands through touchtone input or speech-recognition technologies.
- Allows customers to retrieve the required information through voice commands without interacting with an agent, to navigate to the correct department, or to get help from an agent.
- Provides multilingual support for Cisco VVB server prompts for automated speech recognition (ASR) and text-to-speech (TTS) capabilities.
- Provides more comprehensive and effective customer service by efficiently handling call traffic with self-service or fast transfer to the correct agent the first time.
- [Cisco VVB Web Interfaces, on page 1](#)
- [Configure System Parameters, on page 2](#)
- [Pre-configured Cisco VVB Applications, on page 2](#)

Cisco VVB Web Interfaces

You can use a web browser to administer Cisco VVB. Cisco VVB provides the following two web interfaces:

- **Cisco VVB Administration**—Use this web interface to configure system parameters, configure subsystems, view real-time reports that include total system activity and application statistics, and so on.
- **Cisco VVB Serviceability**—Use this web interface to view alarm and trace definitions for Cisco VVB services, start and stop engine, monitor engine activity, and so on.



Note

- If you are using Microsoft Internet Explorer or Mozilla Firefox, ensure that the popup blocker is disabled.
 - Multiple Web sessions for same user are not supported.
-

Configure System Parameters

The initial system parameter configuration is part of the Setup Wizard procedure (during installation).

The following audio codecs are supported:

- G711A for A-law
- G711U for u-law
- G729



Note

- You can change the codec anytime after installation by navigating to **System > System Parameters**.
- Only one codec can be configured.
- G711 and G729 audio codecs with a sampling rate of 8K are supported.
- G729 is not supported for ASR and TTS integrations.

Pre-configured Cisco VVB Applications

The following applications are pre-configured on the Cisco VVB:

Script	Description	Pre-configured Dial Number
<i>CVPComprehensive</i>	Used for comprehensive calls.	7777777777*
<i>Ringtone</i>	Used for playing ringtone and whisper.	919191*
<i>Error</i>	Used for playing error tone.	929292*
<i>VRUComprehensive</i>	Used for VRU-only calls	Customer can configure the dial number.