Say It Smart Specifications for Cisco Unified Customer Voice Portal, Release 12.0(1)

First Published: 2019-01-11

Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
http://www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED “AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com go trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2015–2019 Cisco Systems, Inc. All rights reserved.

Preface

- Change History, on page iii
- About this Guide, on page iii
- Audience, on page iii
- Related Documents, on page iv
- Communications, Services, and Additional Information, on page iv
- Documentation Feedback, on page v

Change History

This table lists changes made to this guide. Most recent changes appear at the top.

Change	See	Date
Initial Release of Document for Release 12.0(1)		January 2019

About this Guide

This document provides specifications for the Say It Smart plug-ins included with Cisco Unified CVP VoiceXML Server.

Audience

This document is intended for voice application developers using Cisco Unified CVP VXML Server and Cisco Unified Call Studio.

Note The grammer logic supplied with the out-of-the-box plug-in follows English grammer logic only. To achieve logic for other languages, you must develop your own plug-in.

Related Documents

Note Planning your Unified CVP solution is an important part of the process in setting up Unified CVP. Read the*Cisco Unified Customer Voice Portal Release Design Guide* before configuring your Unified CVP solution.

Unified CVP provides the following documentation:

- *Design Guide for Cisco Unified Customer Voice Portal*
- *Configuration Guide for Cisco Unified Customer Voice Portal*
- *Element Specifications for Cisco Unified CVP VXML Server and Cisco Unified Call Studio*
- *Installation and Upgrade Guide for Cisco Unified Customer Voice Portal*
- *Administration Guide for Cisco Unified Customer Voice Portal*
- *Port Utilization Guide for Cisco Unified Customer Voice Portal*
- *User Guide for Cisco Unified CVP VXML Server and Cisco Unified Call Studio*
- *Reporting Guide for Cisco Unified Customer Voice Portal*
- *Say It Smart Specifications for Cisco Unified CVP VXML Server and Cisco Unified Call Studio*
- *Troubleshooting Wiki for Cisco Unified Customer Voice Portal*

For additional information about Unified ICME, see the Cisco web site listing Unified ICME documentation.

Communications, Services, and Additional Information

- To receive timely, relevant information from Cisco, sign up at Cisco Profile Manager.
- To get the business impact you're looking for with the technologies that matter, visit Cisco Services.
- To submit a service request, visit Cisco Support.
- To discover and browse secure, validated enterprise-class apps, products, solutions and services, visit Cisco Marketplace.
- To obtain general networking, training, and certification titles, visit Cisco Press.
- To find warranty information for a specific product or product family, access Cisco Warranty Finder.

Cisco Bug Search Tool

Cisco Bug Search Tool (BST) is a web-based tool that acts as a gateway to the Cisco bug tracking system that maintains a comprehensive list of defects and vulnerabilities in Cisco products and software. BST provides you with detailed defect information about your products and software.

Documentation Feedback

Provide your comments about this document to: mailto:contactcenterproducts_docfeedback@cisco.com

CONTENTS

PREFACE

Preface iii

Change History iii

About this Guide iii

Audience iii

Related Documents iv

Communications, Services, and Additional Information iv

Documentation Feedback v

CHAPTER 1

Introduction 1

Say It Smart 1

CHAPTER 2

Credit Card 5

Description 5

Input Formats 5

Output Formats 6

Filesets 6

Audio Files 6

Examples 7

CHAPTER 3

Currency 9

Description 9

Input Formats 9

Output Formats 10

Filesets 10

Audio Files 10

Currency Examples 11

CHAPTER 4 Custom Content 13
Description 13
Input Formats 13
Output Formats 14
Filesets 16
Audio Files 16
Examples 16

CHAPTER 5 Date 19
Description 19
Input Formats 19
Output Formats 22
Filesets 23
Audio Files 24
Examples 27

CHAPTER 6 Digits 29
Description 29
Input Formats 29
Output Formats 29
Filesets 30
Audio Files 30
Examples 30

CHAPTER 7 Filename 33
Description 33
Input Formats 34
Output Formats 34
Filesets 34
Audio Files 34
Examples 34

CHAPTER 8 Number 37

Description 37
Input Formats 37
Output Formats 38
Filesets 38
Audio Files 38
Examples 39

CHAPTER 9 Phone 41
Description 41
Input Formats 41
Output Formats 42
Filesets 42
Audio Files 42
Examples 43

CHAPTER 10 Social Security 45
Description 45
Input Formats 45
Output Formats 46
Filesets 46
Audio Files 46
Examples 46

CHAPTER 11 String 49
Description 49
Input Formats 49
Output Formats 50
Filesets 50
Audio Files 50
Examples 50

CHAPTER 12 State 53
Description 53

Input Formats 53
Output Formats 54
Filesets 54
Audio Files 54
Examples 55

CHAPTER 13 Time 57
Description 57
Input Formats 57
Output Formats 58
Filesets 59
Audio Files 60
Examples 61



CHAPTER 1

Introduction

- Say It Smart, on page 1

Say It Smart

Say It Smart is a Unified CVP technology that handles the breakdown of formatted data into an array of audio files played one after the other to render the data in a manner understandable by a caller. While many Text To Speech (TTS) engines can perform a similar function, the power of Say It Smart is that it can handle the playback using pre-recorded audio. Each Say It Smart type lists the audio files required to fully render all the formatted data it can handle. The user need only record these files according to the guidelines specified below and Say It Smart does the rest.

Each Say It Smart type is handled by a separate plug-in deployed on Cisco Unified Call Studio (Call Studio) and Cisco Unified CVP VXML Server (VXML Server). Unified CVP includes many common types such as dates and times. Developers can produce their own plug-ins to either extend Unified CVP Say it Smart plug-in functionality, or introduce new types.

Note The grammer logic supplied with the out-of-the-box plug-in follows English grammer logic only. To achieve logic for other languages, you must develop your own plug-in.

The following defines the characteristics a Say It Smart plug-in requires:

- **Type** – A Say It Smart plug-in is associated with a single type that defines on a high level what kind of data can be handled by the plug-in. Numbers, dates, or currency values are examples of types.
- **Input Format** – A Say It Smart plug-in can have from one to many input formats that define how the data appears when it is sent to the plug-in. These formats may reflect different ways that type can be represented. For example, a date may appear in MMDDYYYY format or YYYYMMDD.
- **Output Format** – A Say It Smart plug-in can have from one to many output formats that define how to express the data passed to the plug-in. Output formats are dependent on input formats, once an input format is changed, the output formats available also change. Output formats can encapsulate differences in expression, such as reading back a value with pauses. They can also reflect language differences or even preferences in how to tailor the output. For example, a time may have an output format that reads 12:00 as *noon* or another that reads back the time in Spanish.

- **Fileset** – A Say It Smart plug-in can have from one to many filesets that list all the audio files required to render a particular output format. Filesets are dependent on output format, once an output format changes, the filesets available also change. Different filesets represent different combinations of files that will render the same data in the specified output format. The most common use of filesets is to use different groups of files to render the data so it sounds better by using more files, or using fewer files but with a more robotic sound. Another use for filesets would be to provide a different gender or playback speed. For example, a fileset may be introduced that reads back a number slowly for those applications where the audience requires it.
- **Audio Files** – Say It Smart plug-ins return a list of audio files needed to render the data in the manner specified by the above criteria. The application designer is required to record all the audio files specified by the fileset(s) they intend on using, name the audio files appropriately, and place them in a centrally servable location. Some criteria on audio files are:
  - All audio files must be given names listed in the specification (with the appropriate audio type extension). All Unified CVP Say It Smart plug-ins use filenames in lowercase and are named such that they can exist on any computing platform without naming issues (the names do not include spaces or unusual punctuation). Any naming inconsistencies will cause Unified CVP Say It Smart plug-ins to use TTS for those files.
  - All audio files for a Say It Smart format must be of a single audio type. Mixing WAV and VOX files, for example, is not possible.
  - Not all files listed need to be recorded. If the user is fairly sure some files will never be encountered, they can be left off. Unified CVP Say It Smart plug-ins use TTS as a backup so if a missing audio file is requested, it will be read as TTS. This may be a bit disconcerting to the caller but does not cause any issues for the application. For example, the Unified CVP Number Say It Smart plug-in can handle numbers up to 999 trillion and the user may know that their application will not handle numbers larger than ten thousand so may choose not to record *million*, *billion*, or *trillion*.
  - Many of the Unified CVP Say It Smart plug-ins use filesets whose contents include audio files specified by the Unified CVP Number Say It Smart plug-in. Recording the audio files to support Number will greatly reduce the number of files needed for other types.
  - All audio files for a particular plug-in must be stored within the same directory. Unified CVP Say It Smart plug-ins require the audio files used by the plug-in to reside in a single directory, though custom plug-ins can require subdirectories of this root directory.
  - Audio files must be placed in a location made accessible via an HTTP request from the voice browser. Unlike the Unified CVP software itself, serving audio files does not require an application server, they can be served by any web server such as IIS or Apache.

Note For types, input formats, output formats, and filesets, a plug-in defines a name for each as well as a display name. The display name is used for readability purposes and is what Call Studio shows when a new Say It Smart audio item is configured. The actual name is used by VXML Server and the developer when they build dynamic voice element configurations.

The Say It Smart plug-ins requiring the use of a pause produce VoiceXML using the `<break>` tag. Some voice browsers do not support this tag so Say It Smart playback normally including pauses on these browsers would hear no pauses.

This document presents full specifications for all Unified CVP Say It Smart plug-in types, including all input formats, output formats, filesets, and audio files required. The display names of these are also provided.



CHAPTER 2

Credit Card

Basic information about this plugin:

Plugin Name:	creditcard
Display Name:	Credit Card
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartCreditCard

- Description, on page 5
- Input Formats, on page 5
- Output Formats, on page 6
- Filesets, on page 6
- Audio Files, on page 6
- Examples, on page 7

Description

This Say It Smart type handles the reading of a credit card number. Any 13, 14, 15, or 16 digit number will be handled. Many times, a credit card number may appear with dashes at certain places in the number. To avoid having to process the data before it is sent to the plug-in, it will understand the credit card number with these optional dashes, though no punctuation other than dashes is allowed. The plug-in reads the credit card number back digit-by-digit, inserting 150 millisecond pauses at certain places where the credit card number is normally divided.

The plug-in Java class can easily be extended to create, in just a few lines of code, a new plug-in performing the same function with a different pause length or additional formatting options.

Input Formats

Name **(Display Name)**	**Description**

cc_number (13/14/15/16 Digit Number)	The data can be handled in any of the following formats: 16-digit cards (Visa, Mastercard, etc.): ################, ####-####-####-#### 15-digit cards (American Express): ###############, ####-######-##### 14-digit cards (Diner's Club): ##############, ####-#######-#### 13-digit cards (Visa): #############, ####-###-###-###

Output Formats

Name (Display Name)	Input Format Depends On	Description
digits_with_pauses (As digits w/ pauses)	cc_number	The credit card number is played back digit-by-digit with 150 millisecond pauses where the number is normally divided.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard (0-9))	digits_with_pauses	This fileset contains ten files: 0 through 9. It is the only fileset required.

Audio Files

All audio files must be named as appears below. The names do not have an extension, the developer can choose whatever file type is supported by their voice browser.

1	2	3	4	5	6	7	8	9	0	silence

Note The *silence* file is used when *Use Recorded Audio* is selected and when there is no TTS engine in the deployment. The recorded audio requires *silence* pauses be inserted between digits. These pauses are inserted automatically if using a TTS engine. If you do not have a TTS engine in your deployment, then copy the silence file to the same location on your media server as the number files. The silence file must be 150ms in duration.

Examples

Example #1

Data:	1234-5678-9012-3456
Input Format:	cc_number
Output Format:	digits_with_pauses
Fileset	standard
Playback:	“1” “2” “3” “4” <150ms pause> “5” “6” “7” “8” <150ms pause> “9” “0” “1” “2” <150ms pause> “3” “4” “5” “6”

Example #2

Data:	111122222233333
Input Format:	cc_number
Output Format:	digits_with_pauses
Fileset	standard
Playback:	“1” “1” “1” “1” <150ms pause> “2” “2” “2” “2” “2” “2” <150ms pause> “3” “3” “3” “3” “3”



CHAPTER 3

Currency

Basic information about this plugin:

Plugin Name:	currency
Display Name:	Currency ($)
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartCurrency

- Description, on page 9
- Input Formats, on page 9
- Output Formats, on page 10
- Filesets, on page 10
- Audio Files, on page 10
- Currency Examples, on page 11

Description

This Say It Smart type handles the reading of a currency value in dollars and cents. It only handles dollars and cents, so will work with U.S., Canadian, and other currencies using dollars and cents. The input data can optionally include a dollar sign ($) and does not need to include a decimal point. The amount can be positive or negative, and can even contain an exponent. The amount can be up to $999 trillion. The value is read normally, though if one component is zero, it will not be read. If the decimal contains more than two significant digits it will be rounded to the nearest cent.

This plug-in uses the Unified CVP Number Say it Smart plug-in to render the dollar and cent amounts. It uses the same audio files so if recording was done to support Number, those files can be leveraged to support Currency.

Input Formats

Name **(Display Name)**	**Description**

standard (Standard Currency)	The data can appear as a standard number with or without a minus sign, decimal point, $ sign, and even an exponent. No commas are allowed.

Output Formats

Name (Display Name)	Input Format Depends On	Description
dollars_cents (X dollars and Y cents)	standard	The dollar and cent amounts are read separately.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard)	dollars_cents	This fileset involves fewer audio files to render the currency amount but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
enhanced (Enhanced)	dollars_cents	This fileset involves more audio files to render a better sounding currency amount. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.

Audio Files

All audio files must be named as appears below. The names do not have an extension, the developer can choose whatever file type supported by their voice browser.

Standard Fileset

0	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	30	40	50	60	70	80	90	negative	
hundred	thousand	million	billion	trillion	dollars	dollar	and	cents	cent

Enhanced Fileset

0	1	2	3	4	5	6	7	8	9

10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29
30	31	32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47	48	49
50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69
70	71	72	73	74	75	76	77	78	79
80	81	82	83	84	85	86	87	88	89
90	91	92	93	94	95	96	97	98	99
100	200	300	400	500	600	700	800	900	
1000	2000	3000	4000	5000	6000	7000	8000	9000	
negative	thousand	million	billion	trillion	dollars	dollar	and	cents	cent

Currency Examples

Example #1

Data:	$25052.085
Input Format:	standard
Output Format:	dollars_cents
Fileset	enhanced
Playback:	“25” “thousand” “52” “dollars” “and” “9” “cents”

Example #2

Data:	0.01
Input Format:	standard
Output Format:	dollars_cents
Fileset	standard
Playback:	“1” “cent”

Example #3

Data:	6.99E4

Input Format:	standard
Output Format:	dollars_cents
Fileset	standard
Playback:	“60” “9” “thousand” “9” “hundred” “dollars”

Example #4

Data:	-$69900
Input Format:	standard
Output Format:	dollars_cents
Fileset	enhanced
Playback:	“negative” “69” “thousand” “900” “dollars”



CHAPTER 4

Custom Content

Plugin Name:	literal
Display Name:	Custom Content
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartLiteral

- Description, on page 13
- Input Formats, on page 13
- Output Formats, on page 14
- Filesets, on page 16
- Audio Files, on page 16
- Examples, on page 16

Description

This Say It Smart type was introduced to provide several helpful and time saving features to the application designer and developer:

- Provide a way to allow a list of audio files (with TTS transcripts) of variable length to be played one after the other in one audio item.
- Provide a more direct link to internal Java classes that may contain dynamic audio content as an alternative to creating dynamic voice element configurations.
- Provide at least the same functionality as the now “deprecated” File and String Unified CVP Say It Smart types.

Input Formats

Name (Display Name)	**Description**

simple (String (No Delimiters))	A text string that can represent a single filename or a single TTS string.
complex (FILE:::TTS|||…|||FILE:TTS)	A text string that follows a specific format with delimiters in order to represent any number of audio files and TTS transcripts. An audio file is separated from its TTS transcript by three colons. Each audio file/TTS combination is separated from others by three pipes. Note that each component of the combination can be blank if no audio file or TTS content is necessary. The audio will be played in the order in which it appears in the string from left to right.
resultset (ResultSetList Object)	A Java `ResultSetList` object that has been created by the Unified CVP Database element as a result of a database query that is expected to contain audio information. The result must return two columns, the first being the audio file (or `null` if no audio file is needed) and the second column being the TTS transcript for the audio file (or `null` if there is no TTS transcript). There can be any number of strows. The audio will be played in the order in which it appears in the result set.
siscontent (SayItSmartContent Object)	Each Say It Smart plug-in's Java code creates a `SayItSmartContent` object to represent audio content that is then passed to Unified CVP VXML Server to render into VoiceXML. This input format accepts a developer-created object of this type and the plug-in will pass this to VXML Server without making any modifications. This object can contain any number of audio files, TTS transcripts, and pauses the developer desires.
array (String[] Object)	A `String` array that can contain either a list of audio filenames or TTS transcripts (it cannot contain a mixture of audio filenames and TTS transcripts). The audio will be played in the order it appears in the array.

Output Formats

Name **(Display Name)**	**Input Format Depends On**	**Description**
standard (Filename w/ TTS Backup)	complex resultset siscontent	This output format will produce output containing both audio files (if defined) and TTS transcripts (if defined), assuming that the TTS content may contain Speech Synthesis Markup Language (SSML). This adds some additional overhead so use the `standard_no_ssml` output format if it is known that the TTS transcripts do not contain SSML.

standard_no_ssml (Filename w/ TTS Backup (no SSML))	complex resultset siscontent	This output format will produce output containing both audio files (if defined) and TTS transcripts (if defined), assuming that the TTS content does not contain SSML. Assuming no SSML makes the process more efficient than keeping open the possibility that the TTS content may have SSML (as in the `standard` fileset).
tts (TTS Only)	simple complex resultset siscontent array	This output format will produce output containing only the TTS content of the data, even if it contains audio file content. For the simple and array input formats, this output format indicates that the data contains only TTS content. This output format assumes the TTS content may contains SSML. This adds some additional overhead so use the `tts_no_ssml` output format if it is known that the TTS content does not contain SSML.
tts_no_ssml (TTS Only (no SSML))	simple complex resultset siscontent array	This output format will produce output containing only the TTS content of the data, even if it contains audio file content. For the `simple` and `array` input formats, this output format indicates that the data contains only TTS content. Assuming no SSML makes the process more efficient than keeping open the possibility that the TTS content may have SSML (as in the `tts` fileset).
files (Filename(s) Only)	simple complex resultset siscontent array	This output format will produce output containing only the audio file content of the data, even if it contains TTS content. For the `simple` and `array` input formats, this output format indicates that the data contains audio files only.

Filesets

Name (Display Name)	Output Format Depends On	Description
none (No Fileset)	standard standard_no_ssml tts tts_no_ssml files	This plug-in allows the developer to specify any amount of audio files, the names of which are determined at runtime. As a result, there is no need for a fileset. Every Say It Smart plug-in, though, requires at least one fileset, so this one is simply named *none*.

Audio Files

None. The audio files will be determined by the application designer and developer.

Examples

Example #1

Data:	myGreeting.wav
Input Format:	simple
Output Format:	files
Fileset	none
Playback:	myGreeting.wav (with no TTS backup)

Example #2

Data:	This is some text to speech
Input Format:	simple
Output Format:	tts_no_ssml
Fileset	none
Playback:	“This is some text to speech” (this is read as TTS)

Example #3

Data:	a.wav:::backup for a|||b.wav:::backup for b
Input Format:	complex
Output Format:	standard_no_ssml

Fileset	none
Playback:	a.wav (with TTS backup “backup for a”) b.wav (with TTS backup “backup for b”)

There are no examples of input formats that take Java objects as the data must be created by a developer in custom Java code.



CHAPTER 5

Date

Plugin Name:	date
Display Name:	Date
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartDate

- Description, on page 19
- Input Formats, on page 19
- Output Formats, on page 22
- Filesets, on page 23
- Audio Files, on page 24
- Examples, on page 27

Description

This Say It Smart type handles the reading of a date or portions of a date. It handles many input formats for the date, some of which provide only a partial date. The plug-in also supports the components of the date separated by forward slashes (/) and will require the use of this delimiter if any component of the date is expressed with one digit instead of two (for example, May 2 can be expressed as 0502 or 5/2 where the slash is required if any component is not padded with 0s). The date is read back in standard English fashion; the month name (rather than the number), the day, and the year. If only partial information is available, only that data will be read. The plug-in will only read legitimate dates according to the standard Gregorian calendar and will throw an error if an incorrect date is given.

This plug-in uses the Unified CVP Number Say it Smart plug-in to render the year. It uses the same audio files so recordings done to support Number can be leveraged to support Date.

Input Formats

All input formats with more than one date component can appear delimited with forward slashes.

Name **(Display Name)**	**Description**

mmddyyyy (MMDDYYYY)	The full date with the month, day, and four digit year. The data can be handled in any of the following formats: • mmddyyyy • mm/dd/yyyy • m/dd/yyyy • mm/d/yyyy • m/d/yyyy
mmddyy (MMDDYY)	The full date with the month, day, and two digit year. The data can be handled in any of the following formats: • mmddyy • mm/dd/yy • m/dd/yy • mm/d/yy • mm/dd/y • m/d/yy • m/dd/y • mm/d/y • m/d/y
ddmmyyyy (DDMMYYYY)	The full date with the day, month, and four digit year. The data can be handled in any of the following formats: • ddmmyyyy • dd/mm/yyyy • d/mm/yyyy • dd/m/yyyy • d/m/yyyy

ddmmyy (DDMMYY)	The full date with the day, month, and two digit year. The data can be handled in any of the following formats: • ddmmyy • dd/mm/yy • d/mm/yy • dd/m/yy • dd/mm/y • d/m/yy • d/mm/y • dd/m/y • d/m/y
yyyymmdd (YYYYMMDD)	The full date with the four digit year, month, and day. The data can be handled in any of the following formats: • yyyymmdd • yyyy/mm/dd • yyyy/m/dd • yyyy/mm/d • yyyy/m/d
mmyyyy (MMYYYY)	The month and four digit year. The data can be handled in any of the following formats: • mmyyyy • mm/yyyy • m/yyyy
mmyy (MMYY)	The month and two digit year. The data can be handled in any of the following formats: • mmyy • mm/yy • m/yy • mm/y • m/y

mmdd (MMDD)	The month and day. The data can be handled in any of the following formats: • mmdd • mm/dd • m/dd • mm/d • m/d
yyyy (YYYY)	The four digit year alone. The data can be handled in the following format: • yyyy
ddmm (DDMM)	The day and month. The data can be handled in any of the following formats: • ddmm • dd/mm • d/mm • dd/m • d/m
mm (MM)	The month alone. The data can be handled in the following format: • mm

Output Formats

Name **(Display Name)**	**Input Format Depends On**	**Description**
date (The Date)	mmddyyyy ddmmyyyy yyyymmdd	For all input formats containing the full date, this output format plays the month name, day, and full four digit year.
date_19 (The Date w/ YY=19)	mmddyy ddmmyy	For all input formats containing the full date and a two digit year, this plays the month name, day, and year assuming it is in the 1900s.

date_20 (The Date w/ YY=20)	mmddyy ddmmyy	For all input formats containing the full date and a two digit year, this plays the month name, day, and year assuming it is in the 2000s.
month_year (Month/Year)	mmyyyy	Plays the month name and full four digit year.
month_year_19 (Month/Year w/ YY=19)	mmyy	Plays the month name and year assuming it is in the 1900s.
month_year_20 (Month/Year w/ YY=20)	mmyy	Plays the month name and year assuming it is in the 2000s.
month_day (Month/Day)	mmdd ddmm	Plays the month name and the day.
month (Month)	mm	Plays the month name only.
year (Year)	yyyy	Plays the full four digit year only.

Filesets

Name **(Display Name)**	**Output Format Depends On**	**Description**
standard_date (Standard Full Date)	date date_19 date_20	This fileset contains all files needed to render the full date. It involves fewer audio files to render the year but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
enhanced_date (Enhanced Full Date)	date date_19 date_20	This fileset contains all files needed to render the full date. This fileset involves more audio files to render a better sounding year. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.

month_standard_year (Month/Standard Year)	month_year month_year_19 month_year_20	This fileset contains all files needed to render a month and a year. It involves fewer audio files to render the year but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
month_enhanced_year (Month/Enhanced Year)	month_year month_year_19 month_year_20	This fileset contains all files needed to render a month and a year. This fileset involves more audio files to render a better sounding year. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.
month_day (Month/Day)	month_day	This fileset contains all files needed to render a month and a day.
month (Month Only)	month	This fileset contains all files needed to render the month alone.
standard_year (Standard Year)	year	This fileset contains all files needed to render the year alone. It involves fewer audio files but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
enhanced_year (Enhanced Year)	year	This fileset contains all files needed to render the year alone. This fileset involves more audio files to render a better sounding year. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.

Audio Files

All filesets including the month have a separate file for each month. All filesets with the day of the month will have a separate file for each day (*1st*, *2nd*, and so on). Only those filesets containing the year have standard and enhanced versions that render the year with less files or more files respectively. The files required to render the year are almost the same as the Unified CVP Number Say it Smart plug-in with the exception that numbers greater than 9999 are not necessary and zero is replaced with *oh*.

Standard Full Date

January	February	March	April	May	June	July	August	September	October	November	December

1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	11th	12th
13th	14th	15th	16th	17th	18th	19th	20th	21th	22nd	23rd	25th
26th	27th	28th	29th	30th	31st						
oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	30	40	50
60	70	80	90	hundred	thousand						

Enhanced Full Date

January	February	March	April	May	June	July	August	September	October	November	December
1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	11th	12th
13th	14th	15th	16th	17th	18th	19th	20th	21th	22nd	23rd	25th
26th	27th	28th	29th	30th	31st						
oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31	32	33	34	35
36	37	38	39	40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69	70	71
72	72	73	74	75	76	77	78	79	80	81	82
83	84	85	86	87	88	89	90	91	92	93	94
95	96	97	98	99	100	200	300	400	500	600	700
800	900	1000	2000	3000	4000	5000	6000	7000	8000	9000	hundred

Month/Standard Year

January	February	March	April	May	June	July	August	September	October	November	December
oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	30	40	50
60	70	80	90	hundred	thousand						

Month/Enhanced Year

January	February	March	April	May	June	July	August	September	October	November	December

oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31	32	33	34	35
36	37	38	39	40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69	70	71
72	72	73	74	75	76	77	78	79	80	81	82
83	84	85	86	87	88	89	90	91	92	93	94
95	96	97	98	99	100	200	300	400	500	600	700
800	900	1000	2000	3000	4000	5000	6000	7000	8000	9000	hundred

Month/Day

January	February	March	April	May	June	July	August	September	October	November	December
1st	2nd	3rd	4th	5th	6th	7th	8th	9th	10th	11th	12th
13th	14th	15th	16th	17th	18th	19th	20th	21th	22nd	23rd	25th
26th	27th	28th	29th	30th	31st						

Month Only

January	February	March	April	May	June	July	August	September	October	November	December

Standard Year

oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	30	40	50
60	70	80	90	hundred	thousand						

Enhanced Year

oh	1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31	32	33	34	35
36	37	38	39	40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69	70	71

72	72	73	74	75	76	77	78	79	80	81	82
83	84	85	86	87	88	89	90	91	92	93	94
95	96	97	98	99	100	200	300	400	500	600	700
800	900	1000	2000	3000	4000	5000	6000	7000	8000	9000	hundred

Examples

Example #1

Data:	02171971
Input Format:	mmddyyyy
Output Format:	date
Fileset	standard_date
Playback:	“February” “17th” “19” “70” “1”

Example #2

Data:	02/09/05
Input Format:	ddmmyy
Output Format:	date_19
Fileset	enhanced_date
Playback:	“September” “2nd” “19” “oh” “5”

Example #3

Data:	072003
Input Format:	mmyyyy
Output Format:	month_year
Fileset	month_standard_year
Playback:	“July” “2” “thousand” “3”

Example #4

Data:	2387
Input Format:	yyyy
Output Format:	year

Fileset	enhanced_year
Playback:	“23” “87”

Example #5

Data:	12
Input Format:	mm
Output Format:	month
Fileset	month
Playback:	“December”

Example #6

Data:	10/10
Input Format:	mmdd
Output Format:	month_day
Fileset	month_day
Playback:	“October” “10th”



CHAPTER 6

Digits

Plugin Name:	digits
Display Name:	Digit-By-Digit
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartDigit

- Description, on page 29
- Input Formats, on page 29
- Output Formats, on page 29
- Filesets, on page 30
- Audio Files, on page 30
- Examples, on page 30

Description

This Say It Smart type handles the reading of any number digit by digit. The number can be negative or positive and can also contain a decimal (though, unlike Number, exponents are not supported). Every character is read individually.

Input Formats

Name **(Display Name)**	**Description**
number (Any Length Number)	This number can appear as any length whole or decimal number. If the number is negative, the minus sign must be the first character.

Output Formats

Name	**Input Format Depends On**	**Description**

(Display Name)		
digits (Digit-By-Digit)	number	The number can be played back in only one manner: digit by digit.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard)	digits	This single fileset contains all numbers from 0 to 9 as well as *point* and *negative*.

Audio Files

0	2	3	4	5
6	7	8	9	
negative	point			

Examples

Example #1

Data:	96.89
Input Format:	number
Output Format:	digits
Fileset	standard
Playback:	”9” ”6” ”point” ”8” ”9”

Example #2

Data:	-10
Input Format:	number
Output Format:	digits
Fileset	standard

Playback:	“negative“ “1” “0”



CHAPTER 7

Filename

Plugin Name:	file
Display Name:	Filename
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmart

- Description, on page 33
- Input Formats, on page 34
- Output Formats, on page 34
- Filesets, on page 34
- Audio Files, on page 34
- Examples, on page 34

Description

This Say It Smart type handles the playback of an audio file whose name is passed as input to the plug-in. In Call Studio, one can specify a file type to apply to all audio files listed by the Say It Smart type. Filename is no different, the file type extension specified in Call Studio will be appended to the filename passed to the plug-in. If the data sent as input already has an extension, Call Studio file type should be blank. For a TTS backup, the plug-in returns the name of the audio file since the transcript cannot be known in advance. When trying to use this type in TTS only mode, it returns a `null`.

Note **Important.** In Call Studio and VXML Server substitution can be used within audio file names and TTS content, so one can do with substitution what this plug-in does. Additionally, a new Say It Smart plug-in type was introduced: Custom Content, that does what this plug-in does and more (such as allowing for a TTS backup). As a result, this plug-in should be considered *deprecated*. It is still included for backwards compatibility however eventually this plug-in will no longer be included in Unified CVP updates, so use one of the above solutions instead of using this plug-in.

Input Formats

Name (Display Name)	Description
string (A Filename)	Any string (the plug-in does no filename validation).

Output Formats

Name (Display Name)	Input Format Depends On	Description
audio (Audio File)	string	A single audio file whose name is passed to the plug-in.

Filesets

Name (Display Name)	Output Format Depends On	Description
none (No Fileset)	audio	The fileset contains only one file: the one to play.

Audio Files

The only audio file needed is the audio file to play, which is determined dynamically.

Examples

Example #1

Data:	my file
Input Format:	string
Output Format:	audio
Fileset	none

Playback:	[Assuming an extension of “ulaw” was given in Call Studio] “my file.ulaw”

Example #2

Data:	audio_logo.wav
Input Format:	string
Output Format:	audio
Fileset	none
Playback:	[Assuming an extension of ”wav” was given in Call Studio] “audio_logo.wav.wav”



CHAPTER 8

Number

Plugin Name:	number
Display Name:	Number
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartNumber

- Description, on page 37
- Input Formats, on page 37
- Output Formats, on page 38
- Filesets, on page 38
- Audio Files, on page 38
- Examples, on page 39

Description

This Say It Smart type handles the reading of any number. The number can be negative or positive, contain a decimal, and can even contain an exponent. The whole part of the number is read normally and the decimal part of the number is read digit-by-digit. This plug-in can handle numbers up to 999 trillion.

The number can be read back in a way that sounds somewhat robotic, though it uses a minimum number of audio files. The number can also be read back in a manner that sounds better to the caller but will require more files to do so. These differences are encapsulated in the Number type's two filesets: `standard` and `enhanced`. All Unified CVP Say It Smart plug-ins that have numerical components use the Number plug-in to convert their numbers so those plug-ins will list these two filesets as well.

Input Formats

Name **(Display Name)**	**Description**
standard (Standard)	This represents any number, negative or positive, with or without a decimal, and optionally containing an exponent. No commas are allowed.

Output Formats

Name (Display Name)	Input Format Depends On	Description
standard (Standard Number)	standard	The whole part of the number is read normally and the decimal is read digit-by-digit.
no_trailing_0s (Read w/ no Trailing 0s)	standard	The whole part of the number is read normally, the decimal is read digit-by-digit, omitting trailing zeros.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard)	standard no_trailing_0s	This fileset involves fewer audio files to render the number but at the cost of sounding a bit robotic.
enhanced (Enhanced)	standard no_trailing_0s	This fileset involves more audio files to render a better sounding number.

Audio Files

Standard Fileset

0	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	30	40	50	60	70	80	90		
negative	point	hundred	thousand	million	billion	trillion			

Enhanced Fileset

0	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29
30	31	32	33	34	35	36	37	38	39

40	41	42	43	44	45	46	47	48	49
50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69
70	71	72	73	74	75	76	77	78	79
80	81	82	83	84	85	86	87	88	89
90	91	92	93	94	95	96	97	98	99
100	200	300	400	500	600	700	800	900	
1000	2000	3000	4000	5000	6000	7000	8000	9000	
negative	point	thousand	million	billion	trillion				

Examples

Example #1

Data:	4836945.160
Input Format:	standard
Output Format:	standard
Fileset	enhanced
Playback:	“4” “million” “800” “36” “thousand” “900” “45” “point” “1” “6” “0”

Example #2

Data:	3.10
Input Format:	standard
Output Format:	no_trailing_0s
Fileset	standard
Playback:	“3” “point” “1”

Example #3

Data:	36.1234E2
Input Format:	standard
Output Format:	standard
Fileset	standard

Playback:	“3” “thousand” “6” “hundred” “12” “point” “3” “4”

Example #4

Data:	-3E-2
Input Format:	standard
Output Format:	standard
Fileset	standard
Playback:	“negative” “0” “point” “0” “0” “3”



CHAPTER 9

Phone

Plugin Name:	phone
Display Name:	Phone Number
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartPhone

- Description, on page 41
- Input Formats, on page 41
- Output Formats, on page 42
- Filesets, on page 42
- Audio Files, on page 42
- Examples, on page 43

Description

This Say It Smart type handles the reading of a 10 digit phone number. The number must have an area code and cannot be an 11-digit number starting with 1. Many times, a phone number may appear with various formatting. To avoid having to process the data before it is sent to the plug-in, the plug-in will understand the standard phone number formats. The phone number is read digit-by-digit, inserting 150 millisecond pauses after the area code and exchange.

The plug-in Java class can easily be extended to create, in just a few lines of code, a new plug-in performing the same function with a different pause length or additional formatting options.

Input Formats

Name **(Display Name)**	**Description**

10_digit_whole_number (10 Digit Number)	The data can be handled in any of the following formats: • ########## • (###) ###-#### • (###)###-#### • ###-###-#### • ###.###.#### • (###)####### **Note** The second format contains a space after the area code; the third does not.

Output Formats

Name (Display Name)	Input Format Depends On	Description
digits_with_pauses (As Digits w/ Pauses)	10_digit_whole_number	The phone number is played back digit-by-digit with 150 millisecond pauses where the number is normally divided.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard (0-9))	digits_with_pauses	This fileset contains ten files: 0 through 9. It is the only fileset required.

Audio Files

All audio files must be named as appears below. The names do not have an extension, the developer can choose whatever file type supported by their voice browser.

Note The *silence* file is used when *Use Recorded Audio* is selected and when there is no TTS engine in the deployment. The recorded audio requires *silence* pauses be inserted between digits. These pauses are inserted automatically if using a TTS engine. If you do not have a TTS engine in your deployment, then copy the silence file to the same location on your media server as the number files. The silence file must be 150ms in duration.

0	1	2	3	4	5	6	7	8	9	silence

Examples

Example #1

Data:	(800) 555-1212
Input Format:	10_digit_whole_number
Output Format:	digits_with_pauses
Fileset	standard
Playback:	“8” “0” “0” <150ms pause> “5” “5” “5” <150ms pause> “1” “2” “1” “2”

Example #2

Data:	1112223333
Input Format:	10_digit_whole_number
Output Format:	digits_with_pauses
Fileset	standard
Playback:	“1” “1” “1” <150ms pause> “2” “2” “2” <150ms pause> “3” “3” “3” “3”



CHAPTER 10

Social Security

Plugin Name:	ssn
Display Name:	Social Security Number
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartSocialSecurity

- Description, on page 45
- Input Formats, on page 45
- Output Formats, on page 46
- Filesets, on page 46
- Audio Files, on page 46
- Examples, on page 46

Description

This Say It Smart type handles the reading of a 9-digit social security number. Many times, a social security number may appear with dashes after the third and fifth digits. To avoid having to process the data before it is sent to the plug-in, it will understand the social security number with these optional dashes, though no punctuation other than dashes is allowed. It reads it back digit-by-digit, inserting 150 millisecond pauses after the third and fifth digits.

The plug-in Java class can easily be extended to create, in just a few lines of code, a new plug-in performing the same function with a different pause length or additional formatting options.

Input Formats

Name **(Display Name)**	**Description**
9_digit_whole_number (9 Digit Number)	The data can be handled in any of the following formats: • ######### • ###-##-####

Output Formats

Name (Display Name)	Input Format Depends On	Description
digits_with_pauses (As Digits w/ Pauses)	9_digit_whole_number	The social security number is played back digit-by-digit with 150 millisecond pauses after the third and fifth digits.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard (0-9))	digits_with_pauses	This fileset contains ten files: 0 through 9. It is the only fileset required.

Audio Files

Note The *silence* file is used when *Use Recorded Audio* is selected and when there is no TTS engine in the deployment. The recorded audio requires *silence* pauses be inserted between digits. These pauses are inserted automatically if using a TTS engine. If you do not have a TTS engine in your deployment, then copy the silence file to the same location on your media server as the number files. The silence file must be 150ms in duration.

0	1	2	3	4	5	6	7	8	9	silence

Examples

Example #1

Data:	123-45-6789
Input Format:	9_digit_whole_number
Output Format:	digits_with_pauses
Fileset	standard

Playback:	“1” ”2” ”3” <150ms pause> ”4” ”5” <150ms pause> ”6” ”7” ”8” ”9”

Example #2

Data:	111223333
Input Format:	9_digit_whole_number
Output Format:	digits_with_pauses
Fileset	standard
Playback:	“1” ”1” ”1” <150ms pause> ”2” ”2” <150ms pause> ”3” ”3” ”3” ”3”



CHAPTER 11

String

Plugin Name:	string
Display Name:	TTS String
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartString

- Description, on page 49
- Input Formats, on page 49
- Output Formats, on page 50
- Filesets, on page 50
- Audio Files, on page 50
- Examples, on page 50

Description

This Say It Smart type plays back the data sent as input in Text To Speech (TTS). Even when the *Use Recorded Audio* checkbox is checked in Call Studio, the output will be a TTS string containing the passed data. The input data is unmodified unless it contains characters not allowed in XML and the TTS content is not contained within CDATA (this occurs only on some supported voice browsers). These characters will then be converted to their escaped equivalents (for example "<" is converted to "<").

Note **Important.** In Call Studio and VXML Server substitution can be used within audio file names and TTS content, so one can do with substitution what this plug-in does. Additionally, a new Say It Smart plug-in type was introduced: Custom Content, that does what this plug-in does and more. As a result, this plug-in should be considered "deprecated". It is still included for backwards compatibility however eventually this plug-in will no longer be included in Unified CVP updates, so use one of the above solutions instead of using this plug-in.

Input Formats

Name	Description

(Display Name)	
string (A String)	Any string. The string is modified only when the string contains characters illegal to XML and the TTS content is not placed inside CDATA.

Output Formats

Name (Display Name)	Input Format Depends On	Description
tts (The String in TTS)	string	The data will be read by the TTS engine.

Filesets

Name (Display Name)	Output Format Depends On	Description
none (No Fileset)	audio	There is no fileset because this type will never involve the playing of pre-recorded audio files. Every Say It Smart plug-in, though, requires at least one fileset, so this one is simply named “none”.

Audio Files

None. The data will always be rendered in TTS.

Examples

Example #1

Data:	Today’s bingo number is 28.
Input Format:	string
Output Format:	tts
Fileset	none
Playback:	Today’s bingo number is 28 (as TTS).

Example #2

Data:	myfile.wav
Input Format:	string
Output Format:	tts
Fileset	none
Playback:	myfile.wav (as TTS).



CHAPTER 12

State

Plugin Name:	state
Display Name:	U.S./Canada State
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartState

- Description, on page 53
- Input Formats, on page 53
- Output Formats, on page 54
- Filesets, on page 54
- Audio Files, on page 54
- Examples, on page 55

Description

This Say It Smart type handles the reading of a U.S. or Canadian state, territory, or province. The data is passed as the two-letter abbreviation of the state and the plug-in plays back the full name. Please see the Audio Files section to see a list of U.S. and Canadian states, territories, and provinces.

Note When the VoiceXML is produced, the TTS transcript will be exactly the same as the audio filename except without any underscores.

Input Formats

Name **(Display Name)**	**Description**
state_abbreviation (2-Character Abbreviation)	A two letter abbreviation of the state (case insensitive).

Output Formats

Name (Display Name)	Input Format Depends On	Description
state_name (Full State Name)	state_abbreviation	An audio file playing the full state, territory, or province name.

Filesets

Name (Display Name)	Output Format Depends On	Description
standard (Standard)	state_name	There is only one fileset: a separate audio file for each U.S. or Canadian state, territory or province.

Audio Files

The filenames are as shown (no spaces in the names). The two-letter abbreviation for each state, territory, or province is listed in parentheses.

U.S. Territories

american_samoa (AS)	federated_states_of_micronesia (FM)	guam (GU)
marshall_islands (MH)	northern_mariana_islands (MP)	puerto_rico (PR)
us_virgin_islands (VI)	palau (PW)	

U.S. States

alabama (AL)	alaska (AK)	arizona (AZ)	arkansas (AR)
california (CA)	colorado (CO)	connecticut (CT)	delaware (DE)
district_of_columbia (DC)	florida (FL)	georgia (GA)	hawaii (HI
idaho (ID)	illinois (IL)	indiana (IN)	iowa (IA)
kansas (KS)	kentucky (KY)	louisiana (LA)	maine (ME)
maryland (MD)	massachusetts (MA)	michigan (MI)	minnesota (MN)
mississippi (MS)	missouri (MO)	montana (MT)	nebraska (NE)

nevada (NV)	new_hampshire (NH)	new_jersey (NJ)	new_mexico (NM)
new_york (NY)	north_carolina (NC)	north_dakota (ND)	ohio (OH)
oklahoma (OK)	oregon (OR)	pennsylvania (PA)	rhode_island (RI)
south_carolina (SC)	south_dakota (SD)	tennessee (TN)	texas (TX)
utah (UT)	vermont (VT)	virginia (VA)	washington (WA)
west_virginia (WV)	wisconsin (WI)	wyoming (WY)	

Canadian Provinces/Territories

alberta (AB)	british_columbia (BC)	manitoba (MB)	new_brunswick (NB)
newfoundland (NL)	nova_scotia (NS)	northwest_territories (NT)	nunavut (NU)
ontario (ON)	prince_edward (PE)	quebec (QC)	sasketchewan (SK)
yukon (YT)			

Examples

Example #1 (shows case is not important)

Data:	nY
Input Format:	state_abbreviation
Output Format:	state_name
Fileset	standard
Playback:	“new_york”

Example #2

Data:	SK
Input Format:	state_abbreviation
Output Format:	state_name
Fileset	standard
Playback:	“sasketchewan”



CHAPTER 13

Time

Plugin Name:	time
Display Name:	Time/Time Period
Class Name:	com.audium.sayitsmart.plug-ins.AudiumSayItSmartTime

- Description, on page 57
- Input Formats, on page 57
- Output Formats, on page 58
- Filesets, on page 59
- Audio Files, on page 60
- Examples, on page 61

Description

This Say It Smart type handles the playback of the time or a time period. Whether to play back the time or a time period is specified by an input format. The plug-in also supports the different components of the time separated by colons (:) and will require the use of this delimiter if any component of the time is expressed with one digit instead of two (for example, 1:09 AM can be expressed as 0109 or 1:9 where the colon is required if any component is not padded with 0s). The time arrives in 24-hour military format and time periods arrive in combinations of hours, minutes, and seconds. The time is read back in standard English fashion; the hour, the minute, and either “A.M.” or “P.M.”. Time periods are read back with each component followed by a qualifier (*hours*, *minutes*, or *seconds*). The plug-in will only read the time or time period if it is legitimate (the components are within the appropriate range).

This plug-in uses the Unified CVP Number Say it Smart plug-in to render each component of the time or time period. It uses the same audio files so recordings done to support Number can be leveraged to support Time.

Input Formats

Name **(Display Name)**	**Description**

time_hhmm (24Hr Time (HHMM))	This input format is used to specify the time. It must arrive in 24-hour format with the hours from 00 to 23 and the minute from 00 to 59. The data can be handled in any of the following formats: • hhmm • hh:mm • h:mm • hh:m • h:m
period_hhmmss (Time Period (HHMMSS))	This input format is used to specify a time period including hours (from 00 to 99), minutes (from 00 to 59), and seconds (from 00 to 59). The data can be handled in any of the following formats: • hhmmss • hh:mm:ss
period_hhmm (Time Period (HHMM))	This input format is used to specify a time period including hours (from 00 to 99) and minutes (from 00 to 59). The data can be handled in any of the following formats: • hhmm • hh:mm
period_mmss (Time Period (MMSS))	This input format is used to specify a time period including minutes (from 00 to 99) and seconds (from 00 to 59). The data can be handled in any of the following formats: • mmss • mm:ss

Output Formats

Name **(Display Name)**	**Input Format Depends On**	**Description**
time (The Time)	time_hhmm	The time is read back with the hour (from 1 to 12) followed by the minute (from 0 to 59) followed by “A.M.” or “P.M.”. If the minute is zero, it will be omitted.

time_special_12 (The Time 12=Midnight/Noon)	time_hhmm	The time is read back exactly as above except that 00:00 is read as *midnight* and 12:00 is read as *noon*.
period (Time Period)	period_hhmmss period_hhmm period_mmss	The time period is read back with each component followed by the qualifier *hours*, *minutes*, or *seconds*. If one component is zero, it is omitted.

Filesets

Name **(Display Name)**	**Output Format Depends On**	**Description**
standard_time (Standard Time)	time	This fileset involves fewer audio files to render the time but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
enhanced_time (Enhanced Time)	time	This fileset involves more audio files to render a better sounding time. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.
standard_special_12 (Standard Time + Noon/Midnight)	time_special_12	This fileset is exactly the same as `standard_time` except with two extra files; *noon* and *midnight*.
enhanced_special_12 (Enhanced Time + Noon/Midnight)	time_special_12	This fileset is exactly the same as `enhanced_time` except with two extra files; `noon` and `midnight`.
standard_period (Standard Time Period)	period	This fileset involves fewer audio files to render the time period but at the cost of sounding a bit robotic. This directly correlates to the Unified CVP Number Say it Smart plug-in's `standard` fileset.
enhanced_period (Enhanced Time Period)	period	This fileset involves more audio files to render a better sounding time period. This directly correlates to the Unified CVP Number Say It Smart plug-in's `enhanced` fileset.

Audio Files

Note When reading back a time, zeros are replaced by *oh*. for example, 13:05 is read back as *one oh five P.M.* This is not the case for time periods.

standard_time

oh	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	30	40	50	am	pm				

enhanced_time

oh	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29
30	31	32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47	48	49
50	51	52	53	54	55	56	57	58	59
am	pm								

standard_special_12

oh	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	30	40	50	am	pm	noon	midnight		

enhanced_special_12

oh	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29
30	31	32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47	48	49
50	51	52	53	54	55	56	57	58	59

am	pm	noon	midnight						

standard_period

oh	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	30	40	50	60	70	80	90		
hour	hours	minute	minutes	second	seconds				

enhanced_period

0	1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18	19
20	21	22	23	24	25	26	27	28	29
30	31	32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47	48	49
50	51	52	53	54	55	56	57	58	59
60	61	62	63	64	65	66	67	68	69
70	71	72	73	74	75	76	77	78	79
80	81	82	83	84	85	86	87	88	89
90	91	92	93	94	95	96	97	98	99
hour	hours	minute	minutes	second	second				

Examples

Example #1

Data:	20:43
Input Format:	time_hhmm
Output Format:	time
Fileset	standard_time
Playback:	“8” “40” “3” “pm”

Example #2

Data:	20:43

Input Format:	time_hhmm
Output Format:	time
Fileset	enhanced_time
Playback:	“8” “43” “pm”

Example #3

Data:	0000
Input Format:	time_hhmm
Output Format:	time_special_12
Fileset	standard_special_12
Playback:	“midnight”

Example #4

Data:	02:00
Input Format:	time_hhmm
Output Format:	time_special_12
Fileset	enhanced_special_12
Playback:	“2” “am”

Example #5

Data:	12:09
Input Format:	time_hhmm
Output Format:	time
Fileset	standard_time
Playback:	“12” “oh” “9” “pm”

Example #6

Data:	810001
Input Format:	period_hhmmss
Output Format:	period
Fileset	standard_period
Playback:	“80” “1” “hours” “1” “second”

Example #7

Data:	0001
Input Format:	period_hhmm
Output Format:	period
Fileset	standard_period
Playback:	“1” “minute”

Example #8

Data:	99:59
Input Format:	period_mmss
Output Format:	period
Fileset	enhanced_period
Playback:	“99” “minutes” “59” “seconds”

INDEX

A

audio files, plugin component, defined 1

C

credit card two different format examples 7
currency plugin, four examples 11
currency plugin, standard and enhanced audio files 10
custom plugins, examples 16
custom plugins, multiple input and output formats 13
custom plugsin, purposes 13

D

date plugin, multiple audio file sets 24
date plugin, multiple examples 27
date plugin, multiple filesets 23
date plugin, multiple input and output formats 19

F

filename plugin, examples 34
filename plugin, important note 33
fileset, plugin component, defined 1

I

input format, plugin component, defined 1

N

number plugin, multiple examples 39
number plugin, standard and enhanced audio sets 38

O

output format, plugin component, defined 1

P

phone plugin, handles multiple input formats 41

S

Say It Smart Plugins 1
    each component defined 1
social security plugin, examples contains pauses 46
social security plugin, two input formats 45
state plugin, audio files for states, territories and Canadian provinces and territories 54
string plugin, important note 49

T

time plugin, multiple audio file sets 60
time plugin, multiple examples 61
time plugin, multiple filesets 59
time plugin, multiple input formats 57
time plugin, multiple output formats 58
type, plugin component, defined 1