



Phone

- [CcmcipServer1, page 1](#)
- [CcmcipServer2, page 2](#)
- [CtiServer1, page 2](#)
- [CtiServer2, page 2](#)
- [EnableCallPark, page 2](#)
- [EnableDSCPPacketMarking, page 2](#)
- [Meeting_Server_Address, page 3](#)
- [Meeting_Server_Address_Backup, page 3](#)
- [Meeting_Server_Address_Backup2, page 3](#)
- [TftpServer1, page 3](#)
- [TftpServer2, page 4](#)
- [useCUCMGroupForCti, page 4](#)
- [MakeCallHotKey, page 4](#)

CcmcipServer1

Applies to all the Cisco Jabber clients.
Specifies the address of the primary CCMCIP server.

This parameter is required:

- Only if the address of your CCMCIP server is not the same as the TFTP server address.
If the address of the CCMCIP server is the same as the TFTP server address, the client can use the TFTP server address to connect to the CCMCIP server.
- In deployments with Cisco Unified Communications Manager Release 8.
In deployments with Cisco Unified Communications Manager release 9 and later, the client can discover the CCMCIP server if you provision the `_cisco-uds` SRV record.

Cisco Unified Communications Manager release 9.x and earlier—If you enable Cisco Extension Mobility, the `Cisco Extension Mobility` service must be activated on the Cisco Unified Communications Manager nodes that are used for CCMCIP. For information about Cisco Extension Mobility, see the *Feature and Services* guide for your Cisco Unified Communications Manager release.

Example: `<CcmcipServer1>server_address</CcmcipServer1>`

CcmcipServer2

Applies to all the Cisco Jabber clients.

Specifies the address of the secondary CCMCIP server.

Example: `<CcmcipServer2>server_address</CcmcipServer2>`

CtiServer1

Applies to all the Cisco Jabber clients.

Specifies the address of the primary CTI server.

You should specify a CTI server address in the client configuration if users have desk phone devices.

Example: `<CtiServer1>server_address</CtiServer1>`

CtiServer2

Applies to all the Cisco Jabber clients.

Specifies the address of the secondary CTI server.

Example: `<CtiServer2>server_address</CtiServer2>`

EnableCallPark

Applies to the Cisco Jabber mobile clients.

Specifies whether the call park feature is available in the client. To access the call park feature, choose the **More** option in the call window.

- true (default)—Call park is enabled.
- false—Call park is disabled. There is no call park option under the **More** button.

Example: `<EnableCallPark>>false</EnableCallPark>`

EnableDSCPPacketMarking

Applies to Cisco Jabber for Mac and Cisco Jabber for mobile clients.

If `EnableDSCPPacketMarking` is configured with any of these values, then the user will not see **Enable Differentiated Service for Calls** option in the Cisco Jabber client.

Specifies if DSCP marking is applied to the packets:

- true (default)—DSCP marking is enabled and the checkbox in the client is not shown.
- false—DSCP marking is not made to packets and the checkbox in the client is not shown.

Example: `<EnableDSCPpacketMarking>>false<EnableDSCPpacketMarking>`

Meeting_Server_Address

Applies to Cisco Jabber desktop clients.

Specifies the primary Cisco WebEx meeting site URL for users.

Cisco Jabber for Windows client populates the meeting site in the user's host account on the **Options** window. Cisco Jabber for Mac client populates the meeting site in the user's host account on the **Preferences > Meetings** window. Users can enter their credentials to set up the host account and access their Cisco WebEx meetings, if the meeting site requires credentials.



Important

If you specify an invalid meeting site, users cannot add, or edit, any meetings sites in the client user interface.

Example: `<Meeting_Server_Address>Meeting_Site</Meeting_Server_Address>`

Meeting_Server_Address_Backup

Applies to all the Cisco Jabber clients.

Specifies the secondary Cisco WebEx meeting site URL for users.

Example: `<Meeting_Server_Address_Backup>meeting_site</Meeting_Server_Address_Backup>`

Meeting_Server_Address_Backup2

Applies to all the Cisco Jabber clients.

Specifies the tertiary Cisco WebEx meeting site URL for users.

Example: `<Meeting_Server_Address2>meeting_site</Meeting_Server_Address2>`

TftpServer1

Applies to all the Cisco Jabber clients.

Specifies the address of the primary Cisco Unified Communications Manager TFTP service where device configuration files reside. Set one of the following as the value:

- Hostname (*hostname*)
- IP address (*123.45.254.1*)
- FQDN (*hostname.domain.com*)

You should set this parameter in the client configuration only if:

- You deploy the client in phone mode.
- The TFTP server address for the device configuration is different to the TFTP server address for the client configuration.

During installation, you should set the address of the TFTP server where the client configuration file resides with the following argument: TFTP.

Example: `<TftpServer1>hostname</TftpServer1>`

TftpServer2

Applies to all the Cisco Jabber clients.

Specifies the address of the secondary Cisco Unified Communications Manager TFTP service.

Example: `<TftpServer2>hostname</TftpServer2>`

useCUCMGroupForCti

Applies to the Cisco Jabber desktop clients.

Specifies if the Cisco Unified Communications Manager Group handles load balancing for CTI servers. Set one of the following values:

- **true**—The Cisco Unified Communications Manager Group handles CTI load balancing. You should set this value in phone mode deployments only. In full UC mode, the presence server automatically handles CTI load balancing.
- **false** (default)—The Cisco Unified Communications Manager Group does not handle CTI load balancing.

Example: `<useCUCMGroupForCti>true</useCUCMGroupForCti>`

MakeCallHotKey

Applies to Cisco Jabber for Windows.

Specifies a key combination to define a keyboard shortcut in the client. The shortcut allows users to copy text from another application and paste it into the client. When you configure a key combination, it overwrites what another application does with that keyboard shortcut.

- **true** (default)—CTRL+SHIFT+J is enabled as the keyboard shortcut to make click-to-call.
- **false**—The keyboard shortcut is disabled.
- **specify your own keyboard shortcut**—Specify another keyboard shortcut as the value for this parameter, for example `MakeCallHotKey=CTRL+SHIFT+R`. Your own defined keyboard shortcut can use the following keys: CTRL and [SHIFT or ALT (but not both)], + a character, or CTRL + a character.

Example: `<MakeCallHotKey>false</MakeCallHotKey>`