



## Reference

---

- [Call Link Format](#), page 1
- [Mapping Between Link Fields and SIP Headers](#), page 2

## Call Link Format

Call links are constructed in the following format:

```
https://example-jabberguest/call/directory number (DN) or UserID@example.com
```

The following table provides some examples of how links are constructed.

**Table 1: Example Call Link URLs**

URL	Notes
<code>http://example-jabberguest.com/call/janedoe@example.com</code>	URI links work only for endpoints with URI dialing enabled.
<code>http://example-jabberguest.com/call/5309@example.com</code>	4-digit DNs work only for endpoints homed on the same cluster.
<code>http://example-jabberguest.com/call/17011701@example.com</code>	8-digit DNs work for all endpoints on the same domain.



**Note**

---

The domain is optional. If the domain is supplied, it must match the enterprise domain configured in Cisco Unified Communications Manager. If a domain is not supplied on an ad hoc link, the SIP domain (in **Settings > Call Control and Media**) for this server is used.

---

## Mapping Between Link Fields and SIP Headers

Link Field	SIP Header
<b>Destination</b>	Request-URI in the INVITE
<b>Caller SIP Alias</b> <b>Note</b> If you do not enter a value in the <b>Caller SIP alias</b> field, the value in the <b>Default caller SIP alias</b> field is used.	User portion of the <i>From:</i> and <i>Remote Party ID:</i> (RPID) headers Example: <ul style="list-style-type: none"> <li>• From: &lt;sip:alice@cisco.com&gt;</li> <li>• Remote-Party-ID: &lt;sip:alice@cisco.com&gt;</li> </ul>
<b>Caller name</b> <b>Note</b> If you do not enter a value in the <b>Caller name</b> field, the caller name is <i>Jabber Guest</i> .	Display name of the <i>From:</i> and <i>Remote Party ID:</i> (RPID) headers Example: <ul style="list-style-type: none"> <li>• From: "Alice" &lt;sip:alice@cisco.com&gt;</li> <li>• Remote-Party-ID: "Alice" &lt;sip:alice@cisco.com&gt;</li> </ul>
<b>Append unique identifier to SIP alias</b>	Adds a unique identifier to the <i>From:</i> and <i>Remote Party ID:</i> (RPID) headers Example: <ul style="list-style-type: none"> <li>• From: &lt;sip:alice-123@cisco.com&gt;</li> <li>• Remote-Party-ID: &lt;sip:alice-123@cisco.com&gt;</li> </ul>