Introduction

- Build Number, page 1
- Documentation Resources, page 1
- Features and Enhancements, page 2

Build Number

The build number for this release is `10.5.1.194255`

The DownloadURL file element in the XML file for automatic updates is:
`Cisco-Jabber-Mac-10.5.1.194255-55700621-MC0CFQCa+vqcaLln78ybNLNODwO2TWi7GAIUbQtIsYj1SCYx9zpCe8_+9rxfIZM!.zip`

Note To ensure the DSA signature succeeds, configure Web servers to escape special characters. For example, on Microsoft IIS the option is: **Allow double spacing**.

Documentation Resources

Installation and Configuration Guide

The Installation and Configuration Guide contains information to help you plan your deployment, system, network requirements, supported devices, installation and client configuration.

Server Setup Guide

The Server Setup Guide provides the administrators with task-based information to help you configure services for the client.

DNS Configuration Guide

The DNS Configuration Guide contains information to help you plan your deployment, system, network requirements, supported devices, installation and client configuration.

Licensing Information

The Licensing Information document provides information on the open source libraries used by the application.

Accessibility Guide

Provides information on navigating the client, including shortcut keys, keyboard navigation, and other accessibility features.

Advanced Features Guide

The Advanced Features Guide provides an overview of task-based information about end user operation of the client.

For additional information see the Cisco Jabber for Mac documentation page.

Features and Enhancements

Resolved Caveats

This release provides fixes for a number of known issues. See the Resolved Caveats section for a list of caveats fixed in this release.

New Protocol Handler Parameters

You can configure the following protocol handler parameters in the Policies section of the client configuration file:

Parameter	Value	Description
EnableTELProtocolHandler	true false	Specifies if the client registers as the protocol handler for the `TEL:` URI. **true (default)** The client registers as the protocol handler for the `TEL:` URI. **false** The client does not register as the protocol handler for the `TEL:` URI.

Parameter	Value	Description
EnableIMProtocolHandler	true false	Specifies if the client registers as the protocol handler for the `IM:` URI. **true (default)** The client registers as the protocol handler for the `IM:` URI. **false** The client does not register as the protocol handler for the `IM:` URI.
EnableSIPProtocolHandler	true false	Specifies if the client registers as the protocol handler for the `SIP:` URI. **true (default)** The client registers as the protocol handler for the `SIP:` URI. **false** The client does not register as the protocol handler for the `SIP:` URI.

Features and Enhancements