



Planning Worksheets

You will find a variety of planning worksheets for you to copy and fill in. The worksheets contain a sample entry for the component and then blank rows for you to fill in.

Table B-1 *Interface Card Configuration Parameters*

Name	Type	Slot	Description
en-1	EN	0	Ethernet interface 1

Table B-2 *Ethernet Interface Configuration Parameters*

Name	Card	Description

Table B-8 C7 IP Link Configuration Parameters

MML Parameter Name	Configuration Setting
NAME	ss7lnk1
PORT	7001
IF	EnIf1
PRIORITY	1
PEERADDR	172.24.235.199
IPADDR	IP_Addr1
TIMESLOT	0
SLC	0
LNKSET	lnkset1
DESC	SS7 link 0 for lnkset1 to 2611-1
NEXTHOP	0.0.0.0
NETMASK	255.255.255.255
NAME	
PORT	
IF	
PRIORITY	
PEERADDR	
IPADDR	
TIMESLOT	
SLC	
LNKSET	
DESC	
NEXTHOP	
NETMASK	5

Table B-9 IP-Link Configuration Parameters

MML Parameter Name	Value
NAME	eiplnk1
DESC	sigeisup1
SVC	sigeisup1
IF	EnIf2
IPADDR	IP_Addr_1
PORT	8001
PEERADDR	172.24.235.205
PEERPORT	8001
PRIORITY	1
NEXTHOP	0.0.0.0
NETMASK	255.255.255.255
NAME	
DESC	
SVC	
IF	
IPADDR	
PORT	
PEERADDR	
PEERPORT	
PRIORITY	
NEXTHOP	
NETMASK	
NAME	
DESC	
SVC	
IF	
IPADDR	
PORT	
PEERADDR	
PEERPORT	
PRIORITY	
NEXTHOP	
NETMASK	

Table B-16 Media Gateway Signaling Service Configuration Parameters (continued)

MML Parameter Name	Configuration Setting
SIDE	
CUSTGRPID	
CUSTGRPTBL	
ABFLAG	
CRLEN	
DESC	
PATHSIZE	
PORT	
PEERPORT	
SIGSLOT	
SIGPORT	
SIGPORTSKIP	
BACKUP	

Table B-17 TDM Interface Configuration Parameters

NAME	CARD	Description

Table B-22 IP Link Worksheet Example

Name	Interface	IP Address	Port	Priority	Peer IP Address	Peer Port Field	Service	Description
MGC-Ink1	EnIf1	IP_Addr1	2427	1	175.24.235.155	2427	mgcpsr-1	IP link for MGCP service to Gw1

Table B-23 TDM Interface Configuration Parameters

Card	LIFNum	Resist	Data Rate	Clock	DTE/DCE	Coding	Format	Sig Type	HDLC
card1	1	0	56	EXT	DTE	NA	NA	V.35	HDLC

Table B-24 TDM Link Configuration Parameters

MML Parameter Name	Configuration Setting
DESC	
IF	
NAME	
PRI	
SLC	

Table B-24 TDM Link Configuration Parameters (continued)

MML Parameter Name	Configuration Setting
SVC	
TIMESLOT	

Table B-25 Session Set Parameters

MML Parameter Name	Value
NAME	
IPADDR1	
IPADDR2	
PORT	
PEERADDR1	
PEERADDR2	
PEERPORT	
EXTNODE	

