



About Cisco Unified SRST Manager	
Documentation	See Cisco Unified Survivable Remote Site Telephony .
Hardware Requirements	See Installation and Upgrade Guide for Cisco Unified SRST Manager .
VMware Requirements	VMware ESXi 4.1, 5.0, 5.1 and 5.5

Cisco Unified Communications Manager (CUCM) Compatibility

Cisco Unified SRST Manager Version	CUCM Version				
	8.5	8.6	9.0	10.0	11.0
9.0	Supported	Supported	Supported	Not Supported	Not Supported
9.0.6	Supported	Supported	Supported	Supported	Not Supported
11.0	Not Supported	Not Supported	Supported	Supported	Supported

Cisco Unified Survivable Remote Site Telephony (SRST)/Enhanced SRST (E-SRST) Compatibility

Cisco Unified SRST Manager Version	Cisco Unified SRST Versions						
	8.6	8.8	9.0	9.1	10.0	10.5	11.0
9.0	Supported	Supported	Supported	Supported	Supported	Not Supported	Not Supported
9.0.6	Supported	Supported	Supported	Supported	Supported	Not Supported	Not Supported
11.0	Supported	Supported	Supported	Supported	Supported	Supported	Supported

Supported Platforms and SRST Requirements

Router	Cisco Unified SRST Version	Cisco Unified SRST Manager Version			
		9.0	9.0.4	9.0.6	11.0
Cisco 88x	8.6	Not Supported	Not Supported	Not Supported	Not Supported

Supported Phones

Router	Cisco Unified SRST Version	Cisco Unified SRST Manager Version			
		9.0	9.0.4	9.0.6	11.0
Cisco 1861*	8.6	Supported	Supported	Supported	Supported
Cisco 2801*	8.6	Supported	Supported	Supported	Supported
Cisco 2811*	8.6	Supported	Supported	Supported	Supported
Cisco 2821*	8.6	Supported	Supported	Supported	Supported
Cisco 2851*	8.6	Supported	Supported	Supported	Supported
Cisco 2901	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 2911	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 2921	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 2951	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 3825*	8.6	Supported	Supported	Supported	Supported
Cisco 3845*	8.6	Supported	Supported	Supported	Supported
Cisco 3925	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 3925E	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 3945	8.6 or higher	Supported	Supported	Supported	Supported
Cisco 3945E	8.6 or higher	Supported	Supported	Supported	Supported
Cisco ISR 4321	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported
Cisco ISR 4331	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported
Cisco ISR 4351	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported
Cisco ISR 4431	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported
Cisco ISR 4441	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported
Cisco ISR 4451	8.6 or higher	Not Supported	Not Supported	Not Supported	Supported

- Cisco Unified SRST Version 8.6 is minimum required by Cisco Unified SRST Manager. These platforms do not support later versions of E-SRST/SRST.

Supported Phones

Phone Type	Cisco IOS Version - SCCP	Cisco IOS Version - SIP	Cisco Unified Communications Manager Express Version - SCCP	Cisco Unified Communications Manager Express Version - SIP
7902	15.1(4)M	-	8.6	-
7905	15.1(4)M	15.1(4)M	8.6	8.6
7906	15.1(4)M	15.1(4)M	8.6	8.6

Supported Phones

Phone Type	Cisco IOS Version - SCCP	Cisco IOS Version - SIP	Cisco Unified Communications Manager Express Version - SCCP	Cisco Unified Communications Manager Express Version - SIP
7910	15.1(4)M		-	-
7911	15.1(4)M	15.1(4)M	8.6	8.6
7912	15.1(4)M	15.1(4)M	8.6	8.6
7920	15.1(4)M	15.1(4)M	8.6	8.6
7921	15.1(4)M	15.1(4)M	8.6	8.6
7931	15.1(4)M	15.1(4)M	8.6	8.6
7935	15.1(4)M	15.1(4)M	8.6	8.6
7936	15.1(4)M	15.1(4)M	8.6	8.6
7937	15.1(4)M	15.1(4)M	8.6	8.6
7940	15.1(4)M	15.1(4)M	8.6	8.6
7941	15.1(4)M	15.1(4)M	8.6	8.6
7941GE	15.1(4)M	15.1(4)M	8.6	8.6
7960	15.1(4)M	15.1(4)M	8.6	8.6
7961	15.1(4)M	15.1(4)M	8.6	8.6
7961GE	15.1(4)M	15.1(4)M	8.6	8.6
7970	15.1(4)M	15.1(4)M	8.6	8.6
7971	15.1(4)M	15.1(4)M	8.6	8.6
7985	15.1(4)M	-	8.6	-
7942	15.1(4)M	15.1(4)M	8.6	8.6
7945	15.1(4)M	15.1(4)M	8.6	8.6
7965	15.1(4)M	15.1(4)M	8.6	8.6
7975	15.1(4)M	15.1(4)M	8.6	8.6
7962	15.1(4)M	15.1(4)M	8.6	8.6
6901	15.1(4)M	15.2(2)T	8.6	9
6911	15.1(4)M	15.2(2)T	8.6	9
6921	15.1(4)M	15.2(2)T	8.6	9
6941	15.1(4)M	15.2(2)T	8.6	9

Fasttrack Supported Phones

Phone Type	Cisco IOS Version - SCCP	Cisco IOS Version - SIP	Cisco Unified Communications Manager Express Version - SCCP	Cisco Unified Communications Manager Express Version - SIP
6961	15.1(4)M	15.2(2)T	8.6	9
8961	-	15.1(4)M	-	8.6
9951	-	15.1(4)M	-	8.6
9971	-	15.1(4)M	-	8.6
3905	-	15.2(1)T	-	8.8
6945	15.2(1)T	15.2(2)T	8.8	9
8941	15.2(1)T	15.2(2)T	8.8	9
8945	15.2(1)T	15.2(2)T	8.8	9
CIPC	15.1(4)M	15.1(4)M	8.6	8.6
ATA186	15.1(4)M	-	8.6	-
ATA187	-	15.2(2)T	-	9
7821	-	15.4(3)M	-	10.5
7841	-	15.4(3)M	-	10.5
7861	-	15.4(3)M	-	10.5
8831	-	15.4(3)M	-	10.5
DX650	-	15.4(3)M	-	10.5
Jabber-CSF-Client	-	15.4(3)M	-	10.5

Fasttrack Supported Phones

Cisco Unified SRST Manager supports fasttrack from version 11.0 for SIP phones only. Fasttrack support for SIP phone is introduced in Cisco IOS version 15.3(3)M or Cisco Unified Communications Manager Express 10.0 or Cisco Unified SRST 10.0.

Fast track Use Cases for Cisco Unified SRST Manager Phone Configuration

Phone	Inbuilt support in Cisco IOS	Fast track support in Cisco IOS	Support in Cisco Unified SRST Manager	Cisco Unified SRST Manager configures the Phone
	Yes	Not Applicable	Yes	As usual.
	No	Yes	Yes	In Fast track mode

No	No	No	In Fast track mode with reference of 9971 phone.
----	----	----	--

Fast track Supported Phones

Phone Type	Supported Cisco Unified SRST Manager Version	Fasttrack Support for Cisco Unified Communications Manager Express	Reference Phone Family	Inbuilt Support for Cisco IOS
7811	11.0	CUCME 10.0 (15.3(3)M) onwards	6921	3.17S, 15.6(1)T
7821	11.0	CUCME 10.0 (15.3(3)M) onwards	6921	3.13S, 15.4(3)M
7841	11.0	CUCME 10.0 (15.3(3)M) onwards	6921	3.13S, 15.4(3)M
7861	11.0	CUCME 10.0 (15.3(3)M) onwards	6921	3.13S, 15.4(3)M
8811	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
8831	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
8841	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
8851	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
8851NR	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
8861	11.0	CUCME 10.0 (15.3(3)M) onwards	9971	3.17S, 15.6(1)T
ATA 190	11.0	CUCME 10.0 (15.3(3)M) onwards	ATA 187	3.17S, 15.6(1)T

Supported AXL Versions

Cisco Unified SRST Manager Version	Supported Cisco Unified Communications Manager Version	Supported AXL Version
------------------------------------	--	-----------------------

Supported AXL Versions

9.0.4	9.1, 9.0, and 8.5	7.0.1
9.0.6	10.5, 10.0, 9.1, 9.0, and 8.5	8.5
11.0	11.0, 10.5, 10.0, 9.1, and 9.0	9.0

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Copyright ©2017, Cisco Systems, Inc.

All rights reserved. Printed in USA.