



Release Notes for Cisco Virtualization Experience Media Edition for HP Thin Pro and Ubuntu Release 11.7

First Published: 2016-07-28

Last Modified: 2016-11-02

Release and General Information

These release notes describe new features, requirements, restrictions, and caveats for Cisco Virtualization Experience Media Edition for HP Thin Pro and Ubuntu Release 11.7. These release notes are updated for every maintenance release but not for patches or hot fixes.

Before you install Cisco Virtualization Experience Media Edition, we recommend that you review these release notes for information about issues that may affect your system.

Introduction to Virtualization Experience Media Edition

Cisco Virtualization Experience Media Edition (VXME) extends the Cisco collaboration experience to virtual deployments. With supported versions of Cisco Jabber for Windows, users can send and receive phone calls on their hosted virtual desktops (HVD). The VXME software routes all audio and video streams directly from one thin client to another, or to a phone, without going through the HVD.

For more information about Cisco Jabber, see the *Release Notes for Cisco Jabber for Windows* for your release:

http://www.cisco.com/en/US/products/ps12511/prod_release_notes_list.html

Build Numbers

Release 11.7(1)

The build number for Cisco Virtualization Experience Media Edition Client (VXME Client) for this release is 11.7.1–689.

The build number for Cisco VXME Agent for this release is 11.7.1.715–243387.

Release 11.7

The build number for Cisco Virtualization Experience Media Edition Client (VXME Client) for this release is 11.7.0–676.

The build number for Cisco VXME Agent for this release is 11.7.0.711–239892.

Languages

<ul style="list-style-type: none"> • Arabic • Bulgarian • Catalan • Chinese Simplified • Chinese Traditional • Croatian • Czech • Danish • Dutch • English(US) • Finnish • French • German • Greek • Hebrew • Hungarian 	<ul style="list-style-type: none"> • Italian • Japanese • Korean • Norwegian • Polish • Portuguese Brazil • Portuguese Portugal • Romanian • Russian • Serbian • Slovak • Slovenian • Spanish • Swedish • Thai • Turkish
---	--

Virtualization Experience Media Edition Copyright

Copyright © 2012–2016 Cisco or its affiliated entities. All Rights Reserved.

New in This Release for VXME 11.7

This section describes what is new for Cisco Virtualization Experience Media Edition for Windows (VXME for Windows) Release 11.7.

Cisco Jabber Support

Cisco VXME for HP Thin Pro and Ubuntu supports all Cisco Jabber for Windows features, except the following:

- Binary Floor Control Protocol (BFCP) Desktop Share
- Call Pickup
- Call Stats

- Cisco Unified Survivable Remote Site Telephony (SRST)
- Collaboration Edge
- Device Selection menu on the Call Conversation window
- Far End Camera Control (FECC)
- Federal Information Processing Standard, Publication 140-2 (FIPS 140-2) and Information Assurance (IA) Compliance
- Hunt Group
- Jabber to Jabber Call
- Jabber desk phone video (display of video on the desktop when the thin client is connected to the user's desk phone)
- Kerberos and Common Access Card (CAC) with Single Sign On (SSO)
- PreferP2PDesktopShare (configuration parameter to prioritize person to person screen sharing over video sharing in the Jabber configuration file)
- Accessory Call Control (adjust call volume, answer or end phone calls, and mute audio) for the following accessories
 - Logitech
 - Plantronics
 - Sennheiser

New in This Release for VXME 11.7(1)

Cisco VXME for HP Thin Pro and Ubuntu Release 11.7.1 adds support for the Logitech Webcam model C925e.

Documentation Updates

The following table provides information about changes to this document.

Date	Changes
November 2, 2016	System Requirements, on page 4 —Updated Citrix XenDesktop and Citrix XenApp supported versions for Release 11.7(1).
September 28, 2016	New in This Release for VXME 11.7(1), on page 3 —Added to list what is new for the 11.7(1) maintenance release.
September 28, 2016	Build Numbers, on page 1 —Added build numbers for the 11.7(1) maintenance release.
September 28, 2016	System Requirements, on page 4 —Updated to state that Citrix XenApp Published Application is not supported with VXME for HP Thin Pro and Ubuntu.

Date	Changes
September 28, 2016	Resolved Caveats, on page 10 —Updated to include resolved caveats for the 11.7(1) maintenance release.

System Requirements



Important

Each of the components listed in the following table must meet the requirements. Use of unsupported components can result in a nonfunctional deployment.

Only the components and requirements listed in the table are supported.

Component	Requirements
HP Thin Pro thin clients—Hardware	The following client hardware is supported with HP ThinPro 5.2: <ul style="list-style-type: none"> • HP T610 • HP T620 • HP T730
HP ThinPro platform image	Build number: T6X52011
Ubuntu thin clients—Hardware	The following hardware is supported with Ubuntu 14.04 32b LTS: <ul style="list-style-type: none"> • Installed RAM 2 GB • Free Physical Memory 256 MB • Free Disk Space 256 MB • CPU: AMD G-T56N 1.65GHz, or Intel Core2Duo T7500 2.2 GHz • USB 2.0 for USB camera and audio devices
Hosted virtual desktop OS (server-side)	<ul style="list-style-type: none"> • Microsoft Windows 7 32 bit • Microsoft Windows 7 64 bit • Microsoft Windows 8 32 bit • Microsoft Windows 8 64 bit • Microsoft Windows 8.1 32 bit • Microsoft Windows 8.1 64 bit • Microsoft Windows 10 32 bit • Microsoft Windows 10 64 bit

Component	Requirements
Connection broker for the hosted virtual desktop ¹	<ul style="list-style-type: none"> • Citrix XenDesktop 7.5, 7.6, or 7.7 VXME Release 11.7(1) adds support for XenDesktop versions 7.8 and 7.9. • Citrix XenApp 7.5, 7.6, or 7.7—Published desktops only VXME Release 11.7(1) adds support for XenApp versions 7.8 and 7.9. • VMware Horizon 6.0 (with View)—Published desktops only • VMware Horizon 6 version 6.1.0—Published desktops only • VMware Horizon 6 version 6.2.0—Published desktops only <p>Citrix XenApp Published Application is not supported with VXME for HP Thin Pro and Ubuntu.</p>
Citrix Receiver or VMware Horizon Client ² (Installed on the thin client)	<p>For HP Thin Pro</p> <p>The HP Thin Pro image includes Citrix and VMware:</p> <ul style="list-style-type: none"> • ICA Client : 13.1.2.295815-1 • VMware 3.2.0-2331566 <p>For Ubuntu</p> <ul style="list-style-type: none"> • ICA Client V-13.3.0.344519 • VMware Horizon View Client V-4.0.1-3698616
Cisco Unified Communications client on the hosted virtual desktop <ul style="list-style-type: none"> • Cisco Jabber for Windows 	<p>Cisco Jabber for Windows 11.7 running on the hosted virtual desktop (HVD).</p> <p>Cisco VXME is compatible with all future 11.7(X) Cisco Jabber for Windows versions.</p> <p>For complete information about virtual environment compatibility, see the <i>Virtual Environments</i> section in <i>Installation and Configuration Guide for Cisco Jabber for Windows</i> for your release.</p>

Component	Requirements
Windows Server (Only required for Citrix XenApp)	<p>Citrix XenApp 7.5 or 7.6</p> <ul style="list-style-type: none"> • Microsoft Windows Server 2008 R2 (Standard and Datacenter Editions) • Windows Server 2008 R2 SP1 (Standard, Enterprise, and Datacenter Editions) • Microsoft Windows Server 2012 (Standard and Datacenter Editions) <p>Citrix XenApp 7.7 Microsoft Windows Server 2012 (Standard and Data center Editions)</p>
Cisco Unified Communications Manager	Cisco Unified Communications Manager version 9.x or later
Accessories	<p>For a complete listing of supported audio and video accessories, see <i>Unified Communications Endpoint and Client Accessories</i>, at http://www.cisco.com/c/en/us/products/unified-communications/uc_endpoints_accessories.html.</p> <p>Important Ensure that all Jabra devices are running the latest firmware. You can use Jabra Direct to update the firmware. For more information visit: http://www.jabra.com.</p>

¹ A connection broker is software that creates connections to hosted virtual desktops. A connection broker performs a number of tasks that include

- Validating the username and providing a connection for the user.
- Allowing the user to connect to a specific virtual desktop.

² The Citrix Receiver or VMware Horizon Client provides a user interface for the corresponding connection broker.

Installation and Upgrade Notes

This is the first release of Cisco Virtualization Experience Media Edition for HP Thin Pro and Ubuntu. There is no upgrade path to this release.

Finding Documentation

Provide the following URL for the user documentation to your users:

http://www.cisco.com/en/US/products/ps12862/products_user_guide_list.html

You can place a shortcut on the thin client desktop. You can also add the link to the Citrix landing page or to the VMware Horizon View prelogin banner.

Important Notes

Multiple Registrations

A Client Services Framework (CSF) device user can register with the Cisco Unified Communications Manager from only one client at a time. Multiple registrations from multiple clients with the same CSF device are not supported.

**Note**

Cisco recommends that you create only one CSF device for each user. If multiple devices exist for a virtual user, virtual Jabber automatically selects the first device in the list.

Cisco also recommends that you create only one hosted virtual desktop (HVD) for each user. A user signing in to multiple HVDs and instances of Unified Communications clients results in multiple registrations.

Cisco Audio Session Tunnel

Cisco Audio Session Tunnel (CAST) connection to the HVD is not supported.

Cisco Media Services Interface and Dual VLAN

Cisco Media Services Interface (MSI) and Dual VLAN are not supported for this release.

Citrix Netscaler and Cisco Expressway

Cisco Virtualization Experience Media Edition does not support the use of Mobile Remote Access and Cisco Expressway. For remote access, you require Cisco AnyConnect.

Echo Cancellation

Echo cancellation is enabled only for audio calls.

USB Camera Redirection Not Supported with VMware View

USB camera redirection is not supported with VMware View.

HDX RealTime Webcam with Citrix

Cisco Virtualization Experience Media Edition does not support HDX Plug-n-Play for cameras. Citrix recommends using HDX Webcam for camera interactions.

Silent Monitoring and Call Recording

Cisco Virtualization Experience Media Edition supports silent monitoring and call recording. To enable these audio path functions for a device, you configure Cisco Unified Communications Manager. For step-by-step instructions, see the "Monitoring and Recording" section of the *Cisco Unified Communications Manager Features and Services Guide* for your release.

- Cisco Jabber does not provide any interface to start silent monitoring or call recording. Use the appropriate software to silently monitor or record calls.
- Cisco Jabber does not currently support monitoring notification tone or recording notification tone.
- You can use silent monitoring and call recording functionality only. Cisco Jabber does not support other functionality such as barging or whisper coaching.
- You might need to download and apply a device package to enable monitoring and recording capabilities on the device, depending on your version of Cisco Unified Communications Manager.

Determine Device Package Requirements

Use Cisco Unified Communications Manager Administration to determine whether a device requires a device package to enable silent monitoring and recording.

-
- Step 1** Navigate to and open the **Phone Configuration** window for the device, for which you want to enable monitoring and recording.
- Step 2** Locate the **Built-in-Bridge** field.
If the **Built-in-Bridge** field is not available, download and install a device package for the device.
-

Accessories

Jabra Firmware

Ensure that all Jabra devices are running the latest firmware. You can use Jabra Direct to update the firmware. For more information visit: <http://www.jabra.com>.

Adjust Settings for Jabra Bluetooth Devices

Most Jabra Bluetooth devices introduce a short delay in bringing up the audio path (about 1 to 3 seconds). For supported Jabra Bluetooth devices, you can eliminate the delay by changing the device settings in Jabra Direct. For more information, visit <http://www.jabra.com>.

Before You Begin

Jabra Direct must be installed.

-
- Step 1** Open Jabra Direct.
 - Step 2** Click the Jabra device for which you want to modify the settings.
 - Step 3** Click **Settings**.
 - Step 4** Click to expand **Softphone (PC)**.
 - Step 5** From the **Preferred softphone** list, select **Cisco Jabber**.
 - Step 6** Set **Open phone line** to On.
 - Step 7** Set **PC audio** to Off.
 - Step 8** Click **Apply**.
-

Camera Hot Swap

Cisco Virtualization Experience Media Edition establishes video quality at the start of a call. If you start a call with one of the supported HD cameras, and then switch to a standard-definition camera, video quality is affected. We recommend that you switch cameras between calls.

Caveats

Search for Bugs

Bug Classification

Known defects, or bugs, have a severity level that indicates the priority of the defect. Development managers usually define bug severity. Severity helps the product team focus on bug fixes for future releases and prioritize fixes.

The following table describes bug severity levels:

Severity level		Description
1	Catastrophic	Reasonably common circumstances cause the entire system to fail, or a major subsystem to stop working, or other devices on the network to be disrupted. No workarounds exist.
2	Severe	Important functions are unusable and workarounds do not exist. Other functions and the rest of the network is operating normally.
3	Moderate	Failures occur in unusual circumstances, or minor features do not work at all, or other failures occur but low-impact workarounds exist. This is the highest level for documentation bugs.

Severity level		Description
4	Minor	Failures occur under very unusual circumstances, but operation essentially recovers without intervention. Users do not need to install any workarounds and performance impact is tolerable.
5	Cosmetic	Defects do not cause any detrimental effect on system functionality.
6	Enhancement	Requests for new functionality or feature improvements.

Search for Bugs

Use the **Bug Search** page to obtain more information about a bug.

- 1 Go to <https://tools.cisco.com/bugsearch>.
- 2 Sign in with your Cisco.com user ID and password.
- 3 Enter a bug ID or specify search parameters.

For more information, select **Help** at the top right of the **Bug Search** page.

Open Caveats

The following table lists open caveats (bugs) for this release.

Table 1: Open Caveats for Cisco VXME for HP Thin Pro and Ubuntu Release 11.7

Identifier	Component	Severity	Description
CSCux13238	vxme-core	3	Intermittently no remote video on Jabber while on call

Closed Caveats

There are no closed caveats for this release.

Resolved Caveats

The following table lists caveats (bugs) that are fixed in this maintenance release.

Table 2: Resolved Caveats for Cisco VXME for HP Thin Pro and Ubuntu Release 11.7(1)

Caveat ID Number	Component	Severity	Description
CSCva65977	jabber	2	VXME sending malformed Request URI
CSCva99346	vxme-core	2	Intermittent no video showing on Jabber VXME on multi-point video call

Caveat ID Number	Component	Severity	Description
CSCva85830	vxme-core	4	If VXME is not running Jabber phone icon should not become registered
CSCvb19617	jabber	4	Video turns black if you popout window and switch to fullscreen and back

Release 11.7 is the first release for VXME for HP Thin Pro and Ubuntu. There are no resolved caveats for this release.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <http://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2016 Cisco Systems, Inc. All rights reserved.