



About Cisco Mobility Express

- [Overview of Cisco Mobility Express, on page 1](#)
- [Supported Cisco Access Points, on page 1](#)
- [Supported Software Images, on page 2](#)

Overview of Cisco Mobility Express

The Cisco Mobility Express wireless network solution comprises of at least one 802.11ac Wave 2 Cisco Aironet Series access point (AP) with an in-built software-based wireless controller managing other APs in the network.

The AP acting as the controller is referred to as the primary AP while the other APs in the Cisco Mobility Express network, which are managed by this primary AP, are referred to as subordinate APs.

In addition to acting as a controller, the primary AP also operates as an AP to serve clients along with the subordinate APs.

Cisco Mobility Express provides most features of a Cisco wireless controller and has the capability to interface with the following:

- Cisco Prime Infrastructure—For simplified network management, including managing AP groups
- Cisco Identity Services Engine—For advanced policy enforcement
- Connected Mobile Experiences (CMX)—For providing presence analytics and guest access using Connect & Engage

Supported Cisco Access Points

The following Cisco Aironet Series APs are supported in the Cisco Mobility Express network:



Note

- APs listed under primary APs can also function as subordinate APs.
 - The software on the APs listed under primary APs can be converted from Cisco Mobility Express to CAPWAP Lightweight AP software and vice versa. For ordering information, visit the [Cisco Aironet Access Points Ordering Guide](#)
-

Table 1: Cisco APs Supported in Cisco Mobility Express

Primary APs	Subordinate APs
Cisco Aironet 1540 Series	Cisco Catalyst 9100 Series
Cisco Aironet 1560 Series	<ul style="list-style-type: none"> • Cisco Catalyst 9105AX Series • Cisco Catalyst 9115AX Series • Cisco Catalyst 9117AX Series • Cisco Catalyst 9120AX Series • Cisco Catalyst 9130AX Series
Cisco Aironet 1815i	Cisco Aironet 1540 Series
Cisco Aironet 1815w	Cisco Aironet 1560 Series
Cisco Aironet 1830 Series	Cisco Aironet 700i Series
Cisco Aironet 1850 Series	Cisco Aironet 700w Series
Cisco Aironet 2800 Series	Cisco Aironet 1600 Series
Cisco Aironet 3800 Series	Cisco Aironet 1700 Series
	Cisco Aironet 1810W Series
	Cisco Aironet 1810I Series
	Cisco Aironet 1810M Series
	Cisco Aironet 1830 Series
	Cisco Aironet 1850 Series
	Cisco Aironet 2600 Series
	Cisco Aironet 2700 Series
	Cisco Aironet 2800 Series
	Cisco Aironet 3500 Series
	Cisco Aironet 3700 Series
	Cisco Aironet 3800 Series

Supported Software Images

AP models that are supported as primary can be ordered with either of the following as the default factory-shipped software:

- A Cisco Mobility Express software image. These models have model numbers (or Product IDs) ending in *C*.
- A lightweight AP software image, based on the Control and Provisioning of Wireless Access Points (CAPWAP) protocol, for joining a wireless controller. You can manually convert these models on site to have a Cisco Mobility Express software image. For information about this conversion, see [Converting from CAPWAP Lightweight AP to Cisco Mobility Express Software](#).

AP models that are supported only as subordinates require a CAPWAP-based lightweight AP software image.

The Cisco Mobility Express software for your AP model can be downloaded from: <https://software.cisco.com/download/navigator.html>.

From the **Download Software** window, browse to your AP model and then select **Mobility Express Software** to view a list of currently available software, with the latest the top. The software releases are labeled as follows to help you determine which release to download:

- Early Deployment (ED)—These software releases provide new features, new hardware platform support, and bug fixes.
- Maintenance Deployment (MD)—These software releases provide bug fixes and ongoing software maintenance.
- Deferred (DF)—These software releases have been deferred. We recommend that you migrate to an upgraded release.

