



ACS QoS-Group-of-Ruledefs Configuration Mode Commands

The ACS QoS-Group-of-Ruledefs Configuration Mode is used to configure groups of rule definitions (ruledefs).

Command Modes

Exec > ACS Configuration > QoS-Group-of-Ruledefs Configuration

active-charging service *service_name* > **qos-group-of-ruledefs** *group_name*

Entering the above command sequence results in the following prompt:

```
[local] host_name(config-qos-group-of-ruledefs) #
```



Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [add-group-of-ruledef, on page 1](#)
- [add-ruledef, on page 2](#)
- [end, on page 3](#)
- [exit, on page 3](#)

add-group-of-ruledef

This command allows you to add or remove groups-of-ruledefs from a qos-group-of-ruledefs.

Product

ACS

Privilege

Security Administrator, Administrator

Command Modes

Exec > ACS Configuration > QoS-Group-of-Ruledefs Configuration

active-charging service *service_name* > **qos-group-of-ruledefs** *group_name*

Entering the above command sequence results in the following prompt:

```
[local] host_name(config-qos-group-of-ruledefs) #
```

Syntax Description

[no] **add-group-of-ruledef** *group_of_ruledef_name*

no

If added previously, removes the specified group-of-ruledef from the current qos-group-of-ruledefs.

group_of_ruledef_name

Specifies name of the group-of-ruledef to add/remove from the current qos-group-of-ruledefs.

group_of_ruledef_name must be the name of an ACS group-of-ruledef, and must be an alphanumeric string of 1 through 63 characters.

Usage Guidelines

Use this command to add/remove a group-of-ruledefs from a qos-group-of-ruledefs.

Example

The following command adds the group-of-ruledef named *grpruledef1* to the current qos-group-of-ruledefs:

```
add-group-of-ruledef grpruledef1
```

add-ruledef

This command allows you to add or remove ruledefs from a qos-group-of-ruledefs.

Product

ACS

Privilege

Security Administrator, Administrator

Command Modes

Exec > ACS Configuration > QoS-Group-of-Ruledefs Configuration

active-charging service *service_name* > **qos-group-of-ruledefs** *group_name*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-qos-group-of-ruledefs)#
```

Syntax Description

[**no**] **add-ruledef** *ruledef_name*

no

If added previously, removes the specified ruledef from the current qos-group-of-ruledefs.

ruledef_name

Specifies name of the ruledef to add/remove from the current qos-group-of-ruledefs.

ruledef_name must be the name of an ACS ruledef, and must be an alpha and/or numeric string of 1 through 63 characters.

Usage Guidelines

Use this command to add/remove ruledefs from a qos-group-of-ruledefs.

Example

The following command adds the ruledef *ruledef23* to the current qos-group-of-ruledefs:

```
add-ruledef ruledef23
```

end

Exits the current configuration mode and returns to the Exec mode.

| | |
|---------------------------|--|
| Product | All |
| Privilege | Security Administrator, Administrator |
| Syntax Description | end |
| Usage Guidelines | Use this command to return to the Exec mode. |

exit

Exits the current mode and returns to the parent configuration mode.

| | |
|---------------------------|--|
| Product | All |
| Privilege | Security Administrator, Administrator |
| Syntax Description | exit |
| Usage Guidelines | Use this command to return to the parent configuration mode. |

■ exit