



## Feature Defaults Quick Reference

- [Feature Defaults Quick Reference](#), on page 1

## Feature Defaults Quick Reference

The following table indicates what features are enabled or disabled by default.

Feature	Default
5G capable SPGW Selection by MME	Enabled - Always-on
Access Restriction Support on S6d Interface	Disabled - Configuration Required
Cell Broadcast Center - SBc Interface	Enabled - Configuration Required
Collision Handling for Path-Update during Bearer Creation	Enabled - Always-on
Configuration of UE Radio Capability IE Size	Enabled - Configuration Required
Counters for Reason 50/51 on MME and TAI	Enabled - Always-on
Deprecated IPSec/IKEv2 Algorithms Support	Enabled - Always-on
Deprecation of Manual Scaling	Disabled - Configuration Required
Delay Value IE Support in MME	Enabled - Configuration Required
Discontinuation of ORBEM Configuration Support	Enabled - Always-on
ERAB Setup Retry Handling	Disabled - Configuration Required
ESC, UEM and VNF Upgrade Support on VMware VCD	Disabled - Configuration required
Excluding SGWs During Relocation Procedures	Enabled - Always-on
GM Manager Queue Handling	Disabled – Configuration Required
Handling of APN Configuration in ISDR from HSS	Enabled – Always-on
Handling Temporary Failure During UBR-MBC Collision	Disabled-Configuration Required

Feature	Default
Handling the TAU and Location Update Request/Response	Enabled - Always-on
IPv6 MTU Option Support in RA Message Enhancement	Enabled - Always-on
Mapped-UE-Usage-Type IE Support in MME	Disabled - Configuration Required
MEC Location Management Support	Enabled - Always-on
MME Handling of Purge Procedure	Enabled - Configuration Required
MME-MS/VLR SGs Disconnect	Enabled – Configuration Required
MME Manager Status Traps	Enabled - Always-on
MME Support for Service Impacting KPI Bulk Statistics	Enabled - Always-on
Monitor Protocol Support for DCNR	Enabled - Always-on
NB-IOT EDRX Supported values in ATTACH/TAU Accept	Enabled - Configuration Required
NETCONF Event Notification Support for Auto-scaleout	Disabled – Configuration Required <b>Note</b> This feature is dependent on the existing Automatic Scale-out feature.
Network Access Identifier Field Removal from MSISDN	Enabled - Always-on
NFVO-based Deployment of UGP VNF	Disabled - Configuration required
OWM Integra Deployment Automation on VMware VCD	Disabled - Configuration required
Paging eDRX H-SFN Changed to 10 Bits Counter	This feature is enabled/disabled, when the eDRX feature is enabled/disabled.
RAB Release for Attach on the Same IU Connection	Disabled - Configuration Required
Service Impacting SGSN KPI Bulk Statistics	Enabled - Always-on
SRVCC Delete Bearer Request Handling	Disabled – Configuration Required
SRVCC HO Timer Configuration for ESM Notification	Enabled – Configuration Required
Support for Password ExpiryWarning	Enabled - Always-on
Target MME Load Balancing During Handover in MME	Enabled - Always-on