



# Handling of APN Configuration in ISDR from HSS

- [Feature Summary and Revision History, on page 1](#)
- [Feature Changes, on page 1](#)

## Feature Summary and Revision History

### Summary Data

Applicable Product(s) or Functional Area	MME
Applicable Platform(s)	<ul style="list-style-type: none"> <li>• ASR 5500</li> <li>• VPC-DI</li> <li>• VPC-SI</li> </ul>
Feature Default	Enabled – Always-on
Related Changes in This Release	Not applicable
Related Documentation	<i>MME Administration Guide</i>

### Revision History

Revision Details	Release
Handling of APN Configuration in ISDR from HSS support added.	12.12.15
Handling of APN Configuration in ISDR from HSS support added.	21.11.9
First introduced.	21.5.19

## Feature Changes

APN configuration handling received in HSS ISDR message is modified in compliance with 3GPP TS 29.272.

**Previous Behavior:** If All APN configurations included indicator value is set to "MODIFIED/ADDED\_APN\_CONFIGURATIONS\_INCLUDED" then the APN configuration data is merged in the MME DB record.

**New Behavior:** If all APN configurations include indicator value is set to "MODIFIED/ADDED\_APN\_CONFIGURATIONS\_INCLUDED" then the APN configuration data is replaced in the MME DB record.