



# Network Access Identifier Field Removal from MSISDN

- [Feature Summary and Revision History, on page 1](#)
- [Feature Changes, on page 2](#)

## Feature Summary and Revision History

### Summary Data

Applicable Product(s) or Functional Area	P-GW
Applicable Platform(s)	<ul style="list-style-type: none"><li>• ASR 5500</li><li>• VPC-DI</li><li>• VPC-SI</li></ul>
Feature Default	Enabled - Always-on
Related Changes in This Release	Not Applicable
Related Documentation	Not Applicable

### Revision History



#### Important

Revision history details are not provided for features introduced before releases 21.2 and N5.1.

Revision Details	Release
The change in behavior is also applicable to this release.	21.12.12
With this release, the P-GW does not add an extra character "19", that is Network Access Identifier (NAI) field in MSISDN, which is sent in Protocol Configuration Option (PCO) IE in CSRsp message.	21.13

Revision Details	Release
First introduced.	Pre 21.2

## Feature Changes

**Previous Behavior:** When MSISDN was sent in PCO in Create Session Response (CSRsp), the P-GW added an extra character "19" in MSISDN that was present in PCO.

**New Behavior:** While sending MSISDN in PCO in CSRsp, the P-GW does not send NAI, that is to say, the extra character "19".

**Customer Impact:** None