



show administrators

This chapter includes the **show administrators** command output tables.

- [show administrators, on page 1](#)
- [show administrators session id, on page 2](#)

show administrators

Table 1: show administrators Command Output Descriptions

| Field | Description |
|-----------------------------|--|
| Administrator/Operator Name | Displays the name of the administrative user currently accessing the system. |
| M | The M (Lock Mode) characters are defined as follows: <ul style="list-style-type: none">• [blank] – Administrator is in Exec mode• c – Administrator session is currently in Config Mode (shared-lock)• s – Administrator session is currently saving the config• f – Administrator session is currently loading the config file• L – Administrator session is currently in Config Mode with the exclusive-lock |
| Type | Displays the administrative user's type: <ul style="list-style-type: none">• admin = Security Administrator• cfgadm = Administrator• inspect = Inspector• oper = Operator |
| TTY | Displays a reference for the virtual console device for the CLI instance. |

| Field | Description |
|------------|--|
| Start Time | Displays the time and date that the administrative user's session started. |

show administrators session id

Table 2: show administrators session id Command Output Descriptions

| Field | Description |
|-----------------------------|---|
| Administrator/Operator Name | Displays the name of the administrative user currently accessing the system. |
| M | <p>The M (Lock Mode) characters are defined as follows:</p> <ul style="list-style-type: none"> • [blank] – Administrator is in Exec mode • c – Administrator session is currently in Config Mode (shared-lock) • s – Administrator session is currently saving the config • f – Administrator session is currently loading the config file • L – Administrator session is currently in Config Mode with the exclusive-lock |
| Login Context | Displays the context in which the CLI user is working. |
| Remote Addr | Displays the IP address from which the CLI user is accessing the system. |
| Session ID | Displays the assigned session ID. |
| Mode | <p>Displays the user's value:</p> <ul style="list-style-type: none"> • TACACS+ User • Local User • Context User |
| Idle | The total number of sessions currently idle in seconds. |