



# ACS Group-of-Prefixed-URLs Configuration Mode Commands



## Important

This configuration mode is customer specific. For more information, contact your Cisco account representative.

## Command Modes

The ACS Group-of-Prefixed-URLs Configuration Mode is used to create and configure groups of prefixed URLs.

Exec > ACS Configuration > ACS Group-of-Prefixed-URLs Configuration

**active-charging service** *service\_name* > **group-of-prefixed-urls** *group\_name*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-acs-grp-of-prefixed-urls)#
```



## Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [end, on page 1](#)
- [exit, on page 2](#)
- [prefixed-url, on page 2](#)

## end

Exits the current configuration mode and returns to the Exec mode.

## Product

All

## Privilege

Security Administrator, Administrator

## Syntax Description

**end**

## Usage Guidelines

Use this command to return to the Exec mode.

## exit

Exits the current mode and returns to the parent configuration mode.

<b>Product</b>	All
<b>Privilege</b>	Security Administrator, Administrator
<b>Syntax Description</b>	<b>exit</b>
<b>Usage Guidelines</b>	Use this command to return to the parent configuration mode.

## prefixed-url

This command allows you to add or remove URLs from the current group of prefixed URLs.



**Important** A maximum of 10 URLs can be added per group.

<b>Product</b>	ACS
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > ACS Configuration > ACS Group-of-Prefixed-URLs Configuration <b>active-charging service</b> <i>service_name</i> > <b>group-of-prefixed-urls</b> <i>group_name</i> Entering the above command sequence results in the following prompt: <pre>[local]host_name(config-acs-grp-of-prefixed-urls)#</pre>
<b>Syntax Description</b>	<b>[ no ] prefixed-url url</b>  <b>no</b> If added previously, removes the specified URL from the current group of prefixed URLs.  <b>url</b> Specifies the URL to add/remove. <i>url</i> must be an alphanumeric string of 1 through 63 characters.
<b>Usage Guidelines</b>	Use this command to add or remove URLs to be filtered from the group of prefixed URLs.

### Example

The following command adds the URL *http://abc.net* to the current group of prefixed URLs:

```
prefixed-url http://abc.net
```