



PVC Interface Configuration Mode Commands

Command Modes

The PVC (permanent virtual connection) Interface configuration mode is used to create and manage the IP parameters for PVC interface(s) associated with an OLC (ATM-type) for a specific context.

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```



Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [description, on page 2](#)
- [do show, on page 2](#)
- [end, on page 3](#)
- [exit, on page 3](#)
- [ip, on page 3](#)
- [ip access-group, on page 4](#)
- [ip address, on page 5](#)
- [ip mtu, on page 6](#)
- [ip ospf authentication-key, on page 6](#)
- [ip ospf authentication-type, on page 7](#)
- [ip ospf cost, on page 8](#)
- [ip ospf dead-interval, on page 9](#)
- [ip ospf hello-interval, on page 10](#)
- [ip ospf message-digest-key, on page 10](#)
- [ip ospf network, on page 11](#)
- [ip ospf priority, on page 12](#)
- [ip ospf retransmit-interval, on page 13](#)
- [ip ospf transmit-delay, on page 14](#)

description

Defines descriptive text to provide useful information about the current interface.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > **context** *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

description *text*
no description

no

Erases the port's description from the configuration file.

text

text: Must be a string of 1 to 79 alphanumeric characters with no spaces or a string within double quotes that includes printable characters. The description is case-sensitive.

Usage Guidelines

Set the description to provide helpful information, for example the port's primary function, services, end users. Define any information, the only limit is the number of characters, 79.

Example

```
description "PVC12 connects server 1 to home office."
```

do show

Executes all **show** commands while in Configuration mode.

Product

All

Privilege

Security Administrator, Administrator

Syntax Description

do show

Usage Guidelines

Use this command to run all Exec mode **show** commands while in Configuration mode. It is not necessary to exit the Config mode to run a **show** command.

The pipe character | is only available if the command is valid in the Exec mode.

**Caution**

There are some Exec mode **show** commands which are too resource intensive to run from Config mode. These include: **do show support collection**, **do show support details**, **do show support record** and **do show support summary**. If there is a restriction on a specific **show** command, the following error message is displayed:

```
Failure: Cannot execute 'do show support' command from Config mode.
```

end

Exits the PVC interface configuration mode and returns to the Exec mode.

Product

SGSN

Privilege

Security Administrator, Administrator

Syntax Description**end****Usage Guidelines**

Change the mode back to the Exec mode.

exit

Exits the interface configuration mode and returns to the context configuration mode.

Product

SGSN

Privilege

Security Administrator, Administrator

Syntax Description**exit****Usage Guidelines**

Return to the context configuration mode.

ip

The commands in this section are used to configure the IP parameters for the PVC interface.

**Important**

Before configuring the OSPF parameters in this section, you need to enable OSPF using the router command and OSPF configuration sub-mode commands accessed in the Context configuration mode and documented in the Context Configuration Mode chapter of this Command Line Interface Reference.

ip access-group

This command identifies the access control list (ACL) to be associated with this PVC interface in this context.



Important

Prior to using this command, the access list must be created for this context with the **ip access-list** command in the Context configuration mode and then the ACL must be configured using the commands described in CLI chapter ACL Configuration Mode.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > **context** *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

ip access-group *name* { **in** | **out** }
no ip access-group *name* { **in** | **out** }

no

Indicates the specified access group to be removed from the access list.

name

Specifies the access control list (ACL) rule to be added or removed from the group.

name: Must be a string of 1 to 79 alphanumeric characters with no spaces.



Important

Up to 8 ACLs can be applied to a group provided that the number of rules configured within the ACL(s) does not exceed the 128 rule limit for the interface.

in | out

in: Specifies list is for in-bound access control.

out: Specifies the list is for out-bound access control.



Important

Even though "in" or "out" can be specified, context-level ACL rules are automatically applied to both directions.

Usage Guidelines

Use this command to add IP access lists configured for the same context to an IP access-group. The list can be configured to apply to all inbound and/or outbound traffic.

Example

The following adds ACL access-list-1 to the IP access-group associated with this PVC for this context.

```
ip access-group access-list-1 in
```

ip address

Defines the primary IP address and the network mask to be associated with this PVC interface for this context. This command can also be used to configure the secondary IP address.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

```
ip address ip_address ip_mask [ secondary ]
no ip address ip_address
```

no

Removes the IP address information for this PVC from the configuration. It is not necessary to include the subnet mask with the command.

The command must first be issued with the secondary IP address if one exists and then re-issued with the primary IP address.

address *ip_address ip_mask*

Configures the IP address and the network mask for this PVC interface. The first time this command is entered, it automatically defines the primary IP address for this interface.

ip_address and *ip_mask* must be specified using the standard IPv4 or IPv6 dotted decimal notation.

secondary

secondary: Including this keyword indicates the IP address and subnet mask being defined are to be used as the secondary IP address for this PVC interface. This is referred to as multi-homing of the interface.

Usage Guidelines

Configures or deletes the IPv4 or IPv6 addresses and subnet mask to be associated with this PVC.

Example

The following configures the secondary IP address to associate with the interface.

```
ip address 131.2.3.4 255.255.255.0 secondary
```

The following set of commands removes the primary IP address from the PVC interface configuration for this context.

```
no ip address secondary address
no ip address primary address
```

ip mtu

Configures the maximum transmission unit (MTU) to be supported on this interface.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

```
ip mtu value
no ip mtu
```

no

Disables and/or restores the option to the system default.

mtu value

Configures the maximum transmission unit in octets.

value: Enter an integer between 576 and 1600. Default is 1500.

Usage Guidelines

Change the maximum transmission unit size to 1300.

Example

```
ip mtu 1300
```

ip ospf authentication-key

This command configures the password or key to be used for OSPF (Open Shortest Path First) authentication with neighboring routers.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```

Syntax Description

ip ospf authentication-key [**encrypted**] **password** *auth_key*
no ip ospf authentication-key

no

Deletes the authentication key.

encrypted

Enter this keyword if you are pasting a previously encrypted authentication key into the **password** *auth_key* for this command.

password*auth_key*

auth_key is a string variable, from 1 through 16 alphanumeric characters, that denotes the authentication key (password). This variable is entered in clear text format.

Usage Guidelines

Use this command to set the authentication key used when authenticating with neighboring routers.

Example

To set the authentication key to 123abc, use the following command;

```
ip ospf authentication-key password 123abc
```

Use the following command to delete the authentication key;

```
no ip ospf authentication-key
```

ip ospf authentication-type

This command configures the OSPF authentication method to be used with OSPF neighbors over the logical interface.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```

Syntax Description

```
ip ospf authentication-type { message-digest | null | text }
no ip ospf authentication-type { message-digest | null | text }
```

no

Disable this function.

message-digest

Set the OSPF authentication type to use the message digest (MD) authentication method.

null

Set the OSPF authentication type to use no authentication, thus disabling either MD or clear text methods.

text

Set the OSPF authentication type to use the clear text authentication method.

Usage Guidelines

Use this command to set the type of authentication to use when authenticating with neighboring routers.

Example

To set the authentication type to use clear text, enter the following command;

```
ip ospf authentication-type text
```

ip ospf cost

This command configures the cost associated with sending a packet over this logical interface.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

```
configure > context context_name > interface interface_name point-to-point
```

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

```
ip ospf cost value
no ip ospf cost
```

no

Disable this function.

value

Default: 10

The cost to assign to OSPF packets. This must be an integer from 1 through 65535.

Usage Guidelines

Use this command to set the cost associated with routes from the interface.

Example

Use the following command to set the cost to 20;

```
ip ospf cost 20
```

Use the following command to disable the cost setting;

```
no ip ospf cost
```

ip ospf dead-interval

This command configures the dead-interval and the delay time in seconds, for OSPF communications.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```

Syntax Description

```
ip ospf dead-interval value
no ip ospf dead-interval
```

no

Deletes the value set and returns the value to its default.

value

The interval, in seconds, that the router should wait. During this interval, if no packets are received then the system considers the neighboring router to be off-line. This interval is typically 4 times the duration of the hello-interval.

value must be an integer from 1 through 65535. Default: 40

Usage Guidelines

Use this command to set the dead-intervals or delays for OSPF communications.

Example

To set the dead-interval to 100, use the following command;

```
ip ospf dead-interval 100
```

To delete the setting for the dead-interval and reset the dead-interval value to its default of 40, use the following command'

```
no ip ospf dead-interval
```

ip ospf hello-interval

This command configures the delay time in seconds, for OSPF hello interval.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

```
ip ospf hello-interval value  
no ip ospf hello-interval
```

no

Deletes the value set and returns the value to its default.

value

The interval, in seconds, between sending hello packets. This value is typically set to be 1/4 of the value of the **dead-interval**.

value must be an integer from 1 through 65535. Default: 10

Usage Guidelines

Use this command to set the delays for the hello-interval.

Example

To set the hello-interval to 25, use the following command;

```
ip ospf hello-interval 25
```

To delete the setting for the hello-interval and reset the hello-interval value to its default of 10, use the following command'

```
no ip ospf hello-interval
```

ip ospf message-digest-key

This command enables the use of MD5-based OSPF authentication.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > Context Configuration > PVC Interface Configuration configure > context <i>context_name</i> > interface <i>interface_name</i> point-to-point Entering the above command sequence results in the following prompt: <pre>[context_name]host_name(config-if-pvc) #</pre>
Syntax Description	<p>ip ospf message-digest-key <i>key_id</i> md5 [encrypted] password <i>authentication_key</i> no ip ospfmessage-digest-key <i>key_id</i></p> <p>no</p> <p>Deletes the key.</p> <p>message-digest-key <i>key_id</i></p> <p>Specifies the key identifier number. <i>key_id</i> must be an integer from 1 through 255.</p> <p>encrypted</p> <p>Use this if you are pasting a previously encrypted authentication key into the CLI command.</p> <p>password <i>authentication_key</i></p> <p>The password to use for authentication. <i>authentication_key</i> is a string variable, from 1 through 16 alphanumeric characters, that denotes the authentication password. This variable is entered in clear text format.</p>
Usage Guidelines	Use this command to create an authentication key that uses MD5-based OSPF authentication.
Example	<p>To create a key with the ID of 25 and a password of 123abc, use the following command;</p> <pre>ip ospf message-digest-key 25 md5 password 123abc</pre> <p>To delete the same key, enter the following command;</p> <pre>no ip ospf message-digest-key 25</pre>

ip ospf network

Configures the OSPF network type.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > interface *interface_name* point-to-point

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description

```
ip ospf network { broadcast | non-broadcast | point-to-multipoint |  
point-to-point }  
no ip ospf network
```

no

Disable this function.

broadcast

Sets the network type to broadcast.

non-broadcast

Sets the network type to non-broadcast multi access (NBMA).

point-to-multipoint

Sets the network type to point-to-multipoint.

point-to-point

Sets the network type to point-to-point.

Usage Guidelines

Use this command to specify the OSPF network type.

Example

To set the OSPF network type to broadcast, enter the following command;

```
ip ospf network broadcast
```

To disable the OSPF network type, enter the following command;

```
no ip ospf network
```

ip ospf priority

This command designates the OSPF router priority.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > interface *interface_name* point-to-point

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```

Syntax Description

ip ospf priority *value*
no ip ospf priority *value*

no

Disable this function.

value

The priority value to assign. This must be an integer from 0 through 255.

Usage Guidelines

Use this command to set the OSPF router priority.

Example

To set the priority to 25, enter the following command:

```
ip ospf priority 25
```

To disable the priority, enter the following command:

```
no ip ospf priority
```

ip ospf retransmit-interval

This command configures the retransmit-interval and the delay time in seconds, for OSPF communications.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > **interface** *interface_name* **point-to-point**

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc) #
```

Syntax Description

ip ospf dead-interval *value*
no ip ospf dead-interval

no

Deletes the value set and returns the value to its default.

value

The interval, in seconds, between LSA (Link State Advertisement) retransmissions.

value must be an integer from 1 through 65535. Default: 5

Usage Guidelines Use this command to set the retransmit-intervals or delays for OSPF communications.

Example

To set the dead-interval to 25, use the following command;

```
ip ospf retransmit-interval 25
```

ip ospf transmit-delay

This command configures the transmit-delay the OSPF communications parameters.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > Context Configuration > PVC Interface Configuration

configure > context *context_name* > interface *interface_name* point-to-point

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-if-pvc)#
```

Syntax Description **ip ospf transmit-delay *value***
no ip ospf transmit-delay

no

Deletes the value set and returns the value to its default.

transmit-delay *value*

The interval, in seconds, that the router should wait before transmitting a packet.

value must be an integer from 1 through 65535. Default: 1

Usage Guidelines Use this command to set the transmit-delay.

Example

To set the transmit delay to 5 seconds, use the following command;

```
ip ospf transmit-delay 5
```

To delete the setting for the transmit-delay or reset the transmit-delay value to its default of 1, use the following command'

```
no ip ospf transmit-delay
```