



# ACS Group-of-Objects Configuration Mode Commands

The ACS Group-of-Objects Configuration Mode is used to configure groups of Active Charging Service (ACS) objects.

  
**Important**

This configuration mode is available only in 10.2 and later releases.

## Command Modes

Exec > ACS Configuration > ACS Group-of-Objects Configuration  
**active-charging service** *service\_name* > **group-of-objects** *object\_name* [ **type string** ]  
Entering the above command sequence results in the following prompt:  
`[local]host_name(config-acs-group-of-objects) #`

  
**Important**

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [end, on page 1](#)
- [exit, on page 2](#)
- [member-object, on page 2](#)

## end

Exits the current configuration mode and returns to the Exec mode.

### Product

All

### Privilege

Security Administrator, Administrator

### Syntax Description

**end**

### Usage Guidelines

Use this command to return to the Exec mode.

# exit

Exits the current mode and returns to the parent configuration mode.

Product	All
Privilege	Security Administrator, Administrator
Syntax Description	<code>exit</code>
Usage Guidelines	Use this command to return to the parent configuration mode.

# member-object

This command allows you to add or remove objects from the current group-of-objects.



**Important** A maximum of 128 objects can be added to a group-of-objects.

Product	ACS
Privilege	Security Administrator, Administrator
Command Modes	<p>Exec &gt; ACS Configuration &gt; ACS Group-of-Objects Configuration</p> <p><b>active-charging service</b> <i>service_name</i> &gt; <b>group-of-objects</b> <i>object_name</i> [ <b>type string</b> ]</p> <p>Entering the above command sequence results in the following prompt:</p> <pre>[local]host_name(config-acs-group-of-objects)#</pre>
Syntax Description	<p>[ <b>no</b> ] <b>member-object</b> <i>object</i></p> <p><b>no</b></p> <p>If previously added, removes the specified member object from the current group-of-objects.</p> <p><b>object</b></p> <p>Specifies the member object to add to or remove from the current group-of-objects.</p> <p><i>object</i> must be an alpha and/or numeric string of 1 through 63 characters.</p>
Usage Guidelines	Use this command to add or remove member objects from a group-of-objects.

## Example

The following command adds the object *test* to the current group-of-objects:

```
member-object test
```