



IPv4/IPv6 Address Encoding Change in Flow-Description AVP for APPLICATION-START Event Trigger from P-GW

- [Feature Summary and Revision History, on page 1](#)
- [Feature Changes, on page 2](#)

Feature Summary and Revision History

Summary Data

Applicable Product(s) or Functional Area	P-GW
Applicable Platform(s)	<ul style="list-style-type: none"> • ASR 5500 • VPC-DI • VPC-SI
Feature Default	Enabled-Always on
Related Changes in This Release	Not Applicable
Related Documentation	<i>P-GW Administration Guide</i>

Revision History

Revision Details	Release
The P-GW supports IPv4/IPv6 address encoding change in Flow-Description AVP under Application-Detection-Information AVP for APPLICATION-START event trigger.	21.18.25
The StarOS 21.15.52 is enhanced with IPv4/IPv6 address encoding change in Flow-Description AVP under Application-Detection-Information AVP for APPLICATION-START event trigger from P-GW.	21.15.52

Feature Changes

Previous Behavior: In CCR-U for APPLICATION-START event trigger from P-GW, Flow-Description AVP under Application-Detection-Information AVP towards PCRF was encoded as:

- For ipv4 flows a netmask of /0 was used
- For ipv6 flows prefix length of 0 was used

New Behavior: In CCR-U for APPLICATION-START event trigger from P-GW, Flow-Description AVP under Application-Detection-Information AVP towards PCRF is encoded as:

- For ipv4 flows a netmask of /32 is used
- For ipv6 flows prefix length of 128 is used

Customer Impact: PCRF receives flow description value with 32/128 netmask/prefix. If PCRF rejects the value, ADC over Gx will not work.