



Support for 3gpp IKEv2 Private Notify Error Types

This chapter describes the following topics:

- [Feature Summary and Revision History](#), on page 1
- [Feature Description](#), on page 2
- [Configuring Support for 3GPP IKEv2 Private Notify Error Types](#), on page 3
- [Monitoring and Troubleshooting](#), on page 4

Feature Summary and Revision History

Summary Data

| | |
|--|--|
| Applicable Product(s) or Functional Area | ePDG |
| Applicable Platform(s) | <ul style="list-style-type: none">• ASR 5500• VPC-DI• VPC-SI |
| Feature Default | Disabled – Configuration Required |
| Related Changes in This Release | Not applicable |
| Related Documentation | <ul style="list-style-type: none">• <i>ePDG Administration Guide</i>• <i>Command Line Interface Reference</i> |

Revision History

| Revision Details | Release |
|-------------------|---------|
| First introduced. | 21.5.5 |

Feature Description

ePDG treats every error returned on S2b from P-GW in the same way and translates to "Internal Address Failure", ePDG also treats SWM from AAA in the same way and translates it to "AUTH Fail" towards UE. This feature translates the errors received on the S2b from the P-GW and SWm from the AAA into 3GPP defined errors on the SWu interface.

A new backoff timer notify payload is introduced to restrict the UE from retrying immediately after certain permanent errors as defined in 3GPP. New CLI command is introduced to control, enable/disable the back off timer value.

Table 1: SWm to SWu Error Mapping Table

| Notify Message | Value | Descriptions |
|---|-------|--|
| NON_3GPP_ACCESS_TO_EPC_NOT_ALLOWED | 9000 | SWM Result code IE #DIAMETER_ERROR_USER_NO_NON_3GPP_SUBSCRIPTION |
| USER_UNKNOWN | 9001 | SWM Result code IE #DIAMETER_ERROR_USER_UNKNOWN |
| NO_APN_SUBSCRIPTION | 9002 | SWM Result code IE #DIAMETER_ERROR_USER_NO_APN_SUBSCRIPTION or Other scenarios when the requested APN is not included in the user's profile |
| AUTHORIZATION_REJECTED | 9003 | SWM Result code IE #DIAMETER_AUTHORIZATION_REJECTED |
| ILLEGAL_ME | 9006 | SWM Result code IE #DIAMETER_ERROR_ILLEGAL_EQUIPMENT |
| NETWORK_FAILURE | 10500 | SWM Result code IE #DIAMETER_ERROR_UNABLE_TO_COMPLY |
| RAT_TYPE_NOT_ALLOWED | 11001 | SWM Result code IE #DIAMETER_RAT_TYPE_NOT_ALLOWED |
| IMEI_NOT_ACCEPTED | 11005 | NA |
| PLMN_NOT_ALLOWED | 11011 | SWM Result code IE #DIAMETER_ERROR_ROAMING_NOT_ALLOWED |
| UNAUTHENTICATED_EMERGENCY_NOT_SUPPORTED | 11055 | The emergency PDN connection request has been rejected due to authentication has failed |

Table 2: S2b to SWu Error Mapping Table

| Notify Message | Value | Descriptions |
|--|-------|---|
| PDN_CONNECTION_REJECTION | 8192 | UE PGW selection failure during attach or handoff scenario. |
| MAX_CONNECTION_REACHED | 8193 | The maximum number of PDN connections per UE allowed to be established simultaneously. Max value is 11 due to a limitation in the network mobility procedures. or With “ebi range start <> end <>” CLI under epdg-service max PDN connection per UE change be modified. |
| SEMANTIC_ERROR_IN_THE_TFT_OPERATION | 8241 | S2B Error #74 Semantic error in the TFT operation. |
| SYNTACTICAL_ERROR_IN_THE_TFT_OPERATION | 8242 | S2B Error #75 Syntactic error in the TFT operation. |
| SEMANTIC_ERRORS_IN_PACKET_FILTERS | 8244 | S2B Error #76 Semantic errors in packet filter(s). |
| SYNTACTICAL_ERRORS_IN_PACKET_FILTERS | 8245 | S2B Error #77 Syntactic errors in packet filter(s). |

Configuring Support for 3GPP IKEv2 Private Notify Error Types

This section provides information on CLI commands available in support of this feature.

Configuring 3GPP IKEv2 Private Notify Error Types

Use the following configuration to enable this feature.

```
configure
  context context_name
    epdg-service service_name
      [ no ] allow 3gpp-swu-priv-notify-error-types
    end
```



Important

Either the *Custom S2b/SWm to SWu Error Code Mapping* (existing feature) or the Configuring 3GPP IKEv2 Private Notify Error Types feature can be enabled for epdg-service at a given time.

NOTES:

- **epdg-service** : Creates ePDG service and enters ePDG service configuration mode.

- **allow 3gpp-swu-priv-notify-error-types** : Configures 3GPP Rel.13 SWu Private Notify Error Types for S2b, SWm failures.
- **no**: Disables the 3GPP Rel.13 SWu Private Notify Error Types for S2b, SWm failures related parameters.

Configuring the Backoff-Timer

Use the following configuration to enable this feature.

```
configure
  context context_name
    crypto template template_name ikev2-dynamic
      ikev2-ikesa notify-msg-error { network-failure | no-apn-subscription
    } backoff-timer { backoff_timer | deactivate }
  end
```

NOTES:

- **crypto template**: Configures the context level name to be used to identify the Crypto Template.
- **notify-msg-error**: Configures the notify message error type for backoff Timer.
- **network-failure**: Configures backoff timer for notify message error type network-failure(10500).
- **no-apn-subscription**: Configures backoff timer for notify message error type no-apn-subscription(9002).
- **backoff_timer**: Configures the number of seconds to inform UE Backoff Timer via notify payload after IKE setup failure.
Backoff timer must be an Integer from 0 to 35712000 seconds. Default 3600 seconds.
- **deactivate**: Backoff timer value set to deactivate in the notify payload sent to UE after IKE setup failure.

Monitoring and Troubleshooting

This section provides information on how to monitor and troubleshoot the Support for 3GPP IKEv2 Private Notify Error Types feature.

Show Commands and Outputs

This section provides information on show commands and their corresponding outputs for this feature.

show epdg-service all

The following new fields are added to the output of this command:

- 3GPP SWu Private Notify Error Types

show crypto template tag test

The following new fields are added to the output of this command:

- IKE SA Backoff Timer per Notify Msg Type
 - No APN Subscription
 - Network failure

